Interactive System Productivity Facility (ISPF)

User's Guide Volume II

z/OS Version 1 Release 9.0

SC34-4823-07

Interactive System Productivity Facility (ISPF)

User's Guide Volume II

z/OS Version 1 Release 9.0

SC34-4823-07

Note
Before using this document, read the general information under "Notices" on page 539.

Eighth Edition (December 2007)

This edition applies to ISPF for Version 1 Release 9.0 of the licensed program z/OS (program number 5694-A01) and to all subsequent releases and modifications until otherwise indicated in new editions.

IBM welcomes your comments. A form for comments appears at the back of this publication. If the form has been removed and you have ISPF-specific comments, address your comments to:

IBM Corporation
Reader Comments
DTX/E269
555 Bailey Avenue
San Jose, CA 95141-1003
U.S.A.

Internet: comments@us.ibm.com

If you would like a reply, be sure to include your name and your address, telephone number, e-mail address, or FAX number.

Make sure to include the following in your comment or note:
- Title and order number of this document
- Page number or topic related to your comment

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

The ISPF development team maintains a site on the World Wide Web. The URL for the site is: http://www.ibm.com/software/awdtools/ispf/

© Copyright International Business Machines Corporation 1980, 2007. All rights reserved.
US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Figures vii

Tables xi

Preface xiii
About this document xiii
Who should use this document xiii
What is in this document xiii
Using LookAt to look up message explanations . . xiv
Using IBM Health Checker for z/OS xv

Summary of changes xvii
Eighth Edition (December 2007) xvii

What's in the z/OS V1R9.0 ISPF library? xix

Chapter 1. Primary Option Menu (POM) 1
The Primary Option Menu panel 1
ISPF primary options 1
Primary Option Menu action bar choices 3
Status area on the Primary Option Menu 5
Status pull-down 5
Defining the status area 13

Chapter 2. Settings (option 0) 23
ISPF Settings panel fields 24
Select options. 24
Terminal characteristics 27
Print graphics parms 28
General. 30
ISPF Settings panel action bar 30
Specifying log and list defaults and characteristics (the Log/List action bar choice). . 32
Working with function keys and keylists (the Function Keys action bar choice) 37
The Function keys pull-down 50
Changing default colors (the Colors action bar choice) 51
Specifying ISPF ENVIRON settings (the Environ action bar choice) 57
Specifying shared profile settings (the Environ action bar choice) 58
Specifying workstation parameters (the Workstation action bar choice) 58
Displaying message, system, user, panel, and screen IDs 71

Chapter 3. View (option 1) 77
View Entry Panel action bar 78
View Entry Panel fields 78
Browsing a data set. 80
Ending browse 81
Browse primary commands 81

Chapter 4. Edit (option 2) 95
Editing a data set 95
Edit Entry Panel action bar 96
Edit Entry Panel fields. 96
Distributed editing 98
Double-byte character set support 99

Chapter 5. Utilities (option 3). 101
Utility Selection Panel action bar 101
Library utility (option 3.1) 101
Library Utility panel action bar 102
Library Utility panel fields 102
Library utility options for data sets 102
Library utility options for members 111
Data set utility (option 3.2) 113
Data Set Utility panel action bar 113
Data Set Utility panel fields 114
Data set utility options 114
Move/Copy utility (option 3.3) 132
Move/Copy Utility panel action bar. 132
Move/Copy Utility panel fields 133
Move/Copy utility options. 133
Data set list utility (option 3.4) 139
Data Set List Utility panel action bar 139
Data Set List Utility panel fields 140
Data set list utility options 146
Data set list utility line commands 160
Data set list utility primary commands 168
Reset ISPF statistics utility (option 3.5) 176
Reset ISPF statistics panel action bar 177
Reset ISPF statistics panel fields 177
Reset ISPF statistics utility options 178
Hardcopy utility (option 3.6) 180
Hardcopy utility panel action bar. 180
Hardcopy utility panel fields 181
Generating and submitting JCL 181
Additional batch printing information 183
Using the TSO/E information center facility . . 183
Download data set to workstation utility (option 3.7). 185
Download ISPF C/S component 185
Download/upload data set. 188
Outlist utility (option 3.8) 189
Outlist Utility panel action bar 190
Outlist Utility panel fields 190
Outlist utility options. 191
Command table utility (option 3.9) 192
Command Table Utility panel fields 193
Scrolling a command table 196
Saving a command table 196
Canceling a command table 196
Using command table line commands 196
Format specifications utility (option 3.11) 197

© Copyright IBM Corp. 1980, 2007

Format Specifications panel action bar 197
Format Specifications panel fields 197
Format Specifications panel options 198
Format selection list commands 201
SuperC utility (option 3.12). 203
SuperC Compare Utility panel action bar . . . 204
SuperC Compare Utility panel fields 204
SuperC member lists 208
Submitting a SuperC job in batch mode . . . 209
Using the NOLIST listing type in batch mode 212
SuperCE utility (option 3.13) 213
SuperCE Utility panel action bar 213
SuperCE Utility panel fields 214
SuperCE utility options 217
Search-For utility (option 3.14). 225
Search-For Utility panel action bar 226
Search-For Utility panel fields 226
Specifying additional search strings 228
Search-For strings and keywords 228
Search-For member lists 229
Submitting a Search-For job in batch mode . . 230
Search-ForE utility (option 3.15) 231
Search-ForE Utility panel action bar 232
Search-ForE Utility panel fields 232
ISPF table utility (option 3.16) 238
Table Utility panel action bar 239
Table Utility panel fields. 239
Table utility entry panel options 240
Table data set selection list 240
Table DD selection list 242
Edit/browse table panel. 243
Table output data set selection. 254
Table utility options 255
Table export report options. 256
Export data set attributes 258
Importing data into a table. 259
Exporting data from a table 259
Processing tables that are currently open . . . 260
z/OS UNIX directory list utility (option 3.17). . . 263
z/OS UNIX Directory List Utility panel action bar 264
z/OS UNIX Directory List Utility panel fields 264
z/OS UNIX Directory List Utility panel options 265
z/OS UNIX directory list utility line commands 273
z/OS UNIX directory list utility primary commands 293
z/OS UNIX directory list options panels . . . 297
Switching to super-user (UID 0) mode and back 299
Switching UIDs with the Options pull-down menu 299
Switching UIDs with the SU primary command 299

Chapter 6. Foreground (option 4) . . . 301

Foreground selection panel action bar 301
Foreground processing sequence 302
Expanding packed data 305
Member expansion (ISRLEMX) 306
Restrictions on member expansion and member parts lists. 306
Member expansion ISRLEMX return codes . . 308
Trigger statement errors 308
Input data sets 308
List data sets 309
Password protection 310
Object data sets. 310
Foreground—TSO/E information center facility . . 311
Assembler (option 4.1) 311
COBOL (option 4.2) 312
VS FORTRAN compile (option 4.3) 313
PL/I (option 4.5) 314
VS Pascal compile (option 4.6). 315
Binder/linkage editor (option 4.7) 316
Linkage editor concatenation sequence 318
SCRIPT/VS processor (option 4.9) 318
SCRIPT/VS processing sequence 319
Selecting a formatting style. 322
Changing style options 323
Using SCRIPT/VS with the TSO/E information center facility 324
VS COBOL II interactive debug (option 4.10) . . . 325
OS/VS COBOL debug (option 4.10A) 325
COBOL debug processing sequence 326
Symbolic debug data sets 327
Print output data sets 327
FORTRAN debug (option 4.11) 328
Member parts list (option 4.12) 329
Member not found 333
C/370 compile (option 4.13) 333
REXX/370 compile (option 4.14) 333
Ada/370 compile (option 4.15) 333
AD/Cycle C/370 compile (option 4.16). 334
ISPDTLC (option 4.18) 334
OS/390 C/C++ compile (option 4.19) 334

Chapter 7. Batch (option 5) 335

Batch selection panel action bar 335
Batch processing sequence 336
JCL generation—compilers 338
JCL generation—assemblers and linkage editor . . 339
Assembler (option 5.1) 340
COBOL compile (option 5.2) 341
VS FORTRAN compile (option 5.3) 342
PL/I compile (option 5.5) 342
VS Pascal compile (option 5.6). 343
Binder/linkage editor (option 5.7) 344
VS COBOL II interactive debug (option 5.10) . . . 346
Member parts list (option 5.12) 347
C/370 compile (option 5.13) 347
REXX/370 compile (option 5.14) 347
Ada/370 compile (option 5.15) 348
AD/Cycle C/370 compile (option 5.16). 348
ISPDTLC compile (option 5.18) 348
OS/390 C/C++ compile (option 5.19) 348

Chapter 8. Command (option 6) . . . 349

ISPF command shell panel action bar 349
The saved command area 351
Entering TSO commands, CLISTs, and REXX EXECs. 351
Rules for entering TSO commands 351
Rules for entering CLISTs and REXX EXECs . . 352

Using the session manager 352

Chapter 9. Dialog test (option 7) . . . 355
The dialog test environment 355
Dialog test primary option panel action bar . . 357
Using variables. 358
Severe error handling 358
Commands 359
Ending the current option without saving changes 360
Saving changes. 361
Finding a character string 361
Displaying breakpoint qualification data . . . 361
Restoring the format of the Breakpoints panel 361
Dialog test line commands 361
Setting a keylist for dialog test 362
Functions (option 7.1) 362
Invoke dialog function/selection panel action bar 363
Invoke dialog panel fields 364
Panels (option 7.2). 366
Display panel action bar. 367
Display panel fields 367
Variables (Option 7.3) 368
Variables panel action bar 369
Variables panel fields. 370
Variables commands 370
Manipulating variables 371
Variables usage notes. 371
Tables (option 7.4). 373
Tables panel action bar 373
Tables panel fields. 374
Tables panel options 375
Log (option 7.5) 385
ISPF transaction log not available. 386
Trace output in ispf log 386
Dialog services (option 7.6). 387
Invoke dialog service panel action bar 388
Special display panel 389
Traces (option 7.7). 390
1—function traces 391
2—variable traces 393
Breakpoints (option 7.8) 394
Specifying breakpoints 395
Breakpoints panel action bar 395
Breakpoints panel fields 396
Qualification parameter values 396
Finding a breakpoint 398
Tutorial (option 7.T) 401
Exit (option 7.X) 401

Chapter 10. IBM products (option 9) 403

Chapter 11. SCLM (option 10) 405
SCLM Main Menu action bar 405
SCLM overview 406

Chapter 12. ISPF object/action workplace (option 11) 407
Selecting objects 407
Workplace entry panel 407
Specifying actions 410
Choices on the Workplace action bar 410
Actions that require prompt windows for more information 421
Commands 429
Default CUA function key settings 430
Changing workplace settings 431
Workplace example scenario 435

Appendix A. SuperC reference 439
Utility differences 439
Standard utilities 439
Extended utilities 439
Program description 440
SuperC features for the year 2000 transition . . 441
Applications. 441
SuperC compare process options 443
SuperC compare process statements 453
Process statement notation conventions. . . . 453
CHNGV - CHNG (Compare Type) Line Value 456
CMPBOFS - Compare Byte Offsets 457
CMPCOLM, CMPCOLMN, CMPCOLMO - Compare Columns 458
CMPLINE - Compare Lines 459
CMPSECT - Compare Sections 461
COLHEAD—Define Column Headings. . . . 463
DPLINE, DPLINEC - Don't Process Lines . . . 465
LNCT - Line Count 467
LSTCOLM - List Columns 468
NCHGT, OCHGT - Change Text 469
NEXCLUDE, OEXCLUDE —Exclude Data: . . 471
NFOCUS, OFOCUS— Focus on Data 472
NTITLE, OTITLE - Alternate Listing Title . . . 473
NY2AGE, OY2AGE —Year 2000 Aging Option 474
NY2C, NY2Z, NY2D, NY2P, OY2C, OY2Z, OY2D, OY2P —Year 2000 Date Definitions . . 475
REVREF—Revision Code Reference 478
SELECT - Select PDS Members 479
SLIST - Statements File Listing Control 480
Y2PAST—Year 2000 Global Date Option . . . 481
* and .* - Comment Lines (SuperC Listing) 482
SuperC search-for process options 483
SuperC search-for process statements 486
Process statement notation conventions. . . . 487
CMPCOLM - Compare (Search) Columns . . . 488
CMPLINE - Compare (Search-For) Lines . . . 489
DPLINE, DPLINEC - Don't Process Lines . . . 490
LNCT - Line Count 492
LPSFV - LPSF Count Value. 493
LSTCOLM - List Columns 494
NCHGT - Change Text of New (Search) Text String 495
NTITLE - Alternate Listing Title 497
SELECT - Select PDS Members 498
SLIST - Statements File Listing Control 499
SRCHFOR, SRCHFORC - Search for Strings in the Input Files 500
* and .* - Comment Lines (Search-For Listing) 502
Return codes 503

SuperC and search-for technical overview 504
How SuperC and search-for filter input file lines 504
How SuperC matches input files 505
How SuperC partitions and processes large files 506
Why compare types may produce different comparison results 507
Comparing and searching alias members . . . 507
Comparing load modules 508
Comparing CSECTs 508
How to directly invoke SuperC and search-for 508

Appendix B. SuperC listings 511
SuperC listing title lines 515
Listing Output Section 515
Listing prefix codes 516
Type-of-difference codes 516
Member Summary Listing 518
Summary and statistics/PDS overall totals . . 518
Bottom-of-listing information 519
Y2K comparison 520
Side-by-side listings 520
Effect of File compare type on SuperC listings . . 521
File comparison of a sequential data set or membered PDS. 522
File comparison of a complete PDS 522
Search-For listings 523
Update data set control output examples 524
APNDUPD—append update data set 524
UPDCMS8—update CMS sequenced 8 525
UPDCNTL—update control 525
UPDMVS8—update MVS sequenced 8 529
UPDLDEL—update long source and delta data set 529
UPDPDEL—prefixed delta lines 530
UPDREV—update revision 531
UPDREV2 - update revision (2) 533
UPDSEQ0—update sequenced 0 533
UPDSUMO—update summary only 534

Appendix C. Accessibility 537
Using assistive technologies 537
Keyboard navigation of the user interface 537
z/OS information 537

Notices 539
Programming Interface Information 540
Trademarks 541

Index 543

Figures

1. ISPF Primary Option Menu (ISR@PRIM) . . . 1
2. Status pull-down on the ISPF Primary Option Menu (ISR@PRIM) 6
3. ISPF Primary Option Menu status area – session view 7
4. System information pop-up 8
5. Environment pop-up (release information) 9
6. ISPF Primary Option Menu status area – function keys view 10
7. ISPF Primary Option Menu status area – calendar view 10
8. Julian date pop-up 11
9. Standard date pop-up 12
10. ISPF Primary Option Menu status area – user status view. 12
11. ISPF Primary Option Menu status area – user point-and-shoot view 13
12. ISPF status pop-up (ISPSAMMN) 14
13. Status pull-down in ISPF status pop-up 15
14. Options pull-down in ISPF status pop-up 16
15. Calendar month pop-up window 17
16. Calendar year pop-up window 17
17. Calendar start pop-up window 18
18. Calendar time format pop-up window . . . 18
19. Calendar colors panel (ISPCALGC) 19
20. User view customization panel (ISPSAMUS) 20
21. User point-and-shoot panel (ISPSAMUP) 21
22. ISPF Settings panel (ISPISMMN) 23
23. Screen containing graphics to be printed using PRINTG 29
24. Example of using aspect ratio parameter 0 29
25. Example of using aspect ratio parameter 1 30
26. Log Data Set Defaults panel (ISPISML1) 32
27. List Data Set Defaults panel (ISPISML2) 34
28. List Data Set Characteristics panel (ISPISML3) 35
29. Log and List JCL panel (ISPISMLJ). 37
30. Function keys pull-down on the ISPF settings panel action bar (ISPISMMN) 39
31. PF Key Definitions and Labels panel (ISPOPT3D) 40
32. Using the PF Key Definitions and Labels panel (ISPOPT3E) 41
33. Example screen with function key definition lines 42
34. Keylist Utility panel (ISPKLUP) 43
35. Keylist Create panel (ISPKLUCR) 44
36. Keylist Change panel (ISPKLUCH). 46
37. Keylist utility view panel (ISPKLUB) 47
38. Keylist utility with delete keylist confirmation pop-up (ISPKLUP) 48
39. Tailor Function Key Definition Display panel (ISPOPFA) 49
40. Global Color Change Utility panel (ISPOPT10) 52
41. Global GUI color change utility panel (ISPOPTG1) 53
42. Color change panel with drop-down list 54
43. CUA Attribute Change Utility panel (ISPOPT11). 55
44. CUA Attribute Change Utility panel positioned on the point-and-shoot panel element (ISPOPT1X) 56
45. ISPF ENVIRON Settings panel (ISPENVA) 57
46. Multi-Logon Profile Sharing Settings (ISPISSA) 58
47. Workstation pull-down on the ISPF settings panel action bar (ISPISMMN) 59
48. The Workstation Agent window. 59
49. Initiate Workstation Connection panel (ISPISMGI). 60
50. WSA connection panel 63
51. Client/Server Component Update panel (ISPDTVD1) 64
52. Client/Server Component Install Program panel (ISPWSD0A) 65
53. GUI settings pop-up window (ISPISMGS) 66
54. ISPF Workstation Tool Integration panel 68
55. Modify Tool Configuration window 69
56. Extension Mapping Dialog window 70
57. Identifier pull-down on the ispf settings panel action bar (ISPISMMN) 71
58. Panel displayed with the message identifier set to on. 72
59. Panel displayed with the system name set to on. 72
60. Panel displayed with the user ID set to on 73
61. Panel displayed with the panel identifier set to on. 74
62. Panel displayed with the screen identifier set to on. 75
63. View Entry panel (ISRBRO01) 77
64. Browse - data display (ISRBROBA). 80
65. Browse - column-identification line (ISRBROBA) 82
66. Browse hexadecimal display - vertical (ISRBROBA) 90
67. Browse hexadecimal display - data (ISRBROBA) 91
68. Edit Entry panel (ISREDM01) 95
69. Utility Selection Panel (ISRUTIL) 101
70. Library Utility panel (ISRUDA1) 102
71. Member list commands pop-up window (ISRCMLEP) 103
72. Data Set Information panel (ISRUAIP) 105
73. Volume Information for a Multivolume Data Set (ISRUAMVI) 106
74. Data Set Information for PDSE Managed Data Sets (ISRUAISE) 107
75. Data Set Information for Managed Data Sets (ISRUAISE) 107
76. Volume Information for a Managed Multivolume Data Set (ISRUAMVI) 108
77. Short data set information (ISRUAIP) 109

© Copyright IBM Corp. 1980, 2007

78. Data Set Information (Short) for Managed Data Sets (ISRUAISE) 110
79. Data Set Information (Short) for a PDSE (ISRUAISE) 111
80. Data Set Utility panel (ISRUDA2S) 113
81. Allocate New Data Set panel (ISRUAAP2) 115
82. Allocate New Data Set —managed data set support panel (ISRUAASE) 116
83. Multivolume allocation panel (ISRUAMV) 120
84. Allocation Error Panel (ISRUADCS) 121
85. Confirm Delete panel (ISRUADC1) 124
86. Confirm purge panel (ISRUADC3) 125
87. VSAM Utilities panel (ISRUVSAM) 127
88. Define Cluster panel (ISRUVPC3) 129
89. Editing the IDCAMS command (ISRUVEDT) 130
90. Browsing IDCAMS Errors (ISRUVBRO) 130
91. Using a VSAM profile data set (ISRVMLGT) 131
92. Panel for changing the name of the VSAM profile data set (ISRUVGET) 132
93. Move/Copy Utility panel (ISRUMC1) 132
94. Move/Copy Utility - "To" panel for copying (ISRUMC2B) 134
95. Move/Copy Utility - "To" panel for moving (ISRUMC2B) 136
96. Data Set List Utility panel (ISRUDLP) 139
97. Sequence of data set list display views 143
98. Data set list - volume view (ISRUDSL0) 147
99. Data set list - space view (ISRUDSL0) 149
100. Data set list - attributes view (ISRUDSL0) 149
101. Data set list - total view (ISRUDSL0) 150
102. Data set list - total view with catalog name (ISRUDSL0) 150
103. VTOC summary information panel (ISRUDSLV) 159
104. Data set list commands pop-up (ISRUDABC) 161
105. Member list display - expanded line command field (ISRUDSM) 163
106. Load module library display - expanded line command field (ISRUDSM) 164
107. Data Set List Color Change Utility panel (ISRDLCP) 171
108. Data Set List Utility - SHOWCMD panel (ISRUDSLS) 174
109. Reset ISPF Statistics panel (ISRURSP) 177
110. Hardcopy Utility panel - before JCL generation (ISRUHCP) 180
111. Hardcopy Utility panel - after JCL generation (ISRUHCJP) 182
112. Hardcopy Utility panel - with the TSO/E information center facility installed (ISRUHCPI) 184
113. ISPF Client/Server Component Download panel (ISPWSD01) 185
114. ISPF Client/Server Installation Notice (ISPWSD03) 187
115. ISPF Client/Server Component Install Program panel (ISPWSD06) 188
116. ISPF data set panel (ISPUDLDS) 189
117. Outlist Utility panel (ISRUOLP1) 190
118. Command Table Utility panel (ISPUCMA) 193
119. Command table editing panel (ISPUCMD) 194
120. Format Specifications panel (ISRFM01) 197
121. Format Definition panel (ISRFM02) 199
122. Copy Format Selection List panel (ISRFM04) 201
123. Format Selection List panel (ISRFM03) 201
124. SuperC Utility panel (ISRSSNEW). 203
125. SuperC Utility - Old Data Set panel (ISRSSOLD) 206
126. SuperC member list panel (ISRSSML) 209
127. SuperC Utility - Submit Batch Jobs panel (ISRSCSUB) 210
128. SuperC Utility - submit batch jobs panel using NOLIST (ISRSCSB1) 212
129. SuperCE Utility panel (ISRSEPRI). 213
130. SuperCE - concatenation interactive entry panel (ISRSECAT) 218
131. SuperCE - Concatenation Batch Entry panel (ISRSECAT) 219
132. SuperC process statements panel (ISRSEPRS) 221
133. Browse a SuperCE profile 222
134. SuperCE - Profile Manager panel (ISRSEPMG) 223
135. SuperC - Defaults panel (ISRSDFLT) 225
136. Search-For Utility panel (ISRSFSPR) 226
137. Additional Search Strings panel (ISRSFSST) 228
138. Search member list panel (ISRSSML) 230
139. Search-For Utility - Submit Batch Jobs panel (ISRSFSUB) 231
140. Extended Search-For Utility panel (ISRSFPRI) 232
141. Extended Search-For - concatenation data set entry panel (ISRSFCON) 235
142. Extended Search-For - concatenation batch entry panel (ISRSFCON) 236
143. Search-For process statements panel (ISRSFPRS) 238
144. ISPF Table Utility panel (ISRUTBP0) 239
145. Table data set selection list panel (ISRUTBP1) 241
146. Table DD selection list panel (ISRUTBP2) 242
147. Table display panel, edit mode (ISRUTBP3) 243
148. Extension Variables Panel (ISRUTBP4) 245
149. Table Export Layout panel (ISRUTBP7) 247
150. Table Sort Specification panel (ISRUTBP8) 251
151. Table statistics panel (ISRUTBP6) 252
152. Table structure panel (ISRUTBP5) 253
153. Table Output Data Set Selection panel (ISRUTBP9) 255
154. Table Export Report Options panel (ISRUTBO2) 257
155. Table Export Data Set Attributes panel (ISRUTBO3) 258
156. Export report example 260
157. Panel displayed when the selected table is currently open but not in SHARE mode . . 261
158. Panel displayed when the selected table is currently open in SHARE mode for NOWRITE 261
159. Panel displayed when the selected table is currently open in SHARE mode for WRITE . 262
160. z/OS UNIX Directory List Utility panel (ISRUULP) 264
161. z/OS UNIX Directory List panel (ISRUUDL0) 266
162. z/OS UNIX Directory List—scrolling right 267

163. Example: specifying a z/OS UNIX command to run on a selected file 272
164. Example: running the selected file directly 272
165. Example: specifying a REXX exec to run on a selected file 273
166. z/OS UNIX Directory List Actions pop-up window 274
167. Create New z/OS UNIX File panel (ISRUULNW) 275
168. Copy From z/OS UNIX File panel (ISRUULCF) 277
169. Copy From z/OS UNIX Directory panel (ISRUULCD). 279
170. Replace z/OS UNIX File panel (ISRUULRF) 282
171. Copy Into z/OS UNIX Directory panel (ISRUULRD). 284
172. z/OS UNIX File Information panel (ISRUULIN) 287
173. z/OS UNIX Symbolic Link Information panel (ISRUULIS) 290
174. Foreground Selection Panel (ISRFPA) 301
175. Foreground Print Options panel (ISRFPPRT) 304
176. Foreground Print Options panel with TSO/E information center facility (ISRFPPRI) . . . 311
177. Foreground Assembler panel (ISRFP01) 312
178. Foreground COBOL Compile panel (ISRFP02) 313
179. Foreground VS FORTRAN Compile panel (ISRFP03) 314
180. Foreground PL/I Optimizing Compile panel (ISRFP05) 315
181. Foreground VS Pascal Compile panel (ISRFP06) 316
182. Foreground Binder/Linkage Editor panel (ISRFP07B) 317
183. SCRIPT/VS Processor panel (ISRFP09) 319
184. Foreground Print Options for Style panel (ISRFP09P) 321
185. Select SCRIPT/VS Formatting Style panel (ISRFP09T) 323
186. SCRIPT/VS Options for Style: DRAFT panel (ISRFP09O) 324
187. Foreground Print Options for Style panel with the TSO/E information center facility (ISRFP09I) 325
188. COBOL Debug panel (ISRFP10A) 326
189. FORTRAN Debug panel (ISRFP11) 329
190. Foreground Member Parts List panel (ISRFP12) 330
191. Member parts list display (ISRFP12B) 332
192. Foreground ISPDTLC compile panel (ISPCP01) Screen 1. 334
193. Batch Selection panel (ISRJPA) 335
194. Batch Selection Panel with JCL generated (ISRJPB) 338
195. Batch Assembler panel (ISRJP01) 340
196. Batch COBOL Compile panel (ISRJP02) 341
197. Batch VS FORTRAN Compile panel (ISRJP03) 342
198. Batch PL/I Compile panel (ISRJP05) 343
199. Batch VS Pascal Compile panel (ISRJP06) 344
200. Batch Binder Linkage/Editor panel (ISRJP07B) 345
201. VS COBOL II Interactive Debug panel (ISRJP10) 346
202. Batch Member Parts List panel (ISRJP12) 347
203. ISPF Command Shell panel (ISRTSO) 349
204. ISPF Command Shell panel with saved commands (ISRTSO) 351
205. Dialog test primary option panel (ISPYXD1) 356
206. Keylist change panel (ISPKLUCH) 362
207. Invoke Dialog Function/Selection panel (ISPYFP) 363
208. Display panel (ISPYP1) 366
209. Message display panel (ISPYP2) 368
210. Variables panel (ISPYVPN) 369
211. Tables panel (ISPYTPI) 373
212. Display row panel (ISPYTPD) 376
213. Confirm table row delete panel (ISPYTPCD) 377
214. Modify row panel (ISPYTPM) 378
215. Add row panel (ISPYTPA) 380
216. Structure of table panel (ISPYTPSR) 382
217. Status of table panel with table not open (ISPYTPS1) 383
218. Status of table panel with table open (ISPYTPS1) 384
219. ISPF transaction log (ISPYLP1). 385
220. Invoke dialog service panel (ISPYS1) 388
221. Special display panel (ISPYS2) 390
222. Traces panel (ISPYRI1) 391
223. Function traces panel (ISPYRFP) 392
224. Variable traces panel (ISPYRVP) 393
225. Breakpoints panel (ISPYBP1) 395
226. Breakpoints panel with qualification parameter values (ISPYBP2). 397
227. Breakpoint Primary Option panel (ISPYXM1) 399
228. Dialog Test Tutorial - first panel (ISP70000) 401
229. Additional IBM Program Development Products Panel (ISRDIIS). 403
230. SCLM Main Menu (FLMDMN) 405
231. Workplace entry panel - library view (ISRWORK1). 408
232. Workplace entry panel - data set view (ISRWORK) 409
233. Reset statistics panel (ISRURSET) 422
234. TSO command panel (ISRUTCES). 423
235. WS command panel (ISRUWCES). 424
236. ISPF Command Shell panel (ISRTSO) 425
237. Move panel (ISRUMVC) 426
238. Rename prompt panel (ISRURNAM) 427
239. Rename data set panel (ISRUARP1) 428
240. Rename member panel (ISRUREN) 428
241. Workplace Settings panel (ISRUSETM) 432
242. Priority for filtering input lines 504
243. Find match example 505
244. Split screen showing source data for SuperC listings. 512
245. OVSUM listing of a LINE comparison of two PDS members 512
246. DELTA listing of a LINE comparison of two PDSs 513
247. LONG listing of a word comparison of two PDSs 514

248. Comparison listing with column headings (using COLHEAD) 515
249. Word comparison of two PDSs using change bar to show differences 517
250. Comparison listing with Y2000 dates being compared 520
251. Side-by-side LINE comparison using the NARROW process option 521
252. File comparison of a membered PDS 522
253. File comparison of a complete PDS 523
254. Search-For listing 523
255. UPDCMS8 update data set 525
256. UPDCNTL data set using line compare 526
257. UPDCNTL listing using word compare 527
258. UPDCNTL listing using byte compare 528
259. UPDMVS8 update data set listing 529
260. UPDLDEL update control data set 530
261. UPDPDEL update data set listing 531
262. Example of a UPDREV update file for SCRIPT/VS documents 532
263. Example of a UPDREV update data set for bookmaster documents 532
264. UPDSEQ0 update data set 533
265. UPDSUMO data set using line compare 534
266. UPDSUMO data set using word compare 535
267. UPDSUMO data set using byte compare 536

Tables

1. CUA mode effect on panel display 25
2. CUA mode effect on top-row-displayed indicator 26
3. ISPKYLST key settings 38
4. ISPHELP key settings 38
5. Default key settings 45
6. Displaying forms of the function keys. . . . 50
7. Valid CUA attribute change values 55
8. Valid point-and-shoot change values 57
9. TSO command/CLIST/REXX exec variables (output) 156
10. TSO command/CLIST/REXX exec additional variables (output) 157
11. TSO command/CLIST/REXX exec variables (input) 158
12. Sort fields for source libraries 175
13. SRCHFOR command search string examples 176
14. Reset mod level and reset sequence numbers combinations. 179
15. SuperCE process options 220
16. Search-For process options 237
17. Octal permission values 269
18. Expansion triggers and syntax 306
19. ISRSCAN and ISRLEMX return codes 308
20. Foreground member parts list record formats 332
21. ISRSCAN and ISRLEMX return codes 339
22. Workstation commands 429
23. Workplace function key settings 430
24. Summary of process options for search and compare 443
25. Summary of process statements for compare and search 454
26. Search-For process options 483
27. Summary of Search-For process statements 486
28. UPDCNTL format using line compare 526
29. UPDCNTL format using word compare 527
30. UPDCNTL format using byte compare 529
31. UPDSUMO format using line compare 534
32. UPDSUMO format using word compare 535
33. UPDSUMO format using byte compare 536

© Copyright IBM Corp. 1980, 2007

Preface

This document provides reference and usage information for programmers who develop applications with ISPF. It also provides conceptual and functional descriptions of ISPF.

About this document

This document contains two parts.

The first part provides information about using ISPF options 0-11.

The second part contains the appendixes and provides:

- Descriptions of the SuperC and Search-For programs
- Descriptions and examples of the SuperC output listing formats.

Who should use this document

This document is for application programmers using ISPF. Users should be familiar with coding CLISTs, REXX EXECs, or programs in the MVS environment.

What is in this document

Chapter 1, “Primary Option Menu (POM),” describes the ISPF Primary Option menu, including the main menu options and the status area.

Chapter 2, “Settings (option 0),” describes the ISPF Settings panel and related pop-up windows.

Chapter 3, “View (option 1),” describes how Browse (Option 1) allows you to display source data and listings stored in ISPF libraries or other partitioned or sequential data sets.

Chapter 4, “Edit (option 2),” describes how Edit (Option 2) allows you to create, display, and change data stored in ISPF libraries or other partitioned or sequential data sets.

Chapter 5, “Utilities (option 3),” describes the different functions for library, data set, and catalog maintenance.

Chapter 6, “Foreground (option 4),” describes how Foreground (Option 4) allows ISPF to run the foreground processors.

Chapter 7, “Batch (option 5),” describes how Batch (Option 5) allows ISPF to run the batch processors.

Chapter 8, “Command (option 6),” describes Command (Option 6), and how ISPF allows you to enter TSO commands, CLISTs, and REXX EXECs on the Command line of any panel and in the **Line Command** field on data set list displays.

© Copyright IBM Corp. 1980, 2007

Chapter 9, “Dialog test (option 7),” describes how to use Dialog Test (Option 7) for testing both complete ISPF applications and ISPF dialog parts, including functions, panels, variables, messages, tables, and skeletons.

Chapter 10, “IBM products (option 9),” describes the other IBM products that are supported as ISPF dialogs.

Chapter 11, “SCLM (option 10),” provides an overview of the SCLM product.

Chapter 12, “ISPF object/action workplace (option 11),” describes the Workplace option (Option 11).

Appendix A, “SuperC reference,” provides information about the SuperC return codes, process options, update data set control options, and process statements.

Appendix B, “SuperC listings,” describes and explains the kinds of listings you can produce using SuperC.

Using LookAt to look up message explanations

LookAt is an online facility that lets you look up explanations for most of the IBM® messages you encounter, as well as for some system abends and codes. Using LookAt to find information is faster than a conventional search because in most cases LookAt goes directly to the message explanation.

You can use LookAt from these locations to find IBM message explanations for z/OS® elements and features, z/VM®, z/VSE™, and Clusters for AIX® and Linux™:

- The Internet. You can access IBM message explanations directly from the LookAt Web site at www.ibm.com/servers/eserver/zseries/zos/bkserv/lookat/.
- Your z/OS TSO/E host system. You can install code on your z/OS systems to access IBM message explanations using LookAt from a TSO/E command line (for example: TSO/E prompt, ISPF, or z/OS UNIX® System Services).
- Your Microsoft® Windows® workstation. You can install LookAt directly from the *z/OS Collection* (SK3T-4269) or the *z/OS and Software Products DVD Collection* (SK3T-4271) and use it from the resulting Windows graphical user interface (GUI). The command prompt (also known as the DOS > command line) version can still be used from the directory in which you install the Windows version of LookAt.
- Your wireless handheld device. You can use the LookAt Mobile Edition from www.ibm.com/servers/eserver/zseries/zos/bkserv/lookat/lookatm.html with a handheld device that has wireless access and an Internet browser (for example: Internet Explorer for Pocket PCs, Blazer or Eudora for Palm OS, or Opera for Linux handheld devices).

You can obtain code to install LookAt on your host system or Microsoft Windows workstation from:

- A CD in the *z/OS Collection* (SK3T-4269).
- The *z/OS and Software Products DVD Collection* (SK3T-4271).
- The LookAt Web site (click **Download** and then select the platform, release, collection, and location that suit your needs). More information is available in the LOOKAT.ME files available during the download process.

Using IBM Health Checker for z/OS

IBM Health Checker for z/OS is a z/OS component that installations can use to gather information about their system environment and system parameters to help identify potential configuration problems before they impact availability or cause outages. Individual products, z/OS components, or ISV software can provide checks that take advantage of the IBM Health Checker for z/OS framework. This book might refer to checks or messages associated with this component.

For additional information about checks and about IBM Health Checker for z/OS, see *IBM Health Checker for z/OS: User's Guide*.

SDSF also provides functions to simplify the management of checks. See *z/OS SDSF Operation and Customization* for additional information.

Summary of changes

Eighth Edition (December 2007)

Important Information
The PTFs for these APARs must be applied before using ISPF Version 1 Release 9.0, or the product may not behave as described in this document.

This document describes ISPF Version 1 Release 9.0 with the PTFs for these APARs applied:

OA22250
Enhancements to the ISPF editor support for ASCII data.

OA21378
New messages.

OA21891
Entering long z/OS UNIX path names on Edit, View, and Browse panels.

OA21740
Cross-dependency database.

OA20514
Additional parameters for GETBLDMP SCLM service.

© Copyright IBM Corp. 1980, 2007

What's in the z/OS V1R9.0 ISPF library?

You can order the ISPF books using the numbers provided below.

Title	Order Number
z/OS ISPF Dialog Developer's Guide and Reference	SC34-4821–06
z/OS ISPF Dialog Tag Language Guide and Reference	SC34-4824–06
z/OS ISPF Edit and Edit Macros	SC34-4820–07
z/OS ISPF Messages and Codes	SC34-4815–07
z/OS ISPF Planning and Customizing	GC34-4814–06
z/OS ISPF Reference Summary	SC34-4816–07
z/OS ISPF Software Configuration and Library Manager Guide and Reference	SC34-4817–08
z/OS ISPF Services Guide	SC34-4819–07
z/OS ISPF User's Guide Vol I	SC34-4822–07
z/OS ISPF User's Guide Vol II	SC34-4823–07

© Copyright IBM Corp. 1980, 2007

Chapter 1. Primary Option Menu (POM)

See:
- "The Primary Option Menu panel"
- "Status area on the Primary Option Menu" on page 5

The Primary Option Menu panel

The Primary Option Menu panel, shown in Figure 1, is the first panel that displays when you start ISPF.

```
2   Menu  Utilities  Compilers  Options  Status  Help
 ------------------------------------------------------------------------------
                            ISPF Primary Option Menu
 1                                                          3
 0  Settings      Terminal and user parameters            User ID . : USERID
 1  View          Display source data or listings         Time. . . : 13:54
 2  Edit          Create or change source data            Terminal. : 3278
 3  Utilities     Perform utility functions               Screen. . : 1
 4  Foreground    Interactive language processing         Language. : ENGLISH
 5  Batch         Submit job for language processing      Appl ID . : ISR
 6  Command       Enter TSO or Workstation commands       TSO logon : ISPF
 7  Dialog Test   Perform dialog testing                  TSO prefix: USERID
 9  IBM Products  IBM program development products        System ID : ISD1
 10 SCLM          SW Configuration Library Manager        MVS acct. : IBMGSA
 11 Workplace     ISPF Object/Action Workplace            Release . : ISPF 5.9
 12 z/OS System   z/OS system programmer applications
 13 z/OS User     z/OS user applications

      Enter X to Terminate using Log/List defaults


 Option ===>  ____________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

1 Primary Options.
2 Action bar choices.
3 Dynamic status area.

Figure 1. ISPF Primary Option Menu (ISR@PRIM)

ISPF primary options

When you select one of these options, ISPF displays the selected panel. These options are described in detail in other chapters within this book. Brief descriptions follow:

Option Description

0 **Settings** displays and changes selected ISPF parameters, such as terminal characteristics and function keys. See Chapter 2, "Settings (option 0)," on page 23 for more information.

1 **View** displays data (you cannot change it) using the View or Browse function. Use View or Browse to look at large data sets, such as compiler listings. You can scroll the data up, down, left, or right. If you are using

© Copyright IBM Corp. 1980, 2007

Browse, a FIND command, entered on the command line, allows you to search the data and find a character string. If you are using View, you can use all the commands and macros available to you in the Edit function. See Chapter 3, "View (option 1)" for more information.

2 You can use **Edit** to create or change source data, such as program code and documentation, using the ISPF full-screen editor. You can scroll the data up, down, left, or right. You can change the data by using Edit *line commands*, which are entered directly on a line number, and *primary commands*, which are entered on the command line. See Chapter 3, "View (option 1)" and refer to *z/OS ISPF Edit and Edit Macros* for more information.

3 **Utilities** perform library and data set maintenance tasks, such as moving or copying library or data set members, displaying or printing data set names and volume table of contents (VTOC) information, comparing data sets, and searching for strings of data. See Chapter 5, "Utilities (option 3)" for more information.

4 **Foreground** calls IBM language processing programs in the foreground. See Chapter 6, "Foreground (option 4)" for more information.

5 **Batch** calls IBM language processing programs as batch jobs. ISPF generates Job Control Language (JCL) based on information you enter and submits the job for processing. See Chapter 7, "Batch (option 5)" for more information.

6 **Command** calls TSO commands, CLISTs, or REXX EXECs under ISPF. See Chapter 8, "Command (option 6)" for more information.

7 **Dialog Test** tests individual ISPF dialog components, such as panels, messages, and dialog functions (programs, commands, menus). See Chapter 9, "Dialog test (option 7)" for more information.

9 You can use the **IBM Products** option to select other installed IBM program development products on your system. Products supported are:
- Tivoli Information Management (INFOMAN)
- COBOL Structuring Facility (COBOL/SF)
- Screen Definition Facility II (SDF II and SDF II-P)

See Chapter 10, "IBM products (option 9)" for more information.

10 **SCLM** controls, maintains, and tracks all of the software components of an application. See Chapter 11, "SCLM (option 10)" and refer to *z/OS ISPF Software Configuration and Library Manager Guide and Reference* for more information.

11 **Workplace** gives you access to the ISPF Workplace, which combines many of the ISPF functions onto one object-action panel. See Chapter 12, "ISPF object/action workplace (option 11)" for more information.

12 **z/OS System** gives you access to the z/OS System Programmer Primary Option Menu. It contains options for z/OS elements that are used by system programmers and administrators. It includes options for:
- GDDM® Print Queue Manager
- HCD I/O configuration
- DCE configuration
- APPC Administration
- WLM Work Load Manager
- FFST™ dump formatting

- Infoprint Server
- RMF
- SMP/E
- TCP/IP NPF

13 **z/OS User** gives you access to the z/OS Applications panel. It contains options for z/OS elements that are used by most ISPF users. It includes options for:

- BookManager® Build
- BookManager Read
- BookManager Index Creation
- DFSMSrmm™/ISMF
- DFSMSdfp™/ISMF
- DFSORT™
- BDT File-to-File
- IPCS
- z/OS UNIX Browse
- z/OS UNIX Edit
- z/OS UNIX Shell
- Security Server
- TSO/E Information Center Facility
- SDSF

X **EXIT** leaves ISPF using the log and list defaults. You can change these defaults from the Log/List pull-down on the ISPF Settings panel action bar.

Primary Option Menu action bar choices

The Primary Option Menu action bar offers a quick way of accessing many of the panels within ISPF.

Menu This choice is available from most panels within ISPF and displays many of the options listed on the Primary Option Menu panel. These choices are available from the Menu pull-down:

Settings	Displays the ISPF Settings panel.
View	Displays the View Entry panel.
Edit	Displays the Edit Entry panel.
ISPF Command Shell	Displays the ISPF Command Shell panel.
Dialog Test	Displays the Dialog Test Primary Option panel.
Other IBM Products	Displays the Additional IBM Program Development Products panel.
SCLM	Displays the SCLM Main Menu.
ISPF Workplace	Displays the Workplace entry panel.
Status Area	Displays the ISPF Status panel.
Exit	Exits ISPF.

Utilities

This choice is available from many panels within ISPF and displays the options listed on the Utility Selection panel. These choices are available from the Utilities pull-down:

Library	Displays the Library Utility panel.
Data Set	Displays the Data Set Utility panel.
Move/Copy	Displays the Move/Copy Utility panel.
Data Set List	Displays the Data Set List Options panel.
Reset Statistics	Displays the Reset ISPF Statistics panel.
Hardcopy	Displays the Hardcopy Utility panel.
Download	Displays the panel that enables you to download workstation clients and other files from the host.
Outlist	Displays the Outlist Utility panel.
Commands	Displays the Command Table Utility panel.
Reserved	Reserved for future use by ISPF; an unavailable choice.
Format	Displays the Format Specification panel.
SuperC	Displays the SuperC Utility panel.
SuperCE	Displays the SuperCE Utility panel.
Search-for	Displays the Search-For Utility panel.
Search-forE	Displays the Search-ForE Utility panel.
Table Utility	Displays the ISPF Table Utility panel.

Compilers

The Compilers pull-down offers these choices:

1 **Foreground Compilers** Displays the Foreground Selection Panel.

2 **Background Compilers** Displays the Batch Selection Panel.

3 **ISPPREP Panel Utility** Displays the Preprocessed Panel Utility panel.

4 **DTL Compiler** Displays the ISPF Dialog Tag Language Conversion Utility panel.

Options

The Options pull-down offers these choices:

1 **General Settings** Displays the ISPF Settings panel.

2 **CUA Attributes** Displays the CUA Attribute Change Utility panel.

3 **Keylists** Displays the Keylist Utility panel.

4 **Point-and-Shoot** Displays the CUA Attribute Change Utility panel, positioned on the Point-and-Shoot panel element.

5 **Colors** Displays the Global Color Change Utility panel.

6 **Dialog Test appl ID** Displays the Dialog Test Application ID pop-up to allow you to change the application ID for Dialog test so that you

can look at variables in the application profile for an application that runs under a different application ID than the one under which ISPF was started (by default, ISR).

Status The Status pull-down offers these choices:

1 **Session**
2 **Function keys**
3 **Calendar**
4 **User status**
5 **User point and shoot**
6 **None**

See "Status area on the Primary Option Menu" for more information about using these choices to tailor the status area.

Help The Help pull-down provides general information about ISPF topics and the changes in the current release, as well as information about each of the options and areas on the Primary Option Menu.

Status area on the Primary Option Menu

The status area on the ISPF Primary Option Menu is a 21-column dynamic area that is composed of a 12-character description field, one attribute byte, and an 8-character field to display the value of the selected variable. The status area is limited to eleven description fields and their values. It can be manipulated from two places:

- The Status choice on the ISPF Primary Option Menu action bar. Use this pull-down to specify *what* you want to display in the status area. See "Status pull-down" for additional information and examples.
- The ISPF Status panel, which displays when you select Status Area from the Menu pull-down available on most action bars throughout ISPF. Use this facility to define the *contents* of the status area. See "Defining the status area" on page 13 for additional information and examples.

Note: The ISPF Status panel also contains an action bar choice called "Status". This does *not* affect which Status option displays on the Primary Option Menu panel. It determines which Status option displays within the ISPF Status panel.

The first five logical screens, created by a SPLIT or related command, each have their own status view. For each screen after that, the view defaults to the setting of the first screen.

Status pull-down

When you select one of the choices in the Status pull-down on the ISPF Primary Option Menu action bar (shown in Figure 2 on page 6), you specify what you want to display in the status area on the Primary Option Menu panel.

```
  Menu  Utilities  Compilers  Options  Status  Help
 ------------------------------------------------------------------------
                            ISPF Prim     *. Session                      
                                          2. Function keys                
0  Settings      Terminal and user p      3. Calendar                     USERID
1  View          Display source data      4. User status                  16:04
2  Edit          Create or change so      5. User point and shoot         3278
3  Utilities     Perform utility fun      6. None                         1
4  Foreground    Interactive languag                                      ENGLISH
5  Batch         Submit job for language processing      Appl ID . : ISR
6  Command       Enter TSO or Workstation commands       TSO logon : ISPF
7  Dialog Test   Perform dialog testing                  TSO prefix: USERID
9  IBM Products  IBM program development products        System ID : ISD1
10 SCLM          SW Configuration Library Manager        MVS acct. : IBMGSA
11 Workplace     ISPF Object/Action Workplace            Release . : ISPF 5.9
12 z/OS System   z/OS system programmer applications
13 z/OS User     z/OS user applications

     Enter X to Terminate using Log/List defaults


Option ===>  ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 2. Status pull-down on the ISPF Primary Option Menu (ISR@PRIM)

Note: The current setting is shown as an unavailable choice; that is, displays in blue (the default) with an asterisk as the first digit of the selection number. If you are running in GUI mode the choice is *grayed*.

Session

The Session view, shown in Figure 3 on page 7, displays this information in the status area:

- User ID
- Time
- Terminal
- Screen
- Language
- Application ID
- TSO logon
- TSO prefix
- System ID
- MVS account
- Release.

```
  Menu  Utilities  Compilers  Options  Status  Help
 ------------------------------------------------------------------------------
                            ISPF Primary Option Menu

 0  Settings      Terminal and user parameters            User ID . : USERID
 1  View          Display source data or listings         Time. . . : 16:23
 2  Edit          Create or change source data            Terminal. : 3278
 3  Utilities     Perform utility functions               Screen. . : 1
 4  Foreground    Interactive language processing         Language. : ENGLISH
 5  Batch         Submit job for language processing      Appl ID . : ISR
 6  Command       Enter TSO or Workstation commands       TSO logon : ISPF
 7  Dialog Test   Perform dialog testing                  TSO prefix: USERID
 9  IBM Products  IBM program development products        System ID : ISD1
 10 SCLM          SW Configuration Library Manager        MVS acct. : IBMGSA
 11 Workplace     ISPF Object/Action Workplace            Release . : ISPF 5.9
 12 z/OS System   z/OS system programmer applications
 13 z/OS User     z/OS user applications

      Enter X to Terminate using Log/List defaults


 Option ===>
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 3. ISPF Primary Option Menu status area – session view

System ID is a point-and-shoot field. **MVS Acct** and **Release** are point-and-shoot fields if over 8 characters long. Select these fields to display pop-up windows that contain additional information about the MVS account number and the ISPF environment.

MVS Acct
The account number identifying this MVS user.

System ID
Shows the **SYSPLEX** and **SYSNODE**.

SYSPLEX
The MVS sysplex name as found in the COUPLExx or LOADxx member of SYS1.PARMLIB.

SYSNODE
The network node name of your installation's JES.

```
  Menu  Utilities  Compilers  Options  Status  Help
— ┌──────── System Information ────────┐ ──────────────────────────────────
  │                                    │ Option Menu
  │ SYSPLEX = SYSPLEXD                 │
0 │ SYSNODE = PTHAPD$                  │ eters            User ID . : SUEBURN
1 │  F1=Help    F2=Split   F3=Exit     │ listings         Time. . . : 16:49
2 │  F9=Swap   F12=Cancel              │  data            Terminal. : 3278
3 └────────────────────────────────────┘ ns               Screen. . : 1
4  Foreground    Interactive language processing         Language. : ENGLISH
5  Batch         Submit job for language processing      Appl ID . : ISR
6  Command       Enter TSO or Workstation commands       TSO logon : ISPF
7  Dialog Test   Perform dialog testing                  TSO prefix: SUEBURN
9  IBM Products  IBM program development products        System ID : ISD1
10 SCLM          SW Configuration Library Manager        MVS acct. : IBMGSA
11 Workplace     ISPF Object/Action Workplace            Release . : ISPF 5.9
12 z/OS System   z/OS system programmer applications
13 z/OS User     z/OS user applications

     Enter X to Terminate using Log/List defaults


Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 4. System information pop-up

Release

Displays these variables:

- **ZOS390RL**— The z/OS Release running on your system.
- **ZISPFOS**— The level of ISPF code that is running as part of z/OS on your system. This might or might not match ZOS390RL.
- **ZENVIR**— The ISPF Environment description. See the table of system variables in the *z/OS ISPF Dialog Developer's Guide and Reference* for a complete explanation.

```
  Menu  Utilities  Compilers  Options  Status  Help
─ ┌──────────────────────────── Environment ────────────────────────────┐ ──
   │                                                                     │
   │ ZOS390RL = z/OS   01.04.00                                          │
0  │     The z/OS release running on your system.                        │
1  │                                                                     │
2  │ ZISPFOS  = ISPF FOR z/OS 01.05.00                                   │
3  │     The level of ISPF code that is running as part of z/OS on your  │
4  │     system. This might or might not match ZOS390RL.                 │
5  │                                                                     │
6  │ ZENVIR   = ISPF 5.5  MVS     TSO                                    │
7  │     The ISPF Environment description used by IBM personnel for      │
9  │     internal purposes. The x.y numbers DO NOT directly correlate to  │
1  │     an ISPF release number in all cases. Refer to the Dialog        │
1  │     Developer's Guide for a complete explanation.                   │ 5
1  │                                                                     │
1  │  F1=Help    F2=Split   F3=Exit    F9=Swap   F12=Cancel              │
1  └─────────────────────────────────────────────────────────────────────┘
 


Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 5. Environment pop-up (release information)

Function keys

The Function Keys view, shown in Figure 6 on page 10, displays this information in the status area:

- Number of keys
- Keys displayed per line
- Primary range (lower or upper)
- Display set (primary or alternate)
- List name (name of the currently active keylist)
- List applid (application ID for the currently active keylist)
- List type (private or shared)
- Keylists (on or off).

Note: See “Working with function keys and keylists (the Function Keys action bar choice)” on page 37 for information about changing these settings.

```
  Menu  Utilities  Compilers  Options  Status  Help
 ------------------------------------------------------------------------------
                            ISPF Primary Option Menu

 0  Settings      Terminal and user parameters           No. of keys: 24
 1  View          Display source data or listings        Keys / line: SIX
 2  Edit          Create or change source data           Primary set: LOW
 3  Utilities     Perform utility functions              Display set: PRI
 4  Foreground    Interactive language processing        List name. : ISRSAB
 5  Batch         Submit job for language processing     List applid: ISR
 6  Command       Enter TSO or Workstation commands      List type. : SHARED
 7  Dialog Test   Perform dialog testing                 Keylists . : PRIVATE
 9  IBM Products  IBM program development products
 10 SCLM          SW Configuration Library Manager
 11 Workplace     ISPF Object/Action Workplace
 12 z/OS System   z/OS system programmer applications
 13 z/OS User     z/OS user applications

      Enter X to Terminate using Log/List defaults


 Option ===>
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 6. ISPF Primary Option Menu status area – function keys view

Calendar

The Calendar view, shown in Figure 7, displays the calendar for the current month in the status area.

```
  Menu  Utilities  Compilers  Options  Status  Help
 ------------------------------------------------------------------------------
                            ISPF Primary Option Menu

 0  Settings      Terminal and user parameters           <     Calendar     >
 1  View          Display source data or listings           January   2003
 2  Edit          Create or change source data           Su Mo Tu We Th Fr Sa
 3  Utilities     Perform utility functions                      1  2  3  4
 4  Foreground    Interactive language processing         5  6  7  8  9 10 11
 5  Batch         Submit job for language processing     12 13 14 15 16 17 18
 6  Command       Enter TSO or Workstation commands      19 20 21 22 23 24 25
 7  Dialog Test   Perform dialog testing                 26 27 28 29 30 31
 9  IBM Products  IBM program development products
 10 SCLM          SW Configuration Library Manager       Time . . . . : 05:00
 11 Workplace     ISPF Object/Action Workplace           Day of year. :   135
 12 z/OS System   z/OS system programmer applications
 13 z/OS User     z/OS user applications

      Enter X to Terminate using Log/List defaults


 Option ===>
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 7. ISPF Primary Option Menu status area – calendar view

All of the fields on the calendar are point-and-shoot fields that function as follows:

If you select	ISPF displays
<	the previous month.
calendar	the current month.
>	the next month.
Month, **e.g. July**	the Calendar Month pop-up. Allows you to specify the month. See "Customizing the calendar" on page 16 for details.
Year, **e.g. 2003**	the Calendar Year pop-up. Allows you to specify the year. See "Customizing the calendar" on page 16 for details.
Day	the Calendar Start Day pop-up. Allows you to specify Saturday, Sunday, or Monday as the start day for the calendar. See "Customizing the calendar" on page 16 for details.
Date	the Julian Date pop-up. Provides the Julian date for the date selected.

```
  Menu  Utilities  Compilers  Options  Status  Help
— ┌──────────────── Julian Date ────────────────┐ ──────────────────────────
  │                                             │ u
  │                                             │
0 │ 2003/01/24  is day  024  of year  2003      │        <     Calendar     >
1 │                                             │           January   2003
2 │                                             │        Mo Tu We Th Fr Sa Su
3 │  F1=Help    F2=Split   F3=Exit    F9=Swap   │                1  2  3  4  5
4 │ F12=Cancel                                  │         6  7  8  9 10 11 12
5 └─────────────────────────────────────────────┘ g      13 14 15 16 17 18 19
6  Command       Enter TSO or Workstation commands       20 21 22 23 24 25 26
7  Dialog Test   Perform dialog testing                  27 28 29 30 31
9  IBM Products  IBM program development products
10 SCLM          SW Configuration Library Manager        Time . . . . : 13:42
11 Workplace     ISPF Object/Action Workplace            Day of year. :   024
12 z/OS System   z/OS system programmer applications
13 z/OS User     z/OS user applications

     Enter X to Terminate using Log/List defaults


Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 8. Julian date pop-up

Time	the Calendar Time Format pop-up. Allows you to specify a 12-hour or 24-hour time format for the calendar. See "Customizing the calendar" on page 16 for details.
Day of year	the Standard Date pop-up. Provides the standard date for the day specified in the popup (defaults to the date selected in the calendar).

```
  Menu  Utilities  Compilers  Options  Status  Help
─ ┌──────────────────────────── Standard Date ────────────────────────────┐ ──────
  │                                                                       │
  │                                                                       │
0 │ Enter the day and year below:                                         │     >
1 │                                                                       │ 003
2 │ Day . . . . 024   (Between 1 and 365 or 366 if leap year)             │  Sa Su
3 │ Year  . . . 2003  (Between 1801 and 2099)                             │   4  5
4 │                                                                       │  11 12
5 │ Day  024  of year  2003  is  Friday        ,  2003/01/24              │  18 19
6 │                                                                       │  25 26
7 │                                                                       │
9 │  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward       │
1 │  F9=Swap     F12=Cancel                                               │  13:47
1 └───────────────────────────────────────────────────────────────────────┘    024

     Enter X to Terminate using Log/List defaults




Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 9. Standard date pop-up

User status

The User Status view, shown in Figure 10, displays the status information that you have defined in the Status Area panel.

```
  Menu  Utilities  Compilers  Options  Status  Help
──────────────────────────────────────────────────────────────────────────────
                           ISPF Primary Option Menu

0  Settings      Terminal and user parameters               User ID:   USERID
1  View          Display source data or listings            Date:      24/01/03
2  Edit          Create or change source data               Time:      14:57
3  Utilities     Perform utility functions
4  Foreground    Interactive language processing
5  Batch         Submit job for language processing
6  Command       Enter TSO or Workstation commands
7  Dialog Test   Perform dialog testing
9  IBM Products  IBM program development products
10 SCLM          SW Configuration Library Manager
11 Workplace     ISPF Object/Action Workplace
12 z/OS System   z/OS system programmer applications
13 z/OS User     z/OS user applications

     Enter X to Terminate using Log/List defaults


Option ===> ──────────────────────────────────────────────────────────────────
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 10. ISPF Primary Option Menu status area – user status view

User point and shoot

The User Point-and-Shoot view, shown in Figure 11 on page 13, displays the point-and-shoot function you have defined in the Status Area panel.

Note: If you are running in GUI mode, this function will be displayed as a push button.

```
  Menu  Utilities  Compilers  Options  Status  Help
 ___________________________________________________________________________
                            ISPF Primary Option Menu

0  Settings      Terminal and user parameters                Dialog Test
1  View          Display source data or listings             Edit
2  Edit          Create or change source data                Edit Recovery Table
3  Utilities     Perform utility functions
4  Foreground    Interactive language processing
5  Batch         Submit job for language processing
6  Command       Enter TSO or Workstation commands
7  Dialog Test   Perform dialog testing
9  IBM Products  IBM program development products
10 SCLM          SW Configuration Library Manager
11 Workplace     ISPF Object/Action Workplace
12 z/OS System   z/OS system programmer applications
13 z/OS User     z/OS user applications

     Enter X to Terminate using Log/List defaults


Option ===> _____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 11. ISPF Primary Option Menu status area – user point-and-shoot view

None

If you select None from the Status pull-down, nothing will be displayed in the status area.

Defining the status area

When you select Status Area from the Menu pull-down, ISPF displays the ISPF Status pop-up window (shown in Figure 12 on page 14), with an independent view of the status area. This panel is used to define the contents of the status area choices. You can change the choice displayed in this window by using the Status pull-down on the action bar.

Note: Changing the status area viewed in this panel will *not* affect the choice selected on the ISPF Primary Option Menu panel.

```
  Menu  Utilities  Compilers  Options  Status  Help
_ ┌──────────────────────┐ ──────────────────────────────────────────────────
    Status  Options        F Primary Option Menu
   ────────────────────
0      ISPF Status         user parameters            User ID . : USERID
1                          e data or listings         Time. . . : 11:10
2                          nge source data            Terminal. : 3278
3  <     Calendar     >    ty functions               Screen. . : 1
4     January   2003       anguage processing         Language. : ENGLISH
5  Su Mo Tu We Th Fr Sa    r language processing      Appl ID . : ISR
6            1  2  3  4   Workstation commands       TSO logon : ISPF
7   5  6  7  8  9 10 11    g testing                  TSO prefix: USERID
9  12 13 14 15 16 17 18    evelopment products        System ID : ISD1
1  19 20 21 22 23 24 25    ion Library Manager        MVS acct. : IBMGSA
1  26 27 28 29 30 31       ction Workplace            Release . : ISPF 5.5

    Time . . . . : 11:10   g Log/List defaults
    Day of year. :   024

   Command ===> _________
    F1=Help     F2=Split
0   F3=Exit
                          Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 12. ISPF status pop-up (ISPSAMMN)

Status The Status pull-down, shown in Figure 13 on page 15, offers these choices:

1 Session

2 Function keys

3 Calendar

4 User status

5 User point and shoot

6 None

```
  Menu  Utilities  Compilers  Options  Status  Help
_ ┌──────────────────────────┐ ──────────────────────────────────────────────
I │   Status  Options        │ F Primary Option Menu
  │                          │
0 │   ┌──────────────────────┐  parameters            <     Calendar     >
1 │   │  1. Session          │  a or listings            January   2003
2 │   │  2. Function keys    │  ource data            Su Mo Tu We Th Fr Sa
3 │   │  *. Calendar         │  nctions                          1  2  3  4
4 │   │  4. User status      │  ge processing          5  6  7  8  9 10 11
5 │   │  5. User point and shoot  guage processing    12 13 14 15 16 17 18
6 │   │  6. None             │  tation commands       19 20 21 22 23 24 25
7 │   │  7. Exit             │  ting                  26 27 28 29 30 31
9 │   12 13 14 15 16 17 18   │ evelopment products
1 │   19 20 21 22 23 24 25   │ ion Library Manager        Time . . . . : 11:38
1 │   26 27 28 29 30 31      │ ction Workplace            Day of year. :   024
  │                          │
  │   Time . . . . : 11:38   │ g Log/List defaults
  │   Day of year. :   024   │
  │                          │
  │  Command ===>            │
  │   F1=Help     F2=Split   │
0 │   F3=Exit                │
  └──────────────────────────┘ Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 13. Status pull-down in ISPF status pop-up

Options The Options pull-down, shown in Figure 14 on page 16, offers these choices:

1 **Calendar start day** Displays the Calendar Start Day pop-up, where you can specify Saturday, Sunday, or Monday as the start day for the calendar.

2 **Calendar colors** Displays the Calendar Colors pop-up, where you can change the colors on the calendar.

3 **User status customization** Displays the User View Customization pop-up, where you can define what you want displayed in the status area.

4 **User point and shoot customization** Displays the User Point and Shoot Customization pop-up, where you can define point-and-shoot fields to be displayed in the status area.

```
  Menu  Utilities  Compilers  Options  Status  Help
 ─ ┌──────────────────────┐ ──────────────────────────────────────────────
 I │  Status  Options     │ F Primary Option Menu
   │ ────────             │
 0 │     IS  ┌──────────────────────────────────────────┐     Calendar    >
 1 │         │ 1. Calendar Start day...                 │  January   2003
 2 │         │ 2. Calendar Colors...                    │  Mo Tu We Th Fr Sa
 3 │  <      │ 3. User status customization...          │         1  2  3  4
 4 │    Jan  │ 4. User point and shoot customization... │   6  7  8  9 10 11
 5 │  Su Mo Tu We Th Fr Sa │ r language processing      12 13 14 15 16 17 18
 6 │            1  2  3  4 │ Workstation commands       19 20 21 22 23 24 25
 7 │   5  6  7  8  9 10 11 │ g testing                  26 27 28 29 30 31
 9 │  12 13 14 15 16 17 18 │ evelopment products
 1 │  19 20 21 22 23 24 25 │ ion Library Manager        Time . . . . : 11:38
 1 │  26 27 28 29 30 31    │ ction Workplace            Day of year. :   024
   │                       │
   │  Time . . . . : 11:38 │ g Log/List defaults
   │  Day of year. :   024 │
   │                       │
   │ Command ===>          │
   │  F1=Help     F2=Split │
 0 │  F3=Exit              │
   └───────────────────────┘ Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 14. Options pull-down in ISPF status pop-up

Customizing the calendar

You can customize the calendar to show a different month, year or starting day. You can set the time display to a 12 or 24 hour clock. You can also customize the colors used to display the calendar.

Notes:

1. Changes to the month or year display will last for the current session only. Changes to the starting day and time format will be saved between sessions.
2. You can use the point-and-shoot fields on the calendar displayed on the Primary Option Menu panel or in the Status Area pop-up. Changes made in either location will affect the display in both locations.

Changing the month display: You can change the month that displays in the calendar in a number of ways:

- Click the < or > symbols to display the previous or next month.
- Click the Calendar point-and-shoot field to display the current month.
- Set the month display to a particular month by selecting the month name point-and-shoot field and entering a number in the Calendar Month pop-up window:

```
  Menu  Utilities  Compilers  Options  Status  Help
— ┌──────────── Calendar Month ────────────┐ ──────────────────────────────────
  │                                        │ ption Menu
  │                                        │
0 │ Month . . . 01  1.  January            │ ters            <     Calendar     >
1 │                 2.  February           │ istings            January   2003
2 │                 3.  March              │ data            Su Mo Tu We Th Fr Sa
3 │                 4.  April              │ s                        1  2  3  4
4 │                 5.  May                │ cessing          5  6  7  8  9 10 11
5 │                 6.  June               │ processing      12 13 14 15 16 17 18
6 │                 7.  July               │  commands       19 20 21 22 23 24 25
7 │                 8.  August             │                 26 27 28 29 30 31
9 │                 9.  September          │ products
1 │                 10. October            │  Manager        Time . . . . : 10:13
1 │                 11. November           │ lace            Day of year. :   024
  │                 12. December           │
  │                                        │ g Log/List defaults
  │ Select a choice and press ENTER        │
  │  F1=Help          F2=Split             │
  │  F3=Exit          F7=Backward          │
  └────────────────────────────────────────┘
Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 15. Calendar month pop-up window

Changing the year display: You can change the year that displays in the calendar by selecting the year point-and-shoot field and entering the required year (between 1801 and 2099) in the Calendar Year pop-up window.

```
  Menu  Utilities  Compilers  Options  Status  Help
— ┌──────────────────── Calendar Year ────────────────────┐ ────────────────────
  │                                                       │
  │                                                       │
0 │ Year . . .                                            │ <     Calendar     >
1 │                                                       │    January   2003
2 │ Enter the year to display between 1801 and 2099       │ Mo Tu We Th Fr Sa Su
3 │                                                       │        1  2  3  4  5
4 │  F1=Help         F2=Split        F3=Exit              │  6  7  8  9 10 11 12
5 │  F7=Backward     F8=Forward      F9=Swap              │ 13 14 15 16 17 18 19
6 └───────────────────────────────────────────────────────┘ 20 21 22 23 24 25 26
7  Dialog Test   Perform dialog testing                    27 28 29 30 31
9  IBM Products  IBM program development products
10 SCLM          SW Configuration Library Manager         Time . . . . : 13:57
11 Workplace     ISPF Object/Action Workplace             Day of year. :   024
12 z/OS System   z/OS system programmer applications
13 z/OS User     z/OS user applications

     Enter X to Terminate using Log/List defaults


Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 16. Calendar year pop-up window

Changing the starting day: You can change the calendar display so that the weeks begin on a Saturday, Sunday, or Monday.

1. To display the Calendar Start Day pop-up window, use either of these methods:
   - Select any day name point-and-shoot field (e.g. Mo or Tu).

- From the Menu action bar, select Status Area. Then, from the Options action bar, choose 1. Calendar Start day.

2. Enter option 1. Sunday, 2. Monday or 3. Saturday.

```
  Menu  Utilities  Compilers  Options  Status  Help
─ ┌──────────── Calendar Start Day ────────────┐ ──────────────────────────────
  │                                            │  Menu
  │                                            │
0 │ Current start date  : 2                    │            <     Calendar     >
1 │                                            │ gs            January   2003
2 │ New start date  . . . 2  1. Sunday         │            Mo Tu We Th Fr Sa Su
3 │                          2. Monday         │                   1  2  3  4  5
4 │                          3. Saturday       │ ng           6  7  8  9 10 11 12
5 │                                            │ ssing       13 14 15 16 17 18 19
6 │ Select a choice and press ENTER            │ ands        20 21 22 23 24 25 26
7 │                                            │             27 28 29 30 31
9 │  F1=Help      F2=Split     F3=Exit         │ cts
1 │  F7=Backward  F8=Forward   F9=Swap         │ ger         Time . . . . : 14:02
1 └────────────────────────────────────────────┘             Day of year. :   024

     Enter X to Terminate using Log/List defaults




Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 17. Calendar start pop-up window

Changing the time format: You can change the time format to a 12-hour or 24-hour clock. To do this, select the Time point-and-shoot field and enter option 1 or 2 in the Calendar Time Format pop-up window.

```
  Menu  Utilities  Compilers  Options  Status  Help
─ ┌──────────── Calendar Time Format ──────────┐ ──────────────────────────────
  │                                            │
  │                                            │
0 │ Current time format : 2                    │            <     Calendar     >
1 │                                            │            January   2003
2 │ New time format . . . 2  1. 12 hour format │            Mo Tu We Th Fr Sa Su
3 │                          2. 24 hour format │                   1  2  3  4  5
4 │                                            │             6  7  8  9 10 11 12
5 │ Select a choice and press ENTER to continue.│            13 14 15 16 17 18 19
6 │                                            │            20 21 22 23 24 25 26
7 │                                            │            27 28 29 30 31
9 │  F1=Help        F2=Split       F3=Exit     │
1 │  F7=Backward    F8=Forward     F9=Swap     │            Time . . . . : 14:18
1 └────────────────────────────────────────────┘            Day of year. :   024

     Enter X to Terminate using Log/List defaults




Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 18. Calendar time format pop-up window

Changing the calendar colors: To change the colors on the calendar:

1. From the ISPF Status action bar, select Options and then 2. Calendar colors. The Calendar Colors pop-up, Figure 19, is displayed.
2. Type a valid color number in the field next to each calendar element to be changed and press Enter. The color will change immediately in the Sample area.

   To restore a default color, clear the element field and press Enter.
3. Press EXIT (F3) or END to exit and save the changes. Press CANCEL (F12) to exit without saving the changes.

```
  Menu  Utilities  Compilers  Options  Status  Help
─ ┌──────────────────────┐ ──────────────────────────────────────────────
  │ ┌──────────────────────── Calendar Colors ──────────────────────────┐
  │ │                                                          Defaults
0 │ │
1 │ │   Change one or more of the Calendar colors and press enter to
2 │ │   immediately see the effect. Clearing a field restores defaults.
3 │ N
4 │ K Field:            Color:    Valid Colors:    Sample:
5 │ P Scroll Button . . . 8       1. White         <     Calendar     >
6 │ D Heading Date  . . . 8       2. Red              July      1995
7 │ L Heading Text  . . . 8       3. Blue          Su Mo Tu We Th Fr Sa
9 │ L Weekday . . . . . . 8       4. Green                            1
1 │ L Saturday/Sunday . . 8       5. Pink           2  3  4  5  6  7  8
1 │ K Current Day . . . . 8       6. Yellow         9 10 11 12 13 14 15
  │ │                             7. Turq          16 17 18 19 20 21 22
  │ │                             8. CUA default   23 24 25 26 27 28 29
  │ │                                              30 31
  │ │                                              Time . . . . : 10:10
  │ C                                              Day of year. :   202
  │ │
O │ │  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward
  └─┘  F9=Swap     F12=Cancel
F10=A
```

Figure 19. Calendar colors panel (ISPCALGC)

Customizing the user status area

To define the contents of this area:

1. From the ISPF Status action bar, select Options and then 3. User status customization. The User View Customization panel, Figure 20 on page 20, is displayed.

```
  Menu  Utilities  Compilers  Options  Status  Help
 ──────────────── User View Customization ────────────────
 Enter a description and variable name below:

    Description:         Variable name:
    ____________         ________
    ____________         ________
    ____________         ________
    ____________         ________
    ____________         ________
    ____________         ________
    ____________         ________
    ____________         ________
    ____________         ________
    ____________         ________
    ____________         ________
    ____________         ________

 Press EXIT or END to exit and save the changes.
 Press CANCEL to exit without saving the changes.
  F1=Help         F2=Split        F3=Exit
  F7=Backward     F8=Forward      F9=Swap
```

Figure 20. User view customization panel (ISPSAMUS)

2. Enter a heading in the Description field and the name of a System variable or site-defined variable in the Variable name field. See the *z/OS ISPF Dialog Developer's Guide and Reference* for a list of System Variable names.
3. Press EXIT (F3) or END to exit and save the changes. Press CANCEL (F12) to exit without saving the changes.

For example, entering:

```
Description:        Variable name:
User ID:            ZUSER
Date:               ZDATE
Time:               ZTIME
```

would result in the display shown in Figure 10 on page 12.

Customizing the user point-and-shoot status area

You can define up to nine point-and-shoot fields, which you can set to any SELECT service parameter. To do this:

1. From the ISPF Status action bar, select Options and then 4. User point and shoot customization. The User Point-and-Shoot panel, Figure 21 on page 21, is displayed.

```
  Menu  Utilities  Compilers  Options  Status  Help
─ ┌ ┌──────────────────────────── User Point-and-Shoot ────────────────────────────┐
  │ │                                                                               │
  │ │                                                                               │
0 │ │  Press EXIT or END to exit and save the changes.                              │
1 │ │  Press CANCEL to exit without saving the changes.                             │
2 │ │                                                                               │
3 │ │  Enter Point-and-shoot text and SELECT keywords.                              │
4 │ │                                                                               │
5 │ │  Point-and-shoot text:  SELECT service parameters:                            │
6 │ │                                                                More:     +    │
7 │ │  ________________  ______________________________________________________     │
9 │ │                    ______________________________________________________     │
1 │ │                    ______________________________________________________     │
1 │ │                    ______________________________________________________     │
  │ │                    ______________________________________________________     │
  │ │                    ______________________________________________________     │
  │ │  ________________  ______________________________________________________     │
  │ │                    ______________________________________________________     │
  │ │                    ______________________________________________________     │
  │ │                    ______________________________________________________     │
  │ │                    ______________________________________________________     │
0 │ │   F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward          │
  └ e  F9=Swap      F12=Cancel                                                      │
F10 └───────────────────────────────────────────────────────────────────────────────┘
```

Figure 21. User point-and-shoot panel (ISPSAMUP)

2. Enter the text to appear in the status area, in the field on the left of the panel.
3. Enter the Service parameters to be invoked in the lines on the right of the panel. See *z/OS ISPF Services Guide* for information about these parameters.
4. Press EXIT (F3) or END to exit and save the changes. Press CANCEL (F12) to exit without saving the changes.

Chapter 2. Settings (option 0)

The Settings option allows you to display and change a variety of ISPF parameters at any time during the ISPF session. Changes remain in effect until you change the parameter again, and ISPF saves them from session to session. This topic explains how to use the fields on the ISPF Settings panel and the action bar choices.

If you select option 0 on the ISPF Primary Option Menu, the panel shown in Figure 22 is displayed.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ------------------------------------------------------------------------------
                                ISPF Settings

Options                                     Print Graphics
  Enter "/" to select option                  Family printer type 2
  /  Command line at bottom                   Device name . . . . _______
  /  Panel display CUA mode                   Aspect ratio  . . . 0
  _  Long message in pop-up
  _  Tab to action bar choices
  _  Tab to point-and-shoot fields          General
  /  Restore TEST/TRACE options               Input field pad . . B
  _  Session Manager mode                     Command delimiter . ;
  /  Jump from leader dots
  _  Edit PRINTDS Command
  /  Always show split line
  _  Enable EURO sign
  /  Scroll member list
  _  Allow empty member list
  _  Allow empty member list (nomatch)
  /  Empty member list for edit only

Terminal Characteristics
  Screen format   2  1. Data    2. Std     3. Max     4. Part

  Terminal Type   3   1. 3277       2. 3277A      3. 3278       4. 3278A
                      5. 3290A      6. 3278T      7. 3278CF     8. 3277KN
                      9. 3278KN    10. 3278AR    11. 3278CY    12. 3278HN
                     13. 3278HO    14. 3278IS    15. 3278L2    16. BE163
                     17. BE190     18. 3278TH    19. 3278CU    20. DEU78
                     21. DEU78A    22. DEU78T    23. DEU90A    24. SW116
                     25. SW131     26. SW500     27. 3278GR    28. 3278L1
                     29. OTHER
Command ===> ____________________________________________________________________
 F1=HELP      F2=SPLIT     F3=END       F4=RETURN    F5=RFIND     F6=RCHANGE
 F7=UP        F8=DOWN      F9=SWAP     F10=LEFT     F11=RIGHT    F12=RETRIEVE
```

Figure 22. ISPF Settings panel (ISPISMMN)

This facility can also be started from any command line with the SETTINGS command, or from the Settings choice on the Menu pull-down on any action bar where it is available. Typically, the Settings facility should be included as an option on an application's primary option menu or as a choice on a pull-down on an application's primary option menu.

Some of the things you can specify are:
- Terminal characteristics
- Default options for processing the ISPF list and log data sets

© Copyright IBM Corp. 1980, 2007

- Function key assignments
- Placement of command lines
- List data set characteristics
- GDDM graphic print parameters
- Keylist modifications
- Dialog Test option
- Default colors
- Values of CUA panel elements
- Point-and-shoot color and highlight changes
- ENVIRON command options.

ISPF Settings panel fields

Figure 22 on page 23 shows the initial default ISPF Settings. The display or the field-level help indicates the allowable alternatives for these defaults. The values shown in Figure 22 are for an ISPF session in the English language. The corresponding panel displayed for a non-English session is similar, but the accepted terminal types can be different.

Select options

Each option is described in this topic. Use a slash to select an option. Blank out the slash to deselect the option.

Command line at bottom

Specifies that the command line is to appear at the bottom of each logical screen. If you have specified that the panel should be displayed in CUA mode, the command line placement defaults to the bottom.

Notes:

1. The default is to have the command line placement at the bottom. However, if your current application profile table specifies ASIS, the default does not override it.
2. If you deselect this field, the command line appears as specified in the panel definition statements. Unless indicated in the panel definition, it appears at the top of the panel.

When you select the Command line at bottom option, these changes take place:

- The command line moves to the last line of the logical screen or the line above the function keys depending on the CUA mode setting (see Table 1 on page 25).
- Each line that follows the command line shifts up one line.
- The long message overlays the line above the new command line location.

  If the command line for a table display panel has been moved to the bottom and if no alternate placement has been specified for the long message line, the line directly above the repositioned command line is reserved (left blank) for the display of long messages. Otherwise, if you enter erroneous data on that line, a long message could overlay that data.
- In general, the display location of the function key definitions depends on several variables.
  - If the panel display mode CUA option is not selected, and the KEYLIST option is set to OFF, the function key definitions display on the lines immediately above the long message line.

– If the panel display mode CUA option is on, and the KEYLIST option is set to OFF, the function key definitions display below the long message line.
– If the KEYLIST option is set to ON, and the panel definition does not contain a)PANEL statement, the positioning of the function keys depends on the CUA mode setting.
– If the KEYLIST option is set to ON, and the panel definition contains a)PANEL statement, the positioning of the function keys is below the long message line.

If the Panel display CUA mode option is not selected, an exception to this situation occurs when an alternate placement for the long message line has been specified using the LMSG keyword on the)BODY header statement. Under these circumstances, the function key definitions display immediately above the command line.

If a conflict occurs between the placement of the function key definition lines and those that are to display long messages, short messages, and commands, the function keys will not overlay the command line, the line containing the long or short message field, or any line above one of these fields. Because of this condition, function key definition lines cannot appear at all on some screens.

When using the GDDM interface to display panels, the position of a graphics field does not change if the command line moves to the bottom of the screen.

In split-screen mode, if the top screen specifies the Command line at bottom option, the command line is moved to the line directly above the split line, and the long message line overlays the line above the command line. Because the placement setting is stored in the application profile pool, the setting for each logical screen is the same unless a user is running different applications in each screen.

Panel display CUA mode

Specifies that panels be displayed in CUA mode. This selection affects how the long message line, command line, and function keys are displayed, as described in Table 1.

Table 1 summarizes how the command, long message, and function key area appear on the panel depending on whether you select the Panel display in CUA mode option. Note that the table uses the system default to position the long message field. An alternate long message field is not defined using the LMSG keyword on the)BODY header statement.

Table 1. CUA mode effect on panel display

Panel Characteristic	CUA mode selected	CUA mode not selected
Command line at bottom	Long message line Command line Fn=name	PF n=name Long message line Command line
Command line at bottom deselected	Title/short message Command line Long message line : : Fn=name	Title/short message Command line Long message line : : PF n=name

Table 2 on page 26 summarizes the effect of CUA mode on the top-row-displayed indicator.

Table 2. CUA mode effect on top-row-displayed indicator

CUA Mode	Rows	Top-Row-Displayed Message	Message ID
YES	ALL	Row x to z of y	ISPZZ102
YES	SCAN	Row x From y	ISPZZ103
NO	ALL	Row x of y	ISPZZ100
NO	SCAN	Row x of y	ISPZZ100

Long message in pop-up
Specifies that long messages will be displayed in a pop-up window, regardless of the .WINDOW setting in the message source.

Tab to action bar choices
Specifies that you want to use the Tab key to move the cursor among the action bar choices.

Note: You cannot use the Tab key for this purpose if you are running in GUI mode.

Tab to point-and-shoot fields
Specifies that you want to use the Tab key to move the cursor through the point-and-shoot fields on a panel.

Note: You cannot use the Tab key for this purpose if you are running in GUI mode.

Restore TEST/TRACE options
When you select Dialog Test facility (option 7), certain TEST and TRACE options are established that can be different than those specified during ISPF start up. If you select Restore TEST/TRACE options, the TEST or TRACE values are restored to the ISPF call values when you exit dialog test. If you deselect the field, the TEST or TRACE values are not restored when you exit dialog test.

For more information about dialog test, see Chapter 9, “Dialog test (option 7).”

Session Manager mode
Enter a slash to indicate that the Session Manager should handle any line mode output from the processing program.

Jump from leader dots
Enter a slash to enable the ISPF jump function from field prompts that have leader dots (. . or ...). Field prompts that have the ==> will always have the jump function enabled.

If the application developer defines the NOJUMP(ON) attribute keyword on a specific input field, this disables the ″Jump from leader dots″ and takes precedence over the selected Settings ″Jump from leader dots″ or the configuration table setting of ″YES″ for ″Jump from leader dots″.

Edit PRINTDS Command
Enter a slash to intercept the local print request to allow you to modify the statement before the PRINTDS command begins. For more information on editing the PRINTDS command, see the Libraries and Data Sets topic in *z/OS ISPF User’s Guide Vol I*.

Always show split line
Specifies that the split line in split screen mode, as seen on a 3270 display,

should always be shown. The default for this option is that the option is selected. By deselecting this option, the split line does not display when the screen is split at the top or the bottom of the screen.

Enable EURO Sign
Enter a slash to enable the EURO sign (currency symbol). Your terminal or emulator must support the EURO sign for this option to work.

Scroll member list
Enter a slash to specify that ISPF should scroll to the first member selected in the member list after processing. If the Option field is deselected, automatic member list scrolling is disabled and the cursor is placed in front of the last member selected.

Allow empty member list
Specifies whether an empty member list will be displayed for a PDS that contains no members.

Allow empty member list (nomatch)
If the 'Allow empty member list' option is set, this field specifies whether an empty list that results from a nonmatching pattern will be displayed.

Empty member list for edit only
Specifies whether empty member list options apply to non-edit functions such as View and Browse.

Terminal characteristics

The Terminal Characteristics portion of the ISPF Settings panel allows you to specify values for the screen format and terminal type. Each of these characteristics is described here.

Screen format
Specification of screen format applies only to 327*x* and 3290 terminals (or a terminal emulator set to a mode that emulates a 327*x* or 3290 terminal). ISPF ignores screen format for other types of terminal.

Data Format is based on data width.
Std Format is always 24 x 80 characters.
Max Format is determined by the maximum data width and height of the terminal or emulator.
Part Format uses hardware partitions (3279 only)

Notes:

1. ISPF supports screen sizes from 24 x 80 characters to 62 x 160 characters.
2. If you are in an Edit session or you are using the EDIT service, ISPF will not allow you to change the screen format.

Terminal type
Specify a valid terminal type. If you are using a terminal emulator, select the type of terminal that is being emulated (usually a 3278 or 3278*x*).

You can select one of the standard terminal types from the list on the ISPF Settings panel (see Figure 22 on page 23). If the selected terminal type seems to be incompatible with the current ISPF language setting, a 'Terminal Type Warning' Message will be displayed, but the terminal type will be accepted nevertheless.

If you want to use a custom terminal translation table that has been created for your site, select OTHER to specify the name of the translation table. If the load of the new translation tables fails, ISPF reverts to the previous terminal type setting.

You can also select a terminal type by using the ISPTTDEF program, as described in *z/OS ISPF Dialog Developer's Guide and Reference*.

Specification of a terminal type allows ISPF to recognize valid (displayable) characters. Keep in mind that the terminal type value that you specify to ISPF might not be the actual terminal type. For example, if your terminal is a 3279, you specify 3278 because a 3279 terminal has the same character set as a 3278. The keyboard character sets for the specified terminal and the actual terminal are always compatible.

The terminal type designations in the text of this document are often the value to be specified to ISPF rather than the actual terminal type.

This panel can also include one or more installation-dependent options for terminal type, for example:

3277KN	3277 Katakana terminals
3278CF	3278 Canadian French terminals
3278KN	3278 Katakana terminals

A 5550-3270 Kanji emulation Version 3 terminal has the same character set as a 3278 Katakana terminal, so you should specify 3278KN as the terminal type. Also, because the 5550 running with the Japanese 3270PC/G Version 3 or 3270 PC Version 5 has the same character set as a 3278 Katakana terminal, in either case you should specify 3278KN as the terminal type.

The 5550 is run with the Japanese 3270PC V5 or 3270PC/G V3 emulation program. The terminal type, set by the ISPF Settings panel, is set to 3278KN.

Print graphics parms

The Print Graphics Parms portion of the ISPF Settings panel allows you to specify to GDDM the family printer type, device name, and aspect ratio. These parameters are described here:

Family printer type
This parameter has a default value of 2, which cannot be changed.

Device name
VTAM® node name of the physical printer to which graphic display output is to be routed. This name is supplied by your system programmer.

Aspect ratio
How the graphics aspect ratio (relationship to displayed screen image) is to appear on the printed output. Aspect ratio can be either of these:

0 Preserves the aspect ratio of the graphic area as displayed (Figure 23 on page 29). In other words, the ratio of the graphic area width to its height is the same on the printed document (Figure 24 on page 29) as in the displayed view. Zero is the default value. Figure 24 shows how the graphic in Figure 23 would appear if the PRINTG command were issued with an aspect ratio of 0.

1 Preserves the positional relationship between the graphic and the alphanumeric characters outside the graphics area. In other words, the printed graphic (Figure 25 on page 30) aligns horizontally with

characters outside the graphics area the same as it (the printed graphic) aligns in the displayed image.



Figure 23. Screen containing graphics to be printed using PRINTG



Figure 24. Example of using aspect ratio parameter 0

Figure 25 shows how the graphic in Figure 23 would appear if the PRINTG command were issued with an aspect ratio of 1.



Figure 25. Example of using aspect ratio parameter 1

General

The General portion of the ISPF Settings panel allows you to specify values for the input field pad and command delimiter.

Input field pad

Specifies a pad character that controls the initial padding of blank (unfilled) panel input fields, including the selection panels, but not the data portion, of an Edit display. Within Edit, you control null or blank padding with Edit commands.

The pad character specified can be a B (blank), N (nulls), or any special (non-alphanumeric) character.

Note: When you are running in GUI mode, blank pad characters will be displayed as nulls in order to avoid the need to delete blank characters when replace mode is not available.

Command delimiter

You can stack commands on the command line by separating them with a delimiter. The default delimiter, the semicolon, can be changed using this option. Alphanumeric characters, the period (.), and the equal sign (=) are not valid command delimiters. Stacking allows you to enter, for example:

```
===> FIND DEPT;HEX ON
```

which finds the characters DEPT and then displays the file at that point in hexadecimal mode.

The system variable for the delimiter is ZDEL. For more information about ZDEL, refer to the *z/OS ISPF Dialog Developer's Guide and Reference*.

ISPF Settings panel action bar

The ISPF Settings panel action bar choices function as follows:

Log/List

The Log/List pull-down offers these choices:

1 **Log Data set defaults**. See "Log data set defaults" on page 32.

2 **List Data set defaults**. See "List data set defaults" on page 33.

3 **List Data set characteristics**. See "List data set characteristics" on page 35.

4 **JCL**. See "JCL" on page 36.

Function keys

The Function keys pull-down offers you these choices (see "Working with function keys and keylists (the Function Keys action bar choice)" on page 37 for more information):

1 **Non-Keylist PF Key settings**. Displays the PF Key Definitions and Labels panel.

2 **Keylist settings** Displays the Keylist Utility for ISP pop-up.

3 **Tailor function key display**. Displays the Tailor Function Key Definition Display panel.

4 **Show all function keys**. Changes the function key display. This will be an unavailable choice if you are currently showing all function keys.

5 **Show partial function keys**. Changes the function key display. This will be an unavailable choice if you are currently showing a partial list of function keys.

6 **Remove function key display**. Removes function keys from your screen. This will be an unavailable choice if you are currently not showing function keys.

7 **Use private and shared**. Equivalent to using the KEYLIST PRIVATE command.

8 **Use only shared**. Equivalent to using the KEYLIST SHARED command.

9 **Disable keylists**. Disables keylists. This choice is not available if you are currently running with keylists disabled.

10 **Enable keylists**. Enables keylists. This choice is not available if you are currently running with keylists enabled.

Colors

The Colors pull-down offers you these choices (see "Changing default colors (the Colors action bar choice)" on page 51 for more information):

1 **Global colors** Displays the Global Color Change Utility panel.

2 **CUA Attributes** Displays the CUA Attribute Change Utility panel.

3 **Point-and-Shoot** Displays the CUA Attribute Change Utility panel, positioned on the Point-and-Shoot panel element.

Environ

The Environ pull-down offers you these choices (see "Specifying ISPF ENVIRON settings (the Environ action bar choice)" on page 57 for more information):

1 **Environ settings** Displays the ISPF ENVIRON Command Settings panel.

Workstation

The Workstation pull-down offers you these choices (see "Specifying workstation parameters (the Workstation action bar choice)" on page 58 for more information):

1 **Workstation connection** Displays the Initiate GUI Session panel.

2 **GUI panel settings** Displays the GUI Settings panel.
3 **Workstation Tool Integration** Displays the tool integration panel.
4 **Download ISPF C/S Component** Displays the download panel.
5 **Disconnect from the Workstation** Disconnects from the workstation.

Identifier
The Identifier pull-down offers you these choices (see "Displaying message, system, user, panel, and screen IDs" on page 71 for more information):
1 **Message identifier** Displays the Message Identifier pop-up.
2 **Panel identifier** Displays the Panel Identifier pop-up.
3 **Screen Name** Displays the Screen Name pop-up.

Help
The Help pull-down provides general information about the options available in the Settings panel and action bar.

Specifying log and list defaults and characteristics (the Log/List action bar choice)

The Log/List pull-down on the ISPF Settings panel action bar allows you to specify the log and list data set defaults that are used when you terminate ISPF by issuing the RETURN or END command or by entering an `X` on the ISPF Primary Option Menu.

The defaults can also be used when you issue the LOG or LIST command. You may specify the characteristics of the records to be contained in the list data set when it is defined.

Log data set defaults

When you select "Log Data set defaults" from the Log/List pull-down on the ISPF Settings panel action bar, the panel shown in Figure 26 is displayed.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
─ ──────────────────────────── ISPF Settings ──────────────────────────── ──
  │                        Log Data Set Defaults
  │                                                          More:     +    +
0 │ Process option . . . . _  1. Print data set and delete
  │                           2. Delete data set (without printing)
  │                           3. Keep data set (append subsequent
  │                              information to same data set)
  │                           4. Keep data set and allocate new data set
  │ Batch SYSOUT class . . _______________
  │ Local printer ID or
  │ writer-name  . . . . . ________________
  │ Local SYSOUT class . . _______________
  │ Lines per page . . . . 60
  │ Primary pages  . . . . 10
  │ Secondary pages  . . . 10
  │ Log Message ID . . . . _  (/ = Yes)
  │  F1=Help       F2=Split     F3=Exit       F7=Backward   F8=Forward
T │  F9=Swap      F12=Cancel
  ──────────────────────────────────────────────────────────────────────

Command ===> LOGDSD
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 26. Log Data Set Defaults panel (ISPISML1)

Local printer ID or writer name
Enter the name that your installation has assigned to an IBM 328x type of printer or the name of the external writer program. The default is blank. If you enter a name in this field, be sure to leave the Batch SYSOUT class field empty.

Lines per page
ISPF uses this value to determine when to cause a page eject if the eject control is not provided by the dialog; for example, when the dialog issues a LIST service request without the CC keyword specified.

Lines per page can range from 1 to 999. The initial default is 60. Normal values for lines per page are:
60 When printing 6 lines per inch
80 When printing 8 lines per inch.

Primary/Secondary pages
Primary/secondary allocation parameters are specified in terms of the anticipated number of pages of printout. These values are automatically converted by ISPF to the appropriate number of blocks before allocating space for the log data set. The initial default setting is 100 for both Primary pages and Secondary pages.

Specify a primary allocation of zero to prevent allocation and generation of the log.

If you modify the primary/secondary allocation parameters after the data set has been allocated, the new values take effect the next time you start ISPF. The log data set is allocated the first time you perform some action that results in a log message, such as saving edited data or submitting a batch job.

Log Message ID
If you select the Log Message ID option, the message ID is automatically added to the long message text written in the LOG data set.

If you request default processing options for the log data set, these rules apply:

- If you specify Print data set and delete (1), you must also specify a Batch SYSOUT class and job statement information. If you specify Print data set and delete for both log and list, you can specify different Batch SYSOUT classes, but only one job is submitted for printing both data sets.
- If you specify routing to a local printer, you must specify a Local printer ID or writer name, and Batch SYSOUT must be blank. You can also enter a Local SYSOUT class if one is defined.

If you do not follow these rules or do not specify default processing options, primary option X or the RETURN command causes the final termination panel to be displayed.

List data set defaults

When you select “List Data set defaults” from the Log/List pull-down on the ISPF Settings panel action bar, the pop-up shown in Figure 27 on page 34 is displayed.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
─ ┌──────────────────────────── ISPF Settings ────────────────────────────┐ ──
  │                          List Data Set Defaults                       │
                                                                            +
0 │ Process option . . . . _  1. Print data set and delete                 │
  │                           2. Delete data set (without printing)        │
  │                           3. Keep data set (append subsequent          │
  │                              information to same data set)             │
  │                           4. Keep data set and allocate new data set   │
  │ Batch SYSOUT class . . ______________                                  │
  │ Local printer ID or                                                    │
  │ writer-name  . . . . . _________________                               │
  │ Local SYSOUT class . . ______________                                  │
  │ Lines per page . . . . 60                                              │
  │ Primary pages  . . . . 100                                             │
  │ Secondary pages  . . . 200                                             │
  │                                                                        │
  │  F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward    │
T │  F9=Swap      F12=Cancel                                               │
  └────────────────────────────────────────────────────────────────────────┘

Command ===> LISTDSD
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 27. List Data Set Defaults panel (ISPISML2)

Local printer ID
Enter the name that your installation has assigned to an IBM 328x type of printer or the name of the external writer program. The default is blank. If you enter a name in this field, be sure to leave the Batch SYSOUT class field empty.

Lines per page
ISPF uses this value to determine when to cause a page eject if the eject control is not provided by the dialog; for example, when the dialog issues a LIST service request without the CC keyword specified.

Lines per page can range from 1 to 999. The initial default is 60. Normal values for lines per page are:
60 When printing 6 lines per inch
80 When printing 8 lines per inch.

Primary/Secondary pages
Primary/secondary allocation parameters are specified in terms of the anticipated number of pages of printout. These values are automatically converted by ISPF to the appropriate number of blocks before allocating space for the list data set. The initial default settings are 100 for Primary pages and 200 for Secondary pages.

If you modify the primary/secondary allocation parameters after the data set has been allocated, the new values take effect the next time you enter ISPF. The list data set is allocated the first time you request a print function or a dialog issues a LIST service request.

If you request default processing options for the list data set, these rules apply:

- If you specify Print data set and delete (1), you must also specify a Batch SYSOUT class and job statement information. If you specify Print data set and delete for both log and list, you can specify different Batch SYSOUT classes, but only one job is submitted for printing both data sets.

- If you specify routing to a local printer, you must specify a Local printer ID or writer name, and Batch SYSOUT must be blank.

If you do not follow these rules or do not specify default processing options, primary option X or the RETURN command causes the final termination panel to be displayed.

After reviewing or changing the parameters on this panel, enter the END command to return to the previous menu.

List data set characteristics

When you select "List Data set characteristics" from the Log/List pull-down on the ISPF Settings panel action bar, the panel shown in Figure 28 is displayed to allow you to specify the characteristics of the records to be contained in the list data set when it is defined. You can specify the record format, the logical record length, and the line length to be printed. When the characteristics are reset, their new values take effect at once unless the list data set has already been allocated. In that case, the new values are used for the next list data set allocation. These values are saved in your user profile, which ISPF automatically builds and maintains across sessions.

Specifications for logical record length and line length values can affect truncation of lines written to the list data set by a LIST service request. See the description of the LIST service in *z/OS ISPF Services Guide* for more information.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
— ┌──────────────── ISPF Settings ────────────────┐ ──────────────────────────────
  │     List Data Set Characteristics             │
  │                                               │                       More:     +
0 │ Record Format . . . . . . 1  1. FBA          │ t Graphics
  │                              2. VBA           │ mily printer type 2
  │ Logical record length . . 121                 │ vice name . . . .
  │ Line length . . . . . . . 120                 │ pect ratio  . . . 0
  │                                               │
  │                                               │
  │  F1=Help      F2=Split     F3=Exit            │ ral
  │  F7=Backward  F8=Forward   F9=Swap            │ put field pad . . B
  └───────────────────────────────────────────────┘ mmand delimiter . ;
  /  Jump from leader dots
     Edit PRINTDS Command
  /  Always show split line
     Enable EURO sign
  /  Scroll member list

Terminal Characteristics
  Screen format   2  1. Data    2. Std     3. Max     4. Part
Command ===> LISTDSC
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 28. List Data Set Characteristics panel (ISPISML3)

The fields on this panel are described here:

Record Format

The record format specifies the format and characteristics of the records in the list data set. The allowable record formats are:

FBA Fixed-length records that contain ANSI-defined printer control characters

VBA Variable-length records that contain ANSI-defined printer control characters.

The default setting is FBA.

Logical Record Length
The logical record length specifies the length, in bytes, of fixed-length records or the maximum length allowed for variable-length records. The default value is 121. This value represents one ANSI-defined control character and 120 bytes of data to be printed.

Line Length
The line length specifies the length of the logical line to be printed. If the specified line length is greater than the logical record length of the list data set, data is truncated. The range of allowable lengths is from 80 bytes to 160 bytes. The default value is 120.

The information supplied by the parameters allows for the printing of panels whose line lengths would not otherwise be supported by the available printing facilities.

For example:

- If a panel to be printed is 160 bytes wide but printing capabilities allow only 132 bytes, you should specify:
  RECFM FBA or VBA
  Line Length 130
  LRECL 132 (allows for two ANSI-defined control characters).

  The first page of output would contain the first 130 bytes of the panel. The second page would contain the last 30 bytes. This technique is referred to as the *cut and paste* method of printing.
- If a panel to be printed is 132 bytes wide and the printer supports this line length, you should specify:
  RECFM FBA or VBA
  Line Length 132
  LRECL 133 (allows for one ANSI-defined control character).

  The entire panel would be printed on one page of output.
- If a panel to be printed is 80 bytes wide, ISPF uses the default values for the LIST parameters. The entire panel would be printed on one page of output.

JCL

When you select JCL from the Log/List pull-down on the ISPF Settings panel action bar, the pop-up shown in Figure 29 on page 37 is displayed. You can specify up to four default job statements to be used when printing a log or list data set.

```
 Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ──────────────────────────────── ISPF Settings ────────────────────────────────
                                 Log and List JCL

 Job statement information:       (Required for system printer)
 ____________________________________________________________________________
 ____________________________________________________________________________
 ____________________________________________________________________________
 ____________________________________________________________________________

  F1=Help     F2=Split    F3=Exit     F9=Swap    F12=Cancel

    Session Manager mode                  Command delimiter . ;

⋮
```

Figure 29. Log and List JCL panel (ISPISMLJ)

Working with function keys and keylists (the Function Keys action bar choice)

The Function keys pull-down on the ISPF Settings panel action bar (see Figure 30 on page 39) allows you to define function keys and to create, edit, delete, and view keylists.

Nearly all panels in ISPF have associated keylists, although specific keylists typically serve numerous panels. There are several keylists used in the ISPF product panels. These keylists all start with the characters ISR. In addition, ISPF contains some keylists that start with the characters ISP. They are not used in any ISPF product panels, but can be used by an application if needed. Keylists are used when an application panel contains a)PANEL statement.

To accommodate both users who require CUA-compliant keylists and those who prefer to use the traditional ISPF function key assignments, F1-F12 are assigned CUA-compliant values, and F13-F24 are assigned traditional ISPF values. Therefore, the user who runs in default mode (ZPRIKEYS set to UPP; also see "Tailor function key definition display" on page 48) can retain the traditional key settings.

Note: Function keys in Edit are documented in *z/OS ISPF Edit and Edit Macros*. They are not CUA-compliant.

The KEYS and KEYLIST commands have been modified to benefit the user as well. When KEYS is issued from a panel that is not using a keylist, the PF Key Definitions and Labels panel is displayed, which allows you to change the ZPF variable settings, as in previous versions of ISPF. However, if the keys command is issued from a panel with an *active* keylist, the associated Keylist Utility panel Change panel is displayed.

The user can also control the use of keylists associated with panels using the KEYLIST command. Specifying KEYLIST OFF causes ISPF to ignore the keylist in all logical screens running under the application ID from which the KEYLIST OFF command was issued, and to use the ZPF variables for controlling function keys. The KEYLIST ON command (the default) causes ISPF to recognize the preeminence

of keylists again. KEYLIST ON and OFF are equivalent to the Enable and Disable keylist choices on the Function keys pull-downs discussed in “Keylist settings” on page 42.

ISPF default keylist

ISPKYLST is the ISPF default keylist. If you do not specify a keylist to be associated with a panel using the KEYLIST attribute on the PANEL tag (DTL) or using the)PANEL statement, ISPF uses the keys defined for ISPKYLST to display in the function area of the panel when it is displayed. The key settings and forms for ISPKYLST are as shown in Table 3.

Table 3. ISPKYLST key settings

Key	Command	Form
F1	HELP	Short
F2	SPLIT	Long
F3	EXIT	Short
F9	SWAP	Long
F12	CANCEL	Short
F13	HELP	Short
F14	SPLIT	Long
F15	EXIT	Short
F21	SWAP	Long
F24	CANCEL	Short

ISPF default keylist for help panels

You can specify a keylist to be associated with a help panel by using the keylist attribute on the HELP tag (DTL) or by using a)PANEL statement in your panel definition. If you do not specify a keylist, ISPF uses the keys defined for ISPHELP to display in the function area of the help panel when it is displayed. The key settings and forms for ISPHELP are shown in Table 4.

Table 4. ISPHELP key settings

Key	Command	Form
F1	HELP	Short
F2	SPLIT	Long
F3	EXIT	Short
F5	EXHELP	Short
F6	KEYSHELP	Short
F7	UP	Long
F8	DOWN	Long
F9	SWAP	Long
F10	LEFT	Long
F11	RIGHT	Long
F12	CANCEL	Short

Figure 30 on page 39 shows the Function keys pull-down on the ISPF Settings panel action bar. Each pull-down choice is described following the panel.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ________ ┌──────────────────────────────┐ ──────────────────────────────
          │__ 1. Non-Keylist PF Key settings│
          │   2. Keylist settings...        │                    More:     +
Options   │   3. Tailor function key display│ Graphics
  Enter " │   *. Show all function keys     │ ly printer type 2
  /  Comm │   5. Show partial function keys │ ce name . . . .
  /  Pane │   6. Remove function key display│ ct ratio  . . . 0
  /  Long │   *. Use private and shared     │
  /  Tab  │   8. Use only shared            │
     Tab  │   9. Disable keylists           │ l
  /  Rest │  *0. Enable keylists            │ t field pad . . B
     Sess └──────────────────────────────┘ and delimiter . ;
  /  Jump from leader dots
     Edit PRINTDS Command
  /  Always show split line
     Enable EURO sign
  /  Scroll member list

Terminal Characteristics
  Screen format   2  1. Data    2. Std     3. Max     4. Part
Command ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 30. Function keys pull-down on the ISPF settings panel action bar (ISPISMMN)

Non-keylist PF key settings

When you select Non-Keylist PF key settings from the Function keys pull-down on the ISPF Settings panel action bar, the PF Key Definitions and Labels panel shown in Figure 31 on page 40 is displayed. If you enter the KEYS command on the command line of any panel, the system displays one of two panels:

- If you are not using keylists (that is, keylists are disabled) or if there is no keylist associated with the panel from which you enter the KEYS command, the PF Key Definitions and Labels panel shown in Figure 31 on page 40 is displayed.
- If you are using keylists (that is, keylists are enabled) and there is a keylist associated with the panel from which you enter the KEYS command, the Keylist Change panel shown in Figure 36 on page 46 is displayed.

If you define your application panels using panel definition statements, use the PF Key Definitions and Labels - Primary Keys panel shown in Figure 31 to assign function keys and associated labels to ISPF commands.

Note: See “Keylist settings” on page 42 to find out how to assign function keys that are associated with a keylist.

```
                        PF Key Definitions and Labels
                                                                  More:     +
Number of PF Keys . . . 12                        Terminal type  . : 3278

PF1 . . . HELP
PF2 . . . SPLIT
PF3 . . . END
PF4 . . . RETURN
PF5 . . . RFIND
PF6 . . . RCHANGE
PF7 . . . UP
PF8 . . . DOWN
PF9 . . . SWAP
PF10  . . LEFT
PF11  . . RIGHT
PF12  . . RETRIEVE

PF1  label  . . ________   PF2  label  . . ________   PF3  label  . . ________
PF4  label  . . ________   PF5  label  . . ________   PF6  label  . . ________
PF7  label  . . ________   PF8  label  . . ________   PF9  label  . . ________
PF10 label  . . ________   PF11 label  . . ________   PF12 label  . . ________

Press ENTER key to display alternate keys. Enter END command to exit.
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 31. PF Key Definitions and Labels panel (ISPOPT3D)

Note: The panel in Figure 31 is displayed for terminals with 12 function keys. For terminals with 24 function keys, the first panel displayed shows the *primary* keys (F1-F12). When you press the Enter key, ISPF displays a panel showing the *alternate* keys (F13-F24). To alternate between the two panels, press the Enter key.

You can assign function keys to system commands, such as HELP or END, to commands that are meaningful within a particular function or environment, such as the Edit FIND and CHANGE commands, and to line commands, such as the Edit or dialog test I or D commands.

Before changing function key assignments, verify the terminal type selected on the ISPF Settings panel and the number of function keys (12 or 24). For a list of valid terminal types refer to Figure 22 on page 23.

You can define or change a function key function simply by equating the key to a command. For example:

```
PF9 . . . CHANGE ALL ABC XYZ
PF12  . . PRINT
```

In the example, F9 has been equated to an Edit command, and F12 has been equated to the system-defined PRINT command.

If you enter a blank for any function key definition, the key is restored to its ISPF default.

A function key definition beginning with a colon (:) is treated as a special case. The colon is stripped off, and the command to which the key is equated is inserted in the first input field on the line at which the cursor is currently positioned.

A function key definition beginning with a greater-than sign (>) is another special case. It causes the command to be passed to the dialog, regardless of whether the command appears in the command tables. When an ISPF function is executing, do not press the RESET key and then attempt to enter information or use a function key, because the results are unpredictable.

The label fields shown in Figure 31 on page 40 allow you to specify user-defined labels for the displayed representations of function key definitions. This provides for displaying meaningful words of eight characters or fewer, rather than the first eight, possibly meaningless, characters of a lengthy function key definition.

If a label is not assigned, the definitions displayed for that function key consist of the first eight characters of the function key definition.

If the label value is BLANK, the function key number and the equal sign display, but the value portion of that function key definition displays as actual blanks. This label might be used if, for example, a function key is not defined or if it is meaningless to the user, but the dialog developer wants each function key number to appear sequentially in the function key definition lines.

No function key information, not even the number, appears if the label value for that key is NOSHOW.

Figure 32 shows how the function key panel can be used to assign definitions and labels. In this example, F4 has been equated to a TSO data management command, while F12 has been equated to a command that requests job submission. Labels for several function keys are defined as well.

```
                        PF Key Definitions and Labels
                                                                  More:     +
Number of PF Keys . . . 24                        Terminal type  . : 3278

PF1 . . . HELP
PF2 . . . SPLIT
PF3 . . . END
PF4 . . . TSO LISTALC ST
PF5 . . . RFIND
PF6 . . . RCHANGE
PF7 . . . UP
PF8 . . . DOWN
PF9 . . . SWAP
PF10  . . LEFT
PF11  . . RIGHT
PF12  . . TSO SUBMIT NOTIFY

PF1  label  . . ________  PF2  label  . . BLANK     PF3  label  . . ________
PF4  label  . . DATASETS  PF5  label  . . FIND      PF6  label  . . CHANGE
PF7  label  . . NOSHOW    PF8  label  . . NOSHOW    PF9  label  . . ________
PF10 label  . . ________  PF11 label  . . ________  PF12 label  . . SUBMIT

Press ENTER key to display alternate keys. Enter END command to exit.
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 32. Using the PF Key Definitions and Labels panel (ISPOPT3E)

Figure 33 shows the function key settings that are displayed on a panel when defined using the key definitions and labels in Figure 32.

```
------------------------- EMPLOYEE SERIAL -------------- DUPLICATE NUMBER
COMMAND ===>

ENTER EMPLOYEE SERIAL BELOW:




   EMPLOYEE SERIAL ==> 598304       (MUST BE 6 NUMERIC DIGITS)



PRESS ENTER TO DISPLAY NEXT SCREEN FOR ENTRY OF EMPLOYEE DATA.

PRESS END KEY (PF3) TO END THIS SESSION.





 F1=HELP      F2=          F3=END       F4=DATASETS   F5=FIND   F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 33. Example screen with function key definition lines

Keylist settings

To create or change a keylist associated with your panels, or to refer to or delete a keylist help panel from your keylist, select the “ Keylist settings” choice from the Function keys pull-down on the ISPF Settings panel action bar, or enter the KEYLIST command. The first panel displayed is similar to Figure 34 on page 43. If you Enter the KEYS command from a panel that uses a keylist, the keylist change panel for the keylist active on the original panel is displayed.

```
                              Keylist Utility
 File  View
 ------------------------------------------------------------------------
                     Keylist Utility for ISR        Row 1 to 11 of 16

Actions:   N=New  E=Edit  V=View  D=Delete  /=None

  Keylist   Type
  ISRHELP   SHARED
  ISRHLP2   SHARED
  ISRNAB    SHARED
  ISRNSAB   SHARED
  ISRREFL   SHARED
  ISRREFO   SHARED
  ISRSAB    SHARED    *** Currently active keylist ***
  ISRSCRVT  SHARED
  ISRSLAPP  SHARED
  ISRSNAB   SHARED
  ISRSPBC   SHARED

Command ===> ___________________________________ Scroll ===> PAGE
 F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
 F9=Swap      F10=Actions   F12=Cancel
```

Figure 34. Keylist Utility panel (ISPKLUP)

In Figure 34, ISPHELP, ISPHLP2, ISPNAB, ISPSAB, ISPSNAB, ISPTEST, ISRHELP, ISRNAB, and ISRNSAB have already been created for application ISR. ISPSAB, the currently active keylist, and ISPSNAB are keylists for the keylist utility panels. ISPKYLST is the ISPF default keylist for any DTL application panel or any panel defined with a)PANEL section that does not have a keylist defined. ISPHELP is the ISPF keylist for help panels created using DTL or using a)PANEL section.

The application ID is shown on the title line of the panel (ISR in Figure 34) and defaults to the application ID of the keys table in which the keylist was found when the KEYLIST command was entered. You can specify the keylist application ID on the)PANEL statement, or, if using DTL, it can be specified when you call the ISPF conversion utility using the KEYLAPPL option on the ISPDTLC command. If the panel does not specify an application ID, ISPF searches the currently executing application's keys table for a keylist that has the same name as the name specified on the PANEL tag. If the keylist is not found, and the current application ID is not ISP, ISPF searches the ISP application.

The column marked Type indicates whether a keylist is shared or is a private copy. For information about the KEYLIST SHARED and KEYLIST PRIVATE system commands, see the topic about Using Commands, Function Keys, and Light Pen or Cursor Selection in the *z/OS ISPF User's Guide Vol I*. Shared keylists are created by the ISPF DTL Conversion Utility. They cannot be deleted by the keylist utility. If a shared keylist is modified by the keylist utility, it is saved as a private keylist copy in a table named *xxxx*PROF, where *xxxx* is the application ID. The keylist utility now shows the keylist as a private copy. If you have issued the KEYLIST SHARED command, you can still modify a keylist, but you cannot see the changes reflected in the function keys until the KEYLIST PRIVATE command is issued.

Note: The keylist utility is meant for users to modify function keys for their own use. To define function keys for all users of an application or for site-wide use, the definitions in the Dialog Tag Language should be modified and a new *xxxx*KEYS table should be generated.

The Keylist Utility panel action bar choices function as follows:

File Allows you to create a new keylist, to edit, view, or delete existing keylists, or to exit the keylist utility.

View Enables you to display another set of keylists. These options are described in "View pull-down" on page 48.

File pull-down: To create, edit, view, or delete a keylist, use either of these methods:

- Use a slash in the Select column to select a keylist from those displayed, then select the appropriate choice from the File pull-down.
- Select a keylist from those displayed using one of these actions: N(New), E(Edit), V(View), or D(Delete). If you use N(New), you are prompted for the name of the keylist you are about to create.

The choices on the File pull-down function as follows:

New To create a keylist, enter the keylist name when prompted. You are prompted after selecting New from the File pull-down, or after typing N next to any displayed keylist and pressing Enter. The screen shown in Figure 35 is displayed.

```
                              Keylist Utility
  File  Defaults
 ------------------------------------------------------------------------
                        ISR Keylist SAMPLE1 Create        Row 1 to 9 of 24

 Make changes and then select File action bar choice.

 Keylist Help Panel Name . . . ________

 Key       Definition                                  Format  Label
 F1 . . .  ________________________________________    _____   ________
 F2 . . .  ________________________________________    _____   ________
 F3 . . .  ________________________________________    _____   ________
 F4 . . .  ________________________________________    _____   ________
 F5 . . .  ________________________________________    _____   ________
 F6 . . .  ________________________________________    _____   ________
 F7 . . .  ________________________________________    _____   ________
 F8 . . .  ________________________________________    _____   ________
 F9 . . .  ________________________________________    _____   ________

 Command ===> ________________________________________ Scroll ===> PAGE
  F1=Help       F2=Split       F3=Exit        F7=Backward    F8=Forward
  F9=Swap       F10=Actions    F12=Cancel
```

Figure 35. Keylist Create panel (ISPKLUCR)

The Keylist Create panel action bar choices function as follows:

File The File pull-down offers these choices:

1 **Cancel**. Cancels the creation of this keylist and returns to the Keylist Utility panel.

2 **Save and Exit**. Saves the keylist and returns to the Keylist Utility panel.

Defaults
The Defaults pull-down offers you the choice of the five default

function key settings described in Table 5.

Table 5. Default key settings

Condition	Function key settings
No defaults	No values are filled in.
Non-scrollable, no action bar	F1 HELP F2 SPLIT F3 EXIT F9 SWAP F12 CANCEL
Scrollable, no action bar	F1 HELP F2 SPLIT F3 EXIT F7 BACKWARD F8 FORWARD F9 SWAP F12 CANCEL
Non-scrollable, with action bar	F1 HELP F2 SPLIT F3 EXIT F9 SWAP F10 ACTIONS F12 CANCEL
Scrollable, with action bar	F1 HELP F2 SPLIT F3 EXIT F7 BACKWARD F8 FORWARD F9 SWAP F10 ACTIONS F12 CANCEL

If you are creating a keylist on a terminal defined to have 24 keys, the 13-24 keys are set the same as the 1-12 keys. For example, F13 is automatically set the same as F1. HELP, EXIT, ACTIONS, and CANCEL all have display format SHORT. SPLIT, UP, DOWN, and SWAP have display format LONG.

Edit To edit the key definitions, display formats, and labels for a keylist, enter the keylist name when prompted. Select a keylist with a slash and select Edit from the File pull-down, or type E next to a keylist name and press Enter. The screen shown in Figure 36 on page 46 is displayed, showing the existing values.

```
                              Keylist Utility
  File
 ------------------------------------------------------------------------------
 SHARED                  ISR Keylist SAMPLE1 Change         Row 1 to 9 of 24

 Make changes and then select File action bar.

 Keylist Help Panel Name . . .

 Key       Definition                                  Format  Label
 F1 . . .  HELP                                        SHORT   Help
 F2 . . .  SPLIT                                       LONG    Split
 F3 . . .  EXIT                                        SHORT   Exit
 F4 . . .                                              ____    ________
 F5 . . .                                              ____    ________
 F6 . . .                                              ____    ________
 F7 . . .  UP                                          LONG    Backward
 F8 . . .  DOWN                                        LONG    Forward
 F9 . . .  SWAP                                        LONG    Swap

 Command ===>                                          Scroll ===> PAGE
  F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
  F9=Swap       F10=Actions    F12=Cancel
```

Figure 36. Keylist Change panel (ISPKLUCH)

The Keylist Change panel action bar choice functions as follows:

File The File pull-down offers these choices:

1 **Cancel**. Cancels the changes to this keylist and returns to the Keylist Utility panel.

2 **Save and Exit**. Saves the changes to this keylist and returns to the Keylist Utility panel or the panel from which you issued the KEYS command.

These fields appear on the Keylist Utility Change panel:

Row x to x of xx
Indicates that you must scroll the panel to access the remaining label definitions.

Keylist Help Panel Name
To refer to a help panel from this keylist, enter the help panel name in this field in this format:

- Must be 1-8 characters
- First, or only, character must be A-Z or a-z
- Remaining characters, if any, must be A-Z, a-z, 0-9

To remove a help panel name from a keylist, replace the help panel name with blanks.

Definition
If a display format or a label is specified, a definition must also be specified. Any definition is valid.

Format
The only valid display formats are:

LONG The default. Indicates that the key label should be displayed in the function key area when the FKA command is toggled to the first cycle after OFF.

SHORT Indicates that the key label should be displayed in

the function key area when the FKA command is toggled to the first or second cycle after OFF. A key will display more often in the function key area if it is given the SHORT display format.

NO Indicates that the key label should never be displayed in the function key area, regardless of the FKA command toggle cycle.

Label Any label is valid. If the Label field is left blank, it will default to the definition. This will happen only if the field is blank. If the Label field is not blank and the definition is changed, the Label field will not change automatically.

View To view a keylist, but not modify it, enter the keylist name when prompted. Select the keylist with a slash, then select View from the File pull-down, or type V next to the keylist name displayed and press Enter. The screen shown in Figure 37 is displayed.

```
                              Keylist Utility
SHARED                  ISR Keylist SAMPLE1 View          Row 1 to 11 of 24

The definition of the SAMPLE1 keylist is below.

Keylist Help Panel Name . . : ISPSAB

Key       Definition                                Format  Label
F1 . . .  HELP                                      SHORT   Help
F2 . . .  SPLIT                                     LONG    Split
F3 . . .  EXIT                                      SHORT   Exit
F4 . . .
F5 . . .
F6 . . .
F7 . . .  UP                                        LONG    Backward
F8 . . .  DOWN                                      LONG    Forward
F9 . . .  SWAP                                      LONG    Swap
F10  . .
F11  . .

Command ===> _____________________________________________ Scroll ===> PAGE
 F1=Help       F2=Split       F3=Exit        F7=Backward    F8=Forward
 F9=Swap       F12=Cancel
```

Figure 37. Keylist utility view panel (ISPKLUB)

If you select View, the help panel name, key definitions, display formats, and labels are displayed but cannot be changed.

Delete To delete a private copy of a keylist, enter the keylist name when prompted. Select the keylist with a slash, then select Delete from the File pull-down, or type D next to the keylist name displayed and press Enter. The Delete Keylist Confirmation pop-up shown in Figure 38 on page 48 is displayed.

Note: Shared keylists can only be deleted using the Dialog Tag Language.

```
                          Keylist Utility
  File  View
                  Keylist Utility
     Delete Keylist Confirmation        SR         Row 2 to 12 of 17
  Enter "/" to select option            e  /=View
  _  Confirm Delete of SAMPLE1

   F1=Help    F2=Split   F3=Exit
   F9=Swap   F12=Cancel

   Delete Warning
                     *** Currently active keylist ***
   ISRSCRVT  SHARED
   ISRSLAPP  SHARED
   ISRSNAB   SHARED
   ISRSPBC   SHARED

  Command ===>                                        Scroll ===> PAGE
   F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
   F9=Swap      F10=Actions   F12=Cancel
```

Figure 38. Keylist utility with delete keylist confirmation pop-up (ISPKLUP)

Use caution when deleting a keylist from an application that is currently running. If you delete a keylist that is required by a panel in the application, an error message appears and the panel does not display.

Exit Select Exit from the File pull-down to exit the keylist utility.

View pull-down: To display another set of keys on the Keylist Utility panel, select View on the action bar.

The View pull-down choices function as follows:

By current panel keylist
Displays the list of keys related to the current panel.

By current dialog keylist
Displays the list of keys related to the dialog that is currently running.

Specify a keylist application ID
Displays the list of keys for another application.

Tailor function key definition display

The Tailor Function Key Definition Display panel (shown in Figure 39 on page 49) allows you to change the format of the function key definition lines that are displayed at the bottom of the screen. To display this panel, perform one of these actions:

- Select the “Tailor function key display” choice from the Function keys pull-down.
- Issue the PFSHOW TAILOR command from any command line.

```
                              ISPF Settings
                   Tailor Function Key Definition Display

 For all terminals:
   Number of keys  . . 2  1. 12
                          2. 24

   Keys per line . . . 1  1. Six
                          2. Maximum possible

   Primary range . . . 1  1. Lower - 1 to 12
                          2. Upper - 13 to 24

 For terminals with 24 PF keys:
   Display set . . . . 1  1. Primary - display keys 1 to 12
                          2. Alternate - display keys 13 to 24
                          3. All - display all keys

 Press ENTER key to save changes.  Enter END to save changes and exit.

 Command ===> ____________________________________________________________
  F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
  F9=Swap      F12=Cancel
```

Figure 39. Tailor Function Key Definition Display panel (ISPOPFA)

From the Tailor Function Key Definition Display panel you can set these function key parameters:

Number of keys

The number of function keys you specify controls the particular set of function key definitions currently in use.

ISPF automatically determines the terminal type, screen size, and number of function keys:

- If the screen size is greater than 24 lines, but the terminal type specified implies a maximum of 24 screen lines, ISPF sets the terminal type to 3278.
- If you press a function key higher than 12, but the value specified for the number of function keys on your terminal is 12, ISPF sets the terminal type to 3278 and the number of function keys to 24.

ISPF cannot determine the terminal type or number of function keys in these cases:

- If you switched between a 3277 and 3278 Model 2, both of which are 24-line terminals
- If you switched from a terminal with 24 function keys to a terminal with 12 function keys.

In these cases, you must inform ISPF of the terminal type and number of function keys you are using. Otherwise, ISPF uses an incorrect character set and invalid function key definitions.

ISPF automatically sets, or changes, the number of function keys in these cases:

- If you specify 3277, ISPF initializes the number of keys to 12.
- If you specify 3278, ISPF initializes the number of keys to whatever was stored from the user's last ISPF session. If no number is stored from a prior session, the number of keys is initialized to 12.

- If you press a function key higher than 12, ISPF sets the number of keys to 24. ISPF cannot set the number of keys to 24 for the 3278T terminal.

Keys per line
You can specify the number of keys per line to be displayed on the function key definition lines. Six or Maximum possible can be specified, indicating either six keys or the maximum possible keys. Six ensures consistency across all panels. Maximum possible can save space on crowded panels. The Maximum possible option is forced when you select the Panel display CUA mode option on the ISPF Settings panel.

Primary range
You can specify that the primary key range be:
Lower Primary keys are F1-F12.
Upper Primary Keys are F13-F24.

The default value is lower.

Display set
For terminals with 24 function keys, you can choose to display only the primary set of function keys (F1-F12, the default range), the alternate set of function keys (F13-24), or all 24 keys. Your display choices depend on which range you specify for the Primary range option. For terminals with 12 function keys, this setting is ignored.

The Function keys pull-down

The Function keys pull-down provides choices that enable you to display the function keys in various forms.

Choices for changing PF key definitions

You can change the PF Keys that you have defined by using one of the first three choices on the Function Keys pull-down. Choosing “Non-keylist PF Key settings” calls the PF Key Definitions and Labels panel, where you can assign PF keys to ISPF commands, and label them. This choice is like using the KEYS command.

Choosing “Keylist settings” from the pull-down is like using the KEYLIST command, and the “Tailor Function Key Display” choice calls up the Tailor Function Key Definition Display panel.

Choices for showing PF keys on the display screen

By selecting “Show all function keys”, “Show partial function keys”, or “Remove function key display”, you can specify that ISPF use the long form of function key display, the short form of function key display, or no function keys, respectively.

Each of these pull-down choices has an equivalent PFSHOW and FKA command associated with it. The commands operate as toggles; the pull-down choices become unavailable if they are the current setting.

Table 6 on page 50 explains the relationship between the pull-down choices and their related command combinations.

Table 6. Displaying forms of the function keys

Pull-down Choice	Command Equivalent	Result
Show all function keys	PFSHOW PFSHOW ON FKA FKA ON	Long setting; all available function keys displayed. This is the default setting.

Table 6. Displaying forms of the function keys (continued)

Pull-down Choice	Command Equivalent	Result
Show partial function keys	PFSHOW (second time issued) FKA (second time issued) FKA SHORT*	Short setting; a partial listing of the function keys displayed.
Remove function key display	PFSHOW (third time issued) PFSHOW OFF FKA (third time issued) FKA OFF	No function keys displayed. If PFSHOW or FKA is issued for a fourth time, the display returns to the long, or ON, setting.
Note: * The FKA SHORT command can be issued at any time to invoke the short setting.		

Choices for determining who can use your PF keylist

The Function keys pull-down has two choices that are equivalent to the KEYLIST PRIVATE and KEYLIST SHARED commands:

Use private and shared
: Causes ISPF to use the keylist defined as private (equivalent to the KEYLIST PRIVATE command). Private is the default. It is unavailable if it is the current setting.

Use only shared
: Causes ISPF to use the keylist defined as shared (equivalent to KEYLIST SHARED). It is unavailable if it is the current setting.

Choices for enabling keylists

The Function keys pull-down has two choices that are equivalent to the KEYLIST ON and KEYLIST OFF commands:

Enable keylists
: Causes ISPF to use the keylist defined with the panel (equivalent to the KEYLIST ON command). Enable keylists is the default. It is unavailable if it is the current setting.

Disable keylists
: Causes ISPF to ignore the keylist defined with the panel (equivalent to KEYLIST OFF). It is unavailable if it is the current setting.

Changing default colors (the Colors action bar choice)

The Colors pull-down on the ISPF Settings action bar provides access to the Global Color Change Utility, the ISPF CUA Attribute Change Utility, and the Point-and-shoot Color Change panel. In GUI mode, the choice starts the Global GUI Color Change Utility.

Global colors

For ISPF-supported seven-color terminals, ISPF provides the Global Color Change Utility (on the host) and the Global GUI Color Change Utility (on the workstation) to allow you to globally change the current colors ISPF uses for display.

To invoke the utility appropriate for your environment, perform one of these actions:

- Select the Global colors... choice from the Colors pull-down.
- Issue the ISPF system command COLOR from any ISPF command line.

ISPF displays the Global Color Change Utility panel shown in Figure 40 if you are running in host mode; it displays the Global GUI Color Change Utility panel shown in Figure 41 on page 53 if you are running in GUI mode.

Global color change utility: From the panel shown in Figure 40, you can change the ISPF-defined default colors.

```
                          ISPF Settings                                Help
 —                  Global Color Change Utility                    ___________

    Globally change one or more of the ISPF default colors and      More:     +
 O  press ENTER to immediately see the effect. Clearing a color
    field and pressing ENTER restores the default color or
    selecting the Defaults point-and-shoot field restores all
    default colors.

    Enter the EXIT command to save changes or enter the CANCEL
    command to exit without saving.

    ISPF Default Color
      Blue  . . . . _______
      Red . . . . . _______
      Pink  . . . . _______
      Green . . . . _______
      Turquoise . . _______
 T    Yellow  . . . _______
      White . . . . _______
    Command ===> ___________________________________ Defaults
 C   F1=Help       F2=Split       F3=Exit        F7=Backward
     F8=Forward    F9=Swap       F12=Cancel                      9=Swap
 F
```

Figure 40. Global Color Change Utility panel (ISPOPT10)

Enter a new value in the color field beside the ISPF-defined default color to be changed. The valid color choices are RED, PINK, GREEN, YELLOW, BLUE, TURQ, and WHITE.

Color changes are reflected on the panel display immediately after you press Enter. For example, if you type BLUE in the field next to RED and press Enter, any panel element attributes defined as red change to blue.

You can restore an ISPF-defined color to its default value by setting its field to blank and pressing Enter. To restore all the ISPF-defined colors to their default values, select the Defaults point-and-shoot field at the end of the command line.

The EXIT command ends the Global Color Change Utility function and saves global color changes in the ISPSPROF system profile table. The CANCEL command ends the Global Color Change Utility function and restores the global color definitions as they were before the utility was invoked.

Changes to the globally defined colors affect all logical screens whether they are displayed directly by ISPF or whether ISPF has requested that GDDM perform the display. Line mode output, fields, and graphics that the dialog has placed on the screen using direct calls to GDDM are not affected by global color changes.

Global GUI color change utility: If you have set up the GUI interface, you can change its colors. From the Global GUI Color Change Utility panel shown in Figure 41, you can map each of the seven host colors to one of 16 workstation colors:

Host Colors	Workstation Colors
Red	Black
Pink	Dark blue
Green	Dark green
Yellow	Dark cyan
Blue	Dark red
Turq (turquoise)	Dark magenta
White	Brown
	Light gray
	Dark gray
	Light blue
	Light green
	Light cyan
	Light red
	Light magenta
	Yellow
	White

Choose colors that contrast with the panel background so that the text can be read easily.



Figure 41. Global GUI color change utility panel (ISPOPTG1)

This panel provides three options for mapping host colors:

1. **Host colors for all panel fields**. Any colors that you remap affect all panel fields.
2. **Host colors for non-CUA attributes only**. Any colors that you remap affect only panel fields with non-CUA attributes.
3. **Workstation default colors for all panel fields**. Remapping colors will have no effect.

The display will reflect any color changes made immediately when you press Enter.

Note: If a field uses a non-CUA attribute without a color specified, ISPF does not specify a color for the field and the field defaults to the 3270 default color on the host. That same field defaults to the workstation default color when it is displayed on the workstation, even if "Host colors for all panel fields" is selected.

Remapping host colors: From the Global GUI Color Change Utility panel, select a drop-down list button corresponding to one of the seven host colors, and ISPF displays the drop-down list on the panel, as shown in Figure 42.



Figure 42. Color change panel with drop-down list

From the drop-down list, select one of the 16 workstation colors to map to the host color you selected. For example, if you select the workstation color light magenta to map to the host color red, any panel element attributes defined as red change to light magenta on the next display.

The EXIT command terminates the Global GUI Color Change Utility and saves any global color changes in the ISPSPROF system profile table. The CANCEL command terminates the Global GUI Color Change Utility and restores the global color definitions to the values that were in effect before the utility was invoked.

Changes to the globally defined colors affect all logical screens. Background panels and split screen panels are not immediately affected; the color change does not occur until the panels are redisplayed.

CUA cttributes

ISPF provides the CUA Attribute Change Utility to allow you to change the default values of panel colors, intensities, and highlights for panel element attributes. See the *z/OS ISPF Dialog Developer's Guide and Reference* for a description of TYPE values for CUA panel element attributes.

To invoke the ISPF CUA Attribute Change Utility, perform one of these actions:
- Select the CUA attributes... choice from the Colors pull-down.
- Issue the ISPF system command CUAATTR from any ISPF command line.

The CUA Attribute Change Utility panel shown in Figure 43 is displayed. This is a scrollable panel that contains the current values for CUA panel element attribute colors, intensities, and highlights.

```
                              ISPF Settings
                        CUA Attribute Change Utility

 Change colors, intensities, or highlights for panel attribute elements.
 Enter the EXIT command to save changes or enter the CANCEL command to exit
 without saving. To restore the defaults for a type, clear the field and
 press Enter or select the Defaults point-and-shoot field to restore all
 default settings for all types.

 Panel Element                  Color         Intensity  Highlight
                                                                More:     +
 AB Selected Choice . . . . . . YELLOW        LOW        NONE
 AB Separator Line  . . . . . . BLUE          LOW        NONE
 AB Unselected Choice . . . . . WHITE         HIGH       NONE
 Action Message Text  . . . . . RED           HIGH       NONE
 Active Window Frame  . . . . . BLUE          HIGH
 Caution Text . . . . . . . . . YELLOW        HIGH       NONE
 Choice Entry Field . . . . . . TURQ          LOW        USCORE
 Column Heading . . . . . . . . BLUE          HIGH       NONE
 Descriptive Text . . . . . . . GREEN         LOW        NONE
 Command ===>                                                     Defaults
  F1=Help       F2=Split       F3=Exit        F7=Backward    F8=Forward
  F9=Swap       F12=Cancel
```

Figure 43. CUA Attribute Change Utility panel (ISPOPT11)

You can change the default values by typing over the existing values in the table with new values. Table 7 on page 55 shows valid change values:

You can restore an attribute to its default value by setting its field to blank and pressing Enter. To restore all the attributes to their default values, select the Defaults point-and-shoot field at the end of the command line.

Table 7. Valid CUA attribute change values

Color Choices	Intensity Choices	Highlight Choices
RED	HIGH	NONE
PINK	LOW	BLINK
GREEN		REVERSE
YELLOW		USCORE
BLUE		
TURQ		
WHITE		

In the CUA Attribute Change Utility table, if a field is left blank and Enter is pressed, the field defaults to the ISPF provided CUA-defined default value. Changes made to AB Selected Choice, AB Unselected Choice, Action Message Text, Function Keys, Informational Message Text, and Warning Message Text take effect immediately. Changes to other panel elements are reflected in the next panel display. The values of the panel colors, intensities, and highlights are saved across

ISPF invocations in your ISPF system profile table, ISPSPROF. The changes to the panel element values affect all logical screens.

The CUA Attribute Change Utility affects only ISPF's CUA-defined attribute keywords. For example, the CUA Attribute Change Utility does not override this panel element attribute:

```
% TYPE(OUTPUT) COLOR(RED)
```

Color changes made using the ISPF Global Color Change Utility override changes made using the ISPF CUA Attribute Change Utility. For example, you can use the Global Color Change Utility and change red to blue. You might then use the CUA Attribute Change Utility and change normal text to red. Normal text will display as blue.

The ISPF-supported CUA-defined default values for the panel element attributes are listed in *z/OS ISPF Dialog Developer's Guide and Reference*.

Point-and-shoot

The Point-and-Shoot panel element on the CUA Attribute Change Utility panel (shown in Figure 44) allows you to adjust the color, intensity and highlighting of point-and-shoot fields.

See the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I* for information on the point-and-shoot feature.

To display this panel, positioned on the Point-and-Shoot panel element, perform one of these actions:

- Select the Point-and-Shoot... choice from the Colors pull-down.
- Issue the ISPF system command PSCOLOR from any ISPF command line.

```
                              ISPF Settings
                        CUA Attribute Change Utility

 Change colors, intensities, or highlights for panel attribute elements.
 Enter the EXIT command to save changes or enter the CANCEL command to exit
 without saving. To restore the defaults for a type, clear the field and
 press Enter or select the Defaults point-and-shoot field to restore all
 default settings for all types.

 Panel Element                  Color         Intensity  Highlight
                                                                More:   -
 PD Unavailable Choices . . . . BLUE          LOW        NONE
 Reference Phrase . . . . . . . WHITE         HIGH       NONE
 Scroll Information . . . . . . WHITE         HIGH       NONE
 Sel. Available Choices . . . . WHITE         LOW        NONE
 Sel. Unavailable Choices . . . BLUE          LOW        NONE
 Variable Output Info.  . . . . TURQ          LOW        NONE
 Warning Message Text . . . . . YELLOW        HIGH       NONE
 Warning Text . . . . . . . . . RED           HIGH       NONE
 Work Area Separator Line . . . BLUE          LOW        NONE
 Command ===> ____________________________________________________ Defaults
  F1=Help       F2=Split       F3=Exit        F7=Backward    F8=Forward
  F9=Swap      F12=Cancel
```

Figure 44. CUA Attribute Change Utility panel positioned on the point-and-shoot panel element (ISPOPT1X)

To change any of the three attributes, type over the existing values. The changes are reflected on the next panel displayed after you exit this panel. Table 8 shows valid change values:

Table 8. Valid point-and-shoot change values

Color Choices	Intensity Choices	Highlight Choices
RED	HIGH	NONE
PINK	LOW	BLINK
GREEN		REVERSE
YELLOW		USCORE
BLUE		
TURQ		
WHITE		

Specifying ISPF ENVIRON settings (the Environ action bar choice)

Figure 45 shows the ISPF ENVIRON Command Settings panel from which you can choose parameter options for the ENVIRON command. To display this panel, perform one of these actions:

- Select the Environ choice on the ISPF Settings panel action bar, then select option 1, "Environ settings...".
- Issue the ISPF system command ENVIRON from any ISPF command line.

```
 Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ──────────────────────────────── ISPF Settings ────────────────────────────
                        ISPF ENVIRON Command Settings

 Enter "/" to select option
 _  Enable a dump for a subtask abend when not in ISPF TEST mode

 Terminal Tracing (TERMTRAC)
   Enable . . . 3  1. Enable terminal tracing (ON)
                   2. Enable terminal tracing when a terminal error is
                      encountered (ERROR)
                   3. Disable terminal tracing (OFF)
   DDNAME . . . ISPSNAP   (DDNAME for TERMTRAC ON, ERROR, or DUMP.)

 Terminal Status (TERMSTAT)
   Enable . . . 3  1. Yes, invoke TERMSTAT immediately
                   2. Query terminal information
                   3. No
 Command ===> ____________________________________________________________
  F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
  F9=Swap      F12=Cancel

 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 45. ISPF ENVIRON Settings panel (ISPENVA)

The panel text provides an overview of the command and its parameters. For a complete description of the ENVIRON command and its parameters, see *z/OS ISPF Dialog Developer's Guide and Reference*.

Specifying shared profile settings (the Environ action bar choice)

Figure 46 shows the Multi-Logon Profile Sharing Settings panel from which you can choose parameter options for the SHRPROF command. To display this panel, perform one of these actions:

- Select the Environ choice on the ISPF Settings panel action bar, then select option 2, "Shared Profile settings...".
- Issue the ISPF system command SHRPROF from any ISPF command line.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
┌──────────────────────────────── ISPF Settings ────────────────────────────┐
e ISPISSA           Multi-Logon Profile Sharing Settings                    e
e Command ===> ____________________________________________________________  e
e                                                                           e
e Profile Enqueue settings                                                  e
e   Enter "/" to select option          ENQ Lock Wait . . . . . . 1000     e
e   /  Prompt for Profile ENQ Lockout   ENQ Lock Retry Count  . . 1         e
e                                                                           e
e Profile conflicts                                                         e
e   System Profile conflicts            Reference List conflicts           e
e   1  1. Keep                          1  1. Keep                         e
e      2. Discard                        2. Discard                        e
e      3. Prompt                         3. Prompt                         e
e                                                                           e
e   ISPF Profile conflicts              Edit Profile conflicts             e
e   1  1. Keep                          1  1. Keep                         e
e      2. Discard                        2. Discard                        e
e      3. Prompt                         3. Prompt                         e
e                                                                           e
e   Application Profile conflicts       Batch Profile conflicts            e
e   1  1. Keep                          1  1. Keep                         e
e      2. Discard                        2. Discard                        e
e      3. Prompt                                                           e
e                                                                           e
e   Other Profile conflicts                                                 e
e   1  1. Keep                                                              e
e      2. Discard                                                          e
e      3. Prompt                                                           e
e  F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward   e
e  F9=Swap       F12=Cancel                                                 e
└───────────────────────────────────────────────────────────────────────────┘
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 46. Multi-Logon Profile Sharing Settings (ISPISSA)

The panel text provides an overview of the command and its parameters. For a complete description of the SHRPROF command and its parameters, see *z/OS ISPF Dialog Developer's Guide and Reference*.

Specifying workstation parameters (the Workstation action bar choice)

Figure 47 on page 59 shows the Workstation pull-down menu on the ISPF Settings panel action bar.

```
   Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ------------------------------------------------------------------------
                                   ISPF      1. Workstation connection...
                                             2. GUI panel settings...
 Options                                     *. Workstation Tool Integration...
   Enter "/" to select option                4. Download ISPF C/S component...
   /  Command line at bottom                 *. Disconnect from the workstation
   /  Panel display CUA mode
   /  Long message in pop-up
   /  Tab to action bar choices
      Tab to point-and-shoot fields        General

 :
```

Figure 47. Workstation pull-down on the ISPF settings panel action bar (ISPISMMN)

From this pull-down you can start a workstation session, specify GUI panel settings, configure the Workstation Tool Integration dialog, download the ISPF C/S component, and disconnect from the workstation.

Before you can perform these tasks, you must have completed these tasks:

- Successful installation and initialization of TCP/IP or APPC.

  'Appendix B: Configuring Communications for the ISPF Client/Server', in the *z/OS ISPF User's Guide Vol I*, contains procedures to help you to test whether you have satisfied this requirement.
- Successful installation of the ISPF Workstation Agent component.

  See 'Appendix A: Installing the Client/Server component', in the *z/OS ISPF User's Guide Vol I* for additional information.
- Initialization of the ISPF WSA component.

  To initialize the WSA:

  – If you have created a shortcut on your desktop that automatically launches the WSA, double-click the icon.

  If you do not have a shortcut icon:

  1. Go to a command line in your operating system (Windows or Unix).
  2. Change to the directory that contains your WSA executable file.
  3. Enter WSA.

     The Workstation Agent window is displayed on your workstation.



Figure 48. The Workstation Agent window

This window represents the executing ISPF C/S workstation program. For more information about this window, see 'Appendix A: Installing the Client/Server component', in the *z/OS ISPF User's Guide Vol I*. You can minimize this window but you cannot close it while ISPF is running in GUI mode.

Note: If you do not close the WSA window after you end an ISPF C/S session, you will not have to repeat this step to start another ISPF C/S

session; that is, as long as the ISPF C/S component has been started, you can start a workstation session.

Note: You can specify the GUI panel settings without having established a workstation connection and without running in GUI mode. However, your changes will not be seen until you next run GUI mode.

Workstation connection

When you select "Workstation connection" from the Workstation pull-down, one of two events can occur. Either the Initiate Workstation Session panel is displayed, or ISPF tells you that a newer version of the Workstation Agent code is available (if your system programmer has not disabled this feature).

Initiate the workstation connection: If you select "Workstation connection" and your Workstation Agent code matches the latest level available, the Initiate Workstation Connection panel appears, as shown in Figure 49.

```
                              ISPF Settings
                     Initiate Workstation Connection

 /  Save values in system profile?  (/=Yes)

 Workstation Connection                    GUI Network Protocol
 1  1. With GUI display                    1  1. TCP/IP
    2. Without GUI display                    2. APPC
                                              3. Use ISPDTPRF file

 GUI Title
 ____________________________________________________________________
 TCP/IP Address
 ____________________________________________________________________
 APPC Address
 ____________________________________________________________________

 Host Codepage  . . . ____      Host Character Set . . .  ____

 GUI Window Frame               Default Window Background Color
 1  1. Standard (STD)           1  1. Dialog (DLG)
    2. Fixed (FIX)                 2. Standard (STD)
    3. Dialog (DLG)

 Press ENTER to initiate a session. Press EXIT or CANCEL to return
 without initiating a session.
 Command ===> ______________________________________________________
  F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
  F9=Swap      F12=Cancel
```

Figure 49. Initiate Workstation Connection panel (ISPISMGI)

Note: If your WSA is not running, this panel will appear but you will not be able to establish a connection.

The Initiate Workstation Session panel allows you to specify that you want to start a GUI session. Starting a GUI session from this panel if you are in split screen mode or 3290 partition mode is not supported. If you select Workstation connection, you must specify the information in these fields, as appropriate:

Save values in system profile?
The default for this setting is YES. Any changes to this field are saved in the user's system profile.

Workstation connection
Allows you to specify one of these types of connections for your workstation session:

With GUI display
A GUI interface is provided for this session.

Without GUI display
A standard ISPF type of interface is provided for this session.

GUI Network Protocol
The type of network you use to connect the workstation to the host: TCP/IP or APPC.

You can also select the third option "Use ISPDTPRF file", to specify that ISPF get your network address from the file allocated to DD ISPDTPRF. The file can be sequential or a member of a PDS, and it can be fixed blocked (FB) or variable blocked (VB). Each line of the file should be formatted as follows: `userid WORKSTAT protocol_id:network_address`, where:

userid user's TSO userid

protocol_id network protocol identifier, either **ip** for TCP/IP or **lu** for APPC.

network_address
workstation address

For example, KEENE WORKSTAT ip:9.45.202.69.

GUI Title
The title you want displayed in the window frame of your GUI session. This value will be used if dialog variable ZWINTTL or ZAPPTTL is not found.

TCP/IP Address
The workstation's IP address. Required if you specified TCP/IP in the GUI Network Protocol field. The TCP/IP Address prompt is point-and-shoot text. If selected, a pop-up window is displayed containing the last five addresses saved in the system profile.

A TCP/IP address can be in dotted decimal format or in domain name format. Dotted decimal format is a sequence of decimal numbers separated by periods, for example, **9.87.654.321**.

A TCP/IP address in domain name format consists of one or more domain qualifiers separated by periods. The minimum specification for addresses within the same domain is a TCP/IP host name, for example, **jsmith**. The fully-qualified domain name for *jsmith* is formed by appending the appropriate subdomain name and root domain name to *jsmith*, such as **jsmith.raleigh.ibm.com**. To use domain naming, a domain name server must be active and providing domain name resolution for domain names within your TCP/IP network. The domain name server address is determined by the value of the **NSINTERADDR** statement in the TCP/IP configuration data set. ISPF must be able to locate the TCP/IP configuration data set as described in the section on configuring TCP/IP connections in the *z/OS ISPF User's Guide Vol I*.

If an asterisk (*) is specified, the TCP/IP address is obtained automatically from the value of the system variable ZIPADDR.

APPC Address
The workstation's APPC network name. Required if you specified APPC in the GUI Network Protocol field. The APPC Address prompt is point-and-shoot text. If selected, a pop-up window is displayed containing the last five addresses saved in the system profile.

An APPC address can be in fully-qualified LU name format or in symbolic destination name format. A fully-qualified LU name format consists of a network identifier and an LU name, separated by a period. For example, **USIBMNR.NRI98X00** is a fully-qualified LU name.

An APPC address in symbolic destination name format consists of a 1- to 8-character name such as **JSMITH**. The symbolic destination name must be defined as a *DESTNAME* and the corresponding fully-qualified LU name must be defined as the associated *PARTNER_LU* in the APPC/MVS side information.

Host Codepage
The host code page value used in translating data from the host to the workstation. This value **must** be specified with a Host Character Set value if it is to be used. If only one, or neither, of these values is specified, the values from the terminal query are used. If your terminal or emulator does not support code pages, the CODEPAGE and CHARSET parameter values on the ISPSTART command are used. If the ISPSTART values are not specified, the default code page and character set is ENGLISH.

Host Character Set
The host character set value used in translating data from the host to the workstation. This value **must** be specified with a Host Codepage value if it is to be used. If only one, or neither, of these values is specified, the values from the terminal query are used. If your terminal or emulator does not support code pages, the CODEPAGE and CHARSET parameter values on the ISPSTART command are used. If the ISPSTART values are not specified, the default code page and character set is ENGLISH.

GUI Window Frame
Allows you to specify one of these types of window frames for your GUI session:

1 **Standard (STD)**. A GUI window frame that can be resized and that has max/min buttons.

2 **Fixed (FIX)**. A GUI window frame that has a min button but cannot be resized.

3 **Dialog (DLG)**. A GUI window frame that cannot be resized and that does not have max/min buttons.

Note: Pop-up panels will always be displayed in dialog window frames.

Default window background color
Select the background color:

Dialog (DLG)

Standard (STD)

When you complete the fields shown in Figure 49 on page 60 and press Enter, the WSA connection panel is displayed in a separate window (unless your system has

been set up to bypass it - see the topic about the System Register panel in "Installing the Client/Server component", in the *z/OS ISPF User's Guide Vol I* for details).



Figure 50. WSA connection panel

This panel indicates the requestor and the type of connection requested. Click on **Yes** to accept the connection as described, or **No** to reject the connection.

If you accept the connection, the ISPF Settings panel is displayed. This will be in standard or GUI mode, depending on the option selected in the With GUI display field.

Client/server component update: If you select "Workstation connection" but the WSA code does not match the latest level available, the Client/Server Component Update panel is displayed, as shown in Figure 51 on page 64.

Note: If you have not started the WSA, the Initiate Workstation Connection panel displays, but you will not be able to establish a connection.

```
                              ISPF Settings
                     Client/Server Component Update

 Your workstation agent is level  . . . . . . . . . : 439

 It is recommended that you download level  . . . : 505

 Download New Agent?
 1  1. Download now
    2. Do not download
    3. Cease warnings

 Directory to copy file to:
 ____________________________________________________________________

 Data Set to copy file from:
 'ISP.SISPGUI'
 ____________________________________________________________

 Enter "/" to select option
    Create directory to which the file is to be copied.
 Command ===> ____________________________________________________
  F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
  F9=Swap      F12=Cancel
```

Figure 51. Client/Server Component Update panel (ISPDTVD1)

From this panel, you can download the latest WSA or continue to use your current WSA, and even tell ISPF not to notify you again if your WSA does not match the latest available. In the Download New Agent? field, you can specify one of three choices:

Download now
The download copies an installation program for the latest level of the WSA. You must specify the target directory in the “Directory to copy file to:” field. To create a new directory (one that does not already exist on your workstation) for the file, enter a slash mark (/) in the “Create directory to which the file is to be copied” field. The “Data Set to copy file from:” field should already be initialized by your system programmer. If it is not, you must specify the host data set that holds the latest WSA installation program. For example, ‘SYS1.ISP.SISPGUI’.

After downloading the installation program for the WSA, end your ISPF/GUI connection, terminate your old Workstation Agent, and run the installation program to install the new one.

Do not download
You might want to download the new WSA later. If so, select “Do not download”. ISPF does not download the new installation program at this time, but will prompt you again the next time you start a GUI session. Of course, you can always download the agent yourself with the Client/Server Component download function of the ISPF Utilities panel at any time. See “Download data set to workstation utility (option 3.7)” on page 185 for more information.

Cease warnings
ISPF does not download the agent installation program *and* you will not be notified again that your current WSA does not match the latest available on the host until an even higher level is available. That is, if you currently run level 433 and you have asked to Cease warnings at level 440, ISPF will not notify you again until at least level 441 is available.

Upon successful download of the new agent, the panel in Figure 52 appears. This panel gives you the option to end your GUI session and begin the installation immediately (by choosing option 1), or continuing your present session and installing the new Workstation Agent at a later time. See “Download data set to workstation utility (option 3.7)” on page 185 for more information.

```
                              ISPF Settings
                ISPF Client/Server Component Install Program

 The ISPF Client/Server Component workstation install program has been
 copied to your workstation in the current working directory of your
 current workstation agent.

 End your workstation connection and resume the installation by running
 the install program ISPFINST on your workstation in the working
 directory of your active workstation agent. The program is a self
 extracting executable that will result in additional files being
 generated on your workstation.

 Do you wish to end your workstation connection now?
 _  1. Yes, end workstation connection now
    2. No, do not end workstation connection now



 Command ===> _______________________________________________________
  F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
  F9=Swap      F12=Cancel
```

Figure 52. Client/Server Component Install Program panel (ISPWSD0A)

GUI panel settings

When you select “GUI panel settings” from the Workstation pull-down, the GUI Settings pop-up window is displayed, as shown in Figure 53 on page 66.

Note: You do not need to have a Workstation connection running, or to be in GUI mode, to change these settings.

```
   Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
─ ┌──────────────────────────── ISPF Settings ────────────────────────────┐ ────────
  │                             GUI Settings                              │
  │                                                          More:     +  │ e:     +
O │ Close Window                                                          │
  │ 1  1. Cancel                                                          │
  │    2. End                                                             │
  │    3. Exit                                                            │
  │    4. Return                                                          │
  │                                                                       │
  │ Enter "/" to select option                                            │
  │ /  Display ENTER Key                                                  │
  │ /  Accelerator Support                                                │
  │ /  Continue 3270 Mode After Losing Workstation Connection             │
  │ /  Download Images                                                    │
  │ _  Make Path for Images                                               │
  │                                                                       │
  │ Path for Images:                                                      │
T │                                                                       │
  │ Command ===> ____________________________________________             │
  │  F1=Help         F2=Split        F3=Exit         F7=Backward          │
C │  F8=Forward      F9=Swap        F12=Cancel                            │
  └───────────────────────────────────────────────────────────────────────┘ wap
F10=Actions  F12=Cancel
```

Figure 53. GUI settings pop-up window (ISPISMGS)

The GUI Settings pop-up window allows you to specify these GUI parameters:

Close Window
Allows you to specify that one of these commands be processed when you close a GUI window:
- CANCEL
- END
- EXIT
- RETURN.

Display Enter Key
Select this field to display an Enter push button at the bottom of all GUI panels.

Accelerator Support
Select this field to use accelerator keys in this session.

3270 mode after losing workstation connection
Select this field if you want the ISPF session to continue in the 3270 emulator session rather than abend with code 989 when the workstation connection is lost while running in GUI mode.

Download Images
Select this field to download images *from* the host library defined to ddname ISPILIB, *to* the workstation image path. If you are not running ISPF in GUI mode, this setting is ignored.

Make Path for Images
Select this field to have ISPF create the image path you specify, when the image path you specify does not already exist on the workstation.

Path for images
In GUI mode, this field enables you to specify a workstation path for images. The image path can be 244 characters long with no embedded blanks. The image path you specify must follow the accepted path notation

for whichever operating system you are using. If you do not specify an image path, ISPF puts the image requested into the workstation's working directory.

Workstation tool integration

ISPF enables you to edit host data on the workstation, and workstation data on the host. ISPF calls this function *distributed editing*.

The ISPF Workstation Tool Integration dialog, or tool integrator, is a workstation customization tool that enables any workstation application to use data from an MVS host system. After setting up the tool integrator, your workstation-installed applications can interact with the ISPF View and Edit functions and services. Data flow goes both ways with the tool integrator connection. You can work with workstation files on the host or with host files on the workstation.

Overall, the tool integrator enables MVS-based users to use workstation applications and then share data through MVS. MVS, its file system, and RACF®, provide data integrity, security, and distribution capabilities beyond the workstation. Sharing data this way can reduce your installation's dependence on complex LANs, off-load CPU cycles to your workstation, and take advantage of workstation tools.

Starting the tool integration dialog: Before you can use the tool integrator, the Workstation Agent must have been installed and configured. See "Workstation connection" on page 60 for details on these prerequisite tasks.

You can run the tool integrator in either GUI mode or the standard ISPF mode. For information about running ISPF in GUI mode, see the topic about the ISPF user interface in the *z/OS ISPF User's Guide Vol I*.

Note: You cannot issue a WSDISCON command or service call while running the workstation tool integration dialog.

You can display the Workstation Tool Integration Configuration panel, shown in Figure 54 on page 68, using any of these methods:

- Select Workstation Tool Integration from the Workstation pull-down.
- Select the Workstation choice on the action bars found on the Edit or View panels, then choose Workstation Tool Integration.
- Type `INT` on any ISPF command or action line and press Enter.

```
 Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help

  File  Map  Help
 ____________________________________________________________________________

                 Workstation Tool Integration Configuration

 Press EXIT to save tool configuration to connected workstation hard drive.
 Press CANCEL to temporarily update tool configuration for this session.

 Action: E=Edit V=View

    Description  Code  Data    Mode      Command
 _  View         V     TEXT    MODELESS  e
 _  Edit         E     TEXT    MODAL     e
    **End**

 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
  F9=Swap       F10=Actions    F12=Cancel

  Screen format   2  1. Data    2. Std     3. Max     4. Part
Command ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 54. ISPF Workstation Tool Integration panel

The information contained on this panel is defined as follows:

- Line command field
Enter v (view) or e (edit) to display the Tool Configuration panel in View or Edit mode.

Description Text explaining the ISPF action.

Code The ISPF action code assigned to this workstation application.

Data The format used for the object file during download and upload to the host.

Mode The processing mode for this action.

Command The workstation invocation command string or name.

You use this panel to begin to define how the ISPF actions interact with the workstation applications, or just to look at the actions you have already defined.

The Tool Integrator action bar choices: These action bar choices are available on the Workstation Tool Integration panel:

File

Edit Calls the edit function to update the parameters of a workstation action.

View Displays the parameters of a particular action.

Cancel changes
Exit edit without updating the workstation action.

Exit and Save Exit edit and save changes made to the workstation action parameters.

Map

Extension
Starts the Extension Mapping dialog. See "Extension mapping" on page 70 for more information.

Updating an action: To update the configuration of an action, use either of these methods:

- Type e (edit) in the line command field next to View or Edit, and press Enter.
- Type / in the line command field next to View or Edit, then choose File > Edit from the action bars in the panel

After you choose to edit an action, the screen shown in Figure 55 is displayed.

```
                 Modify Tool Configuration
                                                More:     +
Description  . : View      Code  . : V

Options
Data . . 1  1. Text        Invocation   2  1. Modal
            2. Binary                      2. Modeless

Workstation command
e

Additional parameters

Working directory

 F1=Help        F2=Split       F3=Exit        F7=Backward
 F8=Forward     F9=Swap       F12=Cancel
```

Figure 55. Modify Tool Configuration window

The fields found on this panel are as follows:

Description
Text explaining the ISPF action.

Code The ISPF action code assigned to this workstation application.

Data The format used for the object file during download and upload to the host. Use Binary for data that you want to leave unchanged on the host, for example, image files such as bitmaps.

Invocation
The processing mode for this action. Use Modal to ensure that an action is completed before your application moves on to another task. For example, if you want to upload and replace an object on the host, specify Modal. Modeless means that the action can continue while your application performs other tasks, effectively running in parallel with the application.

Workstation Command
The workstation invocation command string or name. This can be the actual command name of the workstation application, or a workstation path and command name.

Additional Parameters
Additional parameters that are recognized by the workstation command.

Working Directory
The directory on the workstation in which files used by Workstation Edit are stored. These include saved copies of workstation files and temporary copies of host files that are being processed by Edit or View on the workstation.

If you do not specify a location, a default directory is used. On Windows, the default is the directory where the ISPF WSA was started. On UNIX systems, the default is the user's home directory.

Extension mapping: The Map choice on the tool integrator action bar enables you to associate a workstation file extension of up to 3 characters with a host data set type. The host data set type is the last qualifier of the data set. These are frequently longer than 3 characters, while most workstation file extensions are 3 or less. The Extension Mapping dialog panel, shown in Figure 56, shows how certain host data set types map to their workstation file extension counterparts.

```
 Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ──────────────────────────────────────────────────────────────────────────
   Workstation Tool Extension Mapping     gs
                                                          More:     +
 Action:  I=Insert  D=Delete  R=Repeat    rint Graphics
                                           Family printer type 2
    Host Type     Workstation Extension    Device name . . . .
 _  ________      ___                      Aspect ratio  . . . 1
    **End**

                                          eneral
                                           Input field pad . . B
                                           Command delimiter . ;

 Command ===>          Scroll ===> PAGE
  F1=Help      F2=Split     F3=Exit        3. Max     4. Part
  F7=Backward  F8=Forward   F9=Swap
                                          Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 56. Extension Mapping Dialog window

To map a host to workstation pair, perform one of these actions:

1. In the Action field, type R to repeat a previous mapping, I to insert a new mapping, or D to delete a current mapping.
2. In the Host Type field, type the last qualifier of the host data set to be mapped.
3. In the Workstation Extension field, type the extension name to be used for the temporary workstation file created.
4. Press Enter.

If you attempt to use a host data set on a workstation and you have not mapped the data set type to one on your workstation, the first 3 characters of the data set type are used by default.

Download ISPF C/S component

When you select "Download ISPF C/S Component" from the Workstation pull-down, the Client/Server component dialog starts. See "Download data set to workstation utility (option 3.7)" on page 185 for more information.

Disconnect from the workstation

When you select "Disconnect from the workstation" from the Workstation pull-down, the Workstation Disconnect Confirmation dialog starts. From the dialog you have the choice of `YES` to disconnect, or `NO` which cancels the disconnect request.

Displaying message, system, user, panel, and screen IDs

The Identifier action bar choice allows you to display message IDs with the message text, and to display system, user, panel, and screen identifiers at the start of the Title line.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ──────────────────────────────────────────────────────────────────────────
                                ISPF Settings     _  1. Message identifier...
                                                     2. Panel identifier...
 Options                                     Print   3. Screen name...
   Enter "/" to select option                  Fam   4. System name...
   /  Command line at bottom                   Dev   5. User ID...
   /  Panel display CUA mode                   Asp
   /  Long message in pop-up
   /  Tab to action bar choices
      Tab to point-and-shoot fields          General
   /  Restore TEST/TRACE options               Input field pad . . B
      Session Manager mode                     Command delimiter . ;

 ⋮
```

Figure 57. Identifier pull-down on the ispf settings panel action bar (ISPISMMN)

Message identifier

You can specify that you want to display message identifiers in either of two ways:

- Select the "Message identifier" choice from the Identifier pull-down on the ISPF Settings panel action bar, as shown in Figure 57.
- Issue the ISPF system command MSGID ON.

When you select "Message identifier" from the Identifier pull-down, the Message Identifier panel is displayed.

If you select the "Display message identifier" option, the message identifier is set to On. The identifier will now display within the message text whenever a long message option is accessed (that is, when you enter the HELP command). Deselect this choice (or issue the MSGID OFF command) to set the message identifier to Off.

This setting only applies to the current ISPF session. To retain the setting across ISPF sessions, select "Default setting for message identifier".

Figure 58 shows an error message on the ISPF Settings panel displayed with the message identifier set to on.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ──────────────────────────────────────────────────────────────────────────
                                ISPF Settings                   Invalid value
                                                                  More:     +
 Options                                   Print Graphics
   Enter "/" to select option                Family printer type 2
   /  Command line at bottom                 Device name . . . . _______
   /  Panel display CUA mode                 Aspect ratio  . . . 8
   /  Long message in pop-up                                   ┌──────────────────┐
   /  Tab to action bar choices                                │ ISPG213 Valid    │
      Tab to point-and-shoot fields          General           │ values are: 0 or 1 │
   /  Restore TEST/TRACE options               Input field     └──────────────────┘
   _  Session Manager mode                     Command delimiter . ;

 ⋮
```

Figure 58. Panel displayed with the message identifier set to on

System name

You can specify that you want to display the system name in either of two ways:

- Select the “System name” choice from the Identifier pull-down on the ISPF Settings panel action bar.
- Issue the ISPF system command SYSNAME ON.

When you select “System name” from the Identifier pull-down, the System Name Identifier panel is displayed.

If you select the “Display system name identifier” option, the system name identifier is set to On. The identifier will now display in the panelid area. Deselect this choice (or issue the SYSNAME OFF command) to set the system name identifier to Off.

This setting only applies to the current ISPF session. To retain the setting across ISPF sessions, select “Default setting for system name”.

Figure 59 shows the top portion of the ISPF Settings panel displayed with the screen identifier set to On.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ──────────────────────────────────────────────────────────────────────────
 ZISD10                         ISPF Settings                   Invalid value
                                                                  More:     +
 Options                                   Print Graphics
   Enter "/" to select option                Family printer type 2
   /  Command line at bottom                 Device name . . . . _______
   /  Panel display CUA mode                 Aspect ratio  . . . 8
   /  Long message in pop-up                                   ┌──────────────────┐

 ⋮
```

Figure 59. Panel displayed with the system name set to on

Note: The commands SYSNAME, USERID, PANELID, and SCRNAME share the same 17-character area at the start of the Title line. If more than one of these commands are specified, ISPF displays as many as will fit, in this order of priority: SYSNAME, if specified, is always displayed. Then, as long as there is enough room, USERID is displayed, then PANELID, then SCRNAME.

User ID

You can specify that you want to display the user ID in either of two ways:

- Select the "User ID" choice from the Identifier pull-down on the ISPF Settings panel action bar.
- Issue the ISPF system command USERID ON.

When you select "User ID" from the Identifier pull-down, the User Identifier panel is displayed.

If you select the "Display user identifier" option, the user identifier is set to On. The identifier will now display in the panelid area. Deselect this choice (or issue the USERID OFF command) to set the user identifier to Off.

This setting only applies to the current ISPF session. To retain the setting across ISPF sessions, select "Default setting for user identifier".

Figure 60 shows the top portion of the ISPF Settings panel displayed with the user identifier (and the system name) set to On.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ──────────────────────────────────────────────────────────────────────────
 ZISD10 MBURNS                   ISPF Settings                   Invalid value
                                                                   More:     +
 Options                                     Print Graphics
   Enter "/" to select option                  Family printer type 2
   /  Command line at bottom                   Device name . . . . _______
   /  Panel display CUA mode                   Aspect ratio  . . . 8
   /  Long message in pop-up                                  ┌──────────────┐

 ⋮
```

Figure 60. Panel displayed with the user ID set to on

Note: The commands SYSNAME, USERID, PANELID, and SCRNAME share the same 17-character area at the start of the Title line. If more than one of these commands are specified, ISPF displays as many as will fit, in this order of priority: SYSNAME, if specified, is always displayed. Then, as long as there is enough room, USERID is displayed, then PANELID, then SCRNAME.

Panel identifier

You can specify that you want to display panel identifiers in either of two ways:

- Select the "Panel identifier" choice from the Identifier pull-down on the ISPF Settings panel action bar, as shown in Figure 57 on page 71.
- Issue the ISPF system command PANELID ON.

When you select "Panel identifier" from the Identifier pull-down, the Panel Identifier panel is displayed.

If you select the “Display panel identifier” option, the panel identifier is set to On. The identifier will now display in the panelid area. Deselect this choice (or issue the PANELID OFF command) to set the panel identifier to Off.

This setting only applies to the current ISPF session. To retain the setting across ISPF sessions, select “Default setting for panel identifier”.

Figure 61 shows the top portion of the ISPF Settings panel displayed with the panel identifier set to On.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ------------------------------------------------------------------------
 ISPISMMN                        ISPF Settings
                                                                More:     +
 Options                                   Print Graphics
   Enter "/" to select option                Family printer type 2
   /  Command line at bottom                 Device name . . . . _______
   /  Panel display CUA mode                 Aspect ratio  . . . 1
   /  Long message in pop-up
 :
```

Figure 61. Panel displayed with the panel identifier set to on

Note: The commands SYSNAME, USERID, PANELID, and SCRNAME share the same 17-character area at the start of the Title line. If more than one of these commands are specified, ISPF displays as many as will fit, in this order of priority: SYSNAME, if specified, is always displayed. Then, as long as there is enough room, USERID is displayed, then PANELID, then SCRNAME.

Screen name

You can specify that you want to display the screen name in either of two ways:

- Select the “Screen name” choice from the Identifier pull-down on the ISPF Settings panel action bar.
- Issue the ISPF system command SCRNAME ON.

When you select “Screen name” from the Identifier pull-down, the Screen Name Identifier panel is displayed.

If you select the “Display screen identifier” option, the screen identifier is set to On. The identifier will now display in the panelid area. Deselect this choice (or issue the SCRNAME OFF command) to set the screen identifier to Off.

This setting only applies to the current ISPF session. To retain the setting across ISPF sessions, select “Default setting for screen identifier”.

Figure 62 shows the top portion of the ISPF Settings panel displayed with the screen identifier set to On.

```
  Log/List  Function keys  Colors  Environ  Workstation  Identifier  Help
 ------------------------------------------------------------------------
 SETTINGS                        ISPF Settings                    Invalid value
                                                                    More:     +
 Options                                   Print Graphics
   Enter "/" to select option                Family printer type 2
   /  Command line at bottom                 Device name . . . . _______
   /  Panel display CUA mode                 Aspect ratio  . . . 8
   /  Long message in pop-up                                    ┌──────────────┐


 :
```

Figure 62. Panel displayed with the screen identifier set to on

Note: The commands SYSNAME, USERID, PANELID, and SCRNAME share the same 17-character area at the start of the Title line. If more than one of these commands are specified, ISPF displays as many as will fit, in this order of priority: SYSNAME, if specified, is always displayed. Then, as long as there is enough room, USERID is displayed, then PANELID, then SCRNAME.

Chapter 3. View (option 1)

The View option (1) displays the View Entry Panel shown in Figure 63.

```
  Menu  RefList  RefMode  Utilities  Workstation  Help
 ------------------------------------------------------------------------------
                              View Entry Panel
                                                                   More:     +
ISPF Library:
   Project . . . MYPROJ
   Group . . . . DEV     . . . ________ . . . ________ . . . ________
   Type  . . . . SOURCE
   Member  . . . ________        (Blank or pattern for member selection list)

Other Partitioned, Sequential or VSAM Data Set, or z/OS UNIX file:
   Name . . . . . ____________________________________________________________ +
   Volume Serial . . . ______    (If not cataloged)

Workstation File:
   File Name . . . . . ________________________________________________________
                                     Options
Initial Macro  . . . . ________       _  Confirm Cancel/Move/Replace
Profile Name . . . . . ________       _  Browse Mode
Format Name  . . . . . ________       _  View on Workstation
Data Set Password  . .                /  Warn on First Data Change
Record Length  . . . . _____          _  Mixed Mode
                                      _  View ASCII data
Command ===> ______________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 63. View Entry panel (ISRBRO01)

This option enables you to view or browse source data and listings stored in ISPF libraries, other partitioned or single-volume or multivolume sequential data sets, or z/OS UNIX files.

View Allows you to use all Edit line commands, primary commands, and macros to manipulate the data. View functions exactly like Edit, with the exception of these primary commands:

SAVE When you enter the SAVE command, ISPF issues a message that you must use the CREATE command to save any data you have changed.

END When you enter the END command, ISPF terminates the View function; no data changes are saved.

Browse Allows you to use the Browse primary commands described in "Browse primary commands" on page 81 to manipulate data.

View is enabled by default. You can disable View, thus allowing only Browse, by modifying the ISPF Configuration Table. You must set the keyword **IS_VIEW_SUPPORTED** to `NO`. For more information, see the topic about the ISPF Configuration Table in *z/OS ISPF Planning and Customizing*.

You can view or browse data that has these characteristics:

- Record Format (RECFM):

© Copyright IBM Corp. 1980, 2007

  - Fixed, variable (non-spanned), or undefined

    Note: If you try to view a data set with RECFM=U, the Browse function is substituted.
  - Blocked or unblocked
  - With or without printer control characters
- Logical Record Length (LRECL):
  - For fixed-length records, up to 32 760 characters. For view only, the minimum record length is 1 character.
  - For variable-length records, up to 32 756 characters. For view only, the minimum record length is 5 characters.
- VSAM data
  - VSAM data can be browsed if the ISPF Configuration table has been customized to enable VSAM support (that is, VSAM_BROWSE_ENABLED or VSAM_VIEW_ENABLED is set to "YES").

    Note: When VSAM support is enabled, the default value for VSAM_BROWSE_COMMAND and VSAM_VIEW_COMMAND is "FMNMAIN DSB /". If the command is not available, IKJ56500I COMMAND FMNMAIN NOT FOUND, is issued as a TSO message.
- z/OS UNIX files.

View Entry Panel action bar

The View Entry Panel action bar choices function as follows:

Menu
: See the details about the Action Bar Choice in the ISPF User Interface topic of the *z/OS ISPF User's Guide Vol I* for information about the Menu pull-down.

RefList
: See the Using Personal Data Set Lists and Library Lists topic in the *z/OS ISPF User's Guide Vol I* for information about referral lists.

RefMode
: See the information about Personal List Modes in the Using Personal Data Set Lists and Library Lists topic in the *z/OS ISPF User's Guide Vol I* for information about referral list modes.

Utilities
: For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Workstation
: The Workstation pull-down offers you one choice:

  1. Workstation Tool Integration
  : See the information about the ISPF Workstation Tool Integration Program in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I* for more information.

Help
: The Help pull-down provides general information about the options and commands available in View, as well as information about each available choice on the View Entry Panel.

View Entry Panel fields

The "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* contains information about all the fields on the View Entry Panel except these:

Initial Macro
: You can specify an Edit macro to be processed before you begin viewing

your sequential data set or any member of a partitioned data set. This initial macro enables you to set up a particular environment for the View session you are beginning.

If you leave the Initial Macro field blank and your Edit profile includes an initial macro specification, the initial macro from your Edit profile is processed.

If you want to suppress the processing of an initial macro in your Edit profile, enter NONE in the Initial Macro field.

Profile Name
You can specify a profile name to override the default Edit profile.

Format Name
Contains the name of a format definition, which is used to view or browse a formatted data set.

Browse Mode
Specifies that you want to browse the data set using the Browse function. This function is useful for large data sets and data sets that are formatted RECFM=U.

Confirm Cancel/Move/Replace
Specifies that you want ISPF to display a confirmation panel whenever you issue a Cancel, Move, or Replace command.

Mixed Mode
Specifies that you want to view or browse unformatted data that contains both EBCDIC and DBCS characters.

View on Workstation
Specifies that you want to view the data on your workstation. This option requires a workstation connection to be used.

Warn on First Data Change
Specifies that you want ISPF to warn you that changes cannot be saved in View. The warning is displayed when the first data change is made.

Record Length
Can be used when browsing a z/OS UNIX file. The numeric value entered in this field is used by ISPF to display the data in the file as fixed-length records, rather than using the newline character to delimit each record. This is useful for browsing files which would otherwise have very large records if the newline character is used as the record delimiter.

View ASCII data
You can select this option when viewing a z/OS UNIX file containing data encoded in ASCII and the file is not tagged with a CCSID of 819. When you select this field with a "/", the editor renders the ASCII data readable by converting the data to the CCSID of the terminal. Also, the editor breaks up the data into records using the ASCII linefeed character (X'0A') and the ASCII carriage return character (X'0D') as the record delimiter. The linefeed and carriage return characters are removed from the data loaded into the editor. It is not necessary to use this option when the file is tagged with a CCSID of 819. If ISPF detects the file is tagged with CCSID 819, it converts the data from ASCII to the CCSID of the terminal.

Browsing a data set

If you select Browse Mode on the View Entry Panel, ISPF displays either a member selection list or a Browse data display. For information about displaying a member list, see the topic about Using Member Selection Lists in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

Note: If you specify a volume serial on the View Entry Panel, you can browse a single volume of a non-SMS multivolume data set.

A Browse data display is shown in Figure 64.

```
   Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    ISPFDEMO.XXX.COBOL(CBLMAIN) - 01.01        Line 00000000 Col 001 080
********************************* Top of Data **********************************
IDENTIFICATION DIVISION.
PROGRAM-ID. 'F20D1000'.
DATE-COMPILED. OCT. 20, 1985
ENVIRONMENT DIVISION.
CONFIGURATION SECTION.
SOURCE-COMPUTER. IBM-370.
OBJECT-COMPUTER. IBM-370.
INPUT-OUTPUT SECTION.
FILE-CONTROL.
    SELECT OLD-COMREC ASSIGN TO DA-S-DD1.
    SELECT D1-REPORTS ASSIGN TO UR-S-D1OUT.
    SELECT OPTION-CARD-FILE ASSIGN TO UR-S-SYSIN.
DATA DIVISION.
FILE SECTION.
FD  OLD-COMREC
    LABEL RECORD IS STANDARD
    RECORDING MODE IS F
 Command ===> ___________________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 64. Browse - data display (ISRBROBA)

Each character in the data that cannot be displayed is changed on the display to either a period or a character that you have specified. Using the DISPLAY command, you can specify whether printer carriage-control characters are to be treated as part of the data, and thus displayed.

You can browse data that is stored in a Unicode format. MVS Conversion Services must first be set up for the appropriate conversions. See *z/OS ISPF Planning and Customizing*.

During Browse, four-way scrolling is available through the scroll commands. You can also use the FIND and LOCATE commands to scroll to a particular character string, line number, or symbolic label.

Whenever you enter a command, such as FIND or one of the scroll commands, that puts the cursor under a character string in the data set, ISPF highlights that character string. This highlighting occurs whether you type the command on the command line and press Enter or press a function key that the command is assigned to.

Ending browse

To end a Browse data display, use the END command. This returns you to the previous panel, which is either a member list display or the View Entry panel. If a member list is displayed, the name of the member you just browsed is at the top of the list. You can select another member from the list or enter the END command again to return to the View Entry Panel.

When the View Entry Panel is displayed again, you can select another data set or member, or you can use the END command to return to the ISPF Primary Option menu.

Browse primary commands

You can prefix any BROWSE command with an ampersand to keep the command displayed on the command line after the command has been processed. This technique allows you to repeat similar commands without reentering the data. For example, if you enter:

```
Command ===> &FIND ABCD
```

the command is displayed after the string has been found, which allows you to then change the operand and issue another FIND command.

Browse provides the functions described in these topics, each of which is controlled by a command that you can type on the command line:

BROWSE—browse recursively
COLUMNS—identify columns
DISPLAY—control the display
EDIT—edit a member
FIND—find character strings
HEX—display data in hexadecimal format
LOCATE—locate lines
RESET—remove the column-identification line
SUBMIT—submit a job stream for background execution
VIEW—view a member

BROWSE—browse recursively

The BROWSE command allows you to browse another member of the same data set. It also allows you to browse any other data set or a z/OS UNIX file without ending your current Browse session.

The BROWSE command has this syntax:

```
►►─BROWSE──┬──────────┬──────────────────────────────────────────►◄
           └─member───┘
```

where:

member An optional member of the ISPF library or other partitioned data set that you are currently browsing. You may enter a member pattern to generate a member list.

For example, if you were browsing a member of library ISPFDEMO.XXX.COBOL, you could enter this command to display the panel shown in Figure 64 on page 80:

```
BROWSE CBLMAIN
```

If you do not specify a member name, the Browse Command - Entry Panel is displayed.

You end a nested Browse session the same way you would a normal one. When you end the nested Browse session, the current Browse session resumes.

COLUMNS—identify columns

You can use the COLUMNS command to provide a temporary indication of where columns occur on the panel. This command displays a column-identification line on the first line of the data area. The command has this syntax:

```
►►──COLUMNS──┬─ON──┬──────────────────────────────────────────────────►◄
             └─OFF─┘
```

where:

ON The default. Displays the column-identification line.

OFF Removes the column-identification line from the display.

Note: You can also remove the column-identification line by entering the RESET command.

An example of the column-identification line is shown in Figure 65. The digits on the identification line show the tens positions: 1 shows column 10, 2 shows column 20, and so forth. The plus signs (+) show the fives positions (columns 5, 15, 25, and so forth.)

```
  Menu  Utilities  Compilers  Help
 ──────────────────────────────────────────────────────────────────────────
 BROWSE    SBURNF.CALL.TRACE                          Line 00000017 Col 001 080
 Command ===>                                                 Scroll ===> CSR
----+----1----+----2----+----3----+----4----+----5----+----6----+----7----+----8
     ISPVCALL Command: ISPVCALL
     ISPF Invocation   ISPF
==============================< Cached Panels >================================
          ISR@PRIM
==========================< Active Command Tables >============================
          USERCMDS  SITECMDS  ISPCMDS
======================< Entries in Open Command Tables >=======================

⋮
```

Figure 65. Browse - column-identification line (ISRBROBA)

DISPLAY—control the display

The DISPLAY command allows you to view data that would not normally be displayed, such as carriage control characters and Unicode data. For other nondisplayable data you can specify a character to represent each character that cannot be displayed.

The DISPLAY command has two formats. The first is used to display carriage-control characters and other nondisplay characters. The second allows data stored using a Unicode CCSID (Coded Character Set Identifier) to be displayed using the CCSID of the terminal.

Carriage-control characters and other nondisplay characters

```
►►─DISPLAY─┬──────┬─┬─NOCC─┬──────────────────────────────────────────►◄
           └─char─┘ └─CC───┘
```

You must enter at least one operand, but you can enter them in any order. If you enter only one operand, the other operand retains its current value.

where:

char The character you want to use to represent characters that cannot be displayed on the screen. It can be a single character, or a single character enclosed in apostrophes (') or quotation marks ("). If you specify a blank as the character, you must enclose it in apostrophes or quotation marks.

CC Shows that carriage control characters are to be displayed and are to be considered part of the data.

NOCC Shows that carriage control characters are not to be displayed and are not to be considered part of the data.

Both operands are stored in your user profile and are in effect whenever you are using Browse. You need to reenter the DISPLAY command only if you want to change one of the operands.

The first settings for display mode are period (.) and NOCC, but the carriage control character status has no effect if the data that you are browsing has no carriage control characters.

Unicode data

```
►►─DISPLAY─┬─┬──────────────────────────┬─┬──────────────────────────┬─┬─CCSID─ccsid_number─┬──────────►◄
           │ └─LINE─┬──────────────────┬─┘ └─COLS─┬──────────────────┬─┘ ├─ASCII────────────┤
           │        └─start_line─end_line─┘        └─start_col─end_col─┘   ├─USASCII─────────┤
           │                                                               ├─EBCDIC──────────┤
           │                                                               ├─UCS2────────────┤
           │                                                               ├─UTF8────────────┤
           │                                                               ├─UTF16───────────┤
           │                                                               └─UTF32───────────┘
           └─RESET──────────────────────────────────────────────────────────────────────────┘
```

where:

LINE *start_line end_line*
Specifies the number of the first and last lines within which Unicode data is displayed. If the LINE keyword is not specified, the DISPLAY command applies to the all lines in the data. If only one value is specified, the DISPLAY command only applies to that line.

COLS *start_col end_col*
Specifies the number of the first and last column within which Unicode data is displayed. If the COLS keyword is not specified, the DISPLAY command applies to the full range of columns in the data. If only one value is specified, the DISPLAY command only applies to that column.

CCSID *ccsid_number* | **ASCII** | **USASCII** | **EBCDIC** | **UCS2** | **UTF8** | **UTF16** | **UTF32**
Specifies the CCSID of the data. The CCSID represents a code page and character set combination.

RESET
This format of the command resets all definitions made with the DISPLAY command. All data is displayed as though it had been stored using the terminal CCSID.

LINE and COLS are optional. LINE, COLS, and CCSID can be specified in any order.

You can issue multiple DISPLAY commands, in which case the specifications are merged. If a range of data is specified more than once, later specifications take precedence over earlier specifications. For example, if you specify one CCSID that applies to rows 3 to 10, then specify another CCSID that applies to columns 30 to 60, the second CCSID takes effect in the area where the DISPLAY commands overlap—that is, columns 30 to 60 in rows 3 to 10.

When you exit the current Browse session, all definitions are reset (as though you had entered DISPLAY RESET).

Examples:

- To use blanks to represent characters that cannot be displayed, enter:
  ```
  DISPLAY " "
  ```
- To use a vertical bar (|) to represent characters that cannot be displayed, enter:
  ```
  DISPLAY |
  ```
- To suppress the display of carriage control characters, enter:
  ```
  DISPLAY NOCC
  ```
- To display columns 20 through 30 of lines 5 through 15 as though the data had been stored using a CCSID of UTF16:
  ```
  DISPLAY LINE 5 15 COLS 20 30 CCSID 1200
  ```
- To display lines 4 through 18 as though the data had been stored using a CCSID of UTF16, except for column 72 in lines 12 through 18, which should be displayed as though the data had been stored using a CCSID of ASCII:
  ```
  DISPLAY LINE 4 18 UTF16
  DISPLAY LINE 12 18 COLS 72 ASCII
  ```
- To revert to displaying the data as though it had been stored using the CCSID of the terminal:
  ```
  DISPLAY RESET
  ```

EDIT—edit a member

The EDIT command allows you to edit another member of the same data set. It also allows you to edit any other data set or z/OS UNIX file without ending your current Browse session.

The EDIT command has this syntax:

```
►►─EDIT──┬──────────┬──────────────────────────────────────────►◄
         └─member───┘
```

where:

member An optional member of the ISPF library or other partitioned data set that you are currently browsing. You may enter a member pattern to generate a member list.

For example, if you were browsing a member of library ISPFDEMO.XXX.COBOL, you could enter this command to display the panel shown in Figure 64 on page 80:

```
EDIT CBLMAIN
```

If you do not specify a member name, the Edit Command - Entry Panel is displayed.

You end a nested Edit session the same way you would a normal one. When you end the nested Edit session, the current Browse session resumes.

FIND—find character strings

The FIND command allows you to find a specified character string. The syntax of the FIND command is:

```
                                  ┌─NEXT──┐   ┌─CHARS──┐
►►─FIND─string─┬──────────┬─┬─────┬─┬─────┬─┬─────┬─┬──────────────────────┬──►◄
               ├─UTF8─────┤ │ALL  │ │PREFIX│ │SUFFIX│ └─left_col─right_col─┘
               ├─ASCII────┤ │FIRST│ │SUFFIX│ │WORD  │
               └─USASCII──┘ │LAST │ │WORD  │
                            └─PREV┘ └──────┘
```

Note: FIND as a Browse command, shown here, has the same syntax as FIND as an Edit command, except the optional X/NX/EX and line range operands are not included.

where:

string Required operand. The character string you want to find.

NEXT | ALL | FIRST | LAST | PREV
Optional operands that define the starting point, direction, and extent of the search. NEXT is the default.

CHARS | PREFIX | SUFFIX | WORD
Optional operand. Operands that set the conditions for a character string match. CHARS is the default.

UTF8 | ASCII | USASCII
Optional operand which specifies that the FIND string is either a UTF8, ASCII, or USASCII character string. This form of the FIND command is only available for the character FIND command, and only for UTF8, ASCII, or USASCII strings.

left_col and right_col
Optional operands. Numbers that identify the columns the FIND command is to search.

You can separate the operands with blanks or commas and you can type them in any order, but *right_col*, if typed, must follow *left_col*.

Specifying find strings: The string operand specifies the characters to be found. For examples of different string formats, refer to the description of the FIND command in *z/OS ISPF Edit and Edit Macros*.

The default is not to differentiate between uppercase and lowercase characters when searching. Except for the character (C) string, differences between uppercase and lowercase strings are ignored. For example, this command:

```
FIND ALL 'CONDITION NO. 1'
```

successfully finds any of these:

```
CONDITION NO. 1
Condition No. 1
condition No. 1
condition no. 1
```

Omitting string delimiters:

Generally, you enter the strings without delimiters. For example, to find all occurrences of ABC, enter:

```
FIND ALL ABC
```

Using string delimiters: You must use delimiters if a string contains embedded blanks or commas, or if a string is the same as a command keyword. You delimit strings with either apostrophes (') or quotation marks ("). For example, to find the next occurrence of `every one`, enter:

```
FIND 'every one'
```

The FIND command does not find the apostrophe or quotation mark string delimiters.

Note: The Browse FIND command does not work with a search argument that contains the command delimiter, even if string delimiters are used. You can specify a hexadecimal search string or use ISPF Option 0 to change the command delimiter to a different character.

Starting point, direction, and extent of search: You can control the starting point, direction, and extent of the search by using one of these operands:

NEXT The scan starts at the first position after the current cursor location and searches ahead to find the next occurrence of the string. NEXT is the default.

ALL The scan starts at the top of the data and searches ahead to find all occurrences of the string. A message in the upper-right corner of the screen shows the number of occurrences found. The second-level message that is displayed when you enter the HELP command shows which columns were searched.

FIRST The scan starts at the top of the data and searches ahead to find the first occurrence of the string.

LAST The scan starts at the bottom of the data and searches backward to find the last occurrence of the string.

PREV The scan starts at the first position before the current cursor location and searches backward to find the previous occurrence of the string.

If you specify FIRST, ALL, or NEXT, the direction of the search is forward; pressing the RFIND function key (F5/17) finds the next occurrence of the designated string. If you specify LAST or PREV, the direction of the search is backward; pressing the RFIND function key finds the previous occurrence of the string. The other optional operands remain in effect, as specified in the last FIND command. These operands include CHARS, WORD, PREFIX, SUFFIX, and *left_col*, *right_col*.

The search proceeds until one or all occurrences of the string are found, or until the end of data is found. If the string is not found, one of these actions takes place:

- If the FIND command was entered on the Command line, a `NO string FOUND` message is displayed in the upper-right corner of the screen.
- If the FIND command was repeated using the RFIND command, either a `BOTTOM OF DATA REACHED` message or a `TOP OF DATA REACHED` message is displayed, depending on the direction of the search. When these messages appear, you can press the RFIND function key again to continue the search by wrapping to the top or bottom of the data. If the string is still not found anywhere in the data, a `NO string FOUND` message is displayed.

Conditions for character string matches: The operands CHARS, PREFIX, SUFFIX, and WORD control the conditions for a successful match with the string based on whether the data string begins and/or ends with a non-alphanumeric character; that is, a special character or a blank. You can abbreviate PREFIX, SUFFIX, and CHARS to PRE, SUF, and CHAR, respectively.

In this example, the highlighted strings would be found and the strings that are not highlighted would be ignored:

```
CHARS 'DO'  - DO DONE ADO ADOPT 'DO' +ADO (DONE) ADO-

PREFIX 'DO' - DO DONE ADO ADOPT 'DO' +ADO (DONE) ADO-

SUFFIX 'DO' - DO DONE ADO ADOPT 'DO' +ADO (DONE) ADO-

WORD 'DO'   - DO DONE ADO ADOPT 'DO' +ADO (DONE) ADO-
```

If you do not specify an operand, the default is CHARS.

Using text strings: Text strings are processed exactly the same as delimited strings. They are provided for compatibility with prior versions of the product.

Using character strings: A character string, which may be used as a string operand in a FIND command, requires that the search be satisfied by an exact character-by-character match. Lowercase alphabetic characters match only with lowercase alphabetic characters and uppercase alphabetic characters match only with uppercase.

If you specify a text string that contains any SO or SI characters, the string is considered a character string.

Specifying the keyword UTF8, ASCII, or USASCII with this form of the FIND command will find occurrences of 'string' within the data being browsed, where 'string' has been stored in the corresponding CCSID format.

Examples:

To find the next occurrence of the characters `XYZ` only if they are in uppercase:

```
FIND C'XYZ'
```

To find the next occurrence of the characters `xyz` only if they are in lowercase:

```
FIND C'xyz'
```

To find the next occurrence of the UTF8 string 'Found' (but not 'FOUND', 'found', or 'FoUnD'):

```
FIND  C'Found' UTF8
```

Using picture strings: A picture string used as a string operand in a FIND command allows you to search for a particular type of character, without regard for the specific character involved. You can use special characters within the picture string to represent the type of character to be found, as follows:

String	Meaning
P'='	Any character
P'¬'	Any nonblank character
P'.'	Any nondisplayable (invalid) character
P'#'	Any numeric character (0-9)
P'-'	Any nonnumeric character
P'@'	Any alphabetic character (uppercase or lowercase).

String	Meaning
P'<'	Any lowercase alphabetic character
P'>'	Any uppercase alphabetic character
P'$'	Any special character (not alphabetic or numeric).

If an APL or TEXT keyboard is being used, this additional character can be used in a picture string:

P'⍠ '	Any APL-specific or TEXT-specific character
P'_'	Any underscored alphabetic APL character and delta.

Only the special characters listed are valid within a picture string, but the string can include alphabetic or numeric characters that represent themselves.

A DBCS subfield cannot be specified as the subject of a picture string for the FIND command.

Examples of picture strings:

P'###'	A string of 3 numeric characters
P'¬ ¬'	Any 2 nonblank characters separated by a blank
P'.'	Any nondisplayable character
P' #'	A blank followed by a numeric character
P'#AB'	A numeric character followed by `'AB'`.

Examples of FIND commands using picture strings:

FIND P'.'	Find next nondisplayable character
FIND P'¬' 72	Find next nonblank character in column 72
F P' ¬' 1	Find the next line with a blank in column 1 followed by a nonblank.

When you use the special characters `'='` or `'.'` and a nondisplayable character is found, a hexadecimal representation is used in the confirmation message that appears in the upper-right corner of the screen. For example:

```
FIND P'..'
```

could result in the message `CHARS X'0205' FOUND`.

Column limitations: The *left_col* and *right_col* operands allow you to search only a portion of each line, rather than the complete line. These operands, which are integers separated by a comma or by at least one blank, show the starting and ending columns for the search. These rules apply:

- If you specify neither *left_col* nor *right_col*, the search continues across all columns within the current boundary columns.
- If you specify *left_col* without *right_col*, the string is found only if it starts in the specified column.
- If you specify both *left_col* and *right_col*, the complete string, not just part of it, must be within the specified columns.

Using RFIND: The RFIND command, which is usually assigned to the F5/17 key, allows you to repeat the previous FIND command without retyping it. Therefore, you can use this command to find successive occurrences of the string specified in the last FIND command. You can also use the RFIND command to return to the top of your data and continue searching when the `BOTTOM OF DATA REACHED` message appears. If you enter the RFIND command on the Command line instead of using a function key, you must position the cursor to the desired starting location before pressing Enter.

If you specify a 1-byte hexadecimal string as the FIND string and the string is found at the second byte of a double-byte character set (DBCS) character, hardware sets the cursor to the first byte of the character. If you then request RFIND, the same data is found again. To find the next occurrence of the string, you must move the cursor to the next character position before requesting RFIND again.

HEX—display data in hexadecimal format

The HEX command causes data to be displayed in hexadecimal format. The syntax of the command is:

```
                  ┌VERT┐
►►─HEX──┬─ON──────┴────┴──────────────────────────────────────────►◄
        │
        ├─VERT──────────┤
        ├─DATA──────────┤
        └─OFF───────────┘
```

You can specify the operands in any order:

where:

ON Turns hexadecimal mode on. This is the default.

OFF Turns hexadecimal mode off.

VERT Valid only when hexadecimal mode is ON. This is the default. Figure 66 shows how VERT causes the hexadecimal representation to be displayed vertically, two rows per byte, under each character.

DATA Valid only when hexadecimal mode is ON. Figure 67 on page 91 shows how DATA causes the hexadecimal representations to be displayed as a string of hexadecimal characters, two per byte. Because the hexadecimal string is twice the length of the data string, it occupies two rows. If you omit this operand, VERT is assumed.

When using browse and placing the cursor anywhere within the record, SCROLL UP positions the data where the cursor is located as the last complete line record on the display. A complete line record consists of the standard character form line, two hexadecimal character lines, and a separator line.

For example, this command would display the hexadecimal notation vertically:

```
HEX VERT
```

Three lines are displayed for each source line. The first line shows the data in standard character form. Figure 66 shows the next two lines with the same data in vertical hexadecimal representation. A separator line is displayed between the two representations to make it easier for you to read the data.

```
   Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE -- USERID.PRIVATE.SCRIPT(BHEX) - 01.00 ------ Line 00000000 Col 001 076
******************************** Top of Data  ********************************


 ------------------------------------------------------------------------------
:H3 ID=BRHEX SUBJECT='BROWSE COMMANDS - HEX'.
7CF4CC7CDCCE4EECDCCE77CDDEEC4CDDDCDCE464CCE74
A83094E2985702421533ED2966250364415420008 57DB
 ------------------------------------------------------------------------------
HEX - DISPLAYING DATA IN HEXADECIMAL FORMAT
CCE464CCEDDCECDC4CCEC4CD4CCECCCCCDCD4CDDDCE
85700049273189570413109508571453941306694 13
 ------------------------------------------------------------------------------
:P.THE DISPLAY OF DATA IN HEXADECIMAL NOTATION IS CONTROLLED BY THE HEX
7D4ECC4CCEDDCE4DC4CCEC4CD4CCECCCCCDCD4DDECECDD4CE4CDDEDDDDCC4CE4ECC4CCE
A7B385049273180660413109508571453941305631396509203653963354028038508 57
 ------------------------------------------------------------------------------


 Command ===> ________________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 66. Browse hexadecimal display - vertical (ISRBROBA)

To display the hexadecimal notation horizontally, use this command:

```
HEX DATA
```

Figure 67 on page 91 shows the next two lines with the same data in DATA hexadecimal representation.

```
   Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE -- USERID.PRIVATE.SCRIPT(BHEX) - 01.00 ------ Line 00000000 Col 001 076
********************************** Top of Data  **********************************


 ------------------------------------------------------------------------------
:H3 ID=BRHEX SUBJECT='BROWSE COMMANDS - HEX'.
7AC8F340C9C47EC2D9C8C5E740E2E4C2D1C5C3E37E7DC2D9D6E6E2C540C3D6D4D4C1D5C4E2406040
C8C5E77D4B
 ------------------------------------------------------------------------------
HEX - DISPLAYING DATA IN HEXADECIMAL FORMAT
C8C5E7406040C4C9E2D7D3C1E8C9D5C740C4C1E3C140C9D540C8C5E7C1C4C5C3C9D4C1D340C6D6D9
D4C1E3
 ------------------------------------------------------------------------------
:P.THE DISPLAY OF DATA IN HEXADECIMAL NOTATION IS CONTROLLED BY THE HEX
7AD74BE3C8C540C4C9E2D7D3C1E840D6C640C4C1E3C140C9D540C8C5E7C1C4C5C3C9D4C1D340D5D6
E3C1E3C9D6D540C9E240C3D6D5E3D9D6D3D3C5C440C2E840E3C8C540C8C5E7
 ------------------------------------------------------------------------------




Command ===> ____________________________________________________ Scroll ===>
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 67. Browse hexadecimal display - data (ISRBROBA)

You can use the FIND command to find invalid characters or any specific hexadecimal character regardless of the setting of hexadecimal mode. See the syntax for picture strings and hexadecimal strings under the description of the FIND command in *z/OS ISPF Edit and Edit Macros*.

LOCATE—locate lines

Use the LOCATE command to bring a particular line to the top of the display. You can identify the line by either its relative line number or a previously defined label.

During Browse, the current position of the screen window is shown by the line/column numbers in the upper-right corner of the screen. The line number refers to the first line of data following the two header lines, and shows the relative position of that line in the data. The `Top of Data` message is treated as relative line zero. You must enter either a line number or a label as an operand.

```
►►─LOCATE──┬─line-number─┬──────────────────────────────────────────►◄
           └─label───────┘
```

where:

line-number A numeric value of up to 8 digits that shows the position of the line from the beginning of the data. The line number is displayed in the upper-right corner.

label Defined by scrolling to the top of the screen the line with which you want to associate the label. You then type the label on the command line in the form:

`.ccccccc`

For example, to find line 18463, you could enter this command:

```
LOCATE 18463
```

ISPF then moves line 18463 to the top of the screen. You can assign a label to it by entering:

```
.label
```

The label is a period followed by up to seven characters that can be displayed, except the comma and the space. It is treated as an internal symbol and is equated to the top line on the screen. You are required to specify the period when you define the label. The next time you want to find this line, you can enter:

```
LOCATE .label
```

The period is usually optional when you use it as an operand in a LOCATE command. However, if the first character in the label is a number, you must specify the period to distinguish the label from a line number.

The latest assignment of a label overrides any previous assignments. You can assign several labels to the same line. Labels are not retained when you leave the Browse option.

RESET—remove the column-identification line

The RESET command removes the column-identification line that you can display by using the COLUMNS command (see page 82). This command has no operands.

SUBMIT—submit a job stream for background execution

The SUBMIT command is used to submit a job stream that is being browsed. If the data set being browsed is modified and saved by another user or by the same user on another screen, the SUBMIT command will submit the updated data set, not the copy being browsed. The TSO SUBMIT command is invoked directly to submit the job stream, so the data set has to be fixed-record format with a record length of 80.

Note: The Browse SUBMIT command is not supported if the underlying data is packed.

VIEW—view a member

The VIEW command allows you to view another member of the same data set. It also allows you to view any other data set or z/OS UNIX file without ending your current Browse session.

The VIEW command has this syntax:

```
►►─VIEW──┬──────────┬──────────────────────────────────────────►◄
         └─member───┘
```

where:

member An optional member of the ISPF library or other partitioned data set that you are currently browsing. You may enter a member pattern to generate a member list.

For example, if you were browsing a member of library ISPFDEMO.XXX.COBOL, you could enter this command to display the panel shown in Figure 64 on page 80:

```
VIEW CBLMAIN
```

If you do not specify a member name, the View Command - Entry Panel is displayed.

You end a nested View session the same way you would a normal one. When you end the nested View session, the current Browse session resumes.

Chapter 4. Edit (option 2)

The Edit option (2) allows you to create, display, and change data stored in ISPF libraries, other partitioned or single-volume or multivolume sequential data sets, or z/OS UNIX files with these characteristics:

- Record Format (RECFM):
  - Fixed or variable (non-spanned)
  - Blocked or unblocked
  - With or without printer control characters
- Logical Record Length (LRECL):
  - From 1 to 32 760, inclusive, for fixed-length records
  - From 5 to 32 756, inclusive, for variable-length records.
- VSAM data
  - VSAM data can be edited if the ISPF Configuration table has been customized to enable VSAM support (that is, VSAM_EDIT_ENABLED is set to "YES").

    Note: When VSAM support is enabled, the default value for VSAM_EDIT_COMMAND is "FMNMAIN DSE /". If the command is not available, IKJ56500I COMMAND FMNMAIN NOT FOUND, is issued as a TSO message.
- z/OS UNIX files.

Editing a data set

When you select the Edit option, the Edit Entry Panel shown in Figure 68 is displayed.

```
  Menu  RefList  RefMode  Utilities  Workstation  Help
 ------------------------------------------------------------------------------
                                Edit Entry Panel

 ISPF Library:
    Project . . . MYPROJ
    Group . . . . DEV      . . . ________ . . . ________ . . .
    Type  . . . . SOURCE
    Member  . . . ________        (Blank or pattern for member selection list)

 Other Partitioned, Sequential or VSAM Data Set, or z/OS UNIX file:
    Data Set Name . . . ____________________________________________________
    Volume Serial . . . ______    (If not cataloged)

 Workstation File:
    File Name . . . . . ____________________________________________________
                                         Options
 Initial Macro  . . . . ________         /  Confirm Cancel/Move/Replace
 Profile Name . . . . . ________         _  Mixed Mode
 Format Name  . . . . . ________         _  Edit on Workstation
 Data Set Password  . .                  _  Preserve VB record length
 Record Length  . . . . _____            _  Edit ASCII data
 Command ===> ___________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 68. Edit Entry panel (ISREDM01)

© Copyright IBM Corp. 1980, 2007

Edit Entry Panel action bar

The Edit Entry Panel action bar choices function as follows:

Menu See the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I* for information about the Menu pull-down.

RefList See the Using Personal Data Set Lists and Library Lists topic in the *z/OS ISPF User's Guide Vol I* for information about referral lists.

RefMode See the details about Personal List Modes in the Using Personal Data Set Lists and Library Lists topic in the *z/OS ISPF User's Guide Vol I* for information about referral list modes.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Workstation Configure ISPF workstation tool integration.

Help The Help pull-down provides general information about the Edit environment as well as information about the main options and edit commands.

Edit Entry Panel fields

You can specify a concatenated sequence of up to four ISPF libraries, but the libraries must have been previously allocated to ISPF with the Data Set utility (3.2).

The fields on this panel are:

Project The common identifier for all ISPF libraries belonging to the same programming project.

Group The identifier for the particular set of ISPF libraries; that is, the level of the libraries within the library hierarchy.

You can specify a concatenated sequence of up to four existing ISPF libraries.

The editor searches the ISPF libraries in the designated order to find the member and copies it into working storage. If the editor does not find the member in the library, it creates a new member with the specified name.

When you save the edited member, the editor places or replaces it in the first ISPF library in the concatenation sequence, regardless of which library it was copied from.

Type The identifier for the type of information in the ISPF library.

Member The name of an ISPF library or other partitioned data set member. Leaving this field blank or entering a pattern causes PDF to display a member list. See *z/OS ISPF User's Guide Vol I* if you need information about entering patterns.

Name Any fully qualified data set name or z/OS UNIX file path name.

For more details about the Name field, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

Volume Serial A real DASD volume or a virtual volume residing on an IBM 3850

Mass Storage System. To access 3850 virtual volumes, you must also have MOUNT authority, which is acquired through the TSO ACCOUNT command.

Workstation File:
If you have made a connection to the workstation, you can specify a workstation file name, for example C: \AUTOEXEC.BAT, in this field.

Initial Macro You can specify a macro to be processed before you begin editing your sequential data set or any member of a partitioned data set. This initial macro allows you to set up a particular editing environment for the Edit session you are beginning. This initial macro overrides any IMACRO value in your profile.

If you leave the Initial Macro field blank and your edit profile includes an initial macro specification, the initial macro from your edit profile is processed.

If you want to suppress an initial macro in your edit profile, type `NONE` in the Initial Macro field. See the topics about Initial Macros and the IMACRO primary command in the *z/OS ISPF Edit and Edit Macros* for more details.

Profile Name The name of an edit profile, which you can use to override the default edit profile. See the topics about Edit Profiles and the edit environment in the *z/OS ISPF Edit and Edit Macros*.

Format Name The name of a format definition or blank if no format is to be used.

Data Set Password
The password for OS password-protected data sets. This is not your RACF password.

Record Length
Applicable when editing a z/OS UNIX file. ISPF normally treats z/OS UNIX files as having variable length records. This field allows you to specify a record length which is used by the editor to load the records from the file into the edit session as fixed-length records. When the file is saved, it is saved with fixed-length records. The Record Length field allows you to convert a variable-length file to fixed length. The value specified in this field must be able to accommodate the largest record in the file. If the editor finds a record that is larger than the length specified, an error message is displayed and the edit session does not proceed.

Confirm Cancel/Move/Replace
When you select this field with a "/", a confirmation panel displays when you request one of these actions, and the execution of that action would result in data changes being lost or existing data being overwritten.

- For MOVE, the confirm panel is displayed if the data to be moved exists. Otherwise, an error message is displayed.
- For REPLACE, the confirm panel is displayed if the data to be replaced exists. Otherwise, the REPLACE command functions like the edit CREATE command, and no confirmation panel is displayed.

- For CANCEL, the confirmation panel is displayed if any data changes have been made, whether through primary commands, line commands, or typing.

  Note: Any commands or data changes pending at the time the CANCEL command is issued are ignored. Data changes are "pending" if changes have been made to the displayed edit data, but no interaction with the host (ENTER, PF key, or command other than CANCEL) has occurred. If no other changes have been made during the edit session up to that point, the confirmation panel is not displayed.

Mixed Mode When you select this field with a "/", it specifies that the editor look for shift-out and shift-in delimiters surrounding DBCS data. If you do not select it, the editor does not look for mixed data.

Edit on Workstation
You can select this option to use your workstation as the editing environment for whichever host data set or workstation file you want to edit.

Preserve VB record length
When you select this field with a "/", it specifies that the editor store the original length of each record in variable-length data sets and when a record is saved, the original record length is used as the minimum length for the record. The minimum length can be changed using the SAVE_LENGTH edit macro command. The editor always includes a blank at the end of a line if the length of the record is zero or eight.

Edit ASCII data
You can use this option when editing a z/OS UNIX file containing data encoded in ASCII and the file is not tagged with a CCSID of 819. You can also speicy this option when creating a new file containing ASCII data. When you select this field with a "/", the editor renders the ASCII data readable by converting the data to the CCSID of the terminal. Also, the editor breaks up the data into records using the ASCII linefeed character (X'0A') and the ASCII carriage return character (X'0D') as the record delimiter. The linefeed and carriage return characters are removed from the data loaded into the editor but written back to the file when the data is saved. It is not necessary to use this option when the file is tagged with a CCSID of 819. If ISPF detects the file is tagged with CCSID 819, it converts the data from ASCII to the CCSID of the terminal. When the file is saved, ISPF ensures the file is tagged with a CCSID of 819.

Distributed editing

If you have made a connection to the workstation, you can also specify a workstation file name such as C: \AUTOEXEC.BAT on the Edit Entry Panel. Or you can specify which environment (host or workstation) should be used to edit a data set. With these options, one of four editing situations can occur:

- Edit a host data set on the host
- Edit a host data set on the workstation
- Edit a workstation file on the host
- Edit a workstation file on the workstation.

Edit a Host Data Set on the Host
The editor searches the ISPF libraries in the designated order to find the member and copy it into working storage. If you specified a nonexistent member of an ISPF library, a new member is created with the specified name.

When you save the edited member, the editor places or replaces it in the first ISPF library in the concatenation sequence, regardless of which library it was copied from.

Edit a Host Data Set on the Workstation
The editor searches the ISPF libraries in the designated order to find the member and copy it into working storage. The data set name is converted to a workstation file name, and that name is appended to the workstation's current working directory. The host data set is transferred to the workstation, and the working file is then passed to the user's chosen edit program.

When you finish the edit session, the working file is transferred back to the host and stored in the first ISPF library in the concatenation sequence.

Edit a Workstation File on the Host
The editor searches the workstation files to find the desired file and copy it into working storage. The workstation file name is converted to a host data set name, and, if greater than 44 characters, it is truncated to be 44. The workstation file is transferred to the host, where you can edit it.

When you finish the edit session, the working file is transferred back to the workstation and stored.

Edit a Workstation File on the Workstation
This edit proceeds as it normally does on your workstation.

Note: Some file names are reserved or restricted depending on the workstation operating system. An attempt to edit a file name that is reserved or restricted by your operating system might cause your workstation operating system or host system to hang. See your workstation operating system documentation to learn restricted or reserved file names.

Double-byte character set support

The ISPF editor supports DBCS alphabets in two ways:

- Formatted data where DBCS characters are in the column positions specified in the format definition created with the Format Utility (option 3.11)
- Mixed characters delimited with the special shift-out and shift-in characters.

  If you are using mixed mode and the record length of a data set is greater than 72 bytes, there is a possibility that a DBCS character might encroach on the display boundary. Here, PDF attempts to display the other characters by replacing an unpaired DBCS character byte with an SO or SI character. If there is a possibility that the replaced SO or SI character was erased, the line number of the line is highlighted. If you change the position of the SO and SI characters on the panel, or if you delete the SO and SI characters entirely, the DBCS character on the boundary is removed to keep the rest of the data intact.

Chapter 5. Utilities (option 3)

The Utilities option (3) provides a variety of functions for library, data set, and catalog maintenance, each of which is described in this topic. The Utility Selection Panel is shown in Figure 69.

```
  Menu  Help
 ------------------------------------------------------------------------------
                            Utility Selection Panel

 1  Library     Compress or print data set.  Print index listing.  Print,
                  rename, delete, browse, edit or view members
 2  Data Set    Allocate, rename, delete, catalog, uncatalog, or display
                  information of an entire data set
 3  Move/Copy   Move, or copy members or data sets
 4  Dslist      Print or display (to process) list of data set names.
                  Print or display VTOC information
 5  Reset       Reset statistics for members of ISPF library
 6  Hardcopy    Initiate hardcopy output
 7  Transfer    Download ISPF Client/Server or Transfer data set
 8  Outlist     Display, delete, or print held job output
 9  Commands    Create/change an application command table
 11 Format      Format definition for formatted data Edit/Browse
 12 SuperC      Compare data sets                            (Standard Dialog)
 13 SuperCE     Compare data sets Extended                   (Extended Dialog)
 14 Search-For  Search data sets for strings of data         (Standard Dialog)
 15 Search-ForE Search data sets for strings of data Extended (Extended Dialog)
 16 Tables      ISPF Table Utility
 17 Udlist      Print or display (to process) z/OS UNIX directory list
 Option ===>  ____________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 69. Utility Selection Panel (ISRUTIL)

Utility Selection Panel action bar

The Utility Selection Panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down provides information about each available choice on the Utilities Menu.

Library utility (option 3.1)

When you select this option, a panel is displayed (Figure 70 on page 102) that allows you to specify a data set and an action to be performed. The Library utility is intended primarily for maintenance of partitioned data sets. However, the print index listing (X), print entire data set (L), data set information (I), and short data set information (S) functions also apply to sequential data sets.

© Copyright IBM Corp. 1980, 2007

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                                Library Utility
                                                                   More:     +
blank Display member list      I Data set information          B Browse member
    C Compress data set        S Short data set information    D Delete member
    X Print index listing      E Edit member                   R Rename member
    L Print entire data set    V View member                   P Print member

                                   Enter "/" to select option
ISPF Library:                      /  Confirm Member Delete
   Project . . . MYPROJ            _  Enhanced Member List
   Group . . . . DEV      . . . ________ . . . ________ . . . ________
   Type  . . . . SOURCE
   Member  . . . ________     (If B, D, E, P, R, V, or blank selected)
   New name  . . ________     (If R selected)

Other Partitioned or Sequential Data Set:
   Data Set Name . . . ______________________________________________
   Volume Serial . . . ________  (If not cataloged)

Option ===> ______________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 70. Library Utility panel (ISRUDA1)

Library Utility panel action bar

The Library Utility panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

RefList
For information about referral lists, see the details about Using Personal Data Set Lists and Library Lists in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down provides information on the options available for processing libraries and members, including compressing and printing partitioned data sets, displaying data set information and member lists, and printing, renaming, deleting, browsing, editing, and viewing members.

Library Utility panel fields

All the fields on the Library Utility panel, with the exception of the "New name" field, are discussed in the Libraries and Data Sets topic in the *z/OS ISPF User's Guide Vol I*. The "New name" field is required when option R (rename member) is chosen; the field must contain the new member name. See "R — rename member" on page 112 for more information about this option.

Library utility options for data sets

The topics listed here describe the options shown on the left side of the Library Utility panel shown in Figure 70. These options are used to work with data sets.

- "Blank — (display member list)" on page 103
- "C — compress data set" on page 103

- "X — print index listing" on page 104
- "L — print entire data set" on page 104
- "I — data set information" on page 104
- "S — short data set information" on page 108

Blank — (display member list)

If you leave the Option field blank, you must specify a partitioned data set. ISPF displays a member list when you press Enter. For more information, see the details about Using Member Selection Lists and Library and Data Set List Utility Line Commands in the Libraries and Data Sets topic in the *z/OS ISPF User's Guide Vol I*.

Notes:

1. The column headers on a member list display (with the exception of Rename) are point-and-shoot sort fields.
2. If you enter a slash in the 1-character or 9-character command field, the Member List Commands pop-up window shown in Figure 71 is displayed so that you can select the command you want to use.
3. The 1-character or 9-character line command field is a point-and-shoot field. If you select the line command field beside a member name, the Member List Commands pop-up window shown in Figure 71 is displayed so that you can select the command you want to use. In addition, you can enter commands (for example, TSO) directly in the 9-character field.
4. You can *chain* the P, R, D, V, E, and B commands; that is, you can select multiple members from a member list for various processing tasks. Use the CANCEL command (from a View, Browse, or Edit session) to break the chain and return to the member list.

```
  Menu  Functions  Confirm  Utilities  Help
_ ┌──────────────────────────────────────────────────┐ ──────────────────────
  │ ISRCMLEP    Action for Member TEST               │     Row 00001 of 00001
  │                                                  │ anged            ID
/ │ Member Action                                    │ 08 13:32:15    GRAHAMP
  │   __   1.  Edit              8.  Copy            │
  │        2.  View              9.  Reset           │
  │        3.  Browse            10. Open   Edit     │
  │        4.  Delete            11. Submit          │
  │        5.  Rename            12. TSO Cmd         │
  │        6.  Print             13. WS Cmd          │
  │        7.  Move              14. Select **None** │
  │                                                  │
  │ Prompt Action . . ________  (For prompt field)   │
  │                                                  │
  │ Select a choice and press ENTER to continue      │
  │  F1=Help         F2=Split        F3=Exit         │
  │  F7=Backward     F8=Forward      F9=Swap         │
  └──────────────────────────────────────────────────┘


Command ===>                                                Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 71. Member list commands pop-up window (ISRCMLEP)

C — compress data set

If you select option C, you can specify any partitioned data set. The compress function is not valid for a PDSE. The compress is accomplished by calling either of these:

- The IEBCOPY utility
- An optional compress request exit routine, which can be specified by your installation.

Using this option can change an existing data set allocation to *exclusive*.

ISPF allocates the IEBCOPY SYSUT3 and SYSUT4 data sets as one primary cylinder, one secondary cylinder. If this is not sufficient for your compress request, these DDNAMES can be preallocated.

X — print index listing

If you select option X, you must specify either a DASD-resident sequential or partitioned data set. The index listing is recorded in the ISPF list data set. For a partitioned data set, the index listing includes general information about the data set followed by a member list. For a sequential data set, the index listing includes general information only. See the topic about Listing Formats in *z/OS ISPF User's Guide Vol I* for examples of the index listing format for source libraries and load libraries.

Notes:

1. A volume serial is not allowed for multivolume data sets using option X.
2. If ISPF was entered in TEST mode, the listing also includes TTR data for each member of the data set. This data is the track and record address, where the members reside on the volume.

L — print entire data set

If you select option L, you must specify either a DASD-resident sequential or partitioned data set. The allowable data set characteristics are the same as for Browse, except that data sets with a logical record length greater than 300 characters are not printed. Also, the data should not contain any printer control characters. Use the Hardcopy utility (option 3.6) to print data sets that contain printer control characters. A source listing of the complete data set (including all members of a partitioned data set), preceded by an index listing, is recorded in the ISPF list data set.

Notes:

1. A volume serial is not allowed for multivolume data sets using option L.
2. The page-numbering format of the ISPF list data set is PAGE: XX of YY. The YY value is calculated using the data set member's current size statistic. When the member's current size is larger than the actual member size, the result is PAGE: XX of YY, where YY is a page number greater than the last value of XX. When the size statistic is smaller than the actual member size, the result is PAGE: XX of YY, until the actual size number XX exceeds YY. Then the result is PAGE: XX, until the end of the member is processed.

I — data set information

If you select option I, the location, characteristics, and current space utilization of the specified data set are displayed. The format ISPF uses to display data set information when DFSMSdfp is not installed or is not available, or when the Storage Management Subsystem is not active, is shown in "U — uncatalog data set" on page 123. See "Information for managed data sets" on page 107 to see how ISPF displays data set information when these products are installed, available, and active.

For sequential data sets, options I and S display the same information. For multivolume data sets, options I and S display current allocation and utilization

values that represent totals from all volumes used. You may not enter a volume serial when you are requesting information on a multivolume data set.

Notes:

1. The space for data sets allocated in blocks is calculated as if all of the tracks, including the last one, contain only full blocks of data. Any partial "short" blocks are ignored.
2. The information shown for current space utilization is the actual data that the data set contains, based on the number of allocation units (blocks, tracks, bytes, megabytes, and so on) that have been written. For a data set allocated in units other than tracks and cylinders, it does not include the unused portion of a track that is only partially filled.

   For example, if a data set allocated in bytes with block size of 600 has one block written to a device with a track size of 1000, 600 bytes of data are written and the remaining 400 bytes cannot be used by a different data set. A track is the smallest possible unit of physical allocation to a data set on DASD. ISPF reports 600 bytes used while other products (such as ISMF) report 1000 bytes used. ISPF reports the space occupied by data in the data set. ISMF reports the space used by this data set that is not available for use by another data set. The difference is a relative indication of the effectiveness of the block size used when the data set was created.

```
                              Data Set Information

Data Set Name . . . . : MYPROJ.DEV.SOURCE

General Data                            Current Allocation
 Management class . . : STANDARD         Allocated cylinders : 1
 Storage class  . . . : BASE             Allocated extents . : 1
  Volume serial . . . : MVS8WF           Maximum dir. blocks : 20
  Device type . . . . : 3390
 Data class . . . . . : **None**
  Organization  . . . : PO              Current Utilization
  Record format . . . : FB               Used cylinders  . . : 1
  Record length . . . : 80               Used extents  . . . : 1
  Block size  . . . . : 27920            Used dir. blocks  . : 1
  1st extent cylinders: 1                Number of members . : 1
  Secondary cylinders : 1
  Data set name type  : PDS

  Creation date . . . : 2002/07/08       Referenced date . . : 2002/07/23
  Expiration date . . : ***None***

Command ===> _____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 72. Data Set Information panel (ISRUAIP)

If the volume serial is followed by a plus (for example, HSM016+), the data set spans multiple volumes. Press Enter to display a list of all allocated volumes that have been used, as shown in Figure 73 on page 106.

```
                              Data Set Information
                 Volume Information
D
G   All allocated volumes:                                ocation
                                 More:     +            cylinders . :        154
    Number of volumes                                   extents . . :          7
      allocated: 2                                      r. blocks . :        700

     HSM016  HSM107                                     lization
    Command ===>                                        ders  . . . . :      151
                                                        ts  . . . . :          7
     F1=Help      F2=Split     F3=Exit                 blocks  . . :        514
     F7=Backward  F8=Forward   F9=Swap

  Expiration date  . . : ***None***

    To display multiple volumes press Enter or enter Cancel to Exit.

Command ===>
 F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
 F9=Swap       F12=Cancel
```

Figure 73. Volume Information for a Multivolume Data Set (ISRUAMVI)

The “Allocated units” and “Used units” fields can vary, depending on the value that was specified in the “Space units” field when you allocated the data set. For example, Figure 73 shows what the Data Set Information panel would look like if the data set was allocated by specifying Cylinders in the “Space units” field.

If directory block information is not available, the Data Set Information panel shows a value of `0 *` for the “Maximum dir. blocks”, “Used dir. blocks”, and “Number of members” fields. The asterisk beside the zero refers you to a note on the panel, which states that the directory is unavailable.

If the data set is a PDS, ISPF must open it to retrieve the directory information. This updates the referenced date for the next time option I is displayed.

If the data set is a PDSE, the “Data set name type” field is LIBRARY and the “Maximum dir. blocks” field is NOLIMIT. Because the used blocks, used extents, and used directory blocks are not applicable to a PDSE, the Data Set Information panel replaces these values with “Used pages” and “% Utilized” (Figure 74 on page 107). Other values that can appear in the “Data set name type” field are:

- HFS - MVS Hierarchical File System data set
- EXTENDED - DFSMSdfp Striped data set
- LARGE - Large format sequential data set

Note: When a PDSE data set is created, it sets aside five pages. This may cause a significant change to the “% Utilized” value for a small data set.

```
Session A - [24x80]
File  Edit  Transfer  Appearance  Communication  Assist  Window  Help
                              Data Set Information

Command ===> ____________________________________________________________

Data Set Name  . . . : P020136.PRIVATE.TABLES

General Data                            Current Allocation
 Management class . . : STANDARD         Allocated tracks  . : 17
 Storage class  . . . : BASE             Allocated extents . : 5
  Volume serial . . . : PRM906           Maximum dir. blocks : NOLIMIT
  Device type . . . . : 3390
 Data class . . . . . : **NONE**
  Organization  . . . : PD              Current Utilization
  Record format . . . : FB               Used pages  . . . . : 181
  Record length . . . : 80               % Utilized  . . . . : 88
  Block size  . . . . : 27920            Number of members . : 48
  1st extent tracks . : 10
  Secondary tracks  . : 10
  Data set name type  : LIBRARY

  Creation date . . . : 1999/12/06       Referenced date . . : 2000/02/04
  Expiration date . . : ***NONE***
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
                                                                  02/015
```

Figure 74. Data Set Information for PDSE Managed Data Sets (ISRUAISE)

Information for managed data sets: The Library Utility option I (Figure 75) displays information for data sets that reside on Storage Management Subsystem Volumes (also called managed data sets) when:

- DFSMSdfp is installed and available.
- Storage Management Subsystem is active.
- Directory block information is available.

```
 Menu  RefList  Utilities  Help
                         Data Set Information

 Data Set Name  . . . . . . : MYDATA2.MULTI
 General Data                                                  More:     +
    Management class  . . . :              Current Allocation
    Storage class . . . . . : STANDARD       Allocated tracks  . :       32
       Volume . . . . . . . : BASE           Allocated extents . :       32
       Device type  . . . . : HSM016 +
    Data class  . . . . . . : 3380
       Organization . . . . : MULTIVOL     Current Utilization
       Record format  . . . : PS             Used tracks . . . . :       31
       Record length  . . . : FB             Used extents  . . . :       31
       Block size . . . . . : 80
       1st extent blocks  . : 3120
       Secondary blocks . . : 17
       Data set name type . :

       Creation date  . . . :              Referenced date . . . :
 Command ===>
  F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
  F9=Swap       F12=Cancel
```

Figure 75. Data Set Information for Managed Data Sets (ISRUAISE)

If the volume serial is followed by a plus (for example, HSM016+), the data set spans multiple volumes.

Note: SMS-managed multivolume data sets will not display a plus unless data has been written past the first volume.

Press Enter to display a list of all allocated volumes as shown in Figure 76.

```
Menu  RefList  Utilities  Help
                         Data Set Information
              Volume Information
D
                                                          More:     +
G   All allocated volumes:                                Allocation
                            More:     +                  ated tracks  . :         32
                                                         ated extents . :         32
     HSM017 HSM018 HSM019 HSM020 HSM021

                                                          Utilization
                                                         tracks . . . . :         31
    Command ===>                                         extents  . . . :         31
     F1=Help      F2=Split     F3=Exit
     F7=Backward  F8=Forward   F9=Swap

      Secondary tracks . . : 17
      Data set name type . : 1

Command ===>
 F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
 F9=Swap       F12=Cancel
```

Figure 76. Volume Information for a Managed Multivolume Data Set (ISRUAMVI)

The major difference between this information and the information that is displayed for data sets on non-managed volumes is the addition of these classes:

- Management class
- Storage class
- Data class

S — short data set information

If you select option S, information about the selected data set is displayed. The information displayed by option S is the same as that displayed by option S of the Data Set utility (option 3.2), but it differs from option I in two respects. Information for partitioned data sets, when displayed by option S, lacks the number of maximum and used directory blocks, and the number of members. For sequential data sets, options I and S display the same information. You can not enter a volume serial when you are requesting information on multivolume data sets.

Notes:

1. The space for data sets allocated in blocks is calculated as if all of the tracks, including the last one, contain only full blocks of data. Any partial “short” blocks are ignored.
2. The information shown for current space utilization is the actual data that the data set contains, based on the number of allocation units (blocks, tracks, bytes, megabytes, and so on) that have been written. For a data set allocated in units other than tracks and cylinders, it does not include the unused portion of a track that is only partially filled.

For example, if a data set allocated in bytes with block size of 600 has one block written to a device with a track size of 1000, 600 bytes of data are written and the remaining 400 bytes cannot be used by a different data set. A track is the smallest possible unit of physical allocation to a data set on DASD. ISPF reports 600 bytes used while other products (such as ISMF) report 1000 bytes used. ISPF reports the space occupied by data in the data set. ISMF reports the space used by this data set that is not available for use by another data set. The difference is a relative indication of the effectiveness of the block size used when the data set was created.

Figure 77 shows a short format example of data set information for a partitioned data set. This is the short format ISPF uses to display data set information when DFSMSdfp is not installed or not available, or when the Storage Management Subsystem is not active. See "Short information for managed data sets" to see how ISPF displays data set information when these products are installed, available, and active.

```
                            Data Set Information
                                                                    More:     +
Data Set Name . . . . : MYPROJ.DEV.SOURCE

General Data                            Current Allocation
 Management class . . : STANDARD         Allocated cylinders : 1
 Storage class  . . . : BASE             Allocated extents . : 1
  Volume serial . . . : MVS8WF
  Device type . . . . : 3390
 Data class . . . . . : **None**        Current Utilization
  Organization  . . . : PO               Used cylinders  . . : 1
  Record format . . . : FB               Used extents  . . . : 1
  Record length . . . : 80
  Block size  . . . . : 27920
  1st extent cylinders: 1
  Secondary cylinders : 1
  Data set name type  : PDS

  Creation date . . . : 2002/07/08       Referenced date . . : 2002/07/31
  Expiration date . . : ***None***

Command ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 77. Short data set information (ISRUAIP)

The "Allocated units" and "Used units" fields can vary, depending on the value that was specified in the "Space units" field when you allocated the data set. For example, Figure 77 shows what the short format of the Data Set Information panel would look like if the data set was allocated by specifying CYLS in the "Space units" field.

Short information for managed data sets: The Library Utility option S displays information (Figure 78 on page 110) for data sets that reside on Storage Management Subsystem volumes (also called managed data sets) when:

- DFSMSdfp is installed and available
- Storage Management Subsystem is active.

```
Session A - [24x80]
File  Edit  Transfer  Appearance  Communication  Assist  Window  Help
                          Data Set Information

Command ===> _____________________________________________________________
                                                                More:     +
Data Set Name  . . . : P020136.PRIVATE.TABLES

General Data                          Current Allocation
 Management class . . : STANDARD       Allocated tracks  . : 17
 Storage class  . . . : BASE           Allocated extents . : 5
  Volume serial . . . : PRM906
  Device type . . . . : 3390
 Data class . . . . . : **NONE**
  Organization  . . . : PD            Current Utilization
  Record format . . . : FB             Used pages  . . . . : 181
  Record length . . . : 80             % Utilized  . . . . : 88
  Block size  . . . . : 27920
  1st extent tracks . : 10
  Secondary tracks  . : 10
  Data set name type  : LIBRARY

  Creation date . . . : 1999/12/06     Referenced date . . : 2000/02/04
  Expiration date . . : ***NONE***
 F1=Help      F2=Split     F3=Exit     F7=Backward  F8=Forward   F9=Swap
F12=Cancel
                                                                 02/015
```

Figure 78. Data Set Information (Short) for Managed Data Sets (ISRUAISE)

The major difference between this information and the information that is displayed for data sets on non-managed volumes is the addition of these classes:
- Management class
- Storage class
- Data class

If the data set is a PDSE, the “Data set name type” field is LIBRARY. Because the used blocks and used extents are not applicable to a PDSE, the Data Set Information panel replaces these values with “Used pages” and “% Utilized” (Figure 79 on page 111). Other values that can appear in the “Data set name type” field are:
- HFS - MVS Hierarchical File System data set
- EXTENDED - DFSMSdfp Striped data set. When the Data Set Name Type is EXTENDED, the SMS Compressible field indicates if the data set is compressible or not (YES or NO).
- LARGE - Large format sequential data set

```
 Menu  RefList  Utilities  Help
                         Data Set Information

Data Set Name  . . . . . . . : MYDATA.EXTENTS.TEST.PDSE
General Data                                                  More:     +
   Management class  . . . . : STANDARD   Current Allocation
   Storage class . . . . . . : BASE         Allocated blocks  . :      13
      Volume . . . . . . . . : HSM019       Allocated extents . :       1
      Device type  . . . . . : 2280
   Data class  . . . . . . . :
      Organization . . . . . : PO         Current Utilization
      Record format  . . . . : FB           Used pages  . . . . :       6
      Record length  . . . . : 80           % Utilized  . . . . :       5
      Block size . . . . . . : 32720
      1st extent blocks  . . : 13
      Secondary blocks . . . : 10
      Data set name type . . : LIBRARY    SMS Compressible  . . : NO


Command ===>
 F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
 F9=Swap       F12=Cancel
```

Figure 79. Data Set Information (Short) for a PDSE (ISRUAISE)

Library utility options for members

The topics listed here describe the options shown on the right side of the Library Utility panel shown in Figure 70 on page 102. These options are used to work with members.

- "B — browse member"
- "C — copy member" on page 112
- "D — delete members" on page 112
- "E — edit member" on page 112
- "G — reset member" on page 112
- "M — move member" on page 112
- "P — print member" on page 112
- "R — rename member" on page 112
- "T — TSO command for member" on page 113
- "V — view member" on page 113
- "W — WS command for member" on page 113

Notes:

1. You can *chain* these commands; that is, you can select multiple members from a member list for various processing tasks. Use the CANCEL command (from a View, Browse, or Edit session) to break the chain and return to the member list.
2. With an enhanced member list, you can enter other commands. See "M — display member list" on page 162.

B — browse member

If you select option B, you must specify a partitioned data set and a member name. The specified member is displayed in Browse mode. You can use all the Browse commands. When you exit Browse, the Library Utility panel reappears.

C — copy member

If you select option C, the copy prompt panel appears where you must specify a partitioned data set and member name for the new member. When you exit Copy, the Library Utility panel reappears.

D — delete members

If you select option D, you must specify a partitioned data set and a member name or pattern. Option D prevents you from deleting a PDS member that any user is currently editing.

If you have selected Confirm Member Delete on the Library Utility panel (ISRUDA1), then you are asked to confirm your intention to delete this member. Note that Confirm Delete is forced on when deleting members by pattern.

Where the member to be deleted is the name of a primary member, the primary name and all associated alias names are deleted. Where the member is an alias member, only the alias name and its directory entry are deleted.

Where a member pattern has been specified, these rules apply:

- All primary members whose name matches the member pattern are deleted.
- All aliases that are associated with a primary member whose name matches the member pattern are deleted, even if the alias name itself does not match the member pattern.
- All aliases whose name matches the member pattern are deleted, even if the alias is associated with a primary member whose name does not match the member pattern.

E — edit member

If you select option E, you must specify a partitioned data set and member name. The specified member is displayed in Edit mode. You can use all EDIT commands. When you exit Edit, the Library Utility panel reappears.

G — reset member

If you select option G, the reset prompt panel displays, where you enter the data set and member name. When you exit, the Library Utility panel reappears.

M — move member

If you select option M, the move prompt panel displays, where you enter the data set and member name. When you exit, the Library Utility panel reappears.

P — print member

If you select option P, you must specify a partitioned data set and a member name. A source listing of the member is recorded in the ISPF list data set.

Note: If any members are to be printed, the data set characteristics must conform to those for the L option.

R — rename member

If you select option R, you must specify a partitioned data set and member name. You must also specify a new member name in the “New name” field. Option R prevents you from renaming a member that is currently being edited by you or another user.

Where the data set refers to a partitioned data set load library (RECFM=U), and the member to be renamed is the name of an primary member, the user data component of any associated alias names will be updated to refer to the renamed primary name.

T — TSO command for member

If you select option T, the TSO command prompt panel appears, where you can enter the TSO command to be run for the member.

V — view member

If you select option V, you must specify a partitioned data set and member name. The specified member is displayed in View mode. You can use all EDIT commands. When you exit View, the Library Utility panel reappears. For more information, see the topic about the View (option 1) in *z/OS ISPF User's Guide Vol I*.

W — WS command for member

If you select option W, the WS command prompt panel appears, where you can enter the WS command to be run for the member.

Data set utility (option 3.2)

When you select this option, a panel is displayed (Figure 80) that allows you to specify a data set and an action to be performed.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                              Data Set Utility

    A Allocate new data set                C Catalog data set
    R Rename entire data set               U Uncatalog data set
    D Delete entire data set               S Short data set information
blank Data set information                 V VSAM Utilities

ISPF Library:
   Project  . . ________          Enter "/" to select option
   Group  . . . ________          /  Confirm Data Set Delete
   Type . . . . ________

Other Partitioned, Sequential or VSAM Data Set:
   Data Set Name . . . ____________________________________________________
   Volume Serial . . . ________  (If not cataloged, required for option "C")

Data Set Password  . . ________  (If password protected)


Option ===> ___________________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 80. Data Set Utility panel (ISRUDA2S)

Data Set Utility panel action bar

The Data Set Utility panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

RefList
For information about referral lists, see the topic about Using Personal Data Set Lists and Library Lists in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down provides information on:
- allocating new partitioned and sequential data sets
- processing existing data sets (renaming, deleting, cataloging, uncataloging, and displaying data set information)
- The VSAM utilities

Data Set Utility panel fields

All the fields on the Data Set Utility panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*. For option A you can specify any DASD-resident sequential or partitioned data set. For the other options, you can specify any DASD-resident data set that is not VSAM. You can get short information on a VSAM data set.

Data set utility options

These topics describe the options shown on the Data Set Utility panel:

- "A — allocate new data set"
- "Allocation errors" on page 120
- "C — catalog data set" on page 121
- "R — rename entire data set" on page 122
- "U — uncatalog data set" on page 123
- "D — delete entire data set" on page 123
- "S — data set information (short)" on page 126
- "Blank — (data set information)" on page 126
- "V — VSAM utilities" on page 127

A — allocate new data set

Use option A to allocate a new data set with or without the Storage Management Subsystem classes (management class, storage class, and data class). A data set that is allocated on a volume that is managed by the Storage Management Subsystem (SMS) is called a *managed* data set. A data set that is allocated on a volume that is not managed by the SMS is called a *non-managed* data set.

To use option A, you must:

1. Enter one of these:
   - An ISPF library name in the Project, Group, and Type fields
   - Another partitioned or sequential data set name in the Data Set Name field.

     See the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for information on how to enter the ISPF library name or the data set name.
2. If you entered an ISPF library name, the value in the Volume Serial field is ignored. However, if you entered another data set name, you can specify the volume on which to allocate the data set in the Volume Serial field. Do not enter a volume serial if you want to do one of these:
   - Use the authorized default volume.
   - Enter a generic unit address in the "Generic unit" field on the Allocate New Data Set panel.

   For more information about Volume Serials, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

3. If your ISPF libraries and data sets are password-protected, enter the password in the Data Set Password field.

   For more information about Data Set Passwords, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

   Note: You cannot assign a password to a managed data set. Therefore, the Data Set Password field is ignored when you allocate a managed data set.
4. Press Enter.

The Allocate New Data Set panel is displayed. This panel enables you to specify data set allocation values. The fields displayed on this panel depend upon the value of the ALLOWED_ALLOCATION_UNITS keyword in the ISPF configuration table. When ALLOWED_ALLOCATION_UNITS is not 'A' the panel shown in Figure 81 is displayed.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                            Allocate New Data Set
                                                                More:     +
 Data Set Name  . . . : MYPROJ.DEV.SOURCE2

 Management class . . . STANDARD       (Blank for default management class)
 Storage class  . . . . BASE           (Blank for default storage class)
  Volume serial . . . . MVS8WF         (Blank for system default volume)
 Data class . . . . . . **NONE**       (Blank for default data class)
  Space units . . . . . _________      (BLKS, TRKS, CYLS, KB, MB, BYTES
                                        or RECORDS)
  Average record unit   U             (M, K, or U)
  Primary quantity  . . 1            (In above units)
  Secondary quantity    1            (In above units)
  Directory blocks  . . 0            (Zero for sequential data set) *
  Record format . . . . FB
  Record length . . . . 80
  Block size  . . . . . _____
  Data set name type    PDS          (LIBRARY, PDS, LARGE, BASIC, *
                                      EXTREQ, EXTPREF or blank)
  Expiration date . . . _________    (YY/MM/DD, YYYY/MM/DD
  Enter "/" to select option           YY.DDD, YYYY.DDD in Julian form
     Allocate Multiple Volumes         DDDD for retention period in days
 Command ===>
  F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
  F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 81. Allocate New Data Set panel (ISRUAAP2)

Otherwise, this panel is displayed: (Figure 82 on page 116).

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                            Allocate New Data Set
                                                                   More:     +
 Data Set Name  . . . : MYPROJ.DEV.SOURCE2

 Management class . . . STANDARD       (Blank for default management class)
 Storage class  . . . . BASE           (Blank for default storage class)
  Volume serial . . . . MVS8WF         (Blank for system default volume) **
  Device type . . . . . ________       (Generic unit or device address) **
 Data class . . . . . . ________       (Blank for default data class)
  Space units . . . . . CYLINDER       (BLKS, TRKS, CYLS, KB, MB, BYTES
                                        or RECORDS)
  Average record unit                  (M, K, or U)
  Primary quantity  . . 1              (In above units)
  Secondary quantity   1               (In above units)
  Directory blocks  . . 0              (Zero for sequential data set) *
  Record format . . . . FB
  Record length . . . . 80
  Block size  . . . . . ______
  Data set name type   PDS             (LIBRARY, HFS, PDS, LARGE, BASIC, *
                                        EXTREQ, EXTPREF or blank)
  Expiration date . . . __________     (YY/MM/DD, YYYY/MM/DD
  Enter "/" to select option             YY.DDD, YYYY.DDD in Julian form
     Allocate Multiple Volumes           DDDD for retention period in days
  Command ===> ____________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 82. Allocate New Data Set —managed data set support panel (ISRUAASE)

When you press Enter with this panel displayed, the new data set is allocated and cataloged. Entering the END command returns you to the previous panel without allocating the data set.

An optional installation exit, the data set allocation exit, can control all data set creation, deletion, allocation, and deactivation done directly by ISPF. This does not include allocations done by ISPF, the TSO ALLOCATE command, or other TSO commands. See *z/OS ISPF Planning and Customizing* for more information about the data set allocation exit.

Your installation must use DFSMSdfp to define the values that you enter in the “Management class”, “Storage class”, and “Data class” fields. If you have no specific requirements, you can leave these fields blank. However, be aware that your installation may provide default management, storage, and data classes. These defaults would take effect if you leave any of the class fields blank and may even override any classes that you specify.

Management class
: Used to obtain data management-related information (migration, backup, and retention criteria, such as expiration date) for the data set allocation.

  If you have no specific management class requirements, you can leave this field blank. However, be aware that your installation may provide a default management class. This default may even override any management class that you specify.

Storage class
: Used to obtain the storage-related information (volume serial) for the data set allocation. Any volume serial that you enter in the “ Volume serial”

field is ignored unless the storage class that you use includes the Guaranteed Space=Yes attribute (useful if you are allocating multivolume data sets).

Data class
Used to obtain the data-related information (space units, primary quantity, secondary quantity, directory block, record format, record length, and data set name type) for the allocation of the data set.

Default values are provided for the fields in Figure 81 on page 115, except for expiration date, based on which of these occurred most recently:
- What you last entered on this panel
- The last display data set information request (options 3.1, 3.2, or 3.4).

You can type over the displayed defaults if you want to change them. Here is a list of the fields on this panel and their definitions:

Volume serial
This field is one that you probably will not need to use very often. It is not required and is usually ignored by the Storage Management Subsystem. Do not enter a volume serial if you want to do one of these:
- Use the authorized default volume.
- Enter a generic unit address in the Generic unit field.
- Use the volume specified by the storage class you are using.

When a storage class is used, your installation and the SMS assume joint responsibility for determining the volume on which the data set is allocated. The SMS enables the installation to select the volumes that are eligible to contain the data set. It then chooses one of those volumes and allocates the data set. The SMS's volume choice is based on:
- storage requirements
- The amount of space a volume has available.

Note: ISPF does not support allocation of tape data sets.

Generic unit
The generic unit address for the direct access volume that is to contain the data set, such as 3380 or 3390. This field overrides the Volume Serial field on the Data Set Utility panel. Therefore, you should leave this field blank if you want to do one of these:
- Use the authorized default volume
- Enter a volume serial in the Volume serial field.

Notes:
1. Leave both the Volume serial and Generic unit fields blank to allow ISPF to select an eligible volume. Eligibility is determined by the unit information in your user entry in the TSO User Attribute Data Set (UADS) or the TSO segment of RACF.
2. At some installations, you are limited to eligible volumes even when an explicit volume serial is specified. At other installations you can specify any mounted volume. This is an installation option.
3. To allocate a data set to a 3850 virtual volume, you must also have MOUNT authority, gained by using the TSO ACCOUNT command or by using the RACF PERMIT command for the TSO AUTH general resource class.

4. If you are allocating an SMS data set, you can enter either an installation defined group name or a generic device type in the Generic unit field, but not a specific device number.

Space units
Any of these:

Track Shows that the amounts entered in the primary and secondary quantity fields are expressed in tracks.

Cylinder Shows that the amounts entered in the primary and secondary quantity fields are expressed in cylinders.

Block Shows that the amounts entered in the primary and secondary quantity fields are expressed in blocks.

Megabyte Shows that the amounts entered in the primary and secondary quantity fields are expressed in megabytes.

Kilobyte Shows that the amounts entered in the primary and secondary quantity fields are expressed in kilobytes.

Byte Shows that the amounts entered in the primary and secondary quantity fields are expressed in bytes.

Records Shows that the amounts entered in the primary and secondary quantity fields are the average number of records of the size specified by the block size field.

Note: "Space units" allows the shortest unique abbreviation for each attribute; for example, T for TRKS, C for CYLS, K for KB, and M for MB, BY for BYTE, R for RECORDS, and BL for BLKS.

Average record unit
Shows the unit used when allocating average record length. `U` specifies single-record units (bytes). `K` specifies thousand-record units (kilobytes). `M` specifies million-record units (megabytes). The default value is U.

Primary quantity
The primary allocation quantity in tracks, cylinders, blocks, megabytes, kilobytes, bytes, or records, as shown in the "Space units" field. This number can be zero for sequential data sets, but must be greater than zero for PDSs. Also, if the primary quantity is zero, the secondary quantity must be greater than zero.

Secondary quantity
The secondary allocation quantity in tracks, cylinders, blocks, megabytes, kilobytes, bytes, or records, as shown in the "Space units" field. This quantity is allocated when the primary quantity is insufficient.

Directory blocks
Enter one of these:

- For partitioned data sets, you must specify the number of directory blocks. Each 256-byte block accommodates these number of directory entries:
  - Data sets with ISPF statistics: 6
  - Data sets without ISPF statistics: 21
  - Load module data sets: 4-7, depending on attributes
- For sequential data sets, set this field to zero.

Record format
Any valid combination of these codes:

F Fixed-length records.
V Variable-length records.
U Undefined format records.
B Blocked records.
A ASA printer control characters.
M Machine code printer control characters.
S Standard (for F) or spanned (for V); use only with sequential data sets.
T Track-overflow feature.

Notes:
1. You must enter either F, V, or U.
2. You can specify S and T, but ISPF does not otherwise support them.

Record length
The logical record length, in bytes, of the records to be stored in the data set.

Block size
The block size, also called *physical record length*, of the blocks to be stored in the data set. Use this field to specify how many bytes of data to put into each block, based on the record length. For example, if the record length is 80 and the block size is 3120, 39 records can be placed in each block.

Note: The record length and block size are verified to be consistent with the record format. If you need to use non-standard characteristics, use the TSO ALLOCATE command.

Expiration date
Allows you to protect valuable data by specifying a date, in your national language, when the data set may be deleted. If you try to delete an unexpired data set, ISPF displays two panels: a Confirm Delete panel, followed by a Confirm Purge panel. See "D — delete entire data set" on page 123 for more information about deleting unexpired data sets.

An expiration date is not required, but if you enter one it should be in one of these formats:

YYYY/MM/DD
Date shown in year, month, and day, or your equivalent national format. The maximum expiration date allowed is 2155/12/31.

YYYY.DDD
Date shown in Julian format, such as 2006.066 for March 7, 2006. The maximum expiration date allowed is 2155.365.

You can specify a DDD value of up to 366 if the YYYY value represents a leap year.

DDDD
The number of days, starting with the creation date, after which the data set can be deleted. DDDD has a range of 0 to 9999.

PERM, NOLIMIT, NEVER, 9999
Specifying any of these values causes ISPF to translate it to a value of `1999.365`. This is treated by ISPF as permanent retention.

Allocate Multiple Volumes
Allows you to allocate sequential data sets that span multiple volumes. ISPF supports a maximum of 59 volumes. Place a slash in this field and press enter to display a panel similar to the one shown in Figure 83 on page 120

page 120.

```
  Menu  RefList  Utilities  Help
 ─ ┌──────────── Multivolume Allocation ────────────┐ ──────────────────────
   │ ISRUAMV                                        │
   │                                                │              More:   - +
   │ Enter the number of volumes to allocate or     │  device address) **
 D │ the names of one or more volumes and           │ lt data class)
   │ press Enter to allocate or enter Cancel        │ S, KB, MB, BYTES
   │ command to exit.  If a number is entered,      │
   │ any volume names will be ignored.              │
   │                                More:     +     │
   │ Number of volumes to allocate: __              │
   │                                                │ tial data set) *
   │ Volume names:                                  │
   │  1. MVS8WF  2. ______  3. ______  4. ______    │
   │Command ===> ___________________________________│
   │ F1=Help       F2=Split       F3=Exit           │ DS, or blank)  *
   │ F7=Backward   F8=Forward     F9=Swap           │ MM/DD
   └────────────────────────────────────────────────┘ D in Julian form
 Enter "/" to select option            DDDD for retention period in days
 /  Allocate Multiple Volumes          or blank)

 Command ===>
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 83. Multivolume allocation panel (ISRUAMV)

This panel allows you to specify up to 59 volumes.

Note:

- Although the volume input fields are numbered consecutively, you may enter volume names in any of the fields.
- The volume that you enter in the “Volume serial” field on the Allocate New Data Set panel will be placed in the first field of the Multivolume Allocation panel.
- If you enter only one volume, standard data set allocation is invoked.
- If you enter a number in the “Number of volumes to allocate” field, any volume names left in the name fields are ignored, and might or might not be the volumes the data set is allocated to.
- When displaying information about a multivolume data set, depending on your system setup, all volumes might not be shown until they have been accessed.

Allocation errors

ISPF attempts to recognize inconsistent attributes for partitioned and sequential data sets before allocating them. However, when conditions outside ISPF’s control result in the allocation of such a data set, the Allocation Error panel (Figure 84 on page 121) is displayed. These conditions are caused by:

- A data class that specifies inconsistent attributes
- Attributes entered on the Allocate New Data Set panel that create inconsistency by overriding other attributes specified by the data class.

```
---------------------------  Allocation Error  -------------------------------

Data Set Name: SYSTEM.LOAD

  Specified data set has zero block size

 The data set allocated contains inconsistent attributes as indicated by
 the message displayed above.  Prior to allocating a managed data set,
 PDF cannot always determine if the attributes are inconsistent.  The
 data class used when allocating the data set may contain inconsistent
 attributes, or the attributes you specified on the allocation panel may
 conflict with those defined in the data class.  This panel gives you the
 opportunity to delete this data set.  If you keep the data set, other
 PDF functions, such as edit, move, copy, or promote, may not be able to
 use the data set.

Instructions:

   Press the Enter key to DELETE the data set.

   Enter the END command to KEEP the data set.

Command ===> _____________________________________________________
 F1=Help    F2=Split   F3=Exit    F9=Swap   F12=Cancel
```

Figure 84. Allocation Error Panel (ISRUADCS)

The term *inconsistent attributes* refers to incompatible values that have been specified for one or more of these items: Space units; Primary or Secondary quantity; Directory blocks; Record format; Record length; Block size.

For example, if you allocate a data set with an undefined record format (RECFM=U) and a block size of zero (BLOCKSIZE=0), some ISPF functions (such as Move and Copy) and services (such as LMMOVE, LMCOPY, and LMINIT) cannot use the data set.

However, when either the linkage editor or the IEBCOPY utility has been called, these functions and services determine the best block size for the data set. Then, when the data set has a block size greater than zero, the ISPF functions and services listed can be used.

The Allocation Error panel gives you the opportunity to delete such a data set because other ISPF functions, such as View (option 1) and Edit (option 2), may not be able to use it.

For information about allocation errors and how they affect data set promotion when using SCLM, refer to *z/OS ISPF Software Configuration and Library Manager Guide and Reference*.

C — catalog data set

If you select option C, the specified data set is cataloged. For this option, you must specify the volume serial on which the data set resides, regardless of whether the data set is specified as project, library, and type, or as another data set name. The data set must reside on the specified volume.

The preceding instructions for cataloging data sets do not apply to data sets that reside on Storage Management Subsystem volumes. These data sets are automatically cataloged when you allocate them. They cannot be cataloged by using option C.

R — rename entire data set

If you select option R, a panel is displayed to allow you to enter the new data set name.

Type the new data set name and press Enter to rename, or enter the END command to cancel. Either action returns you to the previous panel.

If you specify a volume serial for a data set to be renamed, ISPF checks to see whether the data set is cataloged on that volume. If it is, the Rename panel prompts you to specify whether to recatalog the data set. If you specify a volume serial and the data set is not cataloged, it remains uncataloged after you rename it. If a volume serial is not specified, the data set is recataloged to the new data set name and the old data set name is uncataloged.

Notes:

1. ISPF does not rename VSAM data sets or password-protected data sets.
2. A volume serial is not allowed for multivolume data sets using Rename.
3. Generation Data Group (GDG) data sets can only be renamed to something other than GDG names.

   Attention: Trying to rename GDG data sets to a different generation or version number can cause deletion of your GDG data set or group of GDG data sets.
4. When you rename a data set that resides on a Storage Management Subsystem volume, you cannot specify a volume serial in the Volume Serial field. Both the cataloged entry and the VTOC entry are renamed.

Rename processing with RACF: The normal order of processing when ISPF is asked to rename a data set is as follows:

1. The new data set name is cataloged using SVC 26
2. The data set is renamed using SVC 30
3. The old data set name is uncataloged using SVC 26

There are three occasions, however, when ISPF will deviate from this order of processing:

- If the data set is a System Managed (SMS) data set, the update of the catalog (both cataloging the new name and uncataloging the old name) is handled by the operating system when the SVC 30 is issued. In this case, ISPF does not issue either of the SVC 26 requests.
- If the data set is an uncataloged data set, no catalog update will be done. The data set is renamed using the SVC 30 only.
- If the data set is cataloged, but the user specified both the data set name and volume, panel ISRUARP2 is displayed. The user has the option of specifying whether the catalog processing should be done. If the user indicates (via a NO in the “Reply to uncatalog the data set” field) that no catalog processing should be done, only the SVC 30 is used to rename the data set. If the reply is YES, the SVC 30 as well as both SVC 26 requests are issued.

If an error is encountered during a rename request, an attempt is made to return the data set to its original name, and to reset the catalog entries to their original status (remove the new name from the catalog and leave the old name in the catalog).

This order of processing is intended to minimize the possibility that an uncataloged data set will result if an error is encountered during the rename

process. Errors may be encountered due to certain combinations of RACF data set profiles and user access to the groups under which those data set profiles fall. When an error occurs, the user receives a message indicating the status of the data set name, and of the catalog entries.

See the *z/OS Security Server RACF Security Administrator's Guide* or equivalent documentation for your security package, to determine the authorization levels required for each of these operations. The user will need authorization first to catalog the new data set name, then to rename the data set, and then to uncatalog the old data set name. This will require adequate authorization to any discrete or generic data set profiles involved and to the catalogs involved. Be aware that a discrete data set profile is renamed when the data set is renamed.

Renaming with expiration dates: If the data set has an expiration date in its catalog entry, the expiration date is not propagated forward to the new catalog entry. In this case, a confirmation panel is displayed.

As directed by the panel, press Enter if you want to confirm the rename request. If you want the data set to have an expiration date under its new name, use the TSO ALTER command or a similar function to update the new catalog entry.

U — uncatalog data set

If you select option U, the specified data set name is uncataloged. There is no need for the specified data set to be allocated or for the volume on which it resides to be mounted.

If the catalog entry being removed contains an expiration date in the future, a confirmation panel is displayed. Press Enter if you want to confirm the uncatalog request, otherwise press END to cancel the request.

Note: Uncatalog is not allowed for multivolume data sets.

You cannot use option U to uncatalog a data set that resides on a Storage Management Subsystem volume. However, the system uncatalogs these data sets when you delete them, which is done by using option D of either the Data Set utility (option 3.2) or the Data Set List utility (option 3.4).

D — delete entire data set

If you select option D, a confirmation panel is displayed (Figure 85 on page 124) so you can make sure you did not select this option by mistake.

```
  Menu  RefList  Utilities  Help
_ ┌──────────────────────────────────────────────────────────────────┐ ──────
  │                         Confirm Delete
  │                                                        More:     +
  │ Data Set Name . : MYPROJ.DEV.SOURCE
  │ Volume  . . . . : MVS8WF
  │ Creation date . : 2002/07/08
b │
  │ Enter "/" to select option
I │ _  Set data set delete confirmation off
  │
  │ Instructions:
  │   Press ENTER to confirm delete.
  │   (The data set will be deleted and uncataloged.)
O │
  │   Press CANCEL or EXIT to cancel delete.
  │                                                                "C")
  │ Command ===> _____________________________________________
D │  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward
  │  F9=Swap     F12=Cancel
  └──────────────────────────────────────────────────────────────────┘
Option ===> D
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 85. Confirm Delete panel (ISRUADC1)

If you specify a volume serial for the data set to be deleted, ISPF checks to see whether the data set is cataloged on that volume. If so, the Confirm Delete panel prompts you to specify whether to uncatalog the data set. The displayed default is YES. If no volume serial is specified, and the data set does not have an expiration date, the data set is deleted and uncataloged.

Notes:

1. ISPF does not delete password-protected data sets or data sets allocated with an esoteric device type.
2. A volume serial is not allowed for multivolume data sets using Delete.

As directed on the panel, perform one of these actions:

- Press Enter to confirm the data set deletion.
- Enter the CANCEL or EXIT command to cancel. This action returns you to the previous panel.

If the data set has an expiration date that has not expired, ISPF displays a Confirm Purge panel (Figure 86 on page 125) after the Confirm Delete panel.

```
  Menu  RefList  Utilities  Help
_ ┌──────────────────────────────────────────────────────────────────────┐ ────
  │                              Confirm Delete                          │
  │                                                                      │
  │ Data Set being deleted has an expiration date which has not expired  │
  │ Data Set Name . : MYPROJ.DEV.SOURCE                                  │
  │ Volume  . . . . : MVS8WF                                             │
b │ Creation date . : 2002/07/08                                         │
  │ Expiration Date : 2002/10/01                                         │
I │                                                                      │
  │ Enter "/" to select option                                           │
  │ _  Purge Data Set                                                    │
  │                                                                      │
  │ Instructions:                                                        │
O │   Enter "/" to confirm the purge request.                            │
  │   (The data set will be deleted and uncataloged.)                    │
  │                                                                      │
  │   Press CANCEL or EXIT to cancel the purge request.                  │
  │                                                                      │
  │ Command ===> _____________________________________________________   │
D │  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward      │
  │  F9=Swap     F12=Cancel                                              │
  └──────────────────────────────────────────────────────────────────────┘
F10=Actions  F12=Cancel
```

Figure 86. Confirm purge panel (ISRUADC3)

Use a slash to select Purge Data Set if you want ISPF to purge the data set. The statement that is enclosed in parentheses on the Confirm Purge panel shows whether the data set to be purged will be uncataloged.

When you delete a data set, the volume name is compared to the volume name in the configuration table. If the names match, the command specified in the configuration table is used in place of the ISPF delete processing. This lets you delete migrated data sets without first causing them to be recalled.

Delete processing with RACF: If the data set is an SMS data set, it is deleted using SVC 29. The update of the catalog entry is handled by the operating system.

If the data set is not an SMS data set and either it is not cataloged or the user indicates on panel ISRUADC2 (panel ISRUADC2 is shown if the volume is supplied) that it is not to be uncataloged, it is deleted using SVC 29.

If the data set is not an SMS data set and it is cataloged and/or the user indicates on panel ISRUADC2 (panel ISRUADC2 is shown if the volume is supplied) that it is to be uncataloged, this process is followed:
1. The data set is deleted using SVC 29 (SCRATCH).
2. The data set is uncataloged using SVC 26.

This order of processing is intended to minimize the possibility that an uncataloged data set will result if an error is encountered during the delete process. Some combinations of RACF generic and discrete data set profiles and user access to the groups under which those profiles fall can cause this process to fail. If an error is encountered in this process the user is notified via a message of the status of the data set and catalog entries.

See the *z/OS Security Server RACF Security Administrator's Guide* or equivalent documentation for your security package, to determine the authorization levels required for each of these operations. The user will need authorization first to

delete the data set and then to uncatalog the data set name. This will require adequate authorization to any discrete or generic data set profiles involved and to the catalogs involved. Be aware that a discrete data set profile is deleted when the data set is deleted.

S — data set information (short)

If you select option S, information about the selected data set is displayed. The information displayed by option S is the same information displayed by option S on the Library Utility panel (option 3.1). See "S — short data set information" on page 108 for more information and Figure 77 on page 109 for an example. To return to the previous panel, press Enter or enter the END command.

The space for data sets allocated in blocks is calculated as if all of the tracks, including the last one, contain only full blocks of data. Any partial "short" blocks are ignored.

Notes:

1. The information shown for current space utilization is the actual data that the data set contains, based on the number of allocation units (blocks, tracks, bytes, megabytes, and so on) that have been written. For a data set allocated in units other than tracks and cylinders, it does not include the unused portion of a track that is only partially filled.

   For example, if a data set allocated in bytes with block size of 600 has one block written to a device with a track size of 1000, 600 bytes of data are written and the remaining 400 bytes cannot be used by a different data set. A track is the smallest possible unit of physical allocation to a data set on DASD. ISPF reports 600 bytes used while other products (such as ISMF) report 1000 bytes used. ISPF reports the space occupied by data in the data set. ISMF reports the space used by this data set that is not available for use by another data set. The difference is a relative indication of the effectiveness of the block size used when the data set was created.
2. Space utilization values are not displayed for ISAM, VSAM, or BDAM data sets.

See "Short information for managed data sets" on page 109 to learn more about the data set information that is displayed for managed data sets.

Blank — (data set information)

If you leave the Option field blank, information about the selected data set is displayed. The information displayed is the same information displayed by option I on the Library Utility panel (option 3.1). See "I — data set information" on page 104 for more information and "U — uncatalog data set" on page 123 for an example. To return to the previous panel, press Enter or enter the END command.

Notes:

1. For multivolume data sets, options I and S display current allocation and utilization values that represent totals from all volumes used.
2. You can not enter a volume serial when you are requesting information on a multivolume data set.
3. The space for data sets allocated in blocks is calculated as if all of the tracks, including the last one, contain only full blocks of data. Any partial "short" blocks are ignored.
4. The information shown for current space utilization is the actual data that the data set contains, based on the number of allocation units (blocks, tracks, bytes,

megabytes, and so on) that have been written. For a data set allocated in units other than tracks and cylinders, it does not include the unused portion of a track that is only partially filled.

For example, if a data set allocated in bytes with block size of 600 has one block written to a device with a track size of 1000, 600 bytes of data are written and the remaining 400 bytes cannot be used by a different data set. A track is the smallest possible unit of physical allocation to a data set on DASD. ISPF reports 600 bytes used while other products (such as ISMF) report 1000 bytes used. ISPF reports the space occupied by data in the data set. ISMF reports the space used by this data set that is not available for use by another data set. The difference is a relative indication of the effectiveness of the block size used when the data set was created.

5. Space utilization values are not displayed for ISAM, VSAM, or BDAM data sets.

See “Information for managed data sets” on page 107 for information about the data set information that is displayed for managed data sets.

V — VSAM utilities

Use option V to create the IDCAMS commands to define, delete, and list catalog information for VSAM data sets. Before the command is issued, you will be allowed to edit it in an ISPF Edit session. The command will process in the foreground.

Note: The VSAM utilities function builds a command that is syntactically correct; the utility does not do any compatibility checking of the fields used to build the command.

When you select option V, the panel shown in Figure 87 is displayed.

```
 Menu  Utilities  Help
 ------------------------------------------------------------------------
                            VSAM Utilities
                                                            More:     +
  Process Request                 Data Type
   _  1. Define                    __  1.  Alias
      2. Delete                        2.  Alternate Index
      3. Information (Listcat)         3.  Cluster
                                       4.  Generation Data Group
                                       5.  Non-VSAM
                                       6.  Page Space
                                       7.  Path
                                       8.  User Catalog
                                       9.  Data     *
                                       10. Index    *
                                       11. NVR      **
                                       12. Truename **
                                       13. VVR      **
                         * Listcat Only
 Command ===>
  F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
  F9=Swap      F10=Actions   F12=Cancel
```

Figure 87. VSAM Utilities panel (ISRUVSAM)

VSAM Utilities panel action bar: The VSAM Utilities panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down provides information on the VSAM utilities, including the VSAM profile data set and the GET, SAVE, and CHANGE commands.

VSAM Utilities panel fields: There are two fields on the VSAM Utilities panel:

Process Request
Required field. Indicates what is going to be done to the VSAM data set:

1 **Define**. Process an IDCAMS define request

2 **Delete**. Process an IDCAMS delete request against one or more data sets.

3 **Listcat**. Process an IDCAMS list catalog request.

VSAM Data Type
Required field. Indicates what kind of data set is to be defined, deleted or listed:

1 **Alias**. Define, delete, or list an alternate name for a non-VSAM data set or a user catalog

2 **Alternate Index**. Specify that an alternate index is to be defined, deleted, or listed or that an alternate index entry is to be recataloged

3 **Cluster**. Specify that a cluster is to be defined, deleted, or listed or that a cluster entry is to be recataloged

4 **Generation Data Group**. Specify that a generation data group entry is to be defined, deleted, or listed

5 **Non-Vsam**. Specify that a non-VSAM, non-SMS-managed data set is to be defined, deleted, or listed

6 **Page Space**. Specify that a page space is to be defined, deleted, or listed

7 **Path**. Specify that a path is to be defined, deleted, or listed or that a path entry is to be recataloged

8 **User Catalog**. Specify that a catalog is to be defined, deleted, or listed

9 **Data**. List data level information (Listcat request only)

10 **Index**. List index level information (Listcat request only)

11 **NVR**. Delete an SMS-managed non-VSAM volume record entry (Delete request only)

12 **Truename**. Delete the truename entry for a data or index component of a cluster or alternate index or the name of an alternate index (Delete request only)

13 **VVR**. Delete an unrelated VSAM volume record entry (Delete request only).

Example usage – defining a cluster: To define a cluster, on the VSAM Utilities panel, type 1 in the Process Request field and 3 in the VSAM Data Type field. The Define Cluster panel is displayed as shown in Figure 88.

```
 Menu  Function  Utilities  Help
 ------------------------------------------------------------------------
                                Define Cluster

                                                Enter "/" to select option
                                                /  Edit IDCAMS command
                                                /  Browse errors only
 Cluster Name  . . . MYPROJ.DEV.SOURCE3
                                                                  More:     +
                           Cluster Level Information:

 Space Units  . . . . . . . _  1. Cylinders   Primary Quantity . . . ________
                               2. Tracks      Secondary Quantity . . ________
                               3. Records
                               4. Kilobytes
                               5. Megabytes
 Volumes  . . . . . . . . . . ______  . . . ______  . . . ______  . . . ______
 Buffer Space . . . . . . . . ________
 Control Interval Size  . . ______
 Data Class . . . . . . . . . ________
 Management Class . . . . . . ________
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 88. Define Cluster panel (ISRUVPC3)

Notes:

1. Select the Edit IDCAMS command option to edit the IDCAMS command that this process generates before the command is issued. If you do not select this option, the command will be issued when you press Enter.
2. Select the Browse errors only option to browse the output from IDCAMS only when a nonzero return code is returned by IDCAMS.

Fill in the required fields or use a VSAM profile data set as described in "Building a VSAM profile data set" on page 130. When you press Enter, the screen shown in Figure 89 on page 130 is displayed.

Note: If you try to use a profile that was defined for a different request type (for example, Generation Data Group), you will receive a "Type mismatch" error.

```
  Menu  Utilities  Help
 ------------------------------------------------------------------------
                                                        Columns 00001 00072

    Instructions:

      Enter EXECute command to issue request.

      Enter CANcel, END, or RETURN command to cancel request.
****** ***************************** Top of Data ******************************
==MSG> -Warning- The UNDO command is not available until you change
==MSG>           your edit profile using the command RECOVERY ON.
000001  /* IDCAMS COMMAND */
000002  DEFINE CLUSTER (NAME(MYPROJ.DEV.SOURCE3) -
000003         ) -
000004         DATA (NAME(MYPROJ.DEV.SOURCE3.DATA) -
000005         ) -
000006         INDEX (NAME(MYPROJ.DEV.SOURCE3.INDEX) -
000007         )
****** **************************** Bottom of Data ****************************

Command ===> ____________________________________________ Scroll ===> PAGE
 F1=Help      F2=Split     F3=Exit      F5=Rfind     F6=Rchange   F7=Up
 F8=Down      F9=Swap     F10=Left     F11=Right    F12=Cancel
```

Figure 89. Editing the IDCAMS command (ISRUVEDT)

When you are ready to process the command, type EXEC on the Command line and press Enter. If the command processes with a nonzero return code, the panel shown in Figure 90 is displayed.

```
 VSAM Utilities ------------------------------------ LINE 00000000 COL 001 080
********************************** Top of Data **********************************
IDCAMS  SYSTEM SERVICES                                        TIME: 14:49:0

 /* IDCAMS COMMAND */
 DEFINE CLUSTER (NAME(USERID.PRIVATE.PANELS) -
        CYLINDERS(4 1) -
        VOLUMES(111111 -
              ) -
        ) -
        DATA (NAME(USERID.PRIVATE.PANELS.DATA) -
        ) -
        INDEX (NAME(USERID.PRIVATE.PANELS.INDEX) -
        )
IDC3013I DUPLICATE DATA SET NAME
IDC3009I ** VSAM CATALOG RETURN CODE IS 8 - REASON CODE IS IGG0CLEH-38
IDC3003I FUNCTION TERMINATED. CONDITION CODE IS 12

IDC0002I IDCAMS                                                  12
***************  IDCAMS has returned a non-zero return code.   ***************

 COMMAND ===> ___________________________________________ SCROLL ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 90. Browsing IDCAMS Errors (ISRUVBRO)

Press Exit (F3) to return to the panel shown in Figure 89, make the necessary changes, and resubmit the command.

Building a VSAM profile data set: You can build a VSAM profile data set, each member of which can be used to store input fields on a VSAM input panel for

later retrieval to the same panel. If you try to use a profile that was defined for a different request type (for example, Generation Data Group), you will receive a "Type mismatch" error.

When you have filled in a VSAM input panel, select the Save to Profile choice from the Functions pull-down on the action bar. ISPF displays the Profile Member Name panel.

Type in a member name for the profile data set member. When you press Enter, the data set is created with the attributes RECFM=variable blocked, LRECL=203, Type=PDS.

Using a VSAM profile data set: When you have displayed a VSAM input panel, select the Get from Profile choice from the Functions pull-down on the input panel action bar to display the panel shown in Figure 91.

```
  Menu  Functions  Utilities  Help
 ------------------------------------------------------------------------
 GET      USERID.VSAM.PROFILE                              Row 00001 of 00001
    Name     Prompt          Size    Created           Changed            ID
 . PMNTEST                     78   2002/08/05   2002/08/05 11:56:23    USERID
   **End**



 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 91. Using a VSAM profile data set (ISRVMLGT)

When you select a profile and press Enter, the fields on the entry panel will fill with the values stored in the profile data set member.

Changing the VSAM profile data set: To change the name of the active VSAM profile data set, select the Change Profile Data Set choice from the Functions pull-down on an input panel action bar to display the panel shown in Figure 92 on page 132.

```
  Menu  Function  Utilities  Help
 _ ┌──────────────────────────────────────────────────────────────────────┐ _
   │  Menu  Utilities  Help                                               │
   │ ────────────────────────────────────────────────────────────────────│
   │                          Profile Data Set                            │
   │                                                                      │
   │  Profile Data Set . . 'USERID.VSAM.PROFILE'                          │
   │                                                                      │
   │                                                                      │ +
   │ Command ===> ________________________________________________________│
   │  F1=Help      F2=Split      F3=Exit       F9=Swap      F10=Actions   │
   │ F12=Cancel                                                           │
   └──────────────────────────────────────────────────────────────────────┘
                              3. Records
                              4. Kilobytes

 ⋮
```

Figure 92. Panel for changing the name of the VSAM profile data set (ISRUVGET)

You can type the name of a different profile data set. When you press Enter, the data set is created if it does not exist, and this data set becomes the active profile data set.

Move/Copy utility (option 3.3)

When you select this option, a panel is displayed (Figure 93) that allows you to specify the “From” data set (and member if it is partitioned) and an option to be performed. The Move/Copy Utility prevents you from moving or copying a PDS member that you or another user is currently editing.

```
 Menu  RefList  Utilities  Help
 ──────────────────────────────────────────────────────────────────────────
                            Move/Copy Utility

 C  Copy data set or member(s)          CP Copy and print
 M  Move data set or member(s)          MP Move and print

Specify "From" Data Set below, then press Enter key

From ISPF Library:
   Project . . . ________      (--- Options C and CP only         ---)
   Group . . . . ________ . . . ________ . . . ________ . . . ________
   Type  . . . . ________
   Member  . . . ________         (Blank or pattern for member list,
                                   "*" for all members)

From Other Partitioned or Sequential Data Set:
   Data Set Name . . . ____________________________________________________
   Volume Serial . . . ________   (If not cataloged)

Data Set Password  . .            (If password protected)
Option ===> ___________________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 93. Move/Copy Utility panel (ISRUMC1)

Move/Copy Utility panel action bar

The Move/Copy Utility panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

RefList For information about referral lists, see the topic about Using Personal Data Set Lists and Library Lists in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down provides information on how to specify the "From" and "To" data sets, how to select members to copied, and the rules relating to how different data types are moved or copied.

Move/Copy Utility panel fields

All the fields on the Move/Copy Utility panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*. On this panel, you specify the data set that you want to copy, move, lock, or promote. This is called the "From" data set.

If you request a member list or specify an asterisk (*) in the Member field on the "From" panel, ISPF does not display a Member field on the "To" panel. See the Member Selection List Commands section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for information about primary and line commands that are available for the Move/Copy utility member list display.

You can copy or move load modules stored in partitioned data sets with undefined record formats, but you cannot print them.

The deletion of any member because of a move is recorded in your ISPF log data set, if allocated.

When you complete the panel and press Enter, ISPF displays another panel that is determined by the option you selected. This panel allows you to specify the "To" or "Target" data set or controlled library. Both the "From" and "To" or "Target" data sets must already exist. If the "Target" data set does not exist the user is prompted to see if the data set should be allocated. Choices are to allocate the "Target" data set using the characteristics of the "From" data set as a model, or to allocate the new data set by specifying the characteristics for it. This function can be suppressed through the ISPF Configuration table. If it is suppressed, an allocate request for a nonexistent data set fails.

Move/Copy utility options

These topics describe the options shown on the Move/Copy Utility panel:

- "C and CP — copying data sets"
- "M and MP — moving data sets" on page 135
- "Using the move/copy utility with load modules" on page 137
- "Moving or copying alias entries" on page 138
- "Member list processing when using IEBCOPY" on page 138

C and CP — copying data sets

When you use the C and CP options, ISPF supports library concatenation. This allows you to specify up to four input libraries as the "From" data set. The libraries are searched from left to right as they are entered on the panel. The

member to be copied, which is either specified in the Member field or selected from a member list, is copied from the first library in which it is found.

If you select C or CP, the panel shown in Figure 94 is displayed. This panel allows you to specify the "To" data set—the library or data set name that you want the copied data to be stored under.

Note: The Move/Copy utility does not support:

- Supplying a volume serial when attempting to copy a multivolume data set
- Copying unmovable data sets (data set organization POU or PSU).

C — copy data set or member(s): Use option C to copy a data set. You can specify either a DASD-resident sequential or partitioned data set for both the "From" or "To" data sets. The "From" data set is not deleted.

CP — copy and print: Use this option as you would use option C, except that source listings are recorded in the ISPF list data set, as follows:

- If the "To" data set is partitioned, a listing of each new or replaced member is recorded.
- If the "To" data set is sequential, a listing of its complete contents is recorded.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
 COPY     From MYPROJ.DEV.SOURCE
                                                                 More:     +
 Specify "To" Data Set Below

 To ISPF Library:                Options:
    Project  . . MYPROJ             Enter "/" to select option
    Group  . . . DEV                _  Replace like-named members
    Type . . . . SOURCE             /  Process member aliases

 To Other Partitioned or Sequential Data Set:
    Data Set Name . . . ____________________________________________________
    Volume Serial . . . ______    (If not cataloged)

 Data Set Password  . .           (If password protected)

 To Data Set Options:
    Sequential Disposition        Pack Option         SCLM Setting
    _  1. Mod                     3  1. Yes           3  1. SCLM
       2. Old                        2. No              2. Non-SCLM
 Command ===>  ___________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 94. Move/Copy Utility - "To" panel for copying (ISRUMC2B)

All the fields on the Move/Copy Utility "To" panels for copying data sets are explained in the Libraries and Data Sets topic in the *z/OS ISPF User's Guide Vol I*, except these general Options and To Data Set Options:

Replace like-named PDS members
Select this option to allow replacement of a member in the "To" data set with a like-named member in the "From" data set.

Process member aliases
Select this option to allow the primary member and all alias members to be copied together.

Sequential Disposition
If the "To" data set is sequential, enter:

1 To add the "From" data set to the end of the "To" data set (Mod).

2 To replace the "To" data set's entire contents with the contents of the "From" data set (Old).

If the "From" data set consists of several members of an ISPF library or a partitioned data set to be moved or copied to a sequential data set, the members are written to the "To" data set one after another. The "To" data set disposition (Old or Mod) controls only the beginning location of the "To" data set after the copy or move is completed.

Pack Option
To indicate how the data is to be stored in the "To" data set, enter:

1 If you want the data in the "To" data set to be packed.

2 If you do not want the data in the "To" data set to be packed.

3 If you want the data to be stored in the same format in the "To" data set as it is in the "From" data set.

If you are copying data to a sequential data set with disposition of MOD, you cannot mix packed and unpacked data, nor can you copy multiple packed members.

The technique used to pack data is an internal algorithm used only by ISPF. If the data is packed, attempts to access or process the data outside ISPF can cause unwanted results. See the description of the PACK primary command in *z/OS ISPF Edit and Edit Macros* for more information.

SCLM Setting
The SCLM setting is a bit that ISPF uses to determine what type of edit the file last had performed upon it.

1 SCLM This bit is ON to specify that the last edit of this file was under SCLM control.

2 Non-SCLM This bit is ON to specify that the last edit of this file was under control of something other than SCLM.

3 As-is This bit is ON to specify that this operation leaves the current setting unchanged.

M and MP — moving data sets

When you use the M and MP options, ISPF does not provide library concatenation support. You can specify up to four input libraries as the "From" data set. However, only the first library in the sequence is searched. Therefore, the member to be moved, which is either specified in the Member field or selected from a member list, is moved only if it is found in the first library. However, the other three library names remain on the panel and can be used with the C and CP options.

If you select M or MP, the panel shown in Figure 95 on page 136 is displayed. This panel allows you to specify the "To" data set—the library or data set name that you want the moved data stored under.

Note: The Move/Copy utility does not support:

- Supplying a volume serial when attempting to copy a multivolume data set
- Copying unmovable data sets (data set organization POU or PSU).

M — move data set or member(s): Use option M to move a data set. You can specify either a DASD-resident sequential or partitioned data set for both the "From" or "To" data sets.

Option M causes data sets to be deleted after they have been successfully moved to the "To" data set, as follows:
- If the "From" data set is partitioned, the selected members are deleted from it.
- If the "From" data set is sequential, the complete "From" data set is deleted.

MP — move and print: Same as option M, except source listings are recorded in the ISPF list data set, as follows:

- If the "To" data set is partitioned, a listing of each new or replaced member is recorded.
- If the "To" data set is sequential, a listing of its complete contents is recorded.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
 MOVE     From MYPROJ.DEV.SOURCE
                                                                 More:     +
 Specify "To" Data Set Below

 To ISPF Library:                Options:
    Project  . . MYPROJ             Enter "/" to select option
    Group  . . . DEV                _  Replace like-named members
    Type . . . . SOURCE             /  Process member aliases

 To Other Partitioned or Sequential Data Set:
    Data Set Name . . . ______________________________________________
    Volume Serial . . . ______     (If not cataloged)

 Data Set Password  . .           (If password protected)

 To Data Set Options:
    Sequential Disposition        Pack Option         SCLM Setting
    1  1. Mod                     3  1. Yes           3  1. SCLM
       2. Old                        2. No              2. Non-SCLM
 Command ===> ______________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 95. Move/Copy Utility - "To" panel for moving (ISRUMC2B)

All the fields on the Move/Copy Utility "To" panels for moving data sets are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*, except these general Options and To Data Set Options:
- Replace like-named PDS members.
- Process member aliases
- Sequential Disposition
- Pack Option
- SCLM Settings

See "C and CP — copying data sets" on page 133 for descriptions of these fields.

Using the move/copy utility with load modules

For a move or copy of load modules, these rules apply:

- Both data sets must be partitioned and must have an undefined record format (RECFM=U).
- Load modules that were created for planned overlay cannot be moved or copied.
- The print option, if specified, is ignored.
- If the "To" library is LLA-managed, it must be in NOFREEZE mode.
- For Move or Copy, reblocking can be done for load modules only, and is done by using the IEBCOPY COPYMOD function. Whether the load module is reblocked depends on the block sizes for the "To" and "From" data sets, as well as the value of the USE_IEBCOPY_COPY_OR_COPYMOD_OPTION and WHEN_TO_USE_IEBCOPY keyword settings in the ISPF Configuration table (see *z/OS ISPF Planning and Customizing* for more information).
  - If the WHEN_TO_USE_IEBCOPY setting is 0, IEBCOPY is only used:
    - When copying from a data set with a larger block size to a data set with a smaller block size.
    - When a PDSE has been specified in the ″From″ data set concatenation or as the ″To″ data set.
  - If the WHEN_TO_USE_IEBCOPY setting is 1, IEBCOPY is always used to copy load modules.
  - If the WHEN_TO_USE_IEBCOPY setting is 2, IEBCOPY is only used when a PDSE has been specified in the ″From″ data set concatenation or as the ″To″ data set.
  - If the WHEN_TO_USE_IEBCOPY setting indicates that IEBCOPY should be used, these rules apply when determining whether to reblock or not:
    - When the USE_IEBCOPY_COPY_OR_COPYMOD_OPTION setting is 1:
      - If the "To" and "From" block sizes are the same, no reblocking occurs. ISPF uses IEBCOPY COPY.
      - If the "To" block size is larger than the "From" block size, no reblocking occurs. ISPF uses IEBCOPY COPY.
      - If the "To" block size is smaller than the "From" block size, reblocking occurs. ISPF uses IEBCOPY COPYMOD.
    - When the USE_IEBCOPY_COPY_OR_COPYMOD_OPTION setting is 2:
      - If the "To" and "From" block sizes are the same, no reblocking occurs. ISPF uses IEBCOPY COPY.
      - If the "To" block size is larger than the "From" block size, reblocking occurs. ISPF uses IEBCOPY COPYMOD.
      - If the "To" block size is smaller than the "From" block size, reblocking occurs. ISPF uses IEBCOPY COPYMOD.
  - When the USE_IEBCOPY_COPY_OR_COPYMOD_OPTION setting is 3:
    - Reblocking occurs. ISPF uses IEBCOPY COPYMOD.
- If IEBCOPY is used to process the copy, ISPF allocates these data sets:

zprefix.zuser.SPFnnn.IEBCOPY	IEBCOPY SYSPRINT data set
SYSIN	IEBCOPY SYSIN data set
SYSUT3 and SYSUT4	IEBCOPY work data sets

The SYSPRINT data set is deleted when the copy ends successfully. If errors are encountered, it is kept to help you diagnose errors. SYSIN, SYSUT3, and SYSUT4 are temporary data sets that use VIO if available, and are freed upon completion of the copy. All allocations use the value of ISPF Configuration table keyword PDF_DEFAULT_UNIT as the unit. The sizes for the SYSUT3 and SYSUT4 data sets are calculated dynamically, based on the number of members to be copied.

If this is not sufficient for your move/copy request, these DDNAMES can be preallocated. If they are preallocated, ISPF does not free them when the copy is finished.

Moving or copying alias entries

Alias entries can be moved or copied from one partitioned data set to another under these conditions:

- If the "To" library is LLA-managed, it must be in NOFREEZE mode
- If the "Process member aliases" option has been selected (ALIAS mode), these rules apply:
  - Either the Primary member or any alias member may be selected to copy the primary member and all of its aliases. This will occur even if a single member is specified or some of the members are not displayed in the current member selection list.
  - Alias members are copied for both load and non-load data sets, as well as for PDS and PDSE data sets.
  - Copying to the same data set is not supported when aliases are automatically selected, as this would result in the from and to member name being the same.
- If ISPF is not using IEBCOPY and the "Process member aliases" option has not been selected (NOALIAS mode):
  - After the move or copy is successfully completed for the main member or members, then the alias entry or entries can be copied.
  - From a member list:
    - When the main member or members are selected first, are not renamed, and are successfully moved or copied, then the alias entry or entries can be copied if they are selected without leaving the member list.
    - If the target data set is a PDSE, alias entries cannot be copied.
- If IEBCOPY is being used and NOALIAS is in effect:
  - The method described for copying when not using IEBCOPY will also work when using IEBCOPY. In addition, if all main members and aliases are selected at the same time they are processed by the same invocation of IEBCOPY and are copied correctly.
  - If the target data set is a PDSE, alias entries must be selected and processed together with the main member.

In all other cases for move and copy where NOALIAS is in effect, you can select alias names, but they are not preserved as aliases in the "To" data set. That is, the members to which they refer are moved or copied, and the alias entries are stored in the "To" data set with the alias flags turned off.

Member list processing when using IEBCOPY

When copying load modules using the IEBCOPY interface, all selected members are processed as a group. This means that the processing does not stop on the first failure but will attempt to process all selected members before the member list is redisplayed. The Prompt field will be updated to indicate the result for each individual member.

No error message is displayed if two or more members are not processed successfully because they may have failed for different reasons. Reselecting a member and processing it individually will display a specific error message if the processing for that member fails again. These values can appear in the Prompt field:

***COPIED**	Member was copied or copied/locked successfully
***MOVED**	Member was moved successfully
***REPL**	Member was replaced in the output library (Moved or Copied)
***NO DATA**	Member was not found in the input library or BLDL error
***INUSE-I**	ENQ failed on input member
***INUSE-O**	ENQ failed on output member
***NO-COPY**	Member was not copied successfully
***MIXED**	You are attempting to mix load and non-load data
***NO-DEL**	The delete step failed on a Move request
***NO-REPL**	Member exists in the output library and replace not requested
***NO-LOCK**	LMF lock failed on Copy/Lock request
***ALIAS**	Member is a PDSE Program Object alias and cannot be copied individually. It will be copied when the main member is copied.

Data set list utility (option 3.4)

When you select this option, the Data Set List Utility panel (Figure 96) is displayed. You can either display or print lists of ISPF libraries, data sets, or volume table of contents (VTOC) information.

```
  Menu  RefList  RefMode  Utilities  Help
 ------------------------------------------------------------------------------
                            Data Set List Utility

   blank Display data set list              P Print data set list
       V Display VTOC information          PV Print VTOC information

Enter one or both of the parameters below:
   Dsname Level . . .    PDFTOOL.COMMON
   Volume serial  . .    ______

Data set list options
   Initial View                Enter "/" to select option
   1  1. Volume                /  Confirm Data Set Delete
      2. Space                 /  Confirm Member Delete
      3. Attrib                /  Include Additional Qualifiers
      4. Total                 /  Display Catalog Name
                               /  Display Total Tracks

When the data set list is displayed, enter either:
  "/" on the data set list command field for the command prompt pop-up,
  an ISPF line command, the name of a TSO command, CLIST, or REXX exec, or
  "=" to execute the previous command.
Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 96. Data Set List Utility panel (ISRUDLP)

Data Set List Utility panel action bar

The Data Set List Utility Panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

RefList For information about referral lists, see the topic about Using Personal Data Set Lists and Library Lists in the *z/OS ISPF User's Guide Vol I*.

Note: When you use a referral list from within the Data Set List Utility, these functions are performed before the referral list is processed:

- The quotes are removed from the data set name.
- The value in ZPREFIX is added preceding the non-quoted data set name if the first qualifier is not ZPREFIX.
- The member name is removed.

RefMode For information about referral list modes, see the details about Personal List Modes in the Using Personal Data Set Lists and Library Lists topic in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down provides information about displaying and printing data set lists and VTOC information.

Data Set List Utility panel fields

The fields on this panel are:

Dsname level

This field is used to specify the level or levels of any data set that you want ISPF to list or print for you. An optional installation exit, called the data set list (DSLIST) exit, can control whether a data set name should appear in the list. See *z/OS ISPF Planning and Customizing* for more information about this exit.

When you specify the Dsname Level, you are defining the level qualifiers for the data set names to be included in the list. Therefore, in Figure 96 on page 139, the value PDFTOOL.COMMON represents the first two levels of a data set name. An ISPF library typically has a three-level name: project, group, and type.

The Dsname Level field supports the inclusion of system symbols.

ISPF retains the information you put in this field and displays it the next time you use this panel.

Except for the first level, you can specify the level qualifiers fully, partially, or use defaults. Do not enclose the value in the Dsname Level field in quotes.

Asterisks and percent signs may be used to filter the list of data sets that is displayed. For ICF catalog lists and volume lists, asterisks and percent signs may be used in the high-level qualifier. Asterisks may be used anywhere in a qualifier, not just in the first and last positions. However, one qualifier must be at least partially qualified.

A single asterisk by itself indicates that at least one qualifier is needed to occupy that position. A single asterisk within a qualifier indicates that zero or more

characters can occupy that position. A double asterisk by itself indicates that zero or more qualifiers can occupy that position. A double asterisk is invalid within a qualifier.

In this example, all data set names with SYS1 as the first qualifier and at least one other qualifier will be listed.

```
SYS1.*
```

In this example, all data set names with SYS1 as the first qualifier will be listed.

```
SYS1 or SYS1.**
```

In this example, all data set names that have a qualifier of `CLIST` and are in catalogs that you have authority to will be listed. A VTOC list will contain all data set names that have a qualifier of `CLIST`.

```
**.CLIST
```

Notes:

1. If you enter a high-level qualifier of '*' or '**', ISPF displays a pop-up window to warn you that the search will be for all catalogs on the system and will take time. If there are many catalogs, this search could take a considerable amount of time. You can press Enter to continue the search, or you can enter Cancel or End from the pop-up window to cancel the search. Be aware that if you have mount authority, a catalog search with '*' or '**' as the high-level qualifier can require that volumes be mounted for the catalogs to be searched.
2. The ISPF Configuration table contains a selectable option, named DISALLOW_WILDCARDS_IN_HLQ, to disallow the use of the '*' or '%' in the high-level qualifier.

A single percent sign indicates that any one single alphanumeric or national character can occupy that position. One to eight percent signs can be specified in each qualifier. This example is valid for Dsname Level:

```
AAA%*.B*%%%B.C
```

In this example, the list will contain all data sets that start with AAA and one or more other characters, have a second qualifier that starts and ends with B and has at least three other characters between the B's, and have a third qualifier of 'C'. The list will contain entries from catalogs that you have authority to. A VTOC list will contain entries that match these characteristics.

In this example, the list will contain all data sets that start with SYS and one other character, such as SYS1 or SYS2.

```
SYS%
```

If you enter a SYS% alias for a SYS1 data set as the Dsname Level (for example, SYSP as a single qualifier), you see SYSP as an ALIAS because this single qualifier is an alias for SYS1. The data set names pointed to by a SYS% alias can be displayed in a data set list by entering any of these:

- a Dsname Level of SYS1 and a volume
- a Dsname Level of SYS%
- a Dsname Level of the fully qualified data set name (such as SYSP.PARMLIB)

`PRO**CT` is not valid as a data set name level because a double asterisk (**) is not valid in the middle of a qualifier.

Alias names that match the specified Dsname Level will be displayed as the alias name itself. The volume field for all alias names will contain the characters '*ALIAS' to indicate this. Real names that match the Dsname Level will also be displayed.

If you enter ISPFTEST as a Dsname Level and you have real data set names that start with ISPFTEST and aliases for those real names that start with ISPFTEST, you would see a list of this format:

```
ISPFTEST.BASE.CLIST                      TSOPK1
ISPFTEST.BASE.CLIST.ALIAS                *ALIAS
ISPFTEST.BASE.SOURCE                     TSOPK1
ISPFTEST.BASE.SOURCE.ALIAS               *ALIAS
```

A VSAM cluster entry is flagged in the volume field as '*VSAM*'. A VSAM path entry is flagged in the volume field as '*PATH*'. A VSAM alternate index entry is flagged in the volume field as '*AIX*'.

Notes:

1. A catalog search may result in the DSLIST containing duplicate names. This can occur when the definition of user catalog aliases results in multiple catalogs being searched when the data set list is built. Line commands against duplicate data sets in the DSLIST are supported. Selecting the "Display Catalog Name" option will display the name of the catalog associated with each data set on the Total view. This can identify where duplicate data set names were found. The existence of duplicates may be inconsistent when changing the DSLEVEL qualifiers. For example, SYS1.PARM.* may have different results than SYS1.PAR*. Duplicate entries may or may not display in a consistent manner, however the DSLIST will always be complete, with no omissions.
2. If a VSAM cluster matches the Dsname Level, all parts of the cluster are listed even if the data and index portions do not match the Dsname Level.

   When a multicluster (key-range) data portion of a VSAM cluster is displayed on a catalog list, no information is shown except for the volume and device. The information comes from the VTOC and the catalog name does not match the VTOC name. When using a VTOC list the information is displayed.

Volume serial

Use this field to specify the volume serial whose VTOC is to be used by ISPF to display or print a list of data set names or VTOC information. ISPF retains the information you put in this field and displays it the next time you use this panel.

If you want to display a list of only the data sets that reside on a particular volume, leave the Dsname Level field blank and enter the volume serial in the Volume field.

The Volume serial field supports the inclusion of system symbols.

You can enter a single volume name or a generic volume name to list data sets from more than one volume. The volume name can be partially specified using asterisks as global volume name characters and percent signs as placeholders in the volume name. A single asterisk within a volume name indicates that zero or more characters can occupy that position. A single percent sign indicates that any one alphanumeric or national character can occupy that position. Examples follow.

*	Lists data set names matching the Dsname Level from all volumes
PRM*	Lists names from all volumes beginning with 'PRM'

M%C* Lists names from volumes beginning with 'M', followed by any single character, a 'C', and any three other characters

Notes:

1. Specifying a single asterisk as a volume name will require more time to display of print the VTOC list.
2. A generic volume name can not be used to display VTOC information.

Initial view

Use this field to tell ISPF which view of the data set list you would like to see. ISPF retains the information you put in this field and displays it the next time you use this panel.

All the scroll commands function normally from these displays, except for the LEFT and RIGHT commands. These commands switch from one view to another, because the panels used to show the different views are connected as if they formed a ring. Each time you enter the LEFT or RIGHT command, another view is displayed in the sequence shown in Figure 97, starting from the current view.



Figure 97. Sequence of data set list display views

If you enter the RIGHT command with the Total view in the sequence displayed, ISPF displays the Volume view. If you enter the LEFT command with the Volume view displayed, ISPF displays the Total view. The available views are:

1. Volume This view shows a data set list that contains data set names and the volumes on which they reside. Figure 98 on page 147 shows a typical data set list display using the Volume view.

2. Space The Space view shows a data set list that contains data set names, tracks, percentages used, extents, and devices. An additional header line, displayed above the column headings and showing the total tracks of all data sets, the total tracks of all non-excluded datasets, the number of data sets listed and the number of non-excluded data sets listed, is displayed if the Display Total Tracks option is selected. Figure 99 on page 149 shows a typical data set list display using the Space view with the Total Tracks header line.

3. Attrib This view shows a data set list that contains data set names, data set organizations, record formats, logical record lengths, and block sizes. Figure 100 on page 149 shows a typical data set list display using the Attributes view.

Note: For each of the views, the list is sorted by data set name. See the list under Figure 101 on page 150 for descriptions of the fields shown on this panel.

4. Total This view shows a data set list that contains all the information displayed by the Volume, Space, and Attributes views, plus the created, expired, and referred dates. The list is sorted by data set name and has two lines per data set. Figure 101 on page 150 shows a typical data set list display using the Total view.

The catalog name can also be displayed if the Display Catalog Name option is selected and no value is entered into the Volume Serial field. If the Display Catalog Name option is selected, three lines per data set are displayed. Figure 102 on page 150 shows a typical data set list display using the Total view with the Catalog name. See the list under the figure for descriptions of the fields shown on this panel.

An additional header line, displayed above the column headings and showing the total tracks of all data sets, the total tracks of all non-excluded datasets, the number of data sets listed, and the number of non-excluded data sets listed, is displayed if the Display Total Tracks option is selected.

Confirm data set delete

This field controls whether the Confirm Delete panel appears when you use the D (delete data set) line command or the TSO DELETE command from the displayed data set list. Use a slash to select this option.

If you select this option, ISPF displays the Confirm Delete panel (Figure 85 on page 124), giving you an opportunity to change your mind and keep the data set. If you try to delete an unexpired data set, the Confirm Purge panel (Figure 86 on page 125) is displayed following the Confirm Delete panel. Follow the directions on the panel to either confirm or cancel the data set purge.

Attention:

If you deselect the option and the data set is deleted, it cannot be retrieved.

See “D — delete data set” on page 164 for more information about the D line command.

Confirm member delete

This field controls whether the Confirm Member Delete panel is displayed when you use the D (delete) command for a member in the displayed data set list. Use a slash to select this option.

If you select this option, ISPF displays the Confirm Member Delete panel. This panel gives you an opportunity to change your mind and keep the member.

Include additional qualifiers

This field is used to generate the data set list with all data sets matching the qualifiers in the Dsname Level field, including data sets with additional qualifiers.

If this field is not selected, the data set list will include only data sets that match the qualifiers entered in the Dsname Level field.

Examples: Assume that these data sets exist:

```
PDFTOOL.COMMON.ASM
PDFTOOL.COMMON.CLIST
PDFTOOL.COMMON.CLIST.OLD
PDFTOOL.COMMON.CLIST.VB
PDFTOOL.COMMON.CNTL
PDFTOOL.COMMON.CNTL.INPUT
PDFTOOL.COMMON.EXEC
```

1. List data sets whose name starts with PDFTOOL.COMMON. The data set can include additional qualifiers:

```
Dsname Level . . . PDFTOOL.COMMON          PDFTOOL.COMMON.ASM
/  Include Additional Qualifiers           PDFTOOL.COMMON.CLIST
                                           PDFTOOL.COMMON.CLIST.OLD
                                           PDFTOOL.COMMON.CLIST.VB
                                           PDFTOOL.COMMON.CNTL
                                           PDFTOOL.COMMON.CNTL.INPUT
                                           PDFTOOL.COMMON.EXEC
```

2. List data sets whose name is PDFTOOL.COMMON, with no additional qualifiers:

```
Dsname Level . . . PDFTOOL.COMMON          (No data set names found)
_  Include Additional Qualifiers
```

3. List data sets whose name starts with PDFTOOL.COMMON and whose third qualifier starts with “C”. The data set can include additional qualifiers:

```
Dsname Level . . . PDFTOOL.COMMON.C*       PDFTOOL.COMMON.CLIST
/  Include Additional Qualifiers           PDFTOOL.COMMON.CLIST.OLD
                                           PDFTOOL.COMMON.CLIST.VB
                                           PDFTOOL.COMMON.CNTL
                                           PDFTOOL.COMMON.CNTL.INPUT
```

4. List data sets whose name starts with PDFTOOL.COMMON and whose third qualifier starts with “C”. The data set must not have additional qualifiers after the third qualifier:

```
Dsname Level . . . PDFTOOL.COMMON.C*       PDFTOOL.COMMON.CLIST
_  Include Additional Qualifiers           PDFTOOL.COMMON.CNTL
```

Display catalog name

Use this option to have the Total view display for each data set in the list the name of the catalog in which the data set was located.

The option is only applicable when a catalog search is used to build the Data Set List, therefore, it is ignored when a value is entered in the Volume Serial field.

Display total tracks

Use this option to display an additional header line on the Space or the Total view, showing the total tracks of all data sets, the total tracks of all non-excluded datasets, the number of data sets listed, and the number of non-excluded data sets listed.

Depending on the size of the data set list, processing time increases because the tracks information for all datasets has to be collected before the list is displayed.

When the list comprises 50 data sets or more, a pop-up panel is displayed, indicating the progress of the data collection.

Data set list utility options

Sub-sections describe the options shown on the Data Set List Utility panel.

Blank — display data set list

Leave the Option line blank to display a data set list. You can use these parameters to control what data set information is displayed and how delete requests are processed:

1. Enter one or more data set name level qualifiers in the Dsname Level field. See "Dsname level" on page 140 for more information.
2. Enter a volume serial in the Volume field if you want ISPF to create a data set list from the VTOC. If you leave this field blank, the list is created from the catalog. See "Volume serial" on page 142 for more information.
3. In the Initial View field, enter the view of the data set list (Volume, Space, Attributes, or Total) that you want to see first. Examples of these views are shown in Figure 98 on page 147, Figure 99 on page 149, Figure 100 on page 149, and Figure 101 on page 150, respectively.
4. Enter a slash (/) in the Confirm Data Set Delete field to tell ISPF to display a confirmation panel if you enter the D (delete data set) line command or the TSO DELETE command. See "Confirm data set delete" on page 144 for more information.
5. Enter a slash (/) in the Confirm Member Delete field to tell ISPF to display a confirmation panel if you enter the D (delete) command for a member in a data set list.
6. Enter a slash (/) in the Include Additional Qualifiers field to tell ISPF to list all data sets that match the qualifiers in the Dsname Level field, including data sets with additional qualifiers.
7. Enter a slash (/) in the Display Catalog Name field to tell ISPF to display the name of the catalog associated with each data set in the Total view.
8. Enter a slash(/) in the Display Total Tracks field to tell ISPF to display an additional header line above the column headings, showing the total tracks of all data sets, the total tracks of all non-excluded datasets, the number of data sets listed and the number of non-excluded data sets listed. Depending on the size of the data set list, processing time increases because the tracks information has to be collected for the whole list up front. When the list comprises 50 data sets or more, a pop-up panel is displayed, indicating the progress of the data collection.
9. Press Enter to display the data set list, as shown in Figure 98 on page 147.

Note: If a plus displays after the volume serial (for example, HSM020+) on a list obtained from the catalog, the data set spans multiple volumes. Information displayed about that data set by selecting Information or Short Information or by using the Space or Total view will represent the total amounts across all used volumes.

When a VTOC list is displayed and a multivolume data set is included on that volume, there will not be an indicator that this data set spans multiple volumes, and the information on a space or total view will be for that volume only. The information displayed on a VTOC list is only information obtained from the VTOC of that volume. When the multivolume data set is selected for information or for short information, the space information will

be for all volumes that the data set spans.

```
 Menu  Options  View  Utilities  Compilers  Help
 ___________________________________________________________________________
DSLIST - Data Sets Matching HANKO3                                Row 1 of 14

Command - Enter "/" to select action                 Message          Volume
-----------------------------------------------------------------------------
         HANKO3                                                       *ALIAS
         HANKO3.DDIR                                                  *VSAM*
         HANKO3.DDIR.D                                                D$US50
         HANKO3.DDIR.I                                                D$US50
         HANKO3.EXEC                                                  D$US08
         HANKO3.ISD1.ISPF.ISPPROF                                     D$US23
         HANKO3.ISD1.ISPVCALL.TRACE                                   D$US48
         HANKO3.ISPF.ISPPROF                                          D$US26
         HANKO3.ISPVCALL.TRACE                                        D$US14
         HANKO3.LOAD                                                  D$US08
         HANKO3.MAKEDSNS.OUTPUT                                       D$US35
         HANKO3.SYS2.BRODCAST                                         D$US04
         HANKO3.TASID.SNAPSHOT                                        D$US05
         HANKO3.TEST                                                  D$US08
**************************** End of Data Set list ****************************
Command ===> ____________________________________________ Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 98. Data set list - volume view (ISRUDSL0)

Data set list panel action bar: The Data Set List panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Options

The Options pull-down offers these choices:

DSLIST Settings

The settings to control the behavior of the data set list display. Options are:

- Display Edit/View entry panel

  Note: If this field is selected and a workstation Edit request is initiated when no valid workstation connection exists, ISPF indicates on the Edit/View entry panel that no connection exists and treats the request as a host Edit request.
- Update ON (Reference lists)
- List pattern for MO,CO,RS,D actions
- Show status for MO,CO,RS,D actions
- Confirm Member delete
- Confirm Data Set delete
- Do not show expanded command
- E,V,B enhanced member list

  Selecting this choice causes the enhanced member list to be used when the E,V, or B commands are used. De-selecting this choice causes traditional member list processing to occur.

- Display Total Tracks

Refresh List
Refresh the display of the data set list.

Append to List
Select a Personal data set list to append to the existing DSLIST. The DSLIST is rebuilt, including the data sets or data set name levels from the personal list selected.

Note: The APPEND is based on the selected personal data set list. If an entry in the list is not quoted, your TSO prefix is added as the first level of the data set name. If the entry contains a member, the member is ignored. Duplicate personal list entries are ignored. If the entry contains a volume and "Include volume on retrieve" is selected on the Referral List Settings panel, a VTOC search is used instead of the catalog. A catalog search is recommended for best performance. A volume should be used only if the data set is not cataloged.

Enter the DSLIST primary command REFRESH on the DSLIST display panel to erase all appended personal lists.

Save List
Saves the data set list to a file.

Reset Resets the data set list.

View The View pull-down offers these choices:

Note: The current setting is shown as an unavailable choice; that is, it is displayed in blue (the default) with an asterisk as the first digit of the selection number (if you are running in GUI mode, the choice will be *grayed*).

1 **Volume** Changes the display to the Volume view, as shown in Figure 98 on page 147.

2 **Space** Changes the display to the Space view.

```
  Menu  Options  View  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 DSLIST - Data Sets Matching HANKO3                                Row 1 of 14

 Total Tracks:          86 non-x:         86   Data Sets:     14 non-x:     14
 ------------------------------------------------------------------------------
 Command - Enter "/" to select action                       Tracks %Used   XT
 ------------------------------------------------------------------------------
          HANKO3
          HANKO3.DDIR
          HANKO3.DDIR.D                                        45    ?     1
          HANKO3.DDIR.I                                         1    ?     1
          HANKO3.EXEC                                          15   12     1
          HANKO3.ISD1.ISPF.ISPPROF                              1  100     1
          HANKO3.ISD1.ISPVCALL.TRACE                            2  100     1
          HANKO3.ISPF.ISPPROF                                   1  100     1
          HANKO3.ISPVCALL.TRACE                                 2  100     1
          HANKO3.LOAD                                          15   13     1
          HANKO3.MAKEDSNS.OUTPUT                                1  100     1
          HANKO3.SYS2.BRODCAST                                  1    0     1
          HANKO3.TASID.SNAPSHOT                                 1  100     1
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 99. Data set list - space view (ISRUDSL0)

3 **Attributes** Changes the display to the Attributes view.

```
  Menu  Options  View  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 DSLIST - Data Sets Matching HANKO3                                Row 1 of 14

 Command - Enter "/" to select action                 Dsorg  Recfm  Lrecl  Blksz
 ------------------------------------------------------------------------------
          HANKO3
          HANKO3.DDIR                                  VS
          HANKO3.DDIR.D                                VS    ?          ?      ?
          HANKO3.DDIR.I                                VS    ?          ?      ?
          HANKO3.EXEC                                  PO-E  FB        80  32720
          HANKO3.ISD1.ISPF.ISPPROF                     PO    FB        80  27920
          HANKO3.ISD1.ISPVCALL.TRACE                   PS    FB        80  27920
          HANKO3.ISPF.ISPPROF                          PO    FB        80   6160
          HANKO3.ISPVCALL.TRACE                        PS    FB        80  27920
          HANKO3.LOAD                                  PO    U          0  32760
          HANKO3.MAKEDSNS.OUTPUT                       PS    FB        80  27920
          HANKO3.SYS2.BRODCAST                         PS    FB       150   1500
          HANKO3.TASID.SNAPSHOT                        PS    VBA      255  27998
          HANKO3.TEST                                  PS    VBA      138  13800
 ***************************** End of Data Set list *****************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 100. Data set list - attributes view (ISRUDSL0)

4 **Total** Changes the display to the Total view.

```
  Menu  Options  View  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
DSLIST - Data Sets Matching HANKO3                                Row 1 of 14

Total Tracks:          86 non-x:         86   Data Sets:     14 non-x:     14
 ------------------------------------------------------------------------------
Command - Enter "/" to select action                 Message           Volume
      Tracks  %     XT Device  Dsorg Recfm Lrecl Blksz  Created    Referred
 ------------------------------------------------------------------------------
         HANKO3                                                        *ALIAS

 ------------------------------------------------------------------------------
         HANKO3.DDIR                                                   *VSAM*
                                  VS
 ------------------------------------------------------------------------------
         HANKO3.DDIR.D                                                 D$US50
          45   ?     1 3390     VS   ?         ?     ? 2007/02/21 2007/02/21
 ------------------------------------------------------------------------------
         HANKO3.DDIR.I                                                 D$US50
           1   ?     1 3390     VS   ?         ?     ? 2007/02/21 ***None***
 ------------------------------------------------------------------------------
Command ===> ____________________________________________________ Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 101. Data set list - total view (ISRUDSL0)

```
  Menu  Options  View  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
DSLIST - Data Sets Matching HANKO3                                Row 1 of 14

Total Tracks:          86 non-x:         86   Data Sets:     14 non-x:     14
 ------------------------------------------------------------------------------
Command - Enter "/" to select action                 Message           Volume
      Tracks  %     XT Device  Dsorg Recfm Lrecl Blksz  Created    Referred
          Catalog
 ------------------------------------------------------------------------------
         HANKO3                                                        *ALIAS

          CATALOG.MASTER.SYSPLEXD
 ------------------------------------------------------------------------------
         HANKO3.DDIR                                                   *VSAM*
                                  VS
          CATALOG.USER1.SYSPLEXD
 ------------------------------------------------------------------------------
         HANKO3.DDIR.D                                                 D$US50
          45   ?     1 3390     VS   ?         ?     ? 2007/02/21 2007/02/21
          CATALOG.USER1.SYSPLEXD
Command ===> ____________________________________________________ Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 102. Data set list - total view with catalog name (ISRUDSL0)

5 **Sort** You can sort the data set list by any of these fields:
   1. Name
   2. Message
   3. Volume
   4. Tracks
   5. Percent Used
   6. Extents

7. Dsorg
8. Recfm
9. Lrecl
10. Blksz
11. Creation date
12. Expiration date
13. Referenced date
14. Device
15. Volume indicator
16. Catalog

You can also specify the sort sequence (ascending or descending) or accept the default sequence for the associated sort field. By default, character fields are sorted alphabetically and numeric fields are sorted in descending order.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Compilers
The Compilers pull-down offers you these choices:

1 **Foreground Compilers**. Displays the Foreground Selection Panel.

2 **Background Compilers**. Displays the Batch Selection Panel.

3 **ISPPREP Panel Utility** Displays the Preprocessed Panel Utility panel.

4 **DTL Compiler** Displays the ISPF Dialog Tag Language Conversion Utility panel.

Help The Help pull-down provides general information about the data set list, including the format of the displayed list and the available line commands and primary commands.

Data set list panel fields: The fields listed here can appear on the data set list panels. The fields displayed will vary depending on the view that you select.

Total Tracks Total number of tracks of all data sets in the list.

non-x Total number of tracks of all data sets in the list, not including the tracks of all excluded data sets.

When the number of total tracks or total non-excluded tracks exceeds 10 digits (the maximum provided in the header line), the display changes as follows:

*nnnnnnnn***kB**
Kilobyte. The total number is divided by 1024.

*nnnnnnnn***MB**
Megabyte. The total number is divided by 1024*1024.

*nnnnnnnn***GB**
Gigabyte. The total number is divided by 1024*1024*1024.

*nnnnnnnn***TB**
Terabyte. The total number is divided by 1024*1024*1024*1024.

The unchanged number of tracks and non-excluded tracks is available in the shared pool variables ZDLSIZET and ZDLSIZTX .

Data Sets Total number of data sets in the list.

non-x Total number of data sets in the list, not including excluded data sets.

Command Field used to enter a line command, TSO command, CLIST, or REXX EXEC when displaying a data set list. See "Data set list utility line commands" on page 160 for more information.

Name Data set name, as in the VTOC or catalog.

Message This field is initially blank. After you perform an operation on a data set using one of the built-in line commands, one of these messages is displayed in this field:

Line Command	Message
B	Browsed
C	Cataloged
E	Edited
U	Uncataloged
D	Deleted
P	Printed
PX	Index Printed
R	Renamed
I	Info - I
M	Member List
S	Info - S
Z	Compressed
F	Free Completed
=	(message shown for last command entered)
V	Viewed
RA	Refadd
CO	Copied
MO	Moved
RS	Reset
X	– 1 data set(s) not displayed
NX	(no message)
NXF	(no message)
NXL	(no message)

If you enter a TSO command, CLIST, or REXX exec on the Command line, a default message appears in the Message field. The message you see can be one of these:

- In this format, depending on the results of the TSO command, CLIST, or REXX exec:

  ```
  XXXXXXXX  RC=#
  ```

  where:

  XXXXXXXX The command entered

  # The return code.
- "ERROR MSG LOGGED".

  This may occur with PDSE or HFS data sets. A fully formatted message appears in the ISPF log, provided one has been allocated.

Note: See "Data set list utility line commands" on page 160 for a description of the Data Set List Utility line commands.

Volume Volume serial number.

Multivol Indicates more than one volume or a migration level in this manner:

+ (plus sign)
More than one volume
1 Migrated to disk
2 Migrated to tape

Tracks Number of tracks allocated to the data set.

%Used Percentage of allocated tracks used, expressed in whole numbers, not rounded. If any track is used, the minimum percentage is 1. If the data set is a PDSE, the % refers to the percentage of allocated pages used.

See "F — free unused space" on page 165 for information about freeing track space manually.

Note: Space utilization values are not displayed for ISAM, VSAM, or BDAM data sets.

XT Number of extents allocated to the data set.

Device Device type on which the volume that contains the data set is mounted.

Dsorg One of the data set organizations shown. In the definitions of these data set organizations, *unmovable* means the data set contains absolute addresses instead of relative addresses. These data sets are not moved to any other DASD storage location during read/write operations.

PS Sequential
PS-E Sequential Extended Format
PS-L Large Format Sequential
PSU Sequential unmovable
PO Partitioned
POU Partitioned unmovable
PO-E Partitioned extended (PDSE)
DA Direct
DAU Direct unmovable
HSF MVS Hierarchical File System
IS Indexed sequential
ISU Indexed sequential unmovable
VS VSAM
VS-E VSAM Extended Format
blank None of the preceding data set organizations.

Recfm Record format specified when the data set was allocated. See "A — allocate new data set" on page 114 for more information about record formats.

Lrecl Logical record length, in bytes, specified when the data set was allocated.

Blksz Block size, in bytes, specified when the data set was allocated.

Created Creation date in the national format.

Expires Expiration date in the national format, specified when the data set was allocated. If no expiration date was specified, ***None*** is displayed. If a "never expire" date (1999/12/31 or its equivalent) is

specified, ***Perm*** is displayed. See "A — allocate new data set" on page 114 for more information about expiration dates.

Note: The expiration date is only available with the I and S line commands.

Referred Date, in the national format, that this data set was last accessed.

Catalog The name of the catalog in which the data set was located. Only displayed in the Total view when the Display Catalog Name option is selected and no value is entered in the Volume Serial field.

Actions you can take from the data set list panel: These topics describe actions you can take from the Data Set List panel:
- "Line commands"
- "TSO commands, CLISTs, and REXX EXECs"
- "Using the slash (/) character"
- "TSO command/CLIST/REXX exec variables" on page 156

Line commands: Line commands can be entered in the Command field to the left of the data set names. See "Data set list utility line commands" on page 160 for definitions of these line commands.

TSO commands, CLISTs, and REXX EXECs: Besides the ISPF-supplied line commands, you can also enter TSO commands, CLISTs, and REXX EXECs that use a fully qualified data set name as an operand. You can type over the field containing the data set name to enter commands that require more space than is provided in the Command field. ISPF determines the end of the command by scanning the Command field and the field containing the data set name from right to left. The first character found that differs from the original is considered to be the last character of the command. Therefore, it is best to enter a blank after the last character of your command if it extends into the field containing the data set name.

TSO commands, CLISTs, and REXX EXECs entered are invoked using the ISPF SELECT CMD service. Variable names starting with an ampersand (&) are evaluated by ISPF. If you want the underlying command processor to see the ampersand you must specify 2 ampersands. For example:

```
DEF NONVSAM(NAME(/) DEVT(0000) VOLUME(&&SYSR2))
```

Note: If the TSO command, CLIST, or REXX exec issues a return code greater than or equal to 8, processing stops and an error message is displayed.

Using the slash (/) character: If a command, CLIST, or REXX exec requires the data set name in a position other than the first operand or if other operands are needed, you can use the slash (/) character to represent the quoted data set name. If no operands are specified after the command, ISPF uses the name of the data set being acted on as the command's first operand.

To specify a member of a partitioned data set, enclose the member name or pattern in parentheses immediately following the / character. You can use this format with the V (view data set), B (browse data set), D (delete data set), E (edit data set), and M (display member list) line commands. For information about these line commands, see "Data set list utility line commands" on page 160.

You may find it helpful to call the SHOWCMD primary command before using the slash (/) for the first time. After you call SHOWCMD, a special Data Set List Utility panel appears each time you enter a line command, TSO command, CLIST, or REXX exec on a data set list display. The panel shows you the command you entered and how ISPF expanded, and thus interpreted, that command. See "SHOWCMD command" on page 173 for more information about and an example of the SHOWCMD primary command.

The rules shown apply to substituting the slash (/) character for a data set name. Each rule is followed by one or more examples that prove the rule by using either a CLIST or a line command.

In each example, the data set being acted on is USER.TEST.DATA, which always appears, either completely or partially, in uppercase. However, the CLIST or line command is typed in lowercase to differentiate between the CLIST or line command and USER.TEST.DATA when this data set name is either completely or partially typed over.

Each example also shows:

Original The line as it appears before the CLIST or line command is entered.

As typed The line as it appears after the CLIST or line command is typed.

After The line as it appears after the CLIST or line command is expanded to show the placement of quotes and data set name substitution for the slash (/) character.

1. You can type over the data set name. Expanded commands can contain a maximum of 255 characters and are converted to uppercase. This example shows how rule 1 would apply if you typed `%clist1 da(/)`:

```
(Original)          USER.TEST.DATA
(As typed)  %clist1 da(/).TEST.DATA
(After)     %CLIST1 DA('USER.TEST.DATA')
```

2. The data set name substitution character (/) is replaced with the quoted, fully qualified data set name if the character following the / is not a number, letter, or national character. This example shows how rule 2 would apply if you typed `%clist2 / newdate(1986/03/15)`:

```
(Original)          USER.TEST.DATA
(As typed)  %clist2 / newdate(1986/03/15)
(After)     %CLIST2 'USER.TEST.DATA' NEWDATE(1986/03/15)
```

3. If a slash (/) is followed immediately by a member name in parentheses, the ending quote for the data set is placed after the closing parenthesis that follows the member name. This example shows how rule 3 would apply if you typed `%clist3 da(/(xyz))`:

```
(Original)          USER.TEST.DATA
(As typed)  %clist3 da(/(xyz)).DATA
(After)     %CLIST3 DA('USER.TEST.DATA(XYZ)')
```

4. If the first operand is the unquoted data set name as it appears in the list, quotes are added around it or after a closing parenthesis following a member name. This example shows how rule 4 would apply if you typed `b` (the B (browse) line command) and added member `(abc)`:

```
(Original)          USER.TEST.DATA
(As typed)  b       USER.TEST.DATA(abc)
(After)     B 'USER.TEST.DATA(ABC)'
```

5. If the line command does not have any operands or if the data set name has not been substituted as specified by either rule 3 or rule 4, the quoted, fully

qualified data set name is added to the end of the line command. This example shows how rule 5 on page 155 would apply if you typed `%clist4 user.test.fortran`:

```
(Original)          USER.TEST.DATA
(As typed)  %clist4 user.test.fortran
(After)     %CLIST4 USER.TEST.FORTRAN 'USER.TEST.DATA'
```

This example shows how rule 5 on page 155 would apply if you typed `%clist4 'user.test.fortran'`. The purpose of this example is to show that if you enclose the CLIST operand in quotes, ISPF still puts quotes around the data set name being acted on. The results are the same.

```
(Original)          USER.TEST.DATA
(As typed)  %clist4 'user.test.fortran'
(After)     %CLIST4 'USER.TEST.FORTRAN' 'USER.TEST.DATA'
```

This example shows how rule 5 on page 155 would apply if you typed `%clist5 member1(abc)`. The purpose of this example is to show that the results do not change if the CLIST operand contains a member name enclosed in parentheses.

```
(Original)          USER.TEST.DATA
(As typed)  %clist5 member1(abc)ATA
(After)     %CLIST5 MEMBER1(ABC) 'USER.TEST.DATA'
```

TSO command/CLIST/REXX exec variables: If you use a TSO command, CLIST, or REXX exec, ISPF puts the variables described in Table 9 in the shared pool for the TSO command, CLIST, or REXX exec to use.

Table 9. TSO command/CLIST/REXX exec variables (output)

Variable Name	Description	Length in Characters
ZDLBLKSZ	Data set block size	5
ZDLCAT	Cataloged status; one of these: **0** Data set is cataloged on volume ZDLVOL. **2** Data set is cataloged on a volume other than ZDLVOL and is either: • on volume ZDLCAT but uncataloged • on volume ZDLCAT and defined in a user catalog that is connected to the master catalog, but not in the normal catalog search path The name of the user catalog is in ZDLCATNM. **4** Data set is uncataloged on volume ZDLVOL. **6** Data set is not cataloged on any volume and is uncataloged on volume ZDLVOL. **8** Data set is not available on volume ZDLVOL. This status is returned for data sets that have been either migrated or deleted.	(1)
ZDLCATNM	Name of the catalog in which the data set was located	44
ZDLCDATE	Creation date	10
ZDLCMD	Line command	9
ZDLCONF	Delete confirmation (Y | N)	1
ZDLDEV	Device type	8
ZDLDSN	Data set name	44
ZDLDSNTP	Data set name type	8

Table 9. TSO command/CLIST/REXX exec variables (output) (continued)

Variable Name	Description	Length in Characters
ZDLDSORG	Data set organization	4
ZDLEDATE	Expiration date	10
ZDLEXT	Number of extents used	3
ZDLEXTX	Number of extents used, long format	5
ZDLLCMD	Expanded line command	255
ZDLLRECL	Data set logical record length	5
ZDLMIGR	Whether the data set is migrated (YES or NO)	3
ZDLMVOL	Multivolume indicator	1
ZDLOVF	Space overflow indicator	3
ZDLRDATE	Date last referenced	10
ZDLRECFM	Data set record format	5
ZDLSIZE	Data set size in tracks	6
ZDLSIZEX	Data set size in tracks, long format	12
ZDLSPACU	Space units: either BLOCKS, TRACKS, CYLINDERS, BYTES, KILOBYTES, or MEGABYTES	10
ZDLUSED	Percentage of used tracks	3
ZDLVOL	Volume	6
ZDLXSTAT	Exclude status	1

When you select the Display Total Tracks option, and the data set list is displayed either in SPACE view or in TOTAL view, ISPF also puts the variables described in Table 10 in the shared pool for the TSO command, CLIST, or REXX exec to use.

Table 10. TSO command/CLIST/REXX exec additional variables (output)

Variable Name	Description	Length in Characters
ZDLSIZET	Total tracks of all data sets in the list	19
ZDLSIZTX	Total tracks of all data sets in the list, not including the tracks of excluded data sets	19
ZDLDST	Total number of data sets in the list (available for all display views)	6
ZDLDSX	Total number of data sets in the list, not including the excluded data sets	6

Note: ISPF cannot calculate reliable space utilization values for ISAM, VSAM, and BDAM data sets. Therefore, question marks (?) are returned in variables that report space utilization for these data sets.

A TSO command, CLIST, or REXX exec can set these variables and place them in the shared pool to communicate with the Data Set List utility (option 3.4).

Table 11. TSO command/CLIST/REXX exec variables (input)

Variable Name	Description	Length in Characters
ZDLNDSN	New data set name to appear in list	44
ZDLMSG	Message to appear in list	16
ZDLREF	Refresh data set information; Y | N	1

P — print data set list

Use option P to print a data set list. You must:

1. Enter one of these:
   - One or more data set name level qualifiers in the Dsname Level field and a volume serial in the Volume field. The list will contain all data sets for the specified levels and volume. Only the specified volume is searched. See "Dsname level" on page 140 and "Volume serial" on page 142 for more information.
   - One or more data set name level qualifiers in the Dsname Level field, but leave the Volume field blank. The list will contain all data sets for the specified levels that are cataloged.
   - A volume serial in the Volume field, but leave the Dsname Level field blank. The list will contain only the data sets on the specified volume. Only the specified volume is searched.

   Note: All data set lists are formatted the same when they are printed. Therefore, values entered in the Initial View field have no effect when you use option P.
2. Press Enter to print the data set list. The data set list is stored in the ISPF list data set.

V — display VTOC information

Option V is used to display VTOC (volume table of contents) information. To use option V:

1. In the Volume field, specify the volume serial for which you want ISPF to display information.

   Note: VTOC information is formatted the same, whether displayed or printed. Therefore, values entered in the Initial Display View field have no effect when you use option V.
2. Press Enter to display the VTOC information.

   Note: The Dsname Level field is not applicable for the V or PV command. Only the Volume field is relevant.

Figure 103 on page 159 shows an example of a VTOC display.

```
  Menu  RefList  RefMode  Utilities  Help
 ------------------------- VTOC Summary Information -------------------------
 Volume . : MVS8WF

 Unit . . : 3390

  Volume Data             VTOC Data              Free Space  Tracks   Cyls
  Tracks . :   50,085     Tracks  . :      59    Size  . . :   1,146       1
  %Used  . :       97     %Used . . :      60    Largest . :      22       0
  Trks/Cyls:       15     Free DSCBS:   1,187
                                                 Free Extents . :     323

 Command ===> _____________________________________________________________
  F1=Help    F2=Split   F3=Exit    F9=Swap   F12=Cancel
```

```
      3. Attrib                 /  Include Additional Qualifiers
      4. Total                  /  Display Catalog Name
                                /  Display Total Tracks
When the data set list is displayed, enter either:
  "/" on the data set list command field for the command prompt pop-up,
  an ISPF line command, the name of a TSO command, CLIST, or REXX exec, or
     "=" to execute the previous command.
Option ===> V
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 103. VTOC summary information panel (ISRUDSLV)

Track values do not include the remaining alternate tracks for the volume. The free space track values are the number of tracks for the free cylinders plus any additional free tracks.

The fields shown on the VTOC Summary Information panel are:

Unit Shows the type of DASD device the volume is on, such as 3380 or 3390.

Volume Data Describes general information about the volume:

- **Tracks** Total tracks on the volume.
- **%Used** Percentage of total tracks or pages not available for allocation.
- **Trks/Cyls** Number of tracks per cylinder for this volume.

VTOC Data Describes general information about the VTOC on the volume:

- **Tracks** Total tracks allocated to the VTOC.
- **%Used** Percentage of allocated tracks or pages used by data set control blocks (DSCBs).
- **Free DSCBS** Number of unused DSCBs.

Free Space Describes the free space available for data set allocation on the volume under the headings Tracks and Cyls, showing:

- **Size** Total number of free tracks and cylinders.
- **Largest** The largest number of contiguous free tracks and cylinders.

Free Extents The number of free areas with free cylinders.

PV — print VTOC information

Option PV is used to print VTOC information. To use option PV:

1. Blank out the Dsname Level field.
2. In the Volume field, specify the volume serial for which you want ISPF to print information.

   Note: VTOC information is formatted the same, whether displayed or printed. Therefore, values entered in the Initial View field have no effect when using option PV.
3. Press Enter to print the VTOC information. The VTOC information is stored in the ISPF list data set.

   Note: The Dsname Level field is not applicable for the PV or V command. Only the Volume field is relevant.

Data set list utility line commands

After you display a data set list by leaving the Option field blank, you can enter a line command to the left of the data set name. You can also enter TSO commands, CLIST names, or REXX exec names. If a '>' is used before the CLIST or REXX exec name, the parameters passed to the command are not translated to upper case. The z/OS UNIX commands OGET and OPUT can be entered and the parameters are also not translated to upper case.

The slash (/) character, which can be used with TSO commands, CLISTs, and REXX EXECs, can also be used with the V (view data set), B (browse data set), D (delete data set), E (edit data set), and M (display member list) line commands to specify a member name or a pattern. You can type over the field containing the data set name to enter commands that require more than the space provided. For more information about using this symbol, see "Using the slash (/) character" on page 154. For more information about member name patterns, see the details about Displaying Member Lists in the "ISPF Libraries and Data Sets chapter" in the *z/OS ISPF User's Guide Vol I*.

Line commands that are valid for aliases may be used with any alias data sets that are listed. Uncatalog, delete, and rename commands are not valid for alias data sets. A line command such as 'B' for browse or 'I' for information will display the real name of the data set.

The Data Set List Utility always supports the U (uncatalog) line command for tape data sets. The Data Set List Utility can support additional line commands for data sets stored on tape and other removable media, by calling external commands such as DFSMSrmm. This interface is configured in the ISPF configuration table and enabled by setting the configuration table keyword DSLIST_RM_ENABLED to YES.

Depending on the removable media interface, these line commands may be supported:

I Information
S Short Information
D Delete
R Rename
C Catalog
M Member List
P Print
X Print Index
CO Copy

MO Move

Which line commands are actually supported by a particular interface depends on the capabilities of the external command.

For more information about configuring the Data Set List Utility removable media interface, see *z/OS ISPF Planning and Customizing*.

If a CLIST, REXX exec, or program is issued against a data set, ISPF gathers information on the data set and makes it available through dialog variables. See Table 9 on page 156 for the list of those variables. If the data set being processed is on an unmounted file system, a temporary mount is issued, file system.

The Command field and the field containing the data set name fields make up a single point-and-shoot field. If you enter a slash in the Command field or if you select any part of the combined point-and-shoot field, the Data Set List Actions pop-up shown in Figure 104 is displayed so that you can select the command you want to use.

```
  Menu  Options  View  Utilities  Compilers  Help
_ ┌──────────────────────────────────────────────────────────┐ ──────────
D │                    Data Set List Actions                 │ ow 1 of 12
  │                                                   More:  │
C │ Data Set: MYPROJ.DEV.SOURCE                              │     Volume
- │                                                          │ -----------
  │ DSLIST Action                                            │     *ALIAS
  │    __  1.  Edit                    14. Print Index       │     MVS8WF
  │        2.  View                    15. Reset             │     MVS8WJ
/ │        3.  Browse                  16. Move              │     MVS8WF
  │        4.  Member List             17. Copy              │     MVS8WH+
  │        5.  Delete                  18. Refadd            │     MVS8WP
  │        6.  Rename                  19. Exclude           │     MVS8WG
  │        7.  Info                    20. Unexclude 'NX'    │     MVS8WI
  │        8.  Short Info              21. Unexclude first 'NXF'     MVS8WG
  │        9.  Print                   22. Unexclude last 'NXL'      MVS8WD
  │        10. Catalog                 23. SuperC 'SC'       │     MVS8WK
  │        11. Uncatalog               24. SuperCE 'SCE'     │     MV8W07
*│        12. Compress                25. Search-For 'SF'   │ ***********
  │        13. Free                    26. Search-ForE 'SFE' │
  │  F1=Help       F2=Split       F3=Exit       F7=Backward  │
C │  F8=Forward    F9=Swap       F12=Cancel                  │  ===> PAGE
  └──────────────────────────────────────────────────────────┘ 9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 104. Data set list commands pop-up (ISRUDABC)

E — edit data set

For the E command, the processing is similar to selecting the Edit option (2) and entering the library or data set name on the Edit Entry Panel, except that mixed mode is the assumed operation mode.

Note: Multivolume data sets do not support the Volume Serial field for the Edit command.

If you select a library or other partitioned data set, an Edit member list is displayed. For more information about using member selection lists, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

The E line command uses the values from a prompt panel to specify items including the initial macro, profile name, panel name, format, mixed mode, and workstation editing. These values are stored in the profile and are used on subsequent edits.

To change these values, use the "DSLIST settings" panel on the data set list Options pull-down. Check both the "E,V,B enhanced member list" and the "Display Edit/View entry panel" options. The prompt panel is always shown when you edit a sequential file, or when you directly edit a member of a partitioned data set. When you are using a member list you can force the display of the panel by placing a slash mark (/) in the Prompt field next to the member you select.

If the editor appears to be invoking an unexpected initial macro, or it appears to be using an unexpected profile, follow the process described to check the values on the prompt panel.

V — view data set

For the V command, the processing is similar to selecting the View option (1) and entering the library or data set name on the View Entry Panel. If you have set your DSLIST options to not show the edit/view entry panel:

- Mixed mode is the assumed operation mode.
- You cannot specify a data set format, an edit profile, or an initial macro.

Note: Multivolume data sets do not support the Volume Serial field for the View command.

If you select a library or other partitioned data set, an Edit member list is displayed. For more information about using member selection lists, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

B — browse data set

For the B command, processing is the same as if you specify Browse Mode from View (option 1), except that mixed mode is the assumed operation mode and you cannot specify a data set format. To browse a data set with mixed mode off, you must use the View option; deselect Mixed Mode and select Browse Mode on the View Entry Panel. If you enter the B line command beside an ISPF library or other partitioned data set, a Browse member list is displayed. For more information about using member selection lists, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

Note: From a catalog list, multivolume data sets do not support the Volume Serial field for the Browse command.

M — display member list

For the M command, a member selection list of a partitioned data set is displayed. This member list provides an expanded line command field in the area to the left of the list. The line command field in other member lists has room for only one character, unless the browse, view, or edit *enhanced* member list is selected.

From the member list, you can use the same primary commands and line commands that are valid for Library utility (option 3.1) member selection lists. See the information about Using Member Selection Lists and Library and Data Set List Utility Line Commands in the Libraries and Data Sets topic in the *z/OS ISPF User's Guide Vol I*.

Notes:

1. From a VTOC list, you can browse a single volume of a multivolume non-SMS data set.
2. You can *chain* the line commands; that is, you can select multiple members from a member list for various processing tasks. Use the CANCEL command (from a View, Browse, or Edit session) to break the chain and return to the member list.

You can also enter TSO commands, CLISTs, or REXX EXECs in the Line Command field. If you enter a line command other than B (browse), D (delete), E (edit), R (rename), C (copy), M (move), G (reset), J (submit), or P (print), ISPF interprets it as a TSO command, CLIST, or REXX exec.

The command is selected with the quoted, fully qualified data set name and member added to it, such as:

```
COMMAND 'DSN(MEMBER)'
```

See “TSO commands, CLISTs, and REXX EXECs” on page 154 for more information.

Note: If the TSO command, CLIST, or REXX exec issues a return code greater than or equal to 8, processing stops and an error message is displayed.

Figure 105 shows an example of a member list with statistics and an expanded line command field.

```
  Menu  Functions  Confirm  Utilities  Help
 ------------------------------------------------------------------------------
 DSLIST            MYPROJ.DEV.SOURCE                        Row 00001 of 00001
 Command ===> ____________________________________________  Scroll ===> PAGE
            Name     Prompt       Size   Created          Changed          ID
 _________ FL@SPCGB                 21  2003/12/10  2003/12/10 02:58:01  LSACKV
 _________ FL@SPCIM                 21  2003/12/15  2003/12/15 09:37:51  LSACKV
 _________ FL@SPCLO                 21  2003/12/05  2003/12/05 22:52:24  LSACKV
 _________ FL@SPCMI                 21  2003/12/10  2003/12/10 06:22:13  LSACKV
 _________ FL@SPCNG                 21  2003/12/01  2003/12/02 23:09:25  LSACKV
 _________ FL@SPCPR                 21  2003/12/12  2003/12/12 01:46:48  LSACKV
 _________ FL@SPCRA                 21  2003/12/12  2003/12/12 04:03:30  LSACKV
 _________ FL@SPCSC                 23  2004/04/21  2005/12/23 11:54:27  BBAGG
 :
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 105. Member list display - expanded line command field (ISRUDSM)

Figure 106 on page 164 shows load module library statistics with an expanded line command field.

```
  Menu  Functions  Confirm  Utilities  Help
 ------------------------------------------------------------------------
 DSLIST            PDFTDEV.SVT.LOAD                        Row 00001 of 00505
 Command ===> ___________________________________________  Scroll ===> PAGE
            Name     Prompt        Alias-of     Size      TTR     AC   AM   RM
 _________ FLM$CP                  FLMIO24    0000A3E8   089B0F   00    24   24
 _________ FLM$CPI                            000000E8   00F80A   00    31  ANY
 _________ FLM$DE                  FLMIO24    0000A3E8   089B0F   00    24   24
 _________ FLM$DT                  FLMIO24    0000A3E8   089B0F   00    24   24
 _________ FLM$99                  FLMIO24    0000A3E8   089B0F   00    24   24
 _________ FLMA                               00008278   076E0D   00    31  ANY
 _________ FLMB                               000AA8B8   084A10   00    31  ANY
 _________ FLMBCMD                 FLMDDL     00140A68   087906   00    31  ANY

⋮
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 106. Load module library display - expanded line command field (ISRUDSM)

D — delete data set

For the D command, the processing is the same as if you had selected option D from the Data Set utility (option 3.2) without specifying a volume serial. This command deletes and uncatalogs the entire data set. If a member name or pattern is supplied then a member delete will occur.

Note: Delete is not allowed for multivolume data sets from a VTOC list.

If you select the Confirm Delete option on the Data Set List Utility panel, the Confirm Delete panel (Figure 85 on page 124) is displayed to allow you to continue or cancel the operation. Note that Confirm Delete is forced on when deleting members by pattern. If you are trying to delete an unexpired data set, the Confirm Purge panel (Figure 86 on page 125) is also displayed.

When you delete a data set the volume name is compared to the volume name in the configuration table. If the names match, the command specified in the configuration table is used in place of the ISPF delete processing. This allows you to delete migrated data sets without first causing them to be recalled.

R — rename data set

For the R command, the processing is the same as if you had selected option R from the Data Set utility (option 3.2). The Rename Data Set panel is displayed to allow you to specify the new name.

Note: Rename is not allowed for multivolume data sets from a VTOC list.

See “R — rename entire data set” on page 122 for more information.

I — data set information

For the I command, the processing is the same as if you had selected option I from the Library utility (option 3.1) or left the Option field blank with the Data Set utility (option 3.2). See “I — data set information” on page 104 and “Information for managed data sets” on page 107 for more information.

Notes:

1. For multivolume data sets, options I and S display current allocation and utilization values that represent totals from all volumes used.

2. Space utilization values are not displayed for ISAM, VSAM, or BDAM data sets.

S — information (short)

For the S command, the processing is the same as if you had selected option S from the Library utility (option 3.1) or the Data Set utility (option 3.2). See "S — short data set information" on page 108 and "Short information for managed data sets" on page 109 for more information.

Notes:

1. For multivolume data sets, options I and S display current allocation and utilization values that represent totals from all volumes used.
2. Space utilization values are not displayed for ISAM, VSAM, or BDAM data sets.

P — print data set

For the P command, the processing is the same as if you had selected option L from the Library utility (option 3.1). This command formats the contents of a source data set for printing and records the output in the ISPF list data set. It also produces an index listing, which appears at the beginning of the output.

Note: The Print command is not allowed for multivolume data sets from a VTOC list.

C — catalog data set

For the C command, the processing is the same as if you had selected option C from the Data Set utility (option 3.2). See "C — catalog data set" on page 121 for more information.

Note: Multivolume data sets are always cataloged.

U — uncatalog data set

For the U command, the processing is the same as if you had selected option U from the Data Set utility (option 3.2). See "U — uncatalog data set" on page 123 for more information.

Note: The U command is not supported for multivolume data sets.

Z — compress data set

For the Z command, the processing is the same as if you had selected option C from the Library utility (option 3.1). This command recovers wasted space that was formerly occupied by deleted or updated members and is now available for use again. You do not need to compress a PDSE. If you use the Z command on a PDSE, the data is not reorganized.

The Z command calls either the IEBCOPY utility or the compress request exit routine. See *z/OS ISPF Planning and Customizing* for more information.

F — free unused space

For the F command, space that is not being used by the data set is released. For example, if a data set is allocated with 100 tracks but is only using 60 tracks, the F command releases the 40 tracks that are not being used.

Note: The F command is not supported for multivolume data sets.

However, if the data set has been allocated with CYLS (cylinders) specified as the space units, only the tracks beyond the last cylinder used are freed. For example, if a data set occupies 1.2 of 3 allocated cylinders, the F command frees all tracks beyond the last used cylinder, leaving 2 cylinders allocated.

PX — print index listing

For the PX command, the processing is the same as if you had selected option X from the Library utility (option 3.1). The index listing is recorded in the ISPF list data set. See "X — print index listing" on page 104 for more information.

Note: The Print command is not allowed for multivolume data sets from a VTOC list.

RS — reset

For the RESET command, a panel is displayed that prompts you to reset or delete ISPF statistics, and to enter a new user ID, version number, or modification level.

MO — move

For the MOVE command, a panel is displayed that prompts you for a library or data set name for the *to* data set.

Note: How aliases are handled by the MO and CO line commands depends on how the Process member aliases option is set. For more information see "Moving or copying alias entries" on page 138.

CO — copy

For the COPY command, a panel is displayed that prompts you for a library or data set name for the *to* data set.

Note: How aliases are handled by the MO and CO line commands depends on how the Process member aliases option is set. For more information see "Moving or copying alias entries" on page 138.

RA — RefAdd

For the REFADD command, you are provided with an interface to referral lists, where you can add a data set and a volume to a Personal Data Set List.

X — exclude data set

For the EXCLUDE command, one data set from a data set list is excluded from the list.

NX — unexclude data set

For the Unexclude command, one data set, or a set of data sets that have been excluded from a data set list are re-shown.

NXF — unexclude first data set

For the UNEXCLUDE FIRST command, the first of a set of excluded data sets is re-shown.

NXL — unexclude last data set

For the UNEXCLUDE LAST command, the last of a set of excluded data sets is re-shown.

SC — SuperC

The SC command invokes the SuperC Compare Utility with the data set predefined in the "New" Data Set field. These keyword parameters can be entered after the SC command:

NDSN(*new dataset*)
NVOL(*volume for NDSN*)
ODSN(*old dataset*)
OVOL(*volume for ODSN*)
M(*member mask*)
PROMPT

By default no prompting for SuperC information happens.

See "SuperC utility (option 3.12)" on page 203 for more information.

SCE — SuperCE

The SCE command invokes the SuperCE Compare Utility with the data set predefined in the New DS Name field. These keyword parameters can be entered after the SCE command:

NDSN(*new dataset*)
NVOL(*volume for NDSN*)
ODSN(*old dataset*)
OVOL(*volume for ODSN*)
M(*member mask*)
PROMPT

By default no prompting for SuperC information happens.

See "SuperCE utility (option 3.13)" on page 213 for more information.

SF — Search-For

The SF line command invokes the Search-For Utility on the selected data set.

If the selected data set is a PDS or PDSE then the SRCHFOR Member List function is invoked. You can provide a single search string with the SF line command. (Example: `SF string1`). If no search string is provided the Srchfor Options popup window is displayed. Use this panel to enter multiple search strings, process options, and output options. You can use the process options "Set EDIT FIND string" and "Set BROWSE FIND string" to initialize the FIND string in Edit and Browse from the first SRCHFOR string. Use the output option "Filter list" to list only the subset of members that contain one of the search strings.

An option E, V, or B can be entered immediately after the SF command. This will set the default action (Edit, View, or Browse) for when the S line command is used to select a member in the enhanced member list. (Example: `SF B` sets the default action in the member list to Browse.)

See "Search-For utility (option 3.14)" on page 225 for more information.

SFE — Search-ForE

The SFE line command invokes the Extended Search-For Utility on the selected data set.

If the selected data set is a PDS or PDSE then the SRCHFOR Member List function is invoked. You can provide a single search string with the SFE line command. (Example: `SFE string1`). If no search string is provided the Srchfor Options popup window is displayed. Use this panel to enter multiple search strings, process options, and output options. You can use the process options "Set EDIT FIND string" and "Set BROWSE FIND string" to initialize the FIND string in Edit and Browse from the first SRCHFOR string. Use the output option "Filter list" to list only the subset of members that contain one of the search strings.

An option E, V, or B can be entered immediately after the SFE command. This will set the default action (Edit, View, or Browse) for when the S line command is used to select a member in the enhanced member list. (Example: `SFE B` sets the default action in the member list to Browse.)

See "Search-ForE utility (option 3.15)" on page 231 for more information.

= — repeat last command

For the = command, the most recently used line command is repeated. This command is most helpful when the same TSO command, CLIST, or REXX EXEC is to be called for more than one data set in a data set list. For example, suppose you have a CLIST named TESTABC and two data sets named USER.DATA1 and USER.DATA2. To run the CLIST with the two data sets consecutively from a data set list, you could:

1. Type `TESTABC` in the Command field beside USER.DATA1.
2. Type = in the Command field beside USER.DATA2.
3. Press Enter.

This procedure saves keystrokes because you type the CLIST name only once and you press Enter only once.

Data set list utility primary commands

Primary commands are available when you use the Data Set List utility. These commands, which you enter on the command line, are:

- APPEND
- CONFIRM
- EXCLUDE
- FIND and RFIND
- LC
- LOCATE
- MEMBER
- REFRESH
- RESET
- SAVE
- SHOWCMD
- SORT
- SRCHFOR
- VA, VS, VT, and VV

These topics describe these commands:

- "APPEND command" on page 169
- "CONFIRM command" on page 169
- "EXCLUDE command" on page 169
- "FIND and RFIND commands" on page 170
- "LC command" on page 170
- "LOCATE command" on page 171
- "MEMBER command" on page 171
- "REFRESH command" on page 172
- "RESET command" on page 172
- "SAVE command" on page 172
- "SHOWCMD command" on page 173
- "SORT command" on page 174
- "SRCHFOR command" on page 175
- "VA, VS, VT, and VV commands" on page 176

APPEND command

The APPEND primary command appends additional data sets to an existing displayed DSLIST. Use this format:

```
APPEND  [list name | DSname level]
```

You can use the APPEND command with no parameters to get a list of your personal data sets. Then select the one you want to append to the current list.

If you give a *list name* with the command, the list given is appended.

By specifying *DSname level* as a parameter, you can use the resulting list to select which list to append to the current one. For example, entering `APPEND Userid.C*` gives you a list of all personal lists that begin with C as the second-level identifier. Then you can select the one to append.

By specifying *DSname level* in quotes, data sets beginning with the DSname level are appended to the data set list.

The APPEND primary command accepts system symbols. For example:

```
APPEND 'SYS2.**.&SYSPLEX'
```

CONFIRM command

The CONFIRM primary command controls display of the Confirm Delete panel. Use this format:

```
CONFIRM  [ON | OFF]
```

You can use these operands with the CONFIRM command:

ON Tells ISPF to display the Confirm Delete panel when you enter the D (delete data set) line command or TSO DELETE command. This is the default setting.

OFF Tells ISPF not to display the Confirm Delete panel.

For example, this command would tell ISPF not to display the Confirm Delete panel:

```
CONFIRM OFF
```

EXCLUDE command

The EXCLUDE primary command excludes data sets from a list based on a character string. Use this format:

```
EXCLUDE [character string]
            [ALL  ] [PREFIX]
            [NEXT]  [CHARS]
            [FIRST] [SUFFIX]
            [LAST ] [WORD  ]
            [PREV ]
```

You can use these operands with the EXCLUDE command:

character string
Tells ISPF which data set to exclude from the list.

ALL Tells ISPF to exclude every data set in the list.

NEXT | FIRST | LAST | PREV
Operands that define the starting point, direction, and extent of the lines to exclude.

PREFIX | CHARS | SUFFIX | WORD
Operands that set the conditions for a character string match.

For example, this command tells ISPF to exclude a data set that includes BILBO3 in the name from a list:

```
EXCLUDE BILBO3
```

FIND and RFIND commands

The FIND primary command finds and displays a character string within the data set name. Use this format:

```
FIND string [NEXT]  [CHARS]
            [ALL  ] [PREFIX] [X]
            [FIRST] [SUFFIX] [NX]
            [LAST ] [WORD  ]
            [PREV ]
```

For example, this command would tell ISPF to find all occurrences of the character string ELSE:

```
FIND ELSE ALL
```

The operands X and NX can be used to limit your search to excluded (X) or unexcluded (NX) data sets.

For more information about the operands used with this command, see "FIND—find character strings" on page 85. NEXT and CHARS are the default operands.

ISPF automatically scrolls to bring the character string to the top of the list. To repeat the search without reentering the character string, use the RFIND command.

Note: RFIND search starts from the second data set in the list. It is not cursor-sensitive.

LC command

The LC primary command invokes the color change utility from the command line of a data set list display, as shown in Figure 107 on page 171.

```
                    Data Set List Color Change Utility

  Change one or more of the Data Set List Field Attributes and press Enter
  to immediately see the effect.  Clearing a field restores defaults.
                                                                  More:     +
  Field:             Color:       Intens:      Hilite:        Defaults:
  Volume . . . . . . BLUE   . . . LOW    . . . NONE          Blue
* Data Set Name  . . GREEN  . . . LOW    . . . NONE          Green
  Data Set Stats . . TURQ   . . . LOW    . . . NONE          Turquoise
  Create,Expire,
  Catalog  . . . . . YELLOW . . . LOW    . . . NONE          Yellow
  Message  . . . . . WHITE  . . . LOW    . . . NONE          White
  Tracks,Device  . . WHITE  . . . LOW    . . . NONE          White
  Marked Data Set  . YELLOW . . . HIGH   . . . NONE          Yellow
* _ Use Point-and-Shoot field attributes on Data Set Name field
-------------------------------- Example -----------------------------------
Command - Enter '/' to select action                     Message      Volume
 Tracks %  XT Device  Dsorg Recfm Lrecl Blksz    Created   Expires  Referred
         Catalog
-----------------------------------------------------------------------------
         ISR.V5R5M0.ISRLOAD                              Browsed      HSM001
Command ===> ___________________________________________________      Defaults
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 107. Data Set List Color Change Utility panel (ISRDLCP)

LOCATE command

The LOCATE primary command scrolls the list of data sets based on the field on which the data set list is sorted, as described under “SORT command” on page 174. Use this format:

```
LOCATE lparm
```

You can use the *lparm* operand with the LOCATE command for either of these situations:

- If the list is sorted by data set name, specify a data set name.
- If the list is sorted by another field, specify a value for the field by which the list is sorted.

For example, for a data set list sorted by volume, you could enter:

```
LOCATE TSOPK1
```

This command locates the first data set in the list on volume TSOPK1. If the value is not found, the list is displayed starting with the entry before which the specified value would have occurred.

MEMBER command

The MEMBER primary command is used to search for a member name or pattern in all of the partitioned data sets in the data set list. It can be abbreviated as M or MEM. The parameters, **X**, **EX**, **NX**, **RECALL1**, and **RECALL2** are optional. X and EX limit the search to excluded data sets. NX limits the search to non-excluded data sets. RECALL1 includes data sets migrated to DASD in the search. RECALL2 includes all migrated data sets in the search. Use this format:

```
MEMBER string [ X
              [ EX ]
              [ NX ]
              [ RECALL1 ]
              [ RECALL2 ]
```

The data set list is scrolled so that the first data set containing the member or pattern is at the top of the list. The MEMBER command finds any occurrence of the specified member name or pattern within a partitioned data set.

REFRESH command

The REFRESH primary command updates the display of the data set list to whatever the list's current state is. For example, after deleting several items on the list, REFRESH causes the list to be displayed without the deleted items. If you have appended to the list, REFRESH restores the list to its status before the append operation.

RESET command

The RESET primary command unexcludes data sets that were excluded from a list, and removes any pending line commands and messages from the data set list.

SAVE command

The SAVE primary command writes the data set list to the ISPF list data set or to a sequential data set. ISPF writes the data set list in its current sort order. If the Display Catalog Name option is selected and Volume Serial was not entered, the catalog name associated with each data set is included in the Data Set List written to the sequential file. Use this format:

```
SAVE [list-id]
```

where *list-id* is an optional user-specified qualifier of the data set to which the member list will be written. ISPF names the data set:

```
prefix.userid.list-id.DATASETS
```

where:

prefix Your data set prefix, as specified in your TSO user profile. If you have no prefix set, or if your prefix is the same as your user ID, the prefix is omitted and the data set name will be: *userid.list-id.*DATASETS.

userid Your TSO user ID.

The data set is created if it does not exist, or written over if it exists, and has compatible attributes. If you omit the *list-id* operand, the list is written to the ISPF list data set and includes the list headings. If you enter SAVE without a *list-id* and the Display Total Tracks option is selected, an additional header line with the accumulated tracks of all datasets and the number of all data sets in the list is written above the column headings.

This command would tell ISPF to write the list to a sequential data set named either *prefix.userid*.MY.DATASETS or *userid*.MY.DATASETS.

```
SAVE MY
```

If the sequential data set already exists, ISPF writes over it; if not, ISPF creates it.

ISPF displays a progress status pop-up panel when the necessary information to perform a SAVE or SORT primary command has to be retrieved and the data set

list comprises 50 or more data sets. The keyboard locks when this pop-up panel appears and stays locked until the SAVE or SORT command is completed.

SHOWCMD command

The SHOWCMD primary command controls the display of line commands and their operands as they are called. Use this format:

```
SHOWCMD  [ON | OFF]
```

where:

ON Tells ISPF to display line commands. This is the default setting.

OFF Tells ISPF not to display line commands. Though the SHOWCMD default is ON, SHOWCMD is initially set to OFF.

After you enter SHOWCMD ON, a panel (Figure 108 on page 174) is displayed each time you enter a line command, TSO command, CLIST, or REXX exec on a data set list display.

On this panel, you see the command as you typed it and then, a few lines down, you see the command as ISPF interpreted it. Seeing these commands displayed can be especially useful when you use the slash (/) character to substitute for the data set name because the panel shows the line command after expansion occurs. Therefore, you can tell immediately whether you need to add operands to the command.

For example, suppose you have a data set list displayed on the screen and decide to browse member MEMB1 of data set USER.TEST.DATA. To see how ISPF interprets the B (browse) line command, type SHOWCMD ON on the Command line and press Enter. Then, enter this line command in the Line Command field to the left of USER.TEST.DATA:

```
B /(MEMB1)
```

When you press Enter, the panel shown in Figure 108 on page 174 is displayed.

```
                              Data Set List Utility

Data Set Name. : MYPROJ.DEV.SOURCE

Command before expansion:
      B /(TEST)

Command after expansion:
===> B 'MYPROJ.DEV.SOURCE(TEST)'
The expanded command field shown here can be modified,
but the data set name field may not be changed for built-in commands.

Press ENTER key to process the command.
Enter END command to return without processing the command.




Command ===>
 F1=Help    F2=Split   F3=Exit    F9=Swap   F12=Cancel
```

Figure 108. Data Set List Utility - SHOWCMD panel (ISRUDSLS)

Notes:

1. The data set name and commands shown in Figure 108 are for illustrative purposes only. These values are determined by the command you enter and the data set acted on by that command.
2. SHOWCMD must be entered from a data set list. It is invalid if you use a line command, such as M, to display a member list before calling it.

When the panel showing the commands is displayed, you can perform one of these actions:

- Press Enter to call the command displayed in the "Command after expansion" field.
- Change the command displayed in the "Command after expansion" field and then press Enter to call the changed command.
- Enter the END command to return to the data set list display.

For information about using line commands, TSO commands, CLISTs, REXX EXECs, and the / character on a data set list display, see "Blank — display data set list" on page 146.

SORT command

The SORT primary command sorts the data set list by the specified field. Use this format:

```
SORT [field1 [A|D] [field2 [A|D]] ]
```

where:

field1 The major sort field. If only one operand is used, ISPF treats it as *field1*. If both operands are used, ISPF sorts the list by *field1* first, then by *field2* within *field1*.

field2 The minor sort field.

A | D The direction in which values are sorted for this field (A=ascending, D=descending).

For example, to sort a data set list by volume and block size within each volume, use this command:

```
SORT VOLUME BLKSZ
```

If you do not specify a field, ISPF sorts the list by data set name. The keywords described in Table 12 tell ISPF by which fields to sort the data set list.

Table 12. Sort fields for source libraries

Field	Default Sequence	Description
NAME	Ascending	Data set name
MESSAGE	Ascending	Command completion message
VOLUME	Ascending	Volume serial
DEVICE	Ascending	Device type
DSORG	Ascending	Data set organization
RECFM	Ascending	Record format
LRECL	Descending	Logical record length
BLKSZ	Descending	Block size
TRACKS	Descending	Data set size
%USED	Descending	Percentage used
XT	Descending	Extents used
CREATED	Descending	Creation date
EXPIRES	Ascending	Expiration date
REFERRED	Descending	Last accessed data
MVOL	Ascending	Multivolume or migration level
CATALOG	Ascending	Catalog Name
PROMPT	Descending	Data displayed in PROMPT field

Automatic scrolling is performed, if necessary, to bring the major sort field into view. ISPF displays a progress status pop-up panel when the necessary information to perform a SAVE or SORT primary command has to be retrieved and the data set list comprises 50 or more data sets. The keyboard locks when this pop-up panel appears and stays locked until the SAVE or SORT command is completed.

SRCHFOR command

Use the SRCHFOR primary command to search the data sets in the data set list for one or more strings of data using the SuperC Utility (see Option 3.14). You may limit the search to excluded or non-excluded data sets, and control whether migrated data sets are recalled and searched or not. Use this format:

```
SRCHFOR string
```

The string parameter is optional. If specified it is used to prefill the first search string on the subsequent DSLIST Srchfor Options panel.

WORD, SUFFIX, and PREFIX are available operands for search string specification. Note that the search strings are case sensitive and must match exactly as specified. Consider the 'Any case' process option if you want to disregard case.

You can use the C (continuation) operand to specify that both the current and previous string must be found on the same line to constitute a match. Otherwise, lines with either string are treated as matching.

Table 13. SRCHFOR command search string examples

Example Search strings:	Explanation:
`===> ABC` `===> EFG`	Either string ABC or EFG may be found in the search data set.
`===> ABC WORD` `===> EFG C`	The two strings (ABC and EFG) must be found on the same line. ABC must be a complete word, while EFG (a continuation definition) can be part of any word.
`===> ABcD prefix`	The string (ABcD) is detected if the case of each letter matches and it is a prefix of a word.
`===> X'7b00'`	The hex string is specified as the search string. The listing must be browsed with 'HEX ON'.
`===> 'AB C''D'`	The string (AB C'D) is specified.

To start the search, press the Enter key from the DSLIST Srchfor Options panel. To cancel the request and return to the Data Set List, enter END or CANCEL.

Output is in the listing DSN you specify and in the MESSAGE field in the DSLIST. Sort on this field to consolidate results.

VA, VS, VT, and VV commands

The VA, VS, VT, and VV commands change the data set list display to the Attributes, Space, Total, and Volume views, respectively.

Reset ISPF statistics utility (option 3.5)

If you have set STATS mode on, the ISPF editor automatically generates statistics for each member of a partitioned data set. You might want to reset these statistics for these reasons:

- The program you are developing has been completed and you would like to reset all version numbers before starting on the next release.
- A person has left the project, and you wish to reassign some of the members to the user ID of the person who is taking over the work.
- You would like to create ISPF statistics for some members that were created or modified on a system other than ISPF.
- You want to delete existing statistics from a partitioned data set to save space in the directory.

This option allows you to create, update, or delete statistics and to reset sequence numbers.

The Reset ISPF Statistics utility handles only partitioned data sets whose record length is in this range:

- From 1 to 32 760, inclusive, for fixed-length records
- From 5 to 32 756, inclusive, for variable-length records.

For more information about ISPF Member Statistics, see the "ISPF Libraries and Data Sets chapter" in the *z/OS ISPF User's Guide Vol I*.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                            Reset ISPF Statistics
                                                                   More:     +
 R Reset (create/update) ISPF statistics   D Delete ISPF statistics

 New Userid  . . . . . . ________ (If userid is to be changed)
 New Version Number  . . __       (If version number is to be changed)

 SCLM Setting                                Enter "/" to select option
 3  1. SCLM   2. Non-SCLM   3. As is         /  Reset Mod Level
                                             /  Reset Sequence Numbers
 ISPF Library:                               /  Reset Date/Time
    Project . . . MYPROJ                     /  Reset Number of Lines
    Group . . . . DEV
    Type  . . . . SOURCE3
    Member  . . . ________        (Blank or pattern for member selection
                                   list, "*" for all members)
 Other Partitioned Data Set:
    Data Set Name . . .  ____________________________________________________
 Option ===> ____________________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 109. Reset ISPF Statistics panel (ISRURSP)

Reset ISPF statistics panel action bar

The Reset ISPF Statistics panel action bar choices function as follows:

Menu
For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

RefList
For information about referral lists, see the topic about Using Personal Data Set Lists and Library Lists in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help
The Help pull-down offers these choices:

1 General
2 Why you might want to Reset ISPF statistics
3 Filling in the reset utility panel
4 Using the Member list
6 ISPF statistics
7 Appendices
8 Index

Reset ISPF statistics panel fields

All the fields on this panel are described in the Libraries and Data Sets topic in the *z/OS ISPF User's Guide Vol I*, except these fields:

New Userid
This field is used to set the ID field in the statistics. Enter a new user ID here if you want to change the user ID the statistics are recorded under. It is required if you do not specify a new version number.

If you are updating the user ID but not resetting the sequence numbers, the statistics are updated but the data is not scanned or renumbered.

New Version Number
Enter a number here if you want to change the version number. This field is required if you do not specify a new user ID when resetting statistics. It is ignored if you are deleting statistics.

Reset Mod Level
Use a slash to select this option and reset the modification level. Deselect this option if you do not want to reset the modification level. A new version number is required to reset the modification level.

Reset Sequence Numbers
Use a slash to select this option and reset the sequence numbers. Deselect this option if you do not want to reset the sequence numbers. A new version number is required to reset the sequence numbers. Only standard (STD) sequence numbers will be reset.

If the data is in packed format, there can be no sequence number processing. However, statistics for members in packed format can be created or updated if the sequence numbers are not being reset.

SCLM Settings
The SCLM setting is a bit that ISPF uses to determine what type of edit the file last had performed upon it.

1 SCLM This bit is ON to specify that the last edit of this file was under SCLM control.

2 Non-SCLM This bit is ON to specify that the last edit of this file was under control of something other than SCLM.

3 As-is This bit is ON to specify that this copy operation transfers the current setting of this file as it already is.

Reset Date/Time
The setting of this field determines whether to reset the Last Modified Date or Time and the Creation Date of the file.

Reset Number of Lines
The setting of this field determines whether to reset the Current Number of Lines, the Initial Number of Lines, and the Number of Modified Lines settings. If this field is set ON, the Current Number of Lines and Initial Number of Lines settings are set to the actual number of lines of the member.

The Number of Modified Lines setting is dependent on the Reset Mod Level and Reset Sequence Numbers fields. If either of those are reset and the Reset Date/Time field is ON, then the value of the Number of Modified Lines is set to zero. Otherwise, the Number of Modified Lines remains as is.

Reset ISPF statistics utility options

These topics describe the options shown on the Reset ISPF Statistics panel:

- "R — reset (create/update) ISPF statistics" on page 179
- "D — delete ISPF statistics" on page 179
- "Results of resetting statistics" on page 179

R — reset (create/update) ISPF statistics

Use option R either to create statistics in a library that does not currently have them, or to update statistics in a library.

The New Userid field is optional for option R. If you specify a user ID, it is placed in the ID field of the statistics. If you leave the New Userid field blank and select a member without statistics, the ID field of the statistics is set to the current user ID.

Either a new user ID or a new version number is required when you use this option. When you specify a version number, the statistics are created or reset as follows:

Version Number Set to the specified value.

Modification Level Set to zero if requested; otherwise, unchanged.

Creation Date Set to current date in the national format.

Change Date Set to current date, in the national format, and time.

Current No. Lines Set to the current number of data records.

Initial No. Lines Set to the current number of data records.

No. Modified Lines Set to zero if the Reset Sequence Numbers field is selected.

If you have requested updating of the modification level and resetting of the sequence numbers, the last two digits of each sequence number are set to zeros. Otherwise, they are not changed.

If you have requested updating of sequence numbers, the data is scanned to determine if valid, ascending sequence numbers are present in all records. If so, the data is renumbered. Otherwise, the data is assumed to be unnumbered and renumbering is not done.

D — delete ISPF statistics

Use option D to delete ISPF statistics for an ISPF library or other partitioned data set. The New Userid and New Version Number fields are ignored when you use option D.

Results of resetting statistics

What you specify for the New Version Number, Reset Mod Level, and Reset Sequence Numbers fields controls the resetting of the sequence numbers, the modification flags within the data, and the statistics. A new version number is required to reset the modification level and sequence numbers. Therefore, if a new version number is entered and the data is not in packed format, Table 14 shows the various combinations you can use for the Reset Mod Level and Reset Sequence Numbers fields and the results of those combinations.

Table 14. Reset mod level and reset sequence numbers combinations

	Reset Mod Level *Selected*	Reset Mod Level *Deselected*
Reset Sequence Numbers *Selected*	**RESET**	**MOD FLAGS=UNCHANGED SEQ #'s=RESET**
Reset Sequence Numbers *Deselected*	**Unchanged**	**Unchanged**

Hardcopy utility (option 3.6)

The Hardcopy utility allows you to specify a sequential data set or a member of a partitioned data set to be printed, and the destination of the output. It also allows you to specify whether a sequential data set is to be kept or deleted after printing. Partitioned data set members are always kept.

You can use the Hardcopy utility to print any DASD-resident data set except ISPF list and log data sets; use the ISPF LIST command to print log and list data sets during an ISPF session.

An optional print utility exit can be specified by your installation. If this exit is installed, it may cause the Hardcopy utility's response to differ from the descriptions shown here. See *z/OS ISPF Planning and Customizing* for more information about the print utility exit.

Another factor that can affect the Hardcopy utility's performance is whether the TSO/E Information Center Facility is installed. If the TSO/E Information Center Facility is installed, your installation can optionally allow ISPF to display a panel for submitting TSO/E Information Center Facility information with the print request. See "Using the TSO/E information center facility" on page 183 for more information.

If the TSO/E Information Center Facility is not installed, the Hardcopy utility first displays the panel shown in Figure 110.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                                Hardcopy Utility
                                                                More:     +
Process option   _  1. Print and keep data set or member
                    2. Print and delete sequential data sets

  Data Set Name  . .  ____________________________________________________
  Volume Serial  . . . . ______        (If not cataloged)
  Data Set Password  . .               (If password protected)

Print Mode . . . . . . . BATCH        (Batch or Local)

Batch Sysout class . . . ______________     (BATCH only)
Local printer ID or
writer-name  . . . . . . ________________   (LOCAL only)
Local Sysout class . . . ______________     (LOCAL only)

Job statement information: (If not to local printer/external writer, verify
before proceeding)
Command ===> ___________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 110. Hardcopy Utility panel - before JCL generation (ISRUHCP)

Hardcopy utility panel action bar

The Reset ISPF Statistics panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

RefList For information about referral lists, see the topic about Using Personal Data Set Lists and Library Lists in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down offers these choices:

1 General
2 Function of the hardcopy utility
3 Selecting a print mode
4 Submitting a background job to print a data set or member
5 Routing a data set to a printer local to your terminal group
6 Printing a data set using TSO/E Information Center Facility
7 Appendices
8 Index

Hardcopy utility panel fields

The Data Set Name, Volume Serial, Data Set Password, and Job statement information fields, shown in Figure 110 on page 180, are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*. The other fields on the panel are:

Print Mode
Lets you specify one of these print modes:

BATCH Submits your print request as a background job.

LOCAL Routes your data to a local printer, such as an IBM 328x printer that is connected to your terminal group.

Batch Sysout Class
Destination of printed data set. Used only if the data set is to be printed and Batch SYSOUT class is specified.

Local Printer ID or Writer name
Destination of printed data set. Used only if the data set is to be printed and Local Printer ID or external writer name is specified.

Note: If you specify a Local Printer ID or writer name and you have selected the Edit PRINTDS Command option on the ISPF Settings panel (option 0), ISPF displays the Local Print Command Edit panel to allow you to intercept and edit the PRINTDS command before it is processed. For more information on editing the PRINTDS command, see the "ISPF Libraries and Data Sets chapter" in the *z/OS ISPF User's Guide Vol I*.

Local Sysout Class
Used in conjunction with the Local Printer ID or Writer Name. Specifies the output class to use for output processing.

Generating and submitting JCL

Follow these steps to generate and submit JCL for your print jobs:

1. Choose one of the options listed at the top of the panel and type its code, 1 (for PK) or 2 (for PD), in the Option field.
2. Specify a fully qualified data set name and member name.

This is a required field. If you are entering a fully qualified TSO data set name, you must enclose the name in quotes. If you omit the quotes, the data set prefix from your TSO user profile is automatically added to the beginning of the data set name.

3. If the data set is not cataloged, specify the volume serial.
4. If your data set is password protected, type the password in the Data Set Password field. For more information on data set passwords, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.
5. Specify either BATCH or LOCAL in the Print Mode field.
6. Specify one of these:
   - If you chose BATCH in the previous step, type a Batch SYSOUT class and any job statement information you need.
   - If you chose LOCAL in the previous step, type the name of a local printer or writer name in the Local Printer ID field. Job statement information is ignored.
7. Press Enter.

   What happens next depends on your choice in step 5. If you chose BATCH, see step 7a. If you chose LOCAL, see step 7b on page 183.

   a. If you chose BATCH, ISPF generates the JCL and displays the panel shown in Figure 111, with the message `JCL generated` in the upper-right corner.

```
 Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                                Hardcopy Utility                 JCL generated
                                                                   More:     +
Process option  1  1. Print and keep data set or member
                   2. Print and delete sequential data sets
                   3. Exit without submitting job

Enter End command to submit job.

  Data Set Name  . . 'MYPROJ.DEV.SOURCE(TESTA)'
  Volume Serial  . . . . ______        (If not cataloged)
  Data Set Password  . .               (If password protected)

Batch Sysout class . . . A
Print Mode . . . . . . : BATCH        (Batch or Local)
Local printer ID or
writer-name  . . . . . :
Local Sysout class . . :

Job statement information:
Command ===> ____________________________________________________________
 F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 111. Hardcopy Utility panel - after JCL generation (ISRUHCJP)

At this point you can either:

- Cancel the job by typing the CANCEL command in the Option field and pressing Enter.
- Submit the job by typing the END command and pressing Enter. ISPF displays this message at the bottom of the panel:

  `IKJ56250I JOB useridA(JOBnnnnn) SUBMITTED`
  `***`

Press Enter. For more information about BATCH printing, see Additional batch printing information.
- Specify another data set name for printing.

b. If you chose LOCAL, ISPF calls the PRINTDS TSO command processor to print the data set on the specified local printer.

   A message is displayed in the short message area to show that PRINTDS has accepted the request. At this point, you can:
   - Specify another option and press Enter
   - Enter the END command
   - Enter the CANCEL command

8. If you entered CANCEL or END, ISPF determines the next panel you see as follows:
   - If you entered the Hardcopy utility from the ISPF Primary Option Menu or through the jump function (=), ISPF displays the ISPF Primary Option Menu.
   - If you entered the Hardcopy utility from the Utility Selection Panel, ISPF returns you to that panel.

Additional batch printing information

When you enter the desired information and press Enter, ISPF generates JCL that contains the job statement operands and a job step that prints the specified data set, using the IBM IEBGENER utility.

Notes:

1. IEBGENER does not support packed data. If you try to print packed data, you may get unwanted results. IEBGENER prints the data set one logical record per print line. If the logical record length is greater than the printer width, the logical record is truncated.
2. ISPF does not unpack data automatically before printing it. Therefore, if you need to unpack data before printing it, edit the data set and enter the PACK primary command with the OFF operand. See *z/OS ISPF Edit and Edit Macros* for more information about the PACK command.

Once the JCL for the first job step is generated, the job statement operands are shown for information aboutly. They are no longer highlighted and you cannot type over them, since the job statement has already been generated. You can then select another data set name to cause another job step to be generated.

Using the TSO/E information center facility

If the TSO/E Information Center Facility is installed, your installation can allow ISPF to display the panel shown in Figure 112 on page 184.

```
                              Hardcopy Utility


  Process option  1  1. Print and keep data set or member
                     2. Print and delete sequential data set



Data Set Name . . . . _____________________________________________________
Volume Serial . . . . ______        (If not cataloged)
Data Set Password . .               (If password protected data set)

Printer location  . . _______________

Printer format  . . . ________

Number of copies  . . ___




Command ===> ______________________________________________________________
 F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 112. Hardcopy Utility panel - with the TSO/E information center facility installed (ISRUHCPI)

Follow these steps to use the TSO/E Information Center Facility to submit your print jobs:

1. Choose one of the options listed at the top of the panel and type its code, `PK` or `PD`, in the Option field.
2. Enter a fully qualified data set name and member name.

   You must specify at least the low-level qualifier, such as LIST. If you enter your user prefix as part of the data set name, you must enclose the complete data set name in quotes. However, if you omit the user prefix and quotes, your user prefix is automatically added to the beginning of the data set name.
3. If the data set is not cataloged, enter the volume serial.
4. If your data set is password-protected, enter the password in the Data Set Password field. For more information about data set passwords, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.
5. You can either leave the Printer location field blank or enter the location ID of the printer to be used. The location ID is assigned by your installation.

   You can also enter a partial location name followed by an asterisk (*).
6. You can either leave the "Printer format" field blank or enter the format ID of the printer to be used. The format ID is assigned by your installation.

   You can also enter a partial format name followed by an asterisk (*). If your printer location and format entries do not identify a specific printer, a printer selection list is displayed. From this list, which is similar to a member selection list, you can select a printer.
7. Specify the number of copies you want.
8. Press Enter.

   The values entered in the fields on this panel are passed directly to the TSO/E Information Center Facility for processing.

Download data set to workstation utility (option 3.7)

The Download Data Set to Workstation utility allows you to upload or download data sets from the host environment to your workstation. This utility is also used to download the WSA installation files needed to create a workstation connection.

Before you install the workstation utility
Review the information in the topic "Installing the Client/Server component" in the *z/OS ISPF User's Guide Vol I* before you use this utility to install the WSA for the first time.

When you select option 7 from the Utility Selection Panel, ISPF displays the Download Data Set to Workstation panel (ISPUDL). This panel has two options:

1. Download the ISPF C/S component to your workstation
2. Download or upload an ISPF library, PDS or sequential data set

Download ISPF C/S component

This option enables you to download the ISPF Workstation Agent (WSA) component installation program to your desktop workstation. After downloading the WSA and installing it, you can use ISPF on a z/OS host through GUI windows on your workstation and use your workstation connection in distributed editing. See the topic "Installing the Client/Server component" in the *z/OS ISPF User's Guide Vol I* for a description of the download and installation processes.

When you select option 1 from the Download Data Set to Workstation panel, ISPF displays the ISPF Client/Server Component Download panel shown in Figure 113.

```
                Client/Server Component Download

Download methods
_  1. FTP (requires workstation FTP server)
   2. ISPF C/S (requires workstation connection)
   3. Manual

Workstation Type
   1. Windows 2000/NT          3. AIX              5. HP UX
_  2. Reserved             4. Solaris

Directory to copy file to:
            ____________________________________________________________

Data Set to copy file from:
            ____________________________________________________________

Enter "/" to select option
   Create directory to which the file is to be copied.


Command ===> ______________________________________________________________
 F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 113. ISPF Client/Server Component Download panel (ISPWSD01)

The Client/Server Component Download panel enables you to choose the download method and workstation type you want to use to put the WSA installation program on your desktop.

Client/Server Component Download panel

The Client/Server Component Download panel contains these fields:

Download methods
You have three choices for downloading the WSA installation program.

FTP (requires workstation FTP server)
Download using FTP. ISPF invokes the host FTP client to connect with the FTP server on your workstation and transfer the WSA installation program. This option can be used to download the WSA installation program for the first time. It is described in the topic "Installing the Client/Server component" in the *z/OS ISPF User's Guide Vol I*.

ISPF C/S (requires existing workstation connection)
Download using ISPF Client/Server. If you already have a workstation agent installed on your workstation, you can use the built-in file transfer services to download a new or updated WSA installation program. The file must be downloaded in binary format.

Manual
ISPF tells you the name of the file you need to copy. You can copy it with any method you prefer as long as you maintain the data integrity of the WSA installation program. The file must be downloaded in binary format. This option can be used to download the WSA installation program for the first time. It is described in the topic "Installing the Client/Server component" in the *z/OS ISPF User's Guide Vol I*.

Workstation type
The workstation agent runs on different workstation platforms and you must indicate which platform you have, so that you receive the correct version.

1. Windows 2000 or NT
2. Reserved
3. AIX
4. Solaris
5. HP UX

Directory to copy file to
Specify a directory on your workstation where you want to store the WSA installation program. You can specify a full path name or a relative directory, or leave this field blank. If you leave it blank, the download is made to your home directory (in the case of FTP downloads) or the current directory (in the case of client/server downloads). If you specify a relative directory (one that does not start with a drive letter or slash character) the directory is relative to the FTP home directory or the client/server current directory.

Data set to copy file from
The host data set that contains the WSA installation program. This value varies depending on the naming convention that was used when ISPF was installed.

Create directory to which the file is to be copied
If you want ISPF to create the directory on your workstation before copying the WSA installation program, enter a "/" in this field.

ISPF client/server (c/s) download

When you select choice 2 "ISPF C/S (requires workstation connection)" under *Download methods* on the ISPF Client/Server Component Download panel, you are choosing to use the ISPF Client/Server method of downloading. This method is used to obtain updated versions of the WSA and can only be used if you have already installed and initiated the WSA and established a workstation connection. If this is the first time you are downloading the WSA, use the FTP or Manual methods of downloading, instead.

If you do not already have a workstation connection (with or without GUI display) established, ISPF displays the ISPF Client/Server Installation Notice panel shown in Figure 114.

```
ISPWSD03          Client/Server Installation Notice

A workstation connection is required to download a new Client/Server
component using workstation agent file transfer services.

Do you wish to start a workstation connection now?
_   1. Yes, start workstation connection now and continue with download
    2. No, do not start workstation connection

Command ===>
 F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
 F9=Swap      F12=Cancel
```

Figure 114. ISPF Client/Server Installation Notice (ISPWSD03)

The field on this panel is:

Do you wish to start a workstation connection now?
This field enables you to start a workstation connection directly from the panel. This assumes, of course, that you have a previous copy of the WSA installed on your workstation.

1. Yes, start workstation connection now and continue with download.
Select this option when you know you have a Workstation Agent installed and you have initiated it on your workstation.

2. No, do not start workstation connection
Select this option when you know that a prerequisite for establishing a workstation connection has not been met and you want to return to the Client/Server Component Download panel.

If you have already established a workstation connection (see “Initiate the workstation connection” on page 60) and you select this download method, the Client/Server transfer service is immediately invoked to copy the WSA installation program to your workstation. A successful transfer results in the panel shown in Figure 115.

```
                ISPF Client/Server Component Install Program

The ISPF Client/Server Component workstation install program has been
copied to your workstation in directory:

   C:\TEMP

in directory:

End your workstation connection, close the active workstation agent,
and complete the installation by running the install program ISPFINST
on your workstation in the directory specified. The program is a self
extracting executable that will result in additional files being
generated on your workstation.

Do you wish to end your workstation connection now?
_  1. Yes, end workstation connection now
   2. No, do not end workstation connection now

Command ===> _____________________________________________________
 F1=HELP       F2=           F3=END        F4=DATASETS   F5=FIND
 F6=CHANGE     F9=SWAP      F10=LEFT      F11=RIGHT     F12=SUBMIT
```

Figure 115. ISPF Client/Server Component Install Program panel (ISPWSD06)

Running the installation program (ISPFINST)

After you have downloaded the Workstation Agent Installation program, resume the installation by running the program called ISPFINST.EXE (ispfinst on UNIX platforms). This is a self-extracting executable program that generates additional necessary files on your workstation. See the topic "Installing the Client/Server component" in the *z/OS ISPF User's Guide Vol I* for a description of the Workstation Agent installation process.

Download/upload data set

The final option on the Download Data Set to Workstation (option 3.7) panel is called “Data Set — Download/upload ISPF library, partitioned, or seq data set”. This option provides a panel-driven interface to the ISPF FILEXFER service, enabling you to transfer data between the host and the workstation. This is a manually controlled alternative to using the Workstation Tool Integration (see “Workstation tool integration” on page 67).

Selecting option 2 displays the panel shown in Figure 116 on page 189:

```
  Menu  RefList  RefMode  Help
 ------------------------------------------------------------------------------
                  Download/Upload Data Set To/From Workstation

 ISPF Library:
    Project . . . MYPROJ
    Group . . . . DEV     . . . ________ . . . ________ . . . ________
    Type  . . . . SOURCE
    Member  . . . ________      (Blank or pattern for member selection list)

 Other Partitioned or Sequential Data Set:
    Data Set Name . . . ____________________________________________________
    Volume Serial . . . ______  (If not cataloged)

 Workstation File:
    File Name . . . . . ____________________________________________________

 Transfer Option                        Options
 _  1. Download to workstation          _  Generate statistics on upload
    2. Upload from workstation          _  Transfer in text mode
                                        _  Replace existing member/file
 Command ===> ___________________________________________________________________
  F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
  F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 116. ISPF data set panel (ISPUDLDS)

Use the Download or Upload selections to indicate whether you want to download host data to the workstation, or upload workstation data to the host. Enter 1 for “download to workstation”. Enter 2 for “upload from workstation”.

You can transfer data from either PDS or sequential host data sets. The host data set must exist before attempting a transfer, but a PDS member is created if it does not already exist. Workstation files need not exist before downloading data from the host, but the specified directory must be there.

For downloading only, you can specify an asterisk (*) character in the workstation file name. ISPF substitutes the member name of the data being downloaded for the *. This enables you to select multiple members from the member list to be downloaded as separate files.

“Generate Statistics on Upload” indicates whether ISPF member statistics should be generated when a workstation file is uploaded to a member of a PDS. Statistics are only generated when the host data set is record format F or V.

The “Transfer in Text mode” field determines whether the file transfer is done in text mode (with ASCII to EBCDIC translation) or in binary mode (without any translation). When transferring in text Mode, the ispf filexfer service provides a one-to-one mapping of all 256 code points between the host code page and the workstation code page. Most other file transfer utilities (for example, ftp) only provide a one-to-one mapping of displayable characters.

Outlist utility (option 3.8)

This utility gives you the ability to browse, print, delete, or requeue job output that is in a held SYSOUT queue. When you select this option, a panel is displayed (Figure 117 on page 190) that allows you to select an option and enter the appropriate operands.

```
  Menu  Utilities  Help
 ------------------------------------------------------------------------------
                                Outlist Utility
                                                                        More:     +
    L List job names/id(s) via the TSO STATUS command
    D Delete job output from SYSOUT hold queue
    P Print job output and delete from SYSOUT hold queue
    R Requeue job output to a new output class
blank Display job output

For Job to be selected:
   Jobname  . . ________
   Class  . . . _
   JobID  . . . ________

For Job to be requeued:
   New Output class  . . _

For Job to be printed:
   Printer Carriage Control  . . _         (A for ANSI    )
                                           (M for machine )
Option ===> ____________________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 117. Outlist Utility panel (ISRUOLP1)

Outlist Utility panel action bar

The Outlist Utility panel action bar choices function as follows:

Menu
For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help
The Help pull-down offers you these choices:

1 General
2 Listing the status of jobs
3 Deleting the output of a held job
4 Printing the output of a held job
5 Requeueing the output of a held job
6 Displaying the Output of a held job
7 Appendices
8 Index

Outlist Utility panel fields

The fields on this panel are:

Jobname
The held SYSOUT job. It is required for all options except option L.

Class
The SYSOUT hold queue. If you omit the CLASS operand, all SYSOUT queues are searched for the specified job.

JobID
Required only if more than one job exists with the same job name.

New Output class
When requeuing a job (option R), enter the new SYSOUT hold class here.

Printer Carriage Control
When printing a data set (option P), enter a value here that corresponds to the type of carriage control characters in the data set. Valid values are:

A If the data contains American National Standard Institute (ANSI) carriage control characters.

M If the data contains machine control characters.

Blank If the data contains no carriage control characters.

The record formats for the corresponding data sets are FBA, FBM, and FB, respectively.

Outlist utility options

These topics explain the options listed at the top of the Outlist Utility panel:

- "L — list job names/ID(s) via the TSO STATUS command"
- "D — delete job output from SYSOUT hold queue"
- "P — print job output and delete from SYSOUT hold queue"
- "R — requeue job output to a new output class" on page 192
- "Blank — display job output" on page 192

L — list job names/ID(s) via the TSO STATUS command

If you select option L, a list of job names and job IDs is displayed. If you leave the job name blank, or if the job name is your user ID plus one identifying character, the status is listed for all jobs having job names consisting of your user ID followed by that identifying character. If you supply any other job name, the status for that exact job is displayed.

The list of job names is displayed on the lower portion of the panel. If the list is too long to fit on the screen, three asterisks are displayed on the last line of the screen. You can display the remainder of the list by pressing Enter.

D — delete job output from SYSOUT hold queue

If you select option D, the held output for a specific job is deleted from the specified SYSOUT queue.

P — print job output and delete from SYSOUT hold queue

If you select option P, the held output for a specific job is removed from the SYSOUT queue and placed in an ISPF-defined data set for printing. You can choose the record format for this data set by putting an entry in the Printer Carriage Control field.

An optional print utility exit can be installed by your system programmer. If this exit is installed, it may cause the Outlist utility's response to differ from the descriptions provided here. See *z/OS ISPF Planning and Customizing* for more information about the print utility exit.

Another factor that can affect the performance of the Outlist utility is whether the TSO/E Information Center Facility is installed. If the TSO/E Information Center Facility is installed, your installation can optionally allow ISPF to display a panel for submitting the TSO/E Information Center Facility information with the print

request. See Figure 176 on page 311 for an example of this panel and "Using the TSO/E information center facility" on page 183 for information about the fields on this panel.

If the TSO/E Information Center Facility is not installed, the Outlist utility displays the panel shown in Figure 175 on page 304 when you press Enter. Use this panel to tell ISPF how and where the job output is to be printed. This option does not honor multiple copies for output on hold queue. To print multiple copies use option R.

ISPF uses temporary data sets named *prefix.userid*.SPF*nnn*.OUTLIST (if your data set prefix in your TSO user profile is different from your TSO userid) or *userid*.SPF*nnn*.OUTLIST (if your prefix and userid are the same), where *nnn* is a number between 100 and 999.

Attention: If you keep or use all data sets through 999, ISPF resets to 100 and uses the existing data sets. Also, ISPF can use the data sets that you allocate using the temporary data set naming convention.

R — requeue job output to a new output class

If you select option R, the held output for a specific job is requeued to another SYSOUT class from the specified SYSOUT queue. You must enter the new SYSOUT class on the panel in the "New Output class" field. You can use this option to print output with multiple copies by requeuing to a SYSOUT class predefined to print multiple copies.

Blank — display job output

If you leave the Option field blank, the held output for the specified job is displayed in Browse mode. You can use all Browse commands. The data remains in the SYSOUT queue. When you enter the END or RETURN command to end Browse, the Outlist Utility panel is displayed again, and you can then choose to print, requeue, or delete the job output.

Command table utility (option 3.9)

The Command Table utility (option 3.9) enables you to create or change ISPF application command tables. When you select this option, a panel is displayed (Figure 118 on page 193) to prompt you for an application ID. The name of the command table is then derived by adding CMDS to the application ID. If the table exists in the table input library, ISPTLIB, it is displayed and can be modified. If the table does not exist in the table input library, a new table is generated.

The command table displays the search order of commands for a particular logical screen. The order is from top to bottom of those commands displayed. The "User table" and "Site table" fields are blank if no values are set for them in the ISPF Configuration table, or if values have been set but the tables do not exist in the "ISPTLIB" concatenation.

You cannot use this utility to change a command table that is currently in use. Command table ISPCMDS, the system command table, is always in use by the Dialog Manager component. If you enter ISP in the Application ID field, ISPF displays the ISPCMDS command table in read-only mode.

While you are using this utility to change a command table, the table cannot be used for other purposes. For example, you cannot use split screen and select a

function with NEWAPPL(XYZ) if you are changing command table XYZCMDS.

```
  Menu  Help
_ ──────────────────────────────── Commands ────────────────────────────────
I  ISPUCMA                 Command Table Utility

1    Specifications                        Command table search order
     Application ID . . ISR                Application table  . : ISR
2    Enter "/" to select option            User table 1 . . . . : USER
     _  Show description field             User table 2 . . . . :
3                                          User table 3 . . . . :
4                                          Site table 1 . . . . : SITE
                                           Site table 2 . . . . :
5                                          Site table 3 . . . . :
6                                          System table . . . . : ISP
7
8  If no application ID is specified, the current application ID will be
9  used. The name of the command table to be processed is formed by
1  prefixing the application id to the string 'CMDS'.  For example:
1  Application ID  . .  TST results in a command table name of 'TSTCMDS'.
1
1  Command ===> ____________________________________________________________
1   F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
0   F9=Swap      F12=Cancel
 ────────────────────────────────────────────────────────────────────────────
F10=Actions  F12=Cancel
```

Figure 118. Command Table Utility panel (ISPUCMA)

Command Table Utility panel fields

The fields on the Command Table Utility panel function as follows:

Application ID
Contains the name of an application for which you want to define commands.

Show description field
Allows you to display the descriptions as well as the commands and definitions.

The command table for the named application is displayed on a Command Table editing panel (Figure 119 on page 194). This panel can be scrolled up and down using the scroll commands.

```
  File  Menu  Utilities  Help
 ------------------------------------------------------------------------
                                 Update TSTCMDS               Row 1 to 4 of 4

 Insert (I), delete (D), repeat (R) and edit (E) command entries.
 Enter END command to save changes or CANCEL to end without saving.

      Verb      T  Action
 ____ SORT      0  SELECT PGM(PQRSORT) PAR(&ZPARM)
 ____ PREPARE   4
 ____ QUIT      2  ALIAS END
 ____ EXPLAIN   4
 ****************************** Bottom of data ********************************



 Command ===> ____________________________________________________ Scroll ===> PAGE
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 119. Command table editing panel (ISPUCMD)

The column headings on the panel are:

Verb The command verb, which is the name of the command you are defining in the command table. A command verb must be 2 to 8 characters long, inclusive, and must begin with an alphabetic character. The content of this column is assigned to the ZCTVERB system variable.

T (truncation)
The minimum number of characters that you must enter to find a match with the command verb. If this number is zero or equal to the length of the command verb, you must enter the complete command verb. For example, in Figure 119 the PREPARE command has a truncation value of 4. Therefore, for the TST application used as the example in the figure, only the first four letters, PREP, must be entered to call this command. The content of this column is assigned to the ZCTTRUNC system variable.

Action
The actual coding of the action to be carried out when you enter the command. The action length must not be greater than 240 characters. The content of this column is assigned to the ZCTACT system variable.

To enter or edit the coding for the action:

1. Enter the E command table line command to display the Extended Command Entry panel (ISPUCMX).
2. Type the required coding in the Action lines.

   Normally, any text you type in lowercase is translated to uppercase before it is saved.

   To define some of the parameters in lowercase select the **Allow mixed-case in Action field** option on the Extended Command Entry panel. The case of the text you type is not translated and is saved as you input it.

   Note that when you select the **Allow mixed-case in Action field** option:

a. The first word *must* be input in uppercase.
b. If you use &ZPARM to obtain parameters from the command line, the parameters may be translated to uppercase (regardless of the setting of the **Allow mixed-case in Action field** option).

3. Optionally, type a brief description of the purpose of the command in the Description lines.
4. Press PF3 to return to the Command Table Editing panel.

Notes:

1. Do not use ACTIONS, CANCEL, CRETRIEV, CURSOR, EXIT, PRINT, PRINTG, PRINTHI, PRINTL, PRINTLHI, RESIZE, RETF, RETP, RETRIEVE, SPLIT, SPLITV, SWAP, WINDOW, or WS as keywords in the Action column. These keywords are intended only for use in the system command table distributed with ISPF. They are not intended for use in application command tables.
2. Take care with ACTIONs that use ZPARM, as the ISPF parser will add a matching parenthesis if one appears to be missing. Consider an entry of "SELECT CMD(%CMD &ZPARM) NEWAPPL(ISR)". If "(XYZ" is passed then the command will receive "(XYZ) NEWAPPL(ISR)" as a parameter.

The valid actions are:

SELECT
Causes the selected dialog (command, program, or selection panel) to be given control immediately. See *z/OS ISPF Dialog Developer's Guide and Reference* for more information about the SELECT statement and its keywords.

ALIAS
Allows one command verb to carry out the action defined for another. For example, in Figure 119 on page 194, QUIT is an alias for END. Therefore, for the TST application used as the example in the figure, entering QUIT causes the same action to occur as entering END.

An ALIAS command must be defined before the command for which it is an ALIAS.

PASSTHRU
Causes the command to be passed through to the dialog as if it had not been found in the command table.

SETVERB
Causes the command to be passed through to the dialog, with the command verb stored separately from the operands.

NOP
Causes the command to be inoperative. An inactive command message is displayed.

Blank
Causes the command table entry to be ignored. ISPF continues to search for additional entries for the same command verb. If the command is not found in either the application command table or the system command table, an invalid command message is displayed.

xxxxx
A variable name, beginning with an ampersand (&), allows dynamic specification of the command action.

DESCRIPTION
An optional, brief description of the action the command verb is to perform. Since this column is offset three spaces under the Action column, the description length must not

be greater than 80 characters. The content of this column is assigned to the ZCTDESC system variable.

For a new table, this panel initially contains dummy entries with all fields shown as underscores. The underscores are pad characters and need not be blanked out. However, any null entries where at least the verb contains all underscores are automatically deleted when the table is saved.

Scrolling a command table

You can scroll the table entries, using the ISPF UP and DOWN scroll commands, and change one or more entries simply by typing over them.

Saving a command table

The END command causes the table to be saved in the table output library, ISPTABL, and ends the utility.

Canceling a command table

The CANCEL command ends the command table display without saving the table.

Using command table line commands

The line commands you can enter at the left of any entry (by typing over the four quotation marks) are described in these topics:

- "D — deleting lines"
- "E — editing lines"
- "I — inserting lines"
- "R — repeating lines"
- "V — viewing lines"

Multiple line commands or changes can be entered in a single interaction. Line commands followed by a number, such as D3, are repeated that number of times. The lines are processed in the order in which they appear on the screen. Any line commands or changes that are entered concurrently with the END command are processed before the table is saved.

D — deleting lines

The D command deletes one or *n* lines (`D[n]`).

E — editing lines

The E command displays the Extended Command Entry panel (ISPUCMX) where you can edit the action and description fields for a line.

I — inserting lines

The I command inserts one or *n* lines (`I[n]`). The inserted lines contain underscores (pad characters) in all field positions.

R — repeating lines

The R command repeats a line one or *n* times (`R[n]`). The repeated lines contain underscores (pad characters) in the Verb and T (truncation) fields, but the Action and Description fields are copied from the line on which the R command was entered.

V — viewing lines

The V command views one or *n* lines (`V[n]`). You can look at the entire command entry including the command action and description fields, but you cannot change them.

Format specifications utility (option 3.11)

The Format Specifications utility (option 3.11) is provided to support the IBM 5550 terminal using the Double-Byte Character Set (DBCS). It is used to maintain formats that are used when viewing, browsing, and editing to display data sets that contain predefined formatted records.

The purpose of a format is to structure data from a record into fields, and to define the order these fields are to be physically displayed on the screen when you are viewing, browsing, and editing.

When you select this option, a panel is displayed (Figure 120) that allows you to add, copy, delete, or update a format. You can also display the format list.

```
 Menu  Utilities  Help
 ------------------------------------------------------------------------
                           Format Specifications
                                                                 More:     +
   A            Add a new format
   C            Copy formats
   D            Delete a format
   U            Update format
   L or BLANK   Display format list


Format Name . . . ________

For COPY operations, specify the following:

    From Format . . . ________  (Blank for format list, * for all formats)

    From Table  . . . ________  (Default is "ISRFORM" )


Note: The Format Utility is provided for support of the IBM 5550 terminal
Option ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 120. Format Specifications panel (ISRFM01)

Format Specifications panel action bar

The Format Specifications panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down introduces formats and provides information about how to add, copy, delete, update, and display formats.

Format Specifications panel fields

The fields on this panel are:

Format Name The name of the format that you want to add, delete, or update. When copying a format (option C), this is the name you want the copied format stored under.

From Format When copying a format (option C), you can:
- Enter the name of a format you want to copy
- Enter an asterisk (*) to copy all formats
- Leave the field blank to display a copy format selection list.

See Figure 122 on page 201 for an example of a Copy Format Selection List display.

From Table When copying a format (option C), you can:
- Enter the name of a table from which you want to copy a format
- Leave the field blank if you want to copy a format from the ISRFORM table.

Note: The ISRFORM table is the default location in which all of your user-defined formats are stored. If you have not yet defined any formats, this table will be empty.

Format Specifications panel options

These topics describe the options shown at the top of the Format Specifications panel:

- "A — add a new format"
- "C — copy formats" on page 199
- "D — delete a format" on page 201
- "U — update a format" on page 201
- "L or BLANK — display format list" on page 201

A — add a new format

If you specify option A and a format name, the Format Definition panel (Figure 121 on page 199) is displayed.

```
                        Format Definition (FORM01)
                                                                More:     +

 Field   Start   Field   Field        Field   Start   Field   Field
 Number  Column  Length  Type         Number  Column  Length  Type
    1    00000     00      _             2    00000     00      _
    3    00000     00      _             4    00000     00      _
    5    00000     00      _             6    00000     00      _
    7    00000     00      _             8    00000     00      _
    9    00000     00      _            10    00000     00      _
   11    00000     00      _            12    00000     00      _
   13    00000     00      _            14    00000     00      _
   15    00000     00      _            16    00000     00      _
   17    00000     00      _            18    00000     00      _
   19    00000     00      _            20    00000     00      _

 Field Number: Identifies the field position on the screen.
 Start Column: From 1 to 32760; Specifies column position in the record.
 field Length: From 1 to 71; Fields must not overlap.
 Field Type  : E - single-byte, D - double-byte,  M - mixed data

 Enter the END command to exit and save the format.
Command ===> _____________________________________________________________
 F1=Help    F2=Split   F3=Exit    F9=Swap   F12=Cancel
```

Figure 121. Format Definition panel (ISRFM02)

A field definition includes:

Field Number The number of the field for which you are defining a format. You can define up to 20 fields.

Start Column Starting column position in the record.

Field Length Field length in bytes; the maximum is 71 bytes.

Field Type The type of data that can be entered in the field. Valid types are:
- **E** EBCDIC (single-byte)
- **D** DBCS (double-byte)
- **M** Mixed data

Note: All three of these field types can contain extended graphics characters. CAPS ON processing is not possible because of context dependencies. Therefore, it is ignored when you are editing formatted data.

The format definition information applies to both existing records and inserted records in a data set.

Note: It is recommended that you avoid using STD or COBOL formats with numbered data. The results can be different from using formats with unnumbered data. If you must use numbered data, do not define the columns the sequence numbers will appear in, or define an EBCDIC or mixed data field for them.

C — copy formats

If you specify option C on the Format Specifications panel:

- If you specify both an asterisk (*) in the From Format field and a table name other than ISRFORM in the From Table field, all formats stored in the “From” table are copied to ISRFORM.

Note: If you specify a table name in the From Table field, and that table does not have the same format as ISRFORM, a severe error occurs.

- If you specify both a format name and a “From” format, the format is copied. If you specified a “From” table (other than ISRFORM), the format is copied from that table. Otherwise, the format is copied from ISRFORM. The Format Definition panel for the newly created format, containing the currently defined fields, is displayed. You can add, delete, and update field definitions. When you enter the END command, the format definition is stored in ISRFORM under the format name you specified.
- If you specify a format name but no “From” format, the Copy Format Selection List panel (Figure 122 on page 201) is displayed.

  If you did not specify a “From” table, the formats listed are those stored in ISRFORM, the default format table. Otherwise, the formats listed are those stored in the table you specified.

  Note: The ISRFORM table is the default location in which all of your user-defined formats are stored. If you have not yet defined any formats, the table will be empty and you will receive a ″No formats found″ message.

  You can select a format to copy by entering the S line command to the left of that format name. Other commands you can enter are U (Update), R (Rename), D (Delete), SELECT (which is similar to S), SORT, and LOCATE. See “Format selection list commands” on page 201 for a description of these commands.

  The format is copied, and the Format Definition panel for the newly created format, containing the currently defined fields, is displayed. You can add, delete, and update field definitions. When you enter the END command, the format definition is stored in ISRFORM under the format name you specified on the Format Specifications panel.
- If you specify neither a format name nor a “From” format, but you do specify a “From” table (other than ISRFORM), the Copy Format Selection List panel is displayed. You can select one or more formats to copy by entering the S line command to the left of each format names. Each of these formats is copied under the same name from the specified “From” table to the ISRFORM table.

Note: If you do not specify option C but specify a name in the From Format field, the From Format field is ignored.

```
                    Copy Format Selection List (ISRFORM)       Row 1 to 4 of 4
       Name      Rename    Created   Last Modified       ID
       COMMON01            02/11/19  02/11/19  11:08     USERID
       COMMON02            02/11/19  02/11/19  11:16     USERID
       COMMON03            02/11/19  02/11/19  11:16     USERID
       COMMON04            02/11/19  02/11/19  11:16     USERID
******************************* Bottom of data ********************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F12=Cancel
```

Figure 122. Copy Format Selection List panel (ISRFM04)

D — delete a format

If you specify option D and a format name on the Format Specifications panel, the format is deleted.

U — update a format

If you specify option U and a format name on the Format Specification panel, the Format Definition panel containing the currently defined fields is displayed. You can add, delete, and update field definitions.

L or BLANK — display format list

If you specify option L or leave the Option line blank on the Format Specifications panel, the Format Selection List panel (Figure 123) is displayed.

```
                            Format Selection List              Row 1 to 4 of 4
       Name      Rename    Created   Last Modified       ID
       COMMON01            02/11/19  02/11/19  11:08     USERID
       COMMON02            02/11/19  02/11/19  11:16     USERID
       COMMON03            02/11/19  02/11/19  11:16     USERID
       COMMON04            02/11/19  02/11/19  11:16     USERID
******************************* Bottom of data ********************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F12=Cancel
```

Figure 123. Format Selection List panel (ISRFM03)

Format selection list commands

These topics describe the commands you can use on a Format Selection List panel:

- "Locating format names" on page 202
- "Renaming a format" on page 202

- "Sorting format names"
- "Updating or selecting a format"

Deleting a format

If you specify the D line command beside a format name, the format is deleted.

Locating format names

The LOCATE command is another useful tool, especially if you have a long format list. To use the LOCATE command, ensure that the list is sorted by name. Next, enter the LOCATE command on the Command line. The syntax is:

LOCATE *name*

where:

name The name of the format you want to find.

For example, this command would find a format named FORM03:

```
LOCATE FORM03
```

If the format exists, the entry for the specified format name appears as the second line following the header lines. If the specified name is not found, the existing format name that would immediately precede the specified name appears as the first line following the header lines.

Renaming a format

If you specify the R line command beside a format name, you must also specify its new name in the Rename field before you press Enter. If you do not, the `Enter required field` message appears in the upper-right corner of the screen and the cursor moves to the Rename field.

Sorting format names

You can sort the name list on this panel by entering the SORT command on the Command line. The syntax of the SORT command is:

```
SORT [NAME | TIME]
```

where:

NAME Sort by name.

TIME Sort by time last modified.

For example, this command would sort a format selection list by time:

```
SORT TIME
```

Updating or selecting a format

If you specify the U or S line command beside a format name, the Format Definition panel containing the currently defined fields is displayed. You can add, delete, and update field definitions.

You can specify that multiple operations be done at the same time. However, if you specify U or S with other line commands, any commands after the first U or S are ignored.

The SELECT command provides you with another way to specify a format. This command is entered on the Command line.

The syntax of the SELECT command is:

SELECT *name*

where:

name The name of the format you want to select.

If the format exists, the Format Definition panel containing the currently defined fields is displayed. You can add, delete, and update field definitions.

If no format exists for that name, a new format is created, and the Format Definition panel is displayed to allow you to define fields.

SuperC utility (option 3.12)

Note: For an introduction to the SuperC and SuperCE utilities (options 3.12 and 3.13), see Appendix A, "SuperC reference."

The SuperC utility (option 3.12) is a dialog that uses the SuperC program to compare data sets of unlimited size and record length at the file, line, word, or byte level. The panel shown in Figure 124 is used to specify the name of a new data set.

Note: In this context, a *new* data set is an updated version of a previously created data set, such as a data set in your private library that has been modified but has not yet been promoted.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                     SuperC Compare Utility - New Data Set

 Specify "New" Data Set to be compared, then press the ENTER key.
                                                                 More:     +
    Project . . . _______
    Group . . . . _______ . . . _______ . . . _______ . . . _______
    Type  . . . . _______
    Member  . . . _______         (Blank or pattern for member selection list,
                                    "*" for all members)

 "New" Other Partitioned, Sequential or VSAM Data Set:
    Data Set Name . . . ______________________________________________
    Volume Serial . . . ______     (If not cataloged)

 Profile DS Name  . . . ______________________________________________
 Data Set Password  . .            (If New data set password protected)

 Enter "/" to select option      Execution Mode          Output Mode
 _  Mixed Mode                   1  1. Foreground        1  1. View
 _  Bypass selection list           2. Batch               2. Browse
 Command ===> ________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 124. SuperC Utility panel (ISRSSNEW)

This panel requires only the names of the input data sets and a foreground or batch mode setting.

Note: For DBCS searches and compares to function properly, ISPF must be invoked with the JAPANESE keyword, on a terminal that supports DBCS, and the MIXED process option must be supplied to SuperC.

SuperC Compare Utility panel action bar

The SuperC Utility panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

RefList For information about referral lists, see the topic about Using Personal Data Set Lists and Library Lists in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down provides general information about SuperC topics, as well as information about specifying the data sets and options and interpreting listings.

SuperC Compare Utility panel fields

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*, except:

Profile DSN
The name of an optional data set that can contain a compare type, listing type, sequence numbers setting, Browse setting, process options, and process statements. All these elements, when combined in one data set or member, are called a *profile*. See "Profiles and defaults - activate profiles and defaults" on page 221 for information about using the SuperCE utility (option 3.13) to create a profile data set.

The listing type and sequence numbers setting of the profile are copied onto the panel used to specify the old data set name (Figure 125 on page 206), but can be typed over or blanked out. However, other elements of the profile are in effect, even though they are not shown on the panel.

Mixed Mode
Select this field to have SuperC scan and parse the input data set lines for DBCS text strings.

Note: Mixed Mode is not valid for the File or Byte compare.

Bypass Selection List
When a member pattern is entered in the PDS Member List field or the member name portion of the data set field (such as MY.DATA.SET(pattern)), selecting this field causes SuperC to process all members matching that pattern without displaying a member selection list. Leaving this field blank causes the member list to be displayed.

Execution Mode
The processing mode you want to use when comparing the data sets. Choose one of these:

1 **Foreground**. After the old data set panel and member selection, if any, are completed, foreground mode compares the new and old

data sets and stores the results in the data set specified in the **Listing DS Name** field, which you can browse at the terminal.

2 **Batch**. After the old data set panel and the member list, if any, are completed, batch mode causes the display of the SuperC Utility - Submit Batch Jobs panel, so you can specify job card and print disposition information or edit the JCL. Then, the batch job is submitted to compare the new and old data sets. See "Submitting a SuperC job in batch mode" on page 209 for more information.

Note: You cannot specify a data set password in batch mode. If your data sets are password protected, use foreground mode.

Output Mode

The output mode you want to use when displaying the listing file. Choose one of these:

1 **View**. This enables the listing file to be displayed in *view* mode. All View functions are enabled in this mode.

2 **Browse**. This enables the listing file to be displayed in the *browse* mode. All Browse functions are enabled in this mode.

When you complete the New Data Set panel and press Enter, ISPF displays the panel shown in Figure 125 on page 206. Of the five fields shown at the bottom of the panel (Volume Serial, Listing DS Name, Data Set Password, Listing Type, and Sequence Numbers), all except Listing Type may not appear, depending on the mode you choose (foreground or batch) and the contents of the profile data set. Also, if you request a member list or specify an asterisk (*) in the Member field on the new data set panel, ISPF does not display a Member field on the old data set panel.

Note: In this context, an *old* data set is a base version of a data set, such as a data set in a production library.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                     SuperC Compare Utility - Old Data Set

 Specify "Old" Data Set to be compared, then press the ENTER key to compare to
 "New" Data set . . : MYPROJ.DEV.SOURCE
                                                                   More:     +
    Project . . . MYPROJ
    Group . . . . TEST     . . . ________ . . . ________ . . . ________
    Type  . . . . SOURCE
    Member  . . . ________

 "Old" other Partitioned, Sequential or VSAM Data Set:
    Data Set Name . . . ____________________________________________________
    Volume Serial . . . ______      (If not cataloged)

 Listing DS Name  . . . SUPERC.LIST______________________________________________
 Data Set Password  . .            (If Old data set password protected)

 Listing Type . . . . 1  1. Delta   2. CHNG    3. Long    4. OVSUM   5. Nolist

 Command ===> ___________________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 125. SuperC Utility - Old Data Set panel (ISRSSOLD)

Specify the name of an old data set. The type of old data set that you can specify depends on the type of new data set you specified on the previous panel. For example, you can compare:

- A complete new PDS to a complete old PDS
- A new sequential data set to:
  - An old sequential data set
  - An old membered PDS
- A new membered PDS to an old sequential data set.

In this context, the term *membered PDS* refers to a PDS for which a single member has been specified, such as:

```
'USERID.TEST.SCRIPT(NEWDATA)'
```

SuperC treats a membered PDS as a sequential data set because the comparison is done on a one-to-one basis. However, SuperC cannot compare a sequential data set to a complete PDS because it cannot compare one data set to more than one member of another data set.

When you press Enter, ISPF either displays a member selection list or begins the comparison. All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*, except:

Update DS Name

Tells SuperC the name of the data set that will contain column-oriented results of the comparison.

Note: This field is not displayed unless your profile data set contains an update (UPD*xxxx*) process option.

This data set is normally used as input to post processing programs and can be specified in addition to the normal listing data set. See the Process Options selection in "Process options - select process options" on page 219 for information about the SuperC process options.

If you leave this field blank, SuperC uses this default name:

prefix.*userid*.SUPERC.UPDATE

where *prefix* is your TSO prefix and *userid* is your user ID. If your prefix and user ID are identical, only your prefix is used. Also, if you do not have a prefix, only your user ID is used.

If you enter a fully qualified data set name SuperC uses it as specified. Otherwise, SuperC only appends your TSO prefix to the front of the data set name specified. If you run with TSO PROFILE NOPREFIX, SuperC uses the name as you entered it, which can result in an attempt to catalog the name in the master catalog.

If you enter the name of a data set that already exists, the contents of that data set are replaced by the new update output.

If you enter the name of a data set that does not exist, SuperC allocates it for you. The data set is allocated as a sequential data set unless you enter a member name after it, in which case it is allocated as a partitioned data set.

Note: For the UPDMVS8, UPDCMS8, UPDSEQ0, and UPDPDEL process options, the update data set contains valid data but only after a successful compare when differences are detected. The data set is always empty after a comparison that shows the data sets or members being compared have no differences.

Listing Type

The type of listing you want SuperC to create when it compares the data sets. This is a required field, so you must choose one of the listing types shown here. See Appendix B, "SuperC listings" for sample listings.

DELTA Lists the differences between the source data sets, followed by the overall summary.

CHNG Lists the differences between the source data sets, plus up to 10 matching lines before and after the differences. This listing is a variation of the DELTA listing; the matching lines before and after help you recognize changed areas of the source data sets.

LONG Lists all the new data set source lines, plus old data set deleted lines. Both inserted and deleted lines are flagged.

OVSUM Lists only the overall summary of the comparison. However, a PDS comparison generates an individual summary line for each PDS member.

NOLIST Produces no listing output. In foreground mode, only a message is returned to show the outcome of the compare.

Listing DS Name

The name of the list data set to which SuperC writes the results of the comparison. However, if you enter NOLIST in the Listing Type field, SuperC does not create an output listing, so this name is ignored. Also, if you chose batch mode, this field does not appear on the panel. The SuperC Utility - Submit Batch Jobs panel is used instead.

If you leave this field blank, SuperC allocates a list data set, using default data set attributes and this data set name:

prefix.*userid*.SUPERC.LIST

where *prefix* is your TSO prefix and *userid* is your user ID. If your prefix and user ID are identical, only your prefix is used. Also, if you do not have a prefix, only your user ID is used.

If you enter a fully qualified data set name SuperC uses it as specified. Otherwise, SuperC only appends your TSO prefix to the front of the data set name specified. If you run with TSO PROFILE NOPREFIX, SuperC uses the name as you entered it, which can result in an attempt to catalog the name in the master catalog.

If you enter the name of a data set that already exists, the contents of that data set are replaced by the new output listing. However, if the data set is sequential, you can add this listing to the data set instead of replacing it by including the APNDLST process option in your profile data set.

If you enter the name of a data set that does not exist, SuperC allocates it for you. The data set is allocated as a sequential data set unless you enter a member name after it, in which case it is allocated as a partitioned data set.

Sequence Numbers
A value that tells SuperC whether to exclude sequence number fields from its comparison of your data sets. This field is not displayed if the compare type is FILE or BYTE. You can choose one of these:

blank Exclude Sequence Number fields from the comparison if the data set is F 80 or V 255 and the compare type is `Line`

Otherwise, treat as data.

SEQ Exclude Sequence Number fields from the comparison. Sequence numbers are assumed in columns 73-80 in F 80 and in columns 1-8 in V 255 data sets.

NOSEQ Treat F 80/V 255 standard sequence number columns as data.

COBOL Ignore columns 1-6 in F 80 data sets. Data in columns 1-6 is assumed to be sequence numbers.

SuperC member lists

The panel shown in Figure 126 on page 209 is displayed after you specify the old data set name, but only if all these statements are true:

- The new data set is partitioned.
- The Member field, shown on the SuperC Utility panel (see Figure 124 on page 203), or the PDS Member List field, shown on the SuperCE Utility panel (see Figure 129 on page 213) was left blank or a pattern was used, and Bypass Selection List was not selected. For more information on Displaying Member Lists, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.
- The profile data set or statements data set being used does not contain any SELECT process statements.

```
  Menu  Functions  Utilities  Help
 ------------------------------------------------------------------------------
        COMPARE    USERID.COPYBOOK                          Row 00001 of 00027

Enter END command to process selections or CANCEL to leave the member list.
Enter Old member(Oldmem) name if it is different from New member(Newmem) name.

  Newmem   Oldmem           Size    Created           Changed            ID
. BIGCHAR                      4   2001/06/29   2002/02/25 10:42:27    USERID
. BIGKSDS                      3   2001/08/10   2001/08/10 13:15:59    USERID
. CONVT1                      24   2001/06/18   2001/06/18 16:04:26    USERID
. COPYCONC                    12   2001/07/05   2001/07/05 17:33:41    USERID
. COPYMM                       2   2001/06/11   2001/06/11 10:57:01    USERID
. COPY01                       9   2001/02/24   2001/06/13 16:09:28    USERID
. COPY0102                    15   2000/05/11   2001/06/11 11:08:49    USERID
. COPY02                       7   2001/02/24   2001/02/24 17:09:50    USERID
. DITTST1                     27   2001/06/13   2001/06/13 10:38:16    USERID
. FLMLDATE                   443   2001/12/12   2001/12/12 12:41:44    USERID
. FLMUDU                     415   2001/12/10   2001/12/10 20:44:55    USERID
. FMNCCPY1                    35   2000/10/18   2002/09/10 17:18:42    USERID
. FMNCCPY2                    35   2000/10/18   2002/09/10 17:19:11    USERID
Command ===> ____________________________________________ Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 126. SuperC member list panel (ISRSSML)

The members displayed in this list are members in the new data set. If the OLDMEM column is blank, SuperC assumes each member in the new data set is to be compared with a member of the same name in the old data set.

If you enter a member name in the OLDMEM column, SuperC compares this member to the one listed beside it in the NEWMEM column.

To compare your selections, enter the END command. If you have not selected any members, ISPF returns you to the previous panel.

To cancel your selections, enter either:

- The RESET command to remove all unprocessed selections without ending the member list display
- The CANCEL command to end the member list display without processing selections that are still on the screen.

Note: Both the jump function (=) and the RETURN command cause an implied cancellation of selections before they are carried out.

For more information about member lists, see the Using Member Selection Lists section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

Submitting a SuperC job in batch mode

If you selected Batch Mode (2) on the SuperC Utility panel, the panel shown in Figure 127 on page 210 is displayed before the job is submitted. This panel allows you to specify one of these:

- The SYSOUT class, which determines the printer to which your job is sent and the format used for the printed output.
- The name of a listing data set.

- Output data definitions that you can use to give the printer additional instructions, such as an output destination that is not defined by a SYSOUT class.

```
                      SuperC Utility - Submit Batch jobs
                                                                More:     +
Press ENTER to continue submit

Enter "/" to select option                  Generate Output Type:
/  Edit JCL before user submit              1  1. SYSOUT Class
                                              2. Data Set Name
                                              3. //OUTDD DD
SYSOUT Class . . . . A

Data Set Name  . . . _____________________________________________________

//OUTDD DD . . . . . _____________________________________________________
// . . . . . . . . . _____________________________________________________
                     LRECL for the Listing Output will be 133

  Job statement information: (Required - Enter/Verify JOB control statement)

===> ____________________________________________________________________
===> ____________________________________________________________________
===> ____________________________________________________________________
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 127. SuperC Utility - Submit Batch Jobs panel (ISRSCSUB)

The “Job statement information” field is explained in the Job Statement Information section of the “ISPF Libraries and Data Sets chapter” of the *z/OS ISPF User’s Guide Vol I*. The other fields on the panel shown in Figure 127 are:

SYSOUT class

A system output classification defined by your installation, which defines certain print characteristics, such as the printer and the format that is used to produce the output. You can enter any valid SYSOUT parameters. This field is required if you leave the Option field blank.

If you enter either option 1 or option 2, the “SYSOUT class” field is ignored. However, for option 2, you can include the SYSOUT= operand in an OUTDD DD field.

Data Set Name

The name of the listing data set that you want ISPF to store your compare results in. This data set can be either partitioned or sequential.

The Data Set Name field is required if you use option 1 on this panel. This field serves the same purpose as the Listing DS Name field, which is used when running the SuperC utility in foreground mode.

The logical record length (LRECL) of the listing data set is displayed under the blank OUTDD lines on the SuperC Utility - Submit Batch Jobs panel. SuperC creates listings with one of four LRECLs:

132 Standard listing for the NOPRTCC process option; printer control characters are omitted.

133 Standard listing.

202 Wide listing for the NOPRTCC process option; printer control characters are omitted.

203 Wide listing.

If you specify an existing sequential data set with an incorrect LRECL, SuperC overrides the data set specifications. This applies to any listing and update data sets in both foreground and batch.

A separate operation, such as using the Hardcopy utility (option 3.6), is needed to print the listing data set.

If you leave the Option field blank or enter option 2, the Data Set Name field is ignored. Therefore, to specify an output data set in either of these two situations, you must include the DSN= operand in an OUTDD DD field.

Specifying Existing Data Sets

These rules apply when specifying the name of an existing data set:

- When you submit JCL for processing, the output listing produced by that JCL usually replaces the contents of the specified data set, if any exist. Therefore, be careful when specifying the name of an existing data set.

  You can keep a history of changes by using the APNDLST compare option when you run the comparison. This compare option adds the new output listing to the contents of the specified sequential data set instead of replacing it.

  Note: Using the APNDLST process option with a packed output listing file may cause unpredictable results in the output listing file.
- Use standard TSO data set naming conventions.

Specifying Nonexistent Data Sets

These rules apply when specifying the name of a data set that does not exist:

- If you include a member name in the data set specification, ISPF allocates a partitioned data set with suitable attributes for the listing.
- If you do not specify a member name, ISPF allocates a sequential data set.

//OUTDD DD

Output data definitions that are used to specify additional printer instructions in job control language (JCL). This field is required if you use this panel. Otherwise, it is ignored.

The OUTDD DD fields are provided so you can pass to your printer all the JCL needed to format special types of output that may not be supported by your installation's SYSOUT class definitions. The example shown in Figure 127 on page 210 specifies a wide format for printing on 14 3/4-inch forms.

The "SYSOUT class" and Data Set Name fields are ignored. If you need to specify this information, be sure to include it in your OUTDD DD job card. If you specify a data set name in your OUTDD DD job card, the output data set is printed and kept. Otherwise, it is printed and deleted. Here are some examples:

- To specify a SYSOUT class, enter:

  ```
  //OUTDD DD SYSOUT=X
  ```

where X is the SYSOUT class, such as A, B, or C.

- To specify a data set name, enter:

```
//OUTDD  DD  DSN=fully.qualified.name
//           DISP=XXXXX...
```

where XXXXX... is one of these:

– For an old data set:

```
OLD
```

– For a new sequential data set:

```
(NEW,CATLG),SPACE=(3325,(50,100),RLSE),UNIT=SYSDA
```

– For a new partitioned data set

```
(NEW,CATLG),SPACE=(3325,(50,100,25)),UNIT=SYSDA
```

– For a sequential data set that will be modified by, instead of replaced by, the comparison results:

```
MOD
```

Note: These three fields are independent of one another. Also, none of them requires you to provide an OUTDD card in the "Job statement information" field.

Using the NOLIST listing type in batch mode

If you enter the NOLIST listing type and choose batch mode, the options on the SuperC Utility - Submit Batch Jobs panel shown in Figure 127 on page 210 are not valid because no listing is produced. Therefore, an alternate panel is displayed, which blanks out the fields that are not valid but still allows you to submit job statement JCL. This panel is shown in Figure 128.

```
                              Batch Submit - Nolist

Press ENTER to continue submit job or END to Cancel


Enter "/" to select option
/  Edit JCL before user submit


  NOLIST listing type was specified.  There will be no output generated.


  Job statement information: (Required - Enter/Verify JOB control statement)

===> ____________________________________________________________________________
===> ____________________________________________________________________________
===> ____________________________________________________________________________
===> ____________________________________________________________________________



Command ===> ______________________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 128. SuperC Utility - submit batch jobs panel using NOLIST (ISRSCSB1)

When this panel is displayed, you can either:

- Type the job statement JCL and press Enter to submit the job
- Enter the END command to cancel the job.

SuperCE utility (option 3.13)

The SuperCE utility (option 3.13) is a dialog that uses the SuperC program to compare data sets of unlimited size and record length at the file, line, word, or byte level. It is appropriate if you need more flexibility than the standard SuperC utility (option 3.12) provides.

Note: For an introduction to the SuperC and SuperCE utilities (options 3.12 and 3.13), see Appendix A, "SuperC reference," on page 439.

The panel shown in Figure 129 is the first panel of the SuperCE utility. It requires only the names of the input data sets, which are entered using standard TSO naming conventions, such as:

```
New DS Name  . . . . 'USERID.TEST2.SCRIPT'
```

Note: In this context, a *new* data set is an updated version of a previously created data set, such as a data set in your private library that has not yet been promoted.

```
  Menu  Utilities  Options  Help
 ------------------------------------------------------------------------------
                                SuperCE Utility

 New DS Name  . . . ____________________________________________________________
 Old DS Name  . . . ____________________________________________________________
 PDS Member List    ________ (blank/pattern - member list, * - compare all)
    (Leave New/Old DSN "blank" for concatenated-uncataloged-password panel)
    Compare Type              Listing Type              Display Output
    2  1. File                2  1. OVSUM               1  1. Yes
       2. Line                   2. Delta                  2. No
       3. Word                   3. CHNG                   3. Cond
       4. Byte                   4. Long                   4. UPD
                                 5. Nolist
 Listing DSN  . . . . SUPERC.LIST ______________________________________________
 Process Options  . . ________________________________________
                      ________________________________________
 Statements Dsn . . . ______________________________________________________________
 Update DSN . . . . . ______________________________________________________________

 Enter "/" to select option      Execution Mode          Output Mode
 _  Bypass selection list        1  1. Foreground        1  1. View
                                    2. Batch               2. Browse
 Command ===> ______________________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 129. SuperCE Utility panel (ISRSEPRI)

SuperCE Utility panel action bar

The SuperCE Utility panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Options The Options pull-down offers you these choices:

1 Edit Statements
2 Process Options
3 Profiles and Defaults

Help The Help pull-down provides general information about SuperCE topics, including how to specify the input data sets and options.

SuperCE Utility panel fields

A default compare type, listing type, listing data set name, and Browse option are provided if you choose not to specify your own. The fields on the SuperCE Utility panel are:

New DS Name and Old DS Name
Specify the name of a sequential data set, PDS, or membered PDS. Use standard TSO naming conventions, including quotes for fully qualified names. Leave either or both of these fields blank to display a panel on which you can specify concatenated, uncataloged, and password-protected data sets. These panels are shown in Figure 130 on page 218 (foreground compare) and Figure 131 on page 219 (batch compare).

PDS Member List
Leave this field blank to display a member selection list for the new data set. Otherwise, enter either a pattern or an asterisk (*). See "SuperC member lists" on page 208 for more information.

pattern Entering a pattern causes ISPF to display a list of the members in the new data set that match the pattern, unless Bypass Selection List has been specified. For more information about using patterns, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*. For example:

```
PDS Member List  . . ISR*
```

***** Entering an asterisk causes all the members in the new data set to be compared to any like-named members in the old data set. A member list is not displayed. For example:

```
PDS Member List  . . *
```

Members in either data set not having like-named members in the other data set are not compared, but are listed in the output list data set.

When entire data sets are compared by using an asterisk for a member name pattern, each real member that appears in both the old and new data sets is compared once. Alias entries are processed but only to determine if they have matching alias and/or real entries.

Note: You can also use SELECT process statements in the statements data set to specify an optional set of PDS members to be searched. However, the SELECT statement turns off the PDS member list function.

Compare Type
The type of comparison you want SuperC to perform. Choose one of these:

File Compares source data sets for differences, but does not show what the differences are. This is the simplest and fastest method with the least amount of processing overhead. For this compare type,

SuperC prepares summary information only and causes all listing types to produce the same output, except NOLIST, which does not produce any output listing. A message is returned to notify you of the compare results.

Line Compares source data sets for line differences. Reformatted lines (that is, lines with blanks inserted or deleted) are automatically detected for lines ≤ 256 characters. This compare type is the default. It is most useful for comparisons of program source code because it is record-oriented and points out inserted or deleted lines of code. Lines can be of unlimited size.

Word Compares source data sets for word differences. In this context, a *word* is a group of characters that begins and ends with a blank or other line delimiter. If you use the XWDCMP process option, all non-alphanumeric characters are considered to be delimiters. Also, a word cannot be longer than 256 characters.

The Word compare type is most useful for comparing text data sets. If two data sets contain the same words in the same order, SuperC considers them to be identical, even if those words are not on the same lines.

Byte Compares source data sets for byte differences. The output listing data set consists of a hexadecimal printout with character equivalents listed on the right. A BYTE compare with a LONG listing of a data set against itself results in a hexadecimal dump of that data set. This compare type is most useful for comparing machine readable data.

Listing Type
The type of listing you want SuperC to create when it compares the data sets. Listing Type is not a required field in SuperCE. If you do not specify a listing type, the default is DELTA. See the topic about Listing Formats in the *z/OS ISPF User's Guide Vol I* for sample listings.

OVSUM Lists only the general summary of the comparison. However, a PDS comparison generates an individual summary line for each PDS member.

Delta Lists the differences between the source data sets, followed by the general summary.

CHNG Lists the differences between the source data sets, plus up to 10 matching lines before and after the differences. This listing is a variation of the DELTA listing; the matching lines before and after help you recognize changed areas of the source data sets.

Long Lists all the new data set source lines, plus old data set deleted lines. Both inserted and deleted lines are flagged.

Nolist Produces no listing output. In foreground mode, a message is returned to show the outcome of the comparison.

Listing Dsn
The name of the list data set to which SuperC writes the results of the comparison. However, if you enter NOLIST in the Listing Type field, SuperC does not create an output listing, so this name is ignored.

If you leave this field blank, SuperC allocates a list data set, using default data set attributes and this data set name:

prefix.*userid*.SUPERC.LIST

where *prefix* is your TSO prefix and *userid* is your user ID. If your prefix and user ID are identical, only your prefix is used. Also, if you do not have a prefix, only your user ID is used.

If you enter a fully qualified data set name SuperC uses it as specified. Otherwise, SuperC only appends your TSO prefix to the front of the data set name specified. If you run with TSO PROFILE NOPREFIX, SuperC uses the name as you entered it, which can result in an attempt to catalog the name in the master catalog.

If you enter the name of a data set that already exists, the contents of that data set are replaced by the new output listing. However, if the data set is sequential, you can add this listing to the data set instead of replacing it by using the APNDLST process option.

If you enter the name of a data set that does not exist, SuperC allocates it for you. The data set is allocated as a sequential data set unless you enter a member name after it, in which case it is allocated as a member of a partitioned data set.

Process Options
Keywords that tell SuperC how to process the compare operation. You can type these keywords in the Process Options fields or select them from a panel. See the Process Options selection in "Process options - select process options" on page 219 for a table of keywords.

Statements Dsn
The name of the data set that contains your process statements. All statements data sets must be fixed block with 80-byte records (FB 80). See the Edit Statements selection in "Process options - select process options" on page 219 for more information.

Update Dsn
Tells SuperC the name of the data set that will contain column-oriented results of the comparison. This data set is normally used as input to post processing programs and can be specified besides the normal listing data set.

If you leave this field blank and use an update (UPD*xxxx*) option, SuperC uses this default name:

prefix.*userid*.SUPERC.UPDATE

where *prefix* is your TSO prefix and *userid* is your user ID. If your prefix and user ID are identical, only your prefix is used. Also, if you do not have a prefix, only your user ID is used.

If you enter a fully qualified data set name SuperC uses it as specified. Otherwise, SuperC only appends your TSO prefix to the front of the data set name specified. If you run with TSO PROFILE NOPREFIX, SuperC uses the name as you entered it, which can result in an attempt to catalog the name in the master catalog.

If you enter the name of a data set that already exists, the contents of that data set are replaced by the new update output. However, if the data set is sequential, you can add this listing to the data set instead of replacing it by using the APNDUPD process option.

If you enter the name of a data set that does not exist, SuperC allocates it for you. The data set is allocated as a sequential data set unless you enter a member name after it, in which case it is allocated as a partitioned data set.

Note: For the UPDMVS8, UPDCMS8, UPDSEQ0, and UPDPDEL process options, the update data set contains valid data, but only after a successful compare when differences are detected. The data set is always empty after a comparison that shows the data sets or members being compared have no differences.

Display Output
Tells ISPF whether you want to display the output listing in Browse mode. Enter one of these:

Note: The NOLIST listing type overrides Yes, No, and Cond.

Yes Call Browse to display the listing data set after processing the comparison. This is the default.

No Do not call Browse to display the SuperC listing data set.

Cond Do not call Browse unless SuperC finds differences between the data sets.

UPD Browse the update data set instead of the list data set. This parameter is not valid unless you create an update data set by using one or more of the SuperC process options that begin with UPD (UPD*xxxx*).

Bypass Selection List
When a member pattern is entered in the PDS Member List field, selecting this field causes SuperC to process all members matching that pattern without displaying a member selection list. Leaving this field blank causes the member list to be displayed.

Output Mode
The output mode for displaying the listing file. Choose one of these:

1 **View**. This enables the listing file to be displayed in *view* mode. All View functions are enabled in this mode.

2 **Browse**. This enables the listing file to be displayed in the *browse* mode. All Browse functions are enabled in this mode.

SuperCE utility options

These topics describe the Execution Mode options shown on the SuperCE Utility panel:

- “Foreground compare data sets”
- “Batch submit batch data set compare” on page 218
- “Process options - select process options” on page 219
- “Edit statements - edit statements data set” on page 220
- “Profiles and defaults - activate profiles and defaults” on page 221

Foreground compare data sets

If you choose **Foreground**, SuperC processes the data sets in foreground mode, so you can browse the results of the compare. This choice locks your keyboard until SuperC processing is complete.

The panel shown in Figure 130 is displayed if you leave the Option field and the New DS Name or Old DS Name field blank on the SuperCE Utility panel.

```
                    SuperCE - Concatenation Foreground Entry

                              "New" Concatenation
   DS1 . . . ____________________________________________________
   DS2 . . . ____________________________________________________
   DS3 . . . ____________________________________________________
   DS4 . . . ____________________________________________________

                Other "New" Partitioned, Sequential or VSAM Data Set
Data Set Name . . . ____________________________________________________
Volume Serial . . . ______    (If not cataloged)
Password  . . . . .           (Password allowed only in foreground mode)

                              "Old" Concatenation
   DS1 . . . ____________________________________________________
   DS2 . . . ____________________________________________________
   DS3 . . . ____________________________________________________
   DS4 . . . ____________________________________________________

                Other "Old" Partitioned, Sequential or VSAM Data Set
Data Set Name . . . ____________________________________________________
Volume Serial . . . ______    (If not cataloged)
Password  . . . . .           (Password allowed only in foreground mode)
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 130. SuperCE - concatenation interactive entry panel (ISRSECAT)

For fields DS1 through DS4, both new and old, use normal TSO naming conventions. You can specify a series of concatenated data sets, an uncataloged or password-protected data set, or a cataloged data set.

Up to four data sets can be concatenated for both the new and old input data sets. Make sure the data sets are concatenated in the proper sequence, as follows:

1. If two or more sequential data sets are concatenated as one input data set, the data set attributes, such as block size, must be identical.
2. PDS concatenations must have the data set with the largest block size as the first in any concatenation.
3. The SuperCE dialog uses only the first occurrence of a member in the concatenated series of PDSs as source input for a compare. Any other occurrences of the member are ignored.

Other partitioned or sequential data sets, volume serials, and data set passwords are specified as on any other data entry panel. See the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for more information.

Note: The Password fields apply only to the other partitioned or sequential data sets. TSO prompts you if any concatenated data sets are password-protected. The Password field is only enabled in foreground mode.

Batch submit batch data set compare

Option B causes SuperC to process the data sets in batch mode. This choice frees the keyboard, allowing you to continue using ISPF while waiting for SuperC to

compare the data sets. The output listing is sent to the destination specified on the SuperC Utility - Submit Batch Jobs panel (Figure 127 on page 210).

The panel shown in Figure 131 is displayed if you select option B and leave the New DS Name or Old DS Name field blank on the SuperCE Utility panel. You can concatenate up to four data sets that have like attributes. For example, all must be either sequential or partitioned.

```
                    SuperCE - Concatenation Batch Entry

                              "New" Concatenation
   DS1 . . . ____________________________________________________
   DS2 . . . ____________________________________________________
   DS3 . . . ____________________________________________________
   DS4 . . . ____________________________________________________

                Other "New" Partitioned, Sequential or VSAM Data Set
Data Set Name . . . ____________________________________________________
Volume Serial . . . ______     (If not cataloged)
Password  . . . . .            (Password allowed only in foreground mode)

                              "Old" Concatenation
   DS1 . . . ____________________________________________________
   DS2 . . . ____________________________________________________
   DS3 . . . ____________________________________________________
   DS4 . . . ____________________________________________________

                Other "Old" Partitioned, Sequential or VSAM Data Set
Data Set Name . . . ____________________________________________________
Volume Serial . . . ______     (If not cataloged)
Password  . . . . .            (Password allowed only in foreground mode)
Command ===> ________________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 131. SuperCE - Concatenation Batch Entry panel (ISRSECAT)

This panel is the same as the panel shown in Figure 130 on page 218, except the Password field is omitted. If your data sets are password protected, compare the data sets in foreground mode by leaving the Option field on the SuperCE Utility panel blank.

Printing a SuperCE listing in batch mode: If you selected option B on the SuperCE Utility panel, the panel shown in Figure 127 on page 210 is displayed before the job is submitted. This panel allows you to determine whether to print your SuperC listing or write it to a list data set.

Process options - select process options

The compare type that you select determines the available process options, which are listed in Table 15 on page 220.

Table 15. SuperCE process options

Line Compare:

```
ALLMEMS ANYC    APNDLST APNDUPD CKPACKL CNPML   COBOL   COVSUM  DLMDUP  DLREFM
DPACMT  DPADCMT DPBLKCL DPCBCMT DPCPCMT DPFTCMT DPMACMT DPPLCMT DPPSCMT
FMVLNS  GWCBL   LOCS    LONGLN  MIXED   NARROW  NOPRTCC NOSEQ   NOSUMS
REFMOVR SEQ     UPDCMS8 UPDCNTL UPDLDEL UPDMVS8 UPDPDEL UPDREV  UPDREV2
UPDSEQ0 UPDSUMO WIDE    Y2DTONLY
```

Word Compare:

```
ALLMEMS ANYC    APNDLST APNDUPD CKPACKL COBOL   COVSUM
DPACMT  DPADCMT DPBLKCL DPCBCMT DPCPCMT DPFTCMT DPMACMT DPPLCMT DPPSCMT
GWCBL   LOCS    MIXED   NOPRTCC NOSEQ   NOSUMS  SEQ
UPDCNTL UPDREV  UPDREV2 UPDSUMO XWDCMP
```

Byte Compare:

```
ALLMEMS APNDLST APNDUPD COVSUM  LOCS
NOPRTCC NOSUMS  UPDCNTL UPDSUMO
```

File Compare:

```
ALLMEMS APNDLST COVSUM  FMSTOP
LMCSFC  LOCS    NOPRTCC
```

To select one or more SuperCE process options, perform either of these actions:

- Type any nonblank character to the left of the process options you want to select. If `move +` or `move -+` is shown, use the Backward and Forward keys to move through the panel. Press Enter when you have finished. This causes the options you chose to be displayed in the Process Options fields on the SuperCE Utility panel. If you select two options that cannot be chosen together, or if you enter an option name incorrectly, an error message is displayed.
- Use the CANCEL command to return to the SuperCE Utility panel without processing selections.

SuperC process options can affect how the input data is processed, and determine the format and content of the output listing data set. They can also help you save processing time by avoiding comments and blank lines. A separate group of options, called update data set options (UPD*xxxx*), allow you to create update data sets, examples of which are shown in "Update data set control output examples" on page 524.

All these options can be chosen from the XXXX Compare Process Options panels, where XXXX is the compare type (FILE, LINE, WORD, or BYTE) that you are using. The only exception is that the DP*xxxx* (do not process) options are not available from a selection panel when you are conducting a WORD comparison. However, you can type any of them in the Process Options field on the SuperCE Utility panel. Errors caused by mistyping process options are detected when you call the SuperCE utility.

For definitions of the SuperC process options, see "SuperC compare process options" on page 443.

Edit statements - edit statements data set

A statements data set consists of process statements that contain instructions for the SuperC program. They are similar to the process options, but are composed of a keyword and one or more operands. See "Process options - select process options" on page 219 for information about SuperCE process options.

When you select the Edit Statements option from the SuperCE Utility Options pull-down menu, the SuperCE utility displays the statements data set you specified in the Statements Dsn field. This data set is always displayed in Edit mode, allowing you to add, change, or delete SuperC process statements as needed. Only one process statement can appear on each line of the statements data set.

The size of the Edit window depends on the number of lines your terminal can display. The sample panel shown in Figure 132 shows how the Edit window appears on a 24-line display. Examples of some common process statements are listed below the Edit window so you can easily compose the proper input line.

```
           USERID.SUPERC.STMTS                              Columns 00001 00072

   Enter or change Process Statements in the EDIT window below:
****** **************************** Top of Data ******************************
''''''
''''''
''''''
''''''
''''''
****** **************************** Bottom of Data ***************************


   Examples                    Explanation
CMPCOLM 5:60  75:90         Compare using two column compare ranges
LSTCOLM 25:90               List columns 25:90 from input
DPLINE 'PAGE '              Exclude line if "PAGE " found anywhere on line
SELECT  MEM1,NMEM2:OMEM2    Compare MEM1 with MEM1 and NMEM2 with OMEM2
CMPLINE NTOP 'MACRO'        Start comparing after string found in new DSN
LNCT    66                  Set lines per page to 66
                       - - - - -
Others: CHNGV    CMPBOFS CMPCOLMN CMPCOLMO CMPSECT DPLINEC NCHGT
Command ===> ____________________________________________________  Scroll ===> PAGE
 F1=Help      F2=Split     F3=Exit      F5=Rfind     F6=Rchange   F7=Up
 F8=Down      F9=Swap     F10=Left     F11=Right    F12=Cancel
```

Figure 132. SuperC process statements panel (ISRSEPRS)

The SuperC program validates process statements at run time. Invalid process statements are not used and are noted at the bottom of the listing. Unless a higher return code is required by some other condition, a return code of 4 is generated.

See “SuperC compare process statements” on page 453 for process statement syntax, definitions, and examples.

Profiles and defaults - activate profiles and defaults

A SuperC profile is a data set that can contain a compare type, a listing type, a Browse setting, and various combinations of process options and process statements that you select.

SuperC profiles are useful for a wide range of users. Beginners can use profiles created by others as a simple method of running SuperC. Experienced SuperC users can create profiles for the groups of options they use often so that they do not have to remember individual process options and statements. Also, profiles give system programmers a mechanism for setting up complex compare tools that others can simply call by profile name.

Some other characteristics of profiles are:

- A profile can be either a sequential data set or a member of a PDS.
- Data set names are not represented in a profile.
- Profiles can be created only with the SuperCE utility (option 3.13). However, once they are created, they can be used in the standard SuperC utility (option 3.12).
- To change a profile, activate it and make the necessary changes to the information in the fields on the SuperCE Utility panel. Then select option C and create a profile, entering in the Activate/Create Profile DS Name field the name of the profile data set that you want to modify.
- You can modify the SuperC default settings by selecting the Defaults option on the Profile Manager screen. See Figure 135 on page 225 for an example of the SuperC - Defaults panel.
- You can display the contents of a profile data set using View, Browse, or Edit. Figure 133 shows a Browse display of a profile data set.

```
  Menu  Utilities  Compilers  Help
 ___________________________________________________________________________
            USERID.TESTPROF                          Line 00000000 Col 001 080
******************************** Top of Data ********************************
.* PROF PREFIX CTYP=LINE,LTYP=DELTA ,BRW=YES
.* PROF PREFIX PROC1=                                      * MARGIN*
.* PROF PREFIX PROC2=                                      * MARGIN*
****************************** Bottom of Data ******************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 133. Browse a SuperCE profile

Selecting option A on the SuperCE Utility panel displays the panel shown in Figure 134. This panel is used to activate and create profiles.

```
                          SUPERCE - Profile Manager

A  Activate    Reads the specified input profile data set:
               1.  Establishes the process and compare options from the
                   profile prefix lines.
               2.  Establishes the profile as the process statement data set
                   if any process statements are detected.

C  Create      Creates an output profile data set:
               1.  Combines process and compare options from the Primary Panel
                   and any process statements from the Statements Data Set:

               2.  Rewrites the profile data set (if the data set exists) or
                   allocates a new data set before generating the profile.

D  Defaults    Presents panel for modifying SuperC defaults.

Activate/Create
Profile DS Name . . . ____________________________________________________



Option ===> ____________________________________________________________
 F1=Help    F2=Split   F3=Exit    F9=Swap   F12=Cancel
```

Figure 134. SuperCE - Profile Manager panel (ISRSEPMG)

The only field on this panel is:

Activate/Create Profile DS Name

The name of the profile data set that you want to either activate or create. This field is required.

If you choose option A (Activate), SuperCE copies the compare type, listing type, Browse setting, and any process options this data set contains. If the profile also contains process statements, SuperCE displays the name of the profile data set in the Statements Dsn field on the SuperCE Utility panel.

If you choose option C (Create), SuperCE copies the information that is saved into one output data set or member.

These topics describe the options shown at the top of the SuperCE - Profile Manager panel:

- "A — activate"
- "C — create"
- "D — defaults" on page 224

A — activate: Option A (Activate) restores the contents of the profile data set specified in the Activate/Create Profile DS Name field. This data set must be cataloged. When you press Enter, information that was stored in the profile data set when it was created is displayed in the corresponding fields on the SuperCE Utility panel. For example, process options stored in the profile appear in the Process Options fields. At this point, you can make additional changes or choose another option.

C — create: Option C (Create) causes SuperCE to copy data entered on the SuperCE Utility panel and place it in the profile data set specified in the Activate/Create Profile DS Name field. Be sure the correct information is displayed on that panel and that the statements data set, if you specify one, contains the correct process statements before you create the profile.

If the profile data set that you specify does not already exist, SuperCE allocates it for you. Data stored in the profile data set can include:

- These values taken from the fields on the SuperCE Utility panel. The abbreviations in parentheses show how these values are identified in a profile data set:
  - Compare type (CTYP)
  - Listing type (LTYP)
  - Browse setting (BRW)
  - Process options (PROC1 and PROC2).
- Process statements copied from the statements data set that was specified in the Statements Dsn field. This data set name is displayed and highlighted on the SuperCE - Profile Manager panel. For example, the sample panel shown in Figure 134 on page 223 displays the name SUPERC.STMTS.

  If you leave the Statements Dsn field blank, the data set name and the words preceding it are not displayed on the SuperCE - Profile Manager panel and SuperCE does not include any process statements in your profile. See these topics about process options and process statements, respectively:
  - "Process options - select process options" on page 219
  - "Edit statements - edit statements data set" on page 220

D — defaults: Option D (Defaults) brings up an additional panel, shown in Figure 135 on page 225, that allows you to:

- Specify SuperC output data set default allocation parameters

  The first extent and secondary space values are used whenever Options 3.12, 3.13, or 3.14 create a new output data set such as a listing or statements data set. If you specify a new data set with a member name, the directory space value is used to create a PDS. If you blank out any of the values, SuperC will supply defaults.

  Space values are applicable only if you select "Invoke SuperC via PROGRAM interface".

  Note: New data set allocation block size parameters are controlled by the PDF Configuration Table. See *z/OS ISPF Planning and Customizing* for details.
- Specify your own Statements data set initial edit macro name
- Enable or disable a new high performance program interface to SuperC. If you select "Invoke SuperC via PROGRAM interface", ISPF invokes SuperC directly. Otherwise, ISPF invokes SuperC via a CLIST named ISRSFORG (ISRSSRCH for Search-For). The CLIST interface may be useful if you need to customize the allocations or wish to post-process the result. The PROGRAM interface is more efficient and is the default.

```
                              SUPERC - Defaults

        Verify entries below. End or Enter to exit.


New List data set allocation in blocks:
1st Extent . . 50    Secondary . . 100   Directory . . 5

New Update data set allocation in blocks:
1st Extent . . 15    Secondary . . 30    Directory . . 5

New Profile data set allocation in blocks:
1st Extent . . 5     Secondary . . 5     Directory . . 5

New Statements data set allocation in blocks:
1st Extent . . 5     Secondary . . 5     Directory . . 5

Statements data set initial edit macro name . . !ISRSMAC

Enter "/" to select option
/  Invoke SuperC via PROGRAM interface

Command ===> _____________________________________________________________
 F1=Help    F2=Split   F3=Exit    F9=Swap   F12=Cancel
```

Figure 135. SuperC - Defaults panel (ISRSDFLT)

Search-For utility (option 3.14)

Note: For an introduction to the Search-For and Extended Search-For utilities (options 3.14 and 3.15), see Appendix A, “SuperC reference,” on page 439.

The Search-For utility (option 3.14) is a dialog that uses the SuperC program to search your data sets or PDS members for one or more character strings. The Search-For Utility panel, shown in Figure 136 on page 226, is the first panel of the Search-For utility. The only requirements for this panel are:

- A string to be searched for, unless you select “Specify additional search strings”
- A data set to search, along with a volume serial and password if necessary.

A default listing data set name is provided if you choose not to enter your own.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                              Search-For Utility
                                                                 More:     +
 Search String  . . ____________________________________________________

 ISPF Library:
    Project . . . ________
    Group . . . . ________ . . . ________ . . . ________ . . . ________
    Type  . . . . ________
    Member  . . . ________        (Blank or pattern for member selection list,
                                    "*" for all members)
 Other Partitioned, Sequential or VSAM Data Set:
    Data Set Name . . . ___________________________________________________
    Volume Serial . . . ______    (If not cataloged)

 Listing Data Set . . . SRCHFOR.LIST____________________________________
 Data Set Password  . .           (If Search-For data set password protected)

 Enter "/" to select option               Execution Mode        Output Mode
 _  Specify additional search strings     1  1. Foreground      1  1. View
 _  Mixed Mode                               2. Batch             2. Browse
 _  Bypass selection list
 Command ===> ___________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 136. Search-For Utility panel (ISRSFSPR)

Search-For Utility panel action bar

The Search-For Utility panel action bar choices function as follows:

Menu
For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

RefList
For information about referral lists, see the topic about Using Personal Data Set Lists and Library Lists in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help
The Help pull-down provides general information about Search-For topics, including how to specify the input data sets, search string, and options.

Search-For Utility panel fields

All the fields on this panel are explained in the Libraries and Data Sets topic in the *z/OS ISPF User's Guide Vol I*, except these:

Search String
A string to be searched for. No distinction is made between uppercase and lowercase characters. Use the Extended Search-For utility (option 3.15) to specify case-sensitive searches.

Four keywords—C, PREFIX, SUFFIX, and WORD—can help you narrow the scope of a search. See "Search-For strings and keywords" on page 228 for information about these keywords and the rules that govern search string entry.

Specify additional search strings
Select this field to have the Search-For utility search for more than one string. The Search-For utility displays the panel shown in Figure 137 on page 228, on which you can specify additional search strings. This panel precedes a member list request.

If you do not select this option, the Search-For utility searches only for the string entered in the Search String field.

Mixed Mode
Select this field to have the Search-For utility scan and parse the input data set lines for DBCS text strings.

Note: The Word, Prefix, and Suffix Search-For qualifiers have no effect on DBCS strings.

Bypass Selection List
When a member pattern is entered in the PDS Member List field or the member name portion of the data set field (such as MY.DATA.SET(*pattern*)), selecting this field causes SuperC to process all members matching that pattern without displaying a member selection list. Leaving this field blank causes the member list to be displayed.

Execution Mode
The processing mode you want to use when searching the data sets. Specify one of these:

1 **Foreground**. Searches the data sets and stores the results in the data set specified in the Listing Data Set Name field. You can browse the listing data set at the terminal.

2 **Batch**. Causes the display of the Search-For Utility - Submit Batch Jobs panel so that you can specify job card and print disposition information or edit the JCL statements. Then, Search-For submits the batch job to search the data sets. See "Submitting a Search-For job in batch mode" on page 230 for more information.

Note: You cannot specify a data set password in batch mode. If your data sets are password protected, use foreground mode.

Output Mode
The output mode you want to use when displaying the listing file. Choose one of these:

1 **View**. This enables the listing file to be displayed in *view* mode. All View functions are enabled in this mode.

2 **Browse**. This enables the listing file to be displayed in the *browse* mode. All Browse functions are enabled in this mode.

Listing Data Set
The name of the listing data set to which the SuperC program writes the results of the search. If you leave this field blank, the Search-For utility allocates a listing data set, using default data set attributes and this data set name:

prefix.*userid*.SRCHFOR.LIST

where *prefix* is your TSO prefix and *userid* is your user ID. If your prefix and user ID are identical, only your prefix is used. Also, if you do not have a prefix, only your user ID is used.

If you enter a fully qualified data set name SuperC uses it as specified. Otherwise, SuperC only appends your TSO prefix to the front of the data set name specified. If you run with TSO PROFILE NOPREFIX, SuperC uses the name as you entered it, which can result in an attempt to catalog the name in the master catalog.

If you enter the name of a data set that does not exist, the Search-For utility allocates it for you. The data set is allocated as a sequential data set unless you enter a member name after it, in which case it is allocated as a partitioned data set.

Specifying additional search strings

The panel shown in Figure 137 is displayed if you select "Specify additional search strings" on the Search-For Utility panel. You can specify:

- Additional strings to be searched for
- Optional scan-type and continuation keywords.

```
  Menu  RefList  Utilities  Help
 ___________________________________________________________________________ __
I |                        Search-For Strings                                |
 S |                   Specify 1 or more Search Strings below:                |
 I |    ==> ______________________________________________________________   |
   |    ==> ______________________________________________________________   |
   |    ==> ______________________________________________________________   |
   |    ==> ______________________________________________________________   |
   |    ==> ______________________________________________________________   |  ,
   |    ==> ______________________________________________________________   |
 O |    ==> ______________________________________________________________   |
   |    ==> ______________________________________________________________   |
   |    ==> ______________________________________________________________   |
   |    ==> ______________________________________________________________   |
 L |                                                                          |
 D |            Press ENTER to start search or END command to exit.           |
   | Command ===> ________________________________________________________   |
 E |  F1=Help      F2=Split      F3=Exit       F7=Backward   F8=Forward      |
 / |  F9=Swap     F10=Actions   F12=Cancel                                   |
 C |__________________________________________________________________________|
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 137. Additional Search Strings panel (ISRSFSST)

From this panel, pressing Enter either:

- Displays a member list, if requested
- Runs the search if no member list is needed.

Entering the END command returns you to the Search-For Utility panel.

Search-For strings and keywords

Enter the strings that you want SuperC to find. When you press Enter, SuperC looks for the strings without regard to whether they appear in uppercase or

lowercase in the original data set. If you are searching a partitioned data set concatenation, SuperC will inform you (in the CONCAT# field in the listing) in which group it first found the string. If you want SuperC to search all the groups for each member, you can use the SDUPM process option of Extended Search-For (option 3.15). If you want the search to distinguish between uppercase and lowercase, you must use Extended Search-For (option 3.15). If any of the strings are found (string-1 OR string-2 OR string-3) on the line, SuperC considers the condition met. You can restrict SuperC searches further by using one of the SuperC Search-for keywords discussed in "Using keywords."

Entering search strings

Enclose the string in single quotation marks if it contains embedded blanks or apostrophes. Two consecutive apostrophes must be entered to specify a single apostrophe within a search string.

If you need to specify a DBCS string that contains a hexadecimal '7D' (x'7D', the hexadecimal representation of a single quotation mark) as half of a DBCS pair, you must use the Enhanced SearchFor option (option 3.15) with the MIXED process option.

This example searches for the string `IT'S A LIVING`.

```
==> 'IT'S A LIVING'
```

Using keywords

These keywords can help you narrow the range of the search. If you do not use a keyword, SuperC will find the string wherever it exists, even if that happens to be in the middle of a word.

PREFIX Shows the string is preceded by a non-alphanumeric character, such as a blank space. It cannot be used on the same line with SUFFIX or WORD. For example, you can do this:

```
==> ELSE PREFIX
==> ELSE SUFFIX
```

but not this:

```
==> ELSE PREFIX SUFFIX
```

SUFFIX Shows the string is followed by a non-alphanumeric character. It cannot be used on the same line with PREFIX or WORD. See the examples under PREFIX.

WORD Shows the string is both preceded and followed by a non-alphanumeric character. It cannot be used on the same line as PREFIX or SUFFIX. See the examples under PREFIX.

C Continuation. Shows continuation of the previous line(s). Continuation lines generate additional strings, all of which must be found in the same line of an input data set.

Also, the C keyword can be entered on the same line as one of the other keywords. This example tells SuperC to find ELSE and to also find IF, but only when IF is on the same line as ELSE.

```
==> ELSE WORD
==> IF WORD C
```

Search-For member lists

A panel similar to the one shown in Figure 138 on page 230 is displayed only if:

- The search data set is partitioned.

- The Member field on the Search-For Utility panel (Figure 136 on page 226) or the PDS Member List field on the Extended Search-For Utility panel (Figure 140 on page 232) was left blank or a pattern was used and Bypass Selection List was not selected. For more information on Displaying Member Lists, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.
- For the Extended Search-For utility (option 3.15), the statements data set being used does not contain any SELECT process statements.

```
  Menu  Functions  Utilities  Help
 ------------------------------------------------------------------------------
        SEARCH      USERID.DATASET                          Row 00001 of 00026

 Enter END command to process selections or CANCEL to leave the member list.


   Name     Prompt          Size    Created           Changed            ID
 . COPY01T                    10   2002/09/06   2002/09/17 12:56:47    USERID
 . COPY01TM                   10   2002/08/26   2002/08/28 18:23:19    USERID
 . COPY0102                   17   2002/09/05   2002/09/06 09:59:12    USERID
 . DCAR                        7   2002/08/06   2002/08/06 13:59:01    USERID
 . DT1                         5   2002/08/08   2002/08/08 17:09:42    USERID
 . FMNCCPY1                   17   2002/09/12   2002/09/18 14:45:55    USERID
 . FMNCCPY2                   17   2002/09/12   2002/09/12 15:10:06    USERID
 . NEWCPPYT                   17   2002/09/05   2002/09/05 18:24:29    USERID
 . TEMP0102                   17   2002/08/28   2002/08/28 18:38:02    USERID
 . TESTMD1                    10   2002/08/29   2002/08/29 17:02:17    USERID
 . TEST0102                   17   2001/03/08   2002/09/02 15:18:53    USERID
 . TEST3                      17   2002/09/06   2002/09/06 10:04:59    USERID
 . TEST4                      17   2002/09/06   2002/09/06 11:26:50    USERID
 Command ===> _____________________________________________  Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 138. Search member list panel (ISRSSML)

To start the search, enter the END command.

To cancel your selections, enter either:

- The RESET command to remove all unprocessed selections without ending the member list display
- The CANCEL command to end the member list display without processing selections still on the screen.

Note: Both the jump function (=) and the RETURN command cause an implied cancellation of selections before they are carried out.

For more information about member lists, see the Using Member Selection Lists section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

Submitting a Search-For job in batch mode

If you selected Batch Mode (2) on the Search-For Utility panel, the panel shown in Figure 139 on page 231 is displayed before the job is submitted.

```
                    Search-For Utility - Submit Batch jobs

Press ENTER to continue submit

Enter "/" to select option                  Generate Output Type:
/  Edit JCL before user submit              1  1. SYSOUT Class
                                              2. Data Set Name
                                              3. //OUTDD DD
SYSOUT Class . . . . A

Data Set Name  . . . ____________________________________________________

//OUTDD DD . . . . . ____________________________________________________
// . . . . . . . . . ____________________________________________________
                     LRECL for the Listing Output will be 133

Job statement information: (Required - Enter/Verify JOB control statement)
===> ____________________________________________________________________
===> ____________________________________________________________________
===> ____________________________________________________________________
===> ____________________________________________________________________
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 139. Search-For Utility - Submit Batch Jobs panel (ISRSFSUB)

This panel allows you to specify one of these Generate Output types:

- The SYSOUT class, which determines the printer to which your job is sent and the format used for the printed output
- The name of a listing data set
- Output data definitions that you can use to give the printer additional instructions, such as an output destination that is not defined by a SYSOUT class.

The Job Statement information field is explained in the details about Job Statement Information in the Libraries and Data Sets topic of the *z/OS ISPF User's Guide Vol I*. The other fields on this panel, as well as the options listed at the top of the panel, are described in "Submitting a SuperC job in batch mode" on page 209.

Search-ForE utility (option 3.15)

Note: For an introduction to the Search-For and Extended Search-For utilities, see Appendix A, "SuperC reference."

If you select option 3.15, the Extended Search-For Utility panel, shown in Figure 140 on page 232, is displayed. This utility is a dialog that uses the SuperC program to search your data sets or PDS members for one or more character strings. It is appropriate if you need more flexibility than the standard Search-For utility (option 3.14) provides.

```
  Menu  Utilities  Options  Help
 ------------------------------------------------------------------------------
                         Extended Search-For Utility
                                                                   More:     +
Search DS Name  . . _____________________________________________________________
PDS Member List . . ________  (blank/pattern - member list, * - search all)

(Leave Search DSN "blank" for concatenated-uncataloged-password panel)

Enter Search Strings and Optional operands (WORD/PREFIX/SUFFIX,C)
   Caps . . ____________________________________________________________
   Caps . . ____________________________________________________________
   Caps . . ____________________________________________________________
   Asis . . ____________________________________________________________
   Asis . . ____________________________________________________________

Listing DSN . . . . SRCHFOR.LIST_____________________________________________
Process Options . . _________________________________________________________
Statements Dsn  . . _________________________________________________________

Enter "/" to select option      Execution Mode          Output Mode
Command ===> ________________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 140. Extended Search-For Utility panel (ISRSFPRI)

Search-ForE Utility panel action bar

The Search-ForE Utility panel action bar choices function as follows:

Menu
For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Options

1 Edit statements
2 Process options

Help
The Help pull-down provides general information about Extended Search-For topics, including how to specify data sets, search strings, process options and process statements.

Search-ForE Utility panel fields

The panel requires only the entry of character string(s). The fields on this panel are:

Search DS Name
Specify the name of a sequential data set, PDS, or membered PDS. Use standard TSO naming conventions, including quotes for fully qualified names. Leave this field blank to display a panel on which you can specify concatenated, uncataloged, and password-protected data sets. This panel is shown in Figure 141 on page 235.

PDS Member List

Leave this field blank to display a list of all the members in the search data set. Otherwise, enter a pattern or an asterisk (*). See "Search-For member lists" on page 229 for more information.

pattern

Entering a pattern causes ISPF to display a list of the members in the search data set that match the pattern unless Bypass Selection List was selected. See the topic about Displaying Member Lists in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for more information about using patterns. For example:

```
PDS Member List . . . ISR*
```

*

Entering an asterisk causes all the members in the search data set to be searched.

You can also use SELECT process statements in the statements data set to specify an optional set of PDS members to be searched. However, the SELECT statement turns off the PDS member list function.

CAPS

A search string that you want the Extended Search-For utility to find. This search string is converted to uppercase before the search begins and is found only if it exists in the search data set in uppercase.

The ANYC process option causes the string to be found in any case, (uppercase, lowercase, or mixed case) even if you enter the string in the CAPS field.

You can enter up to three uppercase search strings, one in each CAPS field. Here are some examples:

example 1

Either of these strings may be found in the search data set:

```
CAPS . . . . THEN
CAPS . . . . IF
```

example 2

The two strings shown must be found on the same line because of the continuation (C) keyword. `THEN` must be a complete word, while `ISR` must be the prefix of a word.

```
CAPS . . . . THEN WORD
CAPS . . . . ISR PREFIX C
```

example 3

In the next example, a hexadecimal string is specified as the search string. Use this to find unprintable characters.

```
CAPS . . . . X'7B00'
```

example 4

This example searches for the string `JOE'S CLIST`. Notice that the string is enclosed in single quotation marks and the apostrophe following Joe's name has been doubled.

```
CAPS . . . . 'JOE'S CLIST'
```

ASIS

A search string that you want the Extended Search-For utility to find. This search string is searched for as it is when you enter it in the ASIS field. Therefore, the Extended Search-For utility does not

find the string unless it exists in the data set exactly as you enter it in an ASIS field. You can enter one search string in each ASIS field.

The examples following the CAPS field definition apply to the ASIS field as well.

See "Search-For strings and keywords" on page 228 for a list of rules that determine the format required for entering search strings and for definitions of the keywords that are shown in the examples.

The SRCHFOR and SRCHFORC process statements override any strings entered in the CAPS and ASIS fields.

Listing DS Name

The name of the list data set to which the Extended Search-For utility writes the listing information. If you leave this field blank, Extended Search-For allocates a list data set, using default data set attributes and this data set name:

```
prefix.userid.SRCHFOR.LIST
```

where *prefix* is your TSO prefix and *userid* is your user ID. If your prefix and user ID are identical, only your prefix is used. Also, if you do not have a prefix, only your user ID is used.

If you enter a fully qualified data set name SuperC uses it as specified. Otherwise, SuperC only appends your TSO prefix to the front of the data set name specified. If you run with TSO PROFILE NOPREFIX, SuperC uses the name as you entered it, which can result in an attempt to catalog the name in the master catalog.

If you enter the name of a data set that already exists, the contents of that data set are replaced by the new listing output. However, if the data set is sequential, you can add this listing to the data set instead of replacing it by using the APNDLST process option.

If you enter the name of a data set that does not exist, Search-For allocates it for you. The data set is allocated as a sequential data set unless you enter a member name after it, in which case it is allocated as a partitioned data set.

Process Options

Keywords that tell SuperC how to process the search-for operation. You can type these keywords in the Process Options field or select them from a panel. See "SuperC compare process options" on page 443 for tables of keywords.

Bypass Selection List

When a member pattern is entered in the PDS Member List field, selecting this field causes SuperC to process all members matching that pattern without displaying a member selection list. Leaving this field blank causes the member list to be displayed.

Statements Dsn

The name of the data set that contains your search-for process statements, which you can create or change by using option E on the Extended Search-For Utility panel. SuperC reads these process statements before conducting the search. All statements data sets must be fixed block with 80-byte records (FB 80).

Execution Mode

Foreground

If you choose option 1, Foreground, and you leave the Search DS Name field blank, the Extended Search-For - Concatenation Data Set Entry panel, shown in Figure 141, is displayed.

```
                Extended Search-For Concatenation Foreground Entry

                              "Search" Concatenation
   DS1 . . . ____________________________________________________
   DS2 . . . ____________________________________________________
   DS3 . . . ____________________________________________________
   DS4 . . . ____________________________________________________

                       Other "Search" Partitioned, Sequential or VSAM Data Set
Data Set Name . . . ____________________________________________________
Volume Serial . . . ______     (If not cataloged)
Password  . . . . .            (Password allowed only in foreground mode)









Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 141. Extended Search-For - concatenation data set entry panel (ISRSFCON)

For fields DS1 through DS4, use normal TSO naming conventions. You can specify a series of concatenated data sets, an uncataloged or password-protected data set, or a cataloged data set name.

Up to four data sets can be concatenated. Make sure the data sets are concatenated in the proper sequence, as follows:

1. If two or more sequential data sets are concatenated as one input data set, the data set attributes, such as block size, must be identical.
2. PDS concatenations must have the data set with the largest block size as the first in any concatenation.
3. Search-For uses only the first occurrence of a member in the concatenated series of PDSs as source input for a search. Any other occurrences of the member are ignored. You may specify the SDUPM process option to cause SuperC to search for and report all occurrences of the string for the entire concatenated series of PDS members.

Other partitioned or sequential data sets, volume serials, and data set passwords are specified as on any other data entry panel. For more information, see the "ISPF Libraries and Data Sets chapter" in the *z/OS ISPF User's Guide Vol I*.

Note: The Password field applies only to the other partitioned or sequential data set. TSO prompts you if any concatenated data sets are password-protected.

Batch Option 2 causes SuperC to process the data sets in batch mode.

This choice frees the keyboard, allowing you to continue using ISPF while waiting for SuperC to search the data sets. The output listing is sent to the destination specified on the Search-For Utility - Submit Batch jobs panel (Figure 139 on page 231).

The panel shown in Figure 142 is displayed if you select option 2 and leave the Search DS Name field blank on the Extended Search-For Utility panel. You can concatenate up to four data sets that have like attributes. For example, all must be either sequential or partitioned.

```
                 Extended Search-For Concatenation Batch Entry

                              "Search" Concatenation
   DS1 . . . ____________________________________________________
   DS2 . . . ____________________________________________________
   DS3 . . . ____________________________________________________
   DS4 . . . ____________________________________________________

                       Other "Search" Partitioned, Sequential or VSAM Data Set
Data Set Name . . . ____________________________________________________
Volume Serial . . . ______     (If not cataloged)
Password  . . . . .            (Password allowed only in foreground mode)









Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 142. Extended Search-For - concatenation batch entry panel (ISRSFCON)

This panel is the same as the panel shown in Figure 141 on page 235, except the Password field is omitted. If your data sets are password-protected, search the data sets in foreground mode by leaving the Option field on the Extended Search-For Utility panel blank.

Printing an Extended Search-For Listing in Batch Mode

If you selected the Batch option on the Extended Search-For Utility panel, the panel shown in Figure 139 on page 231 is displayed before the job is submitted. Use this panel to specify whether your Search-For listing is to be printed or written to a list data set.

Output Mode
The output mode you want to use when displaying the listing file. Choose one of these:

View This enables the listing file to be displayed in *view* mode. All View functions are enabled in this mode.

Browse
This enables the listing file to be displayed in the *browse* mode. All Browse functions are enabled in this mode.

Select Search-For process options

Table 16 lists all of the process options for Search-For.

Table 16. Search-For process options

ALLMEMS	ANYC	APNDLST	CKPACKL	COBOL	DPACMT	DPADCMT	DPBLKCL
DPCBCMT	DPCPCMT	DPFTCMT	DPMACMT	DPPLCMT	DPPSCMT	FMSTOP	
IDPFX	LMTO	LNFMTO	LONGLN	LPSF	LTO		
MIXED	NOPRTCC	NOSEQ	NOSUMS	SDUPM	SEQ	XREF	

These rules govern the selection of Search-For process options:

- Type any nonblank character to the left of one or more process options. Then press Enter. This causes the options you specify to be displayed in the Process Options field on the Extended Search-For Utility panel. If you select two options that cannot be specified together, or if you enter an option name incorrectly, an error message is displayed. If **more +** or **more -+** is shown, use your Backward and Forward keys to move through the panel.
- Use the CANCEL command to return to the Extended Search-For Utility panel without processing selections.

Search-For process options can affect how the input data is processed, and determine the format and content of the output listing data set. They can also help you save processing time by avoiding comments and blank lines.

All these options except the DP*xxxx* (do not process) options can be chosen from the Search-For Process Options panel. However, you can type any of them in the Process Options field on the Extended Search-For Utility panel. Errors caused by mistyping process options are detected when you call the Extended Search-For utility.

For definitions of the Search-For process options, see “SuperC compare process options” on page 443.

Edit Search-For statements data set

A statements data set consists of process statements that contain instructions for the SuperC program. They are similar to the process options, but are composed of a keyword and one or more operands. See “Select Search-For process options” for information about Search-For process options.

When you select 1 from the Options menu on the Extended Search-For Utility panel, the Extended Search-For utility displays the statements data set you specified in the Statements Dsn field. This data set is always displayed in Edit mode, allowing you to add, change, or delete search-for process statements as needed.

The size of the Edit window depends on the number of lines your terminal can display. The sample panel shown in Figure 143 on page 238 shows how the Edit window appears on a 24-line display. Examples of some common process statements are listed below the Edit window so you can easily compose the proper input line.

```
            USERID.SRCHFOR.STMTS                          Columns 00001 00072

   Enter or change Process Statements in the EDIT window below:
****** **************************** Top of Data ******************************
''''''
''''''
''''''
''''''
''''''
''''''
''''''
''''''
****** *************************** Bottom of Data ***************************
   Examples                    Explanation
SRCHFOR  'ABCD',W           Search for the word "ABCD"
SRCHFORC 'DEFG'             "DEFG" must be on same line as word "ABCD"
CMPCOLM  1:60  75:90        Search columns 1:60 and 75:90 for string(s)
DPLINE 'PAGE ',87:95        Exclude line if "PAGE " found in columns 87:99
DPLINE   'PAGE '            Exclude if "PAGE " found anywhere on line
SELECT   MEM1,MEM2          Search only members MEM1 and MEM2 of PDS
                         - - - - -
Command ===> ____________________________________________ Scroll ===> PAGE
 F1=Help      F2=Split     F3=Exit      F5=Rfind     F6=Rchange   F7=Up
 F8=Down      F9=Swap     F10=Left     F11=Right    F12=Cancel
```

Figure 143. Search-For process statements panel (ISRSFPRS)

The SuperC program validates the process statements at run time. Invalid process statements are not used and are noted at the bottom of the listing. Unless a higher return code is required by some other condition, a return code of 4 is returned.

For the syntax and examples of the Search-For process statements, see “SuperC search-for process statements” on page 486.

ISPF table utility (option 3.16)

The ISPF Table Utility (Option 3.16) provides functions for processing ISPF tables. When you select this option, the ISPF Table Utility entry panel is displayed. This panel allows you to specify a table data set or DD, a table name, and an option to be performed.

The Edit and Browse functions allow you to view the data in the rows of an ISPF table in full-screen mode (that is, multiple rows are displayed on a screen). Line commands allow you to work with individual or multiple table rows. Primary commands are provided to support processing against the entire table, including changing the format of the displayed data. Table data can be scrolled in any direction (up, down, left, or right). All table column values are displayed in scrollable fields, allowing columns to be scrolled left or right, and individual column values to be expanded and displayed in a popup window. The values for any extension variables associated with a particular table row can be displayed.

The Edit function allows you to change the data in a table simply by overtyping the displayed value. Edit function line commands are available to insert new table rows, repeat rows, and delete rows. Extension variables for a table row can be created, modified, or deleted.

The Export function writes the data in an ISPF table to a sequential file so that it can be browsed or edited. You can customize the format of the data written to the sequential file.

The Import function uses the data in a sequential file to either create a new ISPF table or replace an existing table. The data in the sequential file is required to be in a special format generated by the ISPF Table Utility Export function.

```
  Menu  RefList  Utilities  Options  Help
 ------------------------------------------------------------------------
                              ISPF Table Utility
 Option ===> ____________________________________________________________

    blank Display table list                  E Edit table
        B Browse table                        I Import table data

 Enter one of the parameters below:
   Table Data Set . . TBUTIL.TABLES_________________________________
   or Table DD  . . . ________  (Default is ISPTLIB)

   Table Name . . . . ________  (Blank or pattern for table selection list)

   Import Data Set    ___________________________________________

   Enter "/" to select option
   _  Open table in SHARE mode



 F1=Help      F3=Exit     F12=Cancel   F13=Help     F15=End      F16=Return
F17=Rfind    F18=Rchange  F22=Left     F23=Right    F24=Cretriev
```

Figure 144. ISPF Table Utility panel (ISRUTBP0)

Table Utility panel action bar

The Table Utility Panel action bar choices function as follows:

Menu
For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

RefList
For information about referral lists, see the topic about Using Personal Data Set Lists and Library Lists in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Options
The Options pull-down offers these choices:

1 Table Utilities Options

2 Export Report Options

3 Export Data Set Attributes

Help
The Help pull-down provides general information about Table Utility topics as well as information about each of the main panels and options.

Table Utility panel fields

The fields on the ISPF Table Utility panel are:

Table Data Set
The name of the data set containing the table you wish to process.

Table DD
The name of the DD allocated to your ISPF session which contains the table you wish to process.

The default is the ISPTLIB DD if you do not enter data for either the Table Data Set or Table DD. If you enter data in both the Table Data Set and Table DD fields, the Table Data Set takes precedence.

Table Name
The name of the table you wish to process.

If you leave this field blank or supply a pattern the table selection list will be displayed showing the matching tables in the table data set or DD.

Import Data Set
The name of the sequential data set containing the data used to create or replace a table through the Import function.

Open table in SHARE mode
Select this option if the table you choose to process is already open on another logical screen, or if you might need to share the table with another logical screen.

Table utility entry panel options

These are the options shown on the ISPF Table Utility entry panel:

Blank - (Display Table List)
If you leave the Option field blank, a list of tables for the Table Data Set or Table DD is displayed when the Table Name is either blank or contains a pattern. If a valid Table Name is entered, the table list is bypassed and the Edit/Browse panel is displayed.

B - (Browse Table)
If a valid Table Name for the Table Data Set or Table DD is entered, the Browse Table panel is displayed. If the Table Name is either blank or contains a pattern, the table list is displayed allowing you to select the table to be browsed.

E - (Edit Table)
If a valid Table Name for the Table Data Set or Table DD is entered, the Edit Table Display panel is displayed. If the Table Name is either blank or contains a pattern, the table list is displayed allowing you to select the table to be edited.

I - (Import Table Data)
The Import function uses data from a sequential data set to create a new ISPF table or update an existing ISPF table. You must supply a Table Data Set and Table Name for the new or updated table. The sequential data set containing the data that will be used to create or update the table must be specified in the Import Data Set field.

Table data set selection list

This selection list is displayed when you enter a table data set name and either no table name or a table name pattern on the table utility entry panel.

```
  Menu  Utilities  Options  Help
 ------------------------------------------------------------------------------
                              ISPF Table List              Row 1 to 12 of 29
Command ===> ___________________________________________ Scroll ===> CSR

List of tables in table library PDFTOOL.COMMON.TABLES

   Name
   --------
_  BLG0CMDS
_  BLG0KEYS
_  BLG0PROF
_  BLSGEDIT
_  BLSGEDRT
_  BLSGPROF
_  BLSLPROF
_  DAFCMDS
_  ECXPDFPC
_  HSOCMDS
_  MOSCMDS
_  MVS8CMDS
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 145. Table data set selection list panel (ISRUTBP1)

If no table name is supplied, all members in the table data set are shown in the selection list. If a table name pattern is supplied, all members in the table data set that have a name matching the pattern are shown in the selection list.

These line commands are available on the table data set selection list panel:

E The Edit line command displays the EDIT table panel. It is available if you did not enter an option on the table utility entry panel.

B The Browse line command displays the BROWSE table panel. It is available if you did not enter an option on the table utility entry panel.

S When you use the Select line command against a table, either the BROWSE table or EDIT table panel is displayed:

- BROWSE table is displayed if you entered option B on the entry panel.
- EDIT table is displayed if you entered option E on the entry panel.
- If you did not enter option B or E on the entry panel, the panel is determined by how the option "Use EDIT as default to process selected table" is set. To set this option, select Table Utility Options panel from the Options pull-down.

These primary commands are available on the table data set selection list panel:

L *string* The Locate command scrolls the selection list and positions at the top of the display the entry which either matches or precedes (in alphabetic sequence) the value of *string*.

S *tblname* The Select command searches the selection list for an entry that matches *tblname*. If a matching entry is found the table is displayed in either the BROWSE table or EDIT table panel, following the same rules as for the Select line command.

E *tblname* The Edit command is available if you did not enter an option on the table utility entry panel. The selection list is searched for an entry that matches *tblname*. If a matching entry is found the EDIT table panel is displayed.

B *tblname* The Browse command is available if you did not enter an option

on the table utility entry panel. The selection list is searched for an entry that matches *tblname*. If a matching entry is found the BROWSE table panel is displayed.

Table DD selection list

This selection list is displayed when you enter a table DD and either no table name or a table name pattern on the table utility entry panel.

```
  Menu  Utilities  Options  Help
 ------------------------------------------------------------------------
                                ISPF Table List             Row 1 to 12 of 443
Command ===> ___________________________________________ Scroll ===> CSR

List of tables in data sets allocated to DD ISPTLIB

              Concat.
   Name       Number   Table Data Set
   --------   -------  ----------------------------------------------
_  $ISRPROF         1  PDFTDEV.LSACKV.TABLES
_  #ISRPROF         1  PDFTDEV.LSACKV.TABLES
_  ABCPROF          7  LSACKV.ISPF.ISPPROF
_  ACBKEYS         17  SYS1.DGTTLIB
_  ADB2DB2D         9  SYS2.TABLES.SYSPLEXD
_  ADB2PARM        23  DB2.ADMIN.V2R1M0.SADBTLIB
_  ADB21D          23  DB2.ADMIN.V2R1M0.SADBTLIB
_  ADB21DI2        23  DB2.ADMIN.V2R1M0.SADBTLIB
_  ADB21S          23  DB2.ADMIN.V2R1M0.SADBTLIB
_  ADB21SP         23  DB2.ADMIN.V2R1M0.SADBTLIB
_  ADB21T          23  DB2.ADMIN.V2R1M0.SADBTLIB
_  ADB21X          23  DB2.ADMIN.V2R1M0.SADBTLIB
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 146. Table DD selection list panel (ISRUTBP2)

If no table name was supplied, all members in the data sets allocated to the table DD are shown in the selection list. If a table name pattern was supplied, all members in the data sets allocated to the table DD which have a name matching the pattern are shown in the selection list.

The table DD selection list is sorted in member name order. Along with the member name, the selection list displays the name of the table data set where the member was found, and the concatenation number for that data set within the table DD.

These line commands are available on the table DD selection list panel:

E The Edit line command displays the EDIT table panel. It is available if you did not enter an option on the table utility entry panel.

B The Browse line command displays the BROWSE table panel. It is available if you did not enter an option on the table utility entry panel.

S When you use the Select line command against a table, either the BROWSE table or EDIT table panel is displayed:

- BROWSE table is displayed if you entered option B on the entry panel.
- EDIT table is displayed if you entered option E on the entry panel.
- If you did not enter option B or E on the entry panel, the panel is determined by how the option “Use EDIT as default to process selected table” is set. To set this option, select Table Utility Options panel from the Options pull-down.

These primary commands are available on the table data set selection list panel:

L *string* The Locate command scrolls the selection list and positions at the top of the display the entry which either matches or precedes (in alphabetic sequence) the value of *string*.

S *tblname* The Select command searches the selection list for an entry that matches *tblname*. If a matching entry is found the table is displayed in either the BROWSE table or EDIT table panel, following the same rules as for the Select line command.

E *tblname* The Edit command is available if you did not enter an option on the table utility entry panel. The selection list is searched for an entry that matches *tblname*. If a matching entry is found the EDIT table panel is displayed.

B *tblname* The Browse command is available if you did not enter an option on the table utility entry panel. The selection list is searched for an entry that matches *tblname*. If a matching entry is found the BROWSE table panel is displayed.

Edit/browse table panel

The table display panel used for the Edit and Browse functions of the table utility shows multiple rows on the one screen. Each row occupies one line on the screen. The UP and DOWN primary commands allow you to scroll through the rows in a table.

```
  Options  Help
 ------------------------------------------------------------------------------
 BROWSE                   ISPF Table BLSGEDIT                  Row 1 to 15 of 17
 Command ===> ____________________________________________ Scroll ===> CSR
                                                            Shift ===> PAGE
     ZEDPTYPE ZEDPLRCL ZEDPRCFM ZEDPFLAG                 ZEDPBNDL ZEDPBNDR
     ----+--- ----+--- ----+--- ----+----1----+----2---- ----+--- ----+---
__   TRACE    128      F        00000010100000000010000 0        0
__   CLIST    251      V        01000000000100000010000 0        0
__   PANELS   80       F        00000010100010000010000 0        0
__   TRACE    72       F        00000010100000000010000 0        0
__   CNTL     80       F        00000000100010000010000 0        0
__   JCL      80       F        01000000000100000010000 0        0
__   VCALL    80       F        00000000100000000000000 0        0
__   TRACE    121      V        00000000100000000000000 0        0
__   F02      80       F        00000000100000000000000 0        0
__   F03      121      V        00000000100000000000000 0        0
__   PRINT1   129      V        00000000100000000000000 0        0
__   TEXT     251      V        01000000000000000000000 0        0
__   ISPVCALL 80       V        00000000000000000000000 0        0
__   TRACE    80       F        00000000000000000000000 0        0
__   LOG      121      V        00000000000000000000000 0        0
  F1=Help      F3=Exit      F4=Expand    F5=Rfind    F12=Cancel   F13=Help
 F15=End      F16=Return   F17=Rfind    F22=Left    F23=Right    F24=Cretriev
```

Figure 147. Table display panel, edit mode (ISRUTBP3)

The dialog variables for the table rows are displayed in columns across the screen, with the dialog variable names shown as column headings. The RIGHT and LEFT primary commands allow you to view any columns that are not currently visible.

Two options on the Table Utility Options panel control how key values are displayed:

- "Color used to display table key values" specifies the color (BLUE, RED, PINK, GREEN, TURQ, YELLOW, or WHITE).

- "Intensity used to display table key values" specifies the intensity (HIGH or LOW).

The default color is GREEN and the default intensity is HIGH. For the Edit function, key values are always underscored. For the Browse function, key values are not underscored.

To determine the width required for each column field, the table utility must scan the table rows and check the length of the table variable values. While the utility uses an efficient method to scan a table, this process can be time consuming for a table with an extremely large number of rows. You can limit the number of rows scanned through the "Maximum rows searched to determine column width" option on the Table Utility Options panel.

All table variables are displayed in scrollable fields, with a scale indicator displayed below each column heading. Using scrollable fields allows the EXPAND primary command to be used to display the value of a table variable in a popup window. This popup window can display and edit data in HEX mode. The scrollable fields also allow you to use the RIGHT and LEFT primary commands to horizontally scroll column values.

For the Browse function, all the fields displaying table variable values are protected. For the Edit function, all these fields are unprotected and you can make changes to the table variable values by overtyping the displayed data.

For the Edit function, when you press Exit (F3) the changes are saved to a table output library. Normally the changes would be saved to the originating data set.

If you specified the table name and a Table DD on the ISPF Table Utility panel, and the "Always save table in originating data set" check box on the Table Utility Options panel is not selected, ISPF prompts you to specify the output data set. See "Table output data set selection" on page 254 for more information.

Line commands

This topic describes the line commands available on the Edit/Browse panel.

E Extension Variables. Use this command to display the extension variables for the table row. When using the Edit function, the values of the extension variables can be changed, new extension variables can be created, and existing extension variables can be deleted. See "Extension Variables panel" on page 245.

I*n* Insert Row After. Use this command to insert one or more rows after the row where the line command was entered. The table variable values for an inserted row are initialized with blanks.

B*n* Insert Row Before. Use this command to insert one or more rows before the row where the line command was entered. The table variable values for an inserted row are initialized with blanks.

R*n* Repeat Row. Use this command to create one or more copies of the table row. The copied rows are inserted after the row where the line command was entered. For the copied rows, all variables excluding keys are initialized using the values from the corresponding variables in the row where the line command was entered. Key variables are initialized with blanks.

D*n* Delete Row. Use this command to delete one or more table rows.

Notes:

1. The E command is available in both the Edit and Browse functions. The I, B, R, and D commands are only available in the Edit function.
2. For all line commands except E, an optional number from 1 to 9 can be entered as a suffix to the line command character. This causes the command to operate on multiple rows starting with the row on which the command was entered.
3. When processing a keyed table, the optional number is ignored for the line commands I, B, and R.

Extension Variables panel: The Extension Variables panel shows the names and values of the extension variables defined for a table row. To display the extension variables panel, enter the E line command against a table row on the table display screen.

```
 Options  Help
 ------------------------------------------------------------------------------
                BLSGEDIT Extension Variables for Row 1         Row 1 to 3 of 3
Command ===> ____________________________________________ Scroll ===> CSR

Extension variable values scrollable width:    65
S   Name      Value
--  --------  ----------------------------------------------------------------
              ----+----1----+----2----+----3----+----4----+----5----+----6----+
__  ZEDPIMAC
__  ZEDPFLG2  01000011
__  ZEDPFLG3  00000001
****************************** Bottom of data ******************************


 F1=Help    F2=Split   F3=Exit    F4=Expand  F5=Rfind   F7=Up      F8=Down
 F9=Swap   F10=Left   F11=Right  F12=Cancel
```

Figure 148. Extension Variables Panel (ISRUTBP4)

When you edit a table, the extension variable names and their values and the "Extension variable values scrollable width" are displayed in unprotected fields. You can change the extension variable names and values by overtyping the displayed data. You can use the selection field to enter a line command against an extension variable. When you browse a table, the extension variable names and values are protected, and the selection field is unavailable.

The extension variable values are displayed in scrollable fields with a scale indicator displayed below the column heading. You can use the RIGHT and LEFT primary commands to horizontally scroll through one of the values. You can enter the EXPAND primary command to display the value of an extension variable in a popup window. This popup window also enables you to display and edit data in HEX mode.

The "Extension variable values scrollable width" field initially displays the length of the scrollable width of the field that displays the extension variable values. This length will be the maximum of either:

- The length of the field displaying the values. This length depends on the width of the screen. For example, if the screen has a width of 80 characters the field

will have a length of 65 characters. For a screen with a width of 132 characters the field will have a length of 117 characters.

- The length of the largest value for the extension variables displayed.

If you need to lengthen the value for an extension variable beyond the scrollable limit, you can use this field to enter a numeric value to increase the scrollable width of the field. You can then use the EXPAND primary command (F4) to update the value of the extension variable.

Line commands: This topic describes the line commands available on the Extension Variables panel.

I*n* Insert Extension Variable After. Use this command to insert one or more extension variables after the row where the line command was entered. The name and value for the inserted extension variable are initialized with blanks.

B*n* Insert Extension Variable Before. Use this command to insert one or more extension variables before the row where the line command was entered. The name and value for an inserted extension variable are initialized with blanks.

R*n* Repeat Extension Variable. Use this command to create one or more copies of the extension variable. The extension variables are inserted after the row where the line command was entered. For the new extension variables, the names and values are copied from the extension variable where the line command was entered.

D*n* Delete Extension Variable. Use this command to delete one or more extension variables.

Notes:

1. Line commands on the extension variables panel are only available when using the Edit function.
2. For all line commands, an optional number from 1 to 9 can be entered as a suffix to the line command character. This causes the command to operate on multiple extension variables starting with the extension variable against which the command was entered.

Primary commands

This topic describes the primary commands available on the Table Utility Edit/Browse panel:

Navigating through the table:	UP/DOWN, LEFT/RIGHT, FIND/RFIND
Changing the data or how it is displayed:	INSERT, EXPAND, SORT/STATS/STRUCT
Saving or exporting table data:	SAVE/CANCEL, EXPORT/FEXPORT

Browse and Edit primary commands are entered in the Command field. All the primary commands except SAVE are available in both the Edit and Browse functions. The SAVE command is only available in Edit.

CANCEL

Terminate Edit without Saving Changes. The CANCEL command (F12) terminates table editing without saving the table data to the output data set.

CAN can be used as an abbreviation for the CANCEL command.

DOWN
Scroll Down. The standard ISPF DOWN command (F8|F20) can be used to vertically scroll the table display towards the bottom of the table.

ISPF supported scroll amount values used for the DOWN command can be entered in the Scroll field. You can also enter a valid scroll amount in the Command field.

EXPAND
Expand Display of Scrollable Field. The standard ISPF EXPAND command (F4) can be used to display a table variable value in a popup window containing a scrollable dynamic area. To do this, enter EXPAND while the cursor is placed on the field displaying a table variable value.

EXPORT
Display Table Export Layout. The Export Layout panel is displayed when the EXPORT primary command is entered on the Edit/Browse panel. This panel shows the structure used to format the table data written to the export output data set. You can make changes to the structure to alter the format of the data written to the output data set.

```
  Options  Help
 ------------------------------------------------------------------------
                         Table BLG0CMDS Export Layout          Row 1 to 9 of 9
 Command ===> ____________________________________________ Scroll ===> CSR

 Overtype the Order column and press ENTER to rearrange the fields into the
 order in which you would like them to be dumped. Change Width as required.
 Only fields with an Order value less than 999 will be dumped.
 Use the FILE primary command to write the table data to the export data set.
                                                                  Cumulative
 Order     Name      Field Heading                          Width     Width
 -----     --------  ---------------------------------      -------   ----------
 001       ZEDPTYPE  ZEDPTYPE                                     8           9
 002       ZEDPLRCL  ZEDPLRCL                                     8          18
 003       ZEDPRCFM  ZEDPRCFM                                     8          27
 004       ZEDPFLAG  ZEDPFLAG                                    24          52
 005       ZEDPBNDL  ZEDPBNDL                                     8          61
 006       ZEDPBNDR  ZEDPBNDR                                     8          70
 007       ZEDPTABC  ZEDPTABC                                     8          79
 008       ZEDPMASK  ZEDPMASK                                     8          88
 009       ZEDPTABS  ZEDPTABS                                     8          97
 ****************************** Bottom of data ********************************
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 149. Table Export Layout panel (ISRUTBP7)

The screen shows the current structure used to format the table data written to the export data set. The list contains these fields:

Order This input field allows you to enter a number which defines the sequence in which the table variables for each row are placed in the export data set. For example, assigning an Order of 001 to a table variable makes it the first to be written to each table data record in the export data set.

Note: Only table variables that have an Order value less than 999 are written to the export data set.

Name The name of the table variable.

Field Heading
This input field allows you to define a heading for each table

variable written to the export data set. It is initialized with the name of the associated table variable.

Width This input field allows you to define the number of characters allocated to the column used to print a table variable value. This field is initialized to the display length of the table variable value on the table display screen.

Cumulative Width
This field shows the total number of characters required in the export data set record to accommodate this variable and all the preceding table variables.

When you are happy you have the correct format defined, use the FILE primary command to write the table data to the export data set.

These abbreviations can be used for the EXPORT command:

```
EX
EXP
EXPO
EXPOR
```

FILE The FILE command causes the table data to be written to the export data set in the format defined on the export layout panel.

The name of the export output data set can be specified as a parameter to the FILE command. You can enter any fully qualified data set name by enclosing it in apostrophes. If you omit the apostrophes, your TSO prefix or user ID (if no TSO prefix is defined in your TSO user profile) is added to the beginning of the data set name. For example, if a user whose TSO prefix is LSACKV issues the command `FILE TAB1.DATA`, the table data report is written to the export data set LSACKV.TAB1.DATA.

If you do not specify an export data set name on the FILE command, a default name is generated according to these rules:

- If no TSO prefix is defined in your TSO user profile: *userid.tblname*.TBLDUMP
- If your TSO prefix and user ID are the same: *tsopref.tblname*.TBLDUMP
- If your TSO prefix and user ID are not the same: *tsopref.userid.tblname*.TBLDUMP

tsopref is your TSO prefix. *userid* is your TSO user ID. *tblname* is the name of the table you are processing.

A warning message might be displayed if the export data set already exists. You then have the option of terminating the command to avoid overwriting the data set. If you don't want to receive these warnings in future, clear the "Warn if export data set exists" check box on the Table Utility Options panel.

When the FILE command has finished, the export data set is displayed. The "Display mode for export data set" option on the Table Utility Options panel allows you to choose either the ISPF Browse, View, or Edit functions to display the export data set.

These abbreviations can be used for the FILE command:

```
FI
FIL
```

FEXPORT

Fast EXPORT Command. The FEXPORT command writes the table data to the export output data set without displaying the export layout panel.

The name of the export output data set can be specified as a parameter to the FEXPORT command. You can enter any fully qualified data set name by enclosing it in apostrophes. If you omit the apostrophes, your TSO prefix or user ID (if no TSO prefix is defined in your TSO user profile) is added to the beginning of the data set name. For example, if a user whose TSO prefix is LSACKV issues the command `FEXPORT TAB1.DATA`, the table data report is written to the export data set LSACKV.TAB1.DATA.

If you do not specify an export data set name on the FEXPORT command, a default name is generated according to these rules:

- If no TSO prefix is defined in your TSO user profile: *userid*.*tblname*.TBLDUMP
- If your TSO prefix and user ID are the same: *tsopref*.*tblname*.TBLDUMP
- If your TSO prefix and user ID are not the same: *tsopref*.*userid*.*tblname*.TBLDUMP

tsopref is your TSO prefix. *userid* is your TSO user ID. *tblname* is the name of the table you are processing.

If the export data set exists when the FEXPORT command is issued and you have selected "Warn if export data set exists" on the Table Utility Options panel, a warning popup panel is displayed. You then have the option of terminating the command to avoid overwriting the data set.

When the FEXPORT command has finished, the export data set is displayed. The "Display mode for export data set" option on the Table Utility Options panel allows you to choose either the ISPF Browse, View, or Edit functions to display the export data set.

These abbreviations can be used for the FEXPORT command:

```
FE
FEX
FEXP
FEXPO
FEXPOR
```

FIND Search for String in Table. The FIND command can be used to search for the occurrence of a character string in a specified column in the table. If the string is found, the row in which it is found is positioned at the top of the display.

The FIND command has these formats:

```
FIND varname string
FIND n string
```

where:

varname The name of any of the table variables.

n The ordinal number of any column displayed on the current screen.

string The character string to be searched for. The search is not case sensitive.

These abbreviations can be used for the FIND command:

```
F
FI
FIN
```

INSERT
Insert a Blank Row at the Top of the Table. Use the INSERT command to create a new blank row as the first row in the table. This command allows you to create a row in an empty table.

LEFT Scroll Left. The LEFT command (F10|F22) can be used to scroll the table display horizontally towards the first table column.

The scroll amount values used for the LEFT command can be entered in the Shift field. You can also enter one of these valid scroll amounts in the Command field:

PAGE Causes the display to scroll left by the width of the screen.

MAX Causes the display to scroll left so that the first column for the table is the leftmost displayed.

0 to 9999 Causes the display to scroll left the specified number of columns.

Note: Table variable values are displayed in scrollable fields. Therefore if the cursor is placed in a field displaying a table variable value, the LEFT command operates on that field, not on the whole table display.

RFIND
Repeat Last FIND Command. The RFIND command (F5|F17) is used to repeat the last FIND command. It is most useful when assigned to a function key.

R can be used as an abbreviation for the RFIND command.

RIGHT
Scroll Right. The RIGHT command (F11|F23) can be used to scroll the table display horizontally towards the last table column.

The scroll amount values used for the RIGHT command can be entered in the Shift field. You can also enter one of these valid scroll amounts in the Command field:

PAGE Causes the display to scroll right by the width of the screen.

MAX Causes the display to scroll right so that the last column for the table is the rightmost displayed.

0 to 9999 Causes the display to scroll right the specified number of columns.

Note: Table variable values are displayed in scrollable fields. Therefore if the cursor is placed in a field displaying a table variable value, the RIGHT command operates on that field, not on the whole table display.

SAVE Save Table Changes. The SAVE command causes the changes to the table data to be written to the table output library. Normally the changes would be saved to the originating data set.

If you specified the table name and a Table DD on the ISPF Table Utility panel, and the “Always save table in originating data set” check box on the

Table Utility Options panel is not selected, ISPF prompts you to specify the output data set. See "Table output data set selection" on page 254 for more information.

SAV can be used as an abbreviation for the SAVE command.

SORT Display Table Sort Definition. The Sort Specification panel is displayed when the SORT primary command is entered on the Edit/Browse panel. This panel allows you to sort the table according to the values of one or more table variables.

```
  Options  Help
 ------------------------------------------------------------------------
                      Table BLSGEDIT Sort Specification        Row 1 to 9 of 9
Command ===> ____________________________________________ Scroll ===> CSR

Overtype the Order column and press ENTER to rearrange the table variables
into the order in which you would like them to be sorted. Change Sequence to A
(Ascending) or D (Descending) as required. Table BLSGEDIT will only be sorted
using table variable with an Order less than 999.


Order     Name           Sequence (A/D)
-----     --------       --------------
999       ZEDPTYPE             A
999       ZEDPLRCL             A
999       ZEDPRCFM             A
999       ZEDPFLAG             A
999       ZEDPBNDL             A
999       ZEDPBNDR             A
999       ZEDPTABC             A
999       ZEDPMASK             A
999       ZEDPTABS             A
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 150. Table Sort Specification panel (ISRUTBP8)

The screen displays a list of the table variables and contains these fields:

Order This input field allows you to enter a number which defines the sort priority for the associated table variable. For example, assigning an Order of 001 makes the associated table variable the primary sort key.

Note: The table will only be sorted on those variables that have an Order value less than 999.

Name The name of the table variable.

Sequence (A/D)
This input field allows you to define whether to sort in ascending (A) or descending (D) sequence for the associated table variable.

When you press Exit (F3) to return to the Edit/Browse panel it is sorted based on changes made on the table sort display.

Note: If you are using Edit, the sort criteria entered on this screen are saved with the table.

These abbreviations can be used for the SORT command:

```
SO
SOR
```

STATS
Display Table Statistics. The table statistics display is invoked when the

STATS primary command is entered on the browse/edit table display. This screen shows the statistical information that ISPF maintains for the table.

```
                        Statistics for Table BLG0CMDS
Command ===> ____________________________________________________________
The following information is returned by the TBSTATS service:

Created on . . . : 1997/01/14 at 13:26:23
Last updated on  : 2004/08/27 at 09:37:02 by LSACKV

Initial number of rows when created  . . . . . . : 101
Current number of rows . . . . . . . . . . . . . : 101
Number of existing rows which have been updated  : 2
Number of times table has been updated . . . . . : 7
Virtual storage size (bytes) . . . . . . . . . . : 8,072

Last TABLE SERVICES command  . . . . . . . . . . : TBTOP
Return code from above service . . . . . . . . . : 0

Status 1 : 1  - table exists in input library chain
Status 2 : 3  - table is open in WRITE mode in this logical screen
Status 3 : 2  - table is not available for WRITE mode

 F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
 F9=Swap       F10=Actions    F12=Cancel
```

Figure 151. Table statistics panel (ISRUTBP6)

The screen shows these fields:

Created on
The date and time the table was originally created.

Last updated on
The date and time the table was last modified.

by User ID of the last user who modified the table.

Initial number of rows when created
Number of rows that were added during the session when the table was first created and then closed.

Current number of rows
Number of rows currently in the table.

Number of existing rows which have been updated
Number of rows that have been modified in the table at least once. A row that is added to an existing table is considered a modified row.

Number of times table has been updated
Number of editing sessions during which the table has been modified. Opening a table, then making one or more updates, then closing and saving the table increments this count by one.

Virtual storage size (bytes)
Number of bytes of virtual storage required by the table.

Last TABLE SERVICES command
The name of the last table service called.

Return code from above service
The return code issued by the last table service called.

Status 1
The status of the table in the table input library chain.

Status 2
The status of the table in this logical screen.

Status 3
The availability of the table to be used in WRITE mode.

STRUCT
Display Table Structure. The table structure panel is invoked when the STRUCT primary command is entered on the Edit/Browse panel. This panel shows the structure used to format the browse/edit table display. You can change the data displayed on this screen to alter the format of the table display.

```
 Options  Help
 ------------------------------------------------------------------------------
                          Structure of Table BLSGEDIT          Row 1 to 7 of 9
Command ===> ____________________________________________ Scroll ===> CSR

                                 Rows scanned to produce
Number of Rows . . : 17          structure  . . . . . . . . . . : 17
Number of Keys . . : 0
Number of Names  . : 9
 ----------------------------------------------------------------------------
ZEDPTYPE ZEDPLRCL ZEDPRCFM ZEDPFLAG                ZEDPBNDL ZEDPBNDR
 ----------------------------------------------------------------------------

Column  Name      Type  Length  Display Area
------  --------  ----  ------  ------------------------------
001     ZEDPTYPE  Name     8    <= start of display
002     ZEDPLRCL  Name     8    <= displayed
003     ZEDPRCFM  Name     8    <= displayed
004     ZEDPFLAG  Name    24    <= displayed
005     ZEDPBNDL  Name     8    <= displayed
006     ZEDPBNDR  Name     8    <= end of display
007     ZEDPTABC  Name     8
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 152. Table structure panel (ISRUTBP5)

The top area of this screen shows this information about the table:

- Number of Rows
- Number of Keys
- Number of Names
- Rows scanned to produce structure

Note: This value is controlled by the “Maximum rows searched to determine column width” option on the Table Utility Options panel.

The next area of the screen shows the current column headings for the table display.

The bottom area of the screen shows the current structure used to format the table display. This is a list containing these fields:

Column
This input field shows a number representing the relative position of the associated table variable in the table display. You can change the position of a variable in the table display by altering this number.

Name The name of the table variable.

Type Shows a value of Key if the associated variable is defined as a key for the table. Otherwise shows a value of Name.

Length This input field shows the number of characters used to display the table variable value. The table utility calculates this number by scanning the table rows and finding the largest length value for each table variable.

Note: If you have specified a value for the "Maximum rows searched to determine column width" option on the Table Utility Options panel, the table utility might not scan all the table rows and therefore the calculated length value might not be large enough for all variable values.

Display Area Identifies the table variables currently shown on the table display screen.

When you press Exit (F3) to return to the Edit/Browse panel it is reformatted based on changes made on the table structure display.

These abbreviations can be used for the STRUCT command:

```
STR
STRU
STRUC
```

UP Scroll Up. The standard ISPF UP command (F7|F19) can be used to vertically scroll the table display towards the top of the table.

ISPF supported scroll amount values used for the UP command can be entered in the Scroll field. You can also enter a valid scroll amount in the Command field.

Table output data set selection

This panel is displayed when either the first SAVE command is issued or the EXIT command (F3) is issued, and these conditions are all true:

- The table you have modified was specified on the Table Utility Entry panel
- you did not select "Always save table in originating data set" on the Table Utility Options panel
- you specified a Table DD rather than a Table Data Set on the Table Utility Entry panel

```
  Help
 ------------------------------------------------------------------------
                        Table Output Data Set Selection        Row 1 to 7 of 2
Command ===> ____________________________________________ Scroll ===> CSR

No table data set was originally specified, only a table DD. Since there was
more than one table data set allocated to this DD, please select which data
set should receive the updated table. All future SAVE requests will
automatically use the selected table data set. Use END or CANCEL to return
without saving the table.


S  Table Data Set
-  ---------------------------------------------
_  PDFTDEV.LSACKV.TABLES
_  PDFTOOL.COMMON.TABLES
_  PDFTDEV.STG.TABLES
_  PDFTDEV.INT.TABLES
_  PDFTDEV.SVT.TABLES
_  ISPFTEST.TABLES
_  LSACKV.ISPF.ISPPROF
_  MBURNS.ISPF.ISPPROF
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 153. Table Output Data Set Selection panel (ISRUTBP9)

This panel lists the data sets allocated to the table DD specified on the table utility entry panel. Enter an S in the selection field for the data set in which you would like the updated table to be saved. If you press Enter without selecting a data set, the table update is canceled.

Table utility options

To display the Table Utility Options panel, select Table Utility Options from the Options menu on the action bar. This panel allows you to set options that control certain behaviors within the ISPF Table Utility.

These options on the first section of the panel affect the Edit and Browse functions:

Open table in SHARE mode
: Select this option if the table you are to process is already open on another logical screen or if you might need to share the table with another logical screen.

Use EDIT as default to process selected table
: When you select this option, you will default to Edit mode if you do not specify either the Edit or Browse functions on the table utility entry panel or the table selection panel. You will default to browse mode when this option is not selected.

Always save table in originating data set
: *When this option is selected*: If the table you are editing was specified on the table utility entry panel but the Table data set was not specified, the table is automatically saved in the original data set.

  When this option is cleared: When you first attempt to save the table, the table output data set selection panel will be displayed. This panel allows you to choose within the table DD the data set where the table will be saved.

Maximum rows searched to determine column width
: To determine the width required to display each column field, the table utility scans the table rows and checks the length of the table variable

values. This option allows you to specify a number which acts as the limit for the number of rows scanned in this process. If you leave this value blank, all rows will be scanned.

Note: Because the table utility uses an efficient method to scan a table, you can leave this option blank for all but extremely large tables.

Color used to display table key values
Use this option to specify the color (BLUE, RED, PINK, GREEN, TURQ, YELLOW, or WHITE) used to display the values for the key variable in the table. The default is GREEN.

Intensity used to display table key values
Use this option to specify the intensity (HIGH or LOW) used to display the values for the key variables in the table. The default is HIGH.

These options on the second section of the panel affect the Import function:

Warn if table exists in the output library
When this option is selected, a warning message will be displayed if you try to import data into a table that already exists in the specified output data set. You can then choose either to overwrite the existing table or to cancel the import process. If you don't want to receive warning messages in this situation, clear this option.

Use Edit to view the imported table
When this option is selected, the table utility uses the Edit function to display the table that was created or updated by the Import function. If this option is not set, the Browse function will be used to display the table.

These options on the final section of the panel affect the Export function:

Warn if export data set exists
When this option is selected, a warning message will be displayed if the data set you are exporting table data into already exists. You can then choose either to overwrite the data set or to cancel the export process. If you don't want to receive warning messages in this situation, clear this option.

Display mode for export data set
This option allows you to choose whether to use either the ISPF Browse, View, or Edit function to display the export data set after the export process has completed.

Table export report options

To display the Table Export Reports Options panel, select Export Report Options from the Options menu on the action bar. This panel allows you to set options which control the format of the report written to the output data set by the table utility Export function.

```
                        Table Export Report Options
Command ===> ____________________________________________________________


  Enter "/" to select option
  _  Set options to match IMPORT format report

  /  Generate headings
  /  Underline headings

Heading, column and page spacing:

  Blank lines after heading  . . . . . 0   (0 - 9)

  Number of spaces between columns . . 1  (0 - 99)

  Number of lines per page . . . . . . 0  (0 - 99)
                                          (0 if no paging is required)

  Number of blank lines between pages  0  (0 - 99)
                                          (ignored if lines/page = 0)

Enter END to save changes.
Enter CANCEL to cancel changes.
 F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
 F9=Swap       F12=Cancel
```

Figure 154. Table Export Report Options panel (ISRUTBO2)

The panel provides these options:

Set options for IMPORT format report
Select this option if you want to write the export report in the same format that is used by the table utility Import function. Selecting this option causes other options on the panel to be set so as to produce the export report in the appropriate format.

Generate headings
Select this option if you want the export report to have headings for the columns showing the table variable values.

Underline headings (in export report)
Select this option if you want the column headings to be underlined. Column headings for key variables are underlined with plus signs (++++++++). Column headings for non-key variables are underlined with dashes (--------).

Blank lines after heading
This option allows you to specify the number of blank lines printed after the column headings. The number must be between 0 and 9.

Number of spaces between columns
This option allows you to specify the number of spaces printed between the columns showing the table variable values. The number must be between 0 and 99.

Number of lines per page
This option allows you to specify the maximum number of lines printed on each page of the report. The number must be between 0 and 99. If you specify 0, no page breaks will be generated.

Number of blank lines between pages
This option allows you to specify the number of blank lines printed at the

end of a page to separate it from the following page. The number must be between 0 and 99. This option is ignored if you specify 0 for the "Number of lines per page" option.

Export data set attributes

To display the Export Data Set Attributes panel, select Export Data Set Attributes from the Options menu on the action bar. This panel allows you to set various attributes for the output data set created by the table utility Export function.

```
                         Export Data Set Attributes
Command ===> ____________________________________________________________

Management class . . . ________       (Blank for default management class)
Storage class  . . . . ________       (Blank for default storage class)
 Volume serial . . . . ______         (Blank for system default volume) **
 Device type . . . . . SYSALLDA       (Generic unit or device address) **
Data class . . . . . . ________       (Blank for default data class)
 Space units . . . . . TRACK          (BLKS, TRKS, or CYLS)
 Primary quantity  . . 5              (In above units)
 Secondary quantity    5              (In above units)

( ** Only one of these fields may be specified)

Enter END to save changes.
Enter CANCEL to cancel changes.




 F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
 F9=Swap       F12=Cancel
```

Figure 155. Table Export Data Set Attributes panel (ISRUTBO3)

The panel provides these options:

Management class
Specify the SMS management class for the data set. The management class is used to obtain data management-related information for the data set, such as migration, backup, and retention criteria.

Storage class
Specify the SMS storage class for the data set. The storage class is used to obtain storage-related information (volume serial) for the data set.

Volume serial
For a non-SMS data set, specify the volume serial of the direct-access volume you wish to contain the data set.

Device type
For a non-SMS data set, specify the generic unit address for the direct access volume you wish to contain the data set.

Data class
Specify the SMS data class for the data set. The data class is used to obtain data-related information (space units, primary quantity, secondary quantity, directory block, record format, record length, and data set name type) for the data set.

Space units
Specify the disk space units (TRACK, CYLINDER, or BLOCK).

Primary quantity
Enter a number for the primary allocation in space units.

Secondary quantity
Enter a number for the secondary allocation in space units.

Importing data into a table

The ISPF Table Utility supports an Import function, where data in a sequential data set is used to load an ISPF table. The import function is invoked by entering option I (Import table data) on the ISPF Table Utility entry panel.

When you use the Import function, enter these fields on the table utility entry panel:

Table Data Set
This identifies the data set where the table that will be created or updated by the Import function is saved.

Table Name
The name of the table that will be created or updated by the Import function.

Import Data Set
The name of the data set containing the data used as input to the Import function.

The Import function requires the Import Data Set to contain a report in a specific format. This format is generated by the ISPF table utility Export function and has these features:

- The variable name is used as a heading for each column showing the values for the table variables.
- The headings are underlined. Column headings for key variables are underlined with plus signs (++++++++). Column headings for non-key variables are underlined with dashes (--------).
- There are no blank lines after headings.
- There is only 1 space between columns.
- There is no paging.

A warning message might be displayed if the table you specify already exists in the Table Data Set. You then have the option of terminating the command to avoid overwriting the table. If you don't want to receive these warnings in future, clear the "Warn if table exists in the output library" check box on the Table Utility Options panel.

When the import process has finished, the table that was created or updated is displayed. The "Use Edit to view the imported table" option on the Table Utility Options panel allows you to choose either the table utility Edit or Browse function to display the imported table. The default is Browse.

Exporting data from a table

The ISPF Table Utility supports an Export function, where data in an ISPF table is used to write a customizable report to a sequential file. The Export function is invoked by using either the EXPORT or FEXPORT primary commands from the table display screen for the table utility Edit and Browse functions.

Note: The report does not show the values for extension variables defined for table rows.

The EXPORT primary command displays the Export Layout panel, where you can control the layout of the table data in these ways:

- Exclude table variables from the report
- Change the order in which the table variables appear in the report
- Change the column headings

The Table Export Report Options panel allows you to change the format of the report. Selecting the "Set options for IMPORT format report" option ensures the generated report is in a format that can be processed by the table utility Import function. The Export Data Set Attributes panel allows you to define the allocation attributes for the export data set.

Figure 156 shows an example of the export report in a format suitable for the Import function:

```
********************************* Top of Data **********************************
SUBSYS  SERVER  DESCRIPT                           BSECEXIT BCATOWN BJCLASS BJS
+++++++ ------- ---------------------------------- -------- ------- ------- ---
DB2D            DB2 Version 5                                       A
DB26            DB2 Version 6 - Subsystem 1                         A
DB62            DB2 Version 6 - Subsystem 2                         A
DB27            DB2 Version 7                                       A
DBT5            DB2 Version 5.1 for FM/DB2 FVT only                 A
DBT6            DB2 Version 6.1 for FM/DB2 FVT only                 A
DBT7            DB2 Version 6.1 for FM/DB2 FVT only                 A
******************************** Bottom of Data ********************************
```

Figure 156. Export report example

Processing tables that are currently open

Normally, ISPF does not allow a table to be opened and processed if that table is currently open. However, if the table currently open has been opened with the SHARE option, a subsequent open of the table is allowed if:

- The SHARE option is used, and
- The WRITE/NOWRITE option is the same as specified when the table was initially opened

The ISPF Table Utility provides support which allows you to process a table even when that table is currently open.

If a table is currently open in SHARE mode, the ISPF Table Utility can be used to process that table provided you select the "Open table in SHARE mode" option on the ISPF Table Utility panel *and* the Edit (WRITE) or Browse (NOWRITE) option specified matches the WRITE/NOWRITE setting when the table was originally opened.

If a table data set (rather than a table DD) is specified on the entry panel, the ISPF Table Utility also allows you to process a table that is open but not in SHARE mode, or a table that is open in SHARE mode but the WRITE/NOWRITE (edit/browse) setting does not match that of the open table. When this situation is detected, one of the popup windows shown here is displayed allowing you to specify the way in which to process the table:

```
ISRUTBC2            Confirm Table Processing
Command ===> ____________________________________________

CAUTION:
The table TSTTABA is currently open to you or another user.

Instructions:

Press ENTER key to process a temporary copy of the table in data
set VANDYKE.TBUTIL.TABLES.

Press CANCEL or EXIT to cancel processing of the table.
```

Figure 157. Panel displayed when the selected table is currently open but not in SHARE mode

The panel shown in Figure 157 is displayed when the selected table from the table data set (TSTTABA) is currently open but not in SHARE mode.

```
ISRUTBC1            Confirm Table Processing
Command ===> ____________________________________________

CAUTION:
The table TSTTABA is currently open to you in SHARE/NOWRITE mode

Instructions:

Press ENTER key to process a temporary copy of the table in data
set VANDYKE.TBUTIL.TABLES.

Press EXIT key to process the currently open table
in SHARE/NOWRITE (browse) mode.

Press CANCEL to cancel processing of the table.
```

Figure 158. Panel displayed when the selected table is currently open in SHARE mode for NOWRITE

The panel shown in Figure 158 (ISRUTBC1) is displayed when the selected table (TSTTABA) from the table data set is currently open in SHARE mode for NOWRITE (not for update) and you either:

- Did not select the Open table in SHARE mode option on the entry or options panel, or
- Requested to edit (WRITE) the table

```
ISRUTBC1            Confirm Table Processing
Command ===> ____________________________________________________

CAUTION:
The table TSTTABA is currently open to you in SHARE/WRITE mode.

Instructions:

Press ENTER key to process a temporary copy of the table in data
set VANDYKE.TBUTIL.TABLES.

Press EXIT key to process the currently open table
in SHARE/WRITE (edit) mode.

Press CANCEL to cancel processing of the table.
```

Figure 159. Panel displayed when the selected table is currently open in SHARE mode for WRITE

The panel shown in Figure 159 (ISRUTBC1) is displayed when the selected table (ISRPLIST) is currently open in SHARE mode for WRITE (for update) and you either:

- Did not select the Open table in SHARE mode option on the entry or options panel, or
- Requested to browse (NOWRITE) the table

If you press Enter, the table utility:
- Creates a temporary partitioned data set.
- Copies the table from the table data set you specified. into a member in the temporary data set using a generated member name.
- Opens the table using the generated name.
- Displays the table data.

If you press the Exit key (usually PF3) on panel ISRUTBC1, the table utility:
- Displays the data for the currently open table. If this table was originally opened for WRITE, the data is displayed for edit, otherwise it is displayed for browse.

If you press Cancel (or Exit on panel ISRUTBC2):
- The table is not processed and you are returned to the entry or table selection panel.

If you edit a temporary copy of an open table, this panel is displayed when you exit the edit display:

```
ISRUTBPB                Save Temporary Table
Command ===>

Specify the names of the data set and member where the temporary table
will be saved.

Partitioned Data Set Name and Member
   Name  . . . . . . . 'VANDYKE.TBUTIL.TABLES'
   Member  . . . . . . ISRPLIST

Enter "/" to select option
_  Replace existing member


Instructions:

Press ENTER key to save the temporary table in the specified data set
and member.

Press EXIT or CANCEL to exit without saving the temporary table.
```

This panel allows you to save the updated table in a specified data set and member. The panel initially shows the table data set and table (member) you requested to edit. The ″Replace existing member″ option allows you to replace an existing member with the data from the table you have edited. If you press Enter, the table utility writes the table data to the specified data set and member. If you press Exit or Cancel, the data from the temporary table is not saved.

z/OS UNIX directory list utility (option 3.17)

The z/OS UNIX Directory List Utility (option 3.17) supports processing of directories and files in a z/OS UNIX directory structure. When you select this option, the z/OS UNIX Directory List Utility panel (ISRUULP) is displayed.

The layout and options of the Directory List Utility are similar to those in the Data Set List Utility (ISPF option 3.4). You can either display the directory list under the specified path name for further processing, or print the directory list to the ISPF list data set.

```
  Menu  Utilities  Options  Help
 ------------------------------------------------------------------------
                        z/OS UNIX Directory List Utility
Option ===> ____________________________________________________________

   blank Display directory list              P Print directory list

   Pathname . . . /var                                                 +


Enter "/" to select option
/  Confirm File Delete
7  Confirm Non-empty Directory Delete

When the directory list is displayed, enter either:
  "/" on the directory list line command field for the command prompt pop-up,
  an ISPF line command, the name of a TSO command, CLIST, or REXX exec, or
  "=" to execute the previous command.


 Time zone EST5EDT is used to calculate the displayed date and time values.

 F9=Swap     F10=Actions  F12=Cancel
```

Figure 160. z/OS UNIX Directory List Utility panel (ISRUULP)

Note: When the z/OS UNIX Directory List Utility panel is first displayed, a message is displayed showing the time zone that is used to calculate the date and time values displayed in the directory list. The time zone value is obtained from the z/OS UNIX TZ environment variable. If a value for the TZ environment value is not found in the system-wide /etc/profile file or the user's .profile file, the utility calculates displayed date and time values using the operating system GMT offset.

z/OS UNIX Directory List Utility panel action bar

The Data Set List Utility Panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Options
The Options pull-down offers these choices:

1 Directory List Options

Options that control the behavior of the directory list display.

2 Directory List Column Arrangement

Settings that alter the order and size of the column fields that are displayed in the directory list.

Help The Help pull-down provides general information about z/OS UNIX Directory List Utility topics as well as information about displaying and printing a z/OS UNIX Directory List.

z/OS UNIX Directory List Utility panel fields

The z/OS UNIX Directory List Utility panel contains these fields:

Pathname
This is a scrollable field where you enter the path name of the directory you want to list or print. If you leave this field blank, your home directory is used. If the field is blank and you do not have a home directory, you are prompted to enter a path name.

You can use these special characters at the beginning of the Pathname field to represent the path name for a particular directory:

~ (Tilde) The path name for your home directory.

. (Period) The path name for your current working directory.

.. (Double period) The path name of the parent directory of your current working directory.

Note: Within the z/OS UNIX Directory List Utility, you can also use these special characters in any field where a z/OS UNIX file path name can be entered.

Confirm File Delete
This option controls the display of the Confirm Delete panel. This panel is displayed when deleting files or empty directories from the directory list display using the D line command. If this option is selected, the Confirm Delete panel is displayed. If this option is not selected, the panel is not displayed and the file or empty directory is deleted without any additional user interaction.

Confirm Non-empty Directory Delete
This option controls the display of the Confirm Non-empty Directory Delete panel. This panel is displayed when using the directory list D line command to delete a directory that contains files and subdirectories. If this option is selected, the Confirm Non-empty Directory Delete panel is displayed. If this option is not selected, the panel is not displayed and the directory (including all contained files and subdirectories) is deleted without any additional user interaction.

z/OS UNIX Directory List Utility panel options

See:
- “Blank—display directory list”
- “P—print directory list” on page 273

Blank—display directory list

To display a directory list for the specified path, leave the Option line blank and press Enter. If you leave the Pathname field blank, your home directory will be used.

You can also specify the options “Confirm File Delete” and “Confirm Non-empty Directory Delete”to control the behavior of the D (delete file) line command in the directory list.

```
  Menu  Utilities  View  Options  Help
 ------------------------------------------------------------------------------
                           z/OS UNIX Directory List          Row 1 to 13 of 25
Command ===> _____________________________________________ Scroll ===> PAGE

Pathname . : /SYSTEM/etc

Command  Filename        Message          Type Permission Audit  Ext  Fmat
-------------------------------------------------------------------------------
________ .                                Dir  rwxr-xr-x  fff---
________ ..                               Dir  rwxr-xr-x  fff---
________ .nfsc                            File rw-r--r--  fff--- --s- ----
________ ant.conf                         File rwxrwxrwx  fff--- --s- ----
________ bpa                              Dir  rwxr-xr-x  fff---
________ cmx                              Dir  rwxr-xr-x  fff---
________ dce                              Dir  rwxr-xr-x  fff---
________ dfs                              Dir  rwxr-xr-x  fff---
________ inetd.conf                       File rwxrwxrwx  fff--- --s- ----
________ inetd.pid                        File rw-r--r--  fff--- --s- ----
________ ioepdcf                          Syml rwxrwxrwx  fff---
________ ldap                             Dir  rwxr-xr-x  fff---
________ licmgmt                          Dir  rwxr-xr-x  fff---
________ log                              File rw-rw----  fff--- --s- ----
________ pkiserv                          Dir  rwxr-xr-x  fff---
________ profile                          File rwxr-xr-x  fff--- --s- ----
________ security                         Dir  rwxr-xr-x  fff---
 F1=Help    F2=Split   F3=Exit    F4=Expand  F5=Rfind   F7=Up      F8=Down
 F9=Swap   F10=Left   F11=Right  F12=Cancel
```

Figure 161. z/OS UNIX Directory List panel (ISRUUDL0)

The information for each entry in the directory is displayed in column fields across the screen. The number of columns displayed depends on the available screen width. Figure 161 shows the initial directory list display on a terminal with a screen width of 80 and a screen depth of 28.

The RIGHT primary command can be used to scroll the displayed column fields to the right. Figure 162 on page 267 shows the directory list display when the RIGHT command is issued on the previous display:

```
  Menu  Utilities  View  Options  Help
 ------------------------------------------------------------------------------
                           z/OS UNIX Directory List          Row 1 to 13 of 25
 Command ===> ____________________________________________ Scroll ===> PAGE

 Pathname . : /SYSTEM/etc

 Command  Filename        Message          Owner    Group    Links  Size
 ------------------------------------------------------------------------------
 ________ .                                IBMUSER  OMVSGRP      14       8192
 ________ ..                               IBMUSER  OMVSGRP       6       8192
 ________ .nfsc                            IBMUSER  OMVSGRP       1          0
 ________ ant.conf                         IBMUSER  OMVSGRP       1         29
 ________ bpa                              IBMUSER  OMVSGRP       2       8192
 ________ cmx                              IBMUSER  OMVSGRP       2       8192
 ________ dce                              IBMUSER  OMVSGRP       9       8192
 ________ dfs                              IBMUSER  OMVSGRP       8       8192
 ________ inetd.conf                       IBMUSER  OMVSGRP       1       1215
 ________ inetd.pid                        IBMUSER  OMVSGRP       1         10
 ________ ioepdcf                          IBMUSER  OMVSGRP       1         22
 ________ ldap                             IBMUSER  OMVSGRP       2       8192
 ________ licmgmt                          IBMUSER  OMVSGRP       6       8192
 ________ log                              IBMUSER  OMVSGRP       1          0
 ________ pkiserv                          IBMUSER  OMVSGRP       2       8192
 ________ profile                          IBMUSER  OMVSGRP       1      10665
 ________ security                         IBMUSER  OMVSGRP       2       8192
  F1=Help    F2=Split   F3=Exit    F4=Expand  F5=Rfind   F7=Up      F8=Down
  F9=Swap   F10=Left   F11=Right  F12=Cancel
```

Figure 162. z/OS UNIX Directory List—scrolling right

Note: The screens shown in Figure 161 and Figure 162 assume that the default column arrangement settings are used. You can change the width of column fields and the order in which they are displayed, and remove selected columns from the directory list display. See "z/OS UNIX Directory List Column Arrangement panel" on page 298.

z/OS UNIX Directory List panel action bar: The z/OS UNIX Directory List panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

View The View pull-down offers this choice: **1. Sort**

You can sort the list by any of these fields:

1. Filename
2. Message
3. File Type
4. Permissions
5. Permissions - Octal
6. Owner
7. Audit
8. Extended Attributes
9. Format
10. Group
11. Links
12. Size

13. Changed Date/Time
14. Modified Date/Time
15. Accessed Date/Time
16. Created Date/Time

You can also specify the sort sequence (ascending or descending) or accept the default sequence for the associated sort field. By default, character fields are sorted alphabetically and numeric fields are sorted in descending order.

Options
The Options pull-down offers these choices:

1 Directory List Options

Options that control the behaviour of the directory list display.

2 Directory List Column Arrangement

Settings that alter the order and size of the directory list column fields and allow you to remove columns from the display.

3 Refresh List

Refresh the display of the directory list.

4 Save List

Save the directory list to a file.

5 Reset

Reset the directory list.

Help The Help pull-down provides general information about z/OS UNIX Directory List Utility topics, including the format of the directory list and the available line commands and primary commands.

z/OS UNIX Directory List panel fields: The fields listed here can appear on the directory list panel. Which fields are displayed depends on the column arrangements settings and whether the display has been scrolled left or right.

Command Field used to enter a line command, z/OS UNIX command, TSO command, CLIST, or REXX exec against a directory list entry.

Filename The name of the file or subdirectory.

Message This field is initially blank. After you run one of the built-in line commands on a file or subdirectory, a message is displayed showing the last function used on that file or subdirectory:

Line Command	Message
B	Browsed
CI	Replaced
CO	Copied
E	Edited
D	Deleted
I	Information
L	Listed

MM Modified

MX Modified

N Created

R Renamed

X (Depends on whether a z/OS UNIX command or TSO command is executed)

If you enter a TSO command, CLIST, or REXX exec on the Command line, a default message appears in the Message field. The message is in this format:

```
XXXXXXXX  RC=#
```

where:

XXXXXXXX is the command entered

is the return code from the command

If you enter a z/OS UNIX command, the completion status is indicated by one of these messages being displayed in the Message field:

Ended *xxx*
Command has ended with a return code of *xxx*

Terminated *xxx*
Command has terminated due to signal *xxx*

Stopped *xxx*
Command has stopped due to signal *xxx*

Timed out
The elapsed running time of the command exceeded the specified time limit. ISPF sent a SIGKILL signal to terminate the process.

Type The directory entry type. The possible values are:

Dir Directory

File Regular file

Char Character special file

FIFO FIFO (first-in-first-out) special file

Syml Symbolic link

Extl External symbolic link

Perm The file or subdirectory permissions, in octal format. The permissions are displayed as three octal (range 0-7) digits. The first digit defines the access permission for the file owner. The second digit defines the access permission for any member of the file's group. The third digit defines the access permission for anyone else. Table 17 shows the values and associated permissions for the octal digits:

Table 17. Octal permission values

Value	Permissions
0	None
1	Search (or execute)

Table 17. Octal permission values (continued)

Value	Permissions
2	Write
3	Write and search (or execute)
4	Read
5	Read and search (or execute)
6	Read and write
7	Read, write and search (or execute)

If there are extended access control list (ACL) entries defined for the file or subdirectory, the character + is displayed after the octal value.

Permissions
The file or subdirectory permissions, in symbolic format. There are three groups of three characters. The first group describes owner permissions; the second describes group permissions; and the third describes other (or "world") permissions. The characters that may appear in each group are:

r Permission to read the file
w Permission to write to the file
x Permission to execute the file

These characters can appear in the execute (third) position of each group:

s If in owner permissions group, the set-user-ID bit is on; if in group permissions section, the set-group-ID bit is on.
S Same as s except the execute bit is off.
t The sticky bit is on.
T Same as t except the execute bit is off.

Note: You can specify whether permissions are to be displayed in octal or symbolic format on the z/OS UNIX Directory List Options panel.

Audit
Two groups of three characters describing the audit bit settings. The first three characters describe the user-requested audit information. The last three characters describe the auditor-requested audit information. Each group of three characters shows the read, write, and execute (search) audit options. The possible values are:

s Audit successful access attempts
f Audit failed access attempts
a Audit all access attempts
- No audit

Ext
A group of four characters describing the extended attributes for a regular file. The possible values are:

a Program runs APF-authorized if linked AC=1
p Program is considered program-controlled
s Program is enabled to run in a shared address space
l Program is loaded from the shared library region
- Attribute not set

Fmat
File format for regular files. The possible values are:

bin Binary data
nl New line
cr Carriage return
lf Line feed

	crlf Carriage return followed by line feed **lfcr** Line feed followed by carriage return **crnl** Carriage return followed by new line
Owner	The user ID of the owner of the file or subdirectory.
Group	The group name of the owner of the file or subdirectory.
Links	For a file, the number of hard links to the file. For a subdirectory, the number of subdirectories it contains.
Size	The file size, in bytes.
Modified	The date and time the file was last changed.
Changed	The date and time the status of the file was last changed.
Accessed	The date and time the data in the file was last accessed.
Created	The date and time the file was created.

Actions you can take from the Directory List panel: These topics describe actions you can take from the Directory List panel:

- "Line commands"
- "z/OS UNIX commands, TSO commands, CLISTs, and REXX EXECs"
- "Using the path name substitution character" on page 273

Line commands: Line commands can be entered in the Command field to the left of the directory list entries.

z/OS UNIX commands, TSO commands, CLISTs, and REXX EXECs: Besides the ISPF-supplied line commands, you can also enter z/OS UNIX Commands, TSO commands, CLISTs, and REXX EXECs that use a path name as an operand. The line command field is a scrollable field with a maximum length of 255 characters and a display length of 8 characters. If the command you want to enter requires more space than is available in the display field, use the EXPAND function key (F4) to display the entire 255-character line command input field in a pop-up window.

The line command prefix characters > and < are used to identify a command to be run in z/OS UNIX. ISPF uses the **spawn** service (BPX1SPN) to create a new process and execute the command. The > prefix character requests that the command be run by the z/OS UNIX login shell. The < prefix character requests that the command be run directly.

Figure 163 on page 272 shows an example of using the c89 shell command to compile, link-edit, and assemble the C program contained in the file /u/myhome/hello.c. The > character before the command name indicates that it will be run in a login shell environment:

```
                          z/OS UNIX Directory List           Row 1 to 6 of 6
Command ===> ____________________________________________ Scroll ===> CSR

Pathname . : /u/myhome

Command  Filename        Message          Type Permission Audit  Ext  Fmat
--------------------------------------------------------------------------------
________ .                                Dir  rwxrwxrwx  fff---
________ ..                               Dir  rwxrwxrwx  fff---
________ bin                              Dir  rwxrwxrwx  fff---
>c89___  hello.c                          File rwxrwxrwx  fff--- --s- ----
________ prog1                            File rwxrwxrwx  fff--- --s- ----
________ test1                            File rwxrwxrwx  fff--- --s- ----
****************************** Bottom of data ********************************

⋮
```

Figure 163. Example: specifying a z/OS UNIX command to run on a selected file

Figure 164 shows an example of running the program /u/myhome/hello.c directly in z/OS UNIX. The < character indicates that the selected file is the name of a command that is to be run:

```
                          z/OS UNIX Directory List           Row 1 to 6 of 6
Command ===> ____________________________________________ Scroll ===> CSR

Pathname . : /u/myhome/bin

Command  Filename        Message          Type Permission Audit  Ext  Fmat
--------------------------------------------------------------------------------
________ .                                Dir  rwxrwxrwx  fff---
________ ..                               Dir  rwxrwxrwx  fff---
________ bin                              Dir  rwxrwxrwx  fff---
<_______ hello.c                          File rwxrwxrwx  fff--- --s- ----
________ prog1                            File rwxrwxrwx  fff--- --s- ----
________ test1                            File rwxrwxrwx  fff--- --s- ----
****************************** Bottom of data ********************************

⋮
```

Figure 164. Example: running the selected file directly

A line command that is not recognized as a z/OS UNIX Directory List line command, or is not prefixed with < or >, is assumed to be a TSO command, CLIST, or REXX EXEC. These commands are passed to TSO for execution using the ISPF SELECT CMD service. Variable names that start with an ampersand (&) are evaluated by ISPF. If you want the underlying command processor to see the ampersand you must specify two consecutive ampersands (&&).

Figure 165 on page 273 shows an example of running a REXX EXEC called LISTDATA against the file prog1 in directory /u/myhome. This is the same as entering this command on the Command line:

```
TSO LISTDATA '/u/myhome/prog1'
```

```
                          z/OS UNIX Directory List           Row 1 to 6 of 6
Command ===> ____________________________________________ Scroll ===> CSR

Pathname . : /u/myhome

Command  Filename        Message          Type Permission Audit  Ext  Fmat
--------------------------------------------------------------------------------
________ .                                Dir  rwxrwxrwx  fff---
________ ..                               Dir  rwxrwxrwx  fff---
________ bin                              Dir  rwxrwxrwx  fff---
________ hello.c                          File rwxrwxrwx  fff--- --s- ----
listdata prog1                            File rwxrwxrwx  fff--- --s- ----
________ test1                            File rwxrwxrwx  fff--- --s- ----
****************************** Bottom of data ********************************

⋮
```

Figure 165. Example: specifying a REXX exec to run on a selected file

Note: If the TSO command, CLIST, or REXX exec issues a return code greater than or equal to 8, processing stops and an error message is displayed.

Using the path name substitution character: If a command, CLIST, or REXX exec requires the file or subdirectory path name in a position other than the first operand or if other operands are needed, you can use the path name substitution character to represent the path name. If no operands are specified after the command, ISPF uses the path name of the file or subdirectory that is being acted on as the first operand of the command.

Note: For TSO commands, CLISTs, and REXX EXECs, the path name is enclosed in quotes.

The ISPF-defined default for the path name substitution character is the exclamation point (!) character. You can change the value of this character using the z/OS UNIX Directory List Options panel.

For example, if you specify: `CLIST1 FILE(!) DEBUG` in the line command field for file test_data in directory u/myhome the effect will be the same as if you had entered this primary command:

```
TSO CLIST1 FILE('/u/myhome/test_data') DEBUG
```

P—print directory list

Use option P to print a directory list. You must:

1. Enter the path name for the directory you want to list in the Pathname field. If you leave this field blank, the path name for your home directory will be used.
2. Press Enter to print the directory list. The directory list is stored in the ISPF list data set.

Note: The format of the printed directory list is not affected by any changes you make using the z/OS UNIX Directory List Column Arrangement panel.

z/OS UNIX directory list utility line commands

After you display a directory list by leaving the Option field blank, you can enter a line command to the left of a directory entry. You can also enter TSO commands, CLIST names, or REXX exec names. The path name substitution character can be used with TSO commands, CLISTs, and REXX EXECs to represent the quoted path name for a file or subdirectory. For more information about using this symbol, see "Using the path name substitution character."

The line command field is a scrollable field with a maximum length of 255 characters and a display length of 8 characters. If the command you want to enter requires more space than is available in the display field, use the EXPAND function key (F4) to display the entire 255-character line command input field in a pop-up window.

If you enter a slash (/) in the Command field, the Directory List Actions pop-up window is displayed. This window allows you to select the line command you wish to invoke.

```
  Menu  Utilities  View  Options  Help
s                                                          sssssssssss
                    Directory List Actions                  13 of 159
C                                                           ===> PAGE
   File ----- /u/.sh_history
P
   DIRLIST Action
C      1.  Edit                    9.  Rename                Fmat
-      2.  Edit - ASCII            10. Copy Out             -----------
       3.  View                    11. Copy In
       4.  View - ASCII            12. Information
       5.  Browse                  13. Modify Mode Fields
/      6.  New                     14. Modify Extended Attrs  - ----
       7.  Directory List          15. Execute command
       8.  Delete

   Select a choice and press ENTER to process data set action.



                                                           - ----
    F1=Help        F2=Split       F3=Exit        F7=Backward  - nl
    F8=Forward     F9=Swap       F12=Cancel
                                                           8=Down
 F9=Swap   F10=Left   F11=Right  F12=Cancel
```

Figure 166. z/OS UNIX Directory List Actions pop-up window

E—edit regular file

The E (edit) line command can be entered against a regular file. The z/OS UNIX OEDIT command is invoked, enabling the use of the ISPF editor to change the data in the file.

A numeric record length can also be specified as an option with the E line command. This option allows you to set the record length when editing fixed-length text files. When specified, the file will be processed as variable length but loaded into the editor as fixed-length records and saved as fixed-length records. This lets you convert a variable-length file to fixed length.

The z/OS UNIX File Edit Options panel allows you to specify an initial edit macro and edit profile to be used for the edit of the selected file. You can also select the “Bypass z/OS UNIX File Edit Options panel” option to stop this panel being displayed for subsequent file edit sessions.

The “Bypass z/OS UNIX File Edit Options panel” option can also be selected or cleared from the z/OS UNIX Directory List Options panel.

B—browse regular file

The B (browse) line command can be entered against a regular file. The z/OS UNIX OBROWSE command is invoked, enabling the use of the ISPF browse function to view the data in the file.

A numeric record length can also be specified as an option with the B line command. This option allows you to browse fixed-length record files containing text or binary data without new line delimiters.

N—create a new directory entry

The N (new) line command can be entered against any directory entry. The Create New z/OS UNIX File panel is displayed.

```
                        Create New z/OS UNIX File
Command ===> ____________________________________________________________

Pathname . . . . /u/sclmtest                                          +

Permissions  . . ___  (Octal)

Link . . . . . . ______________________________________________        +

                                          Options
File Type  . . . _  1. Directory          _  Set sticky bit
                    2. Regular file       _  Copy...
                    3. FIFO               _  Edit...
                    4. Symbolic Link      _
                    5. External Link
                    6. Hard Link

 F1=Help       F2=Split      F3=Exit       F4=Expand     F7=Backward
 F8=Forward    F9=Swap      F10=Actions   F12=Cancel
```

Figure 167. Create New z/OS UNIX File panel (ISRUULNW)

These mandatory input fields are displayed on this panel:

Pathname
The path name for the z/OS UNIX file to be created. This field is initialized with the path name of the file that the N line command was entered against. The field is scrollable with a length of 1023 bytes. Use the EXPAND function key (F4) to display the entire field in a pop-up window.

Note: In the panel displayed by the N line command, you can specify a "+" (plus) character as the first character of a path name to represent the path name of the directory currently listed.

Permissions
The permissions defined for the new file. Enter as three octal (range 0-7) digits. The first digit defines the access permission for the file owner. The second digit defines the access permission for any member of the file's group. The third digit defines the access permission for anyone else. See Table 17 on page 269.

Link This field is only mandatory when creating a Symbolic Link, External Link, or Hard Link. When creating a Symbolic Link or a Hard Link this field is used to define the path name of the existing file the link refers to. When creating an External Link this field is used to define the external name the link refers to. The field is scrollable with a length of 1023 bytes. Use the EXPAND function key (F4) to display the entire field in a pop-up window.

File Type
This field is used to enter one of the listed numbers corresponding to the type of file you want to create.

1. Directory

2. Regular file
3. FIFO
4. Symbolic Link
5. External Link
6. Hard Link

These optional fields can be selected on this panel:

Set sticky bit
When this option is selected it causes the sticky bit to be set on for the new file or subdirectory. When the sticky bit is set for a directory, a user cannot remove or rename a file in the directory unless one or more of these is true:

- The user owns the file
- The user owns the directory
- The user has superuser authority

If the sticky bit is set for a program file, when executing the program z/OS UNIX will search for the program in the user's STEPLIB, the link pack area, or the link list concatenation.

Copy When this option is selected and you are creating a new regular file, it causes the Replace z/OS UNIX File panel to be displayed, allowing you to have the data from a z/OS UNIX file, data set, or partitioned data set member copied into the new file. When selected and you are creating a new directory, it causes the Copy Into z/OS UNIX Directory panel to be displayed, allowing you to have the data from members in a partitioned data set copied into files in the new directory.

Edit When this option is selected and you are creating a new regular file, it causes the edit function to be invoked allowing you to create and modify data in the new file.

L—directory list

The L (list directory) line command can be entered against a directory. This line command causes a new z/OS UNIX Directory List panel to be displayed, showing the entries for the selected directory. This new directory list display is nested so entering the END or EXIT command on this panel will return you to the previous directory list. Entering the CANCEL command on a nested directory list display will return you to the directory list utility entry panel.

D—delete a file

The D (delete file) line command can be entered against any directory entry. If entered against a file or an empty directory and the Confirm File Delete option is selected, the Confirm Delete panel is displayed. This panel allows the delete operation to be canceled if necessary using the CANCEL or EXIT commands. You can prevent this panel being displayed for subsequent delete operations by selecting the "Set file delete confirmation off" option.

If the deletion proceeds successfully, the file or directory is removed from the file system.

If the D line command is entered against a directory containing files and subdirectories and the Confirm Non-empty Directory Delete option is selected, the Confirm Non-empty Directory Delete panel is displayed. This panel allows the delete operation to be canceled if necessary using the CANCEL or EXIT

commands. You can prevent this panel being displayed for subsequent delete operations by selecting the “Set non-empty directory delete confirmation off” option.

If the deletion proceeds successfully the directory, including all contained files and subdirectories, is removed from the file system.

R—rename a file

The R (rename file) line command can be entered against any directory entry. This line command causes the Rename z/OS UNIX File panel to be displayed. This panel displays the Pathname and Type of the file being renamed. Use the New Pathname field to enter the new name for the file.

Note: In the panel displayed by the R line command, you can specify a ″+″ (plus) character as the first character of a path name to represent the path name of the directory currently listed.

When you press Enter, ISPF attempts to rename the file.

Attention: If the New Pathname you specified corresponds to an existing file, the Confirm Rename panel is displayed. In this situation, proceeding with the rename will cause the existing file with the same name to be deleted.

C or CO—copy data out

The C or CO (copy out) line command can be entered against a regular file or directory.

Note: In the panel displayed by the CO line command, you can specify a ″+″ (plus) character as the first character of a path name to represent the path name of the directory currently listed.

Copying from a regular file: When the C or CO line command is entered against a regular file, the Copy From z/OS UNIX File panel is displayed.

```
                         Copy From z/OS UNIX File
Command ===> ____________________________________________________________

From z/OS UNIX file:
  Name . . . : /u/mburns/cargs1.c

To z/OS UNIX file, data set, or member:
  Name . . . . ____________________________________________________   +
  Permissions  700  (Octal)

Options
  /  Confirm copy to existing target
  _  Update permissions for existing target file
  _  Binary copy
  _  Convert

Conversion Table  ________________________________________________________



 F1=Help     F2=Split    F3=Exit     F4=Expand   F5=Rfind    F7=Up
 F8=Down     F9=Swap    F10=Left    F11=Right   F12=Cancel
```

Figure 168. Copy From z/OS UNIX File panel (ISRUULCF)

This panel allows you to copy the data in a regular file to another z/OS UNIX file, a sequential data set, or a member of a partitioned data set.

Note: When copying to a sequential data set or member of a partitioned data set, ISPF invokes the z/OS UNIX OGET command to perform the copy operation.

The panel displays the path name of the file being copied.

These mandatory input fields are displayed on this panel:

Name The destination where the data from the file will be copied. Any of these can be specified:

- The path name of a z/OS UNIX file.
- The name of a sequential data set.
- The names of an existing partitioned data set and member.

Permissions
When copying to a z/OS UNIX file, defines the permissions for that file. Enter as three octal (range 0-7) digits. The first digit defines the access permission for the file owner. The second digit defines the access permission for any member of the file's group. The third digit defines the access permission for anyone else. See Table 17 on page 269.

These optional input fields are available on this panel:

Confirm copy to existing target
When this option is selected and the target z/OS UNIX file, data set, or member exists, the Confirm Copy panel displays a warning that the data in the target will be overwritten if the copy proceeds.

In this situation, proceeding with the copy will cause the data in the target to be overwritten. Since this is an irrevocable process which may cause loss of valuable data, ISPF requires you to confirm you really want the copy to proceed. If you have made a mistake, the copy operation can be canceled using the CANCEL or EXIT commands.

Update permissions for existing target file
If this option is selected and the target of the copy is an existing z/OS UNIX file, the value specified in the Permissions field will be used to update the permissions for this file.

Binary copy
When this option is selected it indicates the file being copied contains binary data. This causes the copy to take place without any consideration for newline characters or the special characteristics of DBCS data. If this option is not selected the file is assumed to contain TEXT data.

Note: This option is ignored when copying to another z/OS UNIX file.

Convert
This option specifies whether data conversion is required during the copy operation. Typically, conversion is only required when the data contains square brackets. If no value is entered in the Conversion Table field, the data being copied is converted using the default conversion table (BPXFX000) in the standard library concatenation. By default, this would cause a conversion between code pages IBM-037 and IBM-1047. Otherwise the value in the Conversion Table field identifies a conversion table to be used for the copy operation.

Note: This option is ignored when copying to another z/OS UNIX file.

Conversion Table

These types of values can be specified in this field:

- *data_set_name*(*member_name*)

  The partitioned data set and member containing the character conversion table.

- *data_set_name*

  The partitioned data set that has the member BPXFX000 containing the character conversion table.

- (*member_name*)

  The member containing the character conversion table. It is assumed to be in a data set in the standard library concatenation. (The default data set is SYS1.LINKLIB.)

  Note: This field is ignored if the Convert option is not selected or if copying to another z/OS UNIX file.

For further information on the character conversion table refer to the description of the OGET command in the *z/OS UNIX System Services Command Reference*.

Copying from a directory: When the C or CO line command is entered against a directory, the Copy From z/OS UNIX Directory panel is displayed.

```
                      Copy From z/OS UNIX Directory
Command ===> ____________________________________________________

From z/OS UNIX directory:
  Name . . . : /u/mburns/jcldir

To partitioned data set:
  Name . . . . ________________________________________

Options
  _  Replace like-named members
  _  Selection list...
  /  Include lowercase names
  /  Strip suffix ___________________  (Suffix to strip)
  _  Binary copy
  _  Convert

Conversion Table  ____________________________________________________


 F1=Help       F2=Split      F3=Exit       F4=Expand     F7=Backward
 F8=Forward    F9=Swap      F10=Actions   F12=Cancel
```

Figure 169. Copy From z/OS UNIX Directory panel (ISRUULCD)

This panel allows you to copy the data from regular files in a directory to members in a partitioned data set.

Note: When copying to a member of a partitioned data set, ISPF invokes the z/OS UNIX OGET command to perform the copy operation.

For a file to be selected for copying, it must have a file name that conforms to the naming conventions for a partitioned data set member. This panel also provides options that allow you to further control the files selected for copying.

The panel displays the path name of the directory being copied. These mandatory input fields are displayed on this panel:

Name The name of an existing partitioned data set where the regular files in the directory will be copied. The files are copied into members in the partitioned data set.

These optional input fields are available on this panel:

Replace like-named members
When this option is selected, if the file into which the data from a selected member is to be copied already exists in the directory, the existing file will be overwritten with the data from the selected member. If this option is not selected, the member will not be copied.

Selection list
If this option is selected, the z/OS UNIX Directory Copy Selection List panel is displayed. This panel displays a list of the regular files that are eligible to be copied to the partitioned data set. The list contains these fields:

S An input field where you can enter S to indicate the associated regular file is to be copied to the partitioned data set.

Filename
The name of a regular file that can be copied to the partitioned data set. The name conforms to the rules for a member name and fits the selection criteria specified on the Copy From z/OS UNIX Directory panel.

Member
The name to be used for the member into which the data from the associated regular file will be copied. Each member name is generated from the name of the source file. You can change a generated member name to something other than the name assigned by ISPF. For example, if ISPF generates the same member name for two files, you can change one of the member names to make them both unique.

Message
This field displays a message indicating the result of copying the regular file to the member. The possible values displayed are:

***COPIED**
The data from the regular file was successfully copied to a new member in the partitioned data set.

***REPL** The data from the regular file was copied to an existing member in the partitioned data set. The data in the member was overwritten. This can only occur when the Replace like-named members option is selected on the Copy From z/OS UNIX Directory panel.

***NO-REPL**
The data from the regular file was not copied to the partitioned data set member because the member already existed and the Replace like-named members option was not selected on the Copy From z/OS UNIX Directory panel.

FAILED RC=*xx
The OGET command invoked to copy the data from the file to the member failed with return code *xx*. The data was not copied.

When you press Enter on this panel, the selected files will be copied to the partitioned data set. The Message field indicates the result of the copy operation for each file.

Include lowercase names
When this option is selected the file names for the regular files will be converted to uppercase before being checked for a valid member name. If this option is not selected, regular files whose file name contains lowercase characters will not be considered for copying to the partitioned data set.

Strip suffix
When this option is selected suffixes will be stripped from the file name at the first period (.) before being checked for a valid member name. The accompanying input field allows you to specify a particular suffix to be stripped (regular files with other suffixes will not be considered for copying). If this option is not selected, any regular files whose file name includes suffixes will not be copied to the partitioned data set.

Selecting this option can result in ISPF attempting to copy different files into the same member. For example, if the **Strip suffix** option is selected and the directory being copied contains these files:
- pgm1.exe
- pgm1.o
- pgm1.C

the data for each of these files is written to member PGM1. If the **Replace like-named members** option is also selected, member PGM1 will contain the data from file pgm1.C. If the **Replace like-named members** option is not selected, member PGM1 will contain the data from file pgm1.exe.

Binary copy
When this option is selected it indicates the file being copied contains binary data. This causes the copy to take place without any consideration for newline characters or the special characteristics of DBCS data. If this option is not selected the file is assumed to contain TEXT data.

Convert
This option specifies whether data conversion is required during the copy operation. Typically, conversion is only required when the data contains square brackets. If no value is entered in the Conversion Table field, the data being copied is converted using the default conversion table (BPXFX000) in the standard library concatenation. By default, this would cause a conversion between code pages IBM-037 and IBM-1047. Otherwise the value in the Conversion Table field identifies a conversion table to be used for the copy operation.

Conversion Table
These types of values can be specified in this field:
- *data_set_name*(*member_name*)

  The partitioned data set and member containing the character conversion table.
- *data_set_name*

  The partitioned data set that has the member BPXFX000 containing the character conversion table.
- (*member_name*)

  The member containing the character conversion table. It is assumed to be in a data set in the standard library concatenation. (The default data set is SYS1.LINKLIB.)

Note: This field is ignored if the Convert option is not selected or if copying to another z/OS UNIX file.

For further information on the character conversion table refer to the description of the OGET command in the *z/OS UNIX System Services Command Reference*.

CI—copy data in

The CI (copy in) line command can be entered against a regular file or directory.

Note: In the panel displayed by the CI line command, you can specify a "+" (plus) character as the first character of a path name to represent the path name of the directory currently listed.

Copying into a regular file: When the CI line command is entered against a regular file, the Replace z/OS UNIX File panel is displayed.

```
                         Replace z/OS UNIX File
Command ===> ____________________________________________________________

Into z/OS UNIX file:
  Name . . . : /u/mburns/abcde

From z/OS UNIX file, data set, or member:
  Name . . . . ______________________________________________   +

Options
  _  Binary copy
  _  Convert

Conversion Table  ____________________________________________________

 F1=Help        F2=Split       F3=Exit        F4=Expand      F7=Backward
 F8=Forward     F9=Swap       F10=Actions    F12=Cancel
```

Figure 170. Replace z/OS UNIX File panel (ISRUULRF)

This panel allows you to copy into a regular file data from another z/OS UNIX file, a sequential data set, or a member of a partitioned data set.

Notes:

1. When copying from a sequential data set or member of a partitioned data set, ISPF invokes the z/OS UNIX OPUT command to perform the copy operation.
2. this operation will cause existing data in the regular file to be overwritten.

The panel displays the path name of the file into which the data will be copied. These mandatory input fields are displayed on this panel:

Name The source of the data to be copied into the file. Any of these can be specified:

- The path name of a z/OS UNIX file
- The name of a sequential data set
- The names of an existing partitioned data set and member

These optional input fields are available on this panel:

Binary copy
When this option is selected it indicates the data set/member being copied contains binary data. This causes the copy to take place without any consideration for newline characters or the special characteristics of DBCS data. If this option is not selected the data set/member is assumed to contain TEXT data.

Note: This option is ignored when copying to another z/OS UNIX file.

Convert
This option specifies whether data conversion is required during the copy operation. Typically, conversion is only required when the data contains square brackets. If no value is entered in the Conversion Table field, the data being copied is converted using the default conversion table (BPXFX000) in the standard library concatenation. By default, this would cause a conversion between code pages IBM-037 and IBM-1047. Otherwise the value in the Conversion Table field identifies a conversion table to be used for the copy operation.

Note: This option is ignored when copying to another z/OS UNIX file.

Conversion Table
These types of values can be specified in this field:

- *data_set_name*(*member_name*)

  The partitioned data set and member containing the character conversion table.
- *data_set_name*

  The partitioned data set that has the member BPXFX000 containing the character conversion table.
- (*member_name*)

  The member containing the character conversion table. It is assumed to be in a data set in the standard library concatenation. (The default data set is SYS1.LINKLIB.)

  Note: This field is ignored if the Convert option is not selected or if copying from another z/OS UNIX file.

For further information on the character conversion table refer to the description of the OPUT command in the *z/OS UNIX System Services Command Reference*.

Copying into a directory: When the CI line command is entered against a directory, the Copy Into z/OS UNIX Directory panel is displayed.

```
                        Copy Into z/OS UNIX Directory
Command ===> ____________________________________________________________
                                                          More:     +
Into z/OS UNIX directory:
  Name . . . : /u/mburns/abcdir1

From partitioned data set:
  Name . . . . EXEC ____________________________________

Permissions    777
Suffix . . . . ____________________

Options
  _  Replace like-named files
  _  Update permissions for replaced files
  /  Selection list...
  /  Convert to lowercase
  _  Binary copy
  _  Convert

Conversion Table ____________________________________________________
 F1=Help       F2=Split      F3=Exit       F4=Expand     F7=Backward
 F8=Forward    F9=Swap      F10=Actions   F12=Cancel
```

Figure 171. Copy Into z/OS UNIX Directory panel (ISRUULRD)

This panel allows you to copy the data from members of a partitioned data set into regular files in a directory.

Note: ISPF invokes the z/OS UNIX OPUT command to perform the operation of copying data from a member of a partitioned data set into a regular file.

The panel displays the path name of the directory into which the members of the partitioned data set will be copied. These mandatory input fields are displayed on this panel:

Name The name of an existing partitioned data set containing the members that will be copied as regular files into the selected directory.

Permissions
Defines the permissions for new regular files created when copying a partitioned data set member in the directory. When the option "Update permissions for replaced files" is selected, it also defines new permissions applied to a file replaced during the copy operation. Enter as three octal (range 0-7) digits. The first digit defines the access permission for the file owner. The second digit defines the access permission for any member of the file's group. The third digit defines the access permission for anyone else. See Table 17 on page 269.

These optional input fields are available on this panel:

Suffix This field allows you to specify a value that will be added to the end of the member name to form the file name of the regular file that is created or updated during the copy operation. The member name and suffix are separated by a period (.). Any leading periods specified in the suffix are ignored.

Replace like-named files
When this option is selected, if the file into which the data from a selected member is to be copied already exists in the directory, the contents of the existing file will be overwritten with the data from the selected member. If this option is not selected, the copy of that member will not be performed.

Update permissions for replaced files
When this option is selected it causes existing files that are replaced by the copy operation to also have their permissions changed to the value specified in the Permissions field.

Selection List
If this option is selected, the Copy Into z/OS UNIX Directory - Selection List panel is displayed. This panel displays a list of the members in the partitioned data set that can be selected for copying into the directory. The list contains these fields:

S
An input field where you can enter S to indicate the associated member is to be copied into the directory.

Member
The name of the partitioned data set member that can be copied into the directory.

Filename
The name to be used for the regular file into which the data from the associated member will be copied. This is an input field, allowing you to change the file name to something other than the name assigned by ISPF. The field is scrollable and is 1023 bytes long. Use the EXPAND function key (F4) to display the entire field in a pop-up window.

Message
This field displays a message indicating the result of copying the member to the regular file. The possible values displayed are:

***COPIED**
The data from the member was successfully copied to a new regular file in the directory.

***REPL**
The data from the member was copied to an existing regular file in the directory. The data in the file was overwritten. This can only occur when the Replace like-named files option is selected on the Copy Into z/OS UNIX Directory panel.

***NO-REPL**
The data from the member was not copied to the file in the directory because the file already existed and the Replace like-named files option was not selected on the Copy Into z/OS UNIX Directory panel.

FAILED RC=xx*
The OPUT command invoked to copy the data from the member to the regular file failed with return code *xx*. The data was not copied.

When you press Enter on this panel, the selected members will be copied to the directory. The Message field indicates the result of the copy operation for each member.

Convert to lowercase
When this option is selected it causes the member name to be converted to lowercase before it is used to generated the file name for the target regular file.

Binary copy
When this option is selected it indicates the members being copied

contains binary data. This causes the copy to take place without any consideration for newline characters or the special characteristics of DBCS data. If this option is not selected the members are assumed to contain TEXT data.

Convert
This option specifies whether data conversion is required during the copy operation. Typically, conversion is only required when the data contains square brackets. If no value is entered in the Conversion Table field, the data being copied is converted using the default conversion table (BPXFX000) in the standard library concatenation. By default, this would cause a conversion between code pages IBM-037 and IBM-1047. Otherwise the value in the Conversion Table field identifies a conversion table to be used for the copy operation.

Conversion Table
These types of values can be specified in this field:

- *data_set_name*(*member_name*)

  The partitioned data set and member containing the character conversion table.

- *data_set_name*

  The partitioned data set that has the member BPXFX000 containing the character conversion table.

- (*member_name*)

  The member containing the character conversion table. It is assumed to be in a data set in the standard library concatenation. (The default data set is SYS1.LINKLIB.)

  Note: This field is ignored if the Convert option is not selected.

  For further information on the character conversion table refer to the description of the OPUT command in the *z/OS UNIX System Services Reference*.

I—information

The I (information) line command can be entered against any directory entry.

Information display for non-link files: When entered against any directory entry type apart from symbolic and external links, the z/OS UNIX File Information panel is displayed. Figure 172 on page 287 shows an example.

```
  Modify
_____________________________________________________________________________
                          z/OS UNIX File Information
Command ===> ______________________________________________________________
                                                                More:     +
Pathname  . . : /SYSTEM/etc/profile

General Data                                Mode Fields
 File Type . . : File                        Permissions . : 755
 File Size . . : 10665                       Set User ID . : NO
 Links . . . . : 1                           Set Group ID  : NO
 Inode . . . . : E0                          Sticky Bit  . : NO
 File Format . : ----
 Last Modified : 2003/07/10 03:21:51        Extended Attributes
 Last Changed  : 2003/07/10 03:22:40         Shared AS . . : YES
 Last Accessed : 2006/04/05 01:20:34         APF Auth  . . : NO
 Created . . . : 2003/07/10 03:18:18         Pgm Control . : NO
 CCSID . . . . :                             Shared Lib  . : NO
 Text Convert  : NO
                                            Audit
Owner                                        Auditor . . . : ---
 File  . . . . : IBMUSER(0)                  User  . . . . : fff
 F1=Help      F2=Split     F3=Exit      F4=Expand    F7=Backward  F8=Forward
 F9=Swap     F10=Actions  F12=Cancel
```

Figure 172. z/OS UNIX File Information panel (ISRUULIN)

This panel displays information describing the attributes of a z/OS UNIX file. The Pathname field displays the path name of the selected z/OS UNIX file.

The General Information section of the panel displays these fields:

File Type
The type of z/OS UNIX file. The possible values are:
Dir Directory
File Regular file
Char Character special file
FIFO FIFO (first-in-first-out) special file

Size The file size, in bytes.

Links For a file, the number of hard links to the file. For a directory, the number of subdirectories.

Inode File identification number, unique within the file system.

File Format
File format for regular files. The possible values are:

---- Not specified

bin Binary data

nl New line

cr Carriage return

lf Line feed

crlf Carriage return followed by line feed

lfcr Line feed followed by carriage return

crnl Carriage return followed by new line

Last Modified
The date and time the file was last changed.

Last Changed
The date and time the status of the file was last changed.

Last Accessed
The date and time the data in the file was last accessed.

Created
The date and time the file was created.

CCSID
The coded character set identifier assigned to the file for Enhanced ASCII support.

Text Convert
A value of YES indicates the file is enabled for Enhanced ASCII automatic conversion. NO indicates the file is not enabled for automatic conversion.

The Owner section of the panel displays these fields:

File The user ID and UID number of the owner of the file or directory.

Group The group name and GID number of the owner of the file or directory.

The Mode Fields section of the panel displays these fields:

Permissions
The file or directory permissions, in octal format. If there are extended access control list (ACL) entries defined for the file or directory, + is displayed after the octal value.

Set User ID
A value of ON indicates the SETUID bit is on causing the effective user ID of the user process executing a program to be set to that of the file owner when this file is run.

Set Group ID
A value of ON indicates the SETGID bit is on causing the effective group ID of the user process executing a program to be set to that of the file owner when this file is run.

Sticky Bit
A value of ON indicates the sticky bit for the file or directory is set on. For files that are programs this causes z/OS UNIX to search for the program in the user's STEPLIB, the link pack area, or the link list concatenation. For a directory it means a user can only remove or rename a file or remove a subdirectory if one of these conditions is true:

- The user owns the file or subdirectory
- The user owns the directory
- The user has superuser authority

The Extended Attributes section of the panel displays these fields:

Shared AS
A value of YES indicates that the program can run in a shared address space.

APF Auth
A value of YES indicates that the program can run APF authorized if it has been linked with AC=1.

Pgm Control
A value of YES indicates that the program can run as if it were from a program controlled library.

Shared Lib
A value of YES indicates that the program is loaded as a system shared library program.

The Audit section of the panel displays these fields:

Auditor
Shows the audit criteria for this file as defined by a user with auditor authority. The value shows three characters describing the audit bit settings for read, write, and execute (search) access. The possible values for each character are:
s Audit successful access attempts
f Audit failed access attempts
a Audit all access attempts
- No audit

User Shows the audit criteria for this file as defined by the file owner or a superuser. See the Auditor field for the possible values displayed.

The Device Data section of the panel displays these fields:

Device Number
A hexadecimal number that uniquely identifies the mounted file system for this file.

Major Device
For a character special file, this is a number that identifies the device type. The possible values are:

1 Master pseudo-TTY device, which is tied to a slave device by the minor number

2 Slave pseudo-TTY device, which is tied to a master device by the minor number

3 Controlling terminal TTY

4 Null file

5 File descriptor file, which is tied to a file descriptor by the minor number

6 UNIX domain socket name special file

9 System console file

Minor Device
A number that identifies a specific device of a given device type.

The Modify action bar choice provides these options:

Mode Fields
Displays the Modify z/OS UNIX File Mode Fields panel where you can update the mode fields for the currently displayed file.

Extended Attributes
Displays the Modify z/OS UNIX File Extended Attributes panel where you can update the extended attributes for the currently displayed file.

Information display for link files: When the I line command is entered against a symbolic or external link file, the z/OS UNIX Symbolic Link Information panel is displayed. Figure 173 shows an example.

```
                    z/OS UNIX Symbolic Link Information
Command ===> ____________________________________________________________

Pathname  . . . : /SYSTEM/etc/ioepdcf

General Data
 External Link : NO
 File Size . . : 22
 Links . . . . : 1
 Inode . . . . : 7
 Last Modified : 2002/11/20 19:30:53
 Last Changed  : 2002/11/20 19:30:53
 Last Accessed : 2002/11/20 19:30:53
 Created . . . : 2002/11/20 19:30:53

Owner
 File  . . . . : IBMUSER(0)
 Group . . . . : OMVSGRP(1)

Symbolic Link -
 ../etc/dfs/etc/ioepdcf

 F1=Help      F2=Split     F3=Exit      F4=Expand    F7=Backward  F8=Forward
 F9=Swap     F10=Actions  F12=Cancel
```

Figure 173. z/OS UNIX Symbolic Link Information panel (ISRUULIS)

This panel displays information describing the attributes of a z/OS UNIX symbolic or external file. The Pathname field displays the path name of the selected symbolic or external link file.

The General Information section of the panel displays these fields:

External Link
A value of YES indicates the file is an external link to an object outside of the file system. A value of NO indicates the file is a link to another file or a directory.

Size The file size, in bytes.

Links The number of hard links to the file.

Inode File identification number, unique within the file system.

Last Modified
The date and time the file was last changed.

Last Changed
The date and time the status of the file was last changed.

Last Accessed
The date and time the data in the file was last accessed.

Created
The date and time the file was created.

The Owner section of the panel displays these fields:

File The user ID and UID number of the owner of the file or directory.

Group The group name and GID number of the owner of the file or directory.

The Symbolic Link field is a scrollable field that displays the path name or external name to which this symbolic link file refers.

MM—modify mode fields

The MM (modify mode) line command can be entered against any file type apart from symbolic and external link files. This line command causes the Modify z/OS UNIX File Mode Fields panel to be displayed. This panel allows you to modify mode fields for the selected z/OS UNIX file.

The Pathname field displays the path name of the selected file. The Type field display the file type for the selected file.

These optional input fields allow you to make modifications to the mode of the file:

Permissions
This field allows you to change the permissions defined for the file. The current permissions for the file are initially displayed. The permissions are displayed and entered as three octal (range 0-7) digits. The first digit defines the access permission for the file owner. The second digit defines the access permission for any member of the file's group. The third digit defines the access permission for anyone else. See Table 17 on page 269.

Set UID bit
When this option is selected, the file mode SETUID bit is set on. When the option is not selected, the SETUID bit is set off. If the SETUID bit is on, the effective user ID of the user process executing a program will be set to that of the file owner when this file is run.

Set GID bit
When this option is selected, the file mode SETGID bit is set on. When the option is not selected, the SETGID bit is set off. If the SETGID bit is on, the effective group ID of the user process executing a program will be set to that of the file owner when this file is run.

Sticky bit
When this option is selected, the file mode sticky bit is set on. When this option is not selected, the sticky bit is set off. If the sticky bit is on for a file that is a program, z/OS UNIX will search for the program in the user's STEPLIB, the link pack area, or the link list concatenation. If the sticky bit is on for a directory it means a user can only remove or rename a file or remove a subdirectory if one of these conditions is true:

- The user owns the file or subdirectory
- The user owns the directory
- The user has superuser authority

MX—modify extended attributes

The MX (Modify eXtended) line command can be entered against regular files in the directory list. This line command causes the Modify z/OS UNIX File Extended Attributes panel to be displayed. This panel allows you to modify the extended attributes for the selected z/OS UNIX regular file. These attributes only affect files that are programs.

The Pathname field displays the path name of the selected file. The Type field display the file type for the selected file.

These optional input fields allow you to modify the extended attributes:

Use Shared Address Space
When this option is selected, ISPF sets the extended attribute that makes the program eligible to run in a shared address space.

APF Authorized
When this option is selected, ISPF sets the extended attribute that makes the program eligible to run APF-authorized if it has been linked with AC=1.

Program Controlled
When this option is selected, ISPF sets the extended attribute that makes the program eligible to run as if it were from a program controlled library.

Shared Library
When this option is selected, ISPF sets the extended attribute that causes the program to be loaded from the system shared library region.

VA—view ASCII file

The VA (View - ASCII) line command can be entered against a regular file that contains data encoded in ASCII and the file is not tagged with a CCSID of 819. The ISPF editor is invoked with the ASCII edit facility which converts the ASCII data to the CCSID of the terminal, allowing you to view the ASCII data in file. If the V line command is used and the file is tagged with a CCSID of 819, ISPF invokes the ASCII edit facility.

X—execute command

The X (eXecute command) line command can be entered against regular files, directories, or symbolic links to regular files or directories in the directory list. This line command causes the Execute Command for z/OS UNIX File panel to be displayed.

This panel allows you to enter and execute a z/OS UNIX command, TSO command, CLIST, or REXX EXEC, with the path name of the selected file being passed as a parameter.

The Pathname field displays the path name of the selected file.

These input fields allow you to specify the command and select the method by which it is run:

Command for file
Use this field to enter the z/OS UNIX command, TSO command, CLIST, or REXX exec to be run.

By default, ISPF appends the path name of the selected file to the end of the command you have entered. If you need to have the path name in a position other than the end of the command, use the path name substitution character to indicate where you want the path name to be placed. The default pathname substitution character is ! (exclamation point). For more information about using this symbol, see “Using the path name substitution character” on page 273.

The path name substitution character can also be changed using the Directory List Options panel (see page 297).

If the command is to run in z/OS UNIX by selecting a Run method of Direct or Login shell, then this field can be left blank. This causes the selected file to be executed.

Run method
This field is mandatory. It allows you to select one of these methods for running the command:

Direct Causes the command to be run in z/OS UNIX.

Login shell Causes the command to be run under the login shell in z/OS UNIX.

TSO Causes the command to be passed to TSO for execution.

z/OS UNIX command time limit
This field allows you to set a limit to the amount of time the command can run. This time limit is entered as a number of seconds. If this limit is exceeded, ISPF sends a SIGKILL signal to the process running the command to terminate execution. If you do not want a time limit set, leave the field blank or enter a value of zero.

The time limit value can also be specified on the Directory List Options panel (see page 297).

z/OS UNIX directory list utility primary commands

These topics describe the primary commands available when using the z/OS UNIX Directory List Utility:

- "EDIT command"
- "FIND and RFIND commands"
- "LEFT command" on page 294
- "LOCATE command" on page 294
- "REFRESH command" on page 295
- "RESET command" on page 295
- "RIGHT command" on page 295
- "SAVE command" on page 295
- "SORT command" on page 296
- "SU command" on page 297

EDIT command

The EDIT primary command is used to edit a file in the directory currently listed. Use this format:

```
EDIT filename
```

The command can be abbreviated as E or EA. If EA is used, the editor is invoked with the ASCII edit feature.

For example, if the command shown here was entered while displaying the directory list for u/myhome it would invoke Edit for the file with a path name of /u/myhome/prog1:

```
E prog1
```

ISPF calls the OEDIT command to edit the file. If the file specified on the EDIT command does not exist in the directory, OEDIT is still called and can be used to create a new file in the directory.

FIND and RFIND commands

The FIND primary command is used to find and display the next occurrence of a character string in the list of file names. Use this format:

```
FIND string [NEXT]
            [ALL]
            [FIRST]
            [LAST]
            [PREV]
```

The command can be abbreviated as F.

For example, this command would tell ISPF to find all occurrences of the character string dat1:

```
F dat1 ALL
```

For more information about the operands used with this command, see "FIND—find character strings" on page 85.

ISPF automatically scrolls to bring the character string to the top of the directory list. To repeat the search without re-entering the character string, use the RFIND command.

Note: The RFIND search starts from the second file on the current directory list screen. It is not cursor-sensitive.

LEFT command

The LEFT primary command scrolls the columns displaying information for the directory list to the left. These columns do not include the Filename and Message columns, which are fixed as the left-hand columns of the Directory List display. Use this format:

```
LEFT [Page|Max|n]
```

where:

Page Specifies to scroll left by the number of columns of data (not counting the fixed fields) that can be displayed within the current screen width. This is the default. P can be used as an abbreviation.

Max Specifies to scroll left so that the first column of data is displayed in the leftmost position. M can be used as an abbreviation.

n Is a numeric value specifying the number of columns to be scrolled to the left.

Note: If you issue the LEFT command while the cursor is positioned in a scrollable field such as the Filename field, ISPF will scroll the scrollable field and the directory list columns will not be scrolled to the left.

LOCATE command

The LOCATE primary command scrolls the directory list based on the field on which the directory list is sorted, as described under "SORT command" on page 296. Use this format:

```
LOCATE lparm
```

You can use the *lparm* operand with the LOCATE command for either of these situations:

- If the list is sorted by the Filename field, specify a file name.
- If the list is sorted by another field, specify a value for the field by which the list is sorted.

The command can be abbreviated as L.

For example, for a directory list sorted by type, you could enter:

```
L Syml
```

This command locates the first symbolic link file in the directory list. If the value is not found, the list is displayed starting with the entry before which the specified value would have occurred.

REFRESH command

The REFRESH primary command updates the display of the directory list to whatever the list's current state is. For example, after deleting several items on the list, REFRESH causes the list to be displayed without the deleted items. ISPF rebuilds the directory list display by re-reading the entries for the directory.

The command can be abbreviated as REF

RESET command

The RESET primary command removes any pending line commands and messages from the directory list.

The command can be abbreviated as RES.

RIGHT command

The RIGHT primary command scrolls the columns displaying information for the directory list to the right. These columns do not include the Filename and Message columns, which are fixed as the left-hand columns of the Directory List display. Use this format:

```
RIGHT [Page|Max|n]
```

where:

Page Specifies to scroll right by the number of columns of data (not counting the fixed fields) that can be displayed within the current screen width. This is the default. P can be used as an abbreviation.

Max Specifies to scroll right so that the first column of data is displayed in the rightmost position. M can be used as an abbreviation.

n Is a numeric value specifying the number of columns to be scrolled to the right.

Note: If you issue the RIGHT command while the cursor is positioned in a scrollable field such as the Filename field, ISPF will scroll the scrollable field and the directory list columns will not be scrolled to the right.

SAVE command

The SAVE primary command writes the directory list to the ISPF list data set or to a sequential data set. ISPF writes the directory list in its current sort order. Use this format:

```
SAVE [list-id]
```

where *list-id* is an optional user-specified qualifier of the data set to which the directory list will be written. ISPF names the data set *prefix.userid.list-id*`.DIRLIST` where:

prefix Your data set prefix, as specified in your TSO user profile. If you have no

prefix set, or if your prefix is the same as your user ID, the prefix is omitted and the data set name will be: *userid.list-id*.DIRLIST

userid Your TSO user ID.

If the data set does not exist it is created. If the data set already exists and has compatible attributes it is overwritten. If you omit the *list-id* operand, the list is written to the ISPF list data set.

This command would tell ISPF to write the list to a sequential data set named either *prefix.userid*.MY.DIRLIST or *userid*.MY.DIRLIST:

```
SAVE MY
```

If the sequential data set already exists, ISPF overwrites it; if not, ISPF creates it.

SORT command

The SORT primary command sorts the directory list by the specified field. Use this format:

```
SORT [field1 [A|D] [field2] [A|D]]
```

where:

field1 The major sort field. If omitted, Filename is assumed.

field2 The minor sort field. If both operands are used, ISPF sorts the list by *field1* first, then by *field2* within *field1*.

A | D Specifies the sort sequence for the associated sort field (A=ascending; D=descending). By default, character fields are sorted alphabetically and numeric fields are sorted in descending order.

For example, to sort a directory list by file type and then in descending order by modification date and time within each file type, use this command:

```
SORT TYPE MODIFIED
```

This table identifies the sort field names and associated sort sequence:

Field	Sequence	Description
FILENAME | FILE | NAME	Ascending	File name
MESSAGE | MES	Ascending	Command message
TYPE	Ascending	File type
PERM	Ascending	Permissions
PERMO	Descending	Permissions (octal)
AUDIT | AUD	Ascending	Audit bit settings
EXTA | EXT	Ascending	Extended attributes
FORMAT | FMAT	Ascending	File format
OWNER | OWN	Ascending	File owner
GROUP | GRP	Ascending	Owner group
LINKS	Descending	File links
SIZE	Descending	File size
MODIFIED | MOD	Descending	Date/time file last changed
CHANGED | CHG	Descending	Date/time file status last changed
ACCESSED | ACC	Descending	Date/time file status last accessed
CREATED | CRE	Descending	Date/time file was created

SU command

The SU primary command allows you to switch to super-user mode (UID 0) or switch back to your initial UID.

For more details, see "Switching UIDs with the SU primary command" on page 299.

z/OS UNIX directory list options panels

These topics describe the panels available through the Options pull-down menu:

- "z/OS UNIX Directory List Options panel"
- "z/OS UNIX Directory List Column Arrangement panel" on page 298

z/OS UNIX Directory List Options panel

This panel allows you to set and save options that change the behaviour of z/OS UNIX Directory List Utility functions. This panel contains these optional input fields:

Width of filename column

Use this field to define the width of the column used to display file names in the directory list. The minimum value you can specify is 8. The maximum value is 30.

Note: The panel field used for the Filename column is defined as scrollable.

Path name substitution character

This field defines the character that can be used to represent the full path name of a selected file. This character shows the position of the file name when it is specified as an argument in a z/OS UNIX command, TSO command, CLIST, or REXX exec. The substitution character can be used with commands that are invoked either as a line command in the directory list or through the Execute Command for z/OS UNIX File panel (see "X—execute command" on page 292). The default character is ! (exclamation point).

z/OS UNIX command time limit

This field allows you to set a limit to the amount of elapsed time for a z/OS UNIX command run either directly or under the login shell. z/OS UNIX commands can be invoked via the X line command (see "X—execute command" on page 292) or by using the line command prefix characters < (direct) or > (login shell) (see "z/OS UNIX commands, TSO commands, CLISTs, and REXX EXECs" on page 271). If the time limit set is exceeded by a z/OS UNIX command, ISPF sends a SIGKILL signal to the process running the command to terminate execution.

If you do not want to set a time limit, leave the field blank or enter a value of zero.

Confirm File Delete

This option controls the display of the Confirm Delete panel. This panel is displayed when you use the directory list line command "D" to delete files or empty directories. When this option is selected, the Confirm Delete panel is displayed. When this option is not selected, the panel is not displayed and the file or empty directory is deleted without any additional user interaction.

Confirm Non-empty Directory Delete

This option controls the display of the Confirm Non-empty Directory

Delete panel. This panel is displayed when you use the directory list line command “D” to delete a directory that contains files and sub-directories. When this option is selected, the Confirm Non-empty Directory Delete panel is displayed. When this option is not selected, the panel is not displayed and the directory (including all contained files and sub-directories) is deleted without any additional user interaction.

Bypass z/OS UNIX File Edit Options panel
When this option is selected, ISPF will not display the z/OS UNIX File Edit Options panel when the directory list line command “E” is used to edit a regular file. When this option is not selected, this panel, which allows you to specify an edit profile and initial edit macro, will be displayed before editing a regular file.

Display permissions in octal format
When this option is selected, permissions for files in the directory list are displayed in octal format. When this option is not selected, permissions are displayed in symbolic format.

z/OS UNIX Directory List Column Arrangement panel

This panel allows you to alter the order and width of the columns displayed on the directory list panel. It lists each column in the z/OS UNIX Directory List. These fields are displayed for each entry:

Restore default column arrangements
Selecting this option allows you to reset the Order and Width values used to format the directory list display to their default values.

Order This input field displays the current ordinal position for the column on the directory list display. You can update the value in this field to alter the position of this column on the directory list display. For example, to move the Owner field to be the second column displayed, type `02` over its current Order number and press Enter. The list of Columns is rearranged to show the Owner field in the second position. When you next display a directory list, the columns are shown in the new order:

```
Pathname . : /

Command  Filename        Message          Type Owner    Permission Audit  Ext
-------------------------------------------------------------------------------
         bin                               Dir  IBMUSER  rwxr-xr-x  fff---
         dev                               Syml IBMUSER  rwxrwxrwx  fff---
         etc                               Syml IBMUSER  rwxrwxrwx  fff---
```

Column
This output field displays the heading for the column on the directory list display.

Width This input field displays the current width for the field for the column on the directory list display. You can update this value to increase or decrease the size of the field for the column. Setting the width value to 0 (zero) means the column will not be displayed in the directory list.

Maximum
This output field displays the maximum value that can be entered in the Width field.

Use of scrollable fields for path names

Because path names can be up to 1023 characters in length, ISPF uses scrollable fields throughout the z/OS UNIX Directory List Utility for the display and entry of path names.

For path name output fields, if a + (scroll indicator) is displayed to the right of the path name it indicates that the path name is larger than the display field length. The RIGHT primary command can be used to view more of the path name by scrolling the value right. Use the EXPAND function key (F4) to display the entire path name field in a pop-up window.

For path name input fields the + scroll indicator is always displayed to the right of the path name, indicating that you can enter a path name larger than the input field length. The RIGHT primary command can be used to obtain more input space by scrolling the value right. Use the EXPAND function key (F4) to display the entire path name input field in a pop-up window.

Switching to super-user (UID 0) mode and back

On the entry panel and the directory list display panel, you can switch to super-user mode (UID 0) or switch back to your initial UID with either:

- The Options pull-down menu, or
- The SU primary command

Switching UIDs with the Options pull-down menu

The Options pull-down menu available on the entry panel and the directory list display panel provides an option that lets you switch to super-user mode (UID 0) or switch back to your initial UID.

When you are operating under your UID, the Options pull-down menu displays this option:

```
3. Enable superuser mode(SU)
```

Note: If you select this option, and you have permission to the BPX.SUPERUSER facility class, you are switched to UID 0 (super-user mode).

When you are operating in super-user mode, the Options pull-down menu displays this option:

```
3. Reset UID to nnn
```

If you select this option, you are switched back to your UID *nnn*.

Switching UIDs with the SU primary command

From the entry or directory list panels, you can switch to super-user mode (UID 0) or switch back to your initial UID with the SU primary command. Use this format:

Syntax

```
►►─SU──┬──────────┬──────────────────────────────────────────►◄
       └─UIDnum───┘
```

where:

UIDnum
The UID to which you you want to switch.

Note: To switch to another UID, you must have permission to the BPX.DAEMON facility class (if defined).

If you do not specify a UID number, you are switched either to UID 0 (if you are currently operating under your UID), or reset back to your UID (if you are currently operating in super-user mode).

Chapter 6. Foreground (option 4)

The Foreground option (4) allows ISPF to run the foreground processors shown on the Foreground Selection panel, Figure 174. All these processors except for COBOL interactive debug, SCRIPT/VS, and FORTRAN interactive debug are also available with the Batch option (5).

When you run a foreground processor, you must wait until the processor ends before doing anything else with ISPF. If you want to use ISPF while waiting for the processor to end, submit the input as a batch job. You can do this by using the Batch option if the processor you need is listed on the Batch Selection panel, Figure 193 on page 335.

```
  Menu  Utilities  Help
 ------------------------------------------------------------------------
                           Foreground Selection Panel

1    Assembler                          11  *FORTRAN debug
2    COBOL                              12   Member Parts List
3    VS FORTRAN                         13  *C/370
5    PL/I                               14  *REXX/370
6    VS PASCAL                          15  *ADA/370
7   *Binder/Link editor                 16  *AD/Cycle C/370
9    SCRIPT/VS                          18   ISPDTLC
10  *VS COBOL II debug                  19  *OS/390 C/C++
10A *OS/VS COBOL debug

    Enter "/" to select option          * No packed data support
    _   Source Data Packed




Option ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 174. Foreground Selection Panel (ISRFPA)

The names of the foreground processors on this panel are point-and-shoot fields. For more information, see the Point-and-Shoot Text Fields section of the ISPF User Interface topic of the *z/OS ISPF User's Guide Vol I*.

Foreground selection panel action bar

The Foreground Selection Panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down provides general information about

© Copyright IBM Corp. 1980, 2007

foreground processing as well as information about each available choice on the Foreground Selection Panel.

Foreground processing sequence

This topic describes the main sequence for foreground processing.

1. If you do not know whether the source data is in packed format, find out by editing the data set and entering the PROFILE command. If the source data is in packed format, the profile shows PACK ON.

   If the data is packed, select the Source Data Packed option. If the data is not packed, deselect this option.

   Also, you should read "Expanding packed data" on page 305, paying close attention to:

   - Information that applies to the foreground processor you plan to use
   - The difference between expanding a sequential data set and expanding members of a partitioned data set.

   When you are satisfied that the data set is ready to be processed, continue with the next step.
2. Select one of the foreground processors listed at the top of the Foreground Selection panel shown in Figure 174 on page 301.

   Note: A region size of 2 megabytes or more will probably be required to run the VS FORTRAN compiler in the foreground.
3. Select the Source Data Packed option to tell ISPF if it needs to expand the source data.

   Note: The Source Data Packed option has no effect on the Member parts list option (4.12). Member parts list can read both packed and unpacked data sets, so no expansion is needed.
4. When the Session Manager licensed program, 5740-XE2, is installed, you can select the Session Manager mode option on the ISPF Settings panel so that you enter Session Manager mode when you call any of the foreground processors. Once you call Session Manager, it stays in effect for all logical screens until you turn it off. For example, if you call Session Manager and then split the screen, Session Manager will be in effect on both logical screens.

   Note: If graphics interface mode is active, Session Manager does not get control of the screen. Graphics interface mode is started when a GRINIT service has been issued, but a GRTERM service has not been issued. See *z/OS ISPF Services Guide* for more information about these two services.
5. Press Enter. ISPF displays the data entry panel for the processor you selected. The remainder of this processing sequence applies to all foreground processors except SCRIPT/VS, VS COBOL II interactive debug, COBOL interactive debug, and Member Parts List. For these processors, use the sequence referred to in this list:

Processor	Reference
SCRIPT/VS	"SCRIPT/VS processor (option 4.9)" on page 318
VS COBOL II interactive debug	"VS COBOL II interactive debug (option 4.10)" on page 325
COBOL interactive debug	"OS/VS COBOL debug (option 4.10A)" on page 325

Processor	Reference
Member parts list	"Member parts list (option 4.12)" on page 329

6. Enter the appropriate ISPF library and concatenation sequence or data set name. If the input data set is partitioned, you can leave the member name blank or use a pattern to display a member list. If you need help, see:
   - The Naming ISPF Libraries and Data Sets section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for help in entering library or data set names
   - The Displaying Member Lists section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for information about patterns and displaying member lists
   - "Input data sets" on page 308 for information about the regular concatenation sequence
   - "Object data sets" on page 310 for information about object modules
   - "Linkage editor concatenation sequence" on page 318 for help with the linkage editor concatenation sequence

   VS FORTRAN has no LIB option, which some foreground processors use to specify the input data set concatenation sequence. Therefore, the concatenation sequence specified in the Group fields is used to find the member to be compiled.

   For FORTRAN interactive debug, the TYPE, or last qualifier, must be either OBJ or LOAD. However, if you specify an OBJ data set as your input data set, you must include a load library or data set in the input search sequence (see step 11).
7. This step applies to FORTRAN interactive debug only. Use the Source Type field to tell ISPF the Type, or last qualifier, of the data set used to create the input object module or load module.
8. Use the List ID field to tell ISPF what to name the output listing. See "List data sets" on page 309 for more information.
9. Enter your password in the Password field if your input data set is password-protected. See "Password protection" on page 310 for more information.
10. The Option field, whether ASSEMBLER, COMPILER, LINKAGE EDITOR, or DEBUG, is remembered from one session to another. Therefore, you do not need to change this field unless the options you need are not displayed.

    Be careful not to enter any options that ISPF generates automatically. These options are listed on the data entry panel. For more information about the options available for your processor, refer to the documentation supplied with that processor.
11. Enter any additional input libraries you need. For FORTRAN interactive debug, enter any input LOAD libraries that you need to complete the search sequence. These libraries must be LOAD libraries only. See "Input data sets" on page 308 if you need help.
12. Once all the input fields have been specified, press Enter to call the foreground processor.

    If the Session Manager is installed and you selected Session Manager mode on the ISPF Settings panel, the foreground processor and all function keys and PA keys are under the control of the Session Manager. When foreground processing is complete, you are prompted to enter a null line to return to ISPF control.

If the Session Manager is not called, the PA and function keys have their usual TSO-defined meanings; generally, the function keys are treated the same as the Enter key.

13. Communication with foreground processors is in line-I/O mode. Whenever you see three asterisks, press Enter.
14. If the foreground processor generated an output listing, the listing is displayed automatically in Browse mode.

    Note: If a Foreground processing program ends abnormally, ISPF displays a message in the upper-right corner of the screen and does not enter Browse mode. The list data set is retained, but the Foreground Print Options panel (see step 15) is not displayed.

    You can scroll the output up or down using the scroll commands. All the Browse commands are available to you. When you finish browsing the listing, enter the END command.
15. An optional print utility exit routine can be installed by your system programmer. If this exit routine is installed, it may cause the Foreground option's response to differ from the descriptions shown here. See *z/OS ISPF Planning and Customizing* for more information about the print utility exit.

    Another factor that can affect the performance of the Foreground option is whether the TSO/E Information Center Facility is installed. If the TSO/E Information Center Facility is installed, your installation can optionally allow ISPF to display a panel for submitting TSO/E Information Center Facility information with the print request. See Figure 176 on page 311 for an example of this panel and "Using the TSO/E information center facility" on page 183 for information about the fields on this panel. If the TSO/E Information Center Facility is not installed, the Foreground option displays the panel shown in Figure 175 to allow you to print, keep, or delete the output.

```
                         Foreground Print Options

  PK  Print data set and keep          K  Keep data set (without printing)
  PD  Print data set and delete        D  Delete data set (without printing)

  If END command is entered, data set is kept without printing.

Data set name . :

Print mode  . . . BATCH              (Batch or Local)

Batch SYSOUT class . . _____________
Local Printer id or
      writer-name. . . _______________  (For local printer)
Local SYSOUT class . . _____________

Job statement information:           (Required for system printer)
  ===> ________________________________________________________________________
  ===> ________________________________________________________________________
  ===> ________________________________________________________________________
  ===> ________________________________________________________________________
Option  ===> ____________________________________________________________________
 F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 175. Foreground Print Options panel (ISRFPPRT)

On this panel, the "Data set name" field shows the name of the list data set that contains the output generated by the processor you selected. In the

Option field, enter one of the options shown at the top of the panel. The "Print mode", "Batch SYSOUT class", "Local Printer id or writer name", and Local SYSOUT Class fields on this panel are described under "Hardcopy utility (option 3.6)" on page 180. The "Job statement information" field is described under the Job Statement Information section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

When you press Enter, the processor entry panel is displayed again. A message indicating completion of the process is displayed in the upper-right corner of the screen.

16. You can perform one of these actions:
    - Enter other parameters and call the same processor.
    - Enter the END command to return to the Foreground Selection panel and select another processor.
    - Enter the RETURN command to go to the ISPF Primary Option Menu.
    - Use the jump function (=) to choose any primary option.

Expanding packed data

Packed data is data in which ISPF has replaced any repeating characters with a sequence showing how many times the character is repeated. Packing data allows you to use direct access storage devices (DASD) more efficiently because the stored data occupies less space than it would otherwise.

If the source data that you want to process is packed, it must be expanded before it can be successfully processed by any of the language processors. Which expansion method you should use depends on whether your source data is:

- A sequential data set that contains expansion triggers

  An *expansion trigger* is a keyword that tells ISPF to expand additional data before copying, including, or imbedding it in the source data. Examples are INCLUDE and COPY statements, and SCRIPT .IM (imbed) control words. For information about defining your own expansion triggers, refer to *z/OS ISPF Planning and Customizing*.

  ISPF does not recognize expansion triggers in data stored as a sequential data set. Therefore, for this type of data, you should follow these steps:

  1. Manually expand the data that is to be copied, included, or imbedded in your source data. To do this, edit the source data, enter the PACK OFF command, and then save the data. When you have finished processing the data, you can repack it by editing it again and entering PACK ON.
  2. Select the Source Data Packed option before calling one of the language processors.

- Either of these:
  - A sequential data set that does not contain expansion triggers
  - Any member of a partitioned data set, either with or without expansion triggers.

  ISPF does recognize expansion triggers in data stored as members of a partitioned data set. Also, if your source data does not contain expansion triggers, you do not have to be concerned with them. Therefore, for these two types of data, select the Source Data Packed option before calling one of the language processors.

In each of the preceding situations, selecting the Source Data Packed option causes ISPF to expand packed source data before it is processed. For partitioned data sets,

any included members are also expanded inline where the INCLUDE or COPY statements, .IM SCRIPT control words, or other user-defined trigger statements are found.

Member expansion (ISRLEMX)

Member expansion uses simple language scanners to find expansion triggers. If you specify that the source data is not packed, the ISRSCAN program is used. However, if you specify that the source data is packed, member expansion uses the ISRLEMX program.

These scanners do not have all the sophistication of the actual language processors. Therefore, unusual code or code that does not compile cannot be successfully processed by member expansion. Examples are trigger statements:

- With comments that extend onto the next line
- That have compiler instructions to change the content of the code to be included.

Compiler control statements and symbolic substitution are not considered during member expansion. Instead, ISRLEMX creates a temporary data set to be used as input to the language processor. All members to be processed, including members imbedded with COPY, INCLUDE, or .IM statements, are copied into this data set, expanded, and passed on to the language processor. The temporary data set will have the same block size as the input data set that contains your source data.

When using languages that allow multiple compilations, such as VS FORTRAN, you must put the source statement that ends the program in your original, or top-level, program. This statement cannot be in an included member.

Table 18 shows the languages processed by member expansion, their expansion triggers, syntax, and the input columns processed for fixed-record data and variable-record data.

Table 18. Expansion triggers and syntax

Language	Expansion Trigger	Syntax	Input Columns Processed for F/FB Format	Input Columns Processed for V/VB Format
Assembler	`COPY`	`COPY name`	1 - 80	N/A
PL/I	`%INCLUDE`	`%INCLUDE DDNAME(name);` `%INCLUDE name;`	2 - 72	10 - 100
COBOL	`COPY`	`COPY name.`	7 - 72	N/A
VS FORTRAN	`INCLUDE`	`INCLUDE (name)`	1 - 72	N/A
Pascal	`%INCLUDE`	`%INCLUDE name;` `%INCLUDE DDNAME(name);`	1 - 72	1 - 100

SCRIPT	`.IM`	`.IM name`
		`.IM (name)`
		`.IM ('name')`
			1-reclength or 9-reclength	1-reclength or 1-(reclength-8)

All languages	`User-trigger`	`User-trigger name`	N/A	N/A

Restrictions on member expansion and member parts lists

These restrictions apply only to the member expansion and member parts listing functions:

- These restrictions apply to all languages:

  - Expansion triggers must follow their respective language coding conventions unless otherwise noted.
  - Multiple names and preprocessor variables on trigger statements are not permitted.
  - User triggers and their start column are specified at installation time and must be:
    - No more than 20 characters long
    - Uppercase with no imbedded blanks.

    No part of the user trigger can be in a comment or continuation field.
  - Macros cannot be in packed form.
  - The trigger statement must be the only statement in the logical record. No continuation is allowed into or from a trigger statement. Also, the trigger keyword must be the first character on the trigger statement that is not a blank and can be followed by only one statement delimiter.
  - For compilers that allow names longer than 8 characters, the name is truncated at 8.
  - For compilers that allow uppercase and lowercase names, all referenced names are converted to uppercase.
- This restriction applies to assembler only:
  - The user trigger cannot start in column 1.
- This restriction applies to FORTRAN only:
  - The member expansion function allows only the fixed form of coding.
- This restriction applies to PL/I, Pascal, and COBOL:
  - Free form coding is allowed except in trigger statements.
- Other COBOL restrictions are:
  - The name is truncated at 8 characters or the first hyphen (-), whichever comes first.
  - The first statement in the COBOL program must be either an expansion trigger, a valid COBOL division header, a TITLE, a PROCESS, or a CBL statement. The expansion trigger can precede all other statements, but it must start in FIELD B.

    If an expansion trigger is the first statement, it must eventually resolve (through multiple expansion triggers if needed) to a valid COBOL division header, TITLE, PROCESS, or CBL statement.
  - In the COPY statement, the text-name is the only value processed. The statement must end on the same line as the COPY keyword with a period followed by a space. If any option is found, the COPY statement is not expanded.
  - In the IDENTIFICATION DIVISION, the division header or paragraph header statements must be blank except for the division or paragraph name. The trigger statement must be on the next line that is neither blank nor a comment.
  - In all other divisions, the trigger statement (line) can be on any line in the division.
  - If the WITH DEBUGGING MODE clause is not found in the SOURCE COMPUTER paragraph, all debug lines are passed to the compiler without being scanned for expansion triggers, as if they were comment lines. If the clause is found, valid trigger statements found on debug lines are expanded and a `D` is inserted in column 7 of all the non-comment, non-continuation lines included.

  - Any character found in FIELD A that is not a blank causes the end of the paragraph form of the NOTE statement.
- These are SCRIPT/VS restrictions:
  - The `.im` statement must be the only statement in the logical record and must start in the first valid column. The first logical record is tested for line numbers, as follows:
    - For fixed-length records, if the last 8 characters are all numeric, they are skipped for the complete library.
    - For variable-length records, if the first 8 characters are all numeric, processing begins with column 9.

    The statements can be in either uppercase, lowercase, or mixed case.
  - Because ISPF creates a sequential data set from the imbedded members, use of the `.EF` control word will cause all statements in the sequential data set following the `.EF` to be ignored. The use of .EF is not recommended with packed data.

Member expansion ISRLEMX return codes

Table 19 describes the ISRLEMX return codes.

Table 19. ISRSCAN and ISRLEMX return codes

ISRSCAN		ISRLEMX	
12	Member not found.	**1-15**	Parameter *n* was too long, where *n* = 1 to 15.
16	OPEN error on DDNAME=IN.	**16**	Too many parameters.
20	I/O error on DDNAME=IN.	**17**	Too few parameters.
24	OPEN error on DDNAME=OUT.	**20**	Severe error in expand module. An error message should be printed in the ISRLMSG data set.
28	I/O error on DDNAME=OUT.		

Trigger statement errors

Some of the more common errors that occur are:
- Restricted option
- Statement on more than one line
- Referenced member name not found.

If an error occurs, the trigger statement is not expanded and is passed to the language processor.

In SCRIPT/VS, if the error was found in a user trigger, one blank line is inserted before and after the statement in question.

Input data sets

Input to a foreground processor is either:
- A member of an ISPF library or other partitioned data set. If you do not specify a member name, ISPF displays a member list, or
- A sequential data set

If an ISPF library is the input source, the member can be in any library in the concatenation sequence. You can include additional input by using:

- The COPY statement for assembler and COBOL
- The INCLUDE statement for PL/I, FORTRAN, and Pascal
- The SCRIPT/VS imbed control word (.im)
- Macros
- Additional input libraries.

Whenever the input source is partitioned, you can specify additional input libraries. They must be partitioned data sets that are not password protected. You cannot specify additional input libraries if the input source is sequential. Specify the fully qualified data set names, enclosed in apostrophes, such as:

```
Additional input libraries:
        ===> 'ABC.MACROS'
```

For example, in Figure 177 on page 312, a concatenation sequence of three ISPF data sets and one additional input library has been specified. The concatenation order is:

```
ISPFDEMO.XXX.ASM
ISPFDEMO.A.ASM
ISPFDEMO.MASTER.ASM
ISPFTEST.FLAG.ASM
```

The last data set in the concatenation sequence, ISPFTEST.FLAG.ASM, is entered as an additional input library at the bottom of the panel. Additional input libraries are always last in the sequence.

Before calling a foreground processor, ISPF scans the concatenated sequence of libraries to find the member to be processed. For this example, the member name is TOP. If member TOP first appears in data set ISPFDEMO.A.ASM, this prompter command would be generated by Assembler XF.

```
ASM  'ISPFDEMO.A.ASM(TOP)'
      LIB('SYS1.MACLIB',
          'ISPFDEMO.XXX.ASM',
          'ISPFDEMO.A.ASM',
          'ISPFDEMO.MASTER.ASM',
          'ISPFTEST.FLAG.ASM')
      LOAD('ISPFDEMO.XXX.OBJ(TOP)')
      PRINT(LISTASM)
      LIST,TEST,TERM,RENT
```

The processor options are passed to the prompter exactly as you specify them.

Note: The macro library SYS1.MACLIB is included in the concatenation sequence for Assembler only. When included, as the preceding prompter command example shows, it is always first in the sequence because of its large block size.

List data sets

In the List ID field, you can enter the name you want ISPF to use to identify the list data set that will contain the foreground processor output. This name is passed to the foreground processor by either the LIST or PRINT option. These rules apply:

- If the input data set is partitioned the List ID field is optional:
  - Leave the List ID field blank if you want ISPF to use the input member name to identify the output list data set.
  - Enter a LIST ID if you want to use a name other than the input member name to identify the output list data set.

- If the input data set is sequential, you must enter a LIST ID.

For best results, if you plan to debug your program later using COBOL interactive debug:

- Enter the name of the member being compiled in the List ID field if the input data set is partitioned.
- If the input data set is sequential, enter the name of the sequential data set.

Then, when you debug your program, use these same names in the PROG ID fields on the COBOL Interactive Debug panel.

ISPF names the listing:

```
prefix.userid.listid.LIST
```

where

```
prefix
```

is the data set prefix in your TSO profile, if you have one and if it is different from your user ID,

```
userid
```

is your user ID, and

```
listid
```

is the member name or the value in the List ID field.

If you are using the same list data set for multiple job steps, be aware that the DCB information can differ between the language processors and the linkage editor, causing an I/O error when trying to read the list data set. We suggest that you use a different list ID for each job step.

Password protection

Input, object, interpretable text (ITEXT), and symbolic debug data sets can be password-protected. You can specify the password in the Password field on the foreground processor data entry panel. The password does not appear on the screen when you enter it, but ISPF remembers it.

Since foreground processor panels have only one Password field, ISPF prompts you if all data sets do not have the same password.

Object data sets

The information shown here about object data sets applies to all foreground assemblers and compilers. However, if you are using the VS FORTRAN compiler, you must enter OBJECT in the Other field to generate an output object module. The two assemblers and the other compilers generate object modules automatically.

If you specify an ISPF library as the input source, ISPF writes object output from the foreground assembler or compiler to a partitioned data set. This data set has the same name as the first library in the concatenation sequence, but has a type of OBJ. For example, if you specify PROJECT.LIB1.ASM as the first library name, the object output is placed in data set PROJECT.LIB1.OBJ. The member name of the object module is the same as the input member.

If you specify another data set, the object output is placed in a data set of the same name, but with the last qualifier replaced by OBJ. If the data set name has only one qualifier, OBJ is appended as the last qualifier. For example, if you specify an input data set named OTHER.ASM or OTHER, the object output is placed in a data set named OTHER.OBJ. For partitioned data sets, the object output is stored in a member with the same name as the input member. For sequential data sets, the object output is stored in a sequential data set.

Note: The object data set must exist before invoking a foreground or batch option that creates an object module.

Foreground—TSO/E information center facility

If the TSO/E Information Center Facility is installed, your installation can optionally allow ISPF to substitute the panel shown in Figure 176 for the panel shown in Figure 175 on page 304. This panel is valid for all foreground processors except SCRIPT/VS and member parts list. See "Using the TSO/E information center facility" on page 183 for information about the fields on this panel.

```
                         Foreground Print Options

  PK  Print data set and keep          K  Keep data set (without printing)
  PD  Print data set and delete        D  Delete data set (without printing)

  If END command is entered, data set is kept without printing.

Data set name  . . .:

Printer Location  . . _____________

Printer Format  . . . ________

Number of copies  . . ___









Option  ===> ______________________________________________________________
 F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 176. Foreground Print Options panel with TSO/E information center facility (ISRFPPRI)

Assembler (option 4.1)

Foreground Assembler enables you to use either High Level Assembler or Assembler H. Both are called from the Foreground Assembler panel, shown in Figure 177 on page 312. For information about Assembler data sets, see the topic about Allocation Data Sets in the *z/OS ISPF User's Guide Vol I*.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                              Foreground Assembler
                                                                  More:     +
ISPF Library:
   Project . . . MYPROJ
   Group . . . . DEV      . . . ________ . . . ________ . . . ________
   Type  . . . . ________
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ____________________________________________________

List ID . . . ________      Assembler
Password  . .               1  1. High Level Assembler  2. Assembler H

Assembler Options: (options OBJECT and LIST generated automatically)
       ===> ____________________________________________________________

Additional input libraries:
       ===> ____________________________________________________________
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 177. Foreground Assembler panel (ISRFP01)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*, except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained in "Input data sets" on page 308, and here:

Assembler Options
: Be careful not to enter the OBJECT and LIST options in this field. ISPF generates these options automatically. OBJECT writes the output object module to a partitioned data set. LIST writes the output listing to a list data set. See "Object data sets" on page 310 and "List data sets" on page 309 for more information.

Assembler
: Enables you to specify whether to use High Level Assembler or Assembler H. Specify 1 for High Level Assembler or 2 for Assembler H.

COBOL (option 4.2)

ISPF generates an ISPEXEC SELECT PGM(IGYCRCTL) statement to invoke a COBOL compiler using the values you enter on the Foreground COBOL Compile panel, shown in Figure 178 on page 313. For information about COBOL allocation data sets, see the topic about Allocation Data Sets in the *z/OS ISPF User's Guide Vol I*.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                           Foreground COBOL Compile
                                                                   More:     +
ISPF Library:
   Project . . . MYPROJ
   Group . . . . DEV      . . . ________ . . . ________ . . . ________
   Type  . . . . ________
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ______________________________________________________

List ID . . . . . . . ________  Password  . .

Compiler options: (options LIB and OBJECT generated automatically)
  Test  . . . NOTEST  (TEST or NOTEST)
  Other . . . ______________________________________________________________

Additional input libraries:
       ===> ________________________________________________________________
Command ===> ________________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 178. Foreground COBOL Compile panel (ISRFP02)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained in "Input data sets" on page 308, and here:

Test If you plan to run interactive debug after you compile your program, enter TEST in the Test field. Otherwise, enter NOTEST.

Other If you plan to run VS COBOL II interactive debug after you compile your program, enter RESIDENT in the Other field. Otherwise, just enter any other options you need.

Be careful not to enter the LIB and OBJECT options in the Other field. ISPF generates these options automatically. LIB specifies the input data set concatenation sequence. OBJECT writes the output object module to a partitioned data set. See "Input data sets" on page 308 and "Object data sets" on page 310 for more information.

VS FORTRAN compile (option 4.3)

The Foreground VS FORTRAN Compile panel is shown in Figure 179 on page 314.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                        Foreground VS FORTRAN Compile
                                                                  More:     +
ISPF Library:
   Project . . . MYPROJ
   Group . . . . DEV     . . . ________ . . . ________ . . . ________
   Type  . . . . ________
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ______________________________________________

List ID . . . . . . . ________  Password  . .

Compiler options:
  Object  . . ________  (OBJECT or NOOBJECT)
  Other . . . ______________________________________________________

Additional input libraries:
       ===> ________________________________________________________
Command ===> ________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 179. Foreground VS FORTRAN Compile panel (ISRFP03)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained in "Input data sets" on page 308, and here:

Object
ISPF does not automatically generate any options for VS FORTRAN. Instead of generating an object module automatically, the VS FORTRAN compiler allows you to decide whether to generate one. To generate an object module, enter OBJECT in the Object field. To avoid generating an object module, enter NOOBJECT. See "Object data sets" on page 310 for more information.

Other If you plan to run FORTRAN interactive debug after you compile your program, enter TEST in the Other field, along with any other options you need.

PL/I (option 4.5)

The Foreground PL/I option enables you to invoke either OS PL/I Version 2 or PL/I for MVS and VM, using the values specified on the Foreground PL/I Compile panel shown in Figure 180 on page 315.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                            Foreground PL/I Compile
                                                                   More:     +
ISPF Library:
   Project . . . MYPROJ
   Group . . . . DEV     . . . ________ . . . ________ . . . ________
   Type  . . . . ________
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ____________________________________________________
List ID . . . ________      Compiler
Password  . .               _  1. OS PL/I Version 2     2. PLI for MVS and VM

Compiler options: (options LIB, OBJECT, and PRINT generated automatically)
       ===> ____________________________________________________________

Additional input libraries:
       ===> ____________________________________________________________
       ===> ____________________________________________________________
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 180. Foreground PL/I Optimizing Compile panel (ISRFP05)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained in "Input data sets" on page 308, and here:

Compiler
Choose the compiler you want to use from the list presented.

Compiler Options
Enter any options you need in the Other field, except LIB, OBJECT, or PRINT. ISPF generates these options automatically. LIB specifies the input data set concatenation sequence. OBJECT writes the output object module to a partitioned data set. PRINT writes the output listing to a list data set. See "Input data sets" on page 308, "Object data sets" on page 310, and "List data sets" on page 309 for more information.

VS Pascal compile (option 4.6)

The Foreground VS Pascal Compile panel is shown in Figure 181 on page 316.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                         Foreground VS PASCAL Compile
                                                                   More:     +
ISPF Library:
   Project . . . MYPROJ
   Group . . . . DEV      . . . ________ . . . ________ . . . ________
   Type  . . . . ________
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ______________________________________________________

List ID . . . . . . . ________  Password  . .

Compiler options: (options LIB, OBJECT, and PRINT generated automatically)
       ===> ____________________________________________________________

Additional input libraries:
       ===> ____________________________________________________________
       ===> ____________________________________________________________
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 181. Foreground VS Pascal Compile panel (ISRFP06)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained in "Input data sets" on page 308, and here:

Other Enter any options you need in the Other field, except LIB, OBJECT, or PRINT. ISPF generates these options automatically. LIB specifies the input data set concatenation sequence. OBJECT writes the output object module to a partitioned data set. PRINT writes the output listing to a list data set. See "Input data sets" on page 308, "Object data sets" on page 310, and "List data sets" on page 309 for more information.

Binder/linkage editor (option 4.7)

The Foreground Binder/Linkage Editor is called from the Foreground Binder/Linkage Edit panel, shown in Figure 182 on page 317.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                        Foreground Binder/Linkage Editor
                                                                   More:     +
ISPF Library:
   Project . . . MYPROJ
   Group . . . . DEV      . . . ________ . . . ________ . . . ________
   Type  . . . . ________
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned Data Set:
   Data Set Name  . . ____________________________________________________

                              Processor
List ID . . . . . ________    1  1. Binder
Password  . . . .               2. Linkage Editor

Linkage editor/binder options: (options LOAD, LIB, and PRINT generated
automatically)
         ===> ____________________________________________________________

Command ===> ________________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 182. Foreground Binder/Linkage Editor panel (ISRFP07B)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained in "Input data sets" on page 308, and here:

Linkage editor/binder options

Enter any options you need, except LOAD, LIB, or PRINT. ISPF generates these options automatically. LOAD writes the output object module to a partitioned data set.

Note: Sequential data sets are invalid when using the Linkage Editor.

LIB specifies the input data set concatenation sequence. PRINT writes the output listing to a list data set. See "List data sets" on page 309 and "Object data sets" on page 310 for more information.

Binder

Determines whether the Linkage Editor (NOBINDER) or Binder (BINDER) is invoked.

Note: The binder is available only if DFSMS 1.1, or later, is installed.

SYSLIB

The name of the data set that is to contain the ISPF library concatenation sequence used to resolve any copy statements specified in your program. See "Input data sets" on page 308 and the SYSLIB Data Set section in the topic about Allocation Data Sets in the *z/OS ISPF User's Guide Vol I* for more information.

SYSLIN

The name of the data set that is to contain the object module. The SYSLIN field is provided to accommodate the VS Pascal XA and NOXA processing options. See "Input data sets" on page 308 and the SYSLIB Data Set section in the topic about Allocation Data Sets in the *z/OS ISPF User's Guide Vol I* for more information.

Linkage editor concatenation sequence

The concatenation sequence used by ISPF to find the member for input to the Linkage Editor is:

```
project-name.lib1-name.type
project-name.lib2-name.type
(and so forth)
```

where `type` is whatever you specify on the panel. For example, it can be OBJ or some other type containing Linkage Editor language (LEL) control statements. If the type is not OBJ, an OBJECT DDNAME is automatically allocated to ease the use of these Linkage Editor control statements:

```
INCLUDE OBJECT(member-name)
```

For example:

```
Project . . . XYZ
Group . . . . MYLIB   . . . MASTER  . . .          . . .
Type  . . . . LEL
Member  . . . TOP
```

In this example, ISPF searches data sets XYZ.MYLIB.LEL and XYZ.MASTER.LEL to find member TOP, which should contain LEL control statements. Also, ISPF allocates to DDNAME OBJECT (DISP=SHR) these concatenated sequence of object libraries:

```
XYZ.MYLIB.OBJ
XYZ.MASTER.OBJ
```

This concatenated sequence is searched by the Linkage Editor if member TOP contains INCLUDE OBJECT(member-name) statements. The concatenation sequence passed to the Linkage Editor by way of the LIB parameter has a type qualifier of LOAD and includes the system libraries you specify, as follows:

```
LIB('project-name.lib1-name.LOAD',
    'project-name.lib2-name.LOAD',
⋮
    and so forth,
⋮
    'syslib1-name',
⋮
    and so forth)
```

This concatenation sequence is used by the Linkage Editor to resolve automatic call references.

SCRIPT/VS processor (option 4.9)

Use of this facility requires the installation of the Document Composition Facility (DCF) program product and its component text processing program, SCRIPT/VS, with the Foreground Environment Feature.

Note: DCF requires the TSO profile prefix to be set. For additional information, refer to DCF documentation.

When you select the SCRIPT/VS option, the first panel displayed is the SCRIPT/VS Processor panel shown in Figure 183 on page 319.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                              SCRIPT/VS Processor
                                                                   More:     +
                                       Enter "/" to select option
 Style . . . . ________                / Display Style Options
                                       / Browse Output
 ISPF Library:
    Project . . . MYPROJ
    Group . . . . DEV      . . . ________ . . . ________ . . . ________
    Type  . . . . SOURCE
    Member  . . . ________  (Blank or pattern for member selection list)

 Other Partitioned or Sequential Data Set:
    Data Set Name  . . ____________________________________________________

 List ID . . . . . . . ________  Password  . .
 Script Command  . . . SCRIPT   (SCRIPT or SCRIPTDB)

 Additional input libraries:
        ===> ____________________________________________________________
 Command ===> ____________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 183. SCRIPT/VS Processor panel (ISRFP09)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* except List ID, which is explained in "List data sets" on page 309, and Style, Display Style Options, and the Browse Output option, which are explained in subsequent sections.

SCRIPT/VS processing sequence

A *style* contains options that tell SCRIPT/VS how to format a document for display or printing. These options include the use of fonts, white space, line lengths, and so forth.

The value you put in the Style field and whether or not you select the Display Style Options and Browse Output options determine this SCRIPT/VS processing sequence:

1. For the Style field, you can perform one of these actions:
   - Enter the name of an existing style.

     You can enter the name of a style you have created or one of the styles SCRIPT/VS creates for you: DRAFT and FINAL. These two styles correspond to the formatting options available in the previous release of SCRIPT/VS Foreground Processing. If you have not defined these options before or if this is your first release of ISPF, the default values for the SCRIPT/VS formatting options are set for you.

     If you enter the name of an existing style in the Style field, that style is used for formatting.
   - Enter the name of a new style you want to define.

     If you enter a new style name, the name is added to your style list. The new style uses SCRIPT/VS formatting options that are equal to the formatting options of the last style. Step 2 on page 320 explains what to do to change these options.
   - Leave the Style field blank.

If you leave the Style field blank, ISPF displays the Select SCRIPT/VS Formatting Style panel. This panel displays a list of the available styles. See "Selecting a formatting style" on page 322 for more information.

2. Use a slash to select Display Style Options. ISPF displays the SCRIPT/VS Options for Style panel, which shows the options that are currently being used and allows you to change them. See "Changing style options" on page 323 for more information.

   If you do not select Display Style Options, ISPF does not display the SCRIPT/VS Options for Style panel.
3. Enter the appropriate ISPF library and concatenation sequence or data set names. You can display a member list by omitting the member name or by using a pattern. See the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* if you need help entering library or data set names, "Input data sets" on page 308 for more information about the concatenation sequence, and the Displaying Member Lists section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for more information about displaying member lists.
4. Enter your password in the Password field if your input data set is password-protected. See "Password protection" on page 310 for more information.
5. Use the List ID field to tell ISPF what to name the output SCRIPT/VS listing. See "List data sets" on page 309 for more information.
6. Use a slash to select the Browse Output option. ISPF displays your output in Browse mode after it has formatted.

   If you do not select the Browse Output option, ISPF skips Browse mode and displays a Foreground Print Options for Style panel, shown in Figure 184 on page 321.
7. Once all the input parameters have been specified, press Enter to call SCRIPT/VS.
8. Communication with SCRIPT/VS is in line-I/O mode. Each time you see three asterisks, press Enter. These asterisks, which usually appear at the bottom of the screen, show that TSO is waiting for you to clear the screen before it can proceed.

   If the Session Manager is installed and you selected the Session Manager mode option on the ISPF Settings panel, SCRIPT/VS and all PF and PA keys are under control of the Session Manager. When formatting is complete, you are prompted to enter a null line to return to ISPF control.

   If the Session Manager is not called, the PA and function keys have their usual TSO-defined meanings; generally, the function keys are treated the same as Enter.
9. One or both of the panels listed may appear, depending on your treatment of the Style and Display Style Options fields. If both appear, they will be in this sequence:
   a. Select SCRIPT/VS Formatting Style
   b. SCRIPT/VS Options for Style

   See "Selecting a formatting style" on page 322 and "Changing style options" on page 323 if you need information about using these panels. When you are finished with each panel, press Enter.
10. If SCRIPT/VS generated an output listing and you selected the Browse Output option, the output is displayed automatically in Browse mode. Otherwise, continue with the next step.

Note: If SCRIPT/VS formatting ends abnormally, ISPF displays a message in the upper-right corner of the screen and does not enter Browse mode. The list data set is retained, but the Foreground Print Options for Style panel (see step 11) is not displayed.

You can scroll the output up or down using the scroll commands. All the Browse commands are available to you. When you finish browsing the listing, enter the END command.

11. An optional print utility exit can be installed by your system programmer. If this exit is installed, it may cause SCRIPT/VS's response to differ from the descriptions here. See *z/OS ISPF Planning and Customizing* for more information about the print utility exit.

    Another factor that can affect the performance of SCRIPT/VS is whether the TSO/E Information Center Facility is installed. If the TSO/E Information Center Facility is installed, your installation can optionally allow ISPF to display a panel for submitting the TSO/E Information Center Facility information with the print request. See Figure 187 on page 325 for an example of this panel and "Using the TSO/E information center facility" on page 183 for information about the fields on this panel.

    If the TSO/E Information Center Facility is not installed, SCRIPT/VS displays the panel shown in Figure 184.

    The Foreground Print Options for Style panel allows you to optionally print the formatted document and specify its disposition. On this panel, the Data Set Name field shows the name of the list data set that contains the SCRIPT/VS output. On the Command line, enter one of the options shown at the top of the panel.

```
                 Foreground Print Options for Style:

  PK  Print data set and keep          K  Keep data set (without printing)
  PD  Print data set and delete        D  Delete data set (without printing)

  If END command is entered, data set is kept without printing.

Data Set Name  :

Print mode . . . BATCH              (Batch or Local)

Batch SYSOUT class . . ________________
Local Printer ID or
      writer-name. . . ________________  (For local printer)
Local SYSOUT class . . ________________

Job statement information:          (Required for system printer)
  ===> ________________________________________________________________________
  ===> ________________________________________________________________________
  ===> ________________________________________________________________________
  ===> ________________________________________________________________________
Command ===> ________________________________________________________________
 F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 184. Foreground Print Options for Style panel (ISRFP09P)

In the Print mode field, enter either of these commands:

- BATCH to submit your print request as a background job.

If you choose BATCH, specify a valid Batch SYSOUT class and job statement information. Specifying BATCH causes SCRIPT/VS to ignore the "Local Printer ID or writer-name" field and the "Local SYSOUT class" field.

SCRIPT/VS list data sets are formatted DCB=RECFM=VBM. Unless the line count is altered, the formatted page length may exceed the JES line count and cause duplicate page ejects. Therefore, specify this job statement information to prevent JES line counting:

```
/*JOBPARM LINECT=0
```

- LOCAL to print the output on a local printer.

  If you choose LOCAL, specify the "Local Printer ID or writer-name" of a local printer and optional "Local SYSOUT class". Specifying LOCAL causes SCRIPT/VS to ignore the "Batch SYSOUT class" field. Job statement information is ignored.

  Page spacing will probably vary from the expected format because of differences between 328x printers and 1403 or 3800 printers used as a formatting guide.

See "Hardcopy utility (option 3.6)" on page 180 if you need information about the "Print mode", "Batch SYSOUT class", "Local Printer ID or writer-name", and "Local SYSOUT class" fields. For information about the "Job statement information" fields, see the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*.

When you press Enter, the SCRIPT/VS Processor panel is displayed again. A message indicating completion of the process is displayed in the upper-right corner of the screen.

12. You can perform one of these actions:
    - Enter other parameters and call SCRIPT/VS again.
    - Enter the END command to return to the Foreground Selection panel and select another processor.
    - Enter the RETURN command to go to the ISPF Primary Option Menu.
    - Use the jump function (=) to choose any primary option.

Selecting a formatting style

Use the Select SCRIPT/VS Formatting Style panel shown in Figure 185 on page 323 to see which styles are available and to select or delete styles as necessary.

```
                     Select SCRIPT/VS Formatting Style        Row 1 to 2 of 2

 Valid Line Commands:  S - Use this STYLE for formatting
                       D - Delete

Line
Cmd   Style       Description

 '    DRAFT       Draft SCRIPT/VS document options
 '    FINAL       Final SCRIPT/VS document options
******************************* Bottom of data ********************************


Command ===> ____________________________________________ Scroll ===> PAGE
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F12=Cancel
```

Figure 185. Select SCRIPT/VS Formatting Style panel (ISRFP09T)

The Select SCRIPT/VS Formatting Style panel is a list that can be scrolled and contains all the styles available to you. Each style is a set of predefined formatting options.

Type either `S` or `D` in the Line Cmd field and press Enter to select or delete a style, respectively. You can only select one style at a time for formatting. However, one or more styles can be deleted at the same time.

The display fields on the Select SCRIPT/VS Formatting Style panel contain:

Style The names of styles that you can either select or delete.

Description A reminder of the purpose of each style. Type over the description to change it.

Changing style options

Use the SCRIPT/VS Options for Style panel to:
- See which options are currently being used for the style you chose
- Change the options as needed.

Figure 186 on page 324 shows the options available for the DRAFT style.

```
                      SCRIPT/VS Options for Style: DRAFT
                                                                More:     +
Profile data set  . . ____________________________________________________
FONTLIB data set  . . ________________________________________
SEGLIB data set . . . ________________________________________
User macro data set  . . . ______________________________________
System macro data set  . . ______________________________________

Bind:       #Odd  . . ________
            #Even . . ________

Device type . . . . . ________
Chars (Fonts) . . . . ____________________________________________________
SYSVAR  . . . . . . . ____________________________________________________
Page  . . . . . . . . ____________________________________________________

Other script parms  . . . ________________________________________________

Enter "/" to select option
_  Twopass                              /  Uppercase only
/  Spelling                             _  Unformat
_  Index                                _  Condensed Text
Command ===> ____________________________________________________________
 F1=Help    F2=Split   F3=Exit    F9=Swap   F12=Cancel
```

Figure 186. SCRIPT/VS Options for Style: DRAFT panel (ISRFP09O)

The fields on the SCRIPT/VS Options for Style panel represent SCRIPT/VS formatting options, all of which are optional. For a complete description of these options, refer to *Document Composition Facility: Generalized Markup Language Starter Set User's Guide*.

If you enter the END command from the SCRIPT/VS Options for Style panel, changes on this panel are not saved. If the style is new, it is saved with default formatting options.

If you press Enter from the SCRIPT/VS Options for Style panel, SCRIPT/VS processes the data set, and then one of these actions occurs:

- A Browse panel is displayed if you selected the Browse Output option on the SCRIPT/VS Processor panel. When you finish browsing the SCRIPT/VS formatted output, a Foreground Print Options for Style panel is displayed.

  Note: If you enter the PRINT parameter in the "Other script parms" field, the Browse panel is not displayed.
- A Foreground Print Options for Style panel is displayed if you did not select the Browse Output option on the Script/VS Processor panel.

See step 11 on page 321 for more information about printing SCRIPT/VS output.

Using SCRIPT/VS with the TSO/E information center facility

If the TSO/E Information Center Facility is installed, your installation can optionally allow ISPF to substitute the panel shown in Figure 187 on page 325 for the panel shown in Figure 184 on page 321. See "Using the TSO/E information center facility" on page 183 for information about the fields on this panel.

```
                  Foreground Print Options for Style:

  PK  Print data set and keep         K  Keep data set (without printing)
  PD  Print data set and delete       D  Delete data set (without printing)

  If END command is entered, data set is kept without printing.

Data Set Name . . . :

Printer location  . . ______________

Printer Format  . . . _______

Number of copies  . . ___





Command  ===> _____________________________________________________________
 F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 187. Foreground Print Options for Style panel with the TSO/E information center facility (ISRFP09I)

VS COBOL II interactive debug (option 4.10)

To run VS COBOL II interactive debug in foreground, the VS COBOL II compiler, Release 2, must be both installed and accessible, for these reasons:

- You must compile your program by using the VS COBOL II compiler (option 4.2 or option 5.2) with the TEST and RESIDENT options before running VS COBOL II interactive debug. Debug output from the compilation is stored in the object module, which ISPF generates automatically.
- The VS COBOL II compiler contains the Debug Productivity Aid (DPA) facility, which ISPF accesses when you run VS COBOL II interactive debug in the foreground.

All VS COBOL II interactive debug processing in the foreground is under DPA's control. DPA displays a series of interactive panels. When processing is complete, return to step 12 on page 303.

OS/VS COBOL debug (option 4.10A)

Before you can run COBOL interactive debug, you must first perform these actions in the order shown:

1. Allocate a symbolic debug data set and, optionally, a print output data set by using the Data Set utility (option 3.2). See "Symbolic debug data sets" on page 327 and "Print output data sets" on page 327 for more information.
2. Compile the program by using the OS/VS COBOL compiler (option 4.2A or option 5.2A) with the TEST option.
3. Use the linkage editor (option 4.7 or option 5.7) to generate an output load module, which COBOL interactive debug will use as input.

The COBOL Debug panel is shown in Figure 188 on page 326.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                           COBOL Interactive Debug
                                                                 More:     +
ISPF Library:
   Project . . . ________
   Group . . . . ________  (Type = LOAD assumed)
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ______________________________________________________

Prog ID . . . . . . . ________ . . . ________ . . . ________ . . . ________

Print ID  . . . . . . ________  Password  . .

Enter "/" to select option
/  Source

Execution Parms:
       ===> ____________________________________________________________
Additional input libraries:
       ===> ____________________________________________________________
       ===> ____________________________________________________________
       ===> ____________________________________________________________

Note: 1. PREFIX.PRINTID.TESTLIST must exist if Print ID is specified.
      2. PREFIX.PROGID.LIST must exist for each program specified if / is
      specified in Source field.
Command ===> ___________________________________________________________
 F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 188. COBOL Debug panel (ISRFP10A)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*, except Prog ID, Print ID, Source, and Execution Parms, which are explained in subsequent topics.

COBOL debug processing sequence

Fill in the fields on the COBOL Debug panel as follows:

1. Enter the ISPF library or data set name that contains the input load module generated by the linkage editor. You can display a member list by omitting the member name or by using a pattern. See the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* if you need help entering library or data set names, "Object data sets" on page 310 for more information about object modules, and the Displaying Member Lists section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for more information about displaying member lists.
2. The Prog ID field tells ISPF the names of the sequential list data sets generated by the OS/VS COBOL compiler. You can enter up to four Prog ID names if you compiled a partitioned data set member or a sequential data set for each name. See "List data sets" on page 309 for more information.
3. The Print ID field is optional. This field tells ISPF the name of a sequential data set to which it writes the print output from the debug session. This data set must be preallocated. See "Print output data sets" on page 327 for more information.

4. Enter your password in the Password field if your input data set is password-protected. See "Password protection" on page 310 for more information.
5. The Source option tells ISPF whether to allocate the list data sets specified in the Prog ID field. If you select Source, these data sets must already exist.
6. The Execution Parms field is remembered from one session to another. Therefore, you do not need to change this field unless the parameters you need are not displayed. Enter any parameters that you want ISPF to pass to the program being debugged.
7. To continue COBOL interactive debug, return to step 12 on page 303.

Symbolic debug data sets

If you want to run COBOL interactive debug on a program compiled with the OS/VS COBOL compiler, you must use the Data Set utility (option 3.2) to allocate a symbolic debug data set before compiling the program. Then, when you compile the program, enter TEST in the Test field on the Foreground OS/VS COBOL Compile panel. The TEST parameter generates the debug output, which ISPF stores in the symbolic debug data set you allocated.

Note: You do not need to allocate a symbolic debug data set for programs compiled with VS COBOL II because the debug output, if requested, is stored in the OBJECT module, which ISPF generates automatically.

When you allocate the data set, specify the same name as the data set that contains your COBOL program, but:

- For an ISPF library, enter:
  - The Group name you will specify in the first Group field on the Foreground OS/VS COBOL Compile panel
  - SYM in the Type field.
- For another partitioned or sequential data set, use SYM to replace the last qualifier. For example, if COBOL.INPUT or COBOL is the input data set name, allocate COBOL.SYM as the symbolic debug data set.

Use these values to allocate symbolic debug data sets:

```
Record format . . . . . F
Record length . . . . . 512
Block size  . . . . . . 512
```

For partitioned data sets, including ISPF libraries, the debug output is stored in a member with the same name as the input member. For sequential data sets, the debug output is stored in a sequential data set.

When you run COBOL interactive debug, the names you put in the Prog ID field on the COBOL Interactive Debug panel must be the same as the input member names if you are to create a correct SYM data set.

Print output data sets

ISPF writes the print output from a debug session to a sequential data set, if you:

- Allocate the data set, using the Data Set utility (option 3.2), before you run COBOL interactive debug
- Enter, in the Print ID field on the COBOL Interactive Debug panel, the name of the data set you allocated.

You can avoid generating the print output by leaving the Print ID field blank, even if you allocated the data set.

The last qualifier in the name of the data set you allocate must be TESTLIST. For example, if you allocate a sequential data set named DEBUG1.TESTLIST and then specify the Print ID as:

```
Print ID . . DEBUG1
```

ISPF writes the print output to a sequential data set named:

```
'prefix.userid.DEBUG1.TESTLIST'
```

where *prefix* is your TSO data set prefix, if you have one and if it is different from your user ID, and *userid* is your TSO user ID. Use these values to allocate print output data sets:

```
Record format . . . . . FBA
Record length . . . . . 121
Block size  . . . . . . 3146
```

The value you put in the Block Size field should be a multiple of 121, the record length. Therefore, if your print output data is too large to fit within the recommended block size (3146), increase this amount by using a multiple of 121, such as 3267 or 3388.

FORTRAN debug (option 4.11)

Before you can run FORTRAN interactive debug, you must first compile the program using the VS FORTRAN compiler (option 4.3 or option 5.3) with the OBJECT and TEST options.

The FORTRAN interactive debug option supports both FORTRAN Interactive Debug Version 2 (5668-903) and FORTRAN Interactive Debug Version 1 (5734-F05). ISPF looks for Version 2 first, then Version 1, and finally its own Debug Dialog, which displays the panel shown in Figure 189 on page 329.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                          FORTRAN Interactive Debug
                                                                   More:     +
ISPF Library:
   Project . . . _______
   Group . . . . _______ . . . _______ . . . _______ . . . _______
   Type  . . . . OBJ     (OBJ or LOAD)
   Member  . . . _______  (Blank or pattern for member selection list)

Source Type  . . _______

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ____________________________________________________

List ID . . . . . . . _______  Password  . .

Debug Options: (options LIB, SOURCE, and PRINT generated automatically)
       ===> ____________________________________________________________

Additional input libraries:
       ===> ____________________________________________________________
       ===> ____________________________________________________________
       ===> ____________________________________________________________
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 189. FORTRAN Debug panel (ISRFP11)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained in "Input data sets" on page 308, and here:

Debug Options
: Enter any options you need, except LIB, SOURCE, or PRINT. ISPF generates these options automatically. LIB specifies the input data set concatenation sequence. SOURCE specifies the input source program, whose type is identified in the Source Type field. PRINT writes the output listing to a list data set. See "Input data sets" on page 308 and "List data sets" on page 309 for more information.

Member parts list (option 4.12)

The member parts list uses the program ISRLEMX to show this information for each source program module specified:

- The names of the modules it calls or includes.
- The names of the modules that call or include it.

The languages permitted in the member expansion function also are permitted in the member parts list function, and the expansion triggers have the same restrictions. See "Member expansion (ISRLEMX)" on page 306. Besides the expansion triggers, the member parts list also uses the CALL statements in assembler, PL/I, COBOL, and VS FORTRAN. The format of the CALL statement is:

```
CALL name
```

where the delimiter after the name can be either a left parenthesis, a blank, or a valid statement delimiter. In COBOL, the CALL statement is valid only in the

PROCEDURE DIVISION, and the `CALL PGMA` and `CALL 'PGMA'` statements both result in a reference to the member name PGMA.

When you select the Foreground Member parts list option (4.12), the panel shown in Figure 190 is displayed.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                          Foreground Member Parts List

 1 Browse/Print member parts
 2 Write member parts data set

 ISPF Library:
    Project . . . ________
    Group . . . . ________ . . . ________ . . . ________ . . . ________
    Type  . . . . ________
    Member  . . . ________  (Blank or pattern for member selection list)

 Language . . . . ________  (Defaults to Type value)

 Groups for Primary members . . . 1  (1, 2, 3, or 4)

 Output Data Set:          (option 2 only)
    Data Set Name  . . ____________________________________________________


 Option ===> ____________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 190. Foreground Member Parts List panel (ISRFP12)

The member parts list does not use the Source Data Packed option on the Foreground Selection panel; both packed and unpacked data sets can be read.

Fill in the fields on the Foreground Member Parts List panel as follows:

1. Select one of the options listed at the top of the panel by typing its number in the Option field.
2. Enter the appropriate ISPF library and concatenation sequence or data set names. A blank member name results in a member list being displayed. You can select only one member from this list. A pattern results in the processing of all member names matching the pattern; an asterisk results in all members being processed.

   See the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* if you need help entering library or data set names, the Displaying Member Lists section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for information about using patterns and displaying member lists, and "Input data sets" on page 308 for more information about the concatenation sequence.
3. The Language field is optional. It is used to specify the language in which the source code is written. If you leave this field blank, ISPF uses the value in the Type field as the default. However, the language must be one of these:
   - Assembler
   - COBOL
   - FORTRAN
   - Pascal
   - PLI

- SCRIPT.

4. In the "Groups For Primary members" field, enter a number from 1 to 4. This number tells ISPF how many libraries in the concatenation sequence are to be used in locating primary members. For example, if you enter 2, the first and second libraries specified in the Group field are used to find primary members.
5. If you selected option 2 (write member parts data set), use the Data Set Name field to tell ISPF where to write the output data set. The name you enter:
   - Can be a sequential data set or a member of a partitioned data set
   - Must follow standard TSO data set naming conventions.

   If you enter the name of a data set that does not exist, ISPF allocates it for you.
6. Once all the input parameters have been specified, press Enter to call the Foreground Member Parts List processor.

   If the Session Manager is installed and if you specified Session Manager mode on the Foreground Selection panel, the Foreground Member Parts List processor and all function keys and PA keys are under control of the Session Manager. When processing is complete, you are prompted to enter a null line to return to ISPF control.

   If the Session Manager is not called, the PA and function keys have their usual TSO-defined meanings; generally, the function keys are treated the same as Enter.
7. Communication with the Foreground Member Parts List processor is in line-I/O mode. Each time you see three asterisks, press Enter. These asterisks, which usually appear at the bottom of the screen, show that TSO is waiting for you to clear the screen before it can proceed.
8. The option you chose in step 1 on page 330 determines what happens next.

   Note: If the Foreground Member Parts List processing program ends abnormally, ISPF displays a message in the upper-right corner of the screen and does not enter Browse mode. The list data set is retained, but the Foreground Print Options panel (see step 15 on page 304) is not displayed.

   Option 1 (Browse/print member parts) creates the member parts list and displays it in Browse mode. Figure 191 shows an example.

```
BROWSE - Parts List for ISPFPROJ.ABL.PLI(*) ----------------------------------

 From   Via         From   Via     Member       To    Via          To    Via
------- ---       -------- ---    --------   -------- ---       -------- ---
********************************* Top of Data ***********************************
                                  (MEMBERA )
                                  (MEMBERB )  MEMBERC  C
                  MEMBERB  C      (MEMBERC )  MEMBERD  C         MEMBERE  I
                                              MEMBERG  C*
                  MEMBERC  C      (MEMBERD )  MEMBERE  I
 MEMBERC  I       MEMBERD  I      (MEMBERE )
                                  (MEMBERF )
******************************** Bottom of Data *********************************









Command ===> ____________________________________________________ Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 191. Member parts list display (ISRFP12B)

The figure shows that:

- Library ISPFPROJ.ABL.PLI contains these members:

  MEMBERA Has no calls or includes.

  MEMBERB Calls MEMBERC.

  MEMBERC Calls MEMBERD and MEMBERG, and includes MEMBERE. The asterisk (*) beside the C in the third VIA column means that MEMBERG was not found in the input library.

  MEMBERD Includes MEMBERE.

  MEMBERE Has no calls or includes.

  MEMBERF Has no calls or includes.

- A parts list is requested for all members in the first data set.

You can scroll the output up or down using the scroll commands. All the Browse commands are available to you. When you finish browsing the listing, enter the END command and continue with step 15 on page 304.

Option 2 (Write member parts data set) produces an intermediate sequential member parts list in the data set you named in step 5 on page 331. This data set can be either a sequential data set or a member of a partitioned data set.

If the data set has not been allocated, option 2 allocates it with a logical record length (LRECL) of 17, a block size (BLKSIZE) of 3009, and a record format (RECFM) of FB. The format of the records is shown in Table 20:

Table 20. Foreground member parts list record formats

Field Name	Format	Description
Member name	CHAR(8)	Subject member.
Called by or calls member name	CHAR(8)	Referenced member.
Call flag	BIT(1)	Found on a CALL statement.

Table 20. Foreground member parts list record formats (continued)

Field Name	Format	Description
Include flag	BIT(1)	Found by INCLUDE or COPY.
Not found flag	BIT(1)	Referenced member not found.
From flag	BIT(1)	Subject member called from referenced member.
To flag	BIT(1)	Referenced member called from subject member.
COBOL flag	BIT(1)	Member referenced outside valid COBOL division.
Reserved	BIT(2)	Field that is reserved.

9. You can perform one of these actions:
   - Enter other parameters and call the same processor.
   - Enter the END command to return to the Foreground Selection panel and select another processor.
   - Enter the RETURN command to go to the ISPF Primary Option Menu.
   - Use the jump function (=) to choose any primary option.

Member not found

A *primary library* is one of the number of libraries specified in the "Groups For Primary members" field. A *primary member* is a member that starts the member parts explosion chain. An *explosion chain* is the order in which members are nested, starting with the primary member and continuing through each member that it includes, calls, or copies.

The chain is broken when a member cannot be found in the set of concatenated libraries or no more members are referenced. If a member cannot be found, the name is flagged with an asterisk (*) and processing continues. For instance, internally called routines are not found.

When no more primary members can be found, the listing is printed, written, or browsed. Calls to internal routines or variable names result in the `member not found` flag being set.

C/370 compile (option 4.13)

ISPF supports the C/370 compiler through dialogs supplied with the C/370 compiler (5688-040). See *C Compiler User's Guide for MVS*, SC09-1129 for additional information.

REXX/370 compile (option 4.14)

ISPF supports the REXX/370 compiler through dialogs supplied with the REXX/370 compiler (5695-013). See *IBM Compiler and Library for REXX/370 User's Guide and Reference*, SH19-8160, for additional information.

Ada/370 compile (option 4.15)

ISPF supports the Ada/370 compiler and its tools through dialogs supplied with the Ada/370 compiler (5706-292). See *IBM Ada/370 User's Guide* SC09-1415, for additional information.

AD/Cycle C/370 compile (option 4.16)

ISPF supports the AD/Cycle™ C/370 compiler through dialogs supplied with the AD/Cycle C/370 compiler (5688-216). See *IBM SAA AD/Cycle C/370 Programming Guide* SC09-1356, for additional information.

ISPDTLC (option 4.18)

ISPF supports the ISPF Dialog Tag Language compiler by running the ISPDTLC function. See *z/OS ISPF Dialog Tag Language Guide and Reference* for more information about DTL.

The first ISPDTLC interface panel appears as shown in Figure 192.

```
  Menu  Utilities  Commands  Language  Options  Help
 ------------------------------------------------------------------------
           ISPF Dialog Tag Language Conversion Utility - 5.5

Click here:   Go to DTL input names 5-16        Reset DTL input names 2-16
Enter requested information:         Current Language: ENGLISH
                                                              More:     +
Member name . . . . . . . . ________ (Blank or pattern for member list)
DTL Source data set - 1 . . 'USERID.GML'
DTL Source data set - 2 . . ____________________________________________
DTL Source data set - 3 . . ____________________________________________
DTL Source data set - 4 . . ____________________________________________
Panel data set  . . . . . . 'USERID.PANELS'
Message data set  . . . . . 'USERID.MSGS'
Log data set  . . . . . . . ____________________________________________
  Log File Member name  . . ________ (Required when log file is a PDS)
List data set . . . . . . . ____________________________________________
  List File Member name . . ________ (Required when list file is a PDS)
SCRIPT data set . . . . . . ____________________________________________
Command ===> ___________________________________________________________
 F1=Help       F2=Split       F3=Exit        F7=Backward    F8=Forward
 F9=Swap       F10=Actions    F12=Cancel
```

Figure 192. Foreground ISPDTLC compile panel (ISPCP01) Screen 1

The fields on this panel are explained in the topic "Using the Conversion Utility" in *z/OS ISPF Dialog Tag Language Guide and Reference*.

OS/390 C/C++ compile (option 4.19)

ISPF supports the OS/390 C/C++ compiler and its tools through dialogs supplied with the OS/390 C/C++ compiler (5647-A01). For information about OS/390 C/C++, refer to the *OS/390 C/C++ User's Guide*.

Chapter 7. Batch (option 5)

The Batch option (5) allows ISPF to run the batch processors shown on the Batch Selection panel, Figure 193, as batch jobs. ISPF generates job control language (JCL) for the job, based on information you enter on the batch processing panels, and then submits the job for processing. All these processors, plus SCRIPT/VS, COBOL interactive debug, and FORTRAN interactive debug, are also available with the Foreground option (4).

When you run a batch processor, you can continue using ISPF while the program is running. However, if you run these processors by using the Foreground option, you must wait for processing to end before doing anything else with ISPF. The Foreground Selection panel is shown in Figure 174 on page 301.

```
  Menu  Utilities  Help
 ------------------------------------------------------------------------
                              Batch Selection Panel

1  Assembler              7  *Binder/Link editor    15 *ADA/370
2  COBOL                  10 *VS COBOL II debug     16 *AD/Cycle C/370
3  VS FORTRAN             12  Member Parts List     18  ISPDTLC
5  PLI                    13 *C/370                 19 *OS/390 C/C++
6  VS PASCAL              14 *REXX/370

    Enter "/" to select option          * No packed data support
    /  Source data online
    _  Source data packed

Job Statement Information: Verify before proceeding

===> //LSACKV1  JOB (ACCT),CLASS=A
===> //*
===> //*
===> //*

Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 193. Batch Selection panel (ISRJPA)

The names of the batch processors on this panel are point-and-shoot fields. See the information about Point-and-Shoot Text Fields in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I* for more information.

Batch selection panel action bar

The Batch Selection Panel action bar choices function as follows:

Menu See the information about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I* for more information about the Menu pull-down.

Utilities See the information about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I* for more information about the Utilities pull-down.

© Copyright IBM Corp. 1980, 2007

Help The Help pull-down provides general information about foreground processing as well as information about each available choice on the Batch Selection Panel.

Batch processing sequence

This topic describes the main sequence for batch processing.

1. If you do not know whether the source data is in packed format, find out by editing the data set and entering the PROFILE command. If the source data is in packed format, the profile shows PACK ON.

   If the data is not packed, continue with the next step.

   If the data is packed, you should read "Expanding packed data" on page 305, paying close attention to information that applies to the batch processor you plan to use. When you are satisfied that the data set is ready to be processed, save the data set if you are in Edit and continue with the next step.
2. Select a batch processor. If you bypass the Batch Selection panel, you cannot verify or change the job statement parameters, or generate multiple compilations (multiple job steps) or link-edits within the same job.
3. Select the Source data online option to tell ISPF that the data to be processed resides on a currently mounted volume. ISPF checks the data set information that you entered on the Batch Selection panel and allows you to display a member list. If you do not select this option, ISPF assumes that the data cannot be accessed except by the batch job and does not verify the existence or validity of the specified data set.
4. Select the Source data packed option to tell ISPF that it needs to expand the source data. This option has no effect on the member parts list option (5.12). Member parts list can read both packed and unpacked data sets, so no expansion is needed.
5. Enter any job statement information you need. See the information about Job Statement Information in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for more information.
6. Press Enter. ISPF displays the data entry panel for the processor you selected.

   Note: The remainder of this processing sequence applies to all batch processors except Member Parts List. See "Member parts list (option 5.12)" on page 347 for more information.
7. Enter the appropriate ISPF library and concatenation sequence or data set names.

   For VS COBOL II interactive debug, enter the name of the input object module or load module. The TYPE, or last qualifier, must be either OBJ or LOAD. However, if you specify an OBJ data set as your input data set, you must include a load library or data set in the input search sequence (see step 11 on page 337).

   ISPF displays a member list if you omit the member name or use a pattern. See the information about Naming ISPF Libraries and Data Sets in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* if you need help entering library or data set names, "Input data sets" on page 308 for more information about the concatenation sequence, and the Displaying Member Lists section of the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* for more information about displaying member lists.

Notes:

a. VS FORTRAN has no LIB option. However, the concatenation sequence is still used to find the member to be compiled.

b. Password protection is not supported from the Batch option. Therefore, if your input or output data sets are password-protected, use the Foreground option, which does support passwords.

   If you submit a job requiring a password-protected data set, the system operator will be requested to enter the required password.

8. The List ID field tells ISPF what to name the output listing. Leave this field blank and enter a SYSOUT class to send the listing to a printer. See "List data sets" on page 309 for more information.
9. Enter a SYSOUT class to generate hardcopy of the listing. You can enter any valid SYSOUT parameter. If a List ID is entered, this field is ignored.
10. The Options field, whether ASSEMBLER, COMPILER, or LINKAGE EDITOR, is remembered from one session to another. Therefore, you do not need to change these fields unless the options or parameters you need are not displayed.

    If you need information about the options available for your processor, refer to the documentation provided with the processor.
11. Enter any additional input libraries you need. For VS COBOL II interactive debug, enter any input LOAD libraries that you need to complete the search. These libraries must be LOAD libraries only. See "Input data sets" on page 308 if you need help.
12. Once all the input fields have been specified, press Enter to call the batch processor. ISPF generates the appropriate JCL statements. See "JCL generation—compilers" on page 338 and "JCL generation—assemblers and linkage editor" on page 339 for more information.

    Note: You can leave the entry panel without generating any JCL by entering the END command instead of pressing Enter.
13. One of these actions occurs:
    - If you used the jump function to bypass the Batch Selection panel, ISPF submits the generated JCL and returns directly to the ISPF Primary Option Menu.

      ISPF calls the TSO SUBMIT command to submit a job. The SUBMIT command displays this message:

      ```
      JOB useridA(JOB nnnnn) SUBMITTED
      ***
      ```

      When you press Enter or any other interrupt key, ISPF returns to the previous panel.
    - Otherwise, ISPF returns to the Batch Selection panel with the message `Job step generated` displayed in the short message area on line 1, as shown in Figure 194 on page 338.

```
  Menu  Utilities  Help
 ------------------------------------------------------------------------------
                            Batch Selection Panel           Job step generated
                                                                  More:     +
1  Assembler              7  *Binder/Link editor    15 *ADA/370
2  COBOL                  10 *VS COBOL II debug     16 *AD/Cycle C/370
3  VS FORTRAN             12  Member Parts List     18  ISPDTLC
5  PLI                    13 *C/370                 19 *OS/390 C/C++
6  VS PASCAL              14 *REXX/370

   Enter "/" to select option          * No packed data support
   /  Source data online
   _  Source data packed

Job Statement Information:

===> //LSACKV1  JOB (ACCT),CLASS=A
===> //*
===> //*
===> //*

Option ===>
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 194. Batch Selection Panel with JCL generated (ISRJPB)

The job statement parameters are shown for information only. They are no longer intensified, and you cannot type over them because the JOB statement has already been generated. At this point, you can:

- Select the same or another processor to cause more JCL to be generated.
- Go to the ISPF Primary Option Menu by:
  - Canceling the batch job by entering the CANCEL command
  - Entering the END or RETURN command to cause the generated JCL to be submitted for processing.
- Use the jump function (=) to choose any primary option. If any JCL has been generated, it is submitted for batch processing.

JCL generation—compilers

Figure 198 on page 343 shows an example for the PL/I optimizing compiler. This panel is typical of the batch compiler entry panels. After you fill in an entry panel and press Enter, ISPF generates the appropriate JCL statements. The JCL that would be generated for the PL/I example is:

```
//SCAN   EXEC PGM=ISRLEMX,COND=(12,LE),
//   PARM=('PLI,TOPSEG,B,N,E,4, ,00,ENU,4,7',
//        '1,/,VIO')
//*
//* INSERT STEPLIB DD CARDS HERE FOR ISRLEMX AND THE NATIONAL
//* LANGUAGE LITERAL LOAD MODULE IF THEY ARE NOT IN YOUR SYSTEM
//* LIBRARY
//*
//ISRLCODE DD  DSN=ISPFDEMO.XXX.PLIO,DISP=SHR
//         DD  DSN=ISPFDEMO.A.PLIO,DISP=SHR
//         DD  DSN=ISPFDEMO.MASTER.PLIO,DISP=SHR
//ISRLEXPD DD  UNIT=SYSDA,DISP=(NEW,PASS),SPACE=(CYL,(2,2)),
//             DSN=&&TEMP1
//ISRLMSG  DD  SYSOUT=(A)
//PLIO   EXEC  PGM=IEL0AA,REGION=1024K,COND=(12,LE),
//             PARM='MACRO,XREF'
```

```
//SYSPRINT DD  DSN=ISPFDEMO.LISTPLIO.LIST,UNIT=SYSDA,
//             SPACE=(CYL,(2,2)),DISP=(MOD,CATLG),
//             DCB=(RECFM=VBA,LRECL=125,BLKSIZE=3129)
//SYSIN    DD  DSN=&&TEMP1,DISP=(OLD,DELETE)
//SYSLIB   DD  DSN=ISPFDEMO.XXX.PLIO,DISP=SHR
//         DD  DSN=ISPFDEMO.A.PLIO,DISP=SHR
//         DD  DSN=ISPFDEMO.MASTER.PLIO,DISP=SHR
//         DD  DSN=ISPFTEST.FLAG.PLIO,DISP=SHR
//SYSUT1   DD  UNIT=SYSDA,SPACE=(CYL,(2,2))
//SYSLIN   DD  DSN=ISPFDEMO.XXX.OBJ(TOPSEG),DISP=OLD\
```

The JCL is generated in two steps:

1. The first step processes one of these scan programs, which are distributed as part of ISPF:

   ISRSCAN Copies one member.

   ISRLEMX Copies the primary member, expands any included members, and unpacks any packed members.

   The selected scan program searches the user-specified sequence of concatenated libraries to find the designated member. If the scan program finds the member, it copies the member to a temporary sequential data set that is shown by &&TEMP1 and generated by the system. The scan program then exits with a return code of zero, if no errors are found. If any errors are found, the scan program exits with one of these return codes, which prevents the processing of the second job step. Table 21 describes ISRLEMX return codes:

   Table 21. ISRSCAN and ISRLEMX return codes

ISRSCAN		ISRLEMX	
12	Member not found.	**1-15**	Parameter *n* was too long, where *n* = 1 to 15.
16	OPEN error on DDNAME=IN.	**16**	Too many parameters.
20	I/O error on DDNAME=IN.	**17**	Too few parameters.
24	OPEN error on DDNAME=OUT.	**20**	Severe error in expand module. An error message should be printed in the ISRLMSG data set.
28	I/O error on DDNAME=OUT.		

2. In this example, the second step calls the PL/I optimizing compiler by using the temporary data set designated by &&TEMP1 as the input data set. The concatenation sequence is passed to the compiler through SYSLIB DD statements, to allow inclusion of subsidiary members referenced by %INCLUDE statements in the source text.

   The object module is directed to a partitioned data set with a three-level name composed of the project name, the first library name, and a type qualifier of OBJ. The member name for the object module is the same as the primary member to be compiled.

   The compiler listing is directed to SYSOUT class A, as specified.

JCL generation—assemblers and linkage editor

For batch assembly and link-edit, an optional SYSTERM DD statement is generated (if you specify TERM) besides the JCL shown in “JCL generation—compilers” on page 338, as follows:

```
//SYSTERM  DD  DSN=prefix.member.TERM,DISP=(MOD,CATLG)
```

where:

prefix The data set prefix in your TSO user profile

member For members of partitioned data sets, this is the same member name specified on the entry panel. For sequential data sets, this name is TEMPNAME.

Assembler (option 5.1)

Batch Assembler enables you to invoke either High Level Assembler or Assembler H. Both are called from the Batch Assembler panel, shown in Figure 195. For information about Assembler allocation data sets, see the topic about Allocation Data Sets in the *z/OS ISPF User's Guide Vol I*.

```
  Menu  RefList  Utilities  Help
 ____________________________________________________________________________
                                Batch Assembler
                                                                   More:     +
ISPF Library:
   Project . . . PDFTDEV
   Group . . . . LSACKV  . . . ________ . . . ________ . . . ________
   Type  . . . . ASM
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ______________________________________________________

                                                   Assembler
List ID  . . . . . ________  (Blank for hardcopy)   1  1. High Level Assembler
SYSOUT class . . . ________________  (For hardcopy)    2. Assembler H

Assembler options:
  Term  . . . ______  (TERM or NOTERM)
  Other . . . ____________________________________________________________

Command ===> ______________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 195. Batch Assembler panel (ISRJP01)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*, except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained here and in "Input data sets" on page 308:

Term In the Term field, enter TERM if you want ISPF to generate a terminal data set. A *terminal data set* contains a synopsis of the error messages produced by the Assembler. If the input data set is partitioned, the terminal data set name is:

```
prefix.member.TERM
```

where *prefix* is the data set name prefix in your TSO user profile, if you have one, and *member* is the name of the member being assembled. However, if the input data set is sequential, the terminal data set name is:

```
prefix.TEMPNAME.TERM
```

Enter NOTERM in the Term field to avoid generating the terminal data set. This is a required field.

Other Enter any other options you need in the Other field.

COBOL compile (option 5.2)

ISPF generates an ISPEXEC SELECT PGM(IGYCRCTL) statement to invoke a COBOL compiler using the values you enter on the Batch COBOL Compile panel, shown in Figure 196. For information about COBOL allocation data sets, see the topic about Allocation Data Sets in the *z/OS ISPF User's Guide Vol I*.

```
  Menu  RefList  Utilities  Help
 ____________________________________________________________________________
                              Batch COBOL Compile
                                                                   More:     +
ISPF Library:
   Project . . . PDFTDEV
   Group . . . . LSACKV  . . . ________ . . . ________ . . . ________
   Type  . . . . COBOL
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ______________________________________________________

List ID . . . . . . . ________  (Blank for hardcopy)
SYSOUT class  . . . . ________________  (If hardcopy requested)

Compiler options:
  Term  . . . NOTERM         (TERM or NOTERM)
  Other . . . ____________________________________________________________

Additional input libraries:
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 196. Batch COBOL Compile panel (ISRJP02)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I*, except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained here and in "Input data sets" on page 308:

Term In the Term field, enter TERM if you want ISPF to generate a terminal data set. A *terminal data set* contains a synopsis of the error messages produced by the COBOL compiler. If the input data set is partitioned, the terminal data set name is:

```
prefix.member.TERM
```

where *prefix* is the data set name prefix in your TSO user profile, if you have one, and *member* is the name of the member being assembled. However, if the input data set is sequential, the terminal data set name is:

```
prefix.TEMPNAME.TERM
```

Enter NOTERM in the Term field to avoid generating the terminal data set. This is a required field.

Other If you plan to run VS COBOL II interactive debug after you compile your program, enter TEST, RESIDENT, and any other options you need in the Other field.

VS FORTRAN compile (option 5.3)

The Batch VS FORTRAN Compile panel is shown in Figure 197.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                            Batch VS FORTRAN Compile
                                                                 More:     +
ISPF Library:
   Project . . . PDFTDEV
   Group . . . . LSACKV  . . . ________ . . . ________ . . . ________
   Type  . . . . FORT
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ______________________________________________

List ID . . . . . . . ________  (Blank for hardcopy)
SYSOUT class  . . . . ______________  (If hardcopy requested)

Compiler options:
  Term  . . . NOTERM         (TERM or NOTERM)
  Other . . . ____________________________________________________

Additional input libraries:
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 197. Batch VS FORTRAN Compile panel (ISRJP03)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* except List ID, which is explained in "List data sets" on page 309, "Additional input libraries", which is explained here and in "Input data sets" on page 308:

Term In the Term field, enter TERM if you want ISPF to generate a terminal data set. A *terminal data set* contains a synopsis of the error messages produced by the VS FORTRAN compiler. If the input data set is partitioned, the terminal data set name is:

```
prefix.member.TERM
```

where *prefix* is the data set name prefix in your TSO user profile, if you have one, and *member* is the name of the member being assembled. However, if the input data set is sequential, the terminal data set name is:

```
prefix.TEMPNAME.TERM
```

Enter NOTERM in the Term field to avoid generating the terminal data set. This is a required field.

Other If you plan to run FORTRAN interactive debug after you compile your program, enter TEST in the Other field, along with any other options you need.

PL/I compile (option 5.5)

The Batch PL/I Compile option enables you to invoke either OS PL/I Version 2 or PL/I for MVS and VM, using the values specified on the Batch PL/I compile panel shown in Figure 198 on page 343.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                              Batch PL/I Compile
                                                                   More:     +
ISPF Library:
   Project . . . PDFTDEV
   Group . . . . LSACKV  . . . ________ . . . ________ . . . ________
   Type  . . . . PLI
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ____________________________________________________
                                                   Compiler
List ID  . . . . . ________  (Blank for hardcopy)   1  1. OS PL/I V2R3
SYSOUT class . . . ________________  (For hardcopy)    2. PL/I for MVS and VM
                                                       3. VA PL/I for OS/390

Compiler options:
       ===> ____________________________________________________________

Additional input libraries:
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 198. Batch PL/I Compile panel (ISRJP05)

All the fields on this panel are explained in the “ISPF Libraries and Data Sets chapter” of the *z/OS ISPF User’s Guide Vol I* except List ID, which is explained in “List data sets” on page 309, “Additional input libraries”, which is explained in “Input data sets” on page 308.

Compiler
Choose the compiler you want to use from the list presented.

VS Pascal compile (option 5.6)

The Batch VS Pascal Compile panel is shown in Figure 199 on page 344.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                            Batch VS PASCAL Compile
                                                                  More:     +
ISPF Library:
   Project . . . PDFTDEV
   Group . . . . LSACKV  . . . ________ . . . ________ . . . ________
   Type  . . . . PASCAL
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ____________________________________________________

List ID . . . . . . . ________  (Blank for hardcopy)
SYSOUT class  . . . . ________________  (If hardcopy requested)

Compiler options:
       ===> ____________________________________________________________

Additional input libraries:
       ===> ____________________________________________________________
Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 199. Batch VS Pascal Compile panel (ISRJP06)

All the fields on this panel are explained in the “ISPF Libraries and Data Sets chapter” of the *z/OS ISPF User’s Guide Vol I* except List ID, which is explained in “List data sets” on page 309, and “Additional input libraries”, which is explained in “Input data sets” on page 308.

Binder/linkage editor (option 5.7)

The Batch Binder or Linkage Editor is called from the Batch Binder/Linkage editor panel. The panel in Figure 200 on page 345 shows entries you might make when link-editing a VS Pascal program.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------------
                         Batch Binder/Linkage Editor
                                                                   More:     +
ISPF Library:
   Project . . . PDFTDEV
   Group . . . . COMMON  . . . ________ . . . ________ . . . ________
   Type  . . . . LEL
   Member  . . . ________  (Blank or pattern for member selection list)

Other Partitioned or Sequential Data Set:
   Data Set Name  . . ____________________________________________________

                                                        Processor
List ID . . . . . ________  (Blank for hardcopy)        _  1. Binder
SYSOUT class  . . ______________  (For hardcopy)        _  2. Linkage Editor

Linkage editor/binder options:
  Term  . . . ______    (TERM or blank)
  Other . . . ____________________________________________________________

Command ===> ____________________________________________________________
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 200. Batch Binder Linkage/Editor panel (ISRJP07B)

All the fields on this panel are explained in the "ISPF Libraries and Data Sets chapter" of the *z/OS ISPF User's Guide Vol I* except List ID, which is explained in "List data sets" on page 309, and here:

Binder
Determines whether the Linkage Editor (NOBINDER) or Binder (BINDER) is invoked.

Note: The binder is available only if DFSMS 1.1, or later, is installed.

Term In the Term field, enter TERM if you want ISPF to generate a terminal data set. A *terminal data set* contains a synopsis of the error messages produced by the linkage editor. If the input data set is partitioned, the terminal data set name is:

```
prefix.member.TERM
```

where *prefix* is the data set name prefix in your TSO user profile, if you have one, and *member* is the name of the member being assembled.

Note: Sequential data sets are invalid when using the Linkage Editor.

Leave the Term field blank to avoid generating the terminal data set.

Other Enter any other options you need in the Other field.

SYSLIB
The name of the data set that is to contain the ISPF library concatenation sequence used to resolve any copy statements specified in your program. See "Input data sets" on page 308 and the SYSLIB Data Set section of the topic about Allocation Data Sets in the *z/OS ISPF User's Guide Vol I* for more information.

SYSLIN
The name of the data set that is to contain the object module. The SYSLIN field is provided to accommodate the VS Pascal XA and NOXA processing

options. See “Input data sets” on page 308 and the SYSLIN Data Set section of the topic about Allocation Data Sets in the *z/OS ISPF User’s Guide Vol I* for more information.

VS COBOL II interactive debug (option 5.10)

Before you can run VS COBOL II interactive debug in batch, you must first perform these tasks in the order shown:

1. Compile the program using the VS COBOL II compiler (option 4.2 or option 5.2) with the TEST and RESIDENT options.
2. Use the linkage editor (option 4.7 or option 5.7) to generate an output load module, which VS COBOL II interactive debug will use as input.

The VS COBOL II Interactive Debug panel is shown in Figure 201.

```
  Menu  RefList  Utilities  Help
 ------------------------------------------------------------------------
                        VS COBOL II Interactive Debug
                                                                More:     +
 ISPF Library:
    Project . . . LSACKV
    Group . . . . PRIVATE   (Type = LOAD assumed)
    Member  . . . ________  (Blank or pattern for member selection list)

 Other Partitioned or Sequential Data Set:
    Data Set Name  . . ______________________________________________________

 List ID . . . . . . . ________  (Blank for hardcopy)
 SYSOUT class  . . . . A               (If hardcopy requested)

 Debug command data set:
        ===> ____________________________________________________________

 Additional input libraries:
        ===> ____________________________________________________________
        ===> ____________________________________________________________
 Command ===> ___________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 201. VS COBOL II Interactive Debug panel (ISRJP10)

All the fields on this panel are explained in the “ISPF Libraries and Data Sets chapter” of the *z/OS ISPF User’s Guide Vol I* except List ID, which is explained in “List data sets” on page 309, “Additional input libraries”, which is explained in “Input data sets” on page 308, and here:

Note: For VS COBOL II interactive debug, any additional input libraries that you enter to complete the search sequence must be LOAD libraries only.

Debug command data set
In the “Debug command data set” field, enter the name of the data set that contains the DEBUG command that you want VS COBOL II interactive debug to enter during batch processing. See *VS COBOL II Application Programming Debugging Guide* for more information.

Member parts list (option 5.12)

When you select the Batch Member Parts List option (5.12), the panel shown in Figure 202 is displayed.

The only difference between this panel and the Foreground Member Parts List panel is that option 1 (print member parts) is called *Browse/Print member parts list* in foreground. The foreground version does not print your member parts list unless you use the Foreground Print Options panel to do so.

Otherwise, this version operates the same as the foreground version. See "Member parts list (option 4.12)" on page 329 for more information about using the member parts list function.

The listing is 120 characters wide and uses ANSI printer controls.

```
  Menu  RefList  Utilities  Help
 ____________________________________________________________________________
                            Batch Member Parts List

 1 Print member parts
 2 Write member parts data set

 ISPF Library:
    Project . . . LSACKV
    Group . . . . PRIVATE  . . . ________ . . . ________ . . . ________
    Type  . . . . ________
    Member  . . . ________  (Blank or pattern for member selection list)

 Language . . . . COB      (Defaults to Type value)

 Groups for Primary members . . . 1  (1, 2, 3, or 4)

 SYSOUT class . . . ________________  (Defaults to A )

 Output Data Set:          (option 2 only)
    Data Set Name  . . ____________________________________________________
 Option ===> ______________________________________________________________
  F1=Help     F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 202. Batch Member Parts List panel (ISRJP12)

C/370 compile (option 5.13)

ISPF supports the C/370 compiler through dialogs supplied with the C/370 compiler (5688-040). See *C Compiler User's Guide for MVS*, SC09-1129 for additional information.

REXX/370 compile (option 5.14)

ISPF supports the REXX/370 compiler through dialogs supplied with the REXX/370 compiler (5695-013). See *IBM Compiler and Library for REXX/370 User's Guide and Reference*, SH19-8160, for additional information.

Ada/370 compile (option 5.15)

ISPF supports the Ada/370 compiler and its tools through dialogs supplied with the Ada/370 compiler (5706-292). See *IBM Ada/370 User's Guide*, SC09-1415, for additional information.

AD/Cycle C/370 compile (option 5.16)

ISPF supports the AD/Cycle C/370 compiler through dialogs supplied with the AD/Cycle C/370 compiler (5688-216). See *IBM SAA AD/Cycle C/370 Programming Guide* SC09-1356, for additional information.

ISPDTLC compile (option 5.18)

ISPF supports the ISPF Dialog Tag Language compiler by running the ISPDTLC function. See *z/OS ISPF Dialog Tag Language Guide and Reference* for more information.

The ISPDTLC interface panels are identical to those in the Foreground option. The first panel can be seen in Figure 192 on page 334.

The fields on this panel are explained in the topic "Using the Conversion Utility" in *z/OS ISPF Dialog Tag Language Guide and Reference*.

OS/390 C/C++ compile (option 5.19)

ISPF supports the OS/390 C/C++ compiler and its tools through dialogs supplied with the OS/390 C/C++ compiler (5647-A01). For information about OS/390 C/C++, refer to the *OS/390 C/C++ User's Guide*.

Chapter 8. Command (option 6)

When you select this option, the ISPF Command Shell panel shown in Figure 203 is displayed. You can enter TSO commands, CLISTs, and REXX EXECs on the Command line of any panel and in the Line Command field on data set list displays (option 3.4). However, the ISPF Command Shell panel provides additional capabilities:

- You can enter TSO commands, ISPF commands, CLISTs, and REXX execs in a separate, but optional, **ISPF Command** field. This field is displayed only if your installation chooses to do so. The default panel shown in Figure 203 does not display this field. When you use this field, commands that are typed in the TSO Command Entry field (==>) are not blanked out when you enter the SPLIT command to split the screen.

  Note: If you use this field, you will not have access to the saved command area (see "The saved command area" on page 351).
- You can enter Session Manager mode, but only if this licensed program is installed. See "Using the session manager" on page 352 for more information.
- You can enter a long command that continues on these two lines.

```
  Menu  List  Mode  Functions  Utilities  Help
_____________________________________________________________________________
                                ISPF Command Shell
Enter TSO or Workstation commands below:

===> ________________________________________________________________________
____________________________________________________________________________
____________________________________________________________________________

Place cursor on choice and press enter to Retrieve command

=>
=>
=>
=>
=>
=>
=>
=>
=>
=>

 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 203. ISPF Command Shell panel (ISRTSO)

ISPF command shell panel action bar

The ISPF Command Shell panel action bar choices function as follows:

Note: The ISPF Command Shell panel action bar contains three pull-down choices that let you control the saved command area.
- List
- Mode

© Copyright IBM Corp. 1980, 2007

- Functions

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

List The List pull-down offers you these choices:

Update On Makes the list of commands in the saved command area *live*; that is, new commands are appended automatically.

Update Off Makes the list of commands in the saved command area *static*; that is, new commands are not appended automatically.

The current setting is shown as an unavailable choice.

Mode The Mode pull-down offers you these choices:

Retrieve Allows commands to be retrieved from the saved command area and placed on the TSO Command Entry field (==>) so that you can edit them before they are executed. This mode is the default.

Execute Allows commands to be retrieved from the saved command area and executed in one step.

Delete Allows you to delete commands from the saved command area without executing the commands. Place the cursor on the command to be deleted and press Enter. The command will be blanked out. This process allows you to delete a command if you are running with Update mode set off.

The current setting is shown as an unavailable choice.

Functions
The Functions pull-down offers you this choice:

Compress List Removes duplicate entries and blank spaces in the saved command area if you are running with Update mode set off. Entries are compressed automatically in Update mode.

TSO command
Sets the command shell to route commands to TSO

Workstation command
Sets the command shell to route commands to your workstation.

Notes:

1. Workstation command is available only if you are running the ISPF Client Server.
2. Any command may be prefixed with either `TSO` or `WS` to override the command function setting.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down provides general information on the TSO Command processor panel, including line I/O mode and Session Manager mode, and restrictions on entering commands.

The saved command area

The ISPF Command Shell panel has a saved command area (the bottom portion of the screen) that contains a list of up to 10 commands that you have saved; see Figure 204 for an example. These commands are point-and-shoot fields. What happens when you select a command depends on the mode you specify from the Mode pull-down menu on the action bar.

```
  Menu  List  Mode  Functions  Utilities  Help
_____________________________________________________________________________

                              ISPF Command Shell
Enter TSO or Workstation commands below:

===> ________________________________________________________________________
_____________________________________________________________________________
_____________________________________________________________________________

Place cursor on choice and press enter to Retrieve command

=> status
=> xmit carvm3.userid da('userid.private.clist(types)')seq
=> TIME
=> RECEIVE
=> XMIT CARVM3.SCOTT DA('USERID.PROJ.PANELS(ISAJP10)') SEQ
=> PERMIT 'BOB.*' GENERIC ACCESS(READ) ID(*)
=> rexec -1 SQUIRT -p SPARKY p:\acI13\samples\isr prim\os213\isr_prim
=> XMIT CARVM3.userid DA('USERID.BUILD.LIST77')
=> ssdf
=> XMIT CARVM3.userid DA('USERID.trace')

 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 204. ISPF Command Shell panel with saved commands (ISRTSO)

Entering TSO commands, CLISTs, and REXX EXECs

You do not need to enter TSO before the command on this panel as you do on other panels, unless the command exists in both ISPF and TSO and you want to process the TSO command. If you use TSO, your processed command is blanked out when the ISPF Command Shell panel is displayed again.

TSO commands, CLISTs, and REXX EXECs entered are invoked using the ISPF SELECT CMD service. Variable names starting with an ampersand (&) are evaluated by ISPF. If you want the underlying command processor to see the ampersand you must specify 2 ampersands. For example:

```
DEF NONVSAM(NAME('MY.DATASET') DEVT(0000) VOLUME(&&SYSR2))
```

For example, the HELP, PRINT, and CANCEL commands are interpreted as the ISPF HELP, PRINT, and CANCEL commands, unless you precede them with TSO. Therefore, to get TSO HELP information, enter:

```
===> TSO HELP xxx
```

Rules for entering TSO commands

Do not enter these commands under ISPF:

- LOGON and LOGOFF
- ISPF, PDF, or ISPSTART

- TEST
- Commands that are restricted by TSO or ISPF
- Commands that call a program authorized by the Authorized Program Facility (APF), except for the TSO CALL command
- ISPEXEC service calls.

Rules for entering CLISTs and REXX EXECs

You can enter a CLIST name or REXX exec name on this panel, but these restrictions apply:

- The CLIST or REXX exec cannot call the restricted commands shown in the preceding list. However, this does not apply to ISPEXEC, which can be called in a CLIST or REXX exec.
- CLIST error exits are not entered for ABENDs.
- CLIST TERMIN command procedure statements may cause unwanted results.

Note: Remember that a command issued through an alias may contain some of the characteristics listed here and thus may cause unwanted results.

Using the session manager

If the Session Manager licensed program is installed and available, you can use it by selecting Session Manager mode on the ISPF Settings panel. For information on altering the PDF configuration table to allow you to enter Session Manager mode, refer to *z/OS ISPF Planning and Customizing*.

If you select this option, any display output is displayed in the Session Manager TSOOUT stream.

Note: If GDDM/ISPF mode is active, Session Manager does not get control of the screen. GDDM/ISPF mode is started when a GRINIT service has been issued, but a GRTERM service has not been issued. See *z/OS ISPF Services Guide* for more information about these two services.

The function key definitions are not transferred to the Session Manager from ISPF. When the command ends, the Session Manager prompts you to enter a null line to return to ISPF control and displays the TSO Command Processor panel again when you do so.

If you do not select Session Manager mode, terminal I/O occurs as though the Session Manager were not installed. The terminal operates in normal TSO fashion. Any communication with the command is in line-I/O mode. When the command ends, three asterisks (***) are displayed. Press Enter to display the TSO Command Processor panel again in full screen mode.

To interrupt a TSO command, CLIST, or REXX exec, press the PA1 key. The TSO command ends and the TSO Command Processor panel is displayed again. If terminal input is inhibited, press the Reset key before pressing the PA1 key. If you are in Session Manager mode, enter a null line to return to ISPF full-screen mode.

When the TSO Command Processor panel is displayed again, the command that was just processed is displayed to the right of the arrow. Enter another command or the END command to return to the ISPF Primary Option Menu.

For terminals with primary and alternate screen sizes, ISPF does not check to make sure the same screen settings are in effect when a command, CLIST, or REXX exec ends. If you call a CLIST, REXX exec, or command that changes the screen settings, you are responsible for saving and restoring them before control is returned to ISPF.

Chapter 9. Dialog test (option 7)

This topic describes Dialog Test, option 7 on the ISPF Primary Option Menu.

Dialog Test (option 7) provides you with facilities for testing both complete ISPF applications and ISPF dialog parts, including functions, panels, variables, messages, tables, and skeletons. The Dialog Test option allows you to:

- Call selection panels, command procedures, and programs
- Display panels
- Add new variables and change variable values
- Display a table's structure and status
- Display, add, modify, and delete table rows
- Browse the ISPF log
- Process dialog services
- Add, modify, and delete function and variable trace definitions
- Add, modify, and delete breakpoint definitions.

You can use TSO TEST to complement this option if you want to examine and manipulate non-ISPF storage areas.

You usually test a dialog in one of two ways:

- Test individual dialog parts, including panels, skeletons, and messages, without calling a function or a selection panel. Eventually, you end your test session by entering the END command on the Dialog Test Primary Option Panel.
- Test dialog functions, including programs, commands, and selection panels, using the Functions option (7.1). You can define traces and breakpoints before calling the function.

Any requested traces for variable usage and dialog service calls are written to the ISPF log. You can browse the log using the Log option (7.5).

If you define a breakpoint and the function gets to it, dialog processing is suspended, and Dialog Test displays the Breakpoint Primary Option Panel (Figure 227 on page 399). At this point, you can access and manipulate dialog parts, such as variables, tables, and so forth. Then, if you select the Go option from the Breakpoint Primary Option Panel, the dialog resumes processing.

When the processing is complete, you are returned to the Functions option (7.1). If you select the Cancel option from the Breakpoint Primary Option Panel, the dialog is canceled and the first primary option panel that you were shown during your terminal session is displayed again. For example, if the first screen displayed when you began your session was a master application panel that is different from the ISPF Primary Option Menu, that master application panel is displayed again.

The dialog test environment

The Dialog Test Primary Option Panel, shown in Figure 205 on page 356, follows the conventions for a primary option panel. If you use the RETURN command from one of the selected Dialog Test options, the Dialog Test Primary Option Panel is displayed again. If you use the END command from this panel, you return to the ISPF Primary Option Menu.

© Copyright IBM Corp. 1980, 2007

Dialog test (option 7)

When you enter Dialog Test from the ISPF Primary Option Menu, you enter a new user application with an ID of ISR. When you enter Dialog Test from the ISPF primary option panel, you enter a new user application with an ID of ISP. All options listed on the Dialog Test Primary Option Panel operate in this context. If you call a new function using the Functions options (7.1), a SELECT service call is performed, and the rules for the SELECT service are followed.

```
 Menu  Utilities  Compilers  Options  Status  Help
 ──────────────────────────── Dialog Test ──────────────────────────────
  Menu  Utilities  View  Help
 ─────────────────────────────────────────────────────────────────────
                        Primary Option Panel                          RN

 1 Functions       Invoke dialog functions/selection panel _________
 2 Panels          Display panels
 3 Variables       Display/set variable information                   SH
 4 Tables          Display/modify table information
 5 Log             Browse ISPF log
 6 Dialog Services Invoke dialog services                             RN
 7 Traces          Specify trace definitions
 8 Breakpoints     Specify breakpoint definitions                     A
 T Tutorial        Display information about Dialog Test              5.5
 X Exit            Terminate dialog testing
 Option ===> ____________________________________________________
  F1=Help       F2=Split      F3=Exit       F4=Expand     F5=Rfind
  F6=Resize     F7=Backward   F8=Forward    F9=Swap      F10=Actions

Option ===> 7
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 205. Dialog test primary option panel (ISPYXD1)

Note: You can set the application ID under which you enter the Dialog Test function using the Dialog Test appl ID choice from the Options pull-down on the ISPF Primary Option Menu or using the Dialog Test appl ID choice from the Test pull-down on an Edit panel.

After you begin an application under Dialog Test, you can enter the DTEST command with one of its parameters as a quicker way to start a dialog test function. For example, if you enter **DTEST 8** on the command line, the Option 7.8 Breakpoints panel is displayed. The other parameters of the DTEST command also match the dialog test function they perform:

1 invoke Functions panel
2 invoke Display Panel panel
3 invoke Variables panel
4 invoke Tables panel
5 display Browse Log panel
6 invoke Dialog Services panel
7 invoke Traces selection panel
8 invoke Breakpoint panel

You must use a parameter with the DTEST command, otherwise an error message appears. After you complete the entries on whichever dialog test panel you invoke, leaving the panel returns you to the application you were running with the new entries in place.

Dialog Test is itself a dialog and, therefore, uses dialog variables. Because it is important to allow your dialog to operate without interference, as though in a production environment, Dialog Test accesses and updates variables independently of your dialog variables.

All breakpoints and traces that you set in Dialog Test exist only while you remain within the Dialog Test option.

You should always allocate the ISPF log when using Dialog Test. Do not suppress its generation by typing `0` in the "Primary pages" field that appears on the "Log Data set defaults" and "List Data set defaults" choices from the Log/List pull-down on the ISPF Settings panel. Dialog Test writes trace data to the log when you request it. Also, if Dialog Test finds an unexpected condition, it writes problem data to the log.

When you enter Dialog Test, you are given these ISPF facilities:

- All functions you normally get by specifying the TEST parameter on the ISPSTART command
- Logging of all severe errors, both from user dialogs and Dialog Test. This is normally done when you specify TRACE or TRACEX on the ISPSTART command.
- Suspension of the logging of all ISPEXEC dialog service requests. Such logging normally occurs when you specify TRACE or TRACEX on the ISPSTART command. You should use the Traces option (7.7).

These facilities become active for all logical screens when you are using split-screen mode. At the completion of the last dialog test session (dialog test is no longer active in any logical screen), these options will be restored to the original values established during dialog manager start-up. Optionally, by making the appropriate selection on the ISPF Settings panel, the facilities established by dialog test will remain in effect after the last dialog test session terminates.

Dialog test primary option panel action bar

The Dialog Test Primary Option Panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

View Allows you to select whether the Add row, Modify row, and Display row panels are displayed in pop-up windows and whether Dialog Services (option 7.6) are displayed in a pop-up. By displaying the panel in a pop-up window, you can see the panel underneath and move the window. By displaying the panel as a full-screen display, you can see more data. The setting you choose will remain until you change it.

Help The Help pull-down provides general information about Dialog Test topics as well as information about each available choice on the Dialog Test Primary Option panel.

Using variables

When you select the Dialog Test option from the ISPF Primary Option Menu, you are given a new function pool, a new shared pool, and the profile pool for the application ID under which you entered Dialog Test. When you select Dialog Test from the ISPF Primary Option Menu, you are given a new function pool, a new shared pool, and the ISPPROF profile pool. These pools are used if you set a variable, display a panel, call an ISPF service, and so forth. When you call a new dialog, Dialog Test uses the SELECT service, and follows the rules for the creation of new variable pools. For example, if you call a new dialog using the NEWPOOL option, Dialog Test creates new shared and function variable pools for you. The profile variable pool, ISRPROF or ISPPROF, remains as it was.

If you set a dialog variable in the shared pool from a dialog running under Dialog Test and then call the dialog again from the Command line, you cannot retrieve the value of that variable.

Dialog variables should be initialized and set in the context of the dialog's processing. A dialog's function variable pools are created when it is called; that is, when the SELECT is done. Therefore, to set function variables in newly created pools, you must define a breakpoint early in your dialog's processing, at a point before the function is called.

For example, if you call a dialog with the NEWPOOL parameter, you must define a breakpoint in the dialog before the first function is called to access that dialog's function and shared variable pools. You can change the dialog's profile variable pool before calling the dialog, since a new profile variable pool is not created.

When your dialog ends, all variable pools that were created when the dialog was called are deleted.

Note: ISPF does not support TSO global variables. You can find a severe dialog test error when testing a dialog that refers to a global variable.

Severe error handling

If your dialog finds a severe error when it calls a dialog service, the error is handled as requested by the dialog. The current CONTROL service ERRORS setting, CANCEL or RETURN, determines what is done. If CANCEL is in effect, you can choose whether to continue dialog testing when the Error Message panel is displayed.

Note: If you choose not to continue dialog testing, you return to the ISPF Primary Option Menu. The TEST and TRACE options set by dialog test are restored to the values originally established during dialog manager start-up. Optionally, by making the appropriate selection on the ISPF Settings panel, the facilities established by dialog test will remain in effect after the last dialog test session terminates.

If you find a severe error when manipulating your dialog at a breakpoint, Dialog Test assumes that the CONTROL service ERRORS setting is CANCEL. For example, if you display a panel at a breakpoint and that panel is not found, the Error Message panel is displayed. This occurs even if your current dialog has an ERRORS setting of RETURN.

Regardless of the ERRORS setting, all your severe errors are logged.

If Dialog Test finds a severe error during its processing, the details are logged and this message is shown to you on an error message display:

```
Test severe error
Details precede this message in the ISPF log
```

Dialog Test errors can occur because:

- Proper ISPF libraries are not being used.
- A programming problem has been found.
- You have attempted to process Dialog Test.
- You have called a Dialog Test option without being in test mode or without calling Dialog Test first.

Browse the ISPF log to find the problem; see "Log (option 7.5)" on page 385 for more information.

Commands

You can enter ISPF primary commands on Dialog Test panels. Seven commands have special meaning during Dialog Test operations. You enter them in the Command line of the applicable Dialog Test option panel. These commands, and the Dialog Test options with which they function, are:

Primary Command	Valid Options
CANCEL	
	• Variables (option 7.3) • Tables (option 7.4)[1] • Traces (option 7.7)[2] • Breakpoints (option 7.8)
END	
	• Variables (option 7.3) • Tables (option 7.4)[3] • Traces (option 7.7) [2] • Breakpoints (option 7.8)
LOCATE	
	• Variables (option 7.3) • Tables (option 7.4)[4] • Traces (option 7.7) [2] • Breakpoints (option 7.8)
NEXT/PREV	
	• Tables (option 7.4)[4]
QUAL	
	• Breakpoints (option 7.8)
RESUME	

1. Valid only with Tables options 3 and 4.
2. Valid only with Traces options 1 and 2.
3. Valid only with Tables options 1, 3, and 4.
4. Valid only with Tables options 1 and 3.

	• Breakpoints (option 7.8)
SORT	
	• Variable (option 7.3)

Dialog Test has three line commands that have special meaning during testing operations. These commands, and the options with which they function, are:

Line Command	Valid Options
D (delete)	
	• Variables (option 7.3) • Tables (option 7.4) [1] • Traces (option 7.7) [2] • Breakpoints (option 7.8)
I (insert)	
	• Variables (option 7.3) • Tables (option 7.4) [1] • Traces (option 7.7) [2] • Breakpoints (option 7.8)
R (repeat)	
	• Tables (option 7.4) [1] • Traces (option 7.7) [2] • Breakpoints (option 7.8)

When using the Dialog Test primary and line commands, you should be aware that:

- You can specify both a primary command and line commands before you press the Enter key.
- You can enter multiple line commands on the display.
- You cannot carry out a deletion if one of the included lines contains another line command.
- You can delete lines that contain an input error.
- The line commands are processed in row order when you press the Enter key. Any fields changed in the row are handled before a line command is processed.
- A primary command is handled after processing for all line commands is complete.
- As in the ISPF editor, you can specify a number with each line command to denote repetitive operation, unless you are using the Variables option (7.3). To avoid conflict with the I (insert) line command, the Variables option does not allow you to type a number along with the D command to delete more than one line simultaneously. Therefore, enter a single D line command on each line you want to delete. Unlike the ISPF editor, the Variables option does not support block deletes; however, you can enter this command on more than one line before pressing the Enter key.

Ending the current option without saving changes

The CANCEL command ends the current option. Any changes made to the data are ignored.

Saving changes

The END command ends the current option. Any changes made to the data now take effect.

Finding a character string

The LOCATE command searches for a character string and positions a scrollable display to the next row that contains the string. The scan starts at the end of the first row currently being displayed. A message is displayed indicating the result of the scan.

LOCATE *string*

where:

string The character string you are trying to find. If the string ends in an asterisk (*), a scan for the characters preceding the asterisk is done. The asterisk is optional in the Variables option (option 7.3).

Displaying breakpoint qualification data

The QUAL command can only be entered from the Breakpoints pop-up window. It displays the breakpoint qualification data.

The same breakpoint qualification data can be obtained using the Qualifications choice on the Qualify pull-down.

Restoring the format of the Breakpoints panel

The RESUME command is entered on the Breakpoints panel when qualification parameter values are shown. It restores the format of the Breakpoints panel. Each breakpoint that has qualification is flagged by the characters `*QUAL*` in columns 75 to 80 on that line of the Breakpoints panel.

Dialog test line commands

These line commands have special meaning during testing operations:

D – deleting lines

The D command deletes one line or *n* lines starting with this line. The syntax is:

`D[n]`

If you are using the Variables option (7.3), the *n* operand does not apply. To avoid conflict with the I (insert) line command, the Variables option does not allow you to type a number along with the D command to delete more than one line simultaneously. Therefore, enter a single D line command on each line you want to delete. You can enter this command on more than one line before pressing the Enter key.

I – inserting lines

The I command inserts one line or *n* lines directly after this line, with underscores and quotation marks in the appropriate fields. The syntax is:

`I[n]`

R – repeating lines

The R command repeats this line once or *n* times. The syntax is:

`R[n]`

Setting a keylist for dialog test

Depending on your needs and preferences, you may wish to set a dialog test-specific keylist to enhance productivity. To modify the default function key settings, go to the Dialog Test Primary Option Panel, type KEYS on the Command line, and press Enter to display the pop-up window shown in Figure 206. Or, you may perform these steps to display the pop-up:

1. Select Option 0 from the ISPF Primary Option Menu.
2. Select Keylist settings from the Function keys pull-down on the ISPF Settings panel action bar.
3. Use a slash to select the ISPTEST Keylist; then select Change from the Functions pull-down.

```
                              Keylist Utility
  File
 ------------------------------------------------------------------------------
                         ISR Keylist ISRTEST Change         Row 1 to 9 of 24

 Make changes and then select File action bar.

 Keylist Help Panel Name . . . ISRTESTH

 Key       Definition                                  Format  Label
 F1 . . .  HELP                                        SHORT   Help
 F2 . . .  SPLIT                                       LONG    Split
 F3 . . .  EXIT                                        SHORT   Exit
 F4 . . .  EXPAND                                      SHORT   Expand
 F5 . . .  RFIND                                       SHORT   Rfind
 F6 . . .  RESIZE                                      SHORT   Resize
 F7 . . .  UP                                          LONG    Backward
 F8 . . .  DOWN                                        LONG    Forward
 F9 . . .  SWAP                                        LONG    Swap

 Command ===>                                          Scroll ===> PAGE
  F1=Help       F2=Split       F3=Exit       F7=Backward    F8=Forward
  F9=Swap       F10=Actions    F12=Cancel
```

Figure 206. Keylist change panel (ISPKLUCH)

On the Keylist Change panel, you can reassign existing function keys by typing over the information in the data fields, or create a new function key assignment to suit your needs. For example, you could assign the GO command to F4 if you typically issue GO many times during a dialog test.

If you press F3 or select Save and Exit from the File pull-down, the values that you have assigned will be valid when you return to Dialog Test. If you select Cancel from the File pull-down, the fields return to their original values.

Functions (option 7.1)

The Functions option (7.1) allows you to test a dialog function without having to build supporting code or panels. Dialog functions include panels, command procedures, and programs. The name of the dialog function and the parameters you can pass are the same as those that you can specify from a dialog function when you call the SELECT service. When you press the Enter key, a SELECT service is called.

If you call a new function or selection panel at a breakpoint, the previous function or selection panel is suspended and the new one is processed. When the new activity finishes, the Invoke Dialog Function/Selection Panel is displayed. The old activity resumes when you enter the END command. When the function that was called originally finishes processing, the Invoke Dialog Function/Selection Panel is displayed again.

When you select the Functions option, the scrollable panel shown in Figure 207 is displayed to allow you to specify the dialog function that you want to test. Press F8=Forward to display the rest of the panel.

```
Menu  Utilities  Compilers  Options  Status  Help
──────────────────────────────── Dialog Test ────────────────────────────────
  Menu  Save  Utilities  Help
 ──────────────────────────────────────────────────────────────────────────
                 Invoke Dialog Function/Selection Panel
                                                                 More:     +
Invoke selection panel:
   PANEL  . . ________
   OPT  . . . ──────────────────────────────────────────────────────────────
              ───────

Invoke command:
   CMD  . . . ──────────────────────────────────────────────────────────────
              ──────────────────────────────────────────────────────────────
   LANG . . . ____                  (APL, CREX, or blank)
   MODE . . . ____                  (LINE, FSCR, or blank)

Invoke program:
   PGM  . . . ________
   PARM . . . ──────────────────────────────────────────────────────────────
Command ===> ───────────────────────────────────────────────────────────────
 F1=Help       F2=Split      F3=Exit       F4=Expand     F5=Rfind
 F6=Resize     F7=Backward   F8=Forward    F9=Swap       F10=Actions
```

Figure 207. Invoke Dialog Function/Selection panel (ISPYFP)

There are two alternate Invoke Dialog Function/Selection panels, ISPYFPA and ISPYFPB. ISPYFPA is formatted with the most often used fields at the top of the scrollable area. ISPYFPB is similar, but it has a selection field for panel, command, program, or request selection. Unlike panel ISPYFP and ISPYFPA, when you use ISPYFPB the panel, command, program, and request selection fields can all contain values.

You can specify one of the alternate panels using the ISPF Configuration utility. See *z/OS ISPF Planning and Customizing* for more information.

One of the advantages of placing dialog panels in pop-up windows is that you can move the pop-up within the 3270 physical display area to reveal portions of the underlying panel.

See *z/OS ISPF Dialog Developer's Guide and Reference* for instructions on how to move a pop-up window.

Invoke dialog function/selection panel action bar

The Invoke Dialog Function/Selection Panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Save Allows you to specify that you want to save or clear input field information when you exit this panel.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down offers you these choices:

1 General
2 Invoke Function Panel
3 Usage Notes
4 General Dialog Test

Invoke dialog panel fields

To call a function, you must specify a value for either the PANEL, CMD, or PGM field. You cannot specify more than one of these fields.

The fields on the Invoke Dialog Function/Selection Panel function as follows:

Invoke selection panel:
Use these fields to call a selection panel:

PANEL
The name of the selection panel to be displayed.

OPT An optional parameter indicating the first selection option that must be valid from the specified selection panel. This input field continues onto the next line on the panel.

Invoke command:
Use these fields to call a command:

CMD The name of a command procedure written in CLIST or REXX, or any TSO command, to be called as a dialog function. You can include command parameters.

Use the percent sign (%) as a prefix symbol to tell ISPF to remove the Invoke Dialog Function/Selection Panel and use the full screen to display the results of a CLIST or REXX exec call. A complete CLIST or REXX exec call is indicated by three asterisks. Press the Enter key to return to the Invoke Dialog Function/Selection Panel.

If you omit the `%` prefix, ISPF interprets the command as a TSO command, using line mode to display the command results at the bottom of the Invoke Dialog Function/Selection Panel.

LANG
An optional parameter used to specify APL or CREX.

Type `APL` in this field to specify the use of the APL® language. If this is your first APL request during the session, the command specified in the CMD keyword is called and an APL2 environment is established. If this is not your first APL request during this session, the string specified after the CMD keyword is passed to the APL2 workspace and processed.

Type `CREX` in this field to specify that the command specified in the CMD keyword is a REXX exec that has been compiled and

link-edited into a load module, and that a CLIST/REXX function pool is to be used rather than an ISPF module function pool. LANG(CREX) is optional if the compiled REXX has been link-edited to include any of the stubs EAGSTCE, EAGSTCPP, or EAGSTMP.

See *z/OS ISPF Dialog Developer's Guide and Reference* for more information about Compiled REXX processing.

To specify any language other than APL or Compiled REXX, leave this field blank.

MODE
An optional parameter that overrides:

- Automatic line mode entry, caused when a TSO command is entered.
- Automatic full-screen display caused by the % CLIST or REXX exec prefix. However, it does not prevent ISPF from calling the command as a CLIST or REXX exec.

If you leave this field blank, the % prefix has its normal effect. The valid values for this field are:

LINE Used to enter line mode when calling a CLIST or REXX exec.

FSCR Used to enter full-screen mode when calling a TSO command.

Invoke program:
Use these fields to call a program:

PGM The name of a program to be called as a dialog function.

PARM Optional parameters to be passed to the program. This input field continues onto the next line on the panel.

MODE
An optional parameter used to tell ISPF whether to display the program results in line mode or full-screen mode. If you leave this field blank, ISPF uses line mode as the default. The valid values for this field are:

LINE Used to enter line mode when calling a program. Results of the program are displayed at the bottom of the Invoke Dialog Function/Selection Panel.

FSCR Used to enter full-screen mode when calling a program. ISPF removes the Invoke Dialog Function/Selection Panel and uses the full screen to display the program results. Three asterisks show program completion. Press the Enter key to return to the Invoke Dialog Function/Selection Panel.

Invoke request:
Use this field to call a workstation command:

WSCMD A fully qualified workstation command with any of its parameters.

Options:
Use a slash to select these options:

NEWAPPL Indication of whether a new application is being called. Select this option if the function is a new application.

ID A 1- to 4-character ID for a new application. If you call a new application and leave the ID field blank, the default ID of ISP is used. Note that the ID determines the names of the profile and the command table to be used for the application.

NEWPOOL Indication of whether a new shared variable pool is to be created. Select this option if you want to create a new shared variable pool; however, the selection is ignored if NEWAPPL is selected.

PASSLIB Shows that the current set of application-level ISPF libraries, if any sets exist, is to be used by the application being selected. You can select PASSLIB only if you also select NEWAPPL.

Note: For more information about the PASSLIB field, see the description of the SELECT service in *z/OS ISPF Services Guide*.

Panels (option 7.2)

When you are developing panels, you can use the Panels option (7.2) to test newly created or changed panels and messages without having to build supporting code to display them. Any variables referred to and set during panel processing are written to the current function variable pool.

When you select the Panels option (7.2), the panel in Figure 208 is displayed.

```
 Menu  Utilities  Compilers  Options  Status  Help
                    Dialog Test
   Menu  Save  Utilities  Help
                     Display Panel                          er ID . : USERID
                                                            me. . . : 17:23
 Panel name  . . . . . . . _______                          rminal. : 3278
 Message id  . . . . . . . _______     (Optional)           reen. . : 1
 Cursor field  . . . . . . _______     (Optional)           nguage. : ENGLISH
 Cursor position . . . . . _____       (Optional)           pl ID . : ISR
 Message pop-up field  . . _______     (Optional)           O logon : ISPF
                                                            O prefix: USERID
 Enter "/" to select option                                 stem ID : MVS8
    Display in window                                       S acct. : IBMGSA
                                                            lease . : ISPF 5.5

 Command ===> _____________________________________
  F1=Help      F2=Split     F3=Exit      F4=Expand
  F5=Rfind     F6=Resize    F7=Backward  F8=Forward

Option ===> 7
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 208. Display panel (ISPYP1)

Display panel action bar

The Display Panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Save Allows you to specify that you want to save or clear input field information when you exit this panel.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down offers you these choices:

1 General
2 Display Panel
3 Usage Notes
4 General Dialog Test

Display panel fields

The fields on the Display Panel function as follows:

Panel name
The name of the panel to be displayed.

Message id
The identifier of a message to be displayed on the panel.

Cursor field
The name of the field on the panel where the cursor is to be positioned.

Cursor position
An integer specifying the position in the field where the cursor is to be placed.

Message pop-up field
The name of a panel field the pop-up message window should be placed adjacent to. Note that the message definition determines if the message will appear in a pop-up window.

Display in window
A slash (/) specifies that the panel is to be displayed in a pop-up window.

If you specify a panel name, entries in "Message id", "Cursor field", "Cursor Position", "Message pop-up field", and the Display in window option are optional.

With the exception of the Display in window option, these are the same parameters that a dialog function can specify when calling the DISPLAY service. Selecting the Display in window field is the functional equivalent to the dialog issuing an ADDPOP service before the DISPLAY service.

When the panel is displayed, the)INIT and)PROC sections of the panel are processed in the same way the DISPLAY service would process them.

If you want to set variables before you display the panel, you can use the Variables option (7.3) to do so. When you display the panel, you can type in new data or type over existing data, and then verify the variables by using the Variables option (7.3) again. Data that you type on the panel is retained until you change it, leave Dialog Test, or reset the function pool.

Figure 209 shows the panel that is displayed if you specify message ID ISPD241 and, optionally, a cursor position without identifying a panel name. The long message portion of the identified message is displayed when you enter the HELP command on that panel.

```
                                                                  Invalid option

            This panel is used to display your specified message.



                 The option that was entered was not valid.

Command ===> _____________________________________________________________
 F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
 F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 209. Message display panel (ISPYP2)

When you enter the END command from the panel being tested, the Display Panel reappears on the screen.

Variables (Option 7.3)

The Variables option (7.3) allows you to:

- Display all the ISPF variables defined in the dialog application you are testing.
- Change the value of a variable by typing over it, unless the variable has an N (non-modifiable) attribute.
- Define new variables by inserting lines or by changing the name or pool of a listed variable.
- Delete variable names and blank lines.

When you select this option, you can scroll a display showing all the current variables for the dialog being tested, as shown in Figure 210 on page 369.

In addition to scrolling capability, you can also increase the size of the Variables pop-up window to fill the entire 3270 physical display area using the RESIZE command. The initial RESIZE command increases the pop-up window to its maximum size, and the subsequent RESIZE reduces the window to its original size.

```
  Menu  Utilities  Help
 ------------------------------------------------------------------------
                     Variables - Application: ISR            Row 1 to 9 of 707

 Add, delete, and change variables. Underscores need not be blanked.
 Enter END command to finalize changes, CANCEL command to end without
 changes.

 Current scrollable width of variables is: 57
      Variable P A Value
                   ----+----1----+----2----+----3----+----4----+----5----+--
 ____ Z        S N ________________________________________________________
 ____ ZACCTNUM S N IBMGSA______________________________________________________
 ____ ZAPLCNT  S N 0000________________________________________________________
 ____ ZAPPLID  S N ISR_________________________________________________________
 ____ ZBDMXCNT S N 000000000___________________________________________________
 ____ ZCFGCMPD S N 2001/11/22__________________________________________________
 ____ ZCFGCMPT S N ________________________________________________________
 ____ ZCFGKSRC S N ________________________________________________________
 ____ ZCFGLVL  S N 480R8001____________________________________________________

 Command ===> ___________________________________________ Scroll ===> PAGE
  F1=Help      F2=Split     F3=Exit      F4=Expand    F5=Rfind     F6=Resize
  F7=Backward  F8=Forward   F9=Swap     F10=Actions  F12=Cancel
```

Figure 210. Variables panel (ISPYVPN)

The Variables display is controlled by the selection you make in the View pull-down on the Dialog Test Primary Option Panel action bar:

1 **Display Variables in window**. Variables are displayed in a pop-up window.

2 **Display Variables full-screen**. Variables are displayed full-screen.

Note: The current setting is shown as an unavailable choice; that is, it is displayed in blue (the default) with an asterisk as the first digit of the selection number (if you are running in GUI mode, the choice is *grayed*).

Variables panel action bar

The Variables Panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down offers you these choices:

1 General Variables
2 Definitions
3 Variables Panel
4 Manipulating Variables
5 Primary Commands
6 Line Commands
7 Usage Notes
8 General Dialog Test

Variables panel fields

Each line of the display represents a variable and contains a line command area. The fields on the Variables panel function as follows:

Variable
Name of the variable. The variable name is alphanumeric, with the first character being either alphabetic or one of the special characters $, #, or @. The variable name cannot be longer than eight characters. All alphabetic characters are converted to uppercase when you press the Enter key. The Variable field is required.

P Pool that contains the variable; a required 1-character field, where:

- **V** Function pool; the variable was defined with the VDEFINE service.
- **I** Function pool; a variable that was created by a CLIST or REXX exec, or by using the Variables option. This is an *implicit* variable, which was not explicitly defined by using the VDEFINE service.
- **S** Shared variable pool.
- **P** Profile variable pool.

A Attributes of the variable, a non-modifiable 1-character field, where:

- **N** Non-modifiable variable. Some system-reserved variables are not modifiable.
- **H** Non-modifiable variable containing hexadecimal data. Some system-reserved variables are not modifiable.
- **X** Variable containing hexadecimal data.
- **T** Truncated variable value. The actual value is longer than the 2048 characters that you can display on the expanded panel.

  If you change a line showing a truncated value, only the data shown on the display is stored as the new value.

Value Value of the variable. The value can be up to 2048 characters in length. Each value is scrollable, by placing the cursor over the value and using the LEFT and RIGHT functions keys. The EXPAND function key can be used to display a full screen of data and display hexadecimal values.

Variables commands

The Variables option (7.3) uses the CANCEL, END, and LOCATE commands, and the I (insert) and D (delete) Dialog Test line commands described in “Commands” on page 359. You can change the displayed sort order using the SORT command. SORT with no operands sorts the list by variable pools then by variable name. SORT NAME sorts the list by variable name and then by variable pool. SORT VALUE sorts the list by the displayed Value field. The LOCATE command can be used to search for a specific variable. LOCATE accepts as an operand the name, or first letters of the name of a variable. If the name is not found, the list is positioned near the closest match. You can use the RFIND key to continue searching other variable pools.

Normally, the variable pools are updated with the data from the display when you use the END command to leave the option.

Manipulating variables

The rows of the display are sorted in this order:
1. By pool (function, then shared, then profile)
2. By function pool type (V, then I)
3. Alphabetically by variable name within each pool.

Insertions are left where they are typed on the display. Changes to the display are processed when you press the Enter key. Updating of the variable pools occurs when you enter the END command.

Creating new variables

You can create new dialog variables, but you cannot create two variables with the same name in the same variable pool.

To create a new variable, you can do one of two things:

- Use the I line command to insert a new row, and then type the variable name, pool, and value on the new line. For each field, move the cursor to the start of the field and type new information. The underscores are pad characters; you do not need to blank them out.
- Type over the name of an existing variable, its pool indicator, or both. This creates a new variable and resets the old variable's value to nulls.

  If you change a truncated value, the portion that is not displayed is lost. The new variable value consists only of the visible portion on the screen.

New function pool variables are given an I (implicit) attribute and a CHAR format. If you type `F` in the attribute field, ISPF changes it to `I`.

By using the second method, you can interchange the values of two or more variables by simply changing their names. For example, you can interchange the values for variables A and B by changing the variable name A to B and name B to A, and then pressing the Enter key.

Deleting variables

Any dialog variable in the shared and profile pools can be deleted, unless it has an N attribute. Though you cannot delete a variable from the function pool, you can set its value to blanks.

To delete a variable, use the D line command. However, to avoid conflict with the I (insert) line command, the Variables option does not allow you to type a number along with the D command to delete more than one line simultaneously. Therefore, enter a single D line command on each line you want to delete. You can type this command on more than one line before pressing the Enter key.

Variables usage notes

When using the Variables option (7.3), you should be aware of:

Input errors

Correct any errors before leaving a display. If you cannot correct the errors, use the CANCEL command.

Length and format errors in variables defined with the VDEFINE service are detected when you enter the END command. If ISPF finds such an error, it prompts you to fix the variable value.

Test mode

Variable manipulations carried out under Dialog Test at a breakpoint are

considered an extension of your dialog and, as such, are handled in user mode. Dialog variables, table data, and service return codes that you introduce, delete, or change are treated as though your dialog had made those changes.

Variable life
Profile variables that you create remain in your profile pool from one Dialog Test session to another. Shared and function variables exist only for the duration of Dialog Test.

Split-screen mode
In split-screen mode, two logical screens can share a profile variable pool. Since the Variables option (7.3) takes a snapshot of the variables, any change to a profile variable on one screen is not immediately reflected on the other screen. To get the latest changes, select the Variables option (7.3) again. Also, when one profile variable is changed on two logical screens using split-screen mode, the changed profile variable on the screen where the last END command was entered takes precedence.

Variable value
Variables defined with the VDEFINE service as non-character are displayed in converted form. Any changes made to the variable's value should conform to the defined format.

Do not change them using the hexadecimal representation. A format or length error causes a message to be displayed when you use the END command. When a VDEFINE error occurs, a panel identifies the data and its value and describes the error. You must then correct the error and press the Enter key. If you create a new variable by changing the pool indicator of an existing variable defined as non-character, the new variable has character (CHAR) format.

Hexadecimal data
Hexadecimal data that cannot be displayed is converted to displayable characters or typed using the form:

```
X'nnnnnnnn'
```

where:

n An integer 0 through 9 or an alphabetic character A through F. There must be an even number of characters within the quotation marks.

DBCS data
A variable defined as DBCS by the VDEFINE service or displayed through the field with FORMAT(DBCS) specified in the test environment is displayed using the form:

```
'¬[DBDBDB]'
```

where:

[and] Represent the SO (shift-out) and SI (shift-in) characters, respectively.

If you type a DBCS value in this format on the Variables panel, only the DBCS characters are stored.

Tables (option 7.4)

The Tables option (7.4) allows you to examine and manipulate the rows of a table, and to display table structure and status. When you select this option, the panel in Figure 211 is displayed, on which you show the table function you want and the parameters needed to identify the table.

```
                                Dialog Test
  Menu  Utilities  View  Help
 ------------------------------------------------------------------------
                                  Tables
                                                                More:     +
 1 Display row            3 Modify row            5 Display structure
 2 Delete row             4 Add row               6 Display status

 Table Name  . . ________  Open tables  . . ________  (NOWRITE or WRITE or
                                                       blank for no TBOPEN)
 Row identification:            Current row  . :
 By row number  . . *_______    (* = current row)
  Variable   Value              (Search for row if row number blank)

   ________  ____________________________________________________
   ________  ____________________________________________________
   ________  ____________________________________________________
   ________  ____________________________________________________
   ________  ____________________________________________________
   ________  ____________________________________________________
 DBCS column specification:
 Option ===> ____________________________________________________
  F1=HELP        F2=            F3=END         F4=DATASETS    F5=FIND
  F6=CHANGE      F9=SWAP       F10=LEFT       F11=RIGHT      F12=SUBMIT
```

Figure 211. Tables panel (ISPYTPI)

Tables panel action bar

The Tables panel action bar choices function as follows:

Menu
For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

View
Allows you to select whether the Add row, Modify row, and Display row panels are displayed in pop-up windows. By displaying the panel in a pop-up window, you can see the panel underneath and move the window. By displaying the panel as a full-screen display, you can see more data. The setting you choose will remain in effect until you change it.

Help
The Help pull-down offers you these choices:

1 General Tables
2 Definitions
3 Tables Panel
4 Display Row
5 Delete Row
6 Modify Row
7 Add Row
8 Display Structure

9 Display Status
10 Usage Notes
11 View Action Bar
12 General Dialog Test

Tables panel fields

The fields on the Tables panel function as follows:

Table Name
The name of the table in which you are interested. The table must be open for all, except the Display Status option (6) of the Tables option (7.4). The table can be opened using the Dialog Services option (7.6) or can be opened automatically by specifying the Open tables field WRITE/NOWRITE option.

Open tables
The table must be open for all but the Display Status option (6) of the Tables option (7.4). Specifying WRITE or NOWRITE will cause Tables option to automatically open the table in the respective mode. A blank field directs Tables to bypass the automatic open. If Tables automatically opens the table, it will be closed automatically when the Tables option is terminated. This is done with a TBCLOSE service which will cause any table changes to be preserved if the table were automatically opened with the WRITE option.

This field is ignored if the table has been opened outside of the Tables (7.4) option.

Row identification
Identify a row, either directly by row number or indirectly by specifying table variable names and their values as search operands.

Current row
The position number of the current row after you have identified a table. This field is not modifiable.

By row number
The position number of the table row that you want, or, if you are adding a row, you can use:
TOP Makes the new row first in the table.
BOTTOM Makes the new row last in the table.

Variable
The names of variables whose values are to be used to search the table for a row with matching contents. You insert them by typing over the underscores beneath this heading.

Value
The value to be used in the search, up to 54 characters. For an abbreviated search, type the beginning characters followed by an asterisk.

You can specify a DBCS value in the form:

```
¬[DBDBDB]
```

where:

[and] Represent the SO (shift-out) and SI (shift-in) characters, respectively. For an abbreviated search, type a 2-byte asterisk (*) at the end of the DBCS value. For example:

```
¬[DBDB**]
```

where ** represents the 2-byte asterisk character.

DBCS column specification
The variable names of the values that are DBCS data. The value of the variable is displayed using the form:

```
¬[DBDBDB]
```

If you type a DBCS value in this format on the Modify Row panel or the Add Row panel, only the DBCS characters are stored, regardless of the DBCS column specification.

Option The number of one of the functions displayed on the Tables panel.

Note: The option names (for example, Display row) are point-and-shoot fields; however, if an option is already specified at the Option prompt, it takes precedence over your point-and-shoot selection.

Once you specify a table name, it is retained until you change it or until you leave Dialog Test.

For the Display row (1), Delete row (2), Modify row (3), and Add row (4) options of the Tables option (7.4), you must identify the row you want to display, delete, modify, or add. To do this, you can specify a row number in the "By row number" field, or you can use the Variable and Value fields to specify a list of search operands. To show the current row, leave the asterisk in the "By row number" field. If you specify both a row number and a search operand, the row number is used and the search operand is ignored.

The current row pointer in the table can be changed only at your request or by your dialog.

The list of search operands consists of variable names and values that allow you to specify the values that specific variables have in a row. You can specify the complete value, abbreviate the value with an asterisk to find a row containing a variable beginning with specified characters, or leave the row blank. The search begins with the row following the current row. If a row matching the search operand is not found, the current row pointer is set to the top. You can repeat the search, if necessary.

Tables panel options

Subsequent topics describe the options at the top of the Tables panel.

1—display row

You can use the Display row option to display the contents of an existing row in an open table. When you select the Display row option, perform these tasks on the Tables panel:

- Specify the name of a table in the Table Name field. If the table is not open, specify NOWRITE or WRITE in the "Open tables" field.
- Specify a row number or a search operand list to identify a row.

Note: Use the View action bar choice on the Tables panel to specify whether this display is to be in a pop-up or full-screen.

When you press Enter, you are shown the table row data on a display that you can scroll (Figure 212 on page 376). The pop-up window can also be resized using the

RESIZE command. In the figure, the variables constitute one table row.

```
                                 Dialog Test
  Menu  Utilities  Help
 ------------------------------------------------------------------------------
                 Display row   Table ISPKEYS   row 1       Row 1 to 13 of 74

 Variable   T  A   Value
 KEYLISTN   K      ISPTEST
 KEY1DEF    N      HELP
 KEY1LAB    N      Help
 KEY1ATR    N      SHORT
 KEY2DEF    N      SPLIT
 KEY2LAB    N      Split
 KEY2ATR    N      LONG
 KEY3DEF    N      EXIT
 KEY3LAB    N      Exit
 KEY3ATR    N      SHORT
 KEY4DEF    N
 KEY4LAB    N
 KEY4ATR    N

 Command ===> ___________________________________________ Scroll ===> PAGE
  F1=Help       F2=Split       F3=Exit        F4=Expand      F5=Rfind
  F6=Resize     F7=Backward    F8=Forward     F9=Swap       F10=Actions
```

Figure 212. Display row panel (ISPYTPD)

Each line on the display shows:

Variable Variable name

T Type of variable:
- **K** Key variable.
- **N** Name variable; non-key.
- **S** Save (extension) variable.

A Attribute of each variable:
- **T** Truncated to 58 characters for display.

Value The first 58 characters of the variable value.

Display row commands: The Display Row option uses the END and LOCATE commands described in “Commands” on page 359.

2—delete row

You can use the Delete row option to remove an existing row from an open table. When you select the Delete row option, perform these tasks on the Tables panel:

- Specify the name of a table in the Table Name field. If the table is not open, specify NOWRITE or WRITE in the “Open tables” field.
- Specify a row number or a search operand list to identify a row.

When you press Enter, a panel is displayed (Figure 213 on page 377) to allow you to confirm the delete request.

```
                                 Dialog Test
  Menu  Utilities  View  Help
 ─ ┌──────────────── Confirm Table Row Delete ────────────────┐ ────────────
 I │ ISPYTPCD                                                 │
   │                                                          │  More:     +
 1 │ Table name  : ISPKEYS                                    │ructure
 2 │                                                          │atus
   │ Row number  : 1                                          │
 T │                                                          │r WRITE or
   │                                                          │ no TBOPEN)
 R │          Press ENTER key to confirm delete.              │
 B │                                                          │
   │          Press END key to cancel delete.                 │lank)
   │ Command ===> ____________________________________________│
   │  F1=Help       F2=Split      F3=Exit       F7=Backward   │
   │  F8=Forward    F9=Swap      F12=Cancel                  │
   └──────────────────────────────────────────────────────────┘


 DBCS column specification:
 Option ===> 2
  F1=Help        F2=Split       F3=Exit        F4=Expand      F5=Rfind
  F6=Resize      F7=Backward    F8=Forward     F9=Swap       F10=Actions
```

Figure 213. Confirm table row delete panel (ISPYTPCD)

The fields on the panel are:
Table name Name of an open table
Row number Number of the row to be deleted.

Press Enter to delete the row, or enter the END or CANCEL command to cancel the deletion.

3—modify row

You can use the Modify row option to change the contents of an existing row of an open table. When you select the Modify row option, perform these tasks on the Tables panel:

- Specify the name of a table in the Table Name field. If the table is not open, specify NOWRITE or WRITE in the “Open tables” field.
- Specify a row number or a search operand list to identify a row.

Note: Use the View action bar choice on the Tables panel to specify whether this display is to be in a pop-up or full-screen.

When you press Enter, a display that you can scroll (Figure 214 on page 378) is shown. The pop-up window can also be resized using the RESIZE command.

```
                                 Dialog Test
  Menu  Utilities  Help
 ------------------------------------------------------------------------------
                 Modify row   Table ISPKEYS   row 1        Row 1 to 10 of 74

Modify variable values and savenames. Underscores need not be blanked.
Enter END command to finalize changes.

      Variable  T A Value
____  KEYLISTN  K   ISPTEST
____  KEY1DEF   N   HELP
____  KEY1LAB   N   Help
____  KEY1ATR   N   SHORT
____  KEY2DEF   N   SPLIT
____  KEY2LAB   N   Split
____  KEY2ATR   N   LONG
____  KEY3DEF   N   EXIT
____  KEY3LAB   N   Exit
____  KEY3ATR   N   SHORT

Command ===> ____________________________________________ Scroll ===> PAGE
 F1=Help       F2=Split       F3=Exit        F4=Expand      F5=Rfind
 F6=Resize     F7=Backward    F8=Forward     F9=Swap       F10=Actions
```

Figure 214. Modify row panel (ISPYTPM)

Each line on the panel represents a variable in row 6 of the table and contains a line command field and these fields:

Variable Variable name, modifiable only for save variables.

T Type of variable, non-modifiable:
- **K** Key variable.
- **N** Name variable; non-key.
- **S** Save (extension) variable.

A Attribute of each variable, non-modifiable:
- **T** Truncated to 2048 characters for display.

Value Value of the variable, up to 2048 characters.

Type in new values or change the current values for the key, name, and save variables in the Value column. Enter new save variables by typing over the underscores in the Name column with the variable names and specifying the desired values. The underscores are pad characters; you do not need to blank them out.

When using the Modify row option, be aware that:

- If the table has keys, the values for the keys in the added row must be different from those in the existing rows when you leave the Modify row option. Otherwise, a message is displayed and the row is displayed again so you can change the keys.
- If the table was sorted using the TBSORT dialog service and a sort field is modified, the row's position in the table can change to preserve the search order.
- You cannot change the variable name for a key variable or name variable; if you do, an error message is displayed and the original name is restored.
- You cannot delete a key or name variable and its value from the display or table row.

- If you delete a save variable, assume that the variable no longer exists in this row.
- If more than one variable entry has the same name, all instances of that variable are assigned the value of the last occurrence of the variable; that is, the occurrence closest to the bottom of a display that you can scroll.
- Blank save names are ignored and do not need to be deleted, even if data is left in the value.
- Hexadecimal data that usually cannot be displayed is converted to characters that can be displayed or is typed by using the form:

  `X'nnnnnnnn'`

  where:

  n An integer 0-9 or an alphabetic character A-F. There must be an even number of characters within the quotation marks.
- Variables defined with the VDEFINE service as non-character are shown in converted form; do not change them by using the hexadecimal representation. A format or length error causes a message to be displayed when you use the END command.
- When you leave the Modify row option by using the END command, the row is replaced, and the message `Row modified` is issued.

Modify row commands: The Modify row option uses the CANCEL, END, and LOCATE commands, and the D (delete), I (insert), and R (repeat) Dialog Test line commands described in "Commands" on page 359. Inserted and repeated lines always have a type of S, because only save variables can be added to (or deleted from) a row of an existing table.

4—add row

You can use the Add row option to add a new row after a selected row of an opened table. When you select the Add row option, perform these tasks on the Tables panel:

- Specify the name of a table in the Table Name field. If the table is not open, specify NOWRITE or WRITE in the "Open tables" field.
- Specify a row number or a search operand list to identify a row.

Note: Use the View action bar choice on the Tables panel to specify whether this display is to be in a pop-up or full-screen.

```
                                  Dialog Test
  Menu  Utilities  Help
 ___________________________________________________________________________
                Add row   Table ISPKEYS   after row 1      Row 1 to 10 of 73

 Add variable values and savenames. Underscores need not be blanked.
 Enter END command to finalize changes.

       Variable  T A Value
 ____  KEYLISTN  K   ______________________________________________________
 ____  KEY1DEF   N   ______________________________________________________
 ____  KEY1LAB   N   ______________________________________________________
 ____  KEY1ATR   N   ______________________________________________________
 ____  KEY2DEF   N   ______________________________________________________
 ____  KEY2LAB   N   ______________________________________________________
 ____  KEY2ATR   N   ______________________________________________________
 ____  KEY3DEF   N   ______________________________________________________
 ____  KEY3LAB   N   ______________________________________________________
 ____  KEY3ATR   N   ______________________________________________________

 Command ===> ___________________________________________ Scroll ===> PAGE
  F1=Help       F2=Split      F3=Exit       F4=Expand     F5=Rfind
  F6=Resize     F7=Backward   F8=Forward    F9=Swap      F10=Actions
```

Figure 215. Add row panel (ISPYTPA)

When you press Enter, a scrollable display is shown (Figure 215), containing all the key and name variables in the table. The pop-up window can also be resized using the RESIZE command.

Each row of the display contains a line command field and these fields:

Variable Variable name.

T Type of variable, non-modifiable:
- **K** Key variable.
- **N** Name variable; non-key.
- **S** Save (extension) variable.

A Attribute of each variable. This attribute is non-modifiable and is not used for this option.

Value Space for the variable value to be added, up to 2048 characters.

Type the values for the key and name variables in the Value column, which is originally initialized to all nulls. You cannot change the names of the key and name variables because they were established when the table was created.

You can enter save variables, identified as TYPE S, by typing over the underscores with the save variable names and specifying the desired values. The underscores are pad characters; you do not need to blank them out.

You can add a row with no values to the table, but you are asked to confirm such an action to guard against inadvertent use of the END command.

When using the Add row option, be aware that:

- The position of the new row in the table depends on whether the table was previously sorted using the TBSORT dialog service. If the table was sorted, the new row is placed in sort order; if it has not been sorted, the new row is placed after the row you specified.

- You cannot delete a key or name variable and its value from the display or table row.
- You cannot change the variable name for a key or name variable; if you do, an error message is displayed and the original name is restored.
- If more than one variable entry has the same name, all instances of that variable are assigned the value of the last occurrence of the variable; that is, the occurrence closest to the bottom of the display that you can scroll.
- If the table has keys, the values for the keys in the added row must be different from those in all the existing rows when you leave the Add Row option. Otherwise, a message is displayed and the row is displayed again so you can change the keys.
- Blank save names are ignored and do not need to be deleted, even if data is left in the value.
- Hexadecimal data that usually cannot be displayed is converted to characters that can be displayed or is typed by using the form:

  `X'nnnnnnnn'`

  where:

  n An integer 0-9 or an alphabetic character A-F. There must be an even number of characters within the quotation marks.
- Variables defined with the VDEFINE service as non-character are shown in converted form; do not change them by using the hexadecimal representation. A format or length error causes an error message to be displayed when you use the END command.

Add row commands: The Add row option uses the CANCEL, END, and LOCATE commands, and the D (delete), I (insert), and R (repeat) Dialog Test line commands described in "Commands" on page 359. Inserted and repeated lines always have a type of S, because only save variables can be added to (or deleted from) a row of an existing table.

5—display structure

When you select the Display structure option on the Tables panel, you are shown a display of the table structure for the table specified in the Table Name field. You can scroll this display (Figure 216 on page 382) using the scroll commands. The table name appears in the panel header.

```
                                 Dialog Test
  Menu  Utilities  Help
 ISPYTPSR                Structure of Table ISPKEYS         Row 1 to 8 of 17

 Number of keys . . : 1            Number of rows  . . . : 7
 Number of names  . : 72           Current row pointer . : 1
 KEYS:      KEYLISTN

 NAMES:     KEY1DEF      KEY1LAB      KEY1ATR      KEY2DEF      KEY2LAB
            KEY2ATR      KEY3DEF      KEY3LAB      KEY3ATR      KEY4DEF
            KEY4LAB      KEY4ATR      KEY5DEF      KEY5LAB      KEY5ATR
            KEY6DEF      KEY6LAB      KEY6ATR      KEY7DEF      KEY7LAB
            KEY7ATR      KEY8DEF      KEY8LAB      KEY8ATR      KEY9DEF
            KEY9LAB      KEY9ATR      KEY10DEF     KEY10LAB     KEY10ATR

 Command ===> _____________________________________________ Scroll ===> PAGE
  F1=HELP        F2=            F3=END         F4=DATASETS    F5=FIND
  F6=CHANGE      F9=SWAP       F10=LEFT       F11=RIGHT      F12=SUBMIT


Option ===> 7
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 216. Structure of table panel (ISPYTPSR)

The display contains these fields:

Number of keys	Number of key variables in a row.
Number of names	Number of name variables in a row.
Number of rows	Number of rows currently in the table.
Current row pointer	Current row pointer value.
KEYS	A list of the names of all the key variables.
NAMES	A list of the names of all the name variables.

Display structure command: The KEYS and NAMES lists can be scrolled, and you can use the LOCATE command to find a specific variable name. See “Finding a character string” on page 361 for information about its use.

6—display status

If you select the Display status option from the Tables panel, one of two data information panels is displayed for the table specified in the Table Name field. The information reflects all operations using the specified table, including those done at your request by the Tables options under Dialog Test.

Table not open: If the table is not open for your user ID, you are shown a Status of Table panel (Figure 217 on page 383) with the value NOT OPEN in the “Status for this screen” field.

```
                                 Dialog Test
  Menu  Utilities  Help
 ------------------------------------------------------------------------
                         Status of Table ISPKEYS
                                                                 More:     +
 Status for this screen  : NOT OPEN      Date created        : 1995/01/17
 Table available         : YES           Time created        : 13:47:06
                                         Last date modified  : 2002/06/03
                                         Last time modified  : 22:10:26
                                         Last modified by    : JPHILP
                                         Original row count  : 1
                                         Current row count   : 7
                                         Modified row count  : 7
                                         Update count        : 83

                                       Virtual storage
 Command ===>
  F1=Help        F2=Split       F3=Exit        F4=Expand      F5=Rfind
  F6=Resize      F7=Backward    F8=Forward     F9=Swap       F10=Actions

Option ===> 7
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 217. Status of table panel with table not open (ISPYTPS1)

The panel contains these fields:

Status for this screen
Shows that the table is NOT OPEN for this logical screen.

Table available
YES or NO; whether you can open the table.

Date created
Date the table was created; shown in national format.

Time created
Time the table was created.

Last date modified
Date the table was last modified; shown in national format.

Last time modified
Time the table was last modified.

Last modified by
User ID of the user who last changed the table.

Original row count
The number of rows that were added to a newly created table before closing the table for the first time.

Current row count
The number of rows currently in the table.

Modified row count
The number of rows in the table that have been changed at least once. A row that has been added to an existing table is also considered a changed row.

Update count
Number of times the table has been modified. One or more updates during any table open or close sequence increments this counter by one.

Virtual storage
The number of bytes of virtual storage required by the table when it is open.

The Modify row option on the Tables panel allows you to change a key of a keyed table by adding the new row and deleting the old row. The row counts thus reflect this processing when changing a key value.

Table open: If the table is open for your user ID, you are shown a Status of Table panel (Figure 218) with the value OPEN in the Status for this screen field.

```
                                 Dialog Test
  Menu  Utilities  Help
 ------------------------------------------------------------------------
                         Status of Table ISPKEYS
                                                              More:     +
 Status for this screen  : OPEN           Date created  . . . : 1995/01/17
 Open option . . . . . . : NOWRITE        Time created  . . . : 13:47:06
 Table on disk . . . . . : YES            Last date modified. : 2002/06/03
 Last table service  . . : TBQUERY        Last time modified. : 22:10:26
 Last service return code: 00             Last modified by  . : JPHILP
 Current row pointer . . : TOP            Original row count. : 1
                                          Current row count . : 7
                                          Modified row count. : 7
                                          Update count  . . . : 83

                                       Virtual storage
 Command ===>
  F1=Help       F2=Split      F3=Exit       F4=Expand     F5=Rfind
  F6=Resize     F7=Backward   F8=Forward    F9=Swap      F10=Actions

Option ===> 7
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 218. Status of table panel with table open (ISPYTPS1)

This panel contains these fields:

Status for this screen
Shows that the table is OPEN for this logical screen.

Open option Option used to open the table; this value can be WRITE, NOWRITE, SHR WRITE, or SHR NOWRITE.

Table on disk Whether the table has been saved on disk; this value can be YES or NO.

Last table service
Name of the last table service called.

Last service return code
Last table services return code.

Current row pointer
Current position in the table.

Date created Date the table was created; shown in national format.

Time created Time the table was created.

Last date modified
Date the table was last modified; shown in national format.

Last time modified
Time the table was last modified.

Last modified by
User ID of the user who last changed the table.

Original row count
The number of rows that were added to a newly created table before closing the table for the first time.

Current row count
The number of rows currently in the table.

Modified row count
The number of rows in the table that have been changed at least once. A row that has been added to an existing table is also considered a changed row.

Update count Number of times the table has been modified. One or more updates during any table open or close sequence increments this counter by one.

Virtual storage
The number of bytes of virtual storage required by the table.

The Modify row option on the Tables panel allows you to change a key of a keyed table by adding the new row and deleting the old row. The row counts thus reflect this processing when changing a key value.

Log (option 7.5)

The Log option (7.5) allows you to display and browse data recorded in the ISPF transaction log, as shown in Figure 219.

```
 Browse log - USERID.SPFLOG2.LIST                    Line 00000000 Col 007 086
********************************* Top of Data **********************************
Time                *** ISPF transaction log ***                        Userid:

09:03   Start of ISPF Log - - -  - Session # 16 --------------------------------
10:15      TSO     - Command  -  - SUBMIT NOTIFY
10:37   ***** Dialog Error ***** - Application(ISR); Function Module (ISR@USER);
10:37      Line from panel:      - )BODY  EXPAND(//) WIDTH(&ZWIDTH)  CMD(ZCMD)
10:37      Panel 'ISPYLP1' error - Invalid WIDTH value, (must be numeric chars,
******************************** Bottom of Data ********************************









 Command ===> ____________________________________________________ Scroll ===> PAGE
  F1=HELP      F2=          F3=END       F4=DATASETS  F5=FIND      F6=CHANGE
  F9=SWAP     F10=LEFT     F11=RIGHT    F12=SUBMIT
```

Figure 219. ISPF transaction log (ISPYLP1)

You can use all the Browse commands, except BROWSE, while looking at the ISPF log.

ISPF transaction log not available

Sometimes the log is not available for browsing. This can occur when:

- The log data set is empty.
- The log data set was not created for this session because `0` was entered in the "Primary pages" field on the Log Set Defaults and List Set Defaults pop-ups, which can be reached by selecting Option 0 from the ISPF Primary Option Menu and then selecting the Log Data set defaults and List Data set defaults choices from the Log/List pull-down.
- No data has been written to the log during this session, and although the log data set exists and is not empty, you did not end the last ISPF session normally; for example, an abend can have ended the session. You can browse the log if you take an action that causes a log entry to be written.
- The log data set was previously allocated with a disposition of OLD. It must be allocated with a disposition of MOD.
- The log data set has been previously allocated to SYSOUT.

Trace output in ispf log

This trace output is written to the ISPF log:

- Trace header entries
- Function trace entries
- Variable trace entries.

Each type of entry follows the format of other log entries: a short summary on the left, and a detailed entry on the right.

Trace header entries

The first line of trace data is a trace header that identifies the trace and shows the current application ID, the current function, and the current screen. For split-screen mode, the original screen is 1 and the screen generated by the SPLIT command is 2. The summary section of the header entry identifies the entry as a dialog trace. The trace header entry is written during the test session whenever a function or variable trace entry is to be written for an application, function, or screen that differs from the last.

For example, a trace of logical screen 1 of function TESTF1 in application ISR would place this line in the ISPF log:

```
DIALOG TRACE ---- - APPLICATION(ISR)  FUNCTION(TESTF1)  SCREEN(1)
```

Function trace entries

A pair of function trace entries, a BEGIN entry and an END entry, is generated during a function trace for each traced dialog service that is called. A service can be called from a user dialog that is currently processing, or from a Dialog Test action for the user. The summary portion of each of these entries shows the name of the dialog service, whether it is the beginning or the end of its processing, and whether it was called indirectly from a Dialog Test panel. If the word TEST does not appear, the user dialog called the service directly. For END entries, the service return code is shown on a second line.

The detailed section of the log entries contains an image of the service call and the parameters used to call that service, using two lines if necessary. For example:

```
DISPLAY .. BEGIN ... TEST - DISPLAY PANEL(XYZ)
⋮
DISPLAY .. END.. ... TEST - DISPLAY PANEL(XYZ)
  ..RETURN CODE (0)
```

There can be many log entries between the begin and end entries. For example, any active variable traces can cause log entries during a SELECT trace.

Note these aspects about the service call image:

- The image is truncated after the second line.
- ISPEXEC calls are shown as typed in the dialog.
- ISPLINK and ISPLNK calls (except for the ISREDIT service) are displayed with their parameter values separated by commas. Name-lists are shown as typed in the dialog, in either string or structure format. Structure format includes the count, element length, and list of names. For a variable services parameter whose context is defined by the name-list parameter on the service call, the first four bytes of the parameter value are displayed in hexadecimal format (`X'nnnnnnnn'`).
- Dialog Test calls are shown using the command call format without the ISPEXEC prefix.

Variable trace entries

Two variable trace entry lines are generated for each variable trace log entry. The variable can be referred to or set by a user dialog directly or indirectly by a dialog service, or explicitly set by a Dialog Test option for a user. The summary parts of these entry lines identify the trace. Line one shows the name of the variable, the pool that contains it (F for function, S for shared, P for profile), and an indicator (TEST) if a Dialog Test option set the value. Line two shows the operation done for the variable (GET, PUT, or CHG) and the name of the dialog service that did the operation for non-TEST entries.

The current value of the variable is printed in the detail section of the log entry and can span two lines. For example:

```
LIB1.... POOL(P) .... - VALUE(FLAG)
 ...GET by EDIT       -
```

The value is truncated after the second line.

If the variable value contains characters that cannot be displayed, the value is displayed in hexadecimal format (`X'nnnnnnnn'`).

Dialog services (option 7.6)

The Dialog Services option (7.6) allows you to call a dialog service by entering the service call with or without the ISPEXEC characters.

Figure 220 on page 388 shows the Invoke Dialog Service panel.

```
  Menu  List  Mode  Functions  Utilities  Help
 ___________________________________________________________________________
                             Invoke Dialog Service

 Enter dialog service and its parameters:
 ===> ______________________________________________________________________
 ___________________________________________________________

 Place cursor on choice and press enter to RETRIEVE command.

 => rempop
 => addpop
 => ispexec display
 => ispexec display panel(sample)
 =>
 =>
 =>
 =>
 =>
 =>

 Command ===> ______________________________________________________________
  F1=Help      F2=Split     F3=Exit      F4=Expand    F5=Rfind     F6=Resize
  F7=Backward  F8=Forward   F9=Swap     F10=Actions  F12=Cancel
```

Figure 220. Invoke dialog service panel (ISPYS1)

On this panel, if you want to display panel XYZ, enter:

```
===> DISPLAY PANEL(XYZ)
```

or

```
===> ISPEXEC DISPLAY PANEL(XYZ)
```

The service is called when you press the Enter key. You are informed of the service's completion and return code.

You can call any dialog service that is valid in the command environment except CONTROL at a breakpoint or before calling a function.

The Invoke Dialog Service panel has a saved command area (the bottom portion of the screen) that contains a list of up to 10 commands that you have saved. These commands are point-and-shoot fields. The mode you specify from the Mode pull-down menu on the action bar determines what happens when you select a command.

Invoke dialog service panel action bar

The Invoke Dialog Service panel action bar choices function as follows:

Note: The Invoke Dialog Service panel action bar contains three pull-down choices that let you control the saved command area.
- List
- Mode
- Functions.

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

List The List pull-down offers you these choices:

Note: The current setting is shown as an unavailable choice; that is, it is displayed in blue (the default) with an asterisk as the first digit of the selection number (if you are running in GUI mode, the choice will be *grayed*).

Update On Makes the list of commands in the saved command area *live*; that is, new commands are appended to the list automatically.

Update Off Makes the list of commands in the saved command area *static*; that is, new commands are not appended to the list automatically.

Mode The Mode pull-down offers you these choices:

Note: The current setting is shown as an unavailable choice; that is, it is displayed in blue (the default) with an asterisk as the first digit of the selection number (if you are running in GUI mode, the choice will be *grayed*).

Retrieve Allows commands to be retrieved from the saved command area and placed on the TSO Command Entry field (==>) so that you can edit them before they are executed. This mode is the default.

Execute Allows commands to be retrieved from the saved command area and executed in one step.

Delete Allows you to delete commands from the saved command area without executing the commands. Place the cursor on the command to be deleted and press Enter. The command will be blanked out.

Functions
The Functions pull-down offers you this choice:

Note: The choice is unavailable when you initially enter the panel and after you compress the list; that is, it will display in blue (the default) with an asterisk as the first digit of the selection number (if you are running in GUI mode, the choice will be *grayed*).

Compress List Compresses the saved command area by removing deleted entries.

Utilities
For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down offers you these choices:
1 General
2 General Dialog Test

Special display panel

If you issue the DISPLAY service call with only a message parameter, or with no parameter at all, the Special Display Panel is shown (Figure 221 on page 390).

```
                                Dialog Test
                            Special Display Panel

 This panel is used for two special DISPLAY conditions:

 1.  When DISPLAY is invoked without a panel name.

 2.  When TBDISPL is invoked without a panel name. All of the other
     parameters are ignored.

 Command ===> _____________________________________________________
  F1=Help     F2=Split    F3=Exit     F9=Swap    F12=Cancel
```

Figure 221. Special display panel (ISPYS2)

Traces (option 7.7)

The Traces option (7.7) allows you to define, change, and delete trace specifications. You can trace processed dialog services, except for the VPUT or VGET service issued from a panel, and dialog variables to which are referred during dialog processing. Trace data is placed in the transaction log, where you can browse it by using the Log option (7.5) or print it when you leave ISPF. You can also print the log data set during an ISPF session by using the ISPF LOG command.

Since tracing can degrade dialog performance and create large amounts of output, you should be careful in setting the scope of trace definitions.

When you select this option, a selection panel is displayed (Figure 222 on page 391) on which you can show the type of trace you want to define.

```
  Menu  Utilities  Compilers  Options  Status  Help
─ ┌──────────────────────── Dialog Test ────────────────────────┐ ──────────
    Menu  Utilities  Help
   ──────────────────────────────────────────────────────────
0                              Traces                              : SUEBURN
1                                                                  : 11:00
2   1  Function Traces   Monitor dialog service calls              : 3278
3   2  Variable Traces   Monitor dialog variable usage             : 1
4                                                                  : ENGLISH
5   Option ===>                                                    : ISR
6    F1=Help        F2=Split       F3=Exit        F4=Expand        : ISPF
7    F5=Rfind       F6=Resize      F7=Backward    F8=Forward       : SUEBURN
9                                                                  : MVS8
10 SCLM          SW Configuration Library Manager        MVS acct. : IBMGSA
11 Workplace     ISPF Object/Action Workplace            Release . : ISPF 5.9
12 z/OS System   z/OS system programmer applications
13 z/OS User     z/OS user applications

     Enter X to Terminate using Log/List defaults


Option ===> 7
 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 222. Traces panel (ISPYRI1)

Subsequent topics describe the options shown at the top of the Traces panel.

1—function traces

The Function Traces option on the Traces panel is used to establish criteria for recording the names of dialog service calls, the service parameters, and return code in the ISPF log. If either a dialog or Dialog Test processing causes a service call, that call is recorded in the trace. An example of Dialog Test processing that causes a service call is the use of the Panels option (7.2) to display a panel. Whenever a new application or function causes data to be recorded, a header is placed in the trace.

When you select the Function Traces option, you are shown a panel that you can scroll (Figure 223 on page 392). The pop-up window can also be resized using the RESIZE command. The panel lists all currently defined function traces.

You can add, delete, and change function trace definitions by using this panel, either before calling a function or at a breakpoint.

```
                              Function Traces
  Menu  Utilities  Help
 ------------------------------------------------------------------------------
                                                              Row 1 to 7 of 13

 Add, delete, and change traces.  Underscores need not be blanked.
 Enter END command to finalize changes.

         Function    Active       Dialog services to be traced
        (Required)  (YES,NO)     (No entry=all)
                  (No entry=YES)  ("OR" is assumed between names)

  ____   ALL        NO        ____________________________________
  ____   ________   ___       ____________________________________
  ____   ________   ___       ____________________________________
  ____   ________   ___       ____________________________________
  ____   ________   ___       ____________________________________
  ____   ________   ___       ____________________________________
  ____   ________   ___       ____________________________________

 Command ===> ___________________________________________ Scroll ===> PAGE
  F1=Help       F2=Split      F3=Exit       F4=Expand     F5=Rfind
  F6=Resize     F7=Backward   F8=Forward    F9=Swap      F10=Actions
```

Figure 223. Function traces panel (ISPYRFP)

Each line defines a function trace, showing a line command area and these fields:

Function
The name of the user function that should contain the trace, or ALL to trace every dialog function. Initially, ALL is presented on the display but is not started. Change the NO to a YES in the Active column to start such a trace. If you want to trace a function whose name is ALL, enclose the name in single quotes to distinguish it; that is, type `'ALL'`, not `ALL`.

Active Whether the trace is to be active now:
YES The trace is currently active.
NO The trace is currently not active.
Blank The trace is currently active.

Dialog services to be traced
Names of dialog services to be traced. No entry in this field shows all calls to dialog services for the function are to be traced.

All function traces exist until you leave Dialog Test, or until you delete them from this panel. Enter new information by typing over the existing data. The underscores are pad characters to show the starting and ending positions for each field; you do not need to blank them out. You can create several function traces before you press the Enter key.

During dialog processing, to determine whether the criteria for a function trace have been met, Dialog Test processes a logical AND of the Function, Active, and Dialog services fields specified for that function trace. Dialog Test also processes a logical OR within the Dialog services field to determine whether a particular dialog service has been matched. Therefore, if you want more than one trace for a function, you should create multiple rows.

Function traces commands

The Function Traces option uses the CANCEL, END, and LOCATE commands, and the D (delete), I (insert), and R (repeat) Dialog Test line commands described in "Commands" on page 359.

2—variable traces

The Variable Traces option on the Traces panel is used to establish criteria for recording variable usage. A variable's usage is recorded if an ISPF service is directly asked to operate on the variable (such as VGET, VPUT, and VCOPY), or if an ISPF service is indirectly asked to operate on the variable (such as DISPLAY). Variables changed under the Variables option (7.3) are also recorded if the trace specifications are met.

When you select the Variable Traces option, you are shown a display that you can scroll (Figure 224). The pop-up window can also be resized using the RESIZE command. The display lists all currently defined variable traces. You can add, delete, and change variable trace definitions at a breakpoint, or by using this panel before calling a function.

```
                              Variable Traces
  Menu  Utilities  Help
 ____________________________________________________________________________
                                                              Row 1 to 8 of 13

 Add, delete, and change traces.  Underscores need not be blanked.
 Enter END command to finalize changes.

          Variable       Pool        Operation      Function     Active
         (Required) (No entry=all) (GET,PUT,CHG) (No entry=all) (YES,NO)
                                   (No entry=all)              (No entry=YES)
        ALL
 ____   ________    ________         ___          ________       NO
 ____   ________    ________         ___          ________       ___
 ____   ________    ________         ___          ________       ___
 ____   ________    ________         ___          ________       ___
 ____   ________    ________         ___          ________       ___
 ____   ________    ________         ___          ________       ___
 ____   ________    ________         ___          ________       ___
 ____   ________    ________         ___          ________       ___

 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help       F2=Split       F3=Exit        F4=Expand      F5=Rfind
  F6=Resize     F7=Backward    F8=Forward     F9=Swap       F10=Actions
```

Figure 224. Variable traces panel (ISPYRVP)

Each line defines a variable trace, showing a line command area and these fields:

Variable Name of the variable to be traced, or ALL to show tracing of all variables. Initially, ALL is presented on the display but is not started. Change the NO in the Active column to YES to start such a trace. If you want to trace a variable whose name is ALL, enclose that name in single quotes to distinguish it; that is, type `'ALL'`, not `ALL`.

Pool Pool of interest for variable tracing:
- **F** Function variable pool.
- **S** Shared variable pool.
- **P** Profile variable pool.
- **Blank** All pools.

Operation Type of variable reference to trace:
- **GET** Accesses to the variable's value.
- **PUT** Stores to the variable's value.
- **CHG** Changes to the variable's value.
- **Blank** All references to variable are traced.

Function If there is no entry, this variable is traced for all functions.

Active Indication of whether the trace is to be active:
- **YES** The trace is currently active.
- **NO** The trace is currently not active.
- **Blank** The trace is currently active.

All variable trace definitions exist until you leave Dialog Test, or until you delete them from this panel. Enter new information by typing over the existing data. The underscores are pad characters to show the start and end of each field; you do not need to blank them out. You can create several variable traces before you press the Enter key.

During dialog processing, to determine whether the criteria for a variable trace have been met, Dialog Test processes a logical AND of the Variable, Pool, Operation, Function, and Active fields specified for that variable trace. Therefore, if you want more than one trace for a variable, you should create multiple rows.

Variable traces commands

The Variable Traces option uses the CANCEL, END, and LOCATE commands, and the D (delete), I (insert), and R (repeat) Dialog Test line commands described in "Commands" on page 359.

Breakpoints (option 7.8)

A *breakpoint* is a location at which the processing of your dialog is suspended so that you can use Dialog Test facilities. The Breakpoints option (7.8) allows you to show where such temporary suspensions should occur. At a breakpoint, you can examine and manipulate dialog data such as tables and variables. You can also specify new test conditions, such as traces and other breakpoints.

Breakpoints are located immediately before a dialog service receives control or after it relinquishes control. Breakpoint definitions cause special handling within the ISPLINK, ISPLNK, or ISPEXEC interfaces to dialog services; no user dialog code is modified. When the criteria for a breakpoint are satisfied, your dialog is suspended. You can then do any of the functions shown on the Breakpoint Primary Option Panel. You cannot use as a breakpoint the VPUT or VGET service issued from a panel, nor will breakpoints occur for selections from a menu (selection) panel. Breakpoints occur only for dialog service calls that use the ISPLINK, ISPLNK, or ISPEXEC interfaces.

Along with several menu bar items common across ISPF Version 4.1, the Breakpoints panel has added the Qualify pull-down. You can now display the qualification parameter values from the Breakpoints panel in two ways:
- Enter the QUAL primary command
- Select the Qualifications choice from the Qualify pull-down.

The Function and Active columns are overlaid with a column of data titled Qualification Parameter Values; this column was logically off the screen to the right of the first Breakpoints panel. To resume the format of the Breakpoints panel, you can either:

- Enter the RESUME primary command, or
- Select the Breakpoints choice from the Qualify pull-down

Specifying breakpoints

When you select the Breakpoints option, you are shown a display that you can scroll (Figure 225). The pop-up window can also be resized using the RESIZE command. The display lists all currently defined breakpoints for this session. You can use this panel to add, delete, or change breakpoint definitions, either before calling a function or at a breakpoint.

```
                              Dialog Test
  Menu  Qualify  Utilities  Help
 ------------------------------------------------------------------------
                                Breakpoints                Row 1 to 5 of 13

 Add, delete, and change breakpoints. Underscores need not be blanked.
 Enter END command to finalize changes.

        Service            When            Function        Active
       (Required)   (BEFORE,AFTER,Rnn)  (No entry=all)    (YES,NO)
                      (No entry=all)                   (No entry=YES)


  ____   ________         ______           ________         ___
  ____   ________         ______           ________         ___
  ____   ________         ______           ________         ___
  ____   ________         ______           ________         ___
  ____   ________         ______           ________         ___

 Command ===> ___________________________________________ Scroll ===> PAGE
  F1=Help       F2=Split      F3=Exit       F4=Expand      F5=Rfind
  F6=Resize     F7=Backward   F8=Forward    F9=Swap        F10=Actions

 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 225. Breakpoints panel (ISPYBP1)

Breakpoints panel action bar

The Breakpoints panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Qualify Displays the Qualification parameter values field on the Breakpoints panel so that you can further constrain the conditions under which a breakpoint is to occur.

Utilities For more information, see the details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Help The Help pull-down offers you these choices:

1 General
2 Definitions
3 Breakpoints Panel
4 Qualification Panel
5 Line Commands
6 Primary Commands
7 Usage Notes

8 General Dialog Test

Breakpoints panel fields

Each line defines a breakpoint and includes a line command area and these fields:

Service Name of the dialog service at which to interrupt dialog processing. This field is required.

When Indication of when the breakpoint should occur:

- **BEFORE** Before the service receives control.
- **AFTER** After the service finishes processing.
- **Rnn** After the service finishes processing, but only if the return code is the integer *nn*.
- **Blank** Before and after service processing.

Function The program function or command function that must be processing for the breakpoint to be taken. No entry in this field shows that the breakpoint can occur for all functions.

Active Indication of whether the breakpoint is to be active now:
YES It is currently active.
NO It is currently not active.
Blank It is currently active.

QUAL If present at the end of a row, shows that qualification data exists for the breakpoint. This field is non-modifiable. See "Qualification parameter values" for additional information.

All input fields contain underscores. Empty lines are added to the first display to fill up the screen. If you delete all the lines used for defining breakpoints, the display is automatically refreshed with enough empty lines to fill the screen again.

All breakpoints exist until you end or cancel your Dialog Test session, or until you delete them from this panel. Enter new information by typing over the existing data. The underscores are pad characters to show the starting and ending positions for each field; you do not need to blank them out. You can create several breakpoints before you press the Enter key.

Breakpoints commands

From the Breakpoints panel, you can use the CANCEL, END, LOCATE, QUAL, and RESUME commands, and the D (delete), I (insert), and R (repeat) Dialog Test line commands described in "Commands" on page 359.

Qualification parameter values

A different part of the Breakpoints panel allows you to further constrain the conditions under which a breakpoint is to occur by entering qualification parameter values. On this part of the panel, you can list parameter data with which the named service must have been called.

The Breakpoints panel with the Qualification parameter values field is displayed (Figure 226 on page 397) if you enter the QUAL primary command on the first part of the Breakpoints panel or if you select the Qualifications choice from the Qualify pull-down. The Function and Active columns are overlaid with a column of data titled Qualification parameter values; this column was logically off the screen to the right of the first Breakpoints panel. To resume the format of the Breakpoints panel, use the RESUME primary command or select the Breakpoints choice from

the Qualify pull-down.

```
                                 Dialog Test
  Menu  Qualify  Utilities  Help
 ------------------------------------------------------------------------
                                Breakpoints                Row 1 to 5 of 13

 Add, delete, and change breakpoints. Underscores need not be blanked.
 Enter END command to finalize changes.

       Service          When                 Qualification parameter values
      (Required)  (BEFORE,AFTER,Rnn)                 (No entry=none)
                    (No entry=all)        ("AND" is assumed between values)


 ____  ________        ______      ________________________________________
 ____  ________        ______      ________________________________________
 ____  ________        ______      ________________________________________
 ____  ________        ______      ________________________________________
 ____  ________        ______      ________________________________________

 Command ===> ___________________________________________ Scroll ===> PAGE
  F1=Help       F2=Split       F3=Exit        F4=Expand      F5=Rfind
  F6=Resize     F7=Backward    F8=Forward     F9=Swap       F10=Actions

 F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
F10=Actions  F12=Cancel
```

Figure 226. Breakpoints panel with qualification parameter values (ISPYBP2)

The lines on the Breakpoints panel with qualification parameter values correspond to the lines on the first Breakpoints panel; “Specifying breakpoints” on page 395 describes the Service and When fields. In the Qualification parameter values field, for all services except SELECT, you can enter any combination of:

- One or more parameter values, separated by blanks, that the dialog passes to the service. No order is implied by the specification of the parameter values.

  For example, if you want a breakpoint to occur when message ABC0001 is included on a DISPLAY service request, specify `ABC0001`. If the breakpoint should occur only when message ABC0001 and panel XYZ are both included, specify `ABC0001 XYZ`.
- One or more command call keywords, separated by blanks, that have values that are not blank when a dialog calls the service. For ISPLINK or ISPLNK calls, the keywords matching the calling sequence parameter positions are used.

  For example, if you want a breakpoint to occur whenever the DISPLAY service is called with a message, then specify MSG.

For ISPF’s SELECT and ISREDIT services, you can enter one or more parameter strings that would be entered on these two service calls. A *parameter string* is a series of characters delimited by a blank, a comma, a single quotation mark, or a left or right parenthesis.

For example, if a SELECT call is:

```
SELECT PGM(ABC) PARM(1 2 3 5 '6'),
```

then all or any of these strings can be used: `SELECT`, `PGM`, `ABC`, `1`, `2`, `3`, `5`, `6`.

For a breakpoint to be taken, all qualification data listed must be matched.

All line commands and change capabilities are still available on the Breakpoints panel with qualification parameter values.

During dialog processing, to determine whether the criteria for a breakpoint have been met, Dialog Test processes a logical AND of the Service, When, Function, Active, and Qualification fields specified for that breakpoint. Therefore, if you want more than one breakpoint for an ISPF service, you should create multiple rows.

When you use the Breakpoints option (7.8), be aware of these items:

Qualification
If you plan to qualify several breakpoints, it can be more efficient to specify all breakpoint data on the Breakpoints panel with qualification parameter values.

END command
You can use the END primary command from either the first Breakpoints panel or the Breakpoints panel with qualification parameter values.

Input errors
You must correct input errors before leaving any display using the END, QUAL, or RESUME command. You can use the CANCEL command to end the Breakpoints option, even if input errors remain on the display.

Syntax checking
A dialog service call must pass a basic syntax check before a breakpoint is honored.

Control display
If any CONTROL service settings for DISPLAY LINE or DISPLAY SM (Session Manager) were in effect before the breakpoint, such settings are lost.

Finding a breakpoint

If you call a dialog function or selection panel and find a breakpoint, the Breakpoint Primary Option Panel is displayed. Figure 227 on page 399 shows this selection panel at a breakpoint just after the ISPF DISPLAY service was called while processing the TEST function in application PAY.

```
                                 Dialog Test
  Menu  Utilities  Help
 ------------------------------------------------------------------------
             Breakpoint Primary Option Panel - BEFORE VDEFINE   End of field

 1 Functions       Invoke dialog functions/selection panel ________
 2 Panels          Display panels
 3 Variables       Display/set variable information
 4 Tables          Display/modify table information
 5 Log             Browse ISPF log
 6 Dialog Services Invoke dialog services
 7 Traces          Specify trace definitions
 8 Breakpoints     Specify breakpoint definitions
 T Tutorial        Display information about Dialog Test
 G Go              Continue execution from breakpoint
 C Cancel          Cancel dialog testing

 Current status:
 Application . : PAY      Function . : TEST      Return Code . . 8
 Breakpoint:
 FVR96 ISPFVR97 ISPFVR98 ISPFVR99 ISPFVR00,X'C1C2C3C4',X'C3C8C1D9',4,LIST )
 <
 Option ===> ____________________________________________ Scroll ===> PAGE
  F1=HELP        F2=            F3=END         F4=DATASETS    F5=FIND
  F6=CHANGE      F9=SWAP       F10=LEFT       F11=RIGHT      F12=SUBMIT
```

Figure 227. Breakpoint Primary Option panel (ISPYXM1)

Like the Dialog Test Primary Option Panel, the Breakpoint Primary Option Panel allows you to use the RETURN command from any one of the selected test options to display the Breakpoint Primary Option Panel again. At the Breakpoint Primary Option Panel, the END and RETURN commands have no effect. You must use the Go option (G) to end processing at this breakpoint and continue processing the dialog being tested, or the Cancel option (C) to cancel the Dialog Test option (7). This protects against inadvertent loss of data.

The Breakpoint Primary Option Panel contains all the options of the Dialog Test Primary Option Panel except Exit (7.x) and, as such, presents all but one of the Dialog Test functions to you.

This panel also contains two options not shown on the Dialog Test Primary Option Panel: Go (G) and Cancel (C). When a breakpoint occurs, these options allow you to continue processing or stop processing, respectively:

G The Go option continues dialog processing from a breakpoint. The user dialog resumes processing from the point at which it was suspended.

C The Cancel option ends dialog testing and displays the first primary option panel you displayed at the beginning of your ISPF session again. All trace and breakpoint definitions are lost when you leave Dialog Test.

When a user dialog finds a breakpoint, the current dialog environment is saved. When you select the Go option, the environment is restored, except that:

- If you change variable, table, and file tailoring data at a breakpoint, these actions are an extension of the suspended dialog; it is as though the dialog had taken all the actions itself during processing.
- If you change the service return code on the Breakpoint Primary Option Panel, the new return code is passed back to the dialog as though the service had set the new return code itself.

- If you process the PANELID command at the breakpoint, the last setting for displaying panel identifiers is retained.
- If any CONTROL service settings for DISPLAY LINE or DISPLAY SM (Session Manager) were in effect before the breakpoint, such settings are lost.

Note that the manipulation of one dialog part can cause a change to another dialog part. For example, if a panel is displayed, variables can be set.

All trace and breakpoint definitions are lost if you select the Cancel option.

The Breakpoint Primary Option Panel also displays this information:

AFTER or BEFORE
An indication of whether the dialog has been suspended after or before the service has processed.

Service Name
The name of the service at which the dialog has been suspended. In Figure 227 on page 399, the service name is DISPLAY.

Current status:
The application's current status when the breakpoint occurred. These fields show this status:

Application
The application identifier of the suspended user dialog.

Function
The program or command name of the suspended user dialog.

Return code
The dialog service return code. This field is displayed only if the breakpoint occurs after the dialog service has processed. The Return code field is modifiable; its value is passed back to the dialog (as the service's) when you select the Go option. This helps test dialog error handling.

Breakpoint
One scrollable line showing an image of the dialog service call. Place the cursor over the image and use LEFT, RIGHT, and EXPAND functions to scroll the area. < and > appear below the line to indicate in which direction more data may be available. A maximum of 2048 characters may be displayed.

ISPEXEC calls are shown as typed.

ISPLINK (ISPLNK) calls are displayed with their parameter values separated by commas. Name-lists are shown as typed in the dialog, in string format or in structure format. Structure format includes the count, element length, and list of names. For variable services parameters whose context is defined by the name-list parameter on the service call (for example, the variable value areas for a VDEFINE), the first four bytes of the parameter value are displayed in hexadecimal format (`X'nnnnnnnn'`).

ISPEXEC calls from a program are the same as ISPEXEC calls from a command except that ISPEXEC is not displayed.

Tutorial (option 7.T)

The Tutorial option (7.T) allows you to display information about the Dialog Test facilities. Figure 228 shows the first panel displayed when you select the Tutorial option.

```
Tutorial ------------------- Dialog Test Tutorial ------------------- Tutorial

                          ___________________________
                         |     ISPF Dialog Test      |
                          ___________________________

This tutorial provides information about the features and operation of Dialog
Test.

The Dialog Test tutorial consists of two parts: one describes the Dialog Test
option, as selected from the ISPF Primary Option Panel, and the other
describes the Dialog Test facilities available when a user dialog encounters a
"breakpoint" in its processing.

Beginning users should review the Dialog Test Option topic first.

The following topics are presented in sequence, or can be selected by number:

   1  - Dialog Test Option
   2  - At A User Dialog Breakpoint
------ Cur panel = ISP70000 Prev panel = ISPYXD1  Last msg = ISPYP014   ------
Option ===> ____________________________________________________________________
 F1=Help      F2=Split     F3=Exit      F4=Resize    F5=Exhelp    F6=Keyshelp
 F7=PrvTopic  F8=NxtTopic  F9=Swap     F10=PrvPage  F11=NxtPage  F12=Cancel
```

Figure 228. Dialog Test Tutorial - first panel (ISP70000)

The default function key command assignments for a terminal with 12 function keys are shown at the bottom of the screen if you enter the PFSHOW command.

Exit (option 7.X)

The Exit option (7.X) ends your Dialog Test session. All trace and breakpoint definitions are lost.

Chapter 10. IBM products (option 9)

Option 9 provides an interface to other IBM program development products. It displays a panel that lists other IBM products that are supported as ISPF dialogs, as shown in Figure 229.

```
  Menu  Utilities  Compilers  Options  Status  Help
 ------------------------------------------------------------------------
 |                Additional IBM Program Development Products
 | Option ===> ____________________________________________________________
 |
 | 3  INFOMAN   Tivoli Information Management for z/OS
 | 4  COBOL/SF  COBOL Structuring Facility
 | 6  SDF II    Screen Definition Facility II - Editors and Utilities
 | 7  SDF II-P  Screen Definition Facility II - Prototype
 |
 |
 |
```

Chapter 11. SCLM (option 10)

Option 10 gives you access to the Software Configuration and Library Manager (SCLM), which is an extension of the ISPF library concept. You call SCLM functions by entering one of the options shown on the panel in Figure 230.

If SCLM does not appear on any of your menu panels or on the Menu pull-down, enter TSO SCLM on any ISPF command line. If SCLM is available to your terminal session, the SCLM Main Menu is displayed.

For more information about SCLM, refer to *z/OS ISPF Software Configuration and Library Manager Guide and Reference*.

```
  Menu  Utilities  Help
 ------------------------------------------------------------------------
                                SCLM Main Menu                   Enter option

 Enter one of the following options:

    1  View        ISPF View or Browse data
    2  Edit        Create or change source data in SCLM databases
    3  Utilities   Perform SCLM database utility/reporting functions
    4  Build       Construct SCLM-controlled components
    5  Promote     Move components into SCLM hierarchy
    6  Command     Enter TSO or SCLM commands
    6A Easy Cmds   Easy SCLM commands via prompts
    7  Sample      Create or delete sample SCLM project
    A  SCLM Admin  Maintaining SCLM administrators
    X  Exit        Terminate SCLM

 SCLM Project Control Information:
    Project . . . . ________  (Project high-level qualifier)
    Alternate . . . ________  (Project definition: defaults to project)
    Group . . . . . ________  (Defaults to TSO prefix)
 Option ===> ____________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 230. SCLM Main Menu (FLMDMN)

The option names on this panel are point-and-shoot fields. See the Point-and-Shoot Text Fields section of the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I* for more information.

SCLM Main Menu action bar

The SCLM Main Menu panel action bar choices function as follows:

Menu For more information, see the details about the Menu Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

Utilities For more information, see details about the Utilities Action Bar Choice in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I*.

© Copyright IBM Corp. 1980, 2007

Help The Help pull-down provides general information about SCLM topics as well as information about each available choice on the SCLM Main Menu.

SCLM overview

SCLM is a library facility that supports projects in developing complex software applications. It does this by providing software configuration and library management support. SCLM supports the software development cycle of an application from the program design phase to release of the final product.

SCLM allows designers and programmers to define the architecture of an application (how the components fit together) and ensures that the architecture definition is followed by automatically controlling, maintaining, and tracking software components. By automatically enforcing guidelines and procedures for developing software, SCLM enhances software quality and improves programmer productivity. For complete information on using SCLM, refer to *z/OS ISPF Software Configuration and Library Manager Guide and Reference*.

SCLM addresses these software configuration and library management issues:

- Ensures that two programmers are not working on the same component at the same time.
- Allows users to integrate components only at the correct time and only by using the correct procedure.
- Logs and tracks software changes.
- Provides application integrity; all of the software components used to produce the final product are available, but controlled.
- Documents the interfaces between the software components.

SCLM provides these facilities for automating software configuration and library management tasks:

Project Definition Establishes the database.

Edit Uses the ISPF editor to create and modify the software components.

Build Integrates the software components.

Promote Moves software components through the library hierarchy.

Utilities Maintain the database.

Reports Generate information about the build and promote activities, and about the contents of the database.

Interactive dialogs, batch interfaces, and callable services provide access to the functions and capabilities of SCLM. These functions support the routine use of SCLM by:

- Allowing programmers to use the ISPF editor to create and modify software components
- Providing automated draw down and lockout functions without requiring special customizing to suit a particular installation.

Chapter 12. ISPF object/action workplace (option 11)

Option 11 gives you access to the ISPF Object/Action Workplace. The Workplace combines many of the ISPF functions onto one object-action interface. The idea of object-action is to specify an *object* (such as an ISPF library, data set name, or workstation file) and then specify an *action* to perform upon it. You can specify any of these objects:

- An ISPF Library—a cataloged partitioned data set (PDS) with a three-level data set name in the project.group.type format.
- A partitioned or sequential data set.
- A VSAM data set for use with the data set actions allocate, delete, or information.
- A DSLIST level for data set list actions, for example, 'YOURID.*' for all data sets beginning with YOURID.
- A workstation file name for use with the actions edit or view.
- A volume serial number for uncataloged data sets to use with actions to retrieve volume information, print volume information, build a DSLIST based on a volume serial number, or as a filter for a DSLIST level.
- Personal data set lists or reference lists for use with action DL (DSLIST) only.

Additionally, Workplace provides ISPF Referral list fields to enable object selection through retrieval from personal lists (pre-packaged lists of data sets which you create) or reference lists (lists of recently referenced data sets which ISPF creates).

You can select an action by making a choice on an action bar or by using a command. Eighty-five ISPF functions are available as workplace actions.

There is a fast path system command for starting the Workplace. Type ISPFWORK on any ISPF command line and you are taken to the Workplace entry panel.

You can display the Workplace in GUI mode as well as standard mode. See "Workstation connection" on page 60 for information about how to start GUI mode for ISPF. All of the screens that appear in associated topics are shown in their standard mode.

Selecting objects

The first step in using the Workplace to perform ISPF functions is to specify the particular object that you want to perform an action on, for example, a sequential data set 'YOURID.SOURCE.DATA'. Object specification takes place on the Workplace entry panel.

Workplace entry panel

When you first enter the Workplace, the entry panel that appears is called ISPF Workplace. It is possible to display this panel in two distinct modes, called views: the *Library View* or the *Data Set View*.

The Library View panel has the words "Library View" as a heading just above the referral lists in the lower portion of the screen. This view enables you to work with ISPF library concatenations and library lists.

The Data Set View panel has the words "Data Set View" as a heading just above the referral lists in the lower portion of the screen. This view enables you to work

© Copyright IBM Corp. 1980, 2007

with data set lists, sequential files, or single partitioned data sets. You can choose to work with either entry panel view by using the command LISTVIEW, or the function key ChgView (F11) to toggle between the two panels.

Library view

You use the Library View to work with a ISPF library concatenations. The panel that appears in Figure 231 is the Library View entry panel for the Workplace.

```
  File  View  Options  Space  SuperC  Test  Help
 ------------------------------------------------------------------------
          Smart Action         ISPF Workplace

 ISPF Library
    Project  . . . _______
    Group  . . . . _______ . . . _______ . . . _______ . . . _______
    Type . . . . . SOURCE
    Member . . . . _______    (Blank or pattern for member action list)

 ---------------- ISPF Referral lists for object selection ----------------
 |  Library View    Action      #1-8=Retrieve Entry  DL=DSLIST  /=Open List |
 |  MYLIST   . . . _______      MANUAL DUMMY DATA             02/07/08 11:36 |
 |  REFLIST  . . . _______      Last 8 referenced libraries    -------- ----- |
 ************************* End of ISPF Referral lists *************************




 Action ===> ____________________________________________________ Scroll ===> PAGE
  F1=Help      F2=Split     F3=Exit      F4=Settings  F5=PrvObj    F6=PrvAct
  F7=Backward  F8=Forward   F9=Swap     F10=Actions  F11=ChgView  F12=Cancel
```

Figure 231. Workplace entry panel - library view (ISRWORK1)

When using this Workplace entry panel, you can select a data set or a group of data sets to work with in one of these ways:

- Fill in the ISPF Library fields. These fields are used the same way as they are on other ISPF panels. You can use the traditional method of selecting a data set by entering its Project, Group, Type, and Member names in the ISPF Library fields. Omitting the Member name gives you a list of members to choose from.
- Select an object or list of objects using “ISPF Referral lists for object retrieval”. See “ISPF referral lists for object retrieval” on page 409 for more information. You can access personal and reference lists, and then select libraries from these lists.

Data set view

You use the Data Set View to work with a single data set, a list of data sets, a workstation file, or any action that requires a volume serial.

Note: Catalog, DSLIST, Volume information, Print volume, and Workstation file actions, are only available from the Data Set View.

The panel that appears in Figure 232 on page 409 is the Data Set View entry panel for the Workplace.

```
  File  View  Options  Space  SuperC  Test  Help
 ------------------------------------------------------------------------
          Smart Action         ISPF Workplace

Data Set, DSLIST Level, or Workstation File
   Object Name . . . 'MYPROJ.DEV.SOURCE'
   Volume Serial . . ______  (For actions that require a volume serial)

 ------------------ ISPF Referral lists for object selection ------------------
 |  Data Set View   Action      #1-30=Retrieve Entry  DL=DSLIST  /=Open List  |
 |  REFLIST  . . . ________     Last 30 referenced data sets   -------- -----  |
 |  TEST     . . . ________     Test list                      02/10/01 12:06  |
 |  TEST2    . . . ________     Second Test List               02/10/01 12:05  |
************************* End of ISPF Referral lists *************************
 ------------------------------------------------------------------------
Action ===> ____________________________________________ Scroll ===> PAGE
 F1=Help      F2=Split     F3=Exit      F4=Settings  F5=PrvObj    F6=PrvAct
 F7=Backward  F8=Forward   F9=Swap     F10=Actions  F11=ChgView  F12=Cancel
```

Figure 232. Workplace entry panel - data set view (ISRWORK)

When using this Workplace entry panel, you can select a data set or a group of data sets to work with in one of these ways:

- You can use the traditional method of selecting a data set by entering its name in the Object Name field. For example, enter 'YOURID.SOURCE.DATA' to act upon a data set on the host, or D:\YOUR.FIL to act upon a workstation file (perhaps to edit it using the PDF editor).

  Note: The Object Name field supports the inclusion of system symbols.
- Select an object or list of objects using "ISPF Referral lists for object retrieval". You can access personal and reference lists, and select data sets, libraries, workstation files, VSAM files, and data set levels from each list.

ISPF referral lists for object retrieval

Both views of the ISPF Workplace entry panel enable you to use referral lists. The bottom of the ISPF Workplace panel contains a reference list entry field (REFLIST), followed by a list of personal lists. You can display either referral library lists or referral data set lists, depending on the view you choose.

All data sets and libraries referenced during an ISPF session are appended to the reference lists. You can use the input fields next to the referral lists to access a referral data set in one of these ways:

- Entering a slash (/) in this field causes the personal data set list or library list (depending on the selected view) to be displayed.
- Type `DL` in the input field and press Enter. This builds a DSLIST based on entries in the personal data set list, personal library lists, or Reflists.
- Enter a library entry number (from 1 to 8). If you know the list numbers of your libraries, for example, your panels library is number 1, you can type the number in this field and press Enter. ISPF retrieves the respective library entry from the library reference list.
- Enter a data set entry number (from 1 to 30). If you know the order of your data sets, you can type the number in this field and press Enter. ISPF retrieves the respective data set entry from the data set reference list.

Specifying actions

After you select the object you want to work with, choose the action to perform on it. You can select an action by making a choice on an action bar or by using a command.

Choices on the Workplace action bar

The Workplace action bar makes available these choices.

File

The File action bar choice enables you to manipulate files. The pull-down choices for File are:

Choice **Description**

List Displays a pop-up menu that enables you to choose either a *member list*, a *data set list* list, a list of *personal data set lists* or a list of *personal library lists*. You can perform any of the File actions except *DSLIST* against the resulting member list.

Member list

Displays a list of members for a partitioned data set. To display a member list:

1. Type the library or data set information in the appropriate fields of the Workplace entry panel (library view).
2. Specify blank or a pattern for the member name to display a member list.
3. Select the List action from the File action bar choice.
4. Select "Member list" from the List Action prompt panel.

Note: All member lists displayed by the ISPF Workplace are enhanced member lists, all supported member list actions and commands are available on any member list display.

Data Set list

Displays a list of data sets based on a DSLIST level and, optionally, a volume serial number. The data set list initial view can be set from the Workplace Settings panel. To create a data set list:

1. Type the data set level in the Object name field on the Workplace entry panel (data set view). If you do not full qualify the data set level (by enclosing it in single quotes), your TSO prefix is set as the first level. Optionally, you can enter a volume to view just the data sets that match the DSLIST level on the volume entered. You can also optionally enter just a volume name to list all data sets on the volume entered.
2. Select the List action from the File action bar choice.
3. Select Data Set List from the List Action prompt panel.

Personal Data Set lists

Displays a list of your personal data set lists. All valid personal list actions can be performed against any selected personal list. The personal data set list you used most recently is the current active list. The currently active list cannot be directly deleted from the list dialog, however all other list actions are valid. To list your personal data set lists:

1. Select the List action from the File action bar choice.

2. Select Personal Data Set List from the List Action prompt panel. You can perform this action from either view of the Workplace entry panel.

Personal Library lists

Displays a list of your personal library lists. All valid personal list actions can be performed against any selected personal list. The personal library list you used most recently is the current active list. The currently active list cannot be directly deleted from the list dialog, however all other list actions are valid. To list your personal library lists:

1. Select the List action from the File action bar choice.
2. Select Personal Library List from the List Action prompt panel. You can perform this action from either view of the Workplace entry panel.

Edit

Starts Edit action for a member or a sequential file. The Edit action prompt panel is presented when you choose the Edit pull-down choice on the action bar. Select a file type and an editor and press Enter. The Edit function is used to edit a member of a partitioned data set, a sequential data set, or a workstation file.

Type of File

Select the type of file you want to edit.

1. Host File

Edit a host file using ISPF Edit or a workstation-defined editor. The selection of host or workstation editors is based on the Editor Choice option setting on the Edit Entry panel. To start the member list function, enter a pattern or leave the member field blank on the Workplace entry panel. To edit a single member on the host:

1. Type the library or data set information in the appropriate fields of the Workplace entry panel.
2. Type the member name in the member field (for library view) or in parentheses after the data set name (for data set view).
3. Select Edit under the File action bar choice.
4. Select Host File and ISPF Editor on the Edit Action prompt panel.

To edit a single member on the workstation:

1. Type the library or data set information in the appropriate fields of the Workplace entry panel.
2. Type the member name in the member field (for library view) or in parentheses after the data set name (for data set view).
3. Select Edit under the File action bar choice.
4. Select Host File and Workstation Editor on the Edit Action prompt panel.

2. Workstation File

To edit a workstation file using the ISPF editor:

1. Type the file path and name in the Object name field on the Workstation entry panel (data set view).
2. Select Edit from the File action bar choice.
3. Select Workstation File and ISPF Editor from the Edit Action prompt panel.

To edit a workstation file using a workstation editor:
1. Type the file path and name in the Object name field on the Workstation entry panel (data set view).
2. Select Edit from the File action bar choice.
3. Select Workstation File and Workstation Editor from the Edit Action prompt panel.

Editor Choice

1. ISPF Editor
Selects the ISPF editor.

2. Workstation Editor
Selects the workstation editor.

View Starts View action for a member or a sequential file. The View prompt panel is presented when you choose the View pull-down choice on the File action bar. The View function is used to view a member of a partitioned data set, a sequential data set, or a workstation file.

Type of File
Select the type of file you want to view.

1. Host File
View a host file using ISPF View or a workstation-defined editor/browser. The view mechanism used is based on the *View Choice* setting found on the View entry panel. To enter the member list function, type a pattern or leave the member field blank on the Workstation entry panel. To view a single member on the host:
1. Type the library or data set information in the appropriate fields on the Workplace entry panel.
2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select View from the File action bar choice.
4. Select Host File and ISPF View from the View Action prompt panel.

To view a single member on the workstation:
1. Type the library or data set information in the appropriate fields on the Workplace entry panel.
2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select View from the File action bar choice.
4. Select Host File and Workstation View from the View Action prompt panel.

2. Workstation File
To view a workstation file using ISPF View:
1. Type the file path and name in the Object name field of the Workstation entry panel (data set view).
2. Select View from the File action bar choice.
3. Select Workstation File and ISPF View from the View Action prompt panel.

To view a workstation file using a workstation editor or browser:

1. Type the file path and name in the Object name field of the Workstation entry panel (data set view).
2. Select View from the File action bar choice.
3. Select Workstation File and Workstation View from the View Action prompt panel.

View Choice

1. ISPF View
Selects the ISPF view function.

2. Workstation View
Selects the workstation editor or browser.

Browse
Starts Browse action for a member or a sequential file.

If you do not specify a member name or if you specify a pattern and the specified data set is a PDS, a member list is displayed. Select a member to Browse by typing s next to the member name.

To browse a single member:
1. Type the library or data set information in the appropriate fields of the ISPF Workplace panel.
2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select Browse from the File action bar choice.

Delete Displays a pop-up prompt window with *member* or *data set* as the choices.

If you specify an asterisk (*) as the member name, all members of the PDS are deleted without a member list being displayed.

If you do not specify a member name or if you specify a pattern and the specified data set is a PDS, a member list is displayed. Select members to delete by typing s next to the member name.

Note: You can change how member name patterns are handled in your Workplace Settings. See "Show status for M,C,D,G actions" on page 432 for more information.

To delete a single member:
1. Type the library or data set information in the appropriate fields of the ISPF Workplace panel.
2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select Delete under the File action bar choice for member delete.

To delete a PDS or a sequential data set:
1. Enter the data set name in the Object name field, or enter a library in the ISPF Library field on the Workplace panel.
2. Select Delete under the File action bar choice for data set delete.

Rename
Displays a pop-up prompt window with *member* or *data set* as the choices.

If you do not specify a member name or if you specify a pattern and the specified data set is a PDS, a member list is displayed. Select a member to Rename by typing s next to the member name.

To rename a single member:
1. Type the library or data set information in the appropriate fields of the ISPF Workplace panel.

2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select Rename under the File action bar choice for member rename.

To rename a PDS or a sequential data set:
1. Type the data set name in the Object name field, or type a library in the ISPF Library field on the Workplace panel.
2. Select Rename under the File action bar choice for data set rename.

For more information, see "Rename" on page 427.

Move Starts the move action for a member or a sequential file. A Move entry panel is presented.

If you specify an asterisk (*) as the member name, all members of the PDS are moved without a member list being displayed.

If you do not specify a member name or if you specify a pattern and the specified data set is a PDS, a member list is displayed. Select members to move by typing s next to the member name.

Note: You can change how member name patterns are handled in your Workplace Settings. See "Show status for M,C,D,G actions" on page 432 for more information.

To move a single member:
1. Type the library or data set information in the appropriate fields of the ISPF Workplace panel.
2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select Move from the File action bar choice.

For more information, see "Move or copy" on page 426.

Copy Starts the copy action for a member or a sequential file. A Copy entry panel is presented.

If you specify an asterisk (*) as the member name, all members of the PDS are copied without a member list being displayed.

If you do not specify a member name or if you specify a pattern and the specified data set is a PDS, a member list is displayed. Select members to copy by typing s next to the member name.

Note: You can change how member name patterns are handled in your Workplace Settings. See "Show status for M,C,D,G actions" on page 432 for more information.

To copy a single member:
1. Type the library or data set information in the appropriate fields of the ISPF Workplace panel.
2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select Copy from the File action bar choice.

For more information, see "Move or copy" on page 426.

Reset Starts reset action for a member. A Reset prompt panel is presented for the member.

If you specify an asterisk (*) as the member name, all members of the PDS are reset without a member list being displayed.

If you do not specify a member name or if you specify a pattern and the specified data set is a PDS, a member list is displayed. Select members to reset by typing s next to the member name.

Note: You can change how member name patterns are handled in your Workplace Settings. See "Show status for M,C,D,G actions" on page 432 for more information.

To reset a single member:
1. Type the library or data set information in the appropriate fields of the ISPF Workplace panel.
2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select Reset from the File action bar choice.

For more information, see "Resetting member statistics" on page 421.

Open Is defined on the Workplace Settings panel, making it a user customizable action. After you set this action, it is performed automatically each time you open a member. The Open action can be set to these actions:

User Any TSO command, REXX exec, or CLIST set by the **Open Command** field on the Workplace Settings panel.
E Edit
V View
B Browse
D Delete member
R Rename member
M Move
C Copy
G Reset
P Print member
J Submit
T TSO command action

To open a single member:
1. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
2. Select Open from the File action bar choice. When you press the ENTER key, the action for open runs against the member, or a member list is displayed. See "Changing workplace settings" on page 431 for more information.

Submit
Submits the member or sequential file to TSO for job execution.

If you do not specify a member name or if you specify a pattern and the specified data set is a PDS, a member list is displayed. Select a member to submit by typing s next to the member name.

To submit a single member, fill in these fields of the ISPF Workplace panel:
1. Type the library or data set information in the appropriate fields.
2. Type the member name in the member field (for ISPF library view) or in parentheses after data set name (for data set view).
3. Select Submit from the File action bar choice.

Print The Print selection enables you to print information. The pull-down choices on the Print action prompt panel are:

Data Set
Prints the entire data set. To print a data set:

1. Type the data set name in the Object name field (for the data set view) or enter an ISPF library name in the ISPF Library fields (for the library view).
2. Select the Print action from the File action bar choice.
3. Select Data Set from the Print Action prompt panel.

Data Set index
Prints the data set index for the selected data set. To print a data set index:
1. Type the data set name in the Object name field or type an ISPF library name in the ISPF Library fields.
2. Select the Print action from the File action bar choice.
3. Select Data Set Index from the Print Action prompt panel.

Data Set List
Prints the list of data sets for the selected data set name level. To print a data set list:
1. Type a data set level, or optionally a volume serial, in the appropriate fields on the ISPF Workplace panel.
2. Select Print from the File action bar choice.
3. Select Data set List from the Print Action prompt prompt panel.

VTOC Prints the VTOC information for the selected volume. To print a VTOC summary:
1. Type a volume serial in the proper field on the ISPF Workplace panel.
2. Select Print from the File action bar choice.
3. Select VTOC from the Print Action prompt panel.

Member
Prints the selected member. To print a member:
1. Type the data set name in the Object name field or type an ISPF library name in the ISPF Library fields.
2. Select the Print action from the File action bar choice.
3. Select Member from the Print Action prompt panel.

Command
Enables you to enter TSO, Workstation, or ISPF commands. You are prompted to choose between types of commands. The pull-down choices on the Command prompt are:

TSO Cmd
The TSO Cmd action is used to run a TSO command, passing the data set and member name and any additional parameters to the TSO command entered. To run a TSO command against a single member, fill in these fields of the ISPF Workplace panel:
1. Type the library or data set information in the appropriate fields.
2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select Command from the File action bar choice.
4. Select TSO from the Command Action prompt panel.

WS Cmd
The WS Cmd action is used to run a WS command, passing the data set and member name and any additional parameters to the WS command entered.

To run a WS command against a single member, fill in these fields of the ISPF Workplace panel:

1. Type the library or data set information in the appropriate fields.
2. Type the member name in the member field (for ISPF library view) or in parentheses after the data set name (for data set view).
3. Select Command from the File action bar choice.
4. Select WS command from the Command Action prompt panel.

Note: The ISPF Client/Server must be connected to run the WS command.

ISPF Command Shell

The ISPF command shell option enables TSO commands, CLISTs, and REXX execs to be run under ISPF. You can enter the TSO commands, CLISTs, and REXX execs in the command input field of any panel.

ISPF also enables Workstation commands to be entered in the command input field of any panel.

You can enter a long command that wraps to the next line if you want to. For more information about the ISPF Command Shell, see "ISPF command shell" on page 424.

ISPF Command Table

The command table utility allows you to create or change application command tables.

A command table contains the specification of general commands that can be entered from any panel during the execution of an application. Command tables are identified by application id, and are maintained in the ISPF table input library.

Exit Ends the Workplace, returning to the primary option panel.

View

The View action bar choice displays the object views that are available to you. The currently selected view is unavailable.

The pull-down choices for View are:

Choice	Description
Data Set View	Changes the current view to reference data set list, personal data set lists, and Object name view. To change to the data set view: 1. Select the View action bar choice. 2. Select Data Set View from the pull-down menu.
Library View	Changes the current view to reference library list, personal library lists, and ISPF Library view. To change to the ISPF Library view: 1. Select the View action bar choice. 2. Select Library View from the pull-down menu.
By name	Changes the current view of the personal list by sorting on the name field.

By description
Changes the current view of the personal list by sorting on the description field.

By created Changes the current view of the personal list by sorting on the created field.

By referenced Changes the current view of the personal list by sorting on the referenced field.

Options

The Options action bar choice displays the settings available. The pull-down choices for Options are:

Choice **Description**

Workplace Settings
Displays the Workplace Settings panel. See "Changing workplace settings" on page 431 for more information.

ISPF Settings Displays the ISPF Settings panel. See Chapter 2, "Settings (option 0)," on page 23 for more information.

CUA Attributes
Starts the ISPF CUA Attribute Change Utility dialog. See "CUA cttributes" on page 54 for more information.

Keylists Starts the ISPF Keylist Utility dialog. See "Working with function keys and keylists (the Function Keys action bar choice)" on page 37 for more information.

Point-and-Shoot
Starts the ISPF CUA Attribute Change Utility dialog indexed to the point-and-shoot entry. See "CUA cttributes" on page 54 for more information.

Colors Starts the ISPF Global Color Change Utility dialog. See "Changing default colors (the Colors action bar choice)" on page 51 for more information.

Space

The Space action bar choice enables you to create and maintain data sets. The pull-down choices available for Space are:

Choice **Description**

Allocate Displays a pop-up menu for the allocate action. The choices on the prompt are:

Data Set
The allocate action is used to allocate a partitioned or sequential data set. To allocate a data set:
1. Type the data set name in the Object name field or type an ISPF library name in the ISPF Library fields.
2. Select the Allocate action from the Space action bar choice.
3. Select Data Set from the Allocate Action prompt panel.

Enhanced Data Set
The enhanced allocate action is used to allocate an SMS-managed partitioned or sequential data set. To allocate an SMS data set:
1. Type the data set name in the Object name field or enter an ISPF library name in the ISPF Library fields.

2. Select the Allocate action from the Space action bar choice.
3. Select Enhanced Data Set from the Allocate Action prompt panel.

VSAM Data Set
The VSAM action is used to define, delete, or retrieve information for a VSAM data set. To define, delete, or retrieve information for a VSAM data set:
1. Type the VSAM data set name in the Object name field or enter an ISPF library name in the ISPF Library fields.
2. Select the Allocate action from the Space action bar choice.
3. Select VSAM Data Set from the Allocate Action prompt panel.

Compress
The Compress action is used to recover unused space in a partitioned or sequential data set. To compress a data set:
1. Type the data set name in the Object name field or type an ISPF library name in the ISPF Library fields.
2. Select the Compress action from the Space action bar choice.

Catalog
The Catalog action is used to catalog a partitioned or sequential data set on a direct access device. To catalog a data set:
1. Type the data set name in the Object name field.
2. Type the volume name in the volume field.
3. Select the Catalog action from the Space action bar choice.

Note: You cannot catalog an SMS-managed data set.

Uncatalog
The Uncatalog action is used to uncatalog a partitioned or sequential data set from a direct access device. To uncatalog a data set:
1. Type the data set name in the Object name field.
2. Select the Uncatalog action from the Space action bar choice.

Note: You cannot uncatalog an SMS-managed data set.

A confirmation dialog appears if specified in the Workplace Settings panel. See “Changing workplace settings” on page 431 for more information.

Information
The Data Set Information action is used to retrieve information about a partitioned or sequential data set. To retrieve data set information:
1. Type the data set name in the Object name field or type an ISPF library name in the ISPF Library fields.
2. Select Information from the Space action bar choice.
3. Select one of these choices from the Information Action prompt panel:

   Data Set Long
   Displays information about the selected data set.

   Data Set Short
   Displays a subset of information about the selected data set.

   VTOC summary
   Displays VTOC information about the selected volume. You must type the volume serial of the VTOC in the volume serial field of the Workplace entry panel.

SuperC

The SuperC action bar choice gives you access to SuperC compare and search dialogs for your data sets. The data set you specify on the Workplace panel is automatically filled in for you in the Superc dialog you choose. For more information, see "SuperC utility (option 3.12)" on page 203.

The SuperC pull-down choices are:

Choice	Description
SuperC	Compare two data sets. To SuperC compare two data sets: 1. Type the first data set name in the Object name field or type an ISPF library name in the ISPF Library fields. 2. Select the SuperC action from the SuperC action bar choice. The SuperC Compare Utility— New Data Set Specification panel appears with the data set information entered in it. Make sure the panel is filled in the way you want it to be. 3. Press Enter to display the *Old* SuperC comparison panel, and fill in the panel. 4. Press Enter again to submit the comparison. For more information, see "SuperC utility (option 3.12)" on page 203.
SuperCE	Compare two data sets using extended options. For more information, see "SuperCE utility (option 3.13)" on page 213.
Search-For	Search data sets for strings of data. To SuperC search for strings of data: 1. Type the data set name in the Object name field or type an ISPF library name in the ISPF Library fields. 2. Select the Search-For action from the SuperC action bar choice. The Search-For Utility panel appears with the data set information entered in it. Make sure the panel is filled in the way you want it to be. For more information, see "Search-For utility (option 3.14)" on page 225.
Search-ForE	Search a data set using extended options. For more information, see "Search-ForE utility (option 3.15)" on page 231.

Test

The Test action bar choice gives you access to the ISPF services that help you test dialogs, such as Chapter 9, "Dialog test (option 7)," on page 355. For more information, refer to the *z/OS ISPF Dialog Developer's Guide and Reference*, and the *z/OS ISPF Edit and Edit Macros*.

The Test pull-down choices are:

Choice	Description
Functions	Displays the Dialog Test Function/Selection panel. Select the Functions action from the Test action bar choice. For more information, see "Functions (option 7.1)" on page 362.
Panels	Displays the Dialog Test Display panel. Select the Panels action from the Test action bar choice. For more information, see "Panels (option 7.2)" on page 366.
Variables	Displays the Dialog Test Variables panel. Select the Variables action

from the Test action bar choice. For more information, see "Variables (Option 7.3)" on page 368.

Tables Displays the Dialog Test Tables panel. Select the Tables action from the Test action bar choice. For more information, see "Tables (option 7.4)" on page 373.

Log Displays the ISPF Transaction Log panel. Select the Log action from the Test action bar choice. For more information, see "Log (option 7.5)" on page 385.

Services Displays the Invoke Dialog Service panel. Select the Services action from the Test action bar choice. For more information, see "Dialog services (option 7.6)" on page 387.

Traces Displays the Dialog Test Traces panel. Select the Traces action from the Test action bar choice. For more information, see "Traces (option 7.7)" on page 390.

Break Points Displays the Dialog Test Breakpoints panel. Select the Break Points action from the Test action bar choice. For more information, see "Breakpoints (option 7.8)" on page 394.

Dialog Test Displays the Dialog Test Primary Option panel. Select the Dialog Test action from the Test action bar choice. For more information, see Chapter 9, "Dialog test (option 7)," on page 355.

Dialog Test appl ID
Displays the Dialog Test Application ID panel for changing the Dialog Test application ID. Select the Dialog Test appl ID action from the Test action bar choice.

Help

The Help action bar choice provides access to the program tutorials.

Actions that require prompt windows for more information

Some actions that you call from the Workplace require additional information. You provide this information through the use of pop-up prompt windows. Some common actions of this type are:

- Resetting member statistics
- Using TSO commands
- Using WS commands
- Using the ISPF command shell
- Moving or copying data
- Renaming data sets

Following are the actions and the pop-up windows that accompany each one.

Resetting member statistics

Figure 233 on page 422 shows the pop-up prompt window that appears when you choose Reset from the File action bar, after you choose a member to work with.

```
  Menu  Functions  Confirm  Utilities  Help
_ ┌──────────────────────────────────────────────────────────────────────┐ __
I │                       Reset Member Statistics                        │ 01
  │                                                                      │
S │  Data Set Name:                                                      │ MP
  │  'MYPROJ.DEV.SOURCE(TEST)'                                           │
  │                                                                      │
  │  Options                                                             │
  │  _  1. Reset ISPF statistics                                         │
  │     2. Delete ISPF statistics                                        │
  │                                                                      │
  │  New Userid  . . . _______  (If userid is to be changed)             │
  │  New Version . . . __       (If version number is to be changed)     │
  │  New Mod . . . . . __       (If mod number is to be changed)         │
  │                                                                      │
  │ Press ENTER to process action. Press CANCEL to cancel reset.         │
  │  F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward  │
  │  F9=Swap      F12=Cancel                                             │
  └──────────────────────────────────────────────────────────────────────┘


Command ===>                                                Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 233. Reset statistics panel (ISRURSET)

For more information about how the Reset statistics option works, see “Reset ISPF statistics utility (option 3.5)” on page 176. You can set these items from this window:

Options
Select 1 to Reset ISPF statistics, or 2 to Delete ISPF statistics.

New Userid
Sets the ID field in the statistics. If you want to change the ID the statistics are kept under, enter the new ID here. If you do not specify a new version number, this field is required to be filled in.

New Version
Enter a number here is you want to change the version number. This field is required if you do not enter a new userid. It is ignored if you have chosen the delete action.

New Mod
Use a slash (/) to select this option. Deselect this option if you do not want to reset the modification level. A new version number is required to reset the modification level.

TSO command

Figure 234 on page 423 shows the pop-up prompt window that appears when you choose Command, from the File action bar choice, then select TSO Command from the Command Action prompt panel.

```
 Menu  Functions  Confirm  Utilities  Help
 ------------------------------------------------------------------------------
                              TSO Command Action

 The "/" character can be used within the command string to represent the
 following fully qualified and quoted data set name:
 'MYPROJ.DEV.SOURCE(TEST)'

 Enter TSO Command and any additional parameters as needed:
 ____________________________________________________________________________
 ____________________________________________________________________________

 Press ENTER to execute command, press CANCEL to cancel action.
  F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
  F9=Swap       F12=Cancel
 ------------------------------------------------------------------------------

Command ===>                                                   Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 234. TSO command panel (ISRUTCES)

You can set these items from this window:

TSO Command
The name of the TSO command you want to use. The command name can be followed by command parameters with the / character appearing anywhere within the parameter string.

WS command

Figure 235 on page 424 shows the pop-up prompt window that appears when you choose Command, from the File action bar choice, then select WS Command from the Command Action prompt panel. You must have a workstation connection in place in order to use WS commands.

```
 Menu  Functions  Confirm  Utilities  Help
                              WS Command Action

 The "/" character can be used within the command string to represent the
 following fully qualified, unquoted data set name:
 MYPROJ.DEV.SOURCE(TEST)
 * No workstation connection
 Enter Workstation Command and any additional parameters as needed:
 ____________________________________________________________________________
 ____________________________________________________________________________

 Press ENTER to execute command, press CANCEL to cancel action.
  F1=Help        F2=Split       F3=Exit        F7=Backward    F8=Forward
  F9=Swap       F12=Cancel




Command ===>                                                   Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 235. WS command panel (ISRUWCES)

You can set these items from this window:

WS Command
The name of the WS command you want to use. The command name can be followed by command parameters with the / character appearing anywhere within the parameter string.

ISPF command shell

Figure 236 on page 425 shows the pop-up prompt window that appears when you enter the ISPF command shell. To get to this window, choose Command from the File action bar choice, then choose ISPF Command Shell on the Command Action prompt panel.

```
  Menu  List  Mode  Functions  Utilities  Help
 ___________________________________________________________________________
                              ISPF Command Shell
 Enter TSO or Workstation commands below:

 ===> ______________________________________________________________________
 ___________________________________________________________________________
 ___________________________________________________________________________

 Place cursor on choice and press enter to Retrieve command

 => xmit carvm3.userid da('userid.private.clist(types)')seq
 => status
 =>
 =>
 =>
 =>
 =>
 =>
 =>
 =>

  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F10=Actions  F12=Cancel
```

Figure 236. ISPF Command Shell panel (ISRTSO)

The ISPF Command Shell option enables you to run TSO commands, CLISTs, and REXX execs under ISPF. This panel has one input field. Type the command and its parameters into the input field, leaving at least one space between the command name and the first parameter. The input field continues for two full lines below the start of the input field. The maximum number of characters that you can enter is 234. For example:

```
Enter TSO or Work Station commands below

===> SEND 'THIS MESSAGE DEMONSTRATES THAT A TSO COMMAND ENTERED UNDER
ISPF CAN EXCEED ONE LINE ON THE 3270' USER(ALICE)
```

You can also enter ISPF commands, such as END or RETURN, in this field.

Note: If you enter HELP or CANCEL, it is interpreted as the ISPF Help or Cancel command. To issue TSO Help, enter:

```
===> TSO HELP xxxxx
```

To issue TSO Cancel, enter:

```
===> TSO CANCEL xxxxx
```

The ISPF command shell option enables you to enter most TSO commands under ISPF. Following is a list of commands that are not supported:

- LOGON
- LOGOFF
- ISPSTART, PDF, and ISPF
- TEST
- Commands that you are restricted from using by TSO
- Commands requiring large parameter lists (234 characters is the maximum allowed, including command name)

You can run command procedures under ISPF, subject to these restrictions:

- CLISTs and execs must not invoke restricted commands listed previously.

- TERMIN command procedure statements are not supported.

These restrictions also apply to commands entered from other panels.

After you type a command in the input field, press ENTER to start the command. If you are not operating in Session Manager mode, the cursor is positioned below the command input field. Line-at-a-time I/O from the command, if any, starts at the cursor position. When the command finishes, three asterisks (***) may appear on the screen. To return to ISPF full-screen mode, press ENTER.

The ISPF command shell panel is then redisplayed with the command you entered displayed in the command list (unless you entered the TSO or WS prefix, or List mode is set to update off).

Move or copy

Figure 237 shows the pop-up prompt window that appears when you choose Move from the File action bar, after you choose a member to work with. The panel that appears when you choose Copy is similar to this one.

```
  RefList  Help
 ____________________________________________________________________________
                                MOVE Entry Panel
                                                                   More:     +
 CURRENT from data set: 'MYPROJ.DEV.SOURCE(TEST)'

 To Library                       Options:
    Project . . . MYPROJ             Enter "/" to select option
    Group . . . . DEV                _  Replace like-named members
    Type  . . . . SOURCE             /  Process member aliases

 To Other Data Set Name
    Data Set Name . . . ____________________________________________
    Volume Serial . . . ______     (If not cataloged)

 NEW member name  . . . ________   (Blank unless member to be renamed)

 Options
    Sequential Disposition         Pack Option         SCLM Setting
    2  1. Mod                      1  1. Default       3  1. SCLM
       2. Old                         2. Pack            2. Non-SCLM
 Command ===> ____________________________________________________________
  F1=Help      F2=Split     F3=Exit      F7=Backward  F8=Forward   F9=Swap
 F12=Cancel
```

Figure 237. Move panel (ISRUMVC)

For more information about the Move/Copy utility, see “Move/Copy utility (option 3.3)” on page 132. You can set these items from this window:

To Library
The library to which you want to move or copy the selected data.

To Other Data Set Name
The data set to which you want to move or copy the selected data.

NEW member name
If the “To” and “From” data sets are the same, you can rename the member here.

Replace like-named members
Select this option to allow replacement of a member in the ″To″ data set with a like-named member in the ″From″ data set.

Process member aliases
Select this option to allow the primary member and all alias members to be moved together.

Sequential disposition
Select 1 if Mod, 2 if Old

1 Mod adds new data at the end of data currently contained in the data set.

2 Old begins placing new data at the beginning of the data set, writing over existing data.

Pack option
Indicates how you want the data to be stored in the “To” data set.

1 Data set is packed according to your default settings.

2 Data set is packed.

SCLM setting
Indicates how you want the data to be stored in the “To” data set.

1 SCLM

2 Non-SCLM

3 As is

Rename

Figure 238 shows the pop-up prompt window that appears when you choose Rename from the File action bar, after you choose a member to work with.

```
  File  View  Options  Space  SuperC  Test  Help
_ ┌──────────────────────────────────────────────┐ ──────────────────────────
  │        Workplace Rename Action Prompt        │
  │                                              │
D │ Rename  . . _  1. Data Set                   │
  │                2. Member                     │
  │                                              │ re a volume serial)
  │ Select a choice and press ENTER to continue  │
┌ │                                              │ lection ──────────────────┐
│ │  F1=Help        F2=Split       F3=Exit       │  DL=DSLIST  /=Open List   │
│ │  F7=Backward    F8=Forward     F9=Swap       │ ta sets   -------- -----  │
│ └──────────────────────────────────────────────┘           02/10/01 12:06 │
│ TEST2    . . .              Second Test List                02/10/01 12:05 │
************************* End of ISPF Referral lists *************************
```

```
Action ===> RP                                              Scroll ===> PAGE
 F1=Help      F2=Split     F3=Exit      F4=Settings  F5=PrvObj    F6=PrvAct
 F7=Backward  F8=Forward   F9=Swap     F10=Actions  F11=ChgView  F12=Cancel
```

Figure 238. Rename prompt panel (ISRURNAM)

You choose to rename either a data set or a member from this panel. If you choose data set, the panel in Figure 239 on page 428 appears.

```
                              Rename Data Set

 Data Set Name . . : MYPROJ.DEV.SOURCE
 Volume Serial . . : MVS8WF

 Enter new name below:  (The data set will be recataloged.)

 ISPF Library:
    Project  . . ________
    Group  . . . ________
    Type . . . . SOURCE

 Other Partitioned or Sequential Data Set:
    Data Set Name . . . 'MYPROJ.DEV.SOURCE'


 Command ===> ____________________________________________________
  F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
  F9=Swap      F10=Actions   F12=Cancel
```

Figure 239. Rename data set panel (ISRUARP1)

You can set these items from this window:

New name
The name that you want to use for the renamed data set.

If you choose member, the panel in Figure 240 appears.

```
  Menu  Functions  Confirm  Utilities  Help
 ___________________________________________________________________________
 |            Member Rename                |                  Row 00001 of 00001
 |                                         | d           Changed            ID
 | Enter a new member name:                | /08   2002/07/08 13:32:15    GRAHAMP
 |                                         |
 | Old Name  . . : TEST                    |
 |                                         |
 | New Name  . . . ________                |
 |                                         |
 |                                         |
 | Press ENTER to rename member.           |
 | Press CANCEL to cancel rename.          |
 |                                         |
 |  F1=Help           F2=Split             |
 |  F3=Exit           F7=Backward          |
 |_________________________________________|


Command ===>                                                  Scroll ===> PAGE
 F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
F10=Left   F11=Right  F12=Cancel
```

Figure 240. Rename member panel (ISRUREN)

You can set these items from this window:

New name
The name that you want to use for the renamed member.

Commands

You can use primary commands in the command area (Action line) of the Workplace entry panels.

You must be connected to the workstation to use any workstation file actions. You can configure your workstation editor choice by selecting the *Workstation* action bar from the Edit or View entry prompt panel or from the Workplace Settings panel.

Table 22. Workstation commands

Command	Description	Valid For:
A	Allocate	Data sets
ACTBAR or NOACTBAR	Display or do not display action bar on panel	Action prompt
AP	Allocate	Action prompt
B	Browse	Members and non-PDS data sets
C	Copy	Members and non-PDS data sets
COLOR	Global color change	Action prompt
CP	Command	Action prompt
CUAATTR	CUA attributes	Action prompt
D	Delete	Members and non-PDS data sets
DF	Delete	Data sets
DL	DSLIST	Data set name level
DP	Delete	Action prompt
DVT	VTOC summary	Data summary
E	Edit	Members and non-PDS data sets
EP	Edit	Action prompt
G	Reset member statistics	Members
I	Full information	Data sets
ICS	ISPF command shell	Action prompt
ICT	ISPF command table	Action prompt
IP	Information	Action prompt
J	Submit	Members and non-PDS data sets
K	Catalog	Data sets
KEYLIST	Keylist utility	Action prompt
L	Print data set	Data sets
LOCATE, LOC, or L	Find a specified referral list in the scrollable display of referral lists	Referral lists
LP	List	Action prompt
LV or LISTVIEW	List view	Action prompt
M	Move	Members and non-PDS data sets
ML	Member list	Partitioned data sets
N	Rename	Data sets
O	Open	Members and non-PDS data sets
OPD	Personal data set lists	Referral lists
OPL	Personal library lists	Referral lists
P	Print	Members and non-PDS data sets

Table 22. Workstation commands (continued)

Command	Description	Valid For:
PDL	Print data set list	Data sets
PP	Print	Action prompt
PSCOLOR	Point and shoot	Action prompt
PVT	Print VTOC information	Data sets
Q	VSAM	Data sets
R	Rename	Members and non-PDS data sets
RP	Rename	Action prompt
S	Short information	Data sets
SC	SuperC	Data sets
SCE	SuperC extended	Data sets
SELECT, SEL, or S	Select a specified referral list in the scrollable display of referral lists	Referral lists
SETTINGS	ISPF settings	Action prompt
SF	SearchFor	Data sets
SFE	SearchFor extended	Data sets
T	TSO command	Members and non-PDS data sets
U	Uncatalog	Data sets
V	View	Members and non-PDS data sets
VP	View	Action prompt
W	WS command	Members and non-PDS data sets
WE	Workstation file, edit on host	Workstation files
WEW	Workstation file, edit on workstation	Workstation file
WPSET	Workplace settings	Action prompt
WV	Workstation file, view on host	Workstation files
WVW	Workstation file, view on workstation	Workstation files
X	Print data set index	Data sets
Y	Allocate SMS (enhanced)	Data sets
Z	Compress	Data sets
= (equal sign)	Repeat last command. If no previous action, *view* is the default.	Members and non-PDS data sets

Default CUA function key settings

Table 23 shows how the function keys are defined for the main Workplace panel when the mode is set to keylist ON and function keys are set to primary LOWER.

Table 23. Workplace function key settings

Key	Action	Description:
F1	Help	Workplace help
F2	Split	Split screen
F3	Exit	Exit Workplace
F4	Settings	ISPF Workplace settings
F5	PrvObj	Recall last object
F6	PrvAct	Repeat last action
F7	Backward	Scroll up Reflist

Table 23. Workplace function key settings (continued)

Key	Action	Description:
F8	Forward	Scroll down Reflist
F9	Swap	Swap screen
F10	Actions	Cursor to action bar
F11	ChgView	Change Workplace view
F12	Cancel	Exit Workplace
F13	Help	Help
F14	Split	Split
F15	End	End
F16	Return	Return
F17	Rfind	Repeat find
F18	Rchange	Repeat change
F19	Up	Up (Scroll up)
F20	Down	Down (Scroll down)
F21	Swap	Swap
F22	Left	Left (Scroll left)
F23	Right	Right (Scroll right)
F24	Cretriev	Cursor/retrieve

Changing workplace settings

Figure 241 on page 432 shows the pop-up prompt window that appears when you choose the Workplace Settings pull-down from the Options choice on the Workplace action bar. You can also start this function by entering `WPSET` on the command line. The workplace settings determine how your particular workplace behaves for various functions.

```
 File  Defaults  Colors  Workstation  Help
 ------------------------------------------------------------------------
                      ISPF Workplace Settings Main

 General Options                                 View Options
   Enter "/" to select option                      Data Set List View
   /  Display Edit/View entry panel                1  1. Volume
   /  Automatically Update reference lists            2. Space
   /  Keep member field value                         3. Attrib
   /  Member List for M,C,D,G actions                 4. Total
   /  Show status for M,C,D,G actions
   /  Confirm Member delete                        Member List View
   /  Confirm Data Set delete                      1  1. Standard
   /  Show Workplace Action bar                       2. Extended
   /  Frame ISPF Personal list area
   /  Smart Action Retrieve Entry                  Reflist Frame Char
   /  Display Catalog Name                         1  1. | (X"6A")
   /  Display Total Tracks                            2. | (X"4F")

Press EXIT to save settings. Press CANCEL to cancel any changes.
 F1=Help       F2=Split      F3=Exit       F7=Backward   F8=Forward
 F9=Swap      F10=Actions   F12=Cancel
```

Figure 241. Workplace Settings panel (ISRUSETM)

You can set these items from this window:

Display Edit/View entry panel
When selected, causes the Edit/View prompt panel to appear before you can start an edit or view action for a sequential data set. If you want to display a member list, the prompt panel is only displayed if a slash (/) is entered in the Prompt field of the member list.

The default for this setting is *selected*.

Automatically Update reference lists
When selected, specifies that any data set or library, or both, is added to the respective reference list.

The default for this setting is *selected*.

Keep member field value
When selected, specifies that the member name field for ISPF Library is not to be cleared upon return from a library action.

The default for this setting is *selected*.

Member List for M,C,D,G actions
When selected, specifies that the actions Move, Copy, Delete, and Reset result in a member list. When not selected, these actions act upon all members that match the pattern without displaying a member list.

The default for this setting is *selected*.

Show status for M,C,D,G actions
When selected, displays a status panel for the actions Move, Copy, Delete, and Reset. When not selected, no status panel is displayed.

The default for this setting is *selected*.

Confirm Member delete
When selected, specifies that the delete confirmation panel is displayed before a member is deleted.

The default for this setting is *selected*.

Confirm Data Set delete
When selected, specifies that the delete confirmation panel is displayed before a data set is deleted.

The default for this setting is *selected*.

Show Workplace Action bar
When selected, specifies that the action bar appears on the workplace panels.

The default for this setting is *selected*.

Frame ISPF Referral list area
When selected, specifies that the ISPF referral list area be framed, using the character specified in the Reflist Frame Char field.

Smart Action Retrieve Entry
When selected, specifies that ISPF executes the smart action option against the retrieved data set.

Display Catalog Name
When selected, specifies that the Total view of a Data Set List displays the catalog name in which the data set was located.

Display Total Tracks
When selected, specifies that a Total Tracks header line is displayed on the dataset list above the column headings for the Space and Total view.

View Options
Specifies how to display the data set list.

volume
Displays data set list with a volume view.

space Displays data set list with a space view.

attrib Displays data set list with an attribute view.

total Displays data set list in total view.

Member List View
Specifies how to display the member list

standard
Displays a member list with a 1-character command entry field.

extended
Displays a member list with an 8-character command entry field.

Reflist Frame Char
The character used to frame the ISPF referral list area on your workstation panels.

Workplace Settings panel action bar

These action bar choices appear on the Workplace Settings panel:

File The file pull-downs give you the options to either cancel or exit the current file.

Defaults
You can choose the default enter or open actions from these pull- downs:

Default Enter action

You can select a default action to perform automatically whenever you do an Enter action. The available actions are:

- Smart Action

  The Smart Action enables ISPF to choose the action needed based on the characteristics of the object you are using. ISPF chooses the appropriate action according to these rules:

Object type	Action selected by ISPF
ISPF Library	Member list
Partitioned Data Set	Member list
Pattern containing "*" or "%"	Data Set List
Volume (with no object name)	Data Set List
Member Object	User selectable *
Sequential Data Set	User selectable *
Workstation File	User selectable *

  * Use the Smart Action action bar choice to select the action for member objects, sequential data sets and workstation files.
- Member List
- Data Set List
- Edit
- View
- Browse
- Rename member
- Move
- Copy
- Reset Stats
- Open
- Repeat action

Default Open action

You can select a default action to perform automatically whenever you do an Open action from the Workplace or workplace member lists. The available actions are:

- User command (a user defined command)
- Edit
- View
- Browse
- Delete member
- Rename member
- Move
- Copy
- Reset member
- Print member
- WS Cmd
- TSO Cmd

Colors You can choose the colors for the member list or the data set list from this action bar.

Workstation

You can connect your host and workstation with these choices:

1. Configure ISPF Workstation Tool Integration
2. ISPF C/S Install

Help Provides general workplace settings help, and default enter and open help.

Workplace example scenario

The scenario here illustrates some of the advantages provided by the ISPF Workplace function. To provide you with a reference point of view, the scenario includes points on how you can accomplish the same task using ISPF in the traditional way.

For this example, say that your task is to:

1. Copy a sequential data set into a member of a concatenated ISPF Library.
2. SuperC compare it to another member.
3. Rename the member.
4. Change the Version number in the ISPF statistics.

Subtask 1

Your first step is to copy a sequential data set into a member of a concatenated PDS.

Traditional ISPF: Use the 3.3 Move/Copy Utility.

Workplace: Use the Copy Action against the sequential data set object.

Choose the Workplace option (Option 11) on the main menu. Use the PF11 key to toggle to the data set view. In the Workplace you have a choice of working from a data set list or issuing commands against a single data set.

If you are list-oriented you can specify a wildcard character in the Object Name field (such as, 'USERID.*') to generate a data set list containing the sequential data set.

If you prefer to specify the sequential data set directly you can type it into the Object Name field either with or without single quotes (that is, SEQ.FILE or 'USERID.SEQ.FILE').

In either case these accelerated methods can be alternatives to remembering and typing the input:

- You might be able to retrieve a recently referenced data set name or pattern from the REFLIST in the bottom half of the Workplace.
- You might be able to retrieve a recently referenced data set name or pattern using the recall key PF5.
- You might be able to retrieve a data set name or pattern from a personal list you previously created. These also appear in the bottom half of the Workplace.

Now that the Object has been specified you must specify the Action. In this example, the action is COPY. You can do this several ways, depending on your preferences.

- If you are in a list, you can use the CO line command to copy the data set, or you can put a slash (/) in the line command field to be prompted with a list of available commands to select.
- If you specified the "from" data set directly (not from a list) you can use the Copy option from the File action bar choice, or you can type the `C` fast path command in the Action ==> field to copy the data set.

In either case, a pop-up panel prompts you for the target data set, member name, and other parameters.

Subtask 2

The second step is to SuperC compare one member of a concatenated PDS to another.

Traditional ISPF: Use the 3.13 SuperC compare utility.

Workplace: Use the Workplace-to-SuperC Interface.

Using PF11, toggle back to the Workplace ISPF Library View.

Specify the ISPF library concatenation and member name of the new member you just created by the COPY action. These accelerated methods can be used as alternatives to remembering and typing the input:

- You might be able to retrieve a recently referenced ISPF Library concatenation from the REFLIST in the bottom half of the Workplace.
- You might be able to retrieve a recently referenced ISPF Library concatenation using the recall key PF5.
- You might be able to retrieve an ISPF Library concatenation from a personal list you previously created. These also appear in the bottom half of the Workplace.

Now that the Object has been specified you must specify the Action. The action at this point is SuperCE. Again, specifying this action can be done several ways depending on your preferences.

- You can use the SuperCE option from the SuperC action bar.
- You can type the ″SCE″ fast path command in the Action ==> field and press Enter.

In either case, Workplace enters the SuperCE dialog. Note that your ISPF Library concatenation is transferred to the correct New DSN fields in the SuperCE concatenation panel, so you do not have to type it yourself.

After running your compare, exit the SuperC Utility to return to Workplace.

Subtask 3

The next step is to rename a member of an ISPF Library.

Traditional ISPF: Use the 3.1 Library Utility.

Workplace: Use the Rename member Action.

The ISPF library concatenation and member name of the new member you just compared remains on the Workplace panel. Now you must specify the Rename Action.

How do you prefer to do this?

- You can use the Rename option from the File action bar.
- You can type the ″R″ fast path command in the Action ==> field, then press Enter.
- You can work from a member list and issue the ″R″ line command to rename the member.

Member lists can be created a number of ways in Workplace:

- Just press Enter if your default enter action is Smart Action, a mode that analyzes the object and selects an appropriate action. Select the Workplace Settings option from the Options action bar to view or change your defaults.
- Enter the List option from the File action bar.
- Enter the ″ML″ fast path command.

In any case, Workplace displays a pop-up panel to prompt you for the new member name.

Subtask 4

The final step in this scenario is to change a member's Version number in the ISPF statistics.

Traditional ISPF: Use the 3.5 Reset Statistics Utility.

Workplace: Use the Reset Action.

The ISPF library concatenation and member name of the new member you just compared remains on the Workplace panel. Now you must specify the Reset Action.

Again you have a choice about how to do this:

- You can use the Reset option from the File action bar.
- You can type the ″G″ fast path command in the Action ==> field and press Enter.
- You can work from a member list and issue the ″G″ line command to rename the member or specify the ″/″ line command to be prompted with an action selection list.

In all cases, Workplace displays a pop-up panel to prompt you for Reset parameters.

Appendix A. SuperC reference

This topic provides information about the SuperC return codes, process options, update data set control options, and process statements.

ISPF contains two utilities, SuperC (option 3.12) and SuperCE (option 3.13), that allow you to compare data sets for differences. Also, ISPF contains two other utilities, Search-For (option 3.14) and Search-ForE (option 3.15), that allow you to search data sets for strings of data.

All four of these utilities combine two major components to do their respective functions. The first component is a dialog that provides the data entry panels, selection panels, and messages. The second component is the program module, ISRSUPC. The CPI interface is through a standard parameter list.

You can use the SuperC program without the ISPF utilities. To do this, however, your installation must customize a CLIST or REXX exec (for interactive use), or a PROCLIB procedure (for batch processing of a catalog procedure). A sample CLIST has been provided to show line command processing. A sample PROCLIB JCL catalog procedure has also been provided to show batch submission. The sample CLIST and PROCLIB JCL are located in the SAMPLIB data set as members ISRSCLST and ISRSPROC, respectively.

Utility differences

The standard utilities, SuperC (option 3.12) and Search-For (option 3.14), are easy to use with somewhat reduced function. The extended utilities, SuperCE (option 3.13) and Search-ForE (option 3.15), fully exploit the SuperC program's capabilities.

Standard utilities

The standard utilities are useful for ordinary comparisons and searches. The SuperC utility (option 3.12) uses a two-panel sequence: you specify the new input data set on the first panel and the old input data set on the second. The Search-For utility (option 3.14) uses an optional two-panel sequence: you can specify the input data set and one search string on the first panel, and use the second panel if you need to specify more than one search string.

You can enter additional information on these panels as they are displayed. If you are using the SuperC utility, you can enter the name of a previously prepared profile data set that contains additional information to specify the comparison.

Search-For does not use a profile data set. Also, Search-For finds all occurrences without case distinction when searching for a data string.

Extended utilities

The primary intent of the extended utilities is to provide maximum flexibility and access to all SuperC functions. Input fields are provided to allow you to use process options and statements. Also, the Search-ForE utility's ASIS fields allow you to specify mixed-case search strings.

The input data set name fields differ from standard ISPF format because Project, Group, Type, and Member fields are not provided. Instead, you can enter input

© Copyright IBM Corp. 1980, 2007

data set names horizontally using standard TSO naming conventions. This includes the use of a PDS member name, if desired, as part of a data set name.

The concatenation of input data sets is also different. Up to four data set names, as opposed to the standard four ISPF library groups, can be entered as new or old data sets. This allows data sets with the same attributes to be concatenated. For example, PANELS and MSGS data sets could be concatenated for searching.

Besides compare functions, the SuperCE Utility panel provides access to the Search-ForE utility (option 3.15). This gives you the added advantage of the ability to search for a data string without having to leave SuperCE, in addition to access to more functions than Search-For (option 3.14) provides.

Program description

The SuperC program is a fast and versatile program that can process:
- Two sequential data sets
- Two complete partitioned data sets
- Members of two partitioned data sets
- Concatenated data sets.

In fact, any data set that can be processed by ISPF can be processed by the SuperC program.

Note: SuperC does not support tape data sets.

SuperC can compare data sets even when there are many differences and redundant data. Some examples of redundant data are blank lines, duplicate words, and binary data with many duplicate characters.

Unlike many compare programs, SuperC is not limited to comparing data sets on a line-by-line basis. Instead, it allows you to choose between the four comparison levels listed. The compare type you select determines which kinds of data differences are presented by SuperC. See “Why compare types may produce different comparison results” on page 507 for more information about comparison results.
- File comparisons produce summary information about the differences between the data sets being compared.
- Line comparisons are record-oriented and show matching, inserted, deleted, and reformatted lines. This level is most useful for comparing lines of program source code. It provides the least output difference information and is least sensitive to resynchronization.
- Word comparisons show differences between data strings that are delimited by blanks or nonalphanumeric characters, such as commas. Matching words are found, even if they are not on the same line. This level is most useful for comparing text data sets.
- Byte comparisons determine byte differences. It is most useful for comparing unformatted and machine-readable data.

The SuperC program requires only the names of the input data sets. However, the utility you are using may require other information, such as a listing type. Also, you can enter these types of processing information and options on the utility data entry panels:
- Compare type
- Listing data set name or destination

- Process options
- Statements or profile data set name
- Browse output choice.

The SuperC program allows you to create two kinds of output:
- A listing that shows the results of the comparison or search and
- A structured data set that contains update information.

Within these two categories, you can create many kinds of output that make it easy to see where your data differs. To see your comparison results, you can generate listings that show:
- An overall summary of total changes
- The actual source code where deltas (differences) were found
- The deltas plus up to 10 (the default) matching lines before and after
- The deltas plus all matching lines.

You can format the listings to show differences either sequentially or side-by-side.

In an update data set, output lines are identified and results are put in specific columns. An update data set is especially useful as input to a user-written application program. It allows a program to customize what you see, changing generalized output to information that is specific to a particular application.

The SuperC utility (options 3.12, 3.13, and 3.14) CLISTs allocate or free space under these DDNAMEs: SYSIN, SYSIN2, OLDDD, NEWDD, OUTDD, and DELDD.

SuperC features for the year 2000 transition

SuperC includes features designed to help manage the Year 2000 transition:
- Specify a 100-year period (or “year window”) so that, for dates that have only a 2-digit year, the century can be determined. This can be based on either:
  - A “fixed” year window (with a fixed starting year), or
  - A “sliding” year window (starting at a specified number of years before the current year).
- Compare 2-digit year values in one data set with 4-digit year values in another data set.
- Compare compressed year values in one data set with uncompressed year values in another data set.
- Filter cosmetic differences caused by adding century digits to 2-digit years, so that you can more easily identify real differences in content.

Applications

You can use the SuperC program for many applications other than comparing two source data sets. This topic lists some specific applications for general users, writers and editors, and programmers and systems administrators.

General users can:
- Compare two data sets that have been reformatted. Reformatted data sets contain such differences as indentation level changes, spaces inserted or deleted, or lines that have been reformatted and moved to other parts of the data set.

  SuperC detects and classifies reformatted lines as special changes. You can list these lines in the output, along with the normal insert/delete changes, or eliminate them from the listing. Reducing the number of flagged lines may help you focus on real, rather than cosmetic, changes.

- Determine whether two PDSs, or a concatenation of PDSs, have corresponding like-named members.

  Members absent from one data set but present in the other are listed, as is all change activity between like-named members. The comparison can show changes caused by creating or deleting PDS members.

Writers and editors can:

- Detect word changes within documents.

  SuperC finds word differences even if the words have moved to different lines.
- Verify that only designated areas are changed.

  SuperC comparison results show all areas affected. Changes made to restricted areas may be invalid. Therefore, unintended changes can be detected so that a complete document need not be checked for errors again.
- Create a utility that automatically inserts SCRIPT revision codes.

  You could write a program that uses Word compare to find where words in the new data set are different, makes a copy of the new data set, and then inserts SCRIPT revision codes (.RC) before and after the changed words. This utility could eliminate the need to insert SCRIPT revision codes manually.

Programmers and systems administrators can:

- Generate management reports that show the quantity and type of changes in program source code.

  SuperC can count the changed and unchanged lines of code in an application program. Therefore, comparison results could be used to summarize the changes between different versions of a program.
- Retain a record of change activity.

  Listing data sets can be collected and retained as a permanent record of the changes made before a new program is released. Source code differences can help detect regressions or validate the appropriateness of any code modifications.
- Rewrite a listing data set, including additional headers or change delimiters.

  Some SuperC listings may need to be rewritten before you accept the results. For example, some installations may require security classifications. Others may require a listing created using the WIDE process option to have box delimiters surrounding changed sections.
- Compare data sets across nonconnected systems.

  SuperC can generate a 32-bit hash sum per data set or member using the File compare type. Data sets compared on a nonconnected processor, using SuperC, should have the same hash sums if they are identical. A File comparison of any data set to determine a hash sum can be done by specifying the same data set as both new and old.
- Develop additional uses for update data sets.

  SuperC produces general results with generalized reports. However, your installation may have additional requirements. There are many specialized update formats that you can use to produce listings that match these requirements. Normal SuperC listings may not fit this type of application, but the update data sets are more structured and should be easier to use as data input. See “Update data set control output examples” on page 524 for explanations and examples of the update data sets.

SuperC compare process options

Option P on either the SuperCE Utility panel or the Search-ForE Utility panel provides one or more panels from which you can select process options. For SuperCE, the options displayed are compatible with the compare type (File, Line, Word, or Byte) that you specified in the Compare Type field. The compare type that you select determines the available process options (Table 24).

Table 24. Summary of process options for search and compare

Process Option		Valid For				
		Compare Type				
Keyword	**Description**	**FILE**	**LINE**	**WORD**	**BYTE**	**Search**
ALLMEMS	All members	✓	✓	✓	✓	✓
ANYC	Any case		✓	✓		✓
APNDLST	Append listing output	✓	✓	✓	✓	✓
APNDUPD	Append update		✓	✓	✓	✓
CKPACKL	Check for packed format		✓	✓		
CNPML [1]	Count non-paired member/file lines		✓			
COBOL [2]	For COBOL source files		✓	✓		✓
COVSUM	Conditional summary	✓	✓	✓	✓	
DLMDUP	Do not list matching duplicate lines		✓			
DLREFM	Do not list reformatted lines		✓			
DPACMT	Do not process asterisk (*) comment lines		✓	✓		✓
DPADCMT	Do not process ADA-type comments		✓	✓		✓
DPBLKCL	Do not process blank comparison lines		✓	✓		✓
DPCBCMT	Do not process COBOL-type comment lines		✓	✓		✓
DPCPCMT	Do not process C++ -type comment lines		✓	✓		✓
DPFTCMT	Do not process FORTRAN-type comment lines		✓	✓		✓
DPMACMT	Do not process PC Assembly-type comment lines		✓	✓		✓
DPPLCMT	Do not process PL/I-type comments		✓	✓		✓
DPPSCMT	Do not process Pascal-type comments		✓	✓		✓
FINDALL	Require all strings found for return code 1					✓
FMSTOP	Stop on first mismatch or first string found	✓				✓
FMVLNS	Flag moved lines		✓			
GWCBL	Generate WORD/LINE comparison change bar listing		✓	✓		
IDPFX	Identifier-prefixed listing lines					✓
LMCSFC [3]	Load Module CSECT file compare list	✓				
LMTO [4]	List group member totals					✓
LNFMTO [4]	List not-found member totals only					✓
LOCS	List only changed entries in summary	✓	✓	✓	✓	
LONGLN [5]	Long lines		✓			✓
LPSF [4]	List previous -search -following lines					✓
LTO [4]	List totals only					✓

Table 24. Summary of process options for search and compare (continued)

Process Option		Valid For				
		Compare Type				Search
Keyword	**Description**	**FILE**	**LINE**	**WORD**	**BYTE**	
MIXED	Mixed input (single-byte/double-byte) text		✓	✓		
NARROW [5]	Narrow (side-by-side) listing		✓			
NOPRTCC	No printer control columns	✓	✓	✓	✓	✓
NOSEQ [2]	No sequence numbers		✓	✓		✓
NOSUMS	No summary section		✓	✓	✓	✓
REFMOVR	Reformat override		✓			
SDUPM	Search duplicate members					✓
SEQ [2]	Ignore standard sequence number columns		✓	✓		✓
UPDCMS8 [6]	Update CMS8 format		✓			
UPDCNTL [6]	Update control		✓	✓	✓	
UPDLDEL [6]	Update long control		✓			
UPDMVS8 [6]	Update MVS8 format		✓			
UPDPDEL [6]	Update prefixed delta lines		✓			
UPDREV [6]	Update revision		✓	✓		
UPDREV2 [6]	Update revision (2)		✓	✓		
UPDSEQ0 [6]	Update sequence 0		✓			
UPDSUMO [6]	Update summary only		✓	✓	✓	
WIDE [5]	Wide (side -by -side) listing		✓			
XREF	Cross reference strings					✓
XWDCMP	Extended word comparison			✓		
Y2DTONLY [7]	Year 2000 Compare Dates Only		✓			

Notes:

1. Valid for group LINE comparisons only.
2. COBOL, SEQ, and NOSEQ are mutually exclusive.
3. Not supported for PDSE data sets.
4. LMTO, LNFMTO, LPSF, and LTO are mutually exclusive.
5. LONGLN, NARROW, and WIDE are mutually exclusive.
6. All update (UPD) process options are mutually exclusive. Also, they cannot be used with the process option Y2DTONLY.
7. Y2DTONLY is not supported for change bar listing (process option GWCBL).

Here are the SuperC Compare process options, listed alphabetically:

ALLMEMS All members. Compare all members including alias entries. This functions as though all directory entries were selected from a member list.

ANYC Any case. SuperC converts the lowercase alphabetic characters (a-z) in source data sets to uppercase (A-Z) before comparing the data sets (the actual input data sets are not modified). Use this option to cause strings such as “ABC”, “Abc”, “ABc”, ... to compare equally.

Notes:

1. ANYC has the lowest priority operation affecting the SuperC process. For example, it does not affect any of the strings used in SuperC compare process statements (except SRCHFOR).
2. The ANYC process option does not apply to characters in DBCS text strings.

See Figure 242 on page 504 for more information.

This option is valid for the Line or Word compare types.

APNDLST Append the listing output to the specified or default listing data set. If the data set does not exist, it is allocated as new. Some data sets cannot be appended because of the append listing attributes and new compare listing attribute requirements. SuperC returns an error code for this condition without adding to the output data set.

Normally, APNDLST allows you to collect listings from separate comparisons into one named listing data set (a MOD function). You can sometimes do this without using the APNDLST option by using the SELECT process statement. This allows you to identify any number of members. This produces a single composite listing of a complete or partial PDS with a single SuperC invocation.

This option is valid for all compare types.

APNDUPD Append the update output to the specified or default update data set. If the data set does not exist, it is allocated as new.

APNDUPD allows you to collect updates from multiple comparisons into one update data set. You can also do this without using the APNDUPD option by using the SELECT process statement that identifies different members and produces a single composite update data set.

This option is valid for Line, Word, or Byte Compare.

CKPACKL Check for packed format. This option determines if the member or sequential data set has the standard ISPF packed header format. If required, SuperC unpacks the input data set or member during the comparison.

This option is valid for Line and Word compare types.

CNPML Count non-paired PDS member lines for the group summary listing section. This option is useful for totaling the overall number of lines processed, “don’t process” lines, and changed lines. Otherwise, only the paired members are processed and included in the overall statistics. Members (with CNPML) always count as changes (inserted or deleted) to the total number of lines.

Only valid for a PDS group Line compare.

COBOL Ignore columns 1-6 in both F 80 data sets. Data changes in columns 1-6 are ignored.

This option is valid for the Line or Word compare types.

COVSUM Conditional summary section. List the final summary section and/or the update file for the option UPDSUMO only if there are differences. This is useful when used in combination with APNDLST or APNDUPD.

Valid for File, Line, Word, and Byte compare types.

DLMDUP Don't list matching duplicate lines. SuperC omits the old data set source lines and new data set source lines that match from the side-by-side output listing. This reduces the redundant lines in the side-by-side old data set source lines columns. It puts more emphasis on the old data set changed lines and sections of changes.

This option is valid for the Line compare type in combination with the WIDE or NARROW process option.

DLREFM Don't list old data set reformatted lines. This option omits reformatted old data set lines from the output listing. They usually appear as separate lines under new reformatted lines. Only the new reformatted lines are listed in the output.

Note: DLREFM should not be confused with two other related process options: REFMOVR and DLMDUP. REFMOVR temporarily changes the reformatted line status so that lines can be listed (or excluded) as matched lines. DLMDUP pertains only to duplicate matched lines for the Wide or Narrow listing types.

This option is valid only for the Line compare type.

DPACMT Don't process asterisk (*) comment lines. Lines with an asterisk in column 1 are excluded from the compare set. Other forms of assembler or macro comments are unaffected. SuperC does not filter out assembler comments appearing on the same line as an assembler statement or directive.

This option is valid for the Line or Word compare types.

DPADCMT Don't process ADA-type comments. ADA comments are whole or partial lines that appear after the special "--" sequence. Blank lines are also considered part of the comment set. This option produces a comparison listing with all comments removed and blanked. The DPADCMT process option does not recognize comments within DBCS text strings.

This option is valid for the Line or Word compare types.

DPBLKCL Don't process blank compare lines. Source lines in which all of the compare columns are blank are excluded from the compare set. It is redundant, but not incorrect, to use this option with DPADCMT, DPPLCMT, and DPPSCMT.

Note: The CMPCOLM process statement can be used to control the compare columns inspected. It is possible for the DPBLKCL option to exclude a line that contains nonblank data when you use the CMPCOLM statement to limit the column range of the comparison.

Do not assume that DPBLKCL only excludes complete input blank lines. For example, a blank line could have sequence numbers in columns 73-80 and you could compare the data sets with the SEQ process option.

This option is valid for the Line or Word compare types.

DPCBCMT Don't process COBOL-type comment lines. COBOL source lines with an asterisk in column 7 are excluded from the compare set.

This option is valid for the Line or Word compare types.

DPCPCMT Don't process C++ end-of-line type compiler comments. These are "//" delimited comments. DPPLCMT may also be used with DPCPCMT when the source file contains "/* ... */" comments delimiters.

Valid for LINE and WORD compare types.

DPFTCMT Don't process FORTRAN-type comment lines. FORTRAN source lines with a "C" in column 1 are excluded from the compare set.

This option is valid for the Line or Word compare types.

DPMACMT Do not process PC Assembly-type comments. Lines with an "*" in column 1 are excluded.

Valid for LINE and WORD compare types.

DPPLCMT Don't process PL/I-type comments. PL/I, C, and REXX comments (that is, /* ... */ and blank lines) are excluded from the compare set. This option produces a listing with comments removed and part comments blanked. Blank lines are defined as lines with blanks in all compare column positions.

Notes:

1. The SuperC program detects most cases including multiline, statement embedded, and most quote dependency comments. However, SuperC may exclude some lines that are not comments or include comment lines that should have been excluded. For instance, lines that contain comment delimiters enclosed within quotes appearing on separate lines are difficult to parse and may present recognition problems.
2. The DPPLCMT process option does not recognize comments within DBCS text strings.

This option is valid for the Line or Word compare types.

DPPSCMT Don't process PASCAL-type comments. PASCAL-type comments of the type "(* . . . *)" are filtered and excluded from the compare set as are blank compare lines. This option produces a comparison listing with comments removed and part comments blanked. The DPPSCMT process option does not recognize comments within DBCS text strings.

Note: Both DPPSCMT and DPPLCMT may be a required combination for filtering certain nonstandard PASCAL compiler comments. The combination is allowed. Either may start a comment but only the starting delimiters type may terminate the comment.

This option is valid for the Line or Word compare types.

FMSTOP Stop the compare on the first mismatch in the data set or PDS member. This option is valid only for a file compare.

FMVLNS Flag moved lines. Identifies inserted lines from the new data set that match deleted lines from the old data set. Inserted-moved

lines are noted with “IM-” and deleted-moved lines are noted with “DM-” in the listing. These lines are special cases of inserted or deleted paired lines.

This option is valid for the Line compare type.

GWCBL Generates Word or Line compare change bar listings. SuperC lists new data set lines with change bars (“|”) in column 1 for lines that differ between the new and old data sets. Most deleted lines are indicated by flagging the lines following the deletion (if possible).

Line compare and Word compare may give slightly different results. It is a recommended process option to use on text data sets. GWCBL allows you to see which lines have changes without the distraction of seeing deleted text lines. Blank lines in the listing should never be flagged.

This option is valid for the Line or Word compare types.

LMCSFC Load Module CSECT file compare list. This option lists the name, number of bytes, and hash sum for each PDS load module CSECT. Unchanged paired CSECTS are omitted when you specify the LOCS process option.

This option is only valid for a File compare.

LOCS List only changed entries in the MEMBER SUMMARY LISTING section. Unchanged paired entries and non-paired new and old data set entries are omitted. Preceding the names of these pairs is a CHNG field to indicate whether they compare the same or differently.

This option is valid for all compare types.

LONGLN LONGLN causes SuperC to create a listing with 203 columns, reflecting up to 176 columns from the source lines. The output data set may require special print handling as it might exceed the maximum number of columns handled unless special setup is arranged.

LONGLN and WIDE both generate wide listings. LONGLN is for the normal listing format while WIDE is for a side-by-side listing.

This option is valid for the Line compare type.

MIXED This option indicates that the input text may be a mixture of both single-byte and double-byte (DBCS) text. Double-byte strings are recognized and handled differently than if MIXED were not specified. For instance, single-byte characters are not valid within double-byte strings. Special terminals (for example, 5520) allow entry of DBCS characters.

If an input string starts with a shift-out character then MIXED removes the character from the string. If an input string ends with a shift-in character then MIXED removes the character from the string. Leading SO and trailing SI characters are not removed from strings specified on COLHEAD, NTITLE, or OTITLE process statements.

This option is valid for the Line and Word compare types.

NARROW Narrow side-by-side listing. Creates a 132/133 variable listing data

set with only 55 columns from each source data set. Inserted and deleted lines are flagged and appear side-by-side in the listing output.

This option is valid for the Line compare type.

NOPRTCC No printer control columns. SuperC generates “normal” or NARROW listing data sets with record lengths of 133 columns, or WIDE or LONGLN listing data sets with 203 columns. These listings contain printer control columns and page separators. NOPRTCC eliminates both the page separators and the control column 1. With NOPRTCC, “normal” and NARROW listings are 132 columns, and WIDE and LONGLN listings are 202 columns. However, initial title lines and section separators are still generated.

This option produces a data set that is better for online “browsing” because it does not have interspersed page separator title lines.

Note: It is possible to use a high LNCT value to achieve the same purpose as NOPRTCC. However, NOPRTCC is a process option, is easier to specify, and does not require a separate LNCT process statement in a process statement data set.

This option is valid for all compare types.

NOSEQ No sequence numbers. SuperC Processes F 80 standard sequence number columns as data. This option is extraneous for variable length records and non-F 80 attribute data sets.

This option is valid for all compare types.

NOSUMS No summary listing section. This option omits the summary section including the statistics, options, warning, and error messages from the listing output.

This option is valid for the Line, Word, and Byte compare types.

REFMOVR Reformat override. Reformatted lines are not flagged in the output listing. They are, however, counted for the overall summary statistics and influence the return code since they are a special case of an insert/delete pair.

This is an important output filter option. You may wish to accept formatted lines as changes but not want to browse a change listing with formatted lines annotated. The option is also useful when used in combination with some higher level language “don’t process” comment filter such as DPPLCMT.

This option is valid for the Line compare type.

SEQ Sequence numbers. Ignore F 80 standard sequence number columns. Sequence number column changes in columns 73-80 are ignored with F 80 and columns 1-8 in V 255 records. This is the SuperC default for F 80/V 255 data sets when the compare type is Line. It is not the default for Word compare. SEQ is not valid for any data set that does not have an attribute of F 80/V 255.

This option is valid for the Line or Word compare types.

UPDCMS8 Update CMS Sequenced 8. Produces a data set that contains both

control records and new data set source lines. Columns 73-80 from the old DS lines are used as references. Only fixed 80 data sets are allowed.

SuperC may change the status of matched lines to insert/delete pairs, enlarging the sequence number gaps of the old data set. The CMS update data set (when properly named) can be used as input to CMS XEDIT. For information and an example of this update data set, see Figure 255 on page 525.

This option is valid for the Line compare type.

UPDCNTL Update control. Produces a control data set which relates matches, inserts, deletes, reformats, and "don't process" lines (Line compare only) using relative line numbers (for Line compare), relative word positions (for Word compare), or relative byte offsets (for Byte compare) within the new and old data sets. No source or data from either input data set is included in the output data set. For information and an example of this update data set, see "UPDCNTL—update control" on page 525.

Note: UPDCNTL is the only output to directly display "don't process" line numbers and lengths from each DP (don't process) or MOVED line span. Top inserts or deletes reference line 1. Bottom inserts or deletes reference the maximum line value plus 1. Normal compare listings do not directly indicate DP lines since they have been excluded from the compare set. They may be indirectly detected because most line number reference columns (normally on the extreme right of a listing) refer to the actual line number. You may detect a "don't process" gap in the reported line number values.

This option is valid for the Byte, Line, or Word compare types.

UPDLDEL Source data set with delta changes. UPDLDEL produces a control data set that combines new source matched lines and changes from the new and old source data sets. The control lines are titled as follows:

Title	Control line
***HDR1, *HDR2, and *HDR3**	
	Header titles and data
***M-**	Matched line sequence header
***I-**	Inserted line sequence header
***I-RP**	Inserted line sequence header for replacement lines
***I-RF**	Inserted line sequence header for reformatted lines
***D-**	Deleted line sequence header
***D-RP**	Deleted line sequence header for replacement lines
***D-RF**	Deleted line sequence header for reformatted lines.

Header control records delimit the copied data set lines. This allows you to quickly find changed areas. The lines are full length records. The lines appear similar to the information on a LONG listing. The two input data sets must have the same fixed LRECL or each have a variable RECFM.

You should be able to edit this data set to obtain a final composite source data set including all the change activity of two different

developers. For information and an example of this update data set, see "UPDLDEL—update long source and delta data set" on page 529.

This option is valid for the Line compare type.

UPDPDEL Update prefixed delta lines. This option produces a control data set containing header records and complete (up to 32K line length limit) delta lines from the input source data sets. Each output record is prefixed with identification and information. The update data set is a variable-length data set reflecting the input source data set characteristics. For information and an example of this update data set, see "UPDPDEL—prefixed delta lines" on page 530.

This option is valid for the Line compare type.

UPDMVS8 Update MVS Sequenced 8. Produces a data set that contains both control and new data set source lines. New data set sequence numbers columns 73-80 are used (when possible) as insert references while deletes are from old line columns 73-80. The format is compatible for MVS IEBUPDTE input. Only fixed 80 DS are allowed. For information and an example of this update data set, see Figure 259 on page 529.

This option is valid for the Line compare type.

UPDREV Update Revision. UPDREV produces a copy of the *new* data set with SCRIPT/VS *.rc on/off* or BookMaster® *:rev/:erev* revision codes delimiting most script lines that contain changes.

You may wish to contrast the source lines delimited by the UPDREV option and a similar flagging of the lines with changes from the output listing data set as produced by the GWCBL process.

Note: The revision character used is controlled by using the REVREF process statement. For details, see "REVREF—Revision Code Reference" on page 478.

A REVREF process statement (for example, `REVREF REFID=ABC` or `REVREF RCVAL=1`) is used to define the revision level (SCRIPT/VS tags) or reference ID (BookMaster tags). Alternatively, SCRIPT/VS .rc delimiters may be controlled by the first record in the *new* data set. (For example, `.rc 2 |` as the first record causes level 2 to be used).

Note: BookMaster requires the REFID value to be defined with a *:revision* tag and "RUN=YES" attribute to have the change character inserted in the processed document.

For information and an example of this update data set, see "UPDREV—update revision" on page 531.

Valid for LINE and WORD compare types.

UPDREV2 Update Revision (2). UPDREV2 is identical to UPDREV with the exception that data between these BookMaster tags are not deleted in the update data set:

```
:cgraphic.
:ecgraphic.
:fig.
```

```
:efig.
:lblbox.
:elblbox.
:nt.
:ent.
:screen.
:escreen.
:xmp.
:exmp.
```

Valid for Line and Word compare types.

UPDSEQ0 Update data set using no column number (zero) references. UPDSEQ0 produces a control data set that relates inserts and deletes to the relative line numbers of the old data set. Both control records and new data set source lines are included in the output data set. This option is similar to UPDCMS8 except it uses relative line numbers (starting with zero) instead of sequence numbers from columns 73-80. Both fixed and variable record length lines are allowed. Fixed LRECL < 80 are padded to 80 characters. Insert lines are full fixed- or variable-length copies of the new input data set lines. Fixed-length record data sets with an LRECL <=80 produce a fixed-length data set with the same record length. For information and an example of this update data set, see Figure 264 on page 533.

This option is valid for the Line compare type.

UPDSUMO Update Summary only. UPDSUMO produces an Update data set of four lines (New-dataset-id, Old-dataset-id, totals header, single summary line). The summary line is tagged with a "T" in column 1 and the summary statistics are located at fixed offsets in the output line. The data set has an LRECL of 132. For information and an example of this update data set, see "UPDSUMO—update summary only" on page 534.

This option is valid for the Line, Word, or Byte compare types.

WIDE Wide side-by-side listing. Creates a 202/203 listing data set with up to 80 columns from each source data set line. Inserted and deleted lines are flagged and appear side-by-side in the listing output.

This option is valid for the Line compare type.

XWDCMP Extended Word compare. The "word" character set contains all letters, numbers and the national characters ("$", "#", and "@"). SuperC interprets all other characters as word delimiters. For example:

" ABCD(EFGH) JKL "

would be two words using normal word compare, but five (three words and two delimiters) with the XWDCMP process option. Consecutive delimiters are interpreted as part of the same pseudo-word.

This option is valid for the Word compare type.

Y2DTONLY Year 2000 Compare Dates Only. Indicates that the comparison process is to be performed only on the dates defined by the Year 2000 Date Definition process statements. That is, all data in the input files will be ignored in the comparison process apart from

that defined by NY2C, NY2Z, NY2D, NY2P, OY2C, OY2Z, OY2D, and OY2P process statements. For further details on these process statements, see "NY2C, NY2Z, NY2D, NY2P, OY2C, OY2Z, OY2D, OY2P —Year 2000 Date Definitions" on page 475.

Notes:

1. Y2DTONLY causes a "record-for-record" comparison to be performed between the two input files, whereby dates are simply checked for being equal or unequal. (The "high/low" comparison logic that SuperC normally uses is not applied in the case of Y2DTONLY and, as such, the relative *values* of the dates have no bearing on the result of the comparison.)
2. Y2DTONLY is not supported for the process option GWCBL (change bar listing).

Valid for LINE compare type.

SuperC compare process statements

This topic lists the process statements in alphabetical order, showing their syntax, operand definitions, and examples. All process statements that are shown with a Compare syntax can be:

- Used in a profile data set with the SuperC utility (option 3.12).
- Entered in a statements data set with the SuperCE utility (option 3.13).

All process statements that are shown with a Search syntax can be entered in a statements data set and used with the Search-ForE utility (option 3.15), but not with the Search-For utility (option 3.14).

Each process statement description contains:

Description A description of function and operation of the statement. This description may also refer to other statements that can be used with or affected by this statement.

Examples Sample usage of the statements.

Syntax Diagrams for coding the statement, using either Compare syntax, Search syntax, or both if applicable, according to the conventions listed in "Process statement notation conventions."

Operands A description of any required or optional keywords or operands.

Process statement notation conventions

This topic uses these notation conventions to describe the syntax of the process statements:

- Process statements and keywords are shown in uppercase to help you differentiate between them and their operands, which are shown in lowercase. However, you can enter them in any case you like.
- Operands shown in brackets ([ ]) are optional.
- Stacked operands shown in brackets indicate the optional operands from which you can select one or none.
- Stacked operands shown in braces ({ }) are required operands from which you must select one.
- Syntax diagrams that end with an ellipsis (...) allow you to repeat operands more than once.

- If a statement contains a KYWD operand, this keyword must precede any repetition of the operands that follow.

The compare type that you select determines the process statements available (Table 25).

Table 25. Summary of process statements for compare and search

Process Statement		Valid For				
		Compare Type				
Keyword	**Description**	**FILE**	**LINE**	**WORD**	**BYTE**	**Search**
CHNGV	Change listing value		✓	✓	✓	
CMPBOFS	Compare byte offsets				✓	
CMPCOLM	Compare (search) columns: new, old, search files		✓	✓		✓
CMPCOLMN	Compare columns: new file		✓	✓		
CMPCOLMO	Compare columns: old file		✓	✓		
CMPLINE	Compare lines		✓	✓		✓
CMPSECT	Compare sections		✓	✓		
COLHEAD [1]	Define column headings		✓			
DPLINE	Do not process lines (containing a string)		✓	✓		✓
DPLINEC	Do not process lines—continuation		✓	✓		✓
LNCT	Line count	✓	✓	✓	✓	✓
LPSFV	List previous -search -following value					✓
LSTCOLM	List columns		✓			✓
NCHGT	Change text: new or search file		✓	✓		✓
NEXCLUDE [2]	Exclude data: new file	✓	✓			
NFOCUS [2]	Focus on data: new file	✓	✓			
NTITLE	Alternative listing title: new file	✓	✓	✓	✓	✓
NY2AGE	Year 2000 aging option: new file		✓			
NY2C	Year 2000 date definition: new file, character format		✓			
NY2Z	Year 2000 date definition: new file, zoned decimal format		✓			
NY2D	Year 2000 date definition: new file, unsigned packed decimal format		✓			
NY2P	Year 2000 date definition: new file, packed decimal format		✓			
OCHGT	Change text: old file		✓	✓		
OEXCLUDE [2]	Exclude data: old file	✓	✓			
OFOCUS [2]	Focus on data: old file	✓	✓			
OTITLE	Alternative listing title: old file	✓	✓	✓	✓	
OY2AGE	Year 2000 aging option: old file		✓			
OY2C	Year 2000 date definition: old file, character format		✓			
OY2Z	Year 2000 date definition: old file, zoned decimal format		✓			

Table 25. Summary of process statements for compare and search (continued)

Process Statement		Valid For				
		Compare Type				Search
Keyword	**Description**	**FILE**	**LINE**	**WORD**	**BYTE**	
OY2D	Year 2000 date definition: old file, unsigned packed decimal format		✓			
OY2P	Year 2000 date definition: old file, packed decimal format		✓			
REVREF	Revision code reference		✓	✓		
SELECT	Select PDS members (MVS)	✓	✓	✓	✓	✓
SLIST	Statements listing option	✓	✓	✓	✓	✓
SRCHFOR	Search for a string					✓
SRCHFORC	Search for a string—continuation					✓
Y2PAST	Year 2000 global date option		✓			
*	Process Statement comment to be printed	✓	✓	✓	✓	✓
.*	Process Statement comment not to be printed	✓	✓	✓	✓	✓

Note:
1. Valid only for listing types DELTA and LONG.
2. FILE compare type is valid only with ROWS option of NEXCLUDE, OEXCLUDE, NFOCUS and OFOCUS.

You must include these statements in an input control data set. The process statements data set can be fixed or variable, and its record length can be large, but you must enter process statements only in columns 1 through 72. Only one process statement can be entered per line. SuperC checks process statements and required operands for completeness before beginning a comparison. Comments are not allowed at the end of the line after the statement has been completed. Comment lines should be separate statements. Some statements cause an error message if comments are included on the same line.

You can enter some process statements several times in the statements data set (DPLINE or CMPLINE) as they define independent actions to be taken in the comparison. Others redefine their process scope after their first inclusion (LNCT). Including more than one redefining statement is not recommended but is not reported as an error. There is also no specific rule concerning which statement definition (or re-definition) prevails—the first (least often) or last (most often).

Note: It is best to retain and inactivate old process statements rather than deleting them from the statement data set. This can be easily done by putting a period and an asterisk (.*) in the first two character positions. These statements are ignored and not listed by the SuperC program when the data set is used as a statement data set.

The SuperC Compare Process Statements are listed alphabetically.

CHNGV - CHNG (Compare Type) Line Value

Specifies the maximum number of match lines to precede or follow changed lines in the output listing. This process statement has no formatting effect if you do not use the CHNG listing type. The default value is 10.

Compare Types: Line, Word, and Byte

Examples

`CHNGV 5`	SuperC includes up to 5 match lines before and after a changed line in the output listing.

Syntax

```
CHNGV num
```

Operand Description

num A decimal number between 1 and 1000.

CMPBOFS - Compare Byte Offsets

Compares a data set between byte limits. The start/stop reference values must be hexadecimal values without quotes. Zero (0) is the lowest hexadecimal offset value that you can specify. The statement may be specified on one complete line or may have separate CMPBOFS statements enabling the limits to be fully specified within the 72-character statement line. There are keyword operands: TOP, BTM, NTOP, NBTM, OTOP, and OBTM.

Compare Types: Byte

Examples

`CMPBOFS NTOP 1000 OTOP 5E00`	SuperC interprets the two CMPBOFS statement sequences as compare from hex offset 1000 to the last byte of the new data set and from hex offset 5E00 to the last byte of the old data set.
`CMPBOFS NTOP 1000 CMPBOFS OTOP 5E00`	Performs the same function as the statement in the previous example but it is specified as two separate statements.

Syntax

```
CMPBOFS KYWD  hex-offset [ ...]
```

Operand Description

KYWD

The keyword may be one of these:

TOP New Top and Old Top specification. Defines the byte offset (zero based) to start the Byte compare for both data sets or members.

BTM New Bottom and Old Bottom specification. Defines the byte offset (zero based) to end the Byte compare for both data sets or members. This value may be greater than the data set size but the omission of the BTM specification accomplishes the same objective.

NTOP New Top. Defines the byte offset (zero based) to start the Byte compare for the new data set or member.

OTOP Old Top. Same as NTOP but refers to the old data set or member.

NBTM
New Bottom. Defines the last byte position to end the Byte compare in the new data set or members.

OBTM
Old Bottom. Same as NBTM but refers to the old data set or member.

Hex offset

A hexadecimal value without quotes. Maximum size: 8 hexadecimal digits.

Note: If you do not specify “TOP”, “NTOP”, or “OTOP”, SuperC defaults to the top of the data set. If you do not specify “BTM”, “NBTM”, or “OBTM”, SuperC defaults to the last byte of the data set.

CMPCOLM, CMPCOLMN, CMPCOLMO - Compare Columns

CMPCOLM Applies to the columns in both the new (or search) data set and old data set

CMPCOLMN Applies to the columns only in the new data set

CMPCOLMO Applies to the columns only in the old data set.

SuperC compares the data from the columns of the input data set. Up to 15 compare ranges/individual-columns are allowed and may be entered on additional CMPCOLM, CMPCOLMN, or CMPCOLMO statements. The column values and ranges must be in ascending order.

Notes:

1. Some process options (SEQ, NOSEQ, and COBOL) also define CMPCOLMS. The CMPCOLMS statement overrides all of these options.
2. CMPCOLM, CMPCOLMN and CMPCOLMO cannot be used for WORD compare type or Search if the input contains a mixture of DBCS and non-DBCS data.
3. CMPCOLM, CMPCOLMN and CMPCOLMO cannot be used when using FOCUS COLS or EXCLUDE COLS.
4. Do not use the CMPCOLM, CMPCOLMN and CMPCOLMO process statements if the Y2DTONLY process option has been specified.

Compare Types — Line and Word

Examples

`CMPCOLM 25:75`	Compares columns 25 through 75 in both data sets.
`CMPCOLM 30:60,75`	Compares columns 30 through 60 and column 75 in both data sets.
`CMPCOLM 30:60 75`	Performs the same function as the previous example. Notice that the comma and space are equivalent.
`CMPCOLMN 1:72 CMPCOLMO 9:80`	Compare different columns from each data set.

Syntax

```
CMPCOLM  start-colm[:stop-colm][,...]

CMPCOLMN start-colm[:stop-colm][,...]

CMPCOLMO start-colm[:stop-colm][,...]
```

Operand Description

start-colm A number that identifies the column in which SuperC begins the comparison.

stop-colm A number that identifies the column in which SuperC ends the comparison. This number is separated from the start-colm value by a colon (:).

CMPLINE - Compare Lines

Compares two data sets between line limits. The reference values may be line numbers or data patterns. The statement may be specified on one complete line or may have separate CMPLINE statements for each of the keyword operands: TOP, BTM, NTOP, NBTM, OTOP, and OBTM.

Compare Types — Line and Word

Examples

`CMPLINE  TOP 55 BTM 99`	Compares lines 55 through 99 in both data sets.
`CMPLINE  NTOP 55 NBTM 99`	Limits the comparison to lines 55 through 99 in the new data set.
`CMPLINE  NTOP 'ABCD',5:66`	Starts the comparison when the first ″ABCD″ is detected in columns 5 through 69.
`CMPLINE  OTOP 'ABCD'`	Starts the comparison when SuperC detects the first “ABCD” in any column of the old data set.

Syntax

```
CMPLINE KYWD {rel-line-#                        }[ ...]
       {,'string'[,start-colm[:stop-colm]]}
```

Operand Description

KYWD

The keyword may be one of these:

TOP New and Old Top. Defines the beginning line in both data sets or members.

BTM New and Old Bottom. Defines the ending line in both data sets or members.

NTOP New Top. Defines the beginning line in the new data set.

NBTM
New Bottom. Defines the ending line in the new data set.

OTOP Old Top. Defines the beginning line in the old data set.

OBTM
Old Bottom. Defines the ending line in the old data set.

rel-line-#

The relative number of the record in the data set or member. Valid range = 1 to 999999.

string Character string enclosed within single quotes. For embedded single quotes, use two consecutive quotes (''). For example, enter `'don''t'` for the string “don’t”.

start-colm

A number that identifies the column in which SuperC begins its search for *string*. All columns to the left of this column are ignored.

stop-colm

A number that identifies the column in which SuperC ends its search for *string*, but only for that record. If the data set contains more records, the search continues with the next record, beginning with the column specified as the start-colm.

This number is separated from the start-colm value by a colon (:). All columns to the right of this column are ignored. If the colon and stop-colm are not entered, only the start-colm value is used. For example, if you specify `'ABCD'` as a string that must exist between columns 5 and 69, the

search really includes columns 5 to 72. Therefore, the string can be found even if the first character is in column 69, with the others in columns 70, 71, and 72.

Notes:

1. If SuperC does not find the “top” condition you specify (for example, a pattern is incorrect), the compare continues but usually reports zero lines processed for this data set.
2. If you do not specify “TOP”, “NTOP”, or “OTOP”, SuperC defaults to the top of the data set. If you do not specify “BTM”, “NBTM”, or “OBTM”, SuperC defaults to the end of the data set.

CMPSECT - Compare Sections

Compares multiple sections from one sequential or PDS member to another sequential or PDS member. It is not valid for a PDS group compare of more than one member. It is functionally similar to CMPLINE but requires a section ID name to associate all keyword operands to a particular compare section.

Compare Types — Line and Word

Examples

`CMPSECT SECT01 TOP 25 BTM 50`	Compares lines 25 through 50 in both data sets or members.
`CMPSECT SECT02 NTOP 60 NBTM 70 CMPSECT SECT02 OTOP 65 OBTM 75`	Compares lines 60 through 70 in the new data set to lines 65 through 75 in the old data set.
`CMPSECT SECTX TOP 'PART1:',2:10 CMPSECT SECTX BTM 'END PART1:',2:10`	Starts the comparison of both data sets when SuperC detects the string “PART1:” in columns 2 through 10 and ends the comparison when SuperC detects the string “END PART1:” in columns 2 through 10.
`CMPSECT SECTY NTOP 'PART2:',2:10 CMPSECT SECTY OTOP 'PART2:',6:20 CMPSECT SECTY BTM 'END PART2:',2:10`	Compares a section in the new data set to a section in the old data set. The section in the new data set begins with the string “PART2:” in columns 2 through 10 and ends with the string “END PART2:” in columns 2 through 10. The section in the old data set begins with the string “PART2:” in columns 6 through 20 and ends with the string “END PART2:” in columns 2 through 10.

Note: All of the previous statements could be combined to compare multiple sections of the new and old data sets.

Syntax

```
CMPSECT KYWD {section-id            }[...           ]
       {,'string'[,start-colm[:stop-colm]]}[...]
```

Operand Description

KYWD

The keyword may be one of these:

TOP New and Old Top. Defines the beginning line in both compare sections.

BTM New and Old Bottom. Defines the ending line in both compare sections.

NTOP New Top. Defines the beginning line in the new compare section.

NBTM
New Bottom. Defines the ending line in the new compare section.

OTOP Old Top. Defines the beginning line in the old compare section.

OBTM
Old Bottom. Defines the ending line in the old compare section.

section-id

The relative number of the record in the data set or member. Valid range = 1 to 999999.

string Character string enclosed within single quotes. For embedded single quotes, use two consecutive quotes (''). For example, enter `'don''t'` for the string “don’t”.

start-colm
A number that identifies the column in which SuperC begins its search for *string*. All columns to the left of this column are ignored.

stop-colm
A number that identifies the column in which SuperC ends its search for *string*, but only for that record. If the data set contains more records, the search continues with the next record, beginning with the column specified as the start-colm.

This number is separated from the start-colm value by a colon (:). All columns to the right of this column are ignored. If the colon and stop-colm are not entered, only the start-colm value is used. For example, if you specify `'ABCD'` as a string that must exist between columns 5 and 69, the search really includes columns 5 to 72. Therefore, the string can be found even if the first character is in column 69, with the others in columns 70, 71, and 72.

Note: If a "top" condition is not found (for example, a pattern is incorrect), the compare continues but will usually report zero lines processed for this data set.

COLHEAD—Define Column Headings

Defines column headings and specifies the location and format of the corresponding data to be displayed. For an example of a listing with column headings, see Figure 248 on page 515.

Note: COLHEAD is not available for side-by-side listings. (See "Side-by-side listings" on page 520).

Compare Types

LINE only.

Syntax

```
COLHEAD heading1, heading2, start-print-column:end-print-column,
        N start-column:end-column data-format-indicator,
        O start-column:end-column data-format-indicator
```

Operand Description

heading1 — The heading to appear on the first line for the print column.

heading2 — The heading to appear on the second line for the print column.

start-print-column — The starting print column for the heading specified.

end-print-column — The ending print column for the heading specified. (Must be separated from the *start-print-column* by a colon.)

Note: If the print-column range is shorter than the heading specified, the heading will be truncated.

N — Indicates the operands following relate to the *new* data set.

start-column — The starting position in the *new* data set of the data to be displayed.

end-column — The ending position in the *new* data set of the data to be displayed. (Must be separated from the *start-column* by a colon.)

Data Format Indicator — The format of the data in the *new* data set to be displayed:

- **C** Character
- **B** Binary
- **D** Unsigned packed decimal
- **P** Packed decimal
- **Z** Zoned decimal

O — Indicates the operands following relate to the *old* data set.

start-column — The starting position in the *old* data set of the data to be displayed.

end-column — The ending position in the *old* data set of the data to be displayed. (Must be separated from the *start-column* by a colon.)

Data Format Indicator The format of the data in the *old* data set to be displayed (as for the *new* data set).

Examples

`COLHEAD 'START','DATE',1:7,N 1:6 P,O 11:16` Defines a print column with a heading of "START" in the first line and "DATE" in the second heading line, headings to start in print column 1. The data to be displayed from the new data set is in positions 1 through 6 and is in packed format. The data to be displayed from the old data set is in positions 11 through 16 and is in (the default) character format.

DPLINE, DPLINEC - Don't Process Lines

DPLINE Don't Process Lines
DPLINEC Don't Process Lines Continuation Condition.

The Don't Process Line statement removes from the compare set lines that can be recognized by either a unique character string or a combination of related strings. DPLINEC is the continuation of the immediately preceding DPLINE or DPLINEC process statement. All the strings in a DPLINE/DPLINEC sequence must be found on the same input line for the line to be excluded.

A start-column or range can also be used to restrict the columns scanned. Relative start-columns and relative stop-columns are valid only on DPLINEC statements. This allows you to specify a relative start position depending on the end of the previous DPLINE/DPLINEC in the sequence relationship. Normal scanning starts at the beginning of the input line (resulting in the first found string) unless restricted by user column specifications or the relative operator.

Notes:

1. DPLINE and DPLINEC columns are not restricted by compare columns. The data patterns are also not affected by the ANYC process option. See Figure 242 on page 504 for more information.
2. The relative start operator "+" introduces another important capability of backtrack and retry by advancing the starting scan position. Backtrack allows you to identify a string through a sequence of DPLINE/DPLINEC statements and have a number of similar strings (all on the same line) be examined until the correct sequence is found. This contrasts to the "first found" DPLINE/DPLINEC string and a non-relative DPLINEC rejection when the DPLINEC condition is not met.

Compare Types — Line and Word

Examples

`DPLINE 'ABCDE' DPLINE 'ABCDE',1:99999`	Each of these two statements exclude lines containing the string "ABCDE" from the compare set.
`DPLINE 'AbCde',2 DPLINE 'AbCde',2:2`	Each of these two statements exclude lines where the string "ABCDE" starts in column 2.
`DPLINE 'ABCDE' DPLINEC 'BDEF '`	Both statements exclude lines that contain the strings "ABCDE" and "BDEF ".
`DPLINE 'ABCDE',2:50`	Excludes lines where the string "ABCDE" starts in columns 2 through 50.
`DPLINE 'AB'CD',2:50`	Excludes lines where the string "AB'CDE" starts in columns 2 through 50.
`DPLINE X'C1C27BF1',2:50`	Excludes lines where the string "AB,1" starts in columns 2 through 50.
`DPLINE 'ABC' DPLINEC 'BDEF',+`	Exclude lines containing the string "ABC" followed in the same line by the string "BDEF".
`DPLINE 'ABC's DPLINEC 'BDEF',+5`	Exclude lines containing the string "ABC" and "BDEF" when the string "BDEF" starts in the same line 5 columns after the end of the string "ABC".

Syntax

```
DPLINE  'string'[,start-colm[:stop-colm]]

DPLINEC 'string'[,start-colm[:stop-colm]]
    [,+start-colm[:+stop-colm]]
    [,+]
```

Operand Description

string
Character string enclosed within single quotes. For embedded single quotes, use two consecutive quotes (').

start-colm
A number that identifies the column in which SuperC begins its search for *string*. All columns to the left of this column are ignored.

stop-colm
A number that identifies the column in which SuperC ends its search for *string*, but only for that record. If the data set contains more records, the search continues with the next record, beginning with the column specified as the start-colm.

This number is separated from the start-colm value by a colon (:). All columns to the right of this column are ignored. If the colon and stop-colm are not entered, only the start-colm value is used. This causes a search of a single column for the first character of *string*.

All columns to the right of the column that the last character of *string* can occupy are ignored. For example, if you specify `'ABCD'` as a string that must exist between columns 5 and 69, the search really includes columns 5 to 72. Therefore, the string can be found even if the first character is in column 69, with the others in columns 70, 71, and 72.

+start-colm
The relative column following the end of the previous "Don't process" string in which this *string* must start.

+stop-colm
The relative column following the end of the previous "Don't process" string in which SuperC ends the search for *string*.

+
Following the previous "Don't process" string, scan to the end of the line for *string* (same as + 1:99999).

LNCT - Line Count

Specifies the number of lines per page in the listing output. Ignored if the NOPRTCC process option is specified. The default value is 55 lines.

Compare Types — File, Line, Word, and Byte

Examples

`LNCT 66`	Lists up to 66 lines per page.

Syntax

```
LNCT num
```

Operand Description

num A decimal number between 15 and 999999.

LSTCOLM - List Columns

Selects a range of columns to be listed in the output. This statement overrides the SuperC convention of generating a listing starting with column 1 from the input source data set.

LSTCOLM column selections must be contiguous and can be no wider than the output listing line without truncation.

Compare Types — Line only

Examples

`LSTCOLM 20:90`	Lists columns 20 through 90 in the output listing.

Syntax

```
LSTCOLM range
```

Operand Description

range Two column numbers separated by a single colon (:). Do not leave blanks on either side of the colon.

NCHGT, OCHGT - Change Text

NCHGT Change new input text string
OCHGT Change old input text string.

Change the input source image before performing the comparison. More than one change text statement can be contained in the statements data set.

The find-mask and replacement string need not be the same length. The replacement string may even indicate a null string. Unequal replacements result in either blank insertions on short replacements (at the end of the found word) or downstream blank deletions to accommodate larger replacements (deleted blanks are selected from downstream blank pairs). The net effect of a longer string replacement of a shorter string shows as a reformat of the original line. The replaced text line appears in the output instead of the input text.

One or more question marks ("?") can be used as "wildcard" characters in the find-mask or string. A wildcard in the output string stores the input character "as is".

Compare Types — Line and Word

Examples

`NCHGT 'ABCD','XXXX'`	Changes all "ABCD"s to "XXXX" (exclude) in the new data set.
`OCHGT 'ABCD','XXXX',1:50`	Restricts the mask search to columns 1 through 50 in the old data set.
`OCHGT 'ABCD',',1:50`	Changes string "ABCD" to a null string in columns 1 through 50 in the old data set.
`NCHGT X'7B01',':1',6`	Uses the hexadecimal string change convention.
`NCHGT 'PREF???','NPREF'`	Changes the string "PREF" and the wildcard characters to the string "NPREF".
`NCHGT 'PREF???','NPREF??'`	Changes the string "PREF" and the first wildcard character to the string "NPREF". The second and third wildcard characters are not changed.

Syntax

```
NCHGT 'find-mask','string'[,start-colm[:stop-colm]]

OCHGT 'find-mask','string'[,start-colm[:stop-colm]]
```

Operand Description

find-mask The change text string to be replaced. The *find-mask* must be in single quotes. Use two consecutive single quotes for quotes within the *find-mask*.

string A character string that replaces the contents of *find-mask* before a comparison or search. Single quotation marks are required. If the character string contains a single quotation mark, you must enter it in the process statement as two single quotation marks.

You can include one or more question marks in the *string*. It shows that the position it occupies can be filled by any character, one character per question mark.

If there is not enough space for the string to be substituted, the substitution does not occur. Instead, a warning message is printed at the bottom of the listing.

start-colm A number that identifies the column in which SuperC begins its search for *string*. All columns to the left of this column are ignored.

stop-colm A number that identifies the column in which SuperC ends its search for *string*, but only for that record. If the data set contains more records, the search continues with the next record, beginning with the column specified as the start-colm.

This number is separated from the start-colm value by a colon (:). All columns to the right of this column are ignored. If the colon and stop-colm are not entered, only the start-colm value is used. This causes a search of a single column for the first character of *string*.

All columns to the right of the column that the last character of *string* can occupy are ignored. For example, if you specify `'ABCD'` as a string that must exist between columns 5 and 69, the search really includes columns 5 to 72. Therefore, the string can be found even if the first character is in column 69, with the others in columns 70, 71, and 72.

Notes:

1. Having a string replacement that is longer than the replaced string is not always possible with some lines. A warning message signals when this happens and the problem change-text statement will be designated in the summary section.
2. A string replacement using the “null” character notation does not always work as first envisioned. Nulling a character string only shifts following characters up through the next blank character. One or more blank pad characters are applied to take up the null positions of the original string. Entire lines are not shifted—only nonblank character strings.

```
NCHGT ' ','

blank insertion.

NCHGT '???','
```

NEXCLUDE, OEXCLUDE —Exclude Data:

NEXCLUDE—Exclude applies to the new data set
OEXCLUDE—Exclude applies to the old data set

Excludes rows or columns of data from the comparison. Up to 254 “exclude” statements can be entered for each data set.

Notes:

1. NEXCLUDE and OEXCLUDE statements are mutually exclusive to NFOCUS and OFOCUS statements respectively if using the same operand keyword (ROWS or COLS).
2. Do not use the NEXCLUDE or OEXCLUDE process option if the Y2DTONLY process option has been specified.
3. Valid row range = 1 to 999999.
4. FOCUS COLS and EXCLUDE COLS cannot be used when using CMPCOLM, CMPCOLMN or CMPCOLMO.

Compare Types

FILE (ROWS option only) and LINE.

Syntax

```
xEXCLUDE KYWD start-position:end-position
```

where **x**EXCLUDE can be either **N**EXCLUDE (new data set) or **O**EXCLUDE (old data set), and **KYWD** can be either **ROWS** or **COLS**. COLS is not valid for a FILE compare.

Operand Description

start-position	If ROWS operand used, the first row (record) to be excluded from the comparison. If COLS operand used, the first column to be excluded from the comparison.
end-position	If ROWS operand used, the last row (record) to be excluded from the comparison. If COLS operand used, the last column to be excluded from the comparison. (Must be separated from the *start-position* by a colon.)

Examples

`NEXCLUDE ROWS 5:900`	Excludes rows (records) 5 through 900 on the new data set.
`OEXCLUDE ROWS 1:900`	Excludes rows (records) 1 through 900 on the old data set.
`OEXCLUDE COLS 100:199`	Excludes columns 100 through 199 on the old data set.

NFOCUS, OFOCUS— Focus on Data

NFOCUS—Focus applies to the new data set
OFOCUS—Focus applies to the old data set

Selects (or "focuses on") rows or columns of data to be compared. In other words, only these rows or columns are considered when performing the comparison (or search) process and all other rows or columns are ignored. Up to 254 "focus" statements can be entered for each data set.

Notes:

1. NFOCUS and OFOCUS statements are mutually exclusive to NEXCLUDE and OEXCLUDE statements respectively if using the same operand keyword (ROWS or COLS).
2. Do not use the NFOCUS or OFOCUS process statement if the Y2DTONLY process statement has been specified.
3. Valid row range = 1 to 999999.

Compare Types

FILE (ROWS option only) and LINE.

Syntax

```
xFOCUS KYWD start-position:end-position
```

where **x**FOCUS can be either **N**FOCUS (new data set) or **O**FOCUS (old data set), and **KYWD** can be either **ROWS** or **COLS**. COLS is not valid for a FILE compare.

Operand Description

start-position	If ROWS operand used, the first row (record) to be selected for the comparison. If COLS operand used, the first column to be selected for the comparison.
end-position	If ROWS operand used, the last row (record) to be selected for the comparison. If COLS operand used, the last column to be selected for the comparison. (Must be separated from the *start-position* by a colon.)

Examples

`NFOCUS ROWS 28:90`	Selects rows (records) 28 through 90 on the new data set.
`OFOCUS ROWS 150:165`	Selects rows (records) 150 through 165 on the old data set.
`OFOCUS COLS 10:18`	Selects columns 10 through 18 on the old data set.

NTITLE, OTITLE - Alternate Listing Title

NTITLE New listing data set title identification
OTITLE Old listing data set title identification.

Allows you to specify an alternate data set identification in the output listing (54-character limit for each title identifier). This replaces the data set and library names used in the compare.

Note: This option is most useful when a single non-group compare is done on a temporary data set. The NTITLE/OTITLE identification may be more meaningful than the actual data set names used in the compare. This is only allowed for single members or sequential data sets.

Compare Types

File, Line, Word, and Byte

Examples

`NTITLE 'New Substitution Name'` `OTITLE 'Old Substitution Name'`	Change the titles in the output listing of the new and old data set.

Syntax

```
NTITLE 'string'

OTITLE 'string'
```

Operand Description

string The string can be up to 54 characters and must be delimited by single quotes. Use two consecutive single quotes for each embedded quote. The string is not checked for valid MVS data set name characters.

NY2AGE, OY2AGE —Year 2000 Aging Option

NY2AGE—Aging applies to the new data set
OY2AGE—Aging applies to the old data set

Ages all of the defined dates in either the new or old data set. That is, the number of years specified is added to the "year" portion of each defined date in the data set concerned.

Note: Dates are *defined* by the Year 2000 Date Definition process statements NY2C, NY2Z, NY2D, NY2P, OY2C, OY2Z, OY2D and OY2P; see "NY2C, NY2Z, NY2D, NY2P, OY2C, OY2Z, OY2D, OY2P —Year 2000 Date Definitions" on page 475.

Compare Types

LINE

Syntax

```
NY2AGE years
OY2AGE years
```

Operand Description

years A number (0 to 999) indicating the number of years by which all defined dates in the data set are to be aged.

Examples

`OY2AGE 28`	Ages all defined dates in the "old" data set by 28 years before being compared. The listing will show the original date. For example, a defined date in the "old" data set with a value equating to March 1, 1997, would be aged to March 1, 2025 before being compared to its equivalent in the "new" data set.

NY2C, NY2Z, NY2D, NY2P, OY2C, OY2Z, OY2D, OY2P —Year 2000 Date Definitions

NY2C—New data set, date in character format
NY2Z—New data set, date in zoned decimal format
NY2D—New data set, date in unsigned packed decimal format
NY2P—New data set, date in packed decimal format

OY2C—Old data set, date in character format
OY2Z—Old data set, date in zoned decimal format
OY2D—Old data set, date in unsigned packed decimal format
OY2P—Old data set, date in packed decimal format

Notes:

1. If any Year 2000 Date Definition process statements are used, a Y2PAST process statement should also be used so that the "century" portion of the date can be determined where necessary. (If a Y2PAST process statement is not present, a default fixed window based on the current year is used.)
2. For a description of each date format (character, zone, decimal and packed), see "Date Formats" on page 477.
3. If any Year 2000 Date Definition process statements are used, an *information line* is generated on the listing output.
4. Do not use any Year 2000 Date Definition process statements if using the COLHEAD process statement.

Defines the location and format of a date field on the input data set. Up to 254 date definition statements can be entered for each data set. The matching of the new to the old dates is performed according to the sequence that the statements are entered. That is, the first defined *old* date is matched to the first defined *new* date.

If the number of date definition statements for one data set differ to the number of date definition statements for the other data set, the location and format details for the "missing" date definition statements are assumed to be the same as their counterpart date definition statements for the other data set.

Compare Types

LINE

Syntax

```
xY2y start-column:end-column date-format EMPTY
```

where **x**Y2y can be either **N**Y2y (new data set) or **O**Y2y (old data set), and **y** can be either **C** (character format), **Z** (zoned decimal format), **D** (unsigned packed decimal format), or **P** (packed decimal format).

Note: The EMPTY keyword, when used, must be preceded by a space.

Operand Description

start-column	The first position of the date in the input data set.
end-column	The last position of the date in the input data set. (Must be separated from the *start-column* by a colon.)
date-format	A mask representing the format of the date.

For a Julian date, the mask must be either YYDDD or YYYYDDD.

For date formats other than Julian, the mask must contain 2 “D”s (representing the day part of the date field), 2 “M”s (representing the month), and either 2 or 4 “Y”s (representing the year) or, if the date contains a year only, it must contain either 2 or 4 “Y”s.

If the date is character, there may also be a separator between the different parts. In this case, you can represent the position of the separators by one of these characters:

`S`
`.` (period)
`/` (forward slash)
`:` (colon)

Note: The length of the *date-format* mask must correspond to the length of the date in the input data set as indicated by the values of *start-column* and *end-column*.

EMPTY

This keyword is optional. If it is entered, the defined date field is checked for containing zeros, spaces, low-values, or high-values before commencing the comparison process. If any of these values are found, the date will not be converted according to the Y2PAST criteria but will instead be converted to an extended format with the initial value. For example, a date defined by the process statement `OY2C YYMMDD` which contains all zeros will be compared as “YYYYMMDD” with a value of zeros.

Examples

`NY2C 1:8 MMDDYYYY 9:16 MMDDYYYY 21:28 YYYYMMDD`	The new data set has dates in character format in columns 1 to 8, 9 to 16 and 21 to 28.
`OY2P 5:8 YYMMDD 9:12 YYMMDD`	The old data set has dates in packed decimal format in columns 5 to 8 and 9 to 12.
`OY2P 101:104 MMDDYY`	The old data set has a date in packed decimal format in columns 101 to 104,
`NY2Z 101:108 YYYYMMDD`	The new data set has a date in zoned decimal format in columns 101 to 108.
`NY2C 101:110 YYYY.MM.DD`	The new data set has a date in character format (with separators) in columns 101 to 110.
`OY2C 93:98 DDMMYY EMPTY`	The old data set has a date in character format in columns 93 to 98. If the date field contains zeros, spaces, low-values, or high-values, the date in the old data set is converted before being compared to an extended format (DDMMYYYY) with a value of all zeros, spaces, low-values, or high-values respectively.

Date Formats (Keyword suffixes: C, Z, D, P)

C Character date data.

Examples:
'96' is represented as hexadecimal X'F9F6'
If using a MMDDYY format, March 21, 1996 is represented as hexadecimal X'F0F3F2F1F9F6'

Z Zoned decimal date data. The date can be represented as follows:

X'xyxy' to X'xyxyxyxyxyxyxyxy'

y is hexadecimal 0-9 and represents a date digit. x is hexadecimal 0-F and is ignored.

Examples:
'96' is represented as hexadecimal X'F9C6' or X'0906'
'03211996' is represented as hexadecimal X'F0F3F2F1F1F9F9C6' or X'0003020101090906'

P Packed decimal date data. The date can be represented as follows:

X'zyyx' to X'zyyyyyyyyx'

y is hexadecimal 0-9 and represents a date digit. x is hexadecimal A-F and is ignored. The z part is normally zero but will not be ignored.

Examples:
'96' is represented as hexadecimal X'z96F' or X'z96C'
'1996' is represented as hexadecimal X'z1996C'
'03211996' is represented as hexadecimal X'z03211996x' (the x part is ignored).
'96203' (a Julian date) is represented as hexadecimal X'96203C'

D Unsigned packed decimal date data. The date can be represented as follows:

'yy' to 'yyyyyyyy'

y is hexadecimal 0-9 and represents a date digit.

Examples:
'96' is represented as hexadecimal X'96'
'03211996' is represented as hexadecimal X'03211996'

REVREF—Revision Code Reference

Identifies the revision type (BookMaster or SCRIPT/VS) and level-ID for delimiting UPDREV and UPDREV2 output changes. The revision delimiter may, alternatively, be specified or indicated by using a SCRIPT/VS `.rc` definition statement as the first line of the *new* input data set.

If either the UPDREV or UPDREV2 process option is specified and no REVREF process statement is in the statements data set, or the first *new* data set source line is not a `.rc` script definition statement, SuperC defaults the revision definition to a SCRIPT/VS specification of `.rc 1 |`.

Note: BookMaster requires the REFID value to be defined with a `:revision` tag. Do not forget the "RUN=YES" attribute if you want your document to have the change-bar inserted in the processed document.

Compare Types

LINE, WORD

Syntax

```
REVREF REFID=name
       RCVAL=number
```

Operand Description

REFID=*name* Name of the revision identifier for the BookMaster :rev/:erev. tags.

RCVAL=*number*
Numeric revision code for SCRIPT/VS revision tags.

Examples

`REVREF REFID=ABC`	BookMaster example— `:rev refid=ABC.` and `:erev refid=ABC.` tags.
`REVREF RCVAL=5`	SCRIPT/VS example—`.rc 5` on/off delimiters.

SELECT - Select PDS Members

This process statement allows you to specify members to select from a PDS. You can specify as many member names as will fit on one line. Therefore, if you need to select additional members, enter a new SELECT statement.

For comparisons, the new members are normally compared with old members that have the same names. Use the colon character (:) to compare members that are not named alike. SELECT is valid with all compare types.

Compare Types

File, Line, Word, and Byte

Examples

`SELECT PROG1,NEWPROG2:OLDPROG2,PROG3`

Tells SuperC to make these one-to-one comparisons:

```
NEW MEMBER        OLD MEMBER
----------        ----------
PROG1       ⇒      PROG1
NEWPROG2    ⇒      OLDPROG2
PROG3       ⇒      PROG3
```

Syntax

```
SELECT new-member[:old-member],...
```

Operand Description

new-member The name of a new PDS member that is to be compared to an old PDS member.

old-member The name of an old PDS member that does not have a like-named member in the new PDS. This member name, if entered, must be separated from the new-member name by a colon (:).

If the old-member name is not used, SuperC attempts to compare the new-member to a like-named member of the old PDS.

SLIST - Statements File Listing Control

Turns on or off the printing of process statements in the output listing. The initial state of the control is “on”.

This statement is useful when there are many process statements and the listing of these statements in the summary section is not required for problem determination. For example, a large number of data set selections via SELECT statements would already be indirectly indicated in the group summary listing section. The SELECT statement list would then be redundant and generate extra lines in the listing.

Compare Types

File, Line, Word, and Byte

Examples

`SLIST OFF`	Does not list the process statements that follow this statement.

Syntax

```
SLIST {ON }
      {OFF}
```

Operand Description

ON Causes the lines in the process statements data set following the SLIST statement to be listed in the output listing.

OFF Causes the lines in the process statements data set following the SLIST statement to be suppressed in the output listing.

Y2PAST—Year 2000 Global Date Option

Specifies a 100-year period (used for determining the century-part of a date when only a 2-digit year has been specified). The Y2PAST process statement uses either a fixed or sliding window.

Note: The Y2PAST process statement should always be used if any of the Year 2000 Date Definition process statements (NY2C, NY2Z, NY2D, NY2P, OY2C, OY2Z, OY2D, OY2P) have also been used.

Compare Types

LINE

Syntax

```
Y2PAST fixed
       sliding
```

Operand Description

fixed A 4-digit number indicating a fixed window.

sliding
A 1-digit or 2-digit number indicating a sliding window.

Examples

`Y2PAST 1986`	A fixed window specifying a 100-year period from 1986 to 2085.
`Y2PAST 70`	A sliding window specifying (based on the current year being 1997) a 100-year period from 1927 (70 years in the past) to 2026.
`Y2PAST 5`	A sliding window specifying (based on the current year being 1997) a 100-year period from 1992 (5 years in the past) to 2091.

* and .* - Comment Lines (SuperC Listing)

An asterisk as the first character on a process statement line begins a printable comment line. A period-asterisk (.*) as the first 2 characters on a process statement line begins a comment that is not printed in the SuperC listing.

Note: Embedding comments as separate lines in the statements data set is a good programming practice. Period-asterisk comments are useful for inactivating but retaining old statements in a standard statements data set. These statements do not get lost, will not appear in the summary section, and can be reactivated simply by blanking out the period-asterisk characters in columns 1 and 2.

Compare Types: File, Line, Word, and Byte

Examples

```
 *  This comment prints in the Search-For listing.
 .* This comment does not print in the Search-For listing.
```

Syntax

```
{* } comment
{.*}
```

Operand Description

* Must be in column 1.

.* Must be in columns 1 and 2.

SuperC search-for process options

Table 26 lists all of the process options for Search-For.

Table 26. Search-For process options

ALLMEMS	ANYC	APNDLST	CKPACKL	COBOL	DPACMT	DPADCMT	DPBLKCL
DPCBCMT	DPCPCMT	DPFTCMT	DPMACMT	DPPLCMT	DPPSCMT	FINDALL	FMSTOP
IDPFX	LMTO	LNFMTO	LONGLN	LPSF	LTO		
MIXED	NOPRTCC	NOSEQ	NOSUMS	SDUPM	SEQ	XREF	

You can enter process options in the **Process Options** field of the Search-For Utility panel or select them from one of two Search-For process options panels.

ALLMEMS All members. Search all members including alias entries. This functions as though all directory entries were selected from a member list.

ANYC Any case. Lowercase alphabetic characters (a-z) in source data sets are translated to uppercase (A-Z) before Search-For processing (the actual input data sets are not modified).

Notes:

1. ANYC has the lowest priority operation affecting the SuperC process. For example, it does not affect any of the strings used in SuperC compare process statements (except SRCHFOR).
2. The ANYC process option does not apply to characters in DBCS text strings.

Use this option to find all strings such as “ABC”, “Abc”, “ABc”.

APNDLST The APNDLST process option appends the listing output to the specified or default listing data set. If the data set does not exist, it is allocated as new. Some data sets cannot be appended because of the append listing attributes and Search-For listing attribute requirements. There is an error notification for this condition.

Normally, APNDLST allows you to collect listings from separate searches into one named listing data set (that is, a MOD function). This objective can sometimes be done without using the APNDLST option by using multiple SELECT process statements. This allows you to identify any number of members. It produces a single composite listing with a single Search-For invocation.

CKPACKL Check for packed format. This option determines if the member or sequential data set has the standard ISPF packed expansion trigger format. If required, Search-For unpacks the input data set or member during the search.

COBOL Ignore columns 1-6 in F 80 data sets. Data in columns 1-6 are excluded from the search set.

DPACMT Don’t process asterisk (*) comment lines. Lines with an asterisk in column 1 are excluded from the search set. Other forms of assembler comments are unaffected. Hence, it is not possible to have Search-For filter out assembler comments appearing on the same line as an assembler statement or directive.

DPADCMT Don’t process ADA-type comments. ADA comments are whole or part lines that appear after the special “--” sequence. Blank lines

are also considered part of the comment set. This option produces a listing with all comments removed and blanked.

DPBLKCL Don't process blank lines. Source lines in which all of the search columns are blank are excluded from the Search-For set. It is redundant, but not incorrect, to use this option with DPADCMT, DPPLCMT, and DPPSCMT.

Note: The CMPCOLM process statement can be used to control the columns inspected. It is possible to have a line with nonblank data but filtered by the DPBLKCL option due to the column range values specified on the CMPCOLM statement. This may contradict the user assumption that DPBLKCL only excludes complete input blank lines. Another example of this would be a blank line that has sequence numbers in columns 73-80 and the Search-For run with the SEQ process option.

DPCBCMT Don't process COBOL type comment lines. COBOL source lines with an asterisk in column 7 are excluded from the search set.

DPCPCMT Don't process C++ end-of-line type compiler comments. These are "//" delimited comments. DPPLCMT may also be used with DPCPCMT when the source file contains "/* ... */" comments delimiters.

DPFTCMT Don't process FORTRAN type comment lines. FORTRAN source lines with a "C" in column 1 are filtered and excluded from the search set.

DPMACMT Don't process PC Assembly-type comments. Lines with an "*" in column 1 are excluded.

DPPLCMT Don't process PL/I-type comments. PL/I, C and REXX comments (that is, /* ... */ and blank lines) are filtered and excluded from the search set. This option produces a listing with all comments removed and partial comments blanked.

Notes:

1. The Search-For program detects most cases including multiline, statement embedded, and most quote dependency comments. However, Search-For may exclude some lines that are not comments. For instance, lines that contain comment delimiters that are enclosed in quotes.
2. The DPPLCMT process option does not recognize comments within DBCS text strings.

DPPSCMT Don't process PASCAL-type comments. PASCAL-type comments of the type "(* . . . *)" are filtered and excluded from the Search-For set as are blank compare lines. This option will produce a listing with comments removed and part comments blanked. The DPPSCMT process option does not recognize comments within DBCS text strings.

Note: DPPSCMT and DPPLCMT may be required to filter certain non-standard PASCAL compiler comments. The combination is allowed. Either may start a comment but only the starting delimiters type may terminate the comment.

FINDALL All strings must be satisfied for the search to be considered successful, whereupon the return code is set to one.

Notes:

1. If all searches are not satisfied, there is NO message to indicate this, other than RC=0. To find which searches failed, specify the XREF process option.
2. If the FMSTOP option is specified, the search will stop once it has satisfied all search strings.

FMSTOP Stop the search on the first occurrence of the search string in the data set or PDS member.

IDPFX Identifier prefixed. ID or member-name is prefixed to the search string lines of the listing.

LMTO List group member totals only. Lists only the member summary totals and the overall summary totals for the entire data set or group.

LNFMTO List not-found member or data set totals only. This is a tabular list of members or data sets where the string was not found. It shows the total lines searched.

LONGLN Long lines. LONGLN causes the Search-For program to create a listing with up to 203 columns, reflecting up to 176 columns from the source data sets. This data set may exceed the maximum number of columns handled by many printers.

LPSF List previous Search-For following lines. Lists the matched string line and up to six preceding and six following lines for context. The LPSFV process statement can be used to change the default value of six preceding and following lines to any value from 1 to 50.

LTO List totals only. Lists the overall summary totals for the entire data set group. Does not list member totals.

MIXED This option indicates that the input text may be a mixture of both single-byte and double-byte (DBCS) text. Double-byte strings are recognized and handled differently than if MIXED were not specified. For instance, single-byte characters are not valid within double-byte strings. Special terminals (for example, 5520) allow entry of DBCS characters.

If an input string starts with a shift-out character then MIXED removes the character from the string. If an input string ends with a shift-in character then MIXED removes the character from the string. Leading SO and trailing SI characters are not removed from strings specified on COLHEAD, NTITLE, or OTITLE process statements.

NOPRTCC No printer control columns. Search-For generates a “normal” listing data set with record lengths of 133 columns, or a LONGLN listing with 203 columns. These listings contain printer control columns and page separators. NOPRTCC eliminates both the page separators and control column 1. With NOPRTCC, “normal” listings are 132 columns, and LONGLN listings are 202. Section separators and title lines are still generated. This data set may be better for online browsing. It is easier to browse listings without interspersed page separator titles.

NOSEQ No sequence numbers. Search-For processes F 80 standard sequence number columns as data. This option is extraneous for variable-length records and non-fixed F 80 attribute data sets.

NOSUMS No summary listing section. This option omits the summary section including the statistics, options, warning, and error messages from the listing output.

SDUPM Search duplicate members. Searches all members found in concatenated PDS data sets, even if the members have the same name and are at a higher level. Search duplicate names even if the search is for a single member or if members are specified using the SELECT process statement.

SEQ Sequence numbers. Ignore F 80 standard sequence number columns. Sequence number column changes in columns 73-80 are ignored with F 80 and columns 1-8 in V 255 records. This is the SuperC default for F 80/V 255 data sets when the compare type is Line. It is not the default for Word compare. SEQ is not valid for any data set that does not have an attribute of F 80/V 255.

XREF Cross reference strings. Creates a cross reference index listing by search string. You can use XREF with IDPFX, LMTO, LNFMTO, and LTO.

The XREF option can be useful when more than one search string (or search condition) is specified. The XREF listing is implemented using a multiple pass operation for listing the “lines found” for each individual string. Note that XREF adds some additional processing overhead to the normal search process.

SuperC search-for process statements

Table 27 lists all of the Search-For utility process statements.

Table 27. Summary of Search-For process statements

CMPCOLM	CMPLINE	DPLINE	DPLINEC	LNCT	LPSFV	LSTCOLM
NCHGT	NTITLE	SELECT	SLIST	SRCHFOR	SRCHFORC	.*
*						

You must include these statements in an input control data set. The process statements data set can be fixed or variable, and its record length can be large, but you must enter process statements only in columns 1 through 72. Only one process statement can be entered per line. Search-For checks process statements and required operands for completeness before beginning a comparison. Comments are not allowed at the end of the line after the statement has been completed. Comment lines must be separate statements.

You can enter process statements in the statements data set more than once (for example, DPLINE, SELECT, or CMPLINE) as they define independent actions to be taken. Others redefine their process scope after their first inclusion (for example, LNCT). Including more than one redefining statement is not recommended but is not reported as an error. There is also no specific rule concerning which statement definition (or redefinition) prevails—the first (least often) or last (most often).

Note: It is best to inactivate old process statements that you do not need rather than deleting them from the statement data set. This can be easily done by

putting a period and an asterisk (.*) in the first 2 character positions. These statements will be ignored by the Search-For program when the data set is used as a statement data set.

Process statement notation conventions

This topic uses these notation conventions to describe the syntax of the process statements:

- Process statements and keywords are shown in uppercase to help you differentiate between them and their operands, which are shown in lowercase. However, you can enter them in any case you like.
- Operands shown in brackets ([ ]) are optional.
- Stacked operands shown in brackets indicate the optional operands from which you can select one or none.
- Stacked operands shown in braces ({ }) are required operands from which you must select one.
- Syntax diagrams that end with an ellipsis (...) allow you to repeat operands more than once.
- If a statement contains a KYWD operand, this keyword must precede any repetition of the operands that follow.

CMPCOLM - Compare (Search) Columns

Causes a search of the data between column limits of the input data set. Up to 15 search ranges or individual columns are allowed and may be entered on additional CMPCOLM statements. The column values and ranges must be in ascending order.

Examples

`CMPCOLM 25:75`	Searches columns 25 through 75.
`CMPCOLM 30:60,75`	Searches columns 30 through 60 and column 75.
`CMPCOLM 30:60 75`	Performs the same function as the previous statement.

Syntax

```
CMPCOLM  start-colm[:stop-colm][,...]
```

Operand Description

start-colm A number that identifies the column in which Search-For begins the search. All columns to the left of this column are ignored.

stop-colm A number that identifies the column in which Search-For ends its search. If the data set contains more records, the search continues with the next record, beginning with the column specified as the start-colm.

This number is separated from the start-colm value by a colon (:). All columns to the right of this column are ignored. If the colon and stop-colm are not entered, only the start-colm value is used.

Note: CMPCOLM is an overall limit value for selecting a range of columns to be searched. SRCHFOR and SRCHFORC statements have optional column limits that override the CMPCOLM process statement, SEQ process option, NOSEQ process option, and COBOL process option limits.

CMPLINE - Compare (Search-For) Lines

Searches a data set between line limits. The reference values may be line numbers or data patterns. The statement can be specified on one complete line or have separate CMPLINE statements for each of the two keyword operands NTOP or NBTM.

Examples

`CMPLINE  NTOP 55 NBTM 99`	Search new data set between lines 55 through 99.
`CMPLINE  NTOP 'ABCD',5:66`	Start new data set search when SuperC detects the first “ABCD” in columns 5 through 69.
`CMPLINE  NBTM 'ABCD'`	End new data set search on first “ABCD” found in any column.

Syntax

```
CMPLINE KYWD {rel-line-#                        }[ ...]
       {,'string'[,start-colm[:stop-colm]]}
```

Operand Description

KYWD The keyword may be one of these:

NTOP New Top. Defines the beginning line in the new (search) data set.

NBTM New Bottom. Defines the ending line in the new (search) data set.

rel-line-# The relative number of the record in the data set or member. Valid range = 1 to 999999.

string Character string enclosed within single quotes. For embedded single quotes, use two consecutive quotes (''). For example, enter `'don't'` for the string “don’t”.

start-colm A number that identifies the column in which Search-For begins looking for *string*. All columns to the left of this column are ignored.

stop-colm A number that identifies the column in which Search-For ends its search for *string*, but only for that record. If the data set contains more records, the search continues with the next record, beginning with the column specified as the start-colm.

This number is separated from the start-colm value by a colon (:). All columns to the right of this column are ignored. If the colon and stop-colm are not entered, only the start-colm value is used. This causes a search of a single column for the first character of *string*.

All columns to the right of the column that the last character of *string* can occupy are ignored. For example, if you specify `'ABCD'` as a string that must exist between columns 5 and 69, the search really includes columns 5 to 72. Therefore, the string can be found even if the first character is in column 69, with the others in columns 70, 71, and 72.

DPLINE, DPLINEC - Don't Process Lines

DPLINE Don't Process Lines
DPLINEC Don't Process Lines Continuation Condition.

Removes from the search set a line that can be recognized by either a unique character string or combination of related strings all appearing on the same input line. DPLINEC is the continuation of the immediately preceding DPLINE or DPLINEC process statement. All the strings in a DPLINE/DPLINEC sequence must be found on the same input line for the line to be excluded.

A start-column or stop-column can also be used to restrict the columns scanned. Relative start-columns and relative stop-columns are valid only on DPLINEC statements. You can specify a relative start position depending on the ending of the previous DPLINE/DPLINEC in the sequence relationship. Normal scanning starts at the beginning of the input line (resulting in the first found string) unless restricted by user column specifications or the relative operator.

Examples

`DPLINE 'ABCDE' DPLINE 'ABCDE',1:99999`	Both statements exclude lines containing the string "ABCDE" from the compare set.
`DPLINE 'AbCde',2 DPLINE 'AbCde',2:2`	Both statements exclude lines where the string "ABCDE" starts in column 2.
`DPLINE 'ABCDE' DPLINEC 'BDEF '`	Exclude lines that contain the strings "ABCDE" and "BDEF ".
`DPLINE 'ABCDE',2:50`	Excludes lines where the string "ABCDE" starts in columns 2 through 50.
`DPLINE 'AB'CD',2:50`	Excludes lines where the string "AB'CDE" starts in columns 2 through 50.
`DPLINE X'C1C27BF1',2:50`	Excludes lines where the string "AB,1" starts in columns 2 through 50.
`DPLINE 'ABC' DPLINEC 'BDEF',+`	Exclude lines containing the string "ABC" followed in the same line by the string "BDEF".
`DPLINE 'ABC's DPLINEC 'BDEF',+5`	Exclude lines containing the string "ABC" and "BDEF" when the string "BDEF" starts in the same line 5 column positions after the end of the string "ABC".

Syntax

```
DPLINE  'string'[,start-colm[:stop-colm]]

DPLINEC 'string'[,start-colm[:stop-colm]]
    [,+start-colm[:+stop-colm]]
    [,+]
```

Operand Description

string Character string enclosed within single quotes. For embedded single quotes, use two consecutive quotes (').

start-colm A number that identifies the column in which Search-For begins looking for *string*. All columns to the left of this column are ignored.

stop-colm A number that identifies the column in which Search-For ends its search for *string*, but only for that record. If the data set contains more records, the search continues with the next record, beginning with the column specified as the start-colm.

This number is separated from the start-colm value by a colon (:). All columns to the right of this column are ignored. If the colon and stop-colm are not entered, only the start-colm value is used. This causes a search of a single column for the first character of *string*.

All columns to the right of the column that the last character of *string* can occupy are ignored. For example, if you specify `'ABCD'` as a string that must exist between columns 5 and 69, the search really includes columns 5 to 72. Therefore, the string can be found even if the first character is in column 69, with the others in columns 70, 71, and 72.

+start-colm The relative column following the previous "Don't process" string in which Search-For begins the search for *string*.

+stop-colm The relative column following the previous "Don't process" string in which Search-For ends the search for *string*.

+ Following the previous "Don't process" string, scans to the end of the line for *string* (same as + 1:99999).

Notes:

1. DPLINE and DPLINEC columns are not restricted by search columns. The data patterns are also not affected by the ANYC process option.
2. The relative start operator "+" introduces another important capability of backtrack and retry by advancing the retry starting scan position. Backtrack allows you to identify a string through a sequence of DPLINE/DPLINEC statements and to search a number of similar strings (all on the same line) until the correct sequence is found. This contrasts to the "first found" DPLINE/DPLINEC string and a non-relative DPLINEC rejection when the DPLINEC condition is not met.

LNCT - Line Count

Specifies the number of lines per page in the listing output. This process option is ignored if NOPRTCC process option is specified. The default value is 55 lines.

Examples

`LNCT 66`	Lists up to 66 lines per page.

Syntax

```
LNCT num
```

Operand Description

num A decimal number between 15 and 999 999.

LPSFV - LPSF Count Value

Specifies the maximum number of lines to be used with the process option LPSF. This number replaces the default value of up to six lines before and six lines after the line containing the search string. This process statement has no formatting effect if you do not use the LPSF process option.

Examples

`LPSFV 2`	Lists up to 2 lines before and after the line where Search-For finds the search string.

Syntax

```
LPSFV num
```

Operand Description

num A decimal number between 1 and 50.

LSTCOLM - List Columns

Selects a range of columns to be listed in the output. This statement overrides the Search-For convention of listing lines starting with column 1 from the input source data set.

LSTCOLM column selections must be contiguous and can be no wider than the output listing line without truncation.

Examples

`LSTCOLM 20:90`	Lists columns 20 through 90 in the output listing.

Syntax

```
LSTCOLM range
```

Operand Description

range Two column numbers separated by a single colon (:). Do not leave blanks on either side of the colon.

NCHGT - Change Text of New (Search) Text String

Changes the input source image before performing the search. More than one change text statement may be contained in the statements data set.

The find-mask and replacement string need not be the same length. The replacement string may even indicate a null string. Unequal replacements result in either blank insertions on short replacements (at the end of the found word) or downstream blank deletions to accommodate larger replacements (deleted blanks are selected from downstream blank pairs). The net effect of a longer string replacement of a shorter string shows as a reformat of the original line. The replaced text line appears in the output instead of the input text.

One or more question marks ("?") can be used as "wildcard" characters in the find-mask or string. A wildcard character in the output string stores the input character as is.

Examples

`NCHGT 'ABCD','XXXX'`	Changes all "ABCD"s to "XXXX"s (exclude) in the new data set.
`NCHGT 'ABCD','XXXX',1:50`	Restricts the mask search to columns 1 through 50.
`NCHGT 'ABCD',',1:50`	Changes string "ABCD" to a null string in columns 1 through 50.
`NCHGT X'7B01',':1',6`	Uses the hexadecimal string change convention.
`NCHGT 'PREF???','NPREF'`	Changes the string "PREF" and the wildcard characters to the string "NPREF".
`NCHGT 'PREF???','NPREF??'`	Changes the string "PREF" and the first wildcard character to the string "NPREF". The second and third wildcard characters are not changed.

Syntax

```
NCHGT 'find-mask','string'[,start-colm[:stop-colm]]
```

Operand Description

find-mask The change text string to be replaced. The find-mask must be in single quotes. Use two consecutive single quotes for quote characters within the find-mask.

string A character string that is to replace the contents of *find-mask* before a comparison or search. Single quotation marks are required. If the character string contains a single quotation mark, you must enter it in the process statement as two single quotation marks.

You can include one or more question marks in the *string*. It indicates that the position it occupies can be filled by any character, one character per question mark.

If there is not enough space for the string to be substituted, the substitution does not occur. Instead, a warning message is printed at the bottom of the listing.

start-colm A number that identifies the column in which Search-For begins looking for *string*. All columns to the left of this column are ignored.

stop-colm

A number that identifies the column in which Search-For ends its search for *string*, but only for that record. If the data set contains more records, the search continues with the next record, beginning with the column specified as the start-colm.

This number is separated from the start-colm value by a colon (:). All columns to the right of this column are ignored. If the colon and stop-colm are not entered, only the start-colm value is used. This causes a search of a single column for the first character of *string*.

All columns to the right of the column that the last character of *string* can occupy are ignored. For example, if you specify `'ABCD'` as a string that must exist between columns 5 and 69, the search really includes columns 5 to 72. Therefore, the string can be found even if the first character is in column 69, with the others in columns 70, 71, and 72.

Notes:

1. Replacing a string with a longer string is not always possible with some lines. A warning message appears when this happens and the problem change-text statement is designated in the summary section.
2. A string replacement using the "null" character notation does not always work as first envisioned. Nulling a character string only shifts following characters up through the next blank character. One or more blank pad characters are applied to take up the null positions of the original string. Only nonblank character strings are shifted, not entire lines.

   ```
   NCHGT ' ','

   blank insertion.

   NCHGT '???','
   ```

NTITLE - Alternate Listing Title

NTITLE — listing data set title identification.

Allows you to specify an alternate data set identification in the output listing (54-character limit for each title identifier). This replaces the data set and library names used in the search.

Note: This option is most useful when a single non-group search is done on a temporary data set. The NTITLE identification may be more meaningful than the actual data set names used in the search.

Examples

`NTITLE 'New Substitution Name'`	Change the titles in the output listing of the data set.

Syntax

```
NTITLE 'string'
```

Operand Description

string The string can be up to 54 characters and must be delimited by single quotes. Use two consecutive single quotes for each embedded quote. The string is not checked for valid MVS data set name characters.

SELECT - Select PDS Members

This process statement allows you to specify members to select from a PDS. You can specify as many member names as will fit on one line. Therefore, if you need to select additional members, enter a new SELECT statement.

Examples

`SELECT PROG1,NEWPROG2,PROG3`	Selects PDS members PROG1, NEWPROG2, and PROG3 to be searched.

Syntax

```
SELECT new-member[...]
```

Operand Description

new-member The name of the PDS member that is to be searched.

SLIST - Statements File Listing Control

Turns on or off the printing of process statements in an output listing. The initial state of the control is “on”.

This statement is useful when there are many process statements and the listing of these statements in the summary section is not required for problem determination.

Examples

`SLIST OFF`	Does not list the process statements that follow this statement.

Syntax

```
SLIST {ON }
      {OFF}
```

Operand Description

ON Causes the lines in the process statements data set following the SLIST statement to be listed in the output listing.

OFF Causes the lines in the process statements data set following the SLIST statement to be suppressed in the output listing.

SRCHFOR, SRCHFORC - Search for Strings in the Input Files

SRCHFOR Searches for a text string in the input data set
SRCHFORC Searches for a text string continuation condition.

Specifies the string and the string type (P - prefix, W - word, S - suffix, or blank - for any occurrence of the string). SRCHFORC is the continuation of the immediately preceding SRCHFOR or SRCHFORC process statement. All the strings in a SRCHFOR/SRCHFORC group must be found on the same input line.

A start-column or start-range can also be used to restrict the columns. Relative start-columns and start-ranges are valid only on SRCHFORC statements.

Examples

`SRCHFOR 'ABC'`	Searches for string “ABC” within search columns.
`SRCHFOR 'ABC',W`	Searches for “ABC” as word string.
`SRCHFOR X'4004'`	Searches for hex string within search columns.
`SRCHFOR 'A'bc'`	Searches for string “A'bc”.
`SRCHFOR 'ABC',5:10`	“ABC” starts between positions 5 and 10 of the search columns.
`SRCHFOR 'ABC',W,5`	Word “ABC” starts in column 5.
`SRCHFOR 'ABC' SRCHFORC 'DEF'`	Finds “ABC” and “DEF” on same line within the search columns.
`SRCHFOR 'ABC' SRCHFORC 'DEF',+`	Finds “DEF” to the right of first “ABC” string.
`SRCHFOR 'ABC' SRCHFORC 'DEF',+1:9999`	Finds “DEF” to the right of first “ABC” string.
`SRCHFOR 'ABC' SRCHFORC 'DEF',W,+`	Finds “DEF” to the right of first “ABC” string, but “DEF” must be a word.
`SRCHFOR 'ABC' SRCHFORC 'DEF',+5`	Finds “DEF” to the right of first “ABC” string, but “DEF” must start in fifth column after “ABC”.
`SRCHFOR 'ABC' SRCHFORC 'DEF',+5 SRCHFORC 'GKL'`	Finds “DEF” to the right of first “ABC” string, but “GKL” must also be found on the same line.

Syntax

```
SRCHFOR 'string'[,P][,start-colm[:stop-colm]]
    [,S]
    [,W]


SRCHFORC 'string'[,P][,start-colm[:stop-colm]]
     [,S][,+start-colm[:+stop-colm]]
     [,W][,+]
```

Operand Description

string Character string enclosed within single quotes. For embedded single quotes, use two consecutive single quotes (').

P Prefix. String begins a word, but is not the complete word (Example: string “abc” is a prefix to the word “abcdef”).

S Suffix. String ends a word, but is not the complete word (Example: string “def” is a suffix to the word “abcdef”).

W
Word. String is a complete word. Words are delimited by blanks, or end-of-line characters.

start-colm
A number that identifies the column in which Search-For begins looking for *string*. All columns to the left of this column are ignored.

stop-colm
A number that identifies the column in which Search-For ends its search for *string*, but only for that record. If the data set contains more records, the search continues with the next record, beginning with the column specified as the start-colm.

This number is separated from the start-colm value by a colon (:). All columns to the right of this column are ignored. If the colon and stop-colm are not entered, only the start-colm value is used. This causes a search of a single column for the first character of *string*.

All columns to the right of the column that the last character of *string* can occupy are ignored. For example, if you specify `'ABCD'` as a string that must exist between columns 5 and 69, the search really includes columns 5 to 72. Therefore, the string can be found even if the first character is in column 69, with the others in columns 70, 71, and 72.

+start-colm
The relative column (starting from the column where the string of SRCHFOR/SRCHFORC ended) in which the string must start for the multiple statement relation to be met. Only SRCHFORC statements can contain relative start-columns.

+stop-colm
The number that identifies the relative column (starting from the column where the string of the last SRCHFOR/SRCHFORC ended) in which Search-For ends its search for *string*. Only SRCHFORC statements can contain a relative stop-colm.

+
Continues the scan after the pattern to the end of the line (same as +1:99999).

* and .* - Comment Lines (Search-For Listing)

An asterisk as the first character on a process statement line begins a printable comment line. A period-asterisk (.*) as the first two characters on a process statement line begins a comment that is not printed in the Search-For listing.

Note: Embedding comments as separate lines in the statements data set is a good programming practice. Period-asterisk comments are useful for inactivating but retaining old statements in a standard statements data set. These statements do not get lost, will not appear in the summary section, and can be reactivated simply by blanking out the period-asterisk characters in columns 1 and 2.

Examples

```
 *  This comment prints in the Search-For listing.
 .* This comment does not print in the Search-For listing.
```

Syntax

```
{* } comment
{.*}
```

Operand Description

* Must be in column 1.

.* Must be in columns 1 and 2.

Return codes

Results from calling the SuperC program are returned as condition codes from SuperC. The SuperC and SuperCE utilities generate a short message and a long message to interpret the results for you. However, only the long message displays the return codes, which are:

0 Normal completion. No differences were found in the input data sets.

1 Normal completion. Differences were found in the input data sets.

4 Warning. Erroneous or conflicting input options were detected by the SuperC program. Data sets were compared, but should be checked for results consistent with those expected. Check listing for more details.

6 Warning. The old data set did not contain proper sequence numbers, or the sequence number intervals were not large enough to contain insert activity. This return code applies only to results from the UPDCMS8, UPDMVS8, and UPDSEQ0 process options.

8 Error. Error on old input data set. The data sets were not compared. Check output for more information.

12 Error. Inconsistent data set organizations. The new and old data sets are not both PDSs or sequential data sets. The compare was not run.

16 Error. Error on new input data set. The data sets were not compared. Check output for more information.

20 Warning. Error on update data set; one of these:
- Missing DELDD
- I/O error
- Append to PDS
- Incorrect attributes on an append or PDS output operation.

Processing was completed with the update options reset and ignored. The error can also be returned if an update data set is being used simultaneously as the listing data set.

24 Error. Error occurred during open or during writing to the listing data set. The error can also be returned because of a new or old input data set simultaneously being used as the listing data set. No additional information is generated to better define the error condition.

25 Error. The listing data set was not allocated because of a conflict with the logical record length (LRECL), record format (RECFM), or data set organization. A listing can be saved only in a PDS that has the same LRECL or RECFM; a listing can never be appended to a PDS by using the APNDLST process option; a listing can be appended by using the APNDLST process option only to a sequential data set that has the same LRECL or RECFM. No output was generated.

SCLM Version Compare considerations

This return code is expected if the listing data set is partitioned but the member name is omitted. Correct the specification and try again.

26 Error. The listing data set could not be extended and is full (E37 condition). The results are truncated and incomplete.

28 Error. No data was compared because the old and new data sets were empty. Member names were invalid or there was nothing left to compare after input filtering. See the listing for more information.

32 Error. Insufficient storage was available for the SuperC program to run. The user region size was either too small or storage was too fragmented.

SuperC and search-for technical overview

This topic describes these SuperC and Search-For processes:
- How SuperC and Search-For filter input file lines
- How SuperC matches input file lines
- How SuperC partitions and processes large files
- Why SuperC compare types may produce different results
- How to directly invoke the SuperC and Search-For programs.

How SuperC and search-for filter input file lines

The SuperC and Search-For utilities apply process options and process statements to the input file or files in a specific order. Figure 242 shows schematically the effects, in the order that they occur, of the various "filtering" process options and process statements, on the compare and Search-For input lines. The options and statements nearer the top affect the input line before options or statements nearer the bottom.



- Both options and statements "filter" the input lines.
- "Filtered" input lines are passed to either compare or Search-For processing.

Figure 242. Priority for filtering input lines

How SuperC matches input files

When SuperC compares files, it determines matching and missing lines or words based only on the data content of the input files. It does not use any synchronization data, such as column or sequence numbers, to find matching file sections. It does not use the common “start at the top”, then look-ahead or look-back method to determine large sections of matching data. Neither does it sort the data before comparing.

SuperC is unique in that, except for files that are identical, it does not determine matching sections until it has completely read both files. Missing data units are units that are out of sequence, as opposed to units that have been deleted from a file. During a comparison, SuperC finds all matches, locates the largest set of matching data units, and recursively allows this compare set to divide the file into additional partitioned subsections. All new subsections are processed for corresponding matches. The subprocess ends when no more matches can be found within corresponding *new* and *old* file partitioned subsections. Sections classified as inserted or deleted are corresponding areas for which SuperC could not find a match.

Figure 243 shows an example of a comparison of two files that are identified as having lines represented by A, B, C, ... F. The SuperC algorithm attempts to find the best match set from the input lines. Notice how the match set requires consideration of duplicate lines.

```
      New File Lines                            Old File Lines

         ---A--- ------------Matched Line---------- ---A---

Inserted ---B---                                   ---I--- Deleted

Inserted ---C---    ---------Matched Line---------- ---D--- Largest  ---
         ---D--- ---        ---Matched Line---------- ---E--- Set    |
         ---E--- ------     |  Matched Line---------- ---F--- Unchanged---
         ---F--- ---------  |                        ---B--- Deleted

Inserted ---A---                                   ---C--- Deleted

         ---H--- ------------Matched Line---------- ---H---

         ---A--- ------------Matched Line---------- ---A---

                                                   ---A--- Deleted

 Sequence                 Left Side                Right Side

 Largest Set          -    D E F    Divides Set    D E F
 Top Set              -    A        Matches        A
 Leftover Top Set     -    B C      Mismatches     I
 Largest Bottom Match -    H A      Matches        H A
 Leftover Bottom Set  -    A        Mismatches     B C A

Note:  The inserted “A” on the lower left cannot connect with the
       deleted “A” on the bottom right due to H A barrier.
```

Figure 243. Find match example

How SuperC corrects false matches

Occasionally, SuperC reports that it has detected a false line or word match and has corrected the results in the listing and summary report. Any affected matched pair has been reclassified as an insert/delete pair. Any resulting error might be in the masking of potential matches that would be overlooked due to the early false match coupling. That is an equivalent yet undiscovered match may be overlooked due to the premature false matching. The condition should be of minor importance since it happens so rarely and the masking effect has a low probability of affecting the final results.

An equally important SuperC concern would be whether it finds the best match set and whether it finds all matches. Unfortunately, the match-finding algorithm is not perfect. Ignoring the false match masking problem, and the large number of duplicate source lines obscuring the match set possibilities, occasional matches can be overlooked.

Many Artificial Intelligence (AI) computer programs, like SuperC, only approximate the human intellect that can sometimes make a better match set selection. Furthermore, these same computer programs are designed for speed and efficiency. They necessarily make certain simplifying assumptions and contain additional operational weaknesses. SuperC , however, does not fail to correctly classify mismatches and does not incorrectly classify a mismatch as a match.

How SuperC partitions and processes large files

In SuperC, there is no limit on the size of files processed in terms of lines, words or bytes. Yet it had an internal methodology based upon a maximum field size for each work area storage structure (for example, array size and precision of variables). A method was developed to do the overall comparison process by breaking very large files into smaller comparison partitions and combining the intermediate results into one overall result. The process had to be done carefully so that it did not look as if the file partitioning was determined after some arbitrary limit was reached. That could affect the results on either side of the break point. The partitioning had to be done heuristically based upon the comparison results from the previously inspected intermediate process.

A fixed partitioning size of 32K lines/words/bytes was selected that was based on some test studies. The compare processes up to this limit and iteratively adjusts the intermediate ending break point of the pass by an adaptive method. Continuation from the adjusted end point is the basis for the next pass. That end point might even be adjusted to some previous records that had already been processed. The objective is to achieve the next best compare set for future unprocessed records.

The overall process ends when both files reach the End-of-File during a pass. The results from the intermediate passes are combined into one user end result. Most large compares are never suspected to have been partitioned and recombined.

The unlimited file size solution may appear, at first, unnecessary for Line compare using a virtual address space that is nearly unlimited. Yet there often has to be some limit—even if it is a high value. Programs need to store data with predetermined precision limits and programs work better with limits that are reasonable. Word compare and Byte compare eventually needed a partitioning limit for the compare as the number of words and bytes become large even for small file sizes.

Because of this partitioning process, comparisons of large files may take a long time.

Why compare types may produce different comparison results

Different comparison types often give you slightly different results. Here are some of the reasons:

- File comparisons inspect the complete data set (every byte) for differences. Line and Word comparisons use designated columns that are either the user specifications or SuperC defaults—possibly excluding sequence number columns 73-80.
- Line comparisons pad records with blanks when lines with different lengths are compared. However, Byte comparisons can find blank characters only if they are included in the input data sets.
- For data sets with input line lengths <= 256, Line comparison is done after the lines are padded with blanks to the longest line length. Lines originally of unequal length can compare equally if the blanks at the end of the longer line coincide with the shorter line's blank padding.
- For data sets with input line lengths > 256, Line comparison is done on the lines without blank padding. Lines of unequal length are always mismatches.
- Different comparison types have different sensitivity to being resynchronized. Line comparison synchronization begins at the beginning of a line and ends at the end of a line. Word comparison synchronization begins anywhere on a line on any word boundary and ends at the end of a word. Byte comparison synchronizes after each character.

  Word comparisons at the end of a line might change the size of the word comparison set but would have no effect on a Line comparison. The output reports could look very different.
- Line comparisons may produce different results because SuperC detects lines that have been reformatted. Reformatted lines have no effect on Word comparisons because Word comparisons ignore blank characters and blank lines.
- Results may differ depending on which compared data set is specified as new and which is specified as old. The matching algorithm is sensitive to the largest matched set it finds between data sets. There may be occasions where this set has alternatives of equal lengths. The rules for deciding which set to choose among the equals depend upon the actual content in the data set; therefore, data set dependencies do exist.

Comparing and searching alias members

When you compare or search all of the members of two partitioned data sets using the command `S *` (to select all entries in the directory) on the member list, any members that have alias entries are processed once for the real name, and once for each alias entry. For compare, unpaired aliases appear in the same list as unpaired real members as "NON-PAIRED NEW FILE MEMBERS" or "NON-PAIRED OLD FILE MEMBERS".

When you compare or search entire data sets by using an asterisk (*) for a member name pattern, only real members, not aliases, are processed. For compare, all directory entries (for both real members and aliases) are analyzed. Messages appear at the end of the SuperC output listing that give information about unpaired alias entries for paired real members as follows:

```
"NEW" PAIRED MEMBERS WITH "NEW" ALIAS MEMBERS NOT PAIRED FOLLOW:
        MEMBER1/ALIAS1  MEMBER1/ALIAS2  MEMBER2/ALIAS1 ...
         or
"OLD" PAIRED MEMBERS WITH "OLD" ALIAS MEMBERS NOT PAIRED FOLLOW:
        MEMBER1/ALIAS1  MEMBER1/ALIAS2  MEMBER2/ALIAS1 ...
```

followed by a listing of the unpaired member/alias entries.

Notes:

1. Consider the ALLMEMS process option if you want to compare all directory entries, including aliases, but do not want to select them from a member list. This is useful for batch comparisons of entire load modules.
2. This listing section is not created for non-load module data sets containing alias entries.

Comparing load modules

SuperC compare of load module data might show unexpected differences. This is because SuperC compares all the data in the load module as it is found on DASD, and does not attempt to decode which portions are executable, and which might contain uninitialized storage.

The complex data format on DASD is dependent on the load module data set block size, and defined storage definitions which are controlled by the linkage editor. The size stored by the linkage editor in the PDS directory may differ from the DASD data byte count reported by SuperC and Browse depending on the characteristics of the load module.

If load modules are exact copies of each other, SuperC should find no differences. If load modules have been link-edited from the same object but with different block sizes, SuperC will probably report they are different.

Because of the relative DASD addresses (TTRs) in load modules, the recommended procedure for comparing load modules which have not been reblocked is to use the AMBLIST utility with LISTLOAD OUTPUT=MODLIST against both load modules, then use SuperC to compare the two AMBLIST outputs. There is no easy way to compare load modules with different internal record sizes such as occurs when COPYMOD or LINKEDIT processes them.

Comparing CSECTs

SuperC compare of PDS Load Module Csects (using the LMCSFC Process Option) can return unexpected differences. SuperC looks at the length of the Csect from the control record immediately preceding the Csect data record in the load module. This physical data length can differ from the logical Csect data length in the load module header that the AMBLIST utility uses to report the length of the Csect.

SuperC always compares all of the physical data in each Csect. You can use SuperC Byte compare to examine the Csect data content in detail.

Note: This option is only valid for PDS load modules.

How to directly invoke SuperC and search-for

You can run the SuperC and Search-For programs directly without using the ISPF-provided utilities (Options 3.12, 3.13, 3.14, or 3.15). This requires an installation (or system programmer) to customize a CLIST (for interactive usage) or a PROCLIB procedure (for batch execution of a catalog procedure). Although these

methods are not warranted by the ISPF product, a sample CLIST and a sample PROCLIB procedure are distributed as an aid in the SAMPLIB data set as members ISRSCLST and ISRSPROC.

The sample CLIST allows a TSO user to enter a line command to communicate the operational parameters directly to the SuperC program without displaying the ISPF panels. The sample CLIST will request entry of a search pattern or string. A sample SuperC call as entered on the terminal might look like:

```
superc newfile(.newdata.file) oldfile(ludlow.olddata.file)
```

or

```
exec clist(superc) 'new(.newdata.file) old(ludlow.olddata.file)'
```

where *superc* is the command and *newfile* and *oldfile* are the keywords for the input files.

The SuperC load module may be supported using a private library or a concatenated system library. The installation is responsible for making the corresponding changes to the sample CLIST.

The sample CLIST uses this format:

```
SUPERC NEW(dsn) OLD(dsn) {keyword(parameter) .... }
```

The keywords and parameters are:

CTYPE Specifies the compare type. The parameter can be one of the SuperC compare types (File, Line, Word, or Byte). To call the Search-For program, use CTYPE(SRCH).

LISTING Specifies the listing type. The parameter can be one of the SuperC listing types.

OUTDD Specifies the name of the Listing Data Set. Use a fully qualified *dsn* or use a period (.) to precede the *dsn* with SYSPREF. The use of the period is a compromise because fully qualified names enclosed in quotes are difficult to pass in CLISTs.

BROWSE Specifies the auto display program.

SYSIN Specifies whether SuperC prompts the user for the process statements or uses a statements data set. The parameters can be `PROMPT` or the name of the statements data set.

DELDD Specifies the name of the update data set.

PROCESS Specifies the process options. The parameter can be a SuperC or Search-For process option. Not all options are allowed with each compare type (for example, GWCBL is valid only with Line and Word compare) or with other options (for example, you cannot use SEQ with COBOL). See "SuperC compare process options" on page 443 and "SuperC search-for process options" on page 483 for more information.

Examples

This example shows a SuperC compare JCL sequence:

```
//COMPARE  EXEC PGM=ISRSUPC,PARM=('LINECMP,CHNGL,UPDCNTL')
//STEPLIB  DD   DSN=ISPF.LOAD,DISP=SHR
//NEWDD    DD   DSN=DLUDLOW.PDS(TEST1),DISP=SHR
//OLDDD    DD   DSN=DLUDLOW.PDS(TEST2),DISP=SHR
//OUTDD    DD   SYSOUT=A
//DELDD    DD   DSN=DLUDLOW.UCTL1,DISP=OLD
//SYSIN    DD   *
   CMPCOLM 2:72
/*
```

The sequence allows the SuperC program to compare two input data sets and generates a line compare CHANGE type listing to the spool output queue and a separate UPDCNTL update control data set output using source columns 2 through 72.

A catalog procedure is a set of “canned” JCL statements that you can invoke as an extension of your own JCL. Here is a simplified JCL sequence:

```
//SUPERC JOB
//       EXEC  SUPERC,
//       NEWFILE='DLUDLOW.GROUP.DATA1',
//       OLDFILE='MFRAME.GROUP.DATA2',
//       LISTING=DELTA
```

The keywords NEWFILE, OLDFILE, and LISTING cause symbolic substitution before the job submittal.

Note: A sample catalog procedure is contained in the SAMPLIB member ISRSPROC.

A simplified Search-For JCL sequence follows. The SRCHFOR process statement used in the search is part of the JCL instead of a separate SYSIN data set. Concatenated data sets are also shown as part of the JCL.

```
//         JOB
//SEARCH   EXEC PGM=ISRSUPC,PARM=('SRCHCMP,ANYC')
//STEPLIB  DD   DSN=ISPF330.LOAD,DISP=SHR
//NEWDD    DD   DSN=USERID.PDS,DISP=SHR
//         DD   DSN=USERID.PDS2,DISP=SHR
//OUTDD    DD   SYSOUT=*
//SYSIN    DD     *
SRCHFOR 'NEEDLE',W,10:20
/*
//
```

A very simplified Search-For sample CLIST follows:

```
PROC 0
FREE   FI(NEWDD,SYSIN,OUTDD,SYSIN2)
ALLOC  FI(NEWDD) DA('USERID.PDS(TEST1)')        REUSE SHR
ALLOC  FI(SYSIN) DA('USERID.SYSIN.DATA(STMTS)') REUSE SHR
DELETE              'USERID.USER.PDS'
ALLOC  FI(OUTDD) DA('USERID.USER.LIST') SPACE(10,20) RECFM(F B) +
            REUSE TRACKS RELEASE
CALL 'USERID.ISPF.LOAD(ISRSUPC)' 'SRCHCMP,ANYC'
/*******************************************************/
/* SIMPLE CLIST WITH MINIMUM STATEMENTS.               */
/* "USERID.SYSIN.DATA(STMTS)" MUST CONTAIN SRCH STMTS.*/
/*******************************************************/
```

Appendix B. SuperC listings

The SuperC program allows you to produce four kinds of listings, differing generally depending on the compare type, process options, and process statements used. They range from OVSUM, which shows none of the source data, to LONG, which shows all of it.

Note: Listing types are not applicable for the File compare type. For information about File compare listings, see "Effect of File compare type on SuperC listings" on page 521.

OVSUM Lists only an overall summary of the results of the comparison without showing the differences themselves.

For example, an OVSUM listing of a Line comparison shows how many lines matched, how many were reformatted, how many were inserted, and so forth.

DELTA Lists only the differences between the source data sets or members being compared, followed by overall summary results. Differences are flagged to the left of each output line.

For example, a DELTA listing of a Line comparison shows only the individual lines in each data set or member that are different.

CHNG Same as the DELTA listing, plus up to 10 matching lines, words, or bytes before and after the differences. This shows the differences within the context of the surrounding lines.

For example, suppose a comparison of two data sets shows that each has 15 lines that match, followed by one or more lines that are different, followed by 15 more lines that match. A CHNG listing of a Line comparison of these data sets would show the lines in each data set or member that are different, plus 10 of the 15 lines that match, both before and after.

LONG Same as the CHNG listing, except that this listing shows the entire new data set, plus any data from the *old*, or original, data set that is not in the *new*, or changed, data set.

If we borrow the example used in the CHNG listing definition, a LONG listing would include all 15 matching lines, not just 10.

Subsequent topics begin by explaining the information displayed in the titles lines and at the bottom of the listings. Then, each listing type is discussed in more detail, with examples of listings and descriptions of the listing sections.

The examples were created by comparing two PDSs. The first, USERID.TEST1.SCRIPT, is considered the old data set and contains members DATA, ABEOLD, and WORDSOLD. USERID.TEST2.SCRIPT, the new data set, contains members DATA, ABENEW, and WORDSNEW.

DATA, as the only member name common to both data sets, is the only member compared. Figure 244 on page 512 shows the source data for both the old and new versions of DATA. Figure 245 on page 512 shows the results of an OVSUM comparison of the two versions.

© Copyright IBM Corp. 1980, 2007

```
  File  Edit  Confirm  Menu  Utilities  Compilers  Test  Help
--------------------------------------------------------------------------------
EDIT       USERID.TEST1.SCRIPT(DATA) - 01.02               Columns 00001 00072
****** ***************************** Top of Data ******************************
000100 This line is reformatted; the  spacing  in  the  "new"  member  differs.
000200 This line is the same in both members.
000300 This line differs from the text in the "new" member.
000400 This line is the same in both members.
Command ===> ___________________________________________________ Scroll ===> PAGE
 F1=Help      F2=Split     F3=Exit      F5=Rfind     F6=Rchange   F7=Up
 F8=Down      F9=Swap     F10=Left     F11=Right    F12=Cancel
.  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
  File  Edit  Confirm  Menu  Utilities  Compilers  Test  Help
--------------------------------------------------------------------------------
EDIT       USERID.TEST2.SCRIPT(DATA) - 01.02               Columns 00001 00072
****** ***************************** Top of Data ******************************
000100 This line is reformatted; the spacing in the "new" member differs.
000200 This line is the same in both members.
000300 This line is different from the text in the "old" member.
000400 This line is the same in both members.
000500 This line is in the "new" member, but not in the "old".
****** *************************** Bottom of Data ***************************
Command ===> ___________________________________________________ Scroll ===> PAGE
 F1=Help      F2=Split     F3=Exit      F5=Rfind     F6=Rchange   F7=Up
 F8=Down      F9=Swap     F10=Left     F11=Right    F12=Cancel
```

Figure 244. Split screen showing source data for SuperC listings

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31      9.44       PAGE   1
 NEW:  USERID . TEST2 . SCRIPT(DATA)                                  OLD:  USERID . TEST1 . SCRIPT(DATA)

                          LINE COMPARE SUMMARY AND STATISTICS

          2    NUMBER OF LINE MATCHES                  3    TOTAL CHANGES  (PAIRED+NONPAIRED CHNG)
          1    REFORMATTED LINES                       2    PAIRED CHANGES  (REFM+PAIRED  INS/DEL)
          2    NEW FILE LINE INSERTIONS                1    NON-PAIRED INSERTS
          1    OLD FILE LINE DELETIONS                 0    NON-PAIRED DELETES
          5    NEW FILE LINES PROCESSED
          4    OLD FILE LINES PROCESSED

LISTING - TYPE = OVSUM              COMPARE - COLUMNS =     1 : 72          LONGEST LINE = 80
PROCESS OPTIONS USED :  SEQ(DEFAULT)
```

Figure 245. OVSUM listing of a LINE comparison of two PDS members

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   1
 NEW:  USERID . TEST2 . SCRIPT(DATA)                                    OLD:  USERID . TEST1 . SCRIPT(DATA)

                          LISTING OUTPUT SECTION  (LINE COMPARE)

ID          SOURCE LINES                                                  TYPE    LEN N - LN#   O - LN#
   ---- + ---- 1 ---- + ---- 2 ---- + ---- 3 ---- + ---- 4 ---- + ---- 5 ---- + ---- 6 ---- + ---- 7 ---- + ----
RN -  This line is reformatted:   the spacing in the "new" member differs.                  00010000    RFM=       1  00001  00001
RO -  This line is reformatted:   the spacing in the "new" member differs.                  00010000
                                                                                                        MAT=       1
I    -  This line is different from the text in the "old" member.                           00030000    RPL=       1  00003  00003
D    -  This line differs from the text in the "new" member.                                00030000
                                                                                                        MAT=       1
I    -  This line is in the "new" member, but not in the "old".                             00050000    INS=       1  00005  00004

1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   2
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                          MEMBER SUMMARY LISTING  (LINE COMPARE)

CHNG MEMBERS - COMPARED   NEW-PROC  OLD-PROC MATCHED  NEW-INS  OLD-DEL  REFM-LN  N-DP-LN  O-DP-LN

**       DATA                                5          4          2          2          1          1

         1  TOTAL MEMBER(S) PROCESSED AS A PDS
         1  TOTAL MEMBER(S) PROCESSED HAD CHANGES
         0  TOTAL MEMBER(S) PROCESSED HAD NO CHANGES
         2  TOTAL NEW FILE MEMBER(S) NOT PAIRED
         2  TOTAL OLD FILE MEMBER(S) NOT PAIRED
```

Figure 246. DELTA listing of a LINE comparison of two PDSs (Part 1 of 2)

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   3
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                          MEMBER SUMMARY LISTING (LINE COMPARE)

      NON-PAIRED NEW FILE MEMBERS          |       NON-PAIRED OLD FILE MEMBERS

                ABENEW                     |                ABEOLD
                WORDSNEW                   |               WORDSOLD

1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   4
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                          PDS LINE OVERALL TOTALS

          2    NUMBER OF LINE MATCHES          3    TOTAL CHANGES  (PAIRED+NONPAIRED CHNG)
          1    REFORMATTED LINES               2    PAIRED CHANGES  (REFM+PAIRED  INS/DEL)
          2    NEW FILE LINE INSERTIONS        1    NON-PAIRED INSERTS
          1    OLD FILE LINE DELETIONS         0    NON-PAIRED DELETES
          5    NEW FILE LINES PROCESSED
          4    OLD FILE LINES PROCESSED

LISTING - TYPE = DELTA          COMPARE - COLUMNS =     1 : 72        LONGEST LINE = 80
PROCESS OPTIONS USED :  SEQ(DEFAULT)
```

Figure 246. DELTA listing of a LINE comparison of two PDSs (Part 2 of 2)

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   1
 NEW:  USERID . TEST2 . SCRIPT(DATA)                                    OLD:  USERID . TEST1 . SCRIPT(DATA)

                                LISTING OUTPUT SECTION  (WORD COMPARE)

ID                      SOURCE LINES (COMPARED COLUMNS)                                                          N-LN#   O-LN#

       This line is reformatted:   the spacing in the "new" member differs.                                      00001   00001
       This line is the same in both members.                                                                    00002   00002
MC-    This line                   from the text in the          member.                                         00003   00003
  IC-              is  different                        "old"                                                    00003   00003
DC-                differs                              "new"                                                    00003   00003
       This line is the same in both members.                                                                    00004   00004
   I-  This line is in the "new" member, but not in the "old".                                                   00005   00004


1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   2
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                                MEMBER SUMMARY LISTING  (WORD COMPARE)

CHNG MEMBERS - COMPARED  NEW-PROC OLD-PROC MATCHED NEW-INS OLD-DEL              N-DP-LN  O-DP-LN  N-LN-PRC  LN-INS  O-LN-PRC  LN-DEL

**     DATA                          50         37         35         15         2                                  5         2         4         1

        1   TOTAL MEMBER(S) PROCESSED AS A PDS
        1   TOTAL MEMBER(S) PROCESSED HAD CHANGES
        0   TOTAL MEMBER(S) PROCESSED HAD NO CHANGES
        2   TOTAL NEW FILE MEMBER(S) NOT PAIRED
        2   TOTAL OLD FILE MEMBER(S) NOT PAIRED
```

Figure 247. LONG listing of a word comparison of two PDSs (Part 1 of 2)

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   3
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                                MEMBER SUMMARY LISTING (WORD COMPARE)

      NON-PAIRED NEW FILE MEMBERS            |        NON-PAIRED OLD FILE MEMBERS

                 ABENEW                      |                 ABEOLD
                 WORDSNEW                    |                 WORDSOLD

1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   4
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                                PDS WORD OVERALL TOTALS

          35   NUMBER OF WORD MATCHES          15   TOTAL CHANGES  (PAIRED+NONPAIRED CHNG)
          15   NEW FILE WORD INSERTIONS         2   NEW FILE LINES CHANGED/INSERTED
           2   OLD FILE WORD DELETIONS          1   OLD FILE LINES CHANGED/DELETED
          50   NEW FILE WORDS PROCESSED         5   NEW FILE LINES PROCESSED
          37   OLD FILE WORDS PROCESSED         4   OLD FILE LINES PROCESSED

LISTING - TYPE = LONG            COMPARE - COLUMNS =     1 : 80        LONGEST LINE = 80
PROCESS OPTIONS USED :  SEQ
```

Figure 247. LONG listing of a word comparison of two PDSs (Part 2 of 2)

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31      12.31       PAGE   1
 NEW:  NEW.DATA                                          OLD:  OLD.DATA

                          LISTING OUTPUT SECTION (LINE COMPARE)

ID      SOURCE LINES                                                                                TYPE  LEN N-LN# O-LN#
   Account   Birth          Surname
   Number    Date                                                                                   MAT=      1
I  -  111222     19970101      Jones                                                                RPL=      1 00002 00002
D  -  111222     970201        Jones
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31      12.31       PAGE   2
 NEW:  NEW.DATA                                          OLD:  OLD.DATA

                          LINE COMPARE SUMMARY AND STATISTICS

          1    NUMBER OF LINE MATCHES            1    TOTAL CHANGES  (PAIRED+NONPAIRED CHNG)
          0    REFORMATTED LINES                 1    PAIRED CHANGES  (REFM+PAIRED  INS/DEL)
          1    NEW FILE LINE INSERTIONS          0    NON-PAIRED INSERTS
          1    OLD FILE LINE DELETIONS           0    NON-PAIRED DELETES
          2    NEW FILE LINES PROCESSED
          2    OLD FILE LINES PROCESSED

LISTING - TYPE = DELTA              COMPARE - COLUMNS =      1 : 72          LONGEST LINE = 80
PROCESS OPTIONS USED :  SEQ(DEFAULT)
THE FOLLOWING PROCESS STATEMENTS (USING COLUMNS 1 : 72) WERE PROCESSED:
     COLHEAD 'Account', 'Number', 1:8, N 7:11 P, 0 11:50 P
     COLHEAD 'Birth', 'Date', 10:20, N 7:11 P, O 7:10 P
     COLHEAD 'Surname',,22:61, N 12:51 P,O 11:50 P
```

Figure 248. Comparison listing with column headings (using COLHEAD)

Figure 248 shows how COLHEAD process statements have been used to generate column headings (`Account Number`, `Birth Date`, and `Surname`) for the corresponding input data. For more information, see "COLHEAD—Define Column Headings" on page 463.

SuperC listing title lines

SuperC listings contain two title lines. Figure 246 on page 513 shows an example. The first title line shows:

- The name of the SuperC program, which is described as a file/line/word/byte/s for the compare utility for ISPF for OS/390.
- The date and time the listing was produced. The date is shown according to the format used by your country. The time is shown in 24-hour format, with the hours and minutes separated by a period.
- The page number.

The second title line shows you the names of the new and old data sets that were compared when the listing was created.

Listing Output Section

The Listing Output Section shows any lines, words, or bytes that were found to be different, depending on the compare type being used. For a Word comparison, the source lines that appear in the listing show only the columns of data that were really compared. See Figure 247 on page 514 for an example and "CMPCOLM, CMPCOLMN, CMPCOLMO - Compare Columns" on page 458 for more information.

The Listing Output Section flags changes by using:

- Listing prefix codes
- Type-of-difference codes.

Listing prefix codes

SuperC output lines are flagged with these prefix codes listed under the ID column:

blank *Match*—No prefix code means the data is the same in both data sets.

I *Insert*—Data that is in the new data set, but not in the old data set.

D *Delete*—Data that is in the old data set, but not in the new data set.

DR *Delete Replace*—For Byte compare listings only. A byte(s) in the old data set that was replaced by the byte(s) shown in the preceding insert (I) line.

MC *Match Compose*—For Word compare listings only.A line containing words that match. The line may also contain spaces to show the relationship between the matching words and any inserted or deleted words. Inserted and deleted words are shown in following insert compose (IC) and delete compose (DC) lines.

IC *Insert Compose*—For Word compare listings only. A line containing words from the new data set that are not in the old data set. This line usually follows a match compose (MC) line.

DC *Delete Compose*—For Word compare listings only. A line containing words from the old data set that are not in the new data set. This line usually follows a match compose (MC) or insert compose (IC) line.

IM *Insert Matching*—For compare listings created by using the FMVLNS (flag moved lines) process option. A line in the new data set that also appears in the old data set, but has been moved. If the line was reformatted, this is shown by a flag to the right of the listing.

DM *Delete Matching*—For compare listings created by using the FMVLNS (flag moved lines) process option. A line in the old data set that also appears in the new data set, but has been moved. If the line was reformatted, this is shown by a flag to the right of the listing.

RN *Reformat New*—For Line compare listings only. A reformatted line in the new data set. This line contains the same data as the old data set line, but with different spacing.

RO *Reformat Old*—For Line compare listings only. A line in the old data set that has been reformatted in the new data set. To keep this line out of your output listing, use the DLREFM (delete reformatted line) process option.

| *Change Bar*—For compare listings created by using the GWCBL (generate Word change bar listing) process option. A change bar showing that words were either inserted or deleted. Figure 249 on page 517 provides an example.

Type-of-difference codes

At the far right of some listings are headings that provide additional information about the types of differences SuperC has found. Headings you may see are:

TYPE An abbreviation that identifies the type of difference:

MAT= Matched lines.

RFM= Reformatted lines.

RPL= Replaced lines.

INS= Lines that are in the new data set, but not in the old data set.

DEL= Lines that are in the old data set, but not in the new data set.

IMR= Lines in the new data set that have been moved from where they were in the old data set and reformatted. Listing should show a matching DMR= flag for a line in the old data set.

DMR=
Lines in the old data set that have been moved and reformatted in the new data set. Listing should show a matching IMR= flag for a line in the new data set.

IMV= Lines in the new data set that have been moved from where they were in the old data set. Listing should show a matching DMV= flag for a line in the old data set.

DMV=
Lines in the old data set that have been moved in the new data set. Listing should show a matching IMV= flag for a line in the new data set.

LEN The number of consecutive lines flagged by one of the TYPE abbreviations.

N-LN# and O-LN#
The line number(s) where the flagged line appears in either or both data sets. For insertions, the O-LN# column shows where the line would have appeared in the old data set. For deletions, the N-LN# column shows where the line would have appeared in the new data set.

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   1
 NEW:  USERID . TEST2 . SCRIPT(DATA)                                    OLD:  USERID . TEST1 . SCRIPT(DATA)

                          LISTING OUTPUT SECTION  (WORD COMPARE)

ID          SOURCE LINES

I    -  This line is reformatted:  the spacing in the "new" member differs.          00010005
        This line is the same in both members.                                      00020000
I    -  This line is different from the text in the "old" member.                   00030000
        This line is the same in both members.                                      00040000
I    -  This line is in the "new" member, but not in the "old".                     00050000


1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   2
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                          MEMBER SUMMARY LISTING  (WORD COMPARE)

CHNG MEMBERS - COMPARED   NEW-PROC  OLD-PROC MATCHED  NEW-INS  OLD-DEL          N-DP-LN  O-DP-LN  N-LN-PRC  LN-INS  O-LN-PRC  LN-DEL

**      DATA                          55          40          37          17          2                                   5          3          4          2

        1  TOTAL MEMBER(S) PROCESSED AS A PDS
        1  TOTAL MEMBER(S) PROCESSED HAD CHANGES
        0  TOTAL MEMBER(S) PROCESSED HAD NO CHANGES
        2  TOTAL NEW FILE MEMBER(S) NOT PAIRED
        2  TOTAL OLD FILE MEMBER(S) NOT PAIRED
```

Figure 249. Word comparison of two PDSs using change bar to show differences (Part 1 of 2)

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31      9.44      PAGE   3
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                          MEMBER SUMMARY LISTING (WORD COMPARE)

       NON-PAIRED NEW FILE MEMBERS            |        NON-PAIRED OLD FILE MEMBERS

                 ABENEW                       |                  ABEOLD
                 WORDSNEW                     |                  WORDSOLD

1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31      9.44      PAGE   4
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                          PDS WORD OVERALL TOTALS

          37   NUMBER OF WORD MATCHES          17   TOTAL CHANGES  (PAIRED+NONPAIRED CHNG)
          17   NEW FILE WORD INSERTIONS         3   NEW FILE LINES CHANGED/INSERTED
           2   OLD FILE WORD DELETIONS          2   OLD FILE LINES CHANGED/DELETED
          55   NEW FILE WORDS PROCESSED         5   NEW FILE LINES PROCESSED
          40   OLD FILE WORDS PROCESSED         4   OLD FILE LINES PROCESSED
           1   FALSE MATCH(S) CORRECTED

LISTING - TYPE = LONG            COMPARE - COLUMNS =     1 : 80        LONGEST LINE = 80
PROCESS OPTIONS USED :  GWCBL
```

Figure 249. Word comparison of two PDSs using change bar to show differences (Part 2 of 2)

Member Summary Listing

The information shown in the Member Summary Listing depends on the compare type used. For example, PAGE 2 of the listing in Figure 249 on page 517 shows the number of words that were processed, matched, inserted, deleted, reformatted, and excluded from processing by a process option or statement, such as the DPLINE process option.

This part also shows how many members were processed, had changes, had no changes, and were not paired, with the last category provided for both new and old members.

As the sample listing shows, one member was processed and had changes. It also shows that both PDSs contain two *non-paired* members. The non-paired heading means that these members were not included in the comparison because they were not paired with members in the other PDS. The names of these members are shown in the second part of the Member Summary Listing, PAGE 3 of Figure 249.

Summary and statistics/PDS overall totals

Many SuperC listings contain an overall summary showing totals that are compiled for the compare type being used. For comparisons of sequential data sets or membered PDSs, this summary is called:

```
XXXX COMPARE SUMMARY AND STATISTICS
```

However, for comparisons of complete PDSs, as PAGE 4 of Figure 249 on page 517 shows, the summary is called:

```
PDS XXXX OVERALL TOTALS
```

In both headings, the `XXXX` is replaced by the compare type being used, such as `WORD`. As the sample listing shows, the left side of a LONG listing of a Word comparison shows how many words were matched, inserted, deleted, and processed. Several of these categories are related. For instance, the number of lines processed in the new data set should be equal to the number of line matches, the reformatted lines, and the new file line insertions. The number of processed lines does not include lines that were excluded from processing by a process option or statement, such as the DPLINE process option.

The left side of the sample listing also shows that the SuperC program corrected a *false match*, which it occasionally may detect on the first pass and reclassify as an insert/delete pair. The new classification is correct, but may have caused the process to overlook an alternate match. However, this condition should not occur frequently, which means your comparison results probably will not be affected. The SuperC program never incorrectly calls a data unit (file, line, word, or byte) a match when it should be a mismatch.

On the right side, the listing shows the total number of changes, the number of lines classified as changed/inserted and changed/deleted, and the number of lines processed. In a Line comparison listing, as shown in Figure 246 on page 513, these are called *paired* changes. Paired changes show, for example, that a line inserted in the new data set corresponds to a line deleted from the old data set. The opposite would be true for non-paired insertions or deletions.

The number given as total changes should be the sum of the paired changes, non-paired insertions, and non-paired deletions. For example, in Figure 246 on page 513, the right-side totals are the equivalent of:

```
  2  PAIRED CHANGES
  1  NON-PAIRED INSERTS
+ 0  NON-PAIRED DELETES
 --
  3  TOTAL CHANGES
```

Bottom-of-listing information

The list shown describes information that may appear at the bottom of your SuperC listings. Figure 249 on page 517 shows an example.

- The LISTING-TYPE generated: OVSUM, DELTA, CHNG, or LONG
- The COMPARE-COLUMNS, or the range of columns compared, expressed as two numbers separated by a colon. For example, `1:76` means SuperC compared columns 1 to 76 in both data sets. If two column ranges are shown, the first is the range compared in the new data set or member and the second is the range compared in the old data set or member.
- The length in bytes of the LONGEST-LINE found in any data set or member compared
- A list of the PROCESS OPTIONS USED
- A list of the PROCESS STATEMENTS USED
- Warnings and error messages.

Note: For Byte comparisons, the COMPARE-COLUMNS information is not shown because column ranges are not applicable during Byte comparisons.

Y2K comparison

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       12.31       PAGE   1
 NEW:  NEW.DATA                                    OLD:  OLD.DATA

                              LISTING OUTPUT SECTION (LINE COMPARE)

ID      SOURCE LINES                                                                                TYPE  LEN N-LN# O-LN#
   -----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8
                                                                                                    MAT=      1
I - 970522       `-|ê-                                                                              RPL=      1 00002 00002
INFO   Date cols 11:15 packed 20970522   comp=(2097 05 22)
D - 970522       -|ê-
INFO   Date cols 11:14 packed 970522       comp=(1997 05 22)
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       12.31       PAGE   2
 NEW:  NEW.DATA                                    OLD:  OLD.DATA

                              LINE COMPARE SUMMARY AND STATISTICS

            1    NUMBER OF LINE MATCHES              1    TOTAL CHANGES  (PAIRED+NONPAIRED CHNG)
            0    REFORMATTED LINES                   1    PAIRED CHANGES  (REFM+PAIRED  INS/DEL)
            1    NEW FILE LINE INSERTIONS            0    NON-PAIRED INSERTS
            1    OLD FILE LINE DELETIONS             0    NON-PAIRED DELETES
            2    NEW FILE LINES PROCESSED
            2    OLD FILE LINES PROCESSED

 LISTING - TYPE = DELTA              COMPARE - COLUMNS =     1 : 72          LONGEST LINE = 80
 PROCESS OPTIONS USED :  SEQ(DEFAULT)
THE FOLLOWING PROCESS STATEMENTS (USING COLUMNS 1 : 72) WERE PROCESSED:
      Y2PAST 1987
      NY2P 11:15 YYYYMMDD
      OY2P 11:14 YYYYMMDD
      NFOCUS COLS 1 : 20
      OFOCUS COLS 1 : 20
```

Figure 250. Comparison listing with Y2000 dates being compared

Figure 250 shows how the two Year 2000 date definition process statements have each caused an information (*INFO*) line to be generated. The information line shows:

- The position of the defined date in the record
- The contents of the defined date field
- The date as it was ***actually compared***. In the second information line, you can see the defined date has a 2-digit year portion (″97″) but has actually been compared using a 4-digit year portion (″1997″).

For more information, see “NY2C, NY2Z, NY2D, NY2P, OY2C, OY2Z, OY2D, OY2P —Year 2000 Date Definitions” on page 475.

Note: Occasionally, you might see some ″unusual″ characters on the inserted (I) and deleted (D) lines. These characters simply represent data that is in a non-character (and therefore not directly printable) format in the input record. You can ignore them.

Side-by-side listings

Two process options, NARROW and WIDE, let you produce listings that show source data side-by-side (Figure 251 on page 521) instead of interspersed (Figure 246 on page 513). The NARROW process option shows up to 55 columns from each member, while the WIDE process option shows up to 80. The listing is truncated if it exceeds the line length of the process option being used.

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   1
 NEW:  USERID . TEST2 . SCRIPT(DATA)                                    OLD:  USERID . TEST1 . SCRIPT(DATA)

                              LISTING OUTPUT SECTION  (LINE COMPARE)

ID                NEW FILE LINES                                          ID            OLD FILE LINES                          N-LN#   O-LN#
        ---- 1 ---- + ----- 2 ---- + ----- 3 ----- + ---- 4 ---- + ---- 5 ---- +                ---- + ---- 1 ---- + ---- 2 ---- + ---- 3 ---- + ---- 4 ---- + ---- 5 ---- +
RN      - This line is reformatted:  the spacing in the "new" memb          RO     - This line is reformatted:  the spacing in the "new"      00001   00001
          This line is the same in both members.                                     This line is the same in both members.                 00002   00002
I       - This line is different from the text in the "old" membe           D      - This line differs from the text in the "new" membe       00003   00003
          This line is the same in both members.                                     This line is the same in both members.                 00004   00004
I       - This line is in the "new" member, but not in the "old"                                                                          00005   00004

1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   2
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                              MEMBER SUMMARY LISTING  (LINE COMPARE)

CHNG MEMBERS - COMPARED  NEW-PROC OLD-PROC MATCHED NEW-INS OLD-DEL       REFM-LN   N-DP-LN   O-DP-LN

**      DATA                          5         4         2         2         1

        1  TOTAL MEMBER(S) PROCESSED AS A PDS
        1  TOTAL MEMBER(S) PROCESSED HAD CHANGES
        0  TOTAL MEMBER(S) PROCESSED HAD NO CHANGES
        2  TOTAL NEW FILE MEMBER(S) NOT PAIRED
        2  TOTAL OLD FILE MEMBER(S) NOT PAIRED
```

Figure 251. Side-by-side LINE comparison using the NARROW process option (Part 1 of 2)

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   3
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                              MEMBER SUMMARY LISTING (LINE COMPARE)

      NON-PAIRED NEW FILE MEMBERS          |       NON-PAIRED OLD FILE MEMBERS

                ABENEW                     |                ABEOLD
                WORDSNEW                   |               WORDSOLD

1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   4
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                              PDS LINE OVERALL TOTALS

          2   NUMBER OF LINE MATCHES          3   TOTAL CHANGES  (PAIRED+NONPAIRED CHNG)
          1   REFORMATTED LINES               2   PAIRED CHANGES (REFM+PAIRED INS/DEL)
          2   NEW FILE LINE INSERTIONS        1   NON-PAIRED INSERTS
          1   OLD FILE LINE DELETIONS         0   NON-PAIRED DELETES
          5   NEW FILE LINES PROCESSED
          4   OLD FILE LINES PROCESSED

LISTING - TYPE = LONG            COMPARE - COLUMNS =     1 : 80        LONGEST LINE = 80
PROCESS OPTIONS USED :  SEQ (DEFAULT) NARROW

* * SUPERC INFORM04 * *    LISTING LINES MAY BE TRUNCATED DUE TO LIMITING OUTPUT LINE WIDTH.
```

Figure 251. Side-by-side LINE comparison using the NARROW process option (Part 2 of 2)

Effect of File compare type on SuperC listings

Listing types are not applicable for the File compare type. The information included in a File compare listing depends on whether the data sets being compared are sequential/membered or partitioned, and on the process options or statements used, if any.

File comparison of a sequential data set or membered PDS

This type of comparison is usually the fastest because it shows you only the most basic information about two data sets or members. As Figure 252 shows, this information includes this information for the new and old data sets or members:

- Whether the data sets or members are different (DIFF) or the same (SAME), shown by asterisks
- The number of bytes (N-BYTES, O-BYTES) and lines (N-LINES, O-LINES)
- The hash sum values (N-HASH-SUM, O-HASH-SUM). These values are 32-bit numeric representations of the contents of the new and old data sets, respectively. The values shown in these fields provide a general indication of whether two data sets on two different systems are different. If the values are different, the two data sets are different. If the values are the same, the two data sets may be identical, but not necessarily.

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   1
 NEW:  USERID . TEST2 . SCRIPT(DATA)                                    OLD:  USERID . TEST1 . SCRIPT(DATA)

DIFF  SAME          N-BYTES          O-BYTES          N-LINES          O-LINES          N-HASH-SUM          O-HASH-SUM

      * *               400              400                5                5            8972446D            577EEEFA
```

Figure 252. File comparison of a membered PDS

File comparison of a complete PDS

This type of comparison includes the Member Summary Listing section. As the information about function keys in the ISPF User Interface topic in the *z/OS ISPF User's Guide Vol I* shows, the first information is the same as for a sequential/membered data set comparison, except the totals and hash sums are separated according to member name. Additional totals show how many members were:

- Processed and, of those, how many had changes
- Paired
- Not paired.

The names of the paired and non-paired members are listed at the bottom.

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   1
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                              MEMBER SUMMARY LISTING (FILE COMPARE)

DIFF   SAME          MEMBER-NAME        N-BYTES       O-BYTES       N-LINES       O-LINES       N-HASH-SUM       O-HASH-SUM

* *                  DATA                   400           400             5             5         8972446D         577EEEFA
                     --------------------  -------------  -------------  -------------  -------------  ----------------  ----------------
                     MEMBER TOTALS          400           400             5             5

              2
              1    TOTAL MEMBER(S) PROCESSED AS A PDS
              2    TOTAL MEMBER(S) PROCESSED HAD CHANGES
              1    TOTAL MEMBER(S) PROCESSED HAD NO CHANGES
              5    TOTAL NEW FILE MEMBER(S) NOT PAIRED
              4    TOTAL OLD FILE MEMBER(S) NOT PAIRED

1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   2
 NEW:  USERID . TEST2 . SCRIPT                                          OLD:  USERID . TEST1 . SCRIPT

                              MEMBER SUMMARY LISTING (FILE COMPARE)

                 NON-PAIRED NEW FILE MEMBERS        |        NON-PAIRED OLD FILE MEMBERS

                            ABENEW                  |                ABEOLD
                          WORDSNEW                  |              WORDSOLD
PROCESS OPTIONS USED:  APNDLST
```

Figure 253. File comparison of a complete PDS

Search-For listings

You can also produce listings by using the Search-For utility (option 3.14) and the Extended Search-For utility (option 3.15). A sample listing is shown in Figure 254.

```
1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   1
 LINE -#  SOURCE SECTION                                          SRCH DSN:  TEST2.SCRIPT


 DATA                 ----------------STRING(S) FOUND----------------

      3  This line is the same in both members.                                  00030000
      5  This line is the same in both members.                                  00050000

1    ISRSUPC - MVS/PDF FILE /LINE/WORD/BYTE/SFOR COMPARE UTILITY - ISPF FOR OS/390 1999/03/31       9.44       PAGE   2
              SUMMARY SECTION                                          SRCH DSN:  USERID.TEST2.SCRIPT

 LINES-FOUND   MEMBERS-W/LNS    MEMBERS-PROC    LINES-PROC     COMPARE-COLS    LONGEST-LINE
        2              1               3             60             1: 80            80


 THE FOLLOWING PROCESS STATEMENT(S) WERE PROCESSED:
      SRCHFOR    'This line is'
      SRCHFOR    'both members'
```

Figure 254. Search-For listing

This listing was produced by searching all the members of a PDS named USERID.TEST.SCRIPT and by using the **ASIS** fields on the Extended Search-For Utility panel, as follows:

```
ASIS . . . . 'This line is'
ASIS . . . . 'both members' c
```

PAGE 1 of the listing shows that both strings were found in lines 3 and 5 of member DATA. However, instead of just showing the strings that were being searched for, the listing shows each line in its entirety.

PAGE 2 shows this information:

- Two lines were found.
- One member of the PDS had lines that contained the search string.
- Three members of the PDS were searched and 60 of the lines those members contained were processed.
- In each member, columns 1 to 80 were searched.
- The longest line in any member was 80 bytes.

No process options were specified on the Extended Search-For Utility panel. However, the bottom of PAGE 2 shows that the SuperC program automatically used the SRCHFOR process option because a search was requested. The SRCHFORC process option also was used because the C (continuation) keyword was specified at the end of the second **ASIS** field.

Update data set control output examples

This topic provides examples of the process options that are used to create update data sets. You cannot enter two different process options that begin with UPD. These options are compare options only, for use with the SuperCE utility (option 3.13).

Each description except APNDUPD is accompanied by at least one sample update data set. All the samples were created by comparing member DATA, a PDS member common to both USERID.TEST1.SCRIPT and USERID.TEST2.SCRIPT. Figure 244 on page 512 shows the contents of this member in both PDSs.

Notes:

1. An update compare using the process options UPDCMS8 or UPDMVS8, that results in no differences found, creates an empty update output data set.
2. All “don’t process” options, and DPLINE or CMPLINE process statements are invalid when used with the process options UPDCMS8, UPDMVS8, UPDSEQ0, UPDLDEL, and UPDPDEL. The “don’t process” options are canceled with an error notification.

APNDUPD—append update data set

This process option appends the incremental results of the current compare to an existing update report. It allows you to collect multiple update results under one data set name. However, the width of the update data set being appended must be the same as the width of the original listing. Therefore, update options (UPDxxxx) that would change the width cannot be used with APNDUPD unless the original listing was produced by the same options.

The APNDUPD process option is available with the Line, Word, and Byte compare types.

UPDCMS8—update CMS sequenced 8

This process option produces a data set that contains both control statements and new data set source lines using sequence numbers from old data set columns 73-80. It is available with the Line compare type only.

All UPDCMS8 control statements are identified by the characters "./" in columns 1 and 2 of the 80-byte record, followed by one or more blanks and additional blank-delimited fields. The control statements are sequence (S), insert (I), delete (D), replace (R), and comment (*).

Data sets created with the UPDCMS8 process option can be used as input to the CMS UPDATE command, as described in *z/VM CMS Command and Utility Reference* and *z/VM CMS Macros and Functions Reference*. Figure 255 shows an example of an UPDCMS8 update data set.

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.CMS8(LINE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data ********************************
./ * NEW:  USERID.TEST2.SCRIPT(DATA)                          1999/02/24 17.34
./ * OLD:  USERID.TEST1.SCRIPT(DATA)
./ R 00010000 00010000 $ 00012990 00002990
This line is in the new member, but not in the old.                    00010000
This line is reformatted; the spacing in the new member differs.       00020000
./ R 00030000 00030000 $ 00034990 00004990
This line differs from the text in the old member.                     00040000
./ D 00050000 00050000 $ 00034990 00004990
./ R 00060000 00060000 $ 00034990 00004990
This line differs from the text in the old member.                     00070000
./ D 00080000 00080000 $ 00034990 00004990
./ R 00090000 00090000 $ 00034990 00004990
This line differs from the text in the old member.                     00100000
./ D 00110000 00110000 $ 00034990 00004990
./ R 00120000 00120000 $ 00034990 00004990
This line differs from the text in the old member.                     00130000
./ D 00140000 00140000 $ 00034990 00004990
./ R 00150000 00150000 $ 00034990 00004990
This line differs from the text in the old member.                     00160000
./ D 00170000 00170000 $ 00034990 00004990
./ R 00180000 00180000 $ 00034990 00004990
This line differs from the text in the old member.                     00190000
./ D 00200000 00200000 $ 00034990 00004990
./ R 00210000 00210000 $ 00034990 00004990
This line differs from the text in the old member.                     00220000
./ D 00230000 00230000 $ 00034990 00004990
./ R 00240000 00240000 $ 00034990 00004990
This line differs from the text in the old member.                     00250000
./ D 00260000 00260000 $ 00034990 00004990
./ R 00270000 00270000 $ 00034990 00004990
This line differs from the text in the old member.                     00280000
./ D 00290000 00290000 $ 00034990 00004990
./ R 00300000 00300000 $ 00034990 00004990
This line differs from the text in the old member.                     00310000
./ D 00320000 00320000 $ 00034990 00004990
./ R 00330000 00330000 $ 00034990 00004990
This line differs from the text in the old member.                     00340000
./ D 00350000 00350000 $ 00034990 00004990
./ R 00360000 00360000 $ 00034990 00004990
This line differs from the text in the old member.                     00370000
./ D 00380000 00380000 $ 00034990 00004990
./ R 00390000 00390000 $ 00034990 00004990
This line differs from the text in the old member.                     00400000
./ D 00410000 00410000 $ 00034990 00004990
./ R 00420000 00420000 $ 00034990 00004990
This line differs from the text in the old member.                     00430000
./ D 00440000 00440000 $ 00034990 00004990
./ R 00450000 00450000 $ 00034990 00004990
This line differs from the text in the old member.                     00460000
./ D 00470000 00470000 $ 00034990 00004990
./ R 00480000 00480000 $ 00034990 00004990
This line differs from the text in the old member.                     00490000
./ D 00500000 00500000 $ 00034990 00004990
./ R 00510000 00510000 $ 00034990 00004990
This line differs from the text in the old member.                     00520000
./ D 00530000 00530000 $ 00034990 00004990
./ R 00540000 00540000 $ 00034990 00004990
This line differs from the text in the old member.                     00550000
./ D 00560000 00560000 $ 00034990 00004990
./ R 00570000 00570000 $ 00034990 00004990
This line differs from the text in the old member.                     00580000
./ D 00590000 00590000 $ 00034990 00004990
./ R 00600000 00600000 $ 00034990 00004990
This line differs from the text in the old member.                     00610000
./ D 00620000 00620000 $ 00034990 00004990
./ R 00630000 00630000 $ 00034990 00004990
This line differs from the text in the old member.                     00640000
./ D 00650000 00650000 $ 00034990 00004990
./ R 00660000 00660000 $ 00034990 00004990
This line differs from the text in the old member.                     00670000
./ D 00680000 00680000 $ 00034990 00004990
./ R 00690000 00690000 $ 00034990 00004990
This line differs from the text in the old member.                     00700000
./ D 00710000 00710000 $ 00034990 00004990
./ R 00720000 00720000 $ 00034990 00004990
This line differs from the text in the old member.                     00730000
./ D 00740000 00740000 $ 00034990 00004990
./ R 00750000 00750000 $ 00034990 00004990
This line differs from the text in the old member.                     00760000
./ D 00770000 00770000 $ 00034990 00004990
./ R 00780000 00780000 $ 00034990 00004990
This line differs from the text in the old member.                     00790000
./ D 00800000 00800000 $ 00034990 00004990
./ R 00810000 00810000 $ 00034990 00004990
This line differs from the text in the old member.                     00820000
./ D 00830000 00830000 $ 00034990 00004990
./ R 00840000 00840000 $ 00034990 00004990
This line differs from the text in the old member.                     00850000
./ D 00860000 00860000 $ 00034990 00004990
./ R 00870000 00870000 $ 00034990 00004990
This line differs from the text in the old member.                     00880000
./ D 00890000 00890000 $ 00034990 00004990
./ R 00900000 00900000 $ 00034990 00004990
This line differs from the text in the old member.                     00910000
./ D 00920000 00920000 $ 00034990 00004990
./ R 00930000 00930000 $ 00034990 00004990
This line differs from the text in the old member.                     00940000
./ D 00950000 00950000 $ 00034990 00004990
./ R 00960000 00960000 $ 00034990 00004990
This line differs from the text in the old member.                     00970000
./ D 00980000 00980000 $ 00034990 00004990
./ R 00990000 00990000 $ 00034990 00004990
This line differs from the text in the old member.                     00980000
./ D 00990000 00990000 $ 00034990 00004990
./ R 00990000 00990000 $ 00034990 00004990
This line differs from the text in the old member.                     00990
```

UPDCNTL data set using line compare

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.CNTL(LINE) - 01.00          Line 00000000 Col 001 080
******************************** Top of Data ********************************
*    NEW:  USERID.TEST2.SCRIPT(DATA)                            1999/03/31 17.36
*    OLD:  USERID.TEST1.SCRIPT(DATA)
*  N-LINE-# O-LINE-# MAT-LEN  INS-LEN  DEL-LEN REFM-LEN
   00000001 00000001          00000001
   00000002 00000001                            00000001
   00000003 00000002 00000001
   00000004 00000003          00000001 00000001
   00000005 00000004 00000001
   00000006 00000005                   00000001
*  END




******************************* Bottom of Data ******************************

 Command ===> ___________________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 256. UPDCNTL data set using line compare

The top of Figure 256 shows the names of the new and old input data sets, along with the date and time the update data set was created. Table 28 shows the column numbers used to display the update information:

Table 28. UPDCNTL format using line compare

Column Numbers	Data Item
4-11	New line number
13-20	Old line number
22-29	Match length
31-38	Insert length
40-47	Delete length
49-56	Reformat length

UPDCNTL data set using word compare

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.CNTL(WORD) - 01.00          Line 00000000 Col 001 080
********************************** Top of Data **********************************
*    NEW:  USERID.TEST2.SCRIPT(DATA)                              1999/03/31 17.36
*    OLD:  USERID.TEST1.SCRIPT(DATA)
*  N-LINE-# N-LN-LEN N-COL WD-MAT-# N-WD-INS O-WD-DEL O-LINE-# O-LN-LEN O-COL
   00000001 00000001 00001          00000013
   00000002 00000001 00001 00000010                   00000001 00000001 00001
   00000002 00000001 00059          00000002 00000001 00000001 00000001 00064
   00000003 00000001 00001 00000008                   00000002 00000001 00001
   00000003 00000001 00040          00000001 00000001 00000002 00000001 00040
   00000004 00000001 00001 00000008                   00000003 00000001 00001
   00000004 00000001 00040          00000001 00000001 00000003 00000001 00040
   00000004 00000001 00046 00000001                   00000003 00000001 00046
   00000004 00000001 00054          00000001 00000001 00000003 00000001 00054
   00000005 00000001 00001 00000008                   00000004 00000001 00001
                                              00000013 00000004 00000002 00040
   00000005 00000001 00040 00000001                   00000005 00000001 00057
*  END
******************************** Bottom of Data ********************************
 Command ===> ______________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 257. UPDCNTL listing using word compare

The top of Figure 257 shows the names of the new and old input data sets, along with the date and time the update data set was created. Table 29 shows the column numbers used to display the update information:

Table 29. UPDCNTL format using word compare

Column Numbers	Data Item
4-11	Beginning new line number
13-20	Number of lines
22-26	New column number (beginning of word)
28-35	Number of matching words
37-44	Number of new inserted words
46-53	Number of old deleted words
55-62	Beginning old line number
64-71	Number of old lines
73-77	Old column number

UPDCNTL data set using byte compare

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.CNTL(BYTE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data ********************************
*    NEW:  USERID.TEST2.SCRIPT(DATA)                            1999/03/31 17.37
*    OLD:  USERID.TEST1.SCRIPT(DATA)
*  N-BYTE-O O-BYTE-O MAT-LEN  INS-LEN  DEL-LEN
   00000000 00000000          00000050
   00000050 00000000 0000001E
   0000006E 0000001E                   00000001
   0000006E 0000001F 00000008
   00000076 00000027                   00000001
   00000076 00000028 00000002
   00000078 0000002A                   00000001
   00000078 0000002B 00000004
   0000007C 0000002F                   00000001
   0000007C 00000030 00000007
   00000083 00000037                   00000001
   00000083 00000038 00000006
   00000089 0000003E                   00000001
******************************* Bottom of Data ********************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.CNTL(BYTE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data ********************************
   00000089 0000003F 00000009
   00000092 00000048          00000006
   00000098 00000048 00000003
   0000009B 0000004B          00000001 00000001
   0000009C 0000004C 0000004F
   000000EB 0000009B          00000001 00000001
   000000EC 0000009C 0000002C
   00000118 000000C8          00000003 00000003
   0000011B 000000CB 00000020
   0000013B 000000EB          00000001 00000001
   0000013C 000000EC 0000004F
   0000018B 0000013B                   00000050
   0000018B 0000018B 00000005
*  END

******************************* Bottom of Data ********************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 258. UPDCNTL listing using byte compare

The top of the first panel in Figure 258 shows the names of the new and old input data sets, along with the date and time the update data set was created. The second panel shows the result of scrolling down to see the remainder of the data set.

Table 30 on page 529 shows the column numbers used to display the update information:

Table 30. UPDCNTL format using byte compare

Column Numbers	Data Item
4-11	New byte offset
13-20	Old byte offset
22-29	Number of matching bytes
31-38	Number of inserted bytes
40-47	Number of deleted bytes

UPDMVS8—update MVS sequenced 8

This process option produces a data set that contains both control statements and new data set source lines using sequence numbers from old data set columns 73-80. This process option is available for the Line compare type only.

The format of the generated data may be suitable as input to the IEBUPDTE utility. See *z/OS DFSMSdfp Utilities* for information about the contents of this data set. Figure 259 shows an example of an UPDMVS8 update data set.

```
  Menu  Utilities  Compilers  Help
 --------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.MVS8(LINE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data ********************************
./  CHANGE LIST=ALL,NAME=DATA     OLD:USERID.TEST1.SCRIPT
This line is in the new member, but not in the old.                   00010000
This line is reformatted; the spacing in the new member differs.      00015000
This line differs from the text in the old member.                    00030000
./ DELETE  SEQ1=00050000,SEQ2=00050000









********************************* Bottom of Data *******************************
 Command ===> ______________________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 259. UPDMVS8 update data set listing

The data sets to be compared must have a record format of F 80. They must also contain sequence numbers.

UPDLDEL—update long source and delta data set

This process option produces a data set that contains both control statements, matching new data set source lines, inserted new data set source lines, and deleted old data set source lines. This process option is available for the Line compare type only.

The format of the generated data may be suitable for direct editing. Figure 260 on page 530 shows an example of an UPDLDEL update data set.

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.CNTL(LINE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data ********************************
*HDR1  NEW3.TEST.LIB              NEWMEM
*HDR2  LUDLOW.MACLIB.LIB          OLDMEM                      TYPE = UPDLDEL
*D-    DEL#=  2    N-REF#=000000 O-REF#=000001  *****SUPERC CHANGE HEADER*****
       This is line 1 in the old data set. It is not in the new data set.
       This is line 2 in the old data set. It is not in the new data set.
*M-    MAT#=  2    N-REF#=000001 O-REF#=000003  *****SUPERC CHANGE HEADER*****
       This is a line in both data sets.
       This is a line in both data sets.
*I-RP  INS#=  1    N-REF#=000003 O-REF#=000005  *****SUPERC CHANGE HEADER*****
       This is a line only in the new data set.
*D-RP  DEL#=  1    N-REF#=000003 O-REF#=000005  *****SUPERC CHANGE HEADER*****
       This is a line in both data sets.
*M-    MAT#=  1    N-REF#=000004 O-REF#=000006  *****SUPERC CHANGE HEADER*****
       This is a line in both data sets.
*I-RF  INS#=  1    N-REF#=000005 O-REF#=000007  *****SUPERC CHANGE HEADER*****
       This is a line in both data sets but reformatted.
******************************** Bottom of Data ******************************
 Command ===> ______________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 260. UPDLDEL update control data set

UPDPDEL—prefixed delta lines

This process option produces a data set that contains header records and complete delta lines from the input source data sets, up to a maximum of 32K columns in each output line. It is available for the Line compare type only.

The data set produced is a variable-length data set that reflects the characteristics of the input source data set. Prefix codes, such as `I` for insert, and the line number precede lines from the source data sets. Abbreviations show the total number of consecutive lines flagged as changed, such as `INS#=` for the number of consecutive inserted lines. The number of replaced lines (`RPL#=`) always refers to consecutive pairs of inserted and deleted lines. Figure 261 on page 531 shows an example of an UPDPDEL update data set. The first panel shows only the first 80 columns; the second panel shows the result of scrolling right to see the remainder of the member.

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.PDEL(LINE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data *********************************
*    NEW:  USERID.TEST2.SCRIPT(DATA)                          1999/03/31 17.38
*    OLD:  USERID.TEST1.SCRIPT(DATA)
*ID-   LINE#       SOURCE LINE
                                     INS#= 00000001
I - 00000001  This line is in the new member, but not in the old.
*                                    RPL#= 00000001                MAT#= 00000001
I - 00000004  This line differs from the text in the old member.
D - 00000003  This line differs from the text in the new member.
*                                                 DEL#= 00000001 MAT#= 00000001
D - 00000005  This line is in the old member, but not in the new.
*   END
******************************** Bottom of Data ********************************


 Command ===> _____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.PDEL(LINE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data *********************************
TEST2.SCRIPT(DATA)                                                1999/03/31 17.38
TEST1.SCRIPT(DATA)
 SOURCE LINE
                    INS#= 00000001
 line is in the new member, but not in the old.                     00010000
                    RPL#= 00000001                MAT#= 00000001
 line differs from the text in the old member.                      00040000
 line differs from the text in the new member.                      00030000
                                 DEL#= 00000001 MAT#= 00000001
 line is in the old member, but not in the new.                     00050000

******************************** Bottom of Data ********************************


 Command ===> _____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 261. UPDPDEL update data set listing

UPDREV—update revision

This process option produces an update file containing a copy of the *new* source text with revision tags delimiting the changed text lines.

The UPDREV process option supports two different types of revision tags: one for SCRIPT/VS data sets and one for BookMaster data sets. You use the REVREF process statement to specify which type of revision tag you want (see "REVREF—Revision Code Reference" on page 478). UPDREV is available for LINE and WORD compare types.

Figure 262 shows a SuperC UPDREV data set with SCRIPT/VS revision tags (.rc on/off).

```
.rc 1 |
.rc 1 on
This line is reformatted; the spacing in the "new" file differs.
.rc 1 off
This line is the same in both files.
.rc 1 on
This line differs from the text in the "old" file.
.rc 1 off
This line is the same in both files.
.rc 1 on
This line is in the "new" file, but not in the "old".
.rc 1 off
```

Figure 262. Example of a UPDREV update file for SCRIPT/VS documents

When the UPDREV update file in Figure 262 is subsequently processed by SCRIPT/VS, the final scripted output will have "`|`" revision characters in the left margin of the output document identifying the changed lines (those between the SCRIPT/VS revision tags `.rc 1 on` and `.rc 1 off`).

Note: The revision character ("`|`" in the example in Figure 262) can be specified either by using a REVREF process statement (see "REVREF—Revision Code Reference" on page 478) or by having a SCRIPT/VS `.rc` revision tag as the first record in the *new* data set. Subsequent changes to the source can therefore be separately identified by using different revision characters.

Figure 263 shows a SuperC UPDREV data set with BookMaster revision tags (:rev/:erev).

```
:rev refid=ABC.
This line is reformatted; the spacing in the "new" file differs.
:erev.
:rev refid=ABC.
This line is the same in both files.
:erev.
:rev refid=ABC.
This line differs from the text in the "old" file.
:erev.
:rev refid=ABC.
This line is the same in both files.
:erev.
:rev refid=ABC.
This line is in the "new" file, but not in the "old".
:erev.
```

Figure 263. Example of a UPDREV update data set for bookmaster documents

When the UPDREV update data set in Figure 263 is subsequently processed by BookMaster, the final formatted output will have the revision character associated with the revision ID `abc` (as specified by a `:revision.` BookMaster tag in the *new* input data set) in the left margin of the output document identifying the changed lines (those between the BookMaster revision tags `:rev` and `:erev`).

Note: The revision ID is controlled by the REVREF process statement (see "REVREF—Revision Code Reference" on page 478). Subsequent changes to the source can therefore be separately identified by using different revision IDs (which are associated with unique revision characters).

UPDREV2 - update revision (2)

UPDREV2 is identical to UPDREV with the exception that data between these BookMaster tags are not deleted in the update data set:

```
:cgraphic.
:ecgraphic.
:fig.
:efig.
:lblbox.
:elblbox.
:nt.
:ent.
:screen.
:escreen.
:xmp.
:exmp.
```

UPDSEQ0—update sequenced 0

This process option produces a control data set that relates insertions and deletions to the relative line numbers of the old data set. It is available for the Line compare type only. UPDSEQ0 is similar to UPDCMS8, but uses relative line numbers instead of sequence number columns from the old data set.

This update data set is characterized by control statements followed by source lines from the new data set. All UPDSEQ0 control statements are identified by the characters `./` in columns 1 and 2 of the 80-byte record, followed by one or more blanks and additional blank-delimited fields. The control statements are insert (I), delete (D), replace (R), and comment (*). Control statement data does not extend beyond column 50. Figure 264 shows an example of a UPDSEQ0 update data set listing.

```
  Menu  Utilities  Compilers  Help
 --------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.SEQ0(LINE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data *********************************
./ * NEW:  USERID.TEST2.SCRIPT(DATA)                            1999/03/13 17.39
./ * OLD:  USERID.TEST1.SCRIPT(DATA)
./ R 00000001 00000001 $ 00000002
This line is in the new member, but not in the old.                   00010000
This line is reformatted; the spacing in the new member differs.      00020000
./ R 00000003 00000003 $ 00000001
This line differs from the text in the old member.                    00040000
./ D 00000005 00000005 $ 00000000


******************************** Bottom of Data ********************************


 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 264. UPDSEQ0 update data set

UPDSUMO—update summary only

This process option produces an update data set of four lines: new data set name, old data set name, column headers, and a summary totals line. It is available for the Line, Word, and Byte compare types.

The summary totals line has a T in column 1. The summary statistics are located at fixed offsets in the output line. The data set has a line length of 132 bytes.

UPDSUMO data set using line compare

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.SUM0(LINE) - 01.00          Line 00000000 Col 001 080
********************************** Top of Data **********************************
*    NEW:  USERID.TEST2.SCRIPT                                 1999/03/31 17.40
*    OLD:  USERID.TEST1.SCRIPT
*  NEW-PROC OLD-PROC NEW-INS  OLD-DEL  TOT-CHG  TOT-RFM  FI-PROC  FI-DIFF  N-NOT
T  00000005 00000005 00000002 00000002 00000004 00000001 00000001 00000001 00000
******************************** Bottom of Data ********************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
 .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.SUM0(LINE) - 01.00          Line 00000000 Col 001 080
********************************** Top of Data **********************************
              87/02/24 17.40

RFM  FI-PROC  FI-DIFF  N-NOT-PD O-NOT-PD N-DP-LNS O-DP-LNS
0001 00000001 00000001 00000002 00000002 00000000 00000000
******************************** Bottom of Data ********************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 265. UPDSUMO data set using line compare

In Figure 265, the member is shown in split screen mode. The bottom half of the screen shows the result of scrolling right to see the remainder of the member. Table 31 shows the column numbers used to display the update information:

Table 31. UPDSUMO format using line compare

Column Numbers	Data Item
4-11	Number of new lines processed
13-20	Number of old lines processed
22-29	Number of new line insertions
31-38	Number of old line deletions
40-47	Total number of line changes
49-56	Total number of reformats
58-65	Total number of members processed
67-74	Total number of members different
76-83	Total new members not processed
85-92	Total old members not processed
94-101	Total number of new lines that are not to be processed
103-110	Total number of old lines that are not to be processed

UPDSUMO data set using word compare

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.SUM0(WORD) - 01.00          Line 00000000 Col 001 080
********************************** Top of Data **********************************
*    NEW:  USERID.TEST2.SCRIPT                                 1999/03/31 17.40
*    OLD:  USERID.TEST1.SCRIPT
*  NEW-PROC OLD-PROC NEW-INS  OLD-DEL  TOT-CHG          FI-PROC  FI-DIFF  N-NOT
T  00000054 00000053 00000017 00000016 00000030         00000001 00000001 00000
******************************** Bottom of Data *********************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
 .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.SUM0(WORD) - 01.00          Line 00000000 Col 001 080
********************************** Top of Data **********************************
              87/02/24 17.40

     FI-PROC  FI-DIFF  N-NOT-PD O-NOT-PD
     00000001 00000001 00000002 00000002
******************************** Bottom of Data *********************************
 Command ===> ____________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 266. UPDSUMO data set using word compare

In Figure 266, the member is shown in split screen mode. The bottom half of the screen shows the result of scrolling right to see the remainder of the member. Table 32 shows the column numbers used to display the update information:

Table 32. UPDSUMO format using word compare

Column Numbers	Data Item
4-11	Number of new words processed
13-20	Number of old words processed
22-29	Number of new word insertions
31-38	Number of old word deletions
40-47	Total number of word changes
49-56	Blank space. No reformat columns are represented in Word compare.
58-65	Total number of members processed
67-74	Total number of members different
76-83	Total new members not processed
85-92	Total old members not processed

UPDSUMO data set using byte compare

```
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.SUM0(BYTE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data ********************************
*    NEW:  USERID.TEST2.SCRIPT                                 1999/03/31 17.41
*    OLD:  USERID.TEST1.SCRIPT
*  NEW-PROC OLD-PROC NEW-INS  OLD-DEL  TOT-CHG          FI-PROC  FI-DIFF  N-NOT
T  00000400 00000400 00000092 00000092 00000178         00000001 00000001 00000
********************************* Bottom of Data *****************************
 Command ===> ____________________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
 .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
  Menu  Utilities  Compilers  Help
 ------------------------------------------------------------------------------
 BROWSE    USERID.UPDATE.SUM0(BYTE) - 01.00          Line 00000000 Col 001 080
********************************* Top of Data ********************************
              87/02/24 17.41

     FI-PROC  FI-DIFF  N-NOT-PD O-NOT-PD
     00000001 00000001 00000002 00000002
********************************* Bottom of Data *****************************
 Command ===> ____________________________________________________ Scroll ===> PAGE
  F1=Help    F2=Split   F3=Exit    F5=Rfind   F7=Up      F8=Down    F9=Swap
 F10=Left   F11=Right  F12=Cancel
```

Figure 267. UPDSUMO data set using byte compare

In Figure 267, the member is shown in split screen mode. The bottom half of the screen shows the result of scrolling right to see the remainder of the member. Table 33 shows the column numbers used to display the update information:

Table 33. UPDSUMO format using byte compare

Column Numbers	Data Item
4-11	Number of new bytes processed
13-20	Number of old bytes processed
22-29	Number of new byte insertions
31-38	Number of old byte deletions
40-47	Total number of byte changes
49-56	Blank space. No reformat columns are represented in Byte compare.
58-65	Total number of members processed
67-74	Total number of members different
76-83	Total new members not processed
85-92	Total old members not processed

Appendix C. Accessibility

Accessibility features help a user who has a physical disability, such as restricted mobility or limited vision, to use software products successfully. The major accessibility features in z/OS enable users to:

- Use assistive technologies such as screen readers and screen magnifier software
- Operate specific or equivalent features using only the keyboard
- Customize display attributes such as color, contrast, and font size

Using assistive technologies

Assistive technology products, such as screen readers, function with the user interfaces found in z/OS. Consult the assistive technology documentation for specific information when using such products to access z/OS interfaces.

Keyboard navigation of the user interface

Users can access z/OS user interfaces using TSO/E or ISPF. Refer to *z/OS TSO/E Primer*, *z/OS TSO/E User's Guide*, and *z/OS ISPF User's Guide Vol I* for information about accessing TSO/E and ISPF interfaces. These guides describe how to use TSO/E and ISPF, including the use of keyboard shortcuts or function keys (PF keys). Each guide includes the default settings for the PF keys and explains how to modify their functions.

z/OS information

z/OS information is accessible using screen readers with the BookServer/Library Server versions of z/OS books in the Internet library at:

`http://www.ibm.com/servers/eserver/zseries/zos/bkserv/`

© Copyright IBM Corp. 1980, 2007

Notices

This information was developed for products and services offered in the USA.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
USA

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

IBM World Trade Asia Corporation
Licensing
2-31 Roppongi 3-chome, Minato-ku
Tokyo 106, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:
INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

© Copyright IBM Corp. 1980, 2007

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Mail Station P300
2455 South Road
Poughkeepsie, NY 12601-5400
USA

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this information and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement, or any equivalent agreement between us.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrates programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. You may copy, modify, and distribute these sample programs in any form without payment to IBM for the purposes of developing, using, marketing, or distributing application programs conforming to IBM's application programming interfaces.

Programming Interface Information

This publication primarily documents information that is NOT intended to be used as Programming Interfaces of ISPF.

This publication also documents intended Programming Interfaces that allow the customer to write programs to obtain the services of ISPF. This information is identified where it occurs, either by an introductory statement to a chapter or section or by the following marking:

```
+---------------------Programming Interface information----------------------+


+------------------End of Programming Interface information------------------+
```

Trademarks

The following terms are trademarks of International Business Machines Corporation in the United States, other countries, or both:

AD/Cycle
APL2
BookManager
BookMaster
C++/MVS
COBOL/370
Common User Access
CUA
DB2
DFSMSdfp
DFSMSrmm
DFSORT
FFST
GDDM
IBM
Language Environment
MVS
MVS/XA
OS/390
RACF
SAA
Systems Application Architecture
Tivoli
VTAM
z/OS

Microsoft, Windows, and Windows NT are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Other company, product, and service names may be trademarks or service marks of others.

Index

Special characters

: (colon), using with function key definition 40
/ (data set name character), Data Set List utility (option 3.4) 154
.* Search-For process statement 482, 502
.IM control word 306
* Search-For process statement 482, 502
% field, Data Set List utility 153
%Used field, VTOC Summary Information panel 159
%USED keyword, SORT command 175
> (greater than)
  using with function key definition 41
| (SuperC listing prefix code) 516
&xxxxx action, ACTION column 195
= (repeat last command) line command, Data Set List utility (option 3.4) 168
= workstation command 430
"To" panel for copying 134
"To" panel for moving 136

Numerics

3850 virtual volumes
  allocating a data set to 117
5550 terminal 197

A

A (ANSI) parameter, Printer Carriage Control field 191
A (ASA printer characters) record format 119
accessibility 537
ACCOUNT command, TSO 117
ACCOUNT, TSO 96
ACTBAR workstation command 429
Action column 194
Activate/Create Profile DS Name field, SuperCE Profile Manager panel 223
AD/Cycle C/370 compiler
  batch processing 348
  batch processing (option 5.15) 348
  foreground processing 334
  foreground processing (option 4.15) 333
Additional IBM Program Development Products panel 403
Additional Input Libraries field, Foreground Print Options panel 309
address, APPC 62
address, TCP/IP 61
AFTER parameter
  Breakpoint Primary Option Menu 400
  When field 396
AIX (*AIX*) entry in Volume field 142
Alias action, Action column 195
Alias members, searching 507
Alias members, SuperC compare 507
ALL parameter
  FIND command 86
  Function field 392
  Variable field 393
ALLMEMS 444, 483
allocate action prompt workstation command 429
ALLOCATE command, TSO 116
allocate SMS workstation command 430
allocate workstation command 429
Allocation Error panel 121
allow mixed-case in action field option 194
Always save table in originating data set 244, 255
American National Standard Institute 191
ANYC Search-For process option 483
ANYC SuperCE process option 444
APF authorized status 288, 292
APNDLST Search-For process option 483
APNDLST SuperCE process option 445
APNDUPD SuperCE process option 445
APPC address
  definition 62
APPEND command
  Data Set List utility (option 3.4) 169
  parameters 169
Application ID field, Command Table Utility panel 193
ASCII 87
aspect ratio parameter for PRINTG 28
Assembler concatenation sequence 309
Assembler H (option 4.1) allocation data sets
  overview 311
Assembler H (option 5.1) 340
Assembler Options field
  Foreground Assembler H (option 4.1) 312
Attrib display view, Initial View field 144
audit information, z/OS UNIX 289

B

B (batch) parameter, Mode field
  Search-For Utility panel 227
  SuperC Utility panel 205
B (blocked) record format, Record Format field 119
B (browse) line command
  Data Set List utility (option 3.4) 162
  z/OS UNIX Directory List Utility (option 3.17) 274
Batch (option 5)
  AD/Cycle C/370 compiler (option 5.16) 348
  Assembler H (option 5.1) 340
Batch (option 5) *(continued)*
  C/370 compiler (option 5.13) 347
  JCL generation for Assembler and Linkage Editor 339
  JCL generation for compilers 338
  Linkage Editor (option 5.7) 344
  Member Parts List (option 5.12) 347
  overview 2
  password protection, lack of 337
  PL/I optimizing compiler (option 5.5) 342
  processing sequence 336
  VS COBOL II compiler (option 5.2) 341
  VS COBOL II interactive debug (option 5.10) 346
  VS FORTRAN compiler (option 5.3) 342
  VS Pascal compiler (option 5.6) 343
Batch Assembler H panel 340
Batch Linkage Edit panel 345
Batch Member Parts List panel 347
Batch options
  ISPDTLC 348
  OS/390 C/C++ 348
BATCH parameter, Print Mode field 181
Batch PL/I Optimizing Compile panel 343
Batch Selection panel 335
Batch Selection panel with JCL generated 338
Batch VS COBOL II Compile panel 341
Batch VS FORTRAN Compile panel 342
Batch VS Pascal Compile panel 344
BEFORE parameter
  Breakpoint Primary Option Menu 400
  When field 396
Binary copy option 278, 281, 283, 285
Blank action, Action column 195
Blank lines after headings (in export report) 257
blank parameter
  Active field
    breakpoints 396
    function traces 392
    variable traces 394
  DSORG field 153
  Operation field 394
  Pool field 393
  Printer Carriage Control field 191
  Select Pack option for "To" data set field 135
  Sequence Numbers field 208
  Specify additional search strings field 227
  When field 396
blank, SuperC prefix code 516
BLKS parameter, Space Units field 118
BLKSZ
  field 153

© Copyright IBM Corp. 1980, 2007

BLKSZ *(continued)*
keyword 175
SORT command 175
Block size field, Allocate New Data Set panel 119
bottom-of-listing information, SuperC 519
breakpoints
defined 394
with qualification parameter values 397
Breakpoints (option 7.8)
Cancel (option C) 399
CANCEL primary command 396
control display 398
D (delete) line command 396
END primary command 396, 398
finding a breakpoint 399
Go (option G) 399
I (insert) line command 396
input errors 398
LOCATE primary command 396
primary command 396
QUAL primary command 396
qualification 398
qualification parameter values 396
R (repeat) line command 396
specifying breakpoints 395
syntax checking 398
Breakpoints panel 395
Browse
providing Unicode support 80
BROWSE command
BROWSE 81
COLUMNS 82
DISPLAY 82
displaying after processing 81
FIND 85
HEX 89
LOCATE 91
overview 81
parameter member 81
RESET 92
SUBMIT 81, 92
Browse Command - Entry Panel 82
Browse data display panel 80
Browse field, SCRIPT/VS Processor panel 320
Browse hexadecimal display
data 91
vertical 90
Browse Mode
Browse data display 80
current position in data set 91
ending Browse 81
overview 1, 81
selecting Browse 80
valid logical record length 78
valid record format 77
BROWSE Output field, SuperCE Utility panel 217
browse output mode 205, 217, 227, 236
Browse table command 241, 242
browse table panel 243
Browse workstation command 429
Byte parameter, Compare Type field 215

C

C (catalog data set) line command, Data Set List Utility (option 3.4) 165
C (continuation) keyword, Search-For utility (option 3.14) 229
C or CO (copy out) line command
z/OS UNIX Directory List Utility (option 3.17) 277
C/370 compiler
batch processing (option 5.13) 347
foreground processing (option 4.13) 333
C/C++ for OS/390 (option 4.19) 334
CALL statement format 329
CANCEL command
Breakpoints (option 7.8) 396
Command Table utility (option 3.9) 196
Dialog Test (option 7) 360
table utility 246
Tables (option 7.4) 379, 381
Traces (option 7.7) 393
Variables (option 7.3) 370
CANCEL, Traces (option 7.7) 394
catalog workstation command 429
CATALOG, Sort command field 175
CC parameter, DISPLAY command 83
CCSID
Unicode support in Browse 80
CCSID parameter, DISPLAY command 83
change bar, defined for SuperC 516
char parameter, DISPLAY command 83
character string 87
character string, LOCATE 361
CHARS parameter, FIND command 85
CHG operation 394
CHNG parameter, Listing Type field 207, 215
CHNG SuperC process statement 456
CHNGV SuperC process statement 456
CI (copy in) line command
z/OS UNIX Directory List Utility (option 3.17) 282
CKPACKL Search-For process option 483
CKPACKL SuperCE process option 445
Class field, Outlist Utility panel 190
Client/Server component download option 185
Client/Server download 187
CLIST
error exits 352
CLIST TERMIN command procedure statements 352
closing a data set 81
CMD field 364
CMPBOFS process statement operands 457
CMPCOLM Search-For process statement 488
CMPCOLM SuperC process statement 458
CMPCOLMN SuperC process statement 458
CMPCOLMO SuperC process statement 458
CMPLINE Search-For process statement 489
CMPLINE SuperC process statement 459
CMPSECT SuperC process statement 461
CNPML SuperCE process option 445
COBOL Interactive debug (option 4.10A)
overview 325
print output data sets 327
processing sequence 326
symbolic debug data sets 327
COBOL Interactive Debug panel 326
COBOL parameter, Sequence Numbers field 208
COBOL Search-for process option 483
COBOL SuperCE process option 445
col-1 and col-2 parameters, FIND command 85
COLOR
change defaults 51
Color used to display table key values 243, 256
COLS parameter, DISPLAY command 83
column limitations 88
column-identification line
defined 82
removing with RESET command 92
COLUMNS command, Browse 82
Command (option 6)
interrupting a TSO command, CLIST, or REXX exec 352
overview 2
restrictions for entering a CLIST or REXX exec 352
Session Manager, using 352
terminal settings 353
TSO commands, CLISTs, and REXX EXECs, entering 351
command action prompt workstation command 429
Command field, display view panels 152
command line placement, specifying 24
command prefix (&), displaying commands after processing 81
command stacking
specifying delimiter 30
Command Table Editing panel 194
command table line commands
edit 196
view 196
Command Table utility (option 3.9)
line commands
D (delete) 196
I (insert) 196
R (repeat) 196
primary commands
CANCEL 196
END 196
Command Table Utility panel 193
command time limit
z/OS UNIX directory list 297
commands
Dialog Test 359
displaying after processing 81
entering long commands 349

commands *(continued)*
ISPF command shell 424
line 2
primary 2
TSO command 422
Workplace 429
WS command 423
Compare Type field, SuperCE Utility panel 214
Compare types, SuperC
Byte 215
File 214
Line 215
Word 215
compress request exit 104, 165
compress workstation command 430
Cond parameter, Browse Output field 217
CONFIRM command 169
Data Set List utility (option 3.4) 169
parameters
OFF 169
ON 169
Confirm Delete field, Data Set List Utility panel 144
Confirm Delete panel 124
confirm member delete 144
Confirm Purge panel 125
conversion table
copying z/OS UNIX files 279, 281, 283, 286
COPY command 166
Copy Format Selection List panel 201
copy member 112
COPY statement 306
Copy workstation command 429
Created field
Data Set List utility 153
CREATED keyword, SORT command 175
CSECT compare, Superc 508
CUA
defaults
function key settings 430
CUA attributes workstation command 429
CUA attributes... 55
CUA panel element default values 55
CUA panel element values (changing) 54
CUAATTR option, Change Utility 55
CYLS parameter, Space Units field 118

D

D (DBCS) parameter, Field Type field 199
D (delete lines)
Command Table utility (option 3.9) 196
Data Set List utility (option 3.4) 164
Dialog Test (option 7) 361
Format Specification utility (option 3.11) 202
SCRIPT/VS (option 4.9) 323
D (delete) line command
Breakpoints (option 7.8) 396
D (delete) line command *(continued)*
Tables (option 7.4) 379, 381
Variables (option 7.3) 370
z/OS UNIX Directory List Utility (option 3.17) 276
D (SuperC listing prefix code) 516
DA data set organization, DSORG field 153
DASD volume 96
Data class field, Allocate New Data Set panel 117
DATA parameter
HEX command 89
data set allocation exit 116
data set control blocks 159
Data Set download 188
Data Set Information panel
long format 105
long format for managed data sets 107
short format 109
short format for managed data sets 110
data set list primary commands
CONFIRM 169
EXCLUDE 169
FIND and RFIND 170
LOCATE 171
MEMBER 171
REFRESH 172
RESET 172
SAVE 172
SHOWCMD 173
SORT 174
SRCHFOR 175
VA,VS,VT,VV 176
Data Set List utility (option 3.4)
data set list exit 140
display views and panels
Attrib 144, 149
sequence of display views 143
Space 143, 149
Total 144, 150
Volume 143, 147
line commands
= (repeat last command) 168
B (browse data set) 162
C (catalog data set) 150, 165
D (delete data set) 164
E (edit data set) 161
F (free unused space) 165
I (data set information) 164
M (display member list) 162
P (print data set) 165
R (rename data set) 164
S (information (short)) 165
U (uncatalog data set) 165
V (view data set) 162
X (print index listing) 166
Z (compress data set) 165
line commands that do not support managed data sets
C (catalog data set) 165
U (uncatalog data set) 165
line commands that support managed data sets
I (data set information) 164
Data Set List utility (option 3.4) *(continued)*
line commands that support managed data sets *(continued)*
R (rename data set) 164
S (information (short)) 165
X (print index listing) 166
list data set 172
options
blank - display data set list 146
P - Print data set list 158
PV - Print VTOC information 160
V - Display VTOC information 158
primary commands
CONFIRM 169
FIND 170
LOCATE 171
RFIND 170
SAVE 172
SHOWCMD 173
SORT 174
data set list utility line commands
copy 166
exclude data set 166
move 166
RefAdd 166
reset 166
Search-For 167
Search-ForE 167
SuperC 166
SuperCE 167
unexclude data set 166
unexclude first data set 166
unexclude last data set 166
Data Set List Utility panel 139
Data Set List Utility Primary Commands 168
Data Set List Utility SHOWCMD panel 174
Data Set Name field
Foreground Member Parts List panel 331
SuperC Submit Batch Jobs panel 210
data set organization 153
Data Set Password 97
Data Set utility (option 3.2)
options
A - Allocate new data set 114
blank - data set information 126
C - Catalog data set 121
D - Delete entire data set 123
R - Rename entire data set 122
S - Data set information (short) 126
U - Uncatalog data set 123
options that do not support managed data sets
C - Catalog data set 121
U - Uncatalog data set 123
options that support managed data sets
blank - Data set information 126
R - Rename entire data set 122
S - Data set information (short) 126

Data Set utility (option 3.2) *(continued)*
processing with RACF
D - Delete 125
R - Rename 122
R - rename entire data set (GDG) 122
DAU data set organization, DSORG field 153
DBCS considerations, SuperC 204
DBCS data, copying 278, 281, 283, 285
DC (SuperC listing prefix code) 516
DDDD format, Expiration Date field 119
Debug command data set field 346
Debug Options field, Foreground FORTRAN interactive debug (option 4.11) 329
default keylist for Help Panels 38
delete action prompt workstation command 429
DELETE command, TSO 144, 169
delete compose, defined for SuperC 516
delete matching, defined for SuperC 516
delete replace, defined for SuperC 516
Delete workstation command 429
delete, defined for SuperC 516
DELETE, Traces (option 7.7) 393, 394
Delta parameter, Listing Type field 207, 215
Description column 195
Description field, SCRIPT/VS Formatting Style panel 323
Device Data information, z/OS UNIX 289
Device field, Data Set List utility 153
DEVICE keyword, SORT command 175
device name parameter for PRINTG 28
DFSMSdfp
striped data set type 106, 110
Dialog Function/Selection Panel, invoking 363
Dialog Services (option 7.6), calling a dialog service 387
dialog test
accessing and updating variables 357
available ISPF facilities 357
breakpoint cancel (option C) 355
environment 355
ISPF log generation 357
message displayed for severe errors 359
NEWPOOL option 358
severe error found at breakpoint 358
Dialog Test
DBCS value format 374
log entry for current value of variable 387
modifying a table row 378
reasons errors occur 359
variable usage 358
Dialog Test (option 7)
Breakpoints (option 7.8) 394
commands 359
D (delete lines) 361
Dialog Services (option 7.6) 387
environment 399
exceptions to restoration when using Go (option G) 399
Exit (option 7.X) 401
Dialog Test (option 7) *(continued)*
Functions (option 7.1) 362
I (insert lines) 361
Log (option 7.5) 385
overview 2
Panels (option 7.2) 366
R (repeat lines) 361
severe error handling 358
Traces (option 7.7) 390
Tutorial (option 7.T) 401
variable usage 358
Variables (option 7.3) 368
Dialog Test Primary Option Panel 356
Directory blocks field, Allocate New Data Set panel 118
Directory List Options panel, z/OS UNIX 297
disability 537
DISALLOW_WILDCARDS_IN_HLQ option 141
Display Area field 254
DISPLAY command
Browse 82
parameters 83
Display Directory List option, z/OS UNIX 265
Display mode for export data set 256
Display Style Options field, SCRIPT/VS Processor panel 320
distributed editing 67, 98
DLMDUP SuperCE process option 446
DLREFM SuperCE process option 446
DM (SuperC listing prefix code) 516
Document Composition Facility (DCF) 318
double-byte character set (DBCS)
column specification in dialog test 375
defining data type 199
Dialog Test variables format 372
finding a 1-byte hexadecimal string 89
Format Specification utility (option 3.11) 197
ISPF editor 99
DPACMT Search-For process option 483
DPACMT SuperCE process option 446
DPADCMT Search-For process option 483
DPADCMT SuperCE process option 446
DPBLKCL Search-For process option 484
DPBLKCL SuperCE process option 446
DPCBCMT Search-For process option 484
DPCBCMT SuperCE process option 447
DPFTCMT Search-For process option 484
DPFTCMT SuperCE process option 447
DPLINE Search-for process statement 490
DPLINE SuperC process statement 465
DPLINEC Search-For process statement 490
DPLINEC SuperCE process statement 465
DPPLCMT Search-For process option 484
DPPLCMT SuperCE process option 447
DPPSCMT Search-For process option 484
DPPSCMT SuperCE process option 447
DR (SuperC listing prefix code) 516
DS1-DS4 fields
Extended Search-For - Concatenation Data Set Entry panel 235
SuperCE - Concatenation Interactive Entry panel 218
DSLIST exit 140
DSLIST workstation command 429
Dsname Level field, Data Set List Utility panel 140
Dsorg field, Data Set List utility 153
DSORG keyword, SORT command 175
DTEST system command 356

E

E (EBCDIC) parameter, Field Type field 199
E (edit data set) line command, Data Set List utility (option 3.4) 161
edit
double-byte character set support 99
Edit (option 2)
editing a data set 95
overview 2
valid logical record length 95
valid record format 95
edit action prompt workstation command 429
EDIT command, Browse 84
Edit Entry Panel 95
EDIT primary command
z/OS UNIX directory list 293
Edit table command 241, 242
edit table panel 243
Edit workstation command 429
edit, command table line command 196
edit, distributed 67, 98
editing a member 112
END
Traces (option 7.7) 393, 394
END command
Breakpoints (option 7.8) 396, 398
Command Table utility (option 3.9) 196
Dialog Test (option 7) 361
Variables (option 7.3) 370
Enter Session Manager Mode field 352
Environ settings 57
ENVIRON system command 57
environment, Dialog Test 355
errors
message displayed during dialog test processing 359
reasons for occurring during Dialog Test 359
trigger statement 308
EXCLUDE command 169
Exclude Data Set command 166
Execution Parms field
COBOL interactive debug 327

Exit (option 7.X) ending Dialog Test 401
Exit (option X)
overview 3
EXPAND primary command 244
Expanding Packed Data 305
expansion trigger, defined 305
Expiration data field, Allocate New Data Set panel 119
Expires field, Data Set List utility 153
EXPIRES keyword, SORT command 175
explosion chain, defined 333
EXPORT command 247
export table to data set 259
data set attributes 258
export data set 248
Export Layout panel 247
export report options 256, 260
EXTENDED
data set name type 106, 110
Extended Attributes information, z/OS UNIX 288
extended binary coded decimal interchange code (EBCDIC)
defining data type 199
using numbered data 199
Extended Search-For - Concatenation Batch Entry panel 236
Extended Search-For - Concatenation Data Set Entry panel 235
Extended Search-For Compare utility
applications 441
options
B - submit batch search-for 235
Blank - search-for strings 235
E - edit Search-For statements data set 237
P - select Search-For process options 237
overview 231
process options 443
process statements 453
return codes 503
SuperC program description 440
utility differences 439
Extended Search-For process statements, notation conventions 487
Extended Search-For Utility panel 232
extended utilities 439
extension variables 244

F

F (foreground) parameter, Mode field 204
F (foreground) parameter, Mode field, Search-For Utility panel 227
F (free unused space) line command, Data Set List utility (option 3.4) 165
F (function) pool, Pool field 393
F record format, Record Format field 119
false match, correcting in SuperC 506
false match, defined for SuperC 519
family printer type parameter for PRINTG 28
FEXPORT command 249
field 396
field *(continued)*
Active 392, 394, 396
AFTER 400
Application 400
BEFORE 400
Breakpoint 400
by row number 374
BY ROW NUMBER 374
current row 374
Current row count 383, 385
Current row pointer 382, 384
Current status 400
Cursor field 367
Cursor position 367
Date created 383, 384
DBCS column specification 375
Dialog services to be traced 392
Display in window 367
Function 392, 394, 396, 400
ID 366
KEYS 382
LANG 364
Last date modified 383, 384
Last modified by 383, 385
Last service return code 384
Last table service 384
Last time modified 383, 384
Message id 367
Message pop-up field 367
MODE 365
Modified row count 383, 385
NAMES 382
NEWAPPL 366
NEWPOOL 366
Number of keys 382
Number of names 382
Number of rows 382
Open option 384
Open tables 374
Operation 394
Original row count 383, 385
P (pool) 370
PANEL 364
Panel name 367
PASSLIB 366
PGM 365
Pool 393
Qual 396
Qualification parameter values 397
Return code 400
row identification 374
Row number 377
Service 396
Service Name 400
specifying a DBCS value 374
Status for this screen 383, 384
Table available 383
table name 374
Table name 377
Table on disk 384
Time created 383, 384
Update count 383, 385
using the Value field 374
variable 374
Variable 370, 378
Virtual storage size 383, 385
When 396
field *(continued)*
WSCMD 365
Field Heading field, table utility 247
Field Length field, Format Definition panel 199
Field Number field, Format Definition panel 199
Field Type field, Format Definition panel 199
field1 parameter, SORT command 174
field2 parameter, SORT command 174
FILE command, table utility 248
File comparison of a complete PDS 522
File comparison of a sequential data set or membered PDS 522
File parameter, Compare Type field 214
FILEXFER service 188
FIND command 170
ASCII strings 87
Browse
1-byte hexadecimal strings 89
character strings, use of 87
column limitations 88
conditions for character string matches 87
displaying column numbers searched 86
omitting string delimiters 86
picture strings, use of 88
rules for using col-1 and col-2 88
specifying FIND strings 85
starting point, direction, and extent of search 86
string not found actions 86
text strings, use of 87
using RFIND 89
using string delimiters 86
search operands 85, 86
string matching operands 85
table utility 249
USASCII strings 87
UTF8 strings 87
FIND primary command
z/OS UNIX directory list 293
FIRST parameter, FIND command 86
FMVLNS SuperCE process option 447
Foreground (option 4)
AD/Cycle C/370 compiler (option 4.15) 333
AD/Cycle C/370 compiler (option 4.16) 334
Assembler H (option 4.1) 311
C/370 compiler (option 4.13) 333
COBOL interactive debug (option 4.10A) 325
defined 301
expanding packed data 305
FORTRAN interactive debug (option 4.11) 328
input data sets 308
Linkage Editor (option 4.7) 316
list data sets 309
Members Parts List (option 4.12) 329
object data sets 310
overview 2
password protection 310

Foreground (option 4) *(continued)*
PL/I optimizing compiler (option 4.5) 314
processing sequence 302
REXX/370 compiler (option 4.14) 333
SCRIPT/VS (option 4.9) 318
using the TSO/E Information Center Facility 311
VS COBOL II compiler (option 4.2) 312
VS COBOL II interactive debug (option 4.10) 325
VS FORTRAN compiler (option 4.3) 313
VS Pascal compiler (option 4.6) 315
Foreground Assembler H panel 312
Foreground Environment Feature 318
Foreground Linkage Edit panel 317
Foreground Members Parts List panel 330
Foreground Options
C/C++ for OS/390 334
ISPDTLC 334
Foreground PL/I Optimizing Compile panel 315
Foreground Print Options for Style panel 321
Foreground Print Options panel 304, 311
Foreground Selection panel 301
Foreground VS COBOL II Compile panel 313
Foreground VS FORTRAN Compile panel 314
Foreground VS Pascal Compile panel 316
Format Definition panel 199
Format Name field
Format Specification panel 198
Format Selection List panel 201
Format Specification panel 197
Format Specification utility (option 3.11)
line commands
D (deleting a format) 202
R (renaming a format) 202
S (selecting a format) 202
U (updating a format) 202
options
A - add a new format 198
C - copy formats 199
D - delete a format 201
L or Blank - display format list 201
U - update a format 201
primary commands
LOCATE 202
SORT 202
FORTRAN interactive debug (option 4.11) 328
FORTRAN Interactive Debug panel 329
Free DSCBS field, VTOC Information Display 159
Free Extents field, VTOC Information Display 159
From Format field, Format Specification panel 198
From Table field, Format Specification panel 159, 198
FSCR parameter, MODE field 365
full information workstation command 429
function key defaults, workplace 430
function key settings, workplace 430
function keys
defining functions 39
specifying labels 39
specifying number 49
Functions (option 7.1), testing a dialog function 362

G

Generate headings (in export report) 257
generic unit address 117
GET operation 394
global color change utility 52
global color change workstation command 429
global GUI color change utility 53
graphics interface mode, effect on Session Manager 302
graphics, settings parameters for PRINTG 28
Groups For Primary Members field
Foreground Member Parts List panel 331
Member Parts List Display 333
GUI Installation, ISPF C/S Install Utility 185
GUI parameters, specifying 58
GWCBL SuperCE process option 448

H

Hardcopy utility (option 3.6)
additional batch printing information 183
using the TSO/E Information Center Facility 183
Hardcopy Utility panel
after JCL generation 182
before JCL generation 180
with the TSO/E Information Center Facility installed 184
hashsum, defined 522
HELP command
displaying column numbers searched 86
HEX command
Browse 89
operands
DATA 89
OFF 89
ON 89
VERT 89
hexadecimal data, Dialog Test variables format 372
HFS
data set name type 106, 110
high-level qualifier
wildcards in 141

I

I (data set information) line command, Data Set List utility (option 3.4) 164
I (implicit) variable, P (pool) field 370
I (information) line command
z/OS UNIX Directory List Utility (option 3.17) 286
I (insert lines), Dialog Test (option 7) 361
I (insert) line command
Breakpoints (option 7.8) 396
Tables (option 7.4) 379, 381
Variables (option 7.3) 370
I (insert) line command, Command Table utility (option 3.9) 196
I (SuperC listing prefix code) 516
IBM Products (option 9)
overview 2
IC (SuperC listing prefix code) 516
IDPFX Search-For process option 485
IEBCOPY utility 104, 165
IEBGENER utility 183
If Partitioned, Replace Like-Named Members field 134
If Sequential, "To" Data Set Disposition field 135
IM (SuperC listing prefix code) 516
image path 66
implicit variable 370
import table from data set 259
Include Additional Qualifiers (in data set list) 144
INCLUDE statement 306
inconsistent attributes, defined 121
information action prompt workstation command 429
Information Center Facility
foreground processing sequence 304
Hardcopy utility 180
Outlist utility 191
information, bottom-of-listing 519
Initial Macro field, Edit Entry panel 78
Initial View field
defined 143
views
Attrib 144
sequence of views 143
Space 143
Total 144
Volume 143
input data sets 308
INSERT command 250
insert compose, defined for SuperC 516
insert matching, defined for SuperC 516
insert, defined for SuperC 516
INSERT, Traces (option 7.7) 393, 394
Installation
Download Data Set to Workstation 185
installation exits
compress request 104, 165
data set allocation 116
data set list (DSLIST) 140
print utility 180, 191, 304
Installation program
Workstation agent 188

integration program, workstation tool 67
Intensity used to display table key values 244, 256
IS data set organization, DSORG field 153
ISPCMDS 192
ISPDTLC (option 4.18) 334
ISPDTLC compile, batch 348
ISPDTLC interface panel 334
ISPF
  default keylist 38
  restrictions
    multivolume data sets 117, 140
    tape 117, 160
ISPF C/S download 187
ISPF C/S download utility
  C/S method 187
ISPF C/S Install option 185
ISPF C/S Install Utility
  ISPFINST.EXE 188
ISPF C/S Installation 185
ISPF Command field 349
ISPF command shell 424
ISPF Command Shell panel 349
ISPF command shell workstation command 429
ISPF command table workstation command 429
ISPF Primary Option Menu - status area 5
ISPF referral list
  Workplace (Option 11) 409
ISPF restrictions
  multivolume data sets 117, 140
  tape 117, 160
ISPF Settings (option 0), overview 1
ISPF Table Utility 238
ISPFINST.EXE 188
ISPTLIB 192
ISRFORM table 199
ISRLEMX
  description 306
  member parts list 329
  return codes 308
ISRSCAN
  description 306
  member parts list 339
  return codes 308
ISU data set organization, DSORG field 153

J

JCL generation
  Assembler and Linkage Editor 339
  compilers 338
job control language, generating and submitting print jobs 181
job statement information
  preventing JES line counting 322
job stream, submitting a 81, 92
JobID field, Outlist Utility panel 190
Jobname field, Outlist Utility panel 190
jump function, from leader dots 26

K

K (key) variable 376, 378, 380
KB parameter, Space Units field 118
keyboard 537
keylist
  defaults for Help Panels 38
  help panel name 46
  modification choices 44
keylist utility 38
keylist workstation command 429
keys 38
  PA1 352
  Reset 352

L

L (List) line command
  z/OS UNIX Directory List Utility (option 3.17) 276
label fields
  defining 41
  using PFSHOW command 41
label parameter, LOCATE command 91
Language field, Foreground Member Parts List panel 330
LARGE
  data set name type 106, 110
large files, partitioning and processing in SuperC 506
Largest field, VTOC Information Display 159
LAST parameter, FIND command 86
LC command 170
LC command, Data Set List utility (option 3.4) 170
leader dots, and jump function 26
LEFT primary command
  z/OS UNIX directory list 294
Library utility (option 3.1)
  options
    B - browse member 111
    Blank - display member list 103
    C - compress data set 103
    D - delete member 112
    E - edit member 112
    I - data set information 104
    L - print entire data set 104
    P - print member 112
    R - rename member 112
    S - data set information (short) 108
    V - view member 113
    X - print index listing 104
  options that support managed data sets
    I - data set information 107
    S - data set information (short) 109
    X - print index listing 104
Library Utility panel 102
LINE - Dialog Test (option 7) 361
Line Cmd field, SCRIPT/VS Formatting Style panel 323
line command prefix characters
  z/OS UNIX directory list 271
line commands
  Command Table utility (option 3.9) 196
  Data Set List utility (option 3.4) 154, 160
  defined 2
  Format Specification utility (option 3.11) 202
  SCRIPT/VS (option 4.9) 323
Line parameter, Compare Type field 215
LINE parameter, DISPLAY command 83
LINE parameter, MODE field 365
line-number operand, LOCATE command 91
Linkage Editor (option 4.7)
  concatenation sequence 318
  LEL control statements 318
  overview 316
Linkage Editor (option 5.7) 344
Linkage Editor concatenation sequence 318
Linkage Editor language 318
Linkage Editor Options field, Foreground Linkage Editor (option 4.7) 317
list action prompt workstation command 429
list data set
  list-id 172
  prefix 172
  specifying characteristics 35
  specifying defaults 32
List ID field
  Batch Selection Panel 337
  Foreground Print Options panel 309
  Foreground Selection panel 303
list view workstation command 429
list-id parameter
  SAVE command 172
Listing DS Name field
  Extended Search-For Utility panel 234
  SuperC Utility-Old Data Set Name panel 207
Listing Dsn field, SuperCE Utility panel 215
Listing DSNAME field, Search-For Utility panel 227
listing title lines, SuperC 515
Listing Type field
  SuperC Utility-Old Data Set Name panel 207
  SuperCE Utility panel 215
listing, SuperC member summary 518
listings, Search-for 523
listings, side-by-side 520
LMCSFC SuperCE process option 448
LMTO Search-For process option 485
LNCT Search-For process statement 492
LNCT SuperC process statement 467
LNFMTO Search-For process statement 485
load module library display
  expanded line command field 164
Local parameter, Print Mode field 181
Local Printer ID field, Hardcopy Utility panel 181

LOCATE
Dialog Test (option 7) 361
Traces (option 7.7) 393, 394
LOCATE character string 361
LOCATE command 171
Breakpoints (option 7.8) 396
Browse 91
Data Set List utility (option 3.4) 171
Format Specification utility (option 3.11) 202
parameters
label 91
line-number 91
lparm 171
name 202
Variables (option 7.3) 370
LOCATE primary command
z/OS UNIX directory list 294
Locate table command 241, 243
locate workstation command 429
LOCS SuperCE process option 448
Log (option 7.5)
displaying the ISPF log 385
logged trace output 386
reasons log is not available 386
log data set
specifying defaults 32
Log/List (option 0)
changing defaults 3
long message
line placement 26
specifying 26
long message areas, displaying in a pop-up 26
LONG parameter, Listing Type field 207, 215
LONGLN Search-For process option 485
LONGLN SuperCE process option 448
LookAt message retrieval tool xiv
lowercase, defining parameters in 194
lparm parameter, LOCATE command 171
LPSF Search-For process option 485
LPSFV Search-For process statement 493
Lrecl field, Data Set List utility 153
LRECL keyword, SORT command 175
LSTCOLM Search-For process statement 494
LSTCOLM SuperC process statement 468
LTO Search-For process option 485

M

M (display member list) line command, Data Set List utility (option 3.4) 162
M (machine) parameter, Printer Carriage Control field 191
M (mixed) parameter, Field Type field 199
M record format, Record Format field 119
managed data set
displaying information for 107
Management class field, Allocate New Data Set panel 116
match compose, defined for SuperC 516
match, defined for SuperC 516
matching input files, SuperC 505
Maximum rows searched to determine column width 244, 255
MB parameter, Space Units field 118
MC (SuperC listing prefix code) 516
member
copy from z/OS UNIX file 277
copy to z/OS UNIX file 282
MEMBER command
description 171
member expansion return codes 308
member list display
expanded line command field 163
Member list workstation command 429
member not found 333
member parameter
BROWSE command 81
SYSTERM DD statement 340
Member Parts List (option 4.12)
CALL statement format 329
member not found 333
options
1 - browse/print member parts list 331
2 - write member parts data set 332
overview 329
Procedure Division 330
record format 332
Member Parts List (option 5.12) 347
member parts list display 332
member summary listing, SuperC 518
membered PDS, defined 206
Message field, display view panels 152
MESSAGE keyword, SORT command 175
message retrieval tool, LookAt xiv
mixed case, defining parameters in 194
mixed data
B (browse data set) line command 162
defining data type 199
E (edit data set) line command 161
using numbered data 199
V (view data set) line command 162
Mixed Mode 98
MIXED Search-For process option 485
MIXED SuperCE process option 448
MM (modify mode) line command
z/OS UNIX Directory List Utility (option 3.17) 291
Mod parameter, “To” Data Set Disposition field 135
Mode field
Search-For Utility panel 227
SuperC Utility panel 204
mode fields information, z/OS UNIX 288
Mode, Mixed 98
MOUNT authority 117
MOVE command 166
move member 112
Move workstation command 429
move/copy 426
Move/Copy utility (option 3.3)
alias entries 138
Move/Copy utility (option 3.3) *(continued)*
options
C and CP - copying data sets 133
M and MP - moving data sets 135
with load modules 137
Move/Copy Utility panel 132
Multiple Search Strings panel 228
multiple search strings, entering 228
multivol indicator 153
multivolume data sets 117, 140
MVOL, Sort command field 175
MX (modify extended attributes) line command
z/OS UNIX Directory List Utility (option 3.17) 291

N

N (new) line command
z/OS UNIX Directory List Utility (option 3.17) 275
Name field
display view panels 152
NAME keyword
LOCATE command 202
SORT command 175, 202
name, Writer 181
NARROW Super CE process option 448
NCHGT Search-For process statement 495
NCHGT SuperC process statement 469
new data set, defined for SuperC
description 203
examples 511
used with SuperCE 213
New DS Name field, SuperCE Utility panel 214
New Output Class field, Outlist Utility panel 191
New UserID field, Reset ISPF Statistics panel 177
New Version Number field, Reset ISPF Statistics panel 178
NEWAPPL field 366
NEWPOOL field 366
NEXT parameter, FIND command 86
NO parameter
Active field
breakpoints 396
function traces 392
variable traces 394
Browse Output field 217
Confirm Delete Request field, deselect 144
Replace like-named PDS members field 134
Select pack option For “To” data set field 135
Specify additional search strings field, deselect 227
Table available field 383
Table on disk field 384
NOACTBAR workstation command 429
NOCC parameter, DISPLAY command 83

Nolist parameter, Listing Type field 207, 215
non-paired change, defined for SuperC 519
non-paired members, defined for SuperC 518
NOP action, ACTION column 195
NOPRTCC Search-For process option 485
NOPRTCC SuperCE process option 449
NOSEQ parameter, Sequence Numbers field 208
NOSEQ Search-For process option 486
NOSEQ SuperCE process option 449
NOSUMS Search-For process option 486
NOSUMS SuperCE process option 449
NOT OPEN parameter 383, 384
Notices 539
NOWRITE parameter 384
NTITLE SuperC process statement 473, 497
Number of Copies field, Hardcopy Utility panel 184

O

object data sets 310
Object field
  Foreground VS FORTRAN compiler (option 4.3) 314
OBROWSE command
  browsing z/OS UNIX regular file 274
OCHGT SuperC process statement 469
OEDIT command
  editing z/OS UNIX regular file 274, 293
OFF parameter
  CONFIRM command 169
  HEX command 89
  SHOWCMD command 173
OGET command
  copying z/OS UNIX file to a data set 278
  copying z/OS UNIX file to PDS member 279
old data set, defined for SuperC 511
Old DS Name field, SuperCE Utility panel 214
Old parameter, "To" Data Set Disposition file 135
ON parameter
  CONFIRM command 169
  HEX command 89
  SHOWCMD command 173
Open option field
  NOWRITE parameter 384
  SHR NOWRITE parameter 384
  SHR WRITE parameter 384
  WRITE parameter 384
OPEN parameter 383, 384
Open table in SHARE mode 255
Open workstation command 429
OPT field 364
option
  Cancel (option C) 399
  Go (option G) 399
option selection
  0 - ISPF Settings 1
  1 - View 1
  10 - SCLM 2
  2 - Edit 2
  3 - Utilities 2
  4 - Foreground 2
  5 - Batch 2
  6 - Command 2
  7 - Dialog Test 2
  9 - IBM Products 2
  X - Exit 3
Options pull-down menu, switching UIDs 299
options, table utility 255
OPUT command
  copying member to z/OS UNIX file 284
Order field, table utility 247, 251
OS/390 C/C++ compile, batch 348
Other field
  Batch Assembler H (option 5.1) 341
  Batch Linkage Editor (option 5.7) 345
  Batch VS COBOL II compiler (option 5.2) 341
  Batch VS FORTRAN compiler (option 5.3) 342
  Foreground PL/I optimizing compiler (option 4.5) 315
  Foreground VS COBOL II compiler (option 4.2) 313
  Foreground VS FORTRAN compiler (option 4.3) 314
  Foreground VS Pascal compiler (option 4.6) 316
OTITLE SuperC process statement 473, 497
OUTDD DD field, SuperC Submit Batch Jobs panel 211
Outlist utility (option 3.8)
  options
    Blank - display job output 192
    D - delete job output from SYSOUT hold queue 191
    L - list job names/IDs via the TSO STATUS command 191
    P - print job output and delete from SYSOUT hold queue 191
    R - requeue job output to a new output class 192
Outlist Utility panel 190
overview of ISPF
  ISPF primary options 1
OVSUM listing type
  File comparison of a complete PDS 522
  File comparison of a sequential data set or membered PDS 522
OVSUM parameter, Listing Type field 207, 215
owner information, z/OS UNIX 288, 290

P

P (print) line command
  Data Set List utility (option 3.4) 165
P (profile) pool, Pool field 393
P (profile) variable, P (pool) field 370
PA1 key 352
packed data
  defined 305
packing data, Foreground (option 4) 302
pad characters for panel input fields 30
paired change, defined for SuperC 519
paired members, defined for SuperC 519
panel
  Add Row 380
  Breakpoint Primary Option 398
  confirm table row delete 377
  Dialog Test Tutorial 401
  Display 366
  display row 376
  Function Traces 392
  Invoke Dialog Service 388
  Message Display 368
  modify row 378
  Special Display 390
  Table Structure 382
  Traces 391
  Variable Traces 393
  Variables 369
panels
  data set list display view panels
    ATTRIB view panel 149
    Space view panel 149
    Total view panel 150
    VOLUME view panel 147
  load module library display
    expanded line command field 164
  member list display
    expanded line command field 163
  Tables 373
  working with dialog tables 373
Panels (option 7.2), testing dialog panels 366
parameter
  parenthesis added to 195
parameter string 397
parenthesis, added to command parameter 195
PARM field 365
partitioned data set
  copy from files in z/OS UNIX directory 279
  copy to files in z/OS UNIX directory 283
partitioning and processing in SuperC, large files 506
PASSLIB field 366
Passthru action
  Action column 195
Password field
  Foreground Data Entry panel 310
  Foreground Selection panel 303
password protection 310
Password, Data Set 97
PATH (*PATH*) entry in Volume field 142
path name substitution character
  z/OS UNIX directory list 297
patterns
  Dsname Level field 140

PDS Member List field
defined 214
parameters 233
permissions, display in octal format 298
personal data set lists command 429
personal library lists command 429
Pgm Control status 289, 292
physical record length, defined 119
picture strings, use of 88
PL/I optimizing compiler
batch (option 5.5) 342
foreground (option 4.5) 314
PO data set organization, DSORG field 153
point and shoot workstation command 430
POU data set organization, Dsorg field 153
prefix parameter
data set list to ISPF list data set 172
FIND command 85
SYSTERM DD statement 340
PREFIX parameter, FIND command 85
PREV parameter, FIND command 86
primary commands
Browse 81
CANCEL 360
Command Table utility (option 3.9) 196
Data Set List utility (option 3.4) 168
defined 2
END 361
Format Specification utility (option 3.11) 202
LOCATE 361
QUAL 361
RESUME 361
SU 299
Primary Commands, Data Set List Utility 168
primary library, defined 333
primary member, defined 333
Primary quantity field, Allocate New Data Set panel 118
print action prompt workstation command 430
print data set command 429
print data set index workstation command 430
Print data set list workstation command 430
Print Directory List option, z/OS UNIX 273
Print ID field, COBOL Interactive Debug panel 326, 327
Print Mode field
parameters
BATCH parameter 181
LOCAL parameter 181
SCRIPT/VS Processor panel 321
print output data sets 327
print utility exit
foreground processing sequence 304
Hardcopy utility 180
Outlist utility 191
Print VTOC information workstation command 430
Print workstation command 429
Printer Carriage Control field, Outlist Utility panel 191
Printer Format field, Hardcopy Utility panel 184
Printer Location field, Hardcopy Utility panel 184
PRINTG
parameters 28
specifying printer output 28
printing
Extended Search-For listing in batch mode 236
output 180
SuperCE listing in batch mode 219
Procedure Division 330
Process Options field
Extended Search-For Utility panel 234
SuperCE Utility panel 216
process options, Search-For 483
process statements, Search-For 486
Profile DSN field, SuperC Utility panel 204
Profile Name field, Edit Entry Panel 79
profile, defined for SuperCE 204
Prog ID field, COBOL Interactive Debug panel 326
PROMPT, Sort command field 175
PS data set organization, DSORG field 153
PS-E 153
PS-L 153
PSU data set organization, Dsorg field 153
Purge Data Set field, Confirm Purge panel 125
PUT operation 394

Q

QUAL
command - Breakpoints (option 7.8) 396
Dialog Test (option 7) 361
qualification parameter values
Qualify action bar pull-down
Breakpoints... choice 396
Qualifications... choice 396

R

R (rename) line command
Data Set List utility (option 3.4) 164
Format Specification utility (option 3.11) 202
z/OS UNIX Directory List Utility (option 3.17) 277
R (repeat lines), Dialog Test (option 7) 361
R (repeat) line command
Breakpoints (option 7.8) 396
Command Table utility 196
Tables (option 7.4) 379, 381
RACF, processing with
D - delete 125
RACF, processing with *(continued)*
R - rename 122
Recfm field, Data Set List utility 153
RECFM keyword, SORT command 175
Record format field, Allocate New Data Set panel 118
Record length field, Allocate New Data Set panel 119
RefAdd command 166
Referred field, Data Set List utility 154
REFERRED keyword, SORT command 175
REFMOVR SuperCE process option 449
reformat new, defined for SuperC 516
reformat old, defined for SuperC 516
REFRESH command 172
REFRESH primary command
z/OS UNIX directory list 295
rename 427
rename action prompt workstation command 430
rename data set with expiration date 123
rename processing with RACF 122
rename workstation command 429
Rename workstation command 430
renaming data sets
with expiration date 123
REPEAT, Traces (option 7.7) 393, 394
reset action prompt workstation command 429
RESET command 166, 172
Browse 92
Reset ISPF Statistics panel 177
Reset ISPF Statistics utility (option 3.5)
options
D - delete ISPF statistics 179
R - reset (create/update) ISPF statistics 179
results of resetting statistics 179
valid logical record lengths 176
RESET key
restriction 41
reset member 112
Reset Mod Level field, Reset ISPF Statistics panel 178
RESET parameter, DISPLAY command 84
RESET primary command
z/OS UNIX directory list 295
Reset Seq Numbers field, Reset ISPF Statistics panel 178
reset statistics 421
restrictions on member expansion and member parts lists
all programming languages 306
assembler 307
COBOL 307
FORTRAN 307
Pascal 307
PL/I 307
SCRIPT/VS 308
RESUME - Dialog Test (option 7) 361
return codes
Batch JCL generation 308, 339
member expansion 308
SuperC 503

REXX error exits 352
REXX/370 compiler
batch processing 347
foreground processing 333
RFIND command 170
Data Set List utility (option 3.4) 170
table utility 250
using 89
RFIND primary command
z/OS UNIX directory list 293
RIGHT primary command
z/OS UNIX directory list 295
RN (SuperC listing prefix code) 516
Rnn parameter 396
RO (SuperC listing prefix code) 516
rules
for substituting slash (/) for data set name 155
for using the col-1 and col-2 operands 88
service call image for function trace entries 387
using the add row option 380
using the Dialog Test Breakpoints option 398
using the Modify Row option 378
Run method 293

S

S (information (short)) line command, Data Set List utility (option 3.4) 165
S (select) line command
Format Specification utility (option 3.11) 202
SCRIPT/VS (option 4.9) 323
S (shared) pool, Pool field 393
S (shared) variable, P (pool) field 370
S record format, Record Format field 119
SAVE command 172
Data Set List utility (option 3.4) 172
parameters
list-id 172
name 203
table utility 250
SAVE primary command
z/OS UNIX directory list 295
SCLM (option 10)
overview 2, 405
SCLM Primary Option Menu 405
SCLM Setting 135
SCLM Settings 178
screen format, specifying 27
SCRIPT/VS (option 4.9) 319
changing style options 323
line commands
D (delete) 323
S (select) 323
selecting a formatting style 322
using the TSO/E Information Center Facility 324, 325
SCRIPT/VS Options for Style panel 324
SCRIPT/VS Processor panel 319
scrollable fields, in Table Utility 247
Scrollable fields, in Table Utility 244
SDUPM Search-For process option 486
Search DS Name field, Extended Search-For Utility panel 232
Search Member List panel 230
Search String field, Search-For Utility panel 226
search strings, multiple 228
Search-For command 167
Search-For listings, SuperC 523
Search-For process options 483
Search-For process statements 486
Search-For Process Statements panel 238
Search-For Utility - Submit Batch Jobs panel 231
Search-For utility (option 3.14)
applications 441
invoking directly 508
process options
ANYC (any case) 483
APNDLST (appends the listing to a data set) 483
CKPACKL 483
COBOL (ignore columns 1-6) 483
DPACMT (ignore comment lines) 483
DPADCMT (ignore ADA type comments) 483
DPBLKCL (ignore blank lines) 484
DPCBCMT (ignore COBOL type comments) 484
DPFTCMT (ignore FORTRAN type comments) 484
DPPLCMT (ignore PL/I type comments) 484
DPPSCMT (ignore PASCAL type comments) 484
IDPFX (identifier prefixed) 485
LMTO (list group members totals only) 485
LNFMTO (list not found member/data set totals only) 485
LONGLN (long lines) 485
LPSF (list previous Search-For following lines) 485
LTO (list totals only) 485
MIXED 485
NOPRTCC (no printer control columns) 485
NOSEQ (no sequence numbers - they do not exist) 486
NOSUMS (no summary listing section) 486
SDUPM (search duplicate members) 486
SEQ (sequence numbers - ignore columns 73-80) 486
XREF (cross reference strings) 486
process statements
CMPCOLM (compare columns) 488
CMPLINE (compare lines) 489
DPLINE (don't process lines) 490
DPLINEC (continuation condition of DPLINE) 490
LNCT (line count) 492
LPSFV (count value) 493
Search-For utility (option 3.14) *(continued)*
process statements *(continued)*
LSTCOLM (list columns) 494
NCHGT (change text of new text string) 495
SELECT (select members/data sets to be searched) 498
SLIST (statements data set listing control) 499
SRCHFOR (Search-For strings in the input data sets) 500
SRCHFORC (continuation condition of SRCHFOR) 500
return codes 503
selecting members from a member list 229
SuperC program description 440
utility differences 439
Search-For Utility panel 226
Search-ForE command 167
SearchFor extended workstation command 430
SearchFor workstation command 430
Secondary quantity field, Allocate New Data Set panel 118
Select action, Action column 195
SELECT command
Format Specification utility (option 3.11) 202
Select SCRIPT/VS Formatting Style panel 323
SELECT Search-For process statement 498
SELECT service 356
SELECT SuperC process statement 479
select workstation command 430
SEQ parameter, Sequence Numbers field 208
SEQ Search-For process option 486
SEQ SuperCE process option 449
Sequence field, table utility 251
Sequence Numbers field, SuperC Utility - Old Data Set Name panel 208
sequential data set
copy from z/OS UNIX file 277
copy to z/OS UNIX file 282
Serial, Volume 96
Session Manager
Command (option 6) 352
Foreground (option 4) 302
Member Parts List (option 4.12) 331
SCRIPT/VS 320
using 352
Set options for IMPORT format report 257
SETGID bit 288, 291
Settings option 23
Settings workstation command 430
SETUID bit 288, 291
SETVERB action
Action column 195
shared library status 289, 292
shared profile settings 58
shift-in characters
in Dialog Test variables 372
using the Value field 374

shift-out characters
in Dialog Test variables 372
using the Value field 374
short information command 430
shortcut keys 537
SHOWCMD command 173
Data Set List utility (option 3.4) 173
parameters
OFF 173
ON 173
SHR NOWRITE parameter 384
SHR WRITE parameter 384
SHRPROF system command 58
side-by-side listings, SuperC 520
Size field
VTOC Information Display 159
SLIST process statement
Search-For 499
SuperC 480
smart action 434
Software Configuration and Library Manager (SCLM) 405
SORT command 174
Data Set List utility (option 3.4) 174
Format Specification utility (option 3.11) 202
keywords
%USED 175
BLKSZ 175
CREATED 175
DEVICE 175
DSORG 175
EXPIRES 175
LRECL 175
MESSAGE 175
NAME 175
RECFM 175
REFERRED 175
TRACKS 175
VOLUME 175
XT 175
parameters
field1 174
field2 174
NAME 202
TIME 202
table utility 251
SORT primary command
z/OS UNIX directory list 296
source data for SuperC listings 512
Source Data Online field, Batch Selection panel 336
Source Data Packed field
Batch Selection panel 336
Foreground Print Options panel 305
Foreground Selection panel 302
Source field, COBOL Interactive Debug panel 327
Source Type field, Foreground Selection panel 303
Space display view, Initial View field 143
Space units field, Allocate New Data Set panel 118
Specify additional strings field, Search-For Utility panel 227
Specify Pack option for "To" Data Set field 135
split-screen mode
command line placement 25
SRCHFOR command, Data Set List utility (option 3.4) 175
SRCHFOR Search-For process statement 500
SRCHFORC Search-For process statement 500
standard Search-For utility, entering multiple search strings 228
standard utilities 439
Start Column field 199
starting a GUI session
from Settings (option 0) 60
Statements Dsn field
Extended Search-For Utility panel 234
SuperCE Utility panel 216
statistics
creating or resetting 179
STATS command 251
status area - ISPF Primary Option Menu 5
status area - Primary Option Menu
calendar view 10
Defining 13
function key view 9
No view selected 13
point-and-shoot view 12
session view 6
user view 12
Status for Table panel
table not open 383
table open 384
sticky bit 288, 291
Storage class field, Allocate New Data Set panel 116
string parameter
FIND command 85
STRUCT command 253
Style field
SCRIPT/VS Formatting Style panel 323
SCRIPT/VS Processor panel 319
style, defined for SCRIPT/VS 319
SU primary command 299
z/OS UNIX directory list 297
SUBMIT command, BROWSE 81, 92
Submit workstation command 429
submitting a job stream 81, 92
suffix
add to file name 284
strip from file name 281
SUFFIX parameter, FIND command 87
Superc
CSECT compare 508
SuperC Activate/Create Profile options
A - activate 223
C - create 223
D - default 224
SuperC alias members 507
SuperC CLIST interface 224
SuperC command 166
SuperC compare types
Byte 215
SuperC compare types *(continued)*
different comparison results 507
File 214
Line 215
Word 215
SuperC Compare utility
correcting false matches 506
different comparison results 507
filtering priority for input lines 504
find match example 505
invoking directly 508
partitioning and processing large files 506
process statements
allowed by compare type, table 455
CHNG 456
CHNGV 456
CMPBOFS 457
CMPCOLM 458
CMPCOLMN 458
CMPCOLMO 458
CMPLINE 459
CMPSECT 461
DPLINE 465
DPLINEC 465
LNCT 467
LSTCOLM 468
NCHGT 469
NTITLE 473, 497
OCHGT 469
OTITLE 473, 497
SELECT 479
SLIST 480
SuperC comparison process options
COVSUM 445
DPCPCMT 447, 484
DPMACMT 447, 484
FINDALL 485
FMSTOP 447, 485
UPDREV 451
UPDREV2 451
Y2DTONLY 452
SuperC comparison process statements
end-position (NEXCLUDE operand) 471
end-position (NFOCUS operand) 472
end-position (OEXCLUDE operand) 471
end-position (OFOCUS operand) 472
fixed (Y2PAST operand) 481
RCVAL=number (REVREF operand) 478
REFID=name (REVREF operand) 478
sliding (Y2PAST operand) 481
start-position (NEXCLUDE operand) 471
start-position (NFOCUS operand) 472
start-position (OEXCLUDE operand) 471
start-position (OFOCUS operand) 472
SuperC Defaults panel 225
SuperC extended workstation command 430
SuperC listing prefix codes 516

SuperC listing source data 512
SuperC listing types
CHNG 207, 215
Delta 207, 215
Long 207, 215
Nolist 207, 215
OVSUM 207, 215
SuperC listings
overview 511
prefix codes 516
source and index listings 511
SuperC load module compares 508
SuperC Member List panel 209
SuperC process options
APNDUPD 524
UPDCMS8 525
UPDCNTL 525
UPDMVS8 529
UPDPDEL 530
UPDSEQ0 533
UPDSUMO 534
SuperC Process Statements panel 221
SuperC program, requirements for 440
SuperC programming interface 224
SuperC search process options
DPCPCMT 447, 484
DPMACMT 447, 484
FINDALL 485
FMSTOP 447, 485
SuperC type-of-difference codes
LEN 517
N-LN# and O-LN# 517
types 516
SuperC update files
UPDREV 531, 532
UPDREV2 Revision File (2) 533
SuperC Utility - Submit Batch Jobs panel
overview 210
using NOLIST 212
SuperC utility (option 3.12)
applications 441
new data set 203
old data set 206
printing a Search-For listing in batch mode 230
printing a SuperC listing in batch mode 209
process options 443
process statements 453
program description 440
return codes 503
specifying members on a member list 208
submit options
1 - generate output listing in DATA SET NAME 210
2 - generate output listing using completed //OUTDD DD 211
blank - generate output listing to SYSOUT CLASS 210
utility differences 439
SuperC Utility panel 203
SuperC utility, requirements for 440
SuperC workstation command 430
SuperC, DBCS considerations 204
SuperCE - Concatenation Batch Entry panel 219
SuperCE - Concatenation Interactive Entry panel 218
SuperCE - Profile Manager panel
option A - Activate 223
option C - Create 223
option D - Defaults 224
SuperCE command 167
SuperCE Compare utility
CKPACKL 445
UPDLDEL Long source and Delta data set 529
UPDLDEL prefixed Delta data set 530
SuperCE process statements, notation conventions 453
SuperCE Profile Browse Display panel 222
SuperCE utility (option 3.13)
applications 441
options
A - activate profiles and defaults 221
B - submit batch data set compare 218
Blank - compare data sets 217
E - edit SuperCE statements data set 220
P - select process options 443
P - select SuperCE process options 219
S - Extended Search-For utility 231
process options
ANYC (any case) 444
APNDLST (appends the listing to a data set) 445
APNDUPD (append update output) 445
CKPACKL (check for packed data) 445
CNPML (count non-paired member lines) 445
COBOL (ignore columns 1-6) 445
DLMDUP (don't list matching duplicate lines) 446
DLREFM (don't list old data set reformatted lines) 446
DPACMT (ignore comment lines) 446
DPADCMT (ignore ADA type comments) 446
DPBLKCL (ignore blank lines) 446
DPCBCMT (ignore COBOL type comments) 447
DPFTCMT (ignore FORTRAN type comments) 447
DPPLCMT (ignore PL/I type comments) 447
DPPSCMT (ignore PASCAL type comments) 447
FMVLNS (flagged moved lines) 447
GWCBL (generate change bars) 448
LMCSFC (list name, number of bytes, and hash sum) 448
SuperCE utility (option 3.13) *(continued)*
process options *(continued)*
LOCS (list only changed members or data sets) 448
LONGLN (create listing with 203 columns) 448
MIXED 448
NARROW (create listing with 132 columns) 448
NOPRTCC (no printer control columns) 449
NOSEQ (no sequence numbers--they do not exist) 449
NOSUMS (no summary listing section) 449
overview 443
REFMOVR (reformat override) 449
SEQ (sequence numbers--ignore columns 73-80) 449
UPDCMS8 (update CMS 8 format) 449
UPDCNTL (update control) 450
UPDLDEL (source data set with delta changes) 450
UPDMVS8 (update MVS 8 format) 451
UPDPDEL (update prefix delta lines) 451
UPDSEQ0 (update sequence 0) 452
UPDSUMO (update summary only) 452
WIDE (side-by-side list with 202 columns) 452
XWDCMP (extended word compare) 452
process statements 453
return codes 503
SuperC program description 440
SuperCE utility 213
utility differences 439
SuperCE Utility panel 213
symbolic debug data sets 327
symbolic link information, z/OS UNIX 290
SYSLIB field
Batch Linkage Editor (option 5.7) 345
Foreground Linkage Editor (option 4.7) 317
SYSLIN field
Batch Linkage Editor (option 5.7) 345
Foreground Linkage Editor (option 4.7) 317
SYSOUT Class field
Batch Selection panel 337
Hardcopy Utility panel 181
SuperC - Submit Batch Jobs panel 210
system command table 192
system commands
DTEST 356
SYSTERM DD statement, parameters
member 340
prefix 340

T

T (truncation) column 194
T (variable types) field
  K (key) variable
    add row 380
    delete row 378
    display row 376
  N (name) variable
    add row 380
    delete row 378
    display row 376
  S (save) variable
    add row 380
    delete row 378
    display row 376
T record format, Allocate New Data Set panel 119
table
  date created/modified 252
  editing/browsing
    See ISPF Table Utility
  export to data set 247, 259
  find string in 249
  import from data set 259
  insert blank row 250
  processing if already open 260
  saving changes 244, 250
  size (virtual storage required) 252
  sorting rows 251
  status 253
  structure, displaying 253
table input library 192
Table List panel 241, 242
Table statistics, displaying 251
Table structure, displaying 253
Table Utility (option 3.16)
  Browse command 241, 242
  CANCEL (table changes) command 246
  Edit command 241, 242
  EXPORT command 247
  export report 256, 260
  export to data set 259
  extension variables 244
  FEXPORT command 249
  FILE command 248
  find string in table 249
  import from data set 259
  INSERT command 250
  options 255
  output data set 254
  overview 238
  panel fields 239
  performance 244
  SAVE (table changes) command 250
  saving changes 244
  scrollable fields 244, 247
  scrolling 243
  select table from DD list 242
  select table from library 240
  sorting rows 251
  STATS command 251
  table structure, displaying 253
  tables already open 260
Table Utility Options panel 255
Tables (option 7.4)
  1—display row 375
Tables (option 7.4) *(continued)*
  2—delete row options 376
  3—modify row 377
  4—add row 379
  5—display structure 381
  6—display status 382
  add row line command 381
  CANCEL add row primary command 381
  CANCEL modify row primary command 379
  D (delete) add row line command 381
  D (delete) modify row line command 379
  END add row primary command 381
  END display row command 376
  END modify row primary command 379
  I (insert) add row line command 381
  I (insert) modify row line command 379
  LOCATE add row primary command 381
  LOCATE display row command 376
  LOCATE display structure command 382
  LOCATE modify row primary command 379
  R (repeat) add row line command 381
  R (repeat) modify row line command 379
tape 117, 140
TCP/IP address
  definition 61
TERMIN command procedure statements 352
terminal characteristics, specifying 27
terminal data set, defined 340
terminal type, specifying 27
terminals
  Batch Assembler H (option 5.1) 340
  Batch Linkage Editor (option 5.7) 345
  Batch VS COBOL II compiler (option 5.2) 341
  Batch VS FORTRAN compiler (option 5.3) 342
Test field
  Foreground VS COBOL II compiler (option 4.2) 313
testing
  dialogs 355
  TSO 355
  usual test methods for dialog 355
text strings, use of 87
TIME parameter, SORT command 202
tool integration program 67
Total display view, Initial View field 144
trace output in ISPF log
  function trace entries 386
  trace header entries 386
  variable trace entries 387
Traces (option 7.7)
  1—function traces 391
  2—variable traces 393
Traces (option 7.7) *(continued)*
  CANCEL Function Traces primary command 393
  CANCEL Variable Traces primary command 394
  D (delete) Function Traces line command 393
  D (delete) Variable Traces line command 394
  END Function Traces primary command 393
  END Variable Traces primary command 394
  I (insert) Function Traces line command 393
  I (insert) Variable Traces line command 394
  LOCATE Function Traces primary command 393
  LOCATE Variable Traces primary command 394
  R (repeat) Function Traces line command 393
  R (repeat) Variable Traces line command 394
  working with trace specifications 390
Tracks field
  Data Set List utility 153
  VTOC Information Display 159
TRACKS keyword, SORT command 175
trigger statement errors 308
triggers
  expansion trigger, definition 305
  statement errors 308
  user-defined 306
TRKS parameter, Space Units field 118
Trks/Cyls field, VTOC Information Display 159
TSO
  CLISTs and REXX EXECs
    Data Set List utility (option 3.4) 154
    entering 351
    variables 156, 157
  commands
    ACCOUNT 117
    ALLOCATE 116
    DELETE 169
  TEST 355
TSO ACCOUNT 96
TSO command 422
TSO command for member 113
TSO workstation command 430
TTR data 104
Tutorial (option 7.T), displaying 401
type-of-difference codes, SuperC 516

U

U (uncatalog data set) line command, Data Set List utility (option 3.4) 165
U (updating a format) line command, Format Specification utility (option 3.11) 202
U record format, Record Format field 119
UIDs, switching 299

uncatalog workstation command 430
Underline headings (in export report) 257
Unexclude Data Set command 166
Unexclude First Data Set command 166
Unexclude Last Data Set command 166
Unicode
  FIND command 85
  viewing in Browse 80, 82
Unit field, VTOC Information Display 159
unmovable data set, defined 153
UPD parameter, BROWSE Output field 217
update data set control output examples, SuperC 524
Update DS Name field, SuperC Utility - Old Data Set Name panel 206
Update Dsn field, SuperCE Utility panel 216
UPDCMS8 SuperCE process option 449, 525
UPDCMS8 update data set 525
UPDCNTL SuperCE process option 450, 525
UPDCNTL update data set and formats 525
UPDLDEL SuperCE process option 450
UPDMVS8 SuperCE process option 451, 529
UPDPDEL SuperCE process option 451, 530
UPDPDEL update data set 530
UPDSEQ0 SuperCE process option 452, 533
UPDSEQ0 update data set 533
UPDSUMO SuperCE process option 452, 534
UPDSUMO update data set 534
USASCII 87
Use EDIT as default to process selected table option 255
Use Edit to view the imported table 256
user-defined trigger 306
UTF8 87
Utilities (option 3)
  Command Table utility (option 3.9) 192
  Data Set List utility (option 3.4) 139
  Data Set utility (option 3.2) 113
  Format Specification utility (option 3.11) 197
  Hardcopy utility (option 3.6) 180
  ISPF C/S Install (option 3.7) 185
  Library utility (option 3.1) 101
  Move/Copy utility (option 3.3) 132
  Outlist utility (option 3.8) 189
  overview 2
  Reset ISPF Statistics utility (option 3.5) 176
  Search-For utility (option 3.14) 225
  SuperC utility (option 3.12) 203
  SuperCE utility (option 3.13) 213
  Utility Selection Panel 101
utility differences
  extended 439
  standard 439
Utility Selection Panel 101

V

V (VDEFINE) variable, P (pool) field 370
V (view data set) line command, Data Set List utility (option 3.4) 162
V record format, Record Format field 119
VA (view ASCII file) line command
  z/OS UNIX Directory List Utility (option 3.17) 292
VA command, Data Set List utility (option 3.4) 176
Variables (option 7.3)
  CANCEL primary command 370
  creating new variables 371
  D (delete) line command 370
  DBCS data 372
  deleting variables 371
  END primary command 370
  hexadecimal data 372
  I (insert) line command 370
  input errors 371
  LOCATE primary command 370
  manipulating variables 371
  primary commands 370
  split-screen mode 372
  test mode 371
  usage notes 371, 372
  variable life 372
  variable value 372
  working with dialog variables 368
Verb column 194
VERT parameter, HEX command 89
View (option 1)
  description 77
  View Entry Panel 77
view action prompt workstation command 430
VIEW command, Browse 92
view output mode 205, 217, 227, 236
View workstation command 430
view, command table line command 196
viewing a member 113
Volume DATA field, VTOC Information Display 159
Volume display view, Initial View field 143
Volume field
  Data Set List utility 153
  Data Set List Utility panel 142
VOLUME keyword, SORT command 175
Volume Serial 96
Volume Serial field
  Allocate New Data Set panel 117
volume, DASD 96
VS COBOL II compiler (option 4.2)
  overview 312
VS COBOL II compiler (option 5.2) 341
VS COBOL II interactive debug (option 4.10) 325
VS COBOL II interactive debug (option 5.10) 346
VS COBOL II Interactive Debug panel 346
VS command, Data Set List utility (option 3.4) 176
VS data set organization, DSORG field 153
VS FORTRAN compiler (option 4.3) 313
VS FORTRAN compiler (option 5.3) 342
VS Pascal compiler (option 4.6) 315
VS Pascal compiler (option 5.6) 343
VS-E 153
VSAM (*VSAM*) entry in Volume field 142
VSAM workstation command 430
VT command, Data Set List utility (option 3.4) 176
VTOC Data field, VTOC Information Display 159
VTOC information display 159
VTOC summary workstation command 429
VV command, Data Set List utility (option 3.4) 176

W

Warn if export data set exists 256
Warn if table exists in the output library 256
WE workstation command 430
WEW workstation command 430
WIDE SuperCE process option 452
wildcard characters 140
Word parameter
  Compare Type field 215
  FIND command 85
word, defined for SuperC 215
Workplace (Option 11)
  action bar choices 410
    file 410
    options 418
    space 418
    SuperC 420
    test 420
    view 417
  actions that require prompt windows 421
    ISPF command shell 424
    move/copy 426
    rename 427
    reset statistics 421
    TSO command 422
    WS command 423
  commands 429
  entry panels 407
    data set view 408
    library view 408
  example scenario 435
  ISPF Library field 408
  ISPF referral lists 409
  Object Name field 409
  overview 407
  specifying actions 410
Workplace example 435
workplace function keys 430
Workplace option description 2
workplace settings 431

workplace settings command 430
Workstation agent 188
installation program 188
Workstation Commands
= 430
ACTBAR action prompt 429
allocate 429
allocate action prompt 429
allocate SMS 430
Browse 429
catalog 429
command action prompt 429
compress 430
Copy 429
CUA attributes 429
delete 429
Delete 429
delete action prompt 429
DSLIST 429
Edit 429
edit action prompt 429
full information action prompt 429
global color change 429
information action prompt 429
ISPF command shell 429
ISPF command table 429
keylist 429
list action prompt 429
list view 429
locate 429
Member list 429
Move 429
NOACTBAR action prompt 429
Open 429
personal data set lists 429
personal library lists 429
point and shoot 430
Print 429
print action prompt 430
print data set 429
print data set index 430
Print data set list 430
Print VTOC information 430
rename 429
Rename 430
rename action prompt 430
reset action prompt 429
SearchFor 430
SearchFor extended 430
select 430
Settings 430
short information 430
Submit 429
SuperC 430
SuperC extended 430
TSO 430
uncatalog 430
View 430
view action prompt 430
VSAM 430
VTOC summary 429
WE 430
WEW 430
WS 430
WV 430
WVW 430
workstation connection 60
workstation tool integration program
action bar choices 68
description 67
editing 69
extension mapping 70
startup 67
updating 69
WPSET command 430
WRITE parameter 384
Writer name 181
writing a list to a list data set
data set list 172
WS command 423
WS command for member 113
WS workstation command 430
WV workstation command 430
WVW workstation command 430

X

X (execute) line command
z/OS UNIX Directory List Utility (option 3.17) 292
X (print index listing) line command, Data Set List utility (option 3.4) 166
XREF Search-For process option 486
XT field, Data Set list utility 153
XT keyword, SORT command 175
XWDCMP SuperCE process option 452

Y

YES parameter
Active field 392, 394, 396
BROWSE Output field 217
Confirm Delete Request field, select 144
Replace like-named members field, select 134
Select pack option for “To” data set field 135
Specify additional search strings field, select 227
Table available field 383
Table on disk field 384
YYYY/MM/DD format, Expiration Date field 119
YYYY.DDD format, Expiration Date field 119

Z

Z (compress data set) line command, Data Set List utility (option 3.4) 165
z/OS system programmer applications 2
z/OS UNIX
execute command 292
file permissions 278, 284, 291
z/OS UNIX Directory List Utility (option 3.17)
+ (scroll indicator) 299
action bar choices 267
audit information 289
B (browse) line command 274
z/OS UNIX Directory List Utility (option 3.17) *(continued)*
bypass z/OS UNIX File Edit Options panel 298
C or CO (copy out) line command 277
change column order and width 298
CI (copy in) line command 282
command time limit 297
confirm file delete option 265, 297
D (delete) line command 276
device data information 289
Display Directory List option 265
display permissions in octal format 298
E (edit) line command 274
EDIT primary command 293
extended attributes information 288
FIND primary command 293
I (information) line command 286
L (List) line command 276
LEFT primary command 294
line command prefix characters 271
line commands 273
LOCATE primary command 294
MM (modify mode) line command 291
mode fields information 288
MX (modify extended attributes) line command 291
N (new) line command 275
options 297
overview 263
owner information 288, 290
path name substitution character 297
path names 299
primary commands 293
Print Directory List option 273
R (rename) line command 277
REFRESH primary command 295
RESET primary command 295
restore default column arrangements 298
RFIND primary command 293
RIGHT primary command 295
run command under login shell 271
SAVE primary command 295
scrollable fields for path names 299
SORT primary command 296
sorting 267
SU primary command 297, 299
super-user mode 299
switching UIDs 299
symbolic link information 290
time zone value 264
timeout setting 297
VA (view ASCII file) line command 292
view options 267
width of filename column 297
X (execute) line command 292
z/OS user applications 3
ZDLBLKSZ variable 156
ZDLCAT variable 156
ZDLCATNM variable 156
ZDLCDATE variable 156
ZDLCMD variable 156

ZDLCONF variable 156
ZDLDEV variable 156
ZDLDSN variable 156
ZDLDSNTP variable 156
ZDLDSORG variable 157
ZDLDST variable 157
ZDLDSX variable 157
ZDLEDATE variable 157
ZDLEXT variable 157
ZDLEXTX variable 157
ZDLLCMD variable 157
ZDLLRECL variable 157
ZDLMIGR variable 157
ZDLMSG variable 158
ZDLMVOL variable 157
ZDLNDSN variable 158
ZDLOVF variable 157
ZDLRDATE variable 157
ZDLRECFM variable 157
ZDLREF variable 158
ZDLSIZE variable 157
ZDLSIZET variable 157
ZDLSIZEX variable 157
ZDLSIZTX variable 157
ZDLSPACU variable 157
ZDLUSED variable 157
ZDLVOL variable 157
ZPARM system variable
    parenthesis added to 195

Readers' Comments — We'd Like to Hear from You

Interactive System Productivity Facility (ISPF)
User's Guide Volume II
z/OS Version 1 Release 9.0

Publication No. SC34-4823-07

We appreciate your comments about this publication. Please comment on specific errors or omissions, accuracy, organization, subject matter, or completeness of this book. The comments you send should pertain to only the information in this manual or product and the way in which the information is presented.

For technical questions and information about products and prices, please contact your IBM branch office, your IBM business partner, or your authorized remarketer.

When you send comments to IBM, you grant IBM a nonexclusive right to use or distribute your comments in any way it believes appropriate without incurring any obligation to you. IBM or any other organizations will only use the personal information that you supply to contact you about the issues that you state on this form.

Comments:

Thank you for your support.

Submit your comments using one of these channels:

- Send your comments to the address on the reverse side of this form.

If you would like a response from IBM, please fill in the following information:

Name	Address
Company or Organization	
Phone No.	E-mail address

Readers' Comments — We'd Like to Hear from You
SC34-4823-07

IBM

Cut or Fold
Along Line

Fold and Tape **Please do not staple** Fold and Tape

NO POSTAGE
NECESSARY
IF MAILED IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST-CLASS MAIL PERMIT NO. 40 ARMONK, NEW YORK

POSTAGE WILL BE PAID BY ADDRESSEE

IBM Corporation
Reader Comments
DTX/E269
555 Bailey Avenue
San Jose, CA
U.S.A. 95141-9989

Fold and Tape **Please do not staple** Fold and Tape

SC34-4823-07

Cut or Fold
Along Line

Program Number: 5694-A01

Printed in USA

SC34-4823-07